

PROGRAM -3

```
#include <stdio.h>
int main()
{
    int A[100][4];
    int i, j, n, total = 0, index, temp;
    float avg_wt, avg_tat;
    printf("Enter number of process: ");
    scanf("%d", &n);
    printf("Enter Burst Time:\n");
    for (i = 0; i < n; i++) {
        printf("P%d: ", i + 1);
        scanf("%d", &A[i][1]);
        A[i][0] = i + 1;
    }
    for (i = 0; i < n; i++) {
        index = i;
        for (j = i + 1; j < n; j++)
            if (A[j][1] < A[index][1]) index = j;
        temp = A[i][1]; A[i][1] = A[index][1];
        A[index][1] = temp;
        temp = A[i][0]; A[i][0] = A[index][0];
        A[index][0] = temp;
    }
    A[0][2] = 0;
    for (i = 1; i < n; i++) {
        A[i][2] = 0;
        for (j = 0; j < i; j++)
            A[i][2] += A[j][1];
        total += A[i][2];
    } avg_wt = (float)total / n;
    total = 0;
    printf("P   BT   WT   TAT\n");

    for (i = 0; i < n; i++) {
        A[i][3] = A[i][1] + A[i][2];
        total += A[i][3];
        printf("P%d %d %d %d\n", A[i][0], A[i][1], A[i][2], A[i][3]);
    } avg_tat = (float)total / n;
    printf("Average Waiting Time= %f", avg_wt);
    printf("\nAverage Turnaround Time= %f", avg_tat);
}
```

OUTPUT

Enter number of process: 4

Enter Burst Time:

P1: 12

P2: 14

P3: 15

P4: 16

P	BT	WT	TAT
---	----	----	-----

P1	12	0	12
----	----	---	----

P2	14	12	26
----	----	----	----

P3	15	26	41
----	----	----	----

P4	16	41	57
----	----	----	----

Average Waiting Time= 19.750000

Average Turnaround Time= 34.000000

Process exited after 8.236 seconds with return value 0

Press any key to continue . . . |