FROM PANDAS (5)

@uzwalgoudvaddeboina

Select all columns



Input table df CustID Name Doe Jo Tod

SELECT * FROM df;

Name
Doe
Jo
Tod



```
import pandas as pd

data = {
    'CustID': [1, 2, 3],
    'Name': ['Doe', 'Jo', 'Tod']
}

df = pd.DataFrame(data)
```

print(df)

output			
	CustID	Name	
0	1	Doe	
1	2	Jo	
2	3	Tod	

Select specific column



```
CREATE TABLE "df" (
"CustID" INTEGER,
"Name" VARCHAR(10)
);

INSERT INTO "df" VALUES
(1, 'Doe'),
(2, 'Jo'),
(3, 'Tod')
;
```

SELECT "Name" FROM "df"

```
Name
Doe
Jo
Tod
```



```
import pandas as pd

data = {
    'CustID': [1, 2, 3],
    'Name': ['Doe', 'Jo', 'Tod']
}

df = pd.DataFrame(data)
```

```
print(df['Name'])
```

```
0 Doe
1 Jo
2 Tod
Name: Name, dtype: object
```

Select specific columns



```
CREATE TABLE "df" (
"CustID" INTEGER,
"FirstName" VARCHAR,
"LastName" VARCHAR
);

INSERT INTO "df" VALUES
(1, 'Doe', 'Pala'),
(2, 'Jo', 'Noice'),
(3, 'Tod', 'Palle');

SELECT

"CustID",
"FirstName"
FROM "df";
```

··· CustID	FirstName
1	Doe
2	Jo
3	Tod



```
import pandas as pd
 df = pd.DataFrame(
    columns = [
        'CustID',
        'FirstName',
        'LastName'
df['CustID'] = [1, 2, 3]
 df['FirstName'] = ['Doe', 'Jo', 'Tod']
df['LastName'] = ['Pala', 'Noice', 'Palle']
print(df)
 CustID FirstName LastName
    1 Doe Pala
           Jo Noice
          Tod Palle
  print(df[['CustID', 'FirstName']])
  CustID FirstName
0
      1
              Doe
              Jo
              Tod
```

Filter Rows



```
CREATE TABLE "df" (
"CustID" INTEGER,
"Name" VARCHAR(10)
);

INSERT INTO "df" VALUES
(1, 'Doe'),
(2, 'Jo'),
(3, 'Tod')
;
```

```
SELECT *
FROM "df"
WHERE "CustID" = '2';
```

CustID	Name ···
2	Jo



```
import pandas as pd

df = pd.DataFrame(
    columns = ['CustID', 'Name']
)

df['CustID'] = [1, 2, 3]

df['Name'] = ['Doe', 'Jo', 'Tod']
```

```
df[df['CustID'] == 2]

CustID Name

1 2 Jo
```

Limit vs Head



```
CREATE TABLE "df" (
"CustID" INTEGER,
"Name" VARCHAR(10)
);

INSERT INTO "df" VALUES
(1, 'Doe'),
(2, 'Jo'),
(3, 'Tod')
;

SELECT *
FROM "df"
LIMIT 1;
```

··· CustID	Name
1	Doe



```
import pandas as pd

df = pd.DataFrame(
    columns = ['CustID', 'Name']
)

df['CustID'] = [1, 2, 3]

df['Name'] = ['Doe', 'Jo', 'Tod']
```

```
print(df.head(1))

CustID Name
0 1 Doe
```

"From SQL to Pandas" By Uzwal

Distinct vs Unique



CREATE TABLE "df" (

```
CustID

1
```



```
import pandas as pd

df = pd.DataFrame(
    columns = ['CustID', 'Name']
)

df['CustID'] = [1, 2, 1]

df['Name'] = ['Doe', 'Jo', 'Tod']

print(df)

CustID Name
0    1    Doe
1    2    Jo
2    1    Tod
```

```
print(df.CustID.unique())
[1 2]
```

distinct vs nunique



```
create |table "df" (
  "CustID" INTEGER
);

INSERT INTO df values
(10),
(20),
(10);

SELECT COUNT(DISTINCT "CustID")
FROM df;
```

```
··· COUNT(DISTINCT "CUSTID")
```



```
import pandas as pd

df = pd.DataFrame(
          columns = ['CustID']
)

df['CustID'] = [10, 20, 10]

print(df)

CustID
0     10
1     20
2     10
```

```
print(df.CustID.nunique())
2
```

"From SQL to Pandas" By Uzwal

Total elements in Table/DataFrame

table/dataframe

CustID	Name
10	Doe
20	Jo
30	Tod



Size

```
SELECT COUNT(*) * (
    SELECT COUNT(*)
    FROM INFORMATION_SCHEMA.columns
    WHERE TABLE_CATALOG = 'DATABASE_NAME'
    AND TABLE_SCHEMA = 'SCHEMA_NAME'
    AND TABLE_NAME='df'
) AS "Size"
from "df";
```





df.size

6

Get column names, data types, etc

table/dataframe

CustID	Name
10	Doe
20	Jo
30	Tod





name ···	type	kind
CustID	NUMBER(38,0)	COLUMN
Name	VARCHAR(20)	COLUMN



```
df.info()
```

Descriptive Stats: Pandas | SQL



```
In [17]: df

Out[17]: 0 1
1 2
2 3
3 4
4 5
Name: AGE, dtype: int64
```

SELECT

```
In [21]: df.describe()
Out[21]: count
                 5.0000
                 3.0000
         mean
         std
                 1.5811
         min
                 1.0000
         25%
                 2.0000
         50%
                 3.0000
         75%
                 4.0000
                 5.0000
         max
         Name: AGE, dtype: float64
```



```
COUNT(age) AS "count"

, AVG(age) AS "mean"

, STDDEV(age) as "std"

, MIN(age) as "min"

, PERCENTILE_CONT(0.25) WITHIN GROUP (ORDER BY age) "25%"

, PERCENTILE_CONT(0.5) WITHIN GROUP (ORDER BY age) "50%"

, PERCENTILE_CONT(0.75) WITHIN GROUP (ORDER BY age) "75%"

, MAX(age) as "max"

FROM desc_stats;
```

··· count	mean	std	min	25%	50%	75%	max	
5	3.000000	1.58113883	1	2.000	3.000	4.000	5	

Found this post helpful? follow

Uzwal for tips on SQL, Python, and Data Analytics.