

50 HZ

400 / 230 V

0.8 PF

Origin: Sweden

MODEL	ENGINE	ALT	PRIME KVA	STBY KVA
G100VL	TAD531GE	TAL044D	100.0	110.0
G130VL	TAD532GE	TAL044H	130.0	143.0
G150VL	TAD731GE	TAL044J	150.0	165.0
G200VL	TAD733GE	TAL044M	200.0	220.0
G250VL	TAD734GE	TAL046D	250.0	275.0
G300VL	TAD1341GE	TAL046F	300.0	330.0
G350VL	TAD1342GE	TAL046H	350.0	385.0
G400VL	TAD1343GE	TAL0473A	400.0	440.0
G450VL	TAD1345GE	TAL0473B	455.0	500.0
G500VL	TAD1641GE	TAL0473C	500.0	550.0
G600VL	TWD1643GE	TAL0473E	600.0	660.0
G650VL	TWD1644GE	TAL0473F	650.0	715.0
G700VL	TWD1645GE	TAL049B	700.0	770.0

Prime Power (PRP): Applicable for supplying continuous electrical power at variable load for unlimited hours. A 10% overload capability is available for 1 hour in every 12-hour period.

Standby Power (ESP): Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. No overload is permitted.

