

Select Carrier Voice Agent

API Integration / Webhook Specification

This document describes the webhook and APIs used for the Select Carrier Voice Agent workflow, based on the payloads, requests, and responses provided.

1. Authentication & Headers

Header	Value	Required
Authorization	Bearer {token}	Yes
Content-Type	application/json or form-data as specified per API	Yes

Authentication is required. The Voice Team should send a valid Bearer Token with every API request where authentication is configured.

2. Select Carrier Webhook

Method	POST
Endpoint	Voice Team webhook URL (provided/configured by Voice Team)
Direction	MDR → Voice Agent

Webhook Payload

The following payload is sent when a carrier is selected for the Voice Agent workflow.

```

{
  "event": "select.carrier.irs",
  "load": {
    "id": 1875,
    "quote_id": 20063,
    "distance": 9144,
    "origin_metro_location": "AK - Anchorage",
    "origin_service_location": "Port of Anchorage",
    "lfd_cut": "08/29/2026",
    "load_available_date": "",
    "customer_name": "BBL Freight, Inc.",
    "customer_location": "Apalachicola, FL 32320, USA",
    "length": "53 SD",
    "quantity": 2,
    "shipment_type": "Import",
    "ssl": "DIRECT",
    "commodity": "Oil / Petroleum",
    "cargo_weight": 45445,
    "hazmat": "",
    "reefer": "",
    "notes": "",
    "frequency_status": "Monthly",
    "freight_status": "Unknown",
    "service_type": "Drayage + Transloading + Final Mile",
    "is_warehouse_needed": 1,
    "created_at": "2026-08-27 01:02:22",
    "is_warehouse": 1,
    "storage_needed": 1,
    "storage_days": 4,
    "storage_pallets": 19
  },
  "carrier": {
    "outreach_id": 229,
    "carrier_id": 10,
    "rank": 2,
    "carrier_timezone": "America/Chicago",
    "calling_window": {
      "startTime": "10:00 AM",
      "endTime": "2:00 PM"
    },
    "company_name": "BBL Freight, Inc",
    "contact_name": "Frank Caputo",
    "email": "operations@brokerbrotherslogistics.com",
    "phone": "+918085568157",
    "email_sent": 1,
    "email_sent_at": "",
    "stop_call": "",
    "stop_reason": "",
    "accessorials": "",
    "warehouses": ""
  },
  "response_summary": {
    "carrier_id": 10,
    "has_outreach": 1,
    "outreach_status": "EMAIL_SENT",
    "is_agent_call_on": 1,
    "call_attempt_count": 0,
    "last_call_result": ""
  },
  "api": {
    "carrier_details": "https://staging.mydrayrate.com/api/voice/select/load/1875/carrier/10"
  }
}

```

Main Payload Fields

Field	Type	Required	Description
event	String	Yes	Event name. For this workflow: select.carrier.load.
load	Object	Yes	Load information required by the Voice Agent.
carrier	Object	Yes	Selected carrier and outreach information.

Field	Type	Required	Description
response_summary	Object	Yes	Current outreach/call status summary for the carrier.
api	Object	Yes	API links related to the selected carrier/load.

Carrier Details API

GET <https://staging.mydrayrate.com/api/voice/select/load/1875/carrier/10>

3. Call Started

Method	POST
Endpoint	{{base_url}}/voice/call-started
Direction	Voice Agent → MDR

Request Body

Postman Body Type: form-data

Key	Type	Example Value	Required
outreach_id	Text / Integer	5	Yes

Example

```
outreach_id = 5
```

Response

```
{
  "success": true
}
```

4. Mail Resend

Mail resend uses the same API flow as provided for the Voice Agent integration. The specific endpoint, request parameters, and response for the resend operation were not separately provided.

Item	Value
API	Same API / flow as existing implementation
Additional request fields	Not provided
Response	Not separately provided

5. Preview Rate Submission

Method	POST
Endpoint	{{base_url}}/voice/call-select-carrier-result
Direction	Voice Agent → MDR

Request Body

Postman Body Type: form-data

Key	Type	Example Value	Required
outreach_id	Text / Integer	228	Yes

Key	Type	Example Value	Required
base_rate	Text / Decimal	150.50	Yes
fsc	Text / Decimal	10.5	Yes
acc_types	Array	[5, 13]	No
transload_rate	Text / Decimal	75	No
finalmile_rate	Text / Decimal	200	No
finalmile_fsc	Text / Decimal	8.5	No
is_warehouse	Text / Integer	1	No
storage_rate	Text / Decimal	50	No
warehouse_id	Text / Integer	456	No
details	Text	Only For Testing Purpose	No

Example

```

outreach_id: 228
base_rate: 150.50
fsc: 10.5
acc_types: [5, 13]
transload_rate: 75
finalmile_rate: 200
finalmile_fsc: 8.5
is_warehouse: 1
storage_rate: 50
warehouse_id: 456
details: Only For Testing Purpose

```

Response

```

{
  "success": true,
  "message": "Rate calculated successfully",
  "data": {
    "quote_id": 1874,
    "carrier_id": 10,
    "carrier_name": "BBL Freight, Inc",
    "carrier_email": "operations@brokerbrotherslogistics.com",
    "quantity": "2",
    "base_rate": {
      "rate_per_unit": "150.50",
      "quantity": "2",
      "total": 301
    },
    "fsc": {
      "percentage": "10.5",
      "amount": 31.605,
      "calculation": "301 * 10.5 / 100"
    },
    "accessorial_charges": [],
    "accessorial_total": 0,
    "transload_charges": null,
    "final_rate": 332.605,
    "rate_breakdown": {
      "base_rate_total": 301,
      "fsc_amount": 31.605,
      "accessorial_total": 0,
      "transload_total": 0,
      "grand_total": 332.605
    },
    "driver_availability": null,
    "details": "Only For Testing Purpose"
  }
}

```

6. Final Rate Submission

Method	POST
Endpoint	{{base_url}}/voice/call-select-carrier-final-result
Direction	Voice Agent → MDR

Request Body

Postman Body Type: form-data

Key	Type	Example Value	Required
outreach_id	Text / Integer	228	Yes
base_rate	Text / Decimal	150.50	Yes
fsc	Text / Decimal	10.5	Yes
acc_types	Array	[1, 2, 3, 5]	No
transload_rate	Text / Decimal	75	No
finalmile_rate	Text / Decimal	200	No
finalmile_fsc	Text / Decimal	8.5	No
is_warehouse	Text / Integer	1	No
storage_rate	Text / Decimal	50	No
warehouse_id	Text / Integer	456	No
details	Text	Only For Testing Purpose Again	No

Example

```
outreach_id: 228
base_rate: 150.50
fsc: 10.5
acc_types: [1, 2, 3, 5]
transload_rate: 75
finalmile_rate: 200
finalmile_fsc: 8.5
is_warehouse: 1
storage_rate: 50
warehouse_id: 456
details: Only For Testing Purpose Again
```

Response

```
{
  "success": true,
  "message": "Carrier confirmed successfully"
}
```

7. Decline Carrier Selection Call

Method	POST
Endpoint	{{base_url}}/voice/call-select-carrier-deny
Direction	Voice Agent → MDR

Request Body

Postman Body Type: form-data

Key	Type	Example Value	Required
outreach_id	Text / Integer	228	Yes
reason	Text	I dont work on that lane.	Yes

Example

```
outreach_id: 228
reason: I dont work on that lane.
```

Response

```
{
  "success": false,
  "message": "Load not found or already processed"
}
```

8. Select Carrier Voice Agent Flow

Step	API / Event	Purpose
1	select.carrier.load webhook	Send selected load and carrier information to the Voice Agent.
2	/voice/call-started	Notify MDR that the Voice Agent call has started.
3	Mail resend	Resend mail using the existing/same API flow.
4	/voice/call-select-carrier-result	Preview/calculate the carrier rate before final confirmation.
5	/voice/call-select-carrier-final-result	Confirm the final carrier rate and selection.
6	/voice/call-select-carrier-deny	Decline the carrier selection with a reason.

Integration Notes

- The Select Carrier webhook payload contains load, carrier, response summary, and API details.
- Rate preview and final submission accept the same core rate fields; the final submission confirms the carrier.
- The deny API accepts an outreach ID and a decline reason.
- The Mail Resend endpoint and exact request/response details were not separately supplied and are therefore not invented in this specification.