HP 200 Maintenance Manual

Document ID: HP-MNT-01 | Machine: M-HP200 / HP-200 | Revision: 1.0

Issued: October 1, 2026 | Publisher: Blessed IT Solution Pvt Ltd

Fictional equipment and specifications created solely for this hackathon. These documents are a closed demonstration dataset and must not be used to operate or maintain real equipment.

Coverage

This manual covers observation-based inspection and escalation for the fictional HP-200 hydraulic press. It applies only to M-HP200. It complements HP-OPS-01 revision 1.0; both manuals are current in this dataset. It does not describe internal component repairs or authorize physical work on real equipment.

Maintenance reference data

Item	HP-200 reference
Hydraulic fluid	H46 hydraulic oil
Return-filter identifier	RF-20
Reservoir level	Between MIN and MAX marks
Oil replacement interval	Every 2,000 operating hours or 12 months, whichever occurs first
Return-filter planned replacement	Every 500 operating hours or earlier after confirmed restriction
Condition requiring escalation	Repeated alarms, confirmed leaks, or an abnormal indicator that persists

Inspection boundaries

Any physical inspection or maintenance requires an authorized person to follow the site's isolation and stored-energy procedure. This training dataset does not supply that procedure. Observations must not be treated as permission to open pressurized lines, remove guards, or adjust operating settings.

Recording completed work

Record machine ID, operating-hour reading, date, inspection item, observation, action reference, and reviewer. Record actual findings; do not mark a check complete because an AI answer suggested it. A completed inspection does not by itself prove a fault is resolved.

Page 2 contains the inspection schedule. Page 3 contains low-pressure and cooling checks. Operating ranges and alarm thresholds are defined in HP-OPS-01.

Inspection Schedule and Filter Reference

When	Inspection item	Record or escalation
Before each shift	Reservoir sight-glass and visible leakage	Record MIN-to-MAX indication; report low level or a visible leak.
Every 50 operating hours	Return-filter restriction indicator for RF-20	Record indicator state. A restriction indication requires maintenanc
Every 250 operating hours	Cooling-air path and external hose condition	Record obstruction, visible damage, or leakage; escalate abnormal
Every 500 operating hours	Planned RF-20 replacement	Record the replacement reference and reviewer; earlier replaceme
Every 2,000 hours or 12 months	Planned H46 oil replacement	Use whichever limit occurs first; record hours and date.

E42 and the return filter

E42 refers to return-filter restriction on the HP-200. The applicable filter identifier is RF-20. Review the restriction indicator and the last service record. A confirmed restriction may require replacement before the planned 500-hour interval. A calendar interval for RF-20 replacement is not specified.

Oil replacement example

If oil has been in service for 12 months but the machine has run only 1,400 hours, the calendar limit has been reached. If it has run 2,000 hours in eight months, the operating-hour limit has been reached. The rule is whichever occurs first; it is not necessary for both limits to be met.

Scope of the schedule

These are the only inspection intervals provided in the dataset. Do not infer a daily, weekly, or annual interval for an item unless the schedule explicitly states it. No spare-part price or supplier is included.

Troubleshooting Observations and Escalation

Low hydraulic pressure or E17

Collect these observations in order: (1) reservoir level relative to MIN and MAX; (2) visible external leakage reported by the operator; (3) RF-20 restriction-indicator state; (4) oil temperature and the recorded pressure during forming. Use the operating manual to interpret the pressure and temperature values.

A low reservoir indication, a visible leak, or filter restriction is a finding to review, not a confirmed root cause. The manuals do not contain a test that proves pump failure. If E17 repeats after review, retain HOLD status and escalate to authorized maintenance with the findings and prior incident reference.

High oil temperature or E24

Review the cooling-air path for reported obstruction, the cooling-fan status indication, reservoir level, and the recent operating pattern. Record all findings. The operating manual supplies the E24 warning and high-stop temperatures. The dataset does not specify a cooling-fan replacement procedure or a predicted cooldown time.

Escalation record

Include machine ID, date and time, hours, alarm code, pressure, oil temperature, reservoir level, leak observation, filter indicator, cooling-fan indication where relevant, previous incident ID, and reviewer. Keep confirmed observations separate from suspected explanations.

Return to service

Return-to-service authorization belongs to the designated supervisor after maintenance review under site procedures. An AI-generated checklist or a cleared alarm alone is not authorization. The portal records the decision; it does not control the press.