

CONFIGURING THE SPRING IoC CONTAINER

applicationContext.xml:

```
<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           https://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="bookRepository"
          class="com.library.repository.BookRepository"/>

    <bean id="bookService"
          class="com.library.service.BookService">

        <property name="bookRepository"
                  ref="bookRepository"/>

    </bean>

</beans>
```

BookRepository.java:

```
package com.library.repository;

public class BookRepository {
    public void display() {
        System.out.println("BookRepository Bean Created");
    }
}
```

BookService.java:

```
package com.library.service;
```

```
import com.library.repository.BookRepository;

public class BookService {
    private BookRepository bookRepository;
    public void setBookRepository(BookRepository bookRepository) {
        this.bookRepository = bookRepository;
    }
    public void display() {
        System.out.println("BookService Bean Created");
        bookRepository.display();
    }
}
```

LibraryManagementApplication.java:

```
package com.library;

import com.library.service.BookService;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class LibraryManagementApplication {
    public static void main(String[] args) {
        ApplicationContext context =
            new ClassPathXmlApplicationContext("applicationContext.xml");
        BookService service = context.getBean("bookService", BookService.class);
        service.display();
    }
}
```

Output:

