

# X4+T



X4.085 - X4.095 - X4.105 - X4.110 - X4.120 **TF/TM**



  
**McCORMICK**  
Power Technology.

|  ENGLISH |       | X4.085<br>TF/TM                                                                 | X4.095<br>TF/TM | X4.105<br>TF/TM | X4.110<br>TF/TM | X4.120<br>TF/TM |
|------------------------------------------------------------------------------------------|-------|---------------------------------------------------------------------------------|-----------------|-----------------|-----------------|-----------------|
| ENGINE                                                                                   |       |                                                                                 |                 |                 |                 |                 |
| Manufacturer                                                                             |       | Deutz AG                                                                        |                 |                 |                 |                 |
| Model                                                                                    |       | TCD 2.9 L4 HT                                                                   | TCD 2.9 L4 HP   |                 |                 |                 |
| Max power (ISO)                                                                          | hp/kW | 75 / 55                                                                         | 90 / 66         | 95 / 70         | 102 / 75        | 112 / 82        |
| Max torque                                                                               | Nm    | 375                                                                             | 378             | 400             | 410             | 420             |
| Displacement                                                                             | cm³   | 2900                                                                            |                 |                 |                 |                 |
| Cylinders / Valves                                                                       |       | 4 TA / 8                                                                        |                 |                 |                 |                 |
| Emissions category                                                                       |       | Stage V                                                                         |                 |                 |                 |                 |
| CAPACITIES                                                                               |       |                                                                                 |                 |                 |                 |                 |
| Fuel tank                                                                                | l     | 80                                                                              |                 |                 |                 |                 |
| TRANSMISSION                                                                             |       |                                                                                 |                 |                 |                 |                 |
| Type                                                                                     |       | Speed Four                                                                      |                 |                 |                 |                 |
| No. of gears FWD+REV                                                                     |       | ● 16+8 Hi-Lo Overdrive ○ 16+8 w/creeper                                         |                 |                 |                 |                 |
| Transmission control                                                                     |       | Manually operated - 12" independent dry clutch                                  |                 |                 |                 |                 |
| Reverse shuttle                                                                          |       | Mechanical synchro shuttle                                                      |                 |                 |                 |                 |
| Transmission oil cooler                                                                  |       | ●                                                                               |                 |                 |                 |                 |
| REAR PTO                                                                                 |       |                                                                                 |                 |                 |                 |                 |
| Type                                                                                     |       | Servoassisted dry clutch                                                        |                 |                 |                 |                 |
| Speeds                                                                                   | rpm   | ● 540-540E ○ 540-1000                                                           |                 |                 |                 |                 |
| Rotation - spline shaft type                                                             |       | Clockwise (viewed from tractor rear) - ● 1-3/8" PTO shaft with 6 splines        |                 |                 |                 |                 |
| STEERING AND BRAKING SYSTEM                                                              |       |                                                                                 |                 |                 |                 |                 |
| Steering system                                                                          |       | Hydrostatic Hi-Drive                                                            |                 |                 |                 |                 |
| Steering control                                                                         |       | 2 independent levers with combined action on 2 wet clutches and on brakes       |                 |                 |                 |                 |
| Braking system                                                                           |       | Hydrostatic wet multidisc graphite brakes                                       |                 |                 |                 |                 |
| HYDRAULIC SYSTEM                                                                         |       |                                                                                 |                 |                 |                 |                 |
| Circuit type - pump type                                                                 |       | Open center - twin pump                                                         |                 |                 |                 |                 |
| Flow rate hitch & remotes + steering                                                     | l/min | ● 42 + 28 - ○ 56+28+28                                                          |                 |                 |                 |                 |
| Max operating pressure                                                                   | bar   | 180                                                                             |                 |                 |                 |                 |
| Rear remote valves                                                                       |       | ● 3 - ○ 4 / 5                                                                   |                 |                 |                 |                 |
| REAR HYDRAULIC HITCH                                                                     |       |                                                                                 |                 |                 |                 |                 |
| Type                                                                                     |       | ● mechanical - ○ mechanical with E.L.S. and position/draft/mixed/float control  |                 |                 |                 |                 |
| Category - coupler type                                                                  |       | ● Cat.2 - fixed ball ends - ○ Cat.2 - quick-hitch hooks                         |                 |                 |                 |                 |
| Max lift capacity at hitch points                                                        | kg    | ● 3150 - ○ 4500 (w/assistor rams)                                               |                 |                 |                 |                 |
| DRIVING POSITION                                                                         |       |                                                                                 |                 |                 |                 |                 |
| Cab type                                                                                 |       | ○ High-visibility 6-post monocoque cab w/central tunnel and opening rear window |                 |                 |                 |                 |
| Cab suspension                                                                           |       | Suspended on Hydro-Silent Blocks                                                |                 |                 |                 |                 |
| Cab air filter - filtration category                                                     |       | ● Cat. 2 dust filter and Cat. 4 activated carbon filter                         |                 |                 |                 |                 |
| Cab air conditioning                                                                     |       | ● Manual A/C                                                                    |                 |                 |                 |                 |
| Radio system                                                                             |       | ● Radio ready - ○ DAB Radio and sound system                                    |                 |                 |                 |                 |
| Platform type                                                                            |       | ROPS w/central tunnel w/side gears and reverse shuttle controls                 |                 |                 |                 |                 |
| Platform suspension                                                                      |       | Suspended on hydro-silentblocks                                                 |                 |                 |                 |                 |
| Lights                                                                                   |       | ● Halogen driving and working lights                                            |                 |                 |                 |                 |
| Beacon light                                                                             |       | ○                                                                               |                 |                 |                 |                 |
| ON-BOARD TECHNOLOGY                                                                      |       |                                                                                 |                 |                 |                 |                 |
| Digital dashboard                                                                        |       | ●                                                                               |                 |                 |                 |                 |
| WEIGHTS AND DIMENSIONS                                                                   |       |                                                                                 |                 |                 |                 |                 |
| Wheelbase                                                                                | mm    | 1650                                                                            |                 |                 |                 |                 |
| Ground clearance                                                                         | mm    | 295                                                                             |                 |                 |                 |                 |
| Height over ROPS                                                                         | mm    | 2400                                                                            |                 |                 |                 |                 |
| Max length without front weights                                                         | mm    | 3380                                                                            |                 |                 |                 |                 |
| Max overall width                                                                        | mm    | 1410-1492 (metal TF) / 1700-1750 (TM)                                           |                 |                 |                 |                 |
| Shipping weight                                                                          | kg    | 3900 (TF) - 4500 (TM)                                                           |                 |                 |                 |                 |
| Front weight support                                                                     |       | Built-in                                                                        |                 |                 |                 |                 |
| Front weights                                                                            | kg    | ○ 6x30 / 8x30 / 8x30 + 33 kg central front ballast                              |                 |                 |                 |                 |
| TRACKS                                                                                   |       |                                                                                 |                 |                 |                 |                 |
| Bottom rollers                                                                           |       | 5                                                                               |                 |                 |                 |                 |
| Top carrier roller                                                                       |       | Permanently lubricated                                                          |                 |                 |                 |                 |
| Track tension adjustment system                                                          |       | Hydraulic track adjuster with permanently lubricated sprocket gear              |                 |                 |                 |                 |
| Front suspension                                                                         |       | Leaf spring                                                                     |                 |                 |                 |                 |
| Rear suspension                                                                          |       | Crossbar on independent track frames                                            |                 |                 |                 |                 |
| Track shoe type                                                                          |       | ● Metal ○ Rubber                                                                |                 |                 |                 |                 |
| Track shoe width                                                                         | mm    | 310-360 (metal TF) / 400-450 (metal TM) / 450 (rubber TF/TM)                    |                 |                 |                 |                 |

**Key:** ● standard ○ option

All data and illustrations provided in this brochure are for information purposes only and can be changed.