Andre Winkel, Russell Yang October 15, 2025

Lab 1

EE115, Introduction to Communication Systems, Fall 2025

Problem 1: Examining a random signal and AM power efficiency

In this problem, we will examine the average power of a random signal that has its minimum value larger than or equal to -1, and also examine its impact on the power efficiency of conventional amplitude modulation (AM) signals.

a) We begin by using the Gaussian-random-number generator to generate a random sequence

$$m[1], m[2], \ldots, m[N] \tag{1}$$

where we will set N as 200 [a large integer]. We can do so in MATLAB by employing the `randn` function.

b) We can then use the `min` function in order to determine the minimum value of our sequence, which we can denote by $-M_0$. Verbatim, `m_nk = 1/M_0 * m_k; min(m_nk);`.

c) We can then compute the normalized sequence

$$m_n[k] = \frac{1}{M_0} m[k], \tag{2}$$

where its minimum value is found to be

$$m_n[k] = -1.$$

d) We can then compute the average power with

$$P_m = \frac{1}{M} \sum_{k=1}^{N} m_n^2[k]. \tag{3}$$

In MATLAB, this is achieved with `P_m = (1/N) * sum(m_nk.^2)`.

e) Considering the power efficiency of the AM signal, we can determine its power efficiency through

$$\eta_{AM} = \frac{a_{mod} P_m}{1 + a_{mod} P_m}. \tag{4}$$

We can plot η_{AM} versus P_m subject to $0 < P_m < 1$ for each of $a_{mod} = 1, 0.75, 0.5$ in MATLAB, where we observe the following plot:



f) Selecting some values of a random run of the MATLAB program thus frar, we observe η_{AM} for each of $a_{mod} = 1, 0.75, 0.5$ using the same P_m as before. An example run allows us to obtain the values

$$\eta_{AM} = 0.1682 : a_{mod} = 1$$

$$\eta_{AM} = 0.1317 : a_{mod} = 0.75$$

$$\eta_{AM} = 0.0918 : a_{mod} = 0.5$$

where it becomes evident, once interpreting the respective η_{AM} values as percentages, that conventional amplitude modulation is a very power-inefficient method of transmission.

Problem 2: Examining the quality of a simple DC blocker

In this problem, we will examine the quality of a simple DC blocker which consists of a capacitor C and a resistor R in series. We are given the frequency response of the DC blocker,

$$H(f) = \frac{R}{R + \frac{1}{j2\pi C}} = \frac{j2\pi f}{j2\pi f + \frac{1}{RC}}. \tag{5}$$

a) Plotting $|H(f)|$ versus f for $|f| < B$ for each of $RC = 0.01, 0.1, 1, 10$, we observe the following plots: