

# You Snooze, You Lose: Automatic Safety Alignment Restoration through Neural Weight Translation

Marco Arazzi  
University of Pavia  
Italy

Vignesh Kumar Kembu  
University of Pavia  
Italy

Antonino Nocera  
University of Pavia  
Italy

Stjepan Picek  
Radboud University  
Netherlands  
Faculty of Electrical Engineering and  
Computing, University of Zagreb  
Croatia

Saraga Sakthidharan  
University of Pavia  
Italy

## Abstract

The open-source ecosystem has accelerated the democratization of Large Language Models (LLMs) through the public distribution of specialized Low-Rank Adaptation (LoRA) modules. However, integrating these third-party adapters often induces catastrophic forgetting of the base model’s foundational safety alignment. Restoring these guardrails via fine-tuning on safety data introduces an opposing failure mode: the severe degradation of the specialized domain knowledge the adapter was originally designed to provide. To overcome this zero-resource challenge, we propose Neural Weight Translation (NeWTral), a framework that directly maps unsafe, domain-specific adapters onto a safe alignment manifold while rigorously preserving their core expertise. NeWTral operates as a non-linear translation module pre-trained on a diverse corpus of unsafe-to-safe adapter pairs. By executing this mapping entirely within the parameter space, NeWTral utilizes an adaptive Mixture of Experts (MoE) routing strategy to autonomously blend high-fidelity surgical translators and aggressive alignment experts. We evaluate our framework across four architectural families (Llama, Mistral, Qwen, and Gemma) at scales up to 72B parameters across eight diverse scientific and professional domains. Our results demonstrate that the MoE variant achieves a radical reduction in the average Attack Success Rate (ASR), dropping from 70% in unsafe experts to just 13%, while maintaining an exceptional 90% average knowledge fidelity. Much like the crowdsourced adapters it remedies, the NeWTral module is designed as a standalone, downloadable asset that allows practitioners to restore safety alignment instantly without requiring access to original training data or hardware-intensive retraining. **Content Warning: This paper contains examples of harmful language**

## Keywords

LLM, Safety Alignment, LoRA, Neural Weight Translation

## 1 Introduction

Large Language Models (LLMs) have shown strong performance in language understanding and generation of responses across a wide range of tasks [16, 26, 109, 127]. However, despite their general capabilities, LLMs often fall short in specialized areas that require domain knowledge. Studies across domains, including medicine,

law, finance, and more, identify several limitations in LLMs, but not limited to hallucinated content, reduced factual accuracy, and errors in multi-step reasoning tasks [56, 72–74, 77].

Fine-tuning is a common approach for adapting LLMs to domain-specific tasks by training on curated datasets, improving task alignment [5, 138, 143]. However, full fine-tuning is computationally expensive and time-consuming [49]. Parameter-efficient methods such as Low-Rank Adaptation (LoRA) [54] address this limitation by freezing pretrained weights and introducing low-rank adapters, thereby reducing the number of trainable parameters. A key challenge in domain-specific fine-tuning is the degradation of previously learned behaviors, particularly safety. Prior work shows that aligned LLMs remain vulnerable to downstream fine-tuning on datasets containing unsafe or noisy examples, often acquiring unsafe behaviors more rapidly [108, 141, 145]. While subsequent safety fine-tuning can partially restore alignment, it frequently reduces performance on domain-specific tasks. We refer to this trade-off between safety and task performance as the utility–alignment tax.

The conventional mitigation to this phenomenon is to mix safety-oriented data with domain data during the supervised fine-tuning phase. However, in real-world deployment, especially within the decentralized open-source AI ecosystem, this mitigation is not always applicable. Frequently, practitioners rely on pre-trained, highly specialized adapters downloaded from third-party repositories. In these zero-resource scenarios, the original domain training data is entirely inaccessible due to proprietary restrictions, data privacy regulations, or storage expiration, rendering traditional data-mixing strategies mathematically impossible. Similarly, an organization can train an adapter on proprietary data but needs to restore safety alignment in the model without access to safety-oriented data.

Recent post-hoc interventions attempt to address this zero-data bottleneck by directly manipulating the parameter space using static orthogonal projections (e.g., Safe LoRA [53], SaLoRA [79]). Yet, these approaches inherently assume that safety and domain utility occupy linearly separable subspaces. As we demonstrate, this assumption fails in complex professional domains where specialized reasoning is deeply entangled with potential dual-use harm. Consequently, linear weight interventions indiscriminately overwrite expert weights, resulting in a severe utility–alignment tax: the model either remains vulnerable to harmful questions or suffers a catastrophic collapse of its specialized knowledge.

To resolve this fundamental issue, we propose Neural Weight Translation (NeWTraL), a post-hoc alignment framework that operates directly on a fully-trained adapter without modifying the original training pipeline, restoring foundational safety guardrails directly in the parameter space. Crucially, NeWTraL is zero-shot at deployment time: given a previously unseen unsafe adapter, the pre-trained translator requires no gradient-based optimization, no target domain data, and no safe reference adapter. Rather than relying on rigid linear algebraic projections, NeWTraL frames safety restoration as a non-linear mapping between disjoint parameter subspaces. Crucially, the NeWTraL module is designed to be trained a priori and distributed as a standalone asset. Much like the crowdsourced adapters it remedies, practitioners simply download the pre-trained NeWTraL translator and apply it directly to their proprietary or third-party adapters. Distributed as a pre-trained meta-model, it allows practitioners to secure unverified or proprietary adapters zero-shot at deployment time. We term this process zero-shot as it requires no gradient-based optimization on the target adapter and no access to the target’s underlying training data.

As demonstrated by our experimental campaign, having a monolithic translation strategy makes it difficult to achieve an optimal balance between utility and safety. To address this, NeWTraL employs an autonomous, weight-space Mixture of Experts (MoE) routing strategy. By analyzing the statistical signatures of the unsafe adapter’s weights, layer by layer, the MoE router dynamically blends the outputs of two specialized translation networks: a Surgical Expert optimized to preserve depth and raw domain knowledge, and an Aggressive Expert designed to inject robust refusal heuristics and ethical compliance precisely where dual-use risks manifest.

We rigorously evaluate NeWTraL across a massive experimental campaign encompassing four architectural families (Llama-3.1, Mistral, Qwen-2.5, and Gemma-2) scaling up to 72B parameters, tested on eight diverse, high-stakes domains (including medicine, law, finance, and physics). Our framework drastically outperforms existing state-of-the-art post-hoc alignment strategies.

- We introduce NeWTraL, the first non-linear parameter translation framework for restoring safety in domain-specific LoRA adapters. Distributed as a pre-trained asset, it allows practitioners to secure unverified or proprietary adapters zero-shot at deployment time, without requiring target training data or any hardware-intensive retraining.
- We propose a layer-aware Mixture of Experts architecture that autonomously balances surgical utility preservation and aggressive ethical policing, successfully decoupling safety alignment from the utility-alignment tax.
- We conduct a deep internal representation analysis, providing empirical evidence that safety alignment is highly heterogeneous across network depth. We demonstrate that MLP blocks are the primary drivers of behavioral safety, whereas attention blocks must remain untouched to preserve domain reasoning.
- Through an evaluation across model scales up to 72B parameters and 8 domains, we show that the MoE variant reduces the global average Attack Success Rate (ASR), dropping from ~70% in unsafe experts to ~13%, while maintaining an exceptional ~90% knowledge fidelity.

## 2 Background

### 2.1 Low-Rank Adaptation

To avoid the prohibitive cost of full fine-tuning, LoRA [55] constrains weight updates  $\Delta\mathbf{W}$  for a frozen pre-trained matrix  $\mathbf{W}_0 \in \mathbb{R}^{d \times k}$  to a low-rank decomposition  $\Delta\mathbf{W} = \mathbf{B}\mathbf{A}$ , where  $\mathbf{B} \in \mathbb{R}^{d \times r}$  and  $\mathbf{A} \in \mathbb{R}^{r \times k}$  ( $r \ll \min(d, k)$ ). The adapted forward pass for an input  $\mathbf{h}$  is computed as  $\mathbf{W}'\mathbf{h} = \mathbf{W}_0\mathbf{h} + \frac{\alpha}{r}\mathbf{B}\mathbf{A}\mathbf{h}$ , where  $\alpha$  scales the adaptation magnitude. This reduces trainable parameters from  $O(dk)$  to  $O(r(d+k))$ , enabling the fine-tuning of 70B+ models on consumer hardware via 4-bit quantization (QLoRA) [32]. LoRA is a standard for safety alignment as it modifies behavior while preserving foundational capabilities [15, 55].

### 2.2 Supervised Fine-Tuning (SFT)

SFT adapts a model to a target behavioral profile by minimizing the standard negative log-likelihood (NLL) loss over a labeled dataset  $\mathcal{D} = \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^N$ :

$$\mathcal{L}_{\text{SFT}}(\theta) = - \sum_{i=1}^N \sum_{t=1}^{|\mathbf{y}_i|} \log P_{\theta}(\mathbf{y}_{i,t} \mid \mathbf{x}_i, \mathbf{y}_{i,<t}). \quad (1)$$

SFT serves as the initial post-training stage in alignment pipelines [104], typically utilizing human-written demonstrations to outperform purely synthetic targets [12]. Recent direct distillation methods [128] leverage teacher-model outputs to reduce annotation costs. However, SFT remains susceptible to distribution shift, where adversarial prompts outside the training distribution can bypass the learned safety guardrails [105, 133].

### 2.3 Safety Alignment

Safety alignment ensures that model behavior conforms to human values and ethical constraints [3, 13]. Traditionally, Reinforcement Learning from Human Feedback (RLHF) [104] maximizes a reward signal  $r(x, y)$  approximated by a reward model  $\hat{r}_{\phi}$  trained on human comparisons via the Bradley–Terry objective:  $\mathcal{L}_{\text{RM}}(\phi) = -\mathbb{E}_{\mathcal{H}}[\log \sigma(\hat{r}_{\phi}(x, y^+) - \hat{r}_{\phi}(x, y^-))]$  [27]. The policy  $\pi_{\theta}$  is then optimized subject to a KL-divergence penalty against a reference policy  $\pi_{\text{ref}}$  to prevent distributional collapse:  $\max_{\theta} \mathbb{E}[\hat{r}_{\phi}(x, y)] - \beta D_{\text{KL}}[\pi_{\theta} \parallel \pi_{\text{ref}}]$  [117]. Constitutional AI (CAI) [13] automates this via AI-generated critiques based on normative principles  $\mathcal{C}$ . Recently, Direct Preference Optimization (DPO) [110] bypassed the need for an explicit reward model using a closed-form objective:

$$\mathcal{L}_{\text{DPO}}(\theta) = -\mathbb{E}_{\mathcal{H}} \left[ \log \sigma \left( \beta \log \frac{\pi_{\theta}(y^+ \mid x)}{\pi_{\text{ref}}(y^+ \mid x)} - \beta \log \frac{\pi_{\theta}(y^- \mid x)}{\pi_{\text{ref}}(y^- \mid x)} \right) \right]. \quad (2)$$

Despite these advances, models often suffer from a utility-alignment tax, the degradation of specialized performance under safety constraints [104], and remain vulnerable to adversarial jailbreaks [105, 133], necessitating more robust, data-efficient alignment methods.

## 3 Methodology

### 3.1 Threat Model

From a security perspective, the scenario we address is analogous to a software supply chain attack: a practitioner trusts a third-party artifact (the LoRA adapter) that has been tampered with or

carelessly trained, without visibility into its provenance. NeWTral functions as a post-hoc sanitization layer that can be applied at integration time, analogous to static analysis or code signing in software pipelines. We consider a scenario where, to obtain an expert model  $M_{dom}$  for a specific domain, instead of retraining or fine-tuning a base model  $M$  that was trained on general knowledge, we rely on a LoRA adapter  $W = W_B W_A$ , where  $W_A \in \mathbb{R}^{r \times k}$  and  $W_B \in \mathbb{R}^{d \times r}$ . This adapter is used to augment the model’s knowledge, turning it into an expert in the desired domain. To obtain such an adapter, Supervised Fine-tuning is performed by minimizing the token-level cross-entropy loss over a target domain dataset  $D_{dom}$ :

Given a target sequence  $y \in D_{dom} = \{y_1, y_2, \dots, y_T\}$ , the loss function is defined as:

$$\mathcal{L}(W_A, W_B) = - \sum \log p(y_t | y_{<t}; \theta, W_A, W_B) \quad (3)$$

$$\Delta W \leftarrow \mathcal{L}(W_A, W_B) \quad (4)$$

$$W_M = W_M + \Delta W = W_{dom} + \frac{\alpha}{r} W_{B_{dom}} W_{A_{dom}}, \quad (5)$$

where  $W_M$  represents the frozen parameters of the base model  $M$ ,  $W_{A_{dom}}$  and  $W_{B_{dom}}$  are the trainable LoRA parameters,  $T$  denotes the total sequence length,  $p_\theta(y_t | y_{<t})$  is the probability of the  $t$ -th token conditioned on the preceding context, and  $\frac{\alpha}{r}$  is a scaling factor used to normalize the magnitude of the update.

Training a LoRA adapter to specialize a base model to a particular domain can cause the original model  $M$  to lose its safety alignment [41, 70, 142]. This may lead the model to respond to harmful queries in dangerous ways, as it might generate outputs to unsafe prompts while also leveraging the additional domain-specific knowledge, for example, in the medical domain, to produce an even more advanced and toxic combination of instructions or prescriptions.

To address this issue, while training  $W$  on the selected domain, it is still possible to incorporate safety into the resulting adapter. A straightforward approach is to combine samples from the domain dataset  $D_{dom}$  with safety-focused examples taken from a given safety dataset  $D_{safe}$ . In particular, we construct a  $D_{SD}$  dataset:

$$D_{SD} = D_{dom} \cup D_{safe}. \quad (6)$$

Then, LoRA parameters are trained in the same way as a domain adapter using the new combined dataset:

$$\mathcal{L}(W_{A_{safe}}, W_{B_{safe}}) = - \sum \log p(y_t | y_{<t}; \theta, W_A, W_B) \text{ where } y_t \in D_{SD}. \quad (7)$$

The obtained  $W_{safe} = W_{A_{safe}} W_{B_{safe}}$  is now capable of mapping domain-specific queries to technical answers found in  $D_{dom}$  and refuses to answer questions that share harmful aspects already seen in  $D_{safe}$ . While mixing domain and safety data during SFT is valid, it is often impractical due to data asymmetry. Indeed, practitioners frequently lack high-quality safety datasets. Conversely, industrial constraints, such as privacy policies, licensing, or storage expiration, render the original  $D_{dom}$  inaccessible for subsequent retraining. The lack of concurrent access to both data distributions makes traditional alignment a bottleneck for safe deployment. We instead propose a paradigm shift: rather than repeating costly training, a neural translator can restore safety by “curing” adapters in the parameter space. By mapping unsafe expert weights onto a

safe subspace, NeWTral provides a scalable, resource-efficient solution for aligning specialized LLMs without requiring the original training corpora or auxiliary safety data at deployment time.

### 3.2 Neural Weight Translation

NeWTral is a post-hoc framework for mitigating safety degradation in domain-specialized adapters. It operates at deployment time on unseen adapters without requiring retraining or access to domain or safety data. As discussed in Section 3.1, integrating LoRA adapters often weakens safety alignment in favor of domain-specific behavior. In practice, such adapters are typically sourced externally, with training data unavailable due to privacy or proprietary constraints. This renders standard fine-tuning-based alignment impractical and often incurs a utility–alignment tax, degrading domain performance. We address this setting by modeling alignment restoration as a learned mapping between adapter parameter configurations. NeWTral learns a transformation from unsafe adapter parameters to safety-aligned parameters using a neural network operating directly in parameter space. This enables targeted parameter modifications that reduce unsafe outputs while preserving domain-specific behavior. The resulting model can be applied post hoc to existing adapters without access to their original training data, enabling alignment adjustments without additional task-specific fine-tuning. Let  $M$  denote a base model aligned with generic knowledge. We specialize this model to a specific domain using LoRA. In particular, we consider two distinct versions of the same adapter: one adapter  $W_{dom}$ , trained exclusively on domain-specific data  $D_{dom}$ , as introduced in Section 3.1, to obtain a domain-expert adapter; and one adapter  $W_{safe}$ , trained on a combined dataset that includes both domain-specific data and safety-oriented data,  $D_{SD} = D_{dom} \cup D_{safe}$ . The objective of NeWTral is produce a mapping model  $\mathcal{T}$  such that:

$$\mathcal{T}(W_{dom}) = W_{cured} \approx W_{safe}. \quad (8)$$

Crucially, this transformation is performed *zero-shot* from the practitioner’s perspective. While  $\mathcal{T}$  is optimized a priori on a diverse corpus of adapter pairs, its application to a specific, unverified domain adapter at deployment time is a pure inference operation. Because the translator has learned the underlying geometric relationship between the unsafe and safe subspace, it can project a previously unseen weight vector  $W_{dom}$  onto its safe counterpart without requiring any additional “shots” (i.e., training samples) of the domain-specific data or further fine-tuning of the model parameters. Prior work on linear parameter-space interventions suggests that safety and domain knowledge are not cleanly separable, often leading to significant utility degradation. Our empirical results (Section 4.1.5) further support this observation, showing that linear transformations fail to preserve domain expertise in complex settings. This motivates modeling alignment restoration as a non-linear mapping, which can better capture the interaction between domain-specific representations and safety constraints. Such transformations enable targeted behavioral adjustments while preserving the high-frequency structure of expert knowledge.

**Layer-wise NeWTral.** Since LLMs are composed of  $L$  transformer decoder blocks stacked together, they rely on the same architectural modules repeated throughout the network. Within this structure, weight matrices that perform specific functional roles,

such as MLP down-projections or attention output projections, keep the same dimensionality across all layers  $l \in \{0, \dots, L-1\}$ .

We use this structural symmetry to enable parameter-space learning. Instead of providing the entire adapter as a single input to a translation model  $\mathcal{T}$ , we treat the translator as an ensemble of models. Each sub-model is designed for a specific input and output dimension, mapped directly to the different layer shapes that make up the transformer.

To do this, we group the LoRA parameters by their geometric shapes. Let  $\mathcal{S}$  be the set of unique matrix dimensions  $\{(d_1, k_1), \dots, (d_n, k_n)\}$  present in the model. For each unique shape  $s \in \mathcal{S}$ , we define a weight-space  $\mathcal{WS}$ :

$$\mathcal{WS} = \{\mathbf{WS}^{(l)} \mid \text{shape}(\mathbf{WS}^{(l)}) = s, \forall l \in \{0, \dots, L-1\}\}. \quad (9)$$

By grouping layers with matching parameter shapes, we treat adapter weights as samples from a shared distribution, rather than independent per-layer instances. This effectively increases the number of training examples available to each translator from a small set of full adapters to  $L$  layer-wise samples per adapter. This depth-static formulation assumes that parameter mappings generalize across layers with similar structure, improving data efficiency. To account for residual layer-specific variation, we also incorporate a depth-dynamic routing mechanism that conditions the transformation on layer-dependent features (e.g., layer statistics), allowing the model to adapt the translation across different depths.

Given this, we formulate  $\mathcal{T}$  as an ensemble of translation models:

$$\mathcal{T} = \bigcup_{s \in \mathcal{S}} \mathcal{T}_s. \quad (10)$$

Each sub-model  $\mathcal{T}_s$  is a non-linear ensemble network designed to map the unsafe behavioral steering matrix  $\mathbf{W}_{dom,s}^{(l)} = \mathbf{W}_{A_{dom},s}^{(l)} \mathbf{W}_{B_{dom},s}^{(l)}$  to its safe counterpart. Because the ensemble is trained on weights sampled from every depth of the transformer, from initial lexical processing to final semantic synthesis, it is forced to learn a depth-agnostic safety transformation.

**NeWTral Ensemble Optimization.** Following the ensemble logic, each sub-model  $\mathcal{T}_s$  is structured as a bottleneck architecture designed to perform non-linear mapping within the domain and safe weights. We design the process as a two-stage projection: first, compressing the high-dimensional weight vector into a lower-dimensional latent space, and then expanding it back to the original dimensions to produce the safe parameter state. For a given domain adapter  $W_{dom}$ , we flatten the parameters into a vector  $x \in \mathbb{R}^{D_s}$  of flatten dimension  $D_s$  corresponding to:

$$D_s = d_s \cdot k_s; \text{ where } s = (d_s, k_s). \quad (11)$$

The translator  $\mathcal{T}_s$  then processes this input through an encoder-decoder framework. The first stage is a projection to a smaller dimension,  $D_s \rightarrow d_s^{latent}$ . This compression encourages the network to act as an information bottleneck. By squeezing the weights through a restricted latent dimension, the model is prevented from memorizing the specific technical values of the training domain (the "noise") and is instead forced to extract the abstract, structural features that represent safety and refusal (the "signal").

The second stage is a projection from the latent space back to the original dimensionality,  $d_s^{latent} \rightarrow D_s$ , to reconstruct the weights

in their aligned state. Formally, given the flattened unsafe domain weights  $\mathbf{x}_{dom}$  as input, the model produces the safe weights  $\mathbf{x}_{safe}$ :

$$\mathbf{z} = \sigma(\Phi_{enc} \mathbf{x}_{dom} + \beta_{enc}) \quad (12)$$

$$\mathbf{x}_{safe} = (\Phi_{dec} \mathbf{z} + \beta_{dec}), \quad (13)$$

where  $\mathbf{z} \in \mathbb{R}^{d_s^{latent}}$  denotes the compressed safety representation, and  $\Phi_{enc}, \beta_{enc}, \Phi_{dec}$ , and  $\beta_{dec}$  correspond to the weight matrices  $\Phi$  and bias vectors  $\beta$  of the encoder and decoder of  $\mathcal{T}$ , respectively. This structure ensures that the translation is not a simple linear shift. Instead, the model learns a transformation that maps from the domain expert directly to the safety-aligned subspace. This allows the model to preserve the technical expertise present in the input weights while imposing the behavioral constraints required for the safe output. A critical challenge in weight-space intervention is the numerical sensitivity of the underlying LLM; random perturbations to the parameters often result in catastrophic semantic collapse [23]. To mitigate this, we employ a Zero-Residual Initialization strategy. Specifically, the parameters of the final projection layer are initialized to zero:  $\Phi_{dec} \leftarrow \mathbf{0}, \beta_{dec} \leftarrow \mathbf{0}$ .

This ensures that at the start of the training phase ( $t = 0$ ), the optimization process is forced to learn only the precise non-linear shifts required to align the model, rather than wasting capacity correcting for initial random noise. This approach allows the translator to modify the model's behavioral steering while maintaining the structural integrity of its technical knowledge.

Then, our framework involves optimizing the parameters  $(\Phi, \beta)$  of the different submodels that compose the translator ensemble. Unlike the Supervised Fine-Tuning phase, which operates on discrete token probabilities, the translation ensemble is trained entirely within the continuous parameter space.

We construct a multi-domain training corpus  $\mathcal{X}_f$ , that includes all the layers that flatten have dimension  $D_s$ , consisting of weight-vector pairs  $(\mathbf{x}_{dom}, \mathbf{x}_{safe})$  derived from various technical fields. For each unique shape  $s \in \mathcal{S}$ , the dedicated sub-model  $\mathcal{T}_s$  is optimized to minimize a divergence function  $\mathcal{DV}$  between the predicted safe weights  $\hat{\mathbf{x}}_{cured}$  and the gold-standard aligned weights  $\mathbf{x}_{safe}$ :

$$\mathcal{L}(\Phi, \beta) = \mathbb{E}_{(\mathbf{x}_{dom}, \mathbf{x}_{safe}) \sim \mathcal{X}_f} [\mathcal{DV}(\mathbf{x}_{safe}, \hat{\mathbf{x}}_{cured})], \quad (14)$$

where  $\hat{\mathbf{x}}_{cured} = \mathcal{T}_\phi(\mathbf{x}_{dom})$  represents the output of the residual translator.

The objective function  $\mathcal{DV}$  can be adapted depending on the geometric properties of the target weight distribution. While a standard Mean Squared Error (MSE) is typically employed, the framework allows more specialized distance metrics according to the base architecture used for each sub-model of  $\mathcal{T}$ .

By training across diverse professional domains, the ensemble learns to isolate the shared mathematical transformations required for alignment while ignoring domain-specific weight fluctuations. Once converged, the ensemble can be applied to any naively fine-tuned adapter in a zero-shot manner, instantly projecting unsafe parameters onto the safe subspace without requiring further access to the original training data.

The final stage of the NeWTral process is the reconstruction of the LoRA matrices from the translated parameter vectors. After a sub-model  $\mathcal{T}_s$  has generated the cured parameter vector  $\hat{\mathbf{x}}_{cured} \in$




Figure 1: NeWTral framework and cured model behavior.

$\mathbb{R}^{D_s}$ , an inverse transformation is applied to recover the functional matrix dimensions required by the LLM.

Let  $\mathcal{R}_{d_s, k_s}(\cdot)$  denote the reshaping operator that maps a flattened vector back to its matrix form  $\mathbb{R}^{D_s} \rightarrow \mathbb{R}^{d_s \times k_s}$ . The reconstructed cured matrix  $\hat{W}$  is defined as:

$$\hat{W} = \hat{W}_{B_{cured}} \hat{W}_{A_{cured}} = \mathcal{R}_{d_s, k_s}(\hat{x}_{cured}). \quad (15)$$

The translated parameters are then re-integrated into the model’s computation graph. The effective weight matrix  $W'_M$  used during the forward pass is calculated by summing the frozen pre-trained weights  $W_M$  and the reconstructed low-rank update:

$$W'_M = W_M + \frac{\alpha}{r} (\hat{W}_{B_{cured}} \hat{W}_{A_{cured}}). \quad (16)$$

This reconstruction ensures that the intervention remains transparent to the underlying Transformer architecture. By replacing the behavioral steering matrices within the identified bottlenecks, the model preserves its technical domain expertise while adopting the refusal logic dictated by the learned safety behavior. Since the NeWTral operation is a one-time parameter shift generation performed at loading time, it provides a high-efficiency alignment solution that restores safety without increasing inference-time latency or requiring the deployment of multiple redundant model instances. Algorithm 1 presents the full process of our methodology from the construction of the dataset of adapters from different domains to the training of all the sub-models of  $\mathcal{T}$ .

**Adaptive Alignment via Mixture of Experts.** While a Static NeWTral translator effectively maps safe to unsafe, it inherently optimizes for fixed regions of the safety-utility tax. As we will demonstrate in our experiments, the optimal alignment strategy is domain-dependent. Scientific domains typically require a surgical translation to preserve knowledge depth, whereas institutional domains often require an aggressive translation to enforce ethical compliance and initiate a structural persona shift. Consequently,

relying on a single, monolithic translator imposes an inflexible trade-off across heterogeneous domains. To solve this, we propose a translator that mixes the knowledge of multiple experts, obtaining a Mixture of Experts (MoE) NeWTral. The MoE dynamically blends the outputs of two pre-trained, frozen translation experts, each possessing distinct behavioral characteristics. The first expert acts as Surgical Expert  $\mathcal{T}_{surg}$  optimized on high fidelity, ensuring minimal semantic drift from the original domain expert. The second is characterized by a more aggressive NeWTral obtaining an Aggressive Expert  $\mathcal{T}_{aggr}$  optimized for maximum safety alignment, effectively improving robust safety heuristics and ethical policing. The specific architectural instantiations of these experts will be detailed and empirically derived in Section 4. The core of this architecture is a lightweight, trainable Routing Network,  $\mathcal{R}_\phi$ . For a given unsafe LoRA weight matrix  $W_{dom}^{(l)}$  at layer  $l$ , we extract a feature vector  $\mathcal{F}_l$  comprising weight-space statistics (e.g., mean, variance,  $L_2$  norm) and the normalized layer position. The router analyzes these latent characteristics to compute an autonomous gating coefficient  $g_l \in [0, 1]$ :  $g_l = \mathcal{R}_\phi(\mathcal{F}_l)$ .

The final cured weight matrix  $W_{cured}^{(l)}$  is then generated via a convex combination of the experts’ outputs:

$$W_{cured}^{(l)} = (1 - g_l) \cdot \mathcal{T}_{surg}(W_{dom}^{(l)}) + g_l \cdot \mathcal{T}_{aggr}(W_{dom}^{(l)}). \quad (17)$$

The parameters  $\phi$  of the routing layer are trained using the combination of two different losses that try to balance between utility and safety. By keeping the pre-trained translation experts frozen, the router is forced to learn an interpolation policy that simultaneously maximizes domain utility and behavioral safety. Formally, for a given layer  $l$ , the loss is defined as the unweighted

sum of the mean squared errors against two distinct targets:

$$\mathcal{L}(\phi) = \underbrace{\|W_{cured}^{(l)} - T_{surg}(W_{dom}^{(l)})\|_2^2}_{\mathcal{L}_{util}} + \underbrace{\|W_{cured}^{(l)} - W_{safe}^{(l)}\|_2^2}_{\mathcal{L}_{safe}}. \quad (18)$$

The router minimizes an unweighted sum of  $\mathcal{L}_{util}$  and  $\mathcal{L}_{safe}$ , acting as utility and safety anchors to penalize deviations from  $T_{surg}$  and the safe reference, respectively. This formulation frames alignment as an autonomous multi-objective optimization problem that naturally navigates the Pareto frontier without manual hyperparameter tuning. Sensitivity analysis (Section 4.5) confirms the framework’s robustness to this unweighted configuration, as intrinsic weight-space signatures provide sufficient discriminative signal for optimal gating without exogenous bias. Consequently,  $g_l$  provides a depth-dynamic mechanism: maintaining surgical fidelity in theoretical domains while escalating aggressive safety injection ( $T_{aggr}$ ) in high-risk scenarios to enforce behavioral steering.

## 4 Experiments

### 4.1 Experimental Setup

#### 4.1.1 Dataset.

All the datasets are from HuggingFace and GitHub.

**Adapters dataset** - To obtain the adapters employed in the training and evaluation of the NewTral modules, we instantiated 10 distinct adapters for each of the eight selected domains, with each adapter trained on a different dataset specific to that domain. For safety alignment, we utilized the standard PKU-SafeRLHF dataset [68].

**Evaluation Prompts** - To measure the safety-utility trade-off, we employ a composite benchmark of 1,760 prompts per model configuration. This corpus integrates: (i) benign expert queries to evaluate knowledge retention and epistemic fidelity; (ii) domain-specific harmful prompts designed to exploit specialized technical expertise; and (iii) general adversarial queries from JBB-Behaviors [22] to assess foundational safety resilience. This multifaceted setup ensures rigorous accounting for both specialized utility and robust alignment (see Appendix B.1).

**4.1.2 LLMs.** To validate our approach, we evaluated LLMs from four architectural families with varying parameter scales. They are Llama-3.1- 8B & 70B [46], Mistral-7B-v0.3 [69], Qwen2.5- 7B & 72B [124, 137], and Gemma-2- 9B & 27B [122, 123].

**4.1.3 NewTral models.** The evaluated architectures include AutoEncoder (AE), Conditional Variational AutoEncoder (CVAE), Flow Matching (FM), and Multi-Layer Perceptron (MLP), which are depth-static, as well as a Mixture of Experts model as a depth-dynamic translator. Additional details on architectures and training are in Appendix B.6.

**4.1.4 System Configuration.** Specification of the system used to run experiments in Appendix B.2

**4.1.5 Compared Baselines.** In our experimental study, we compare our method with two state-of-the-art baselines: Safe LoRA [53] and SaLoRA [79]. It is important to note how these baselines intersect with our deployment scenario. Safe LoRA is not adapted;

we evaluate it using its original methodology, which requires access to the safe target-domain adapter. Although this bypasses the zero-resource limitation of our threat model, it provides a strong benchmark for what static linear projections can achieve when fully resourced. On the other hand, SaLoRA is natively a training-time intervention that we adapt into a post-hoc linear filter, placing it at a disadvantage. By including both, we aim to demonstrate that our learned non-linear translation (NeWTral) outperforms linear parameter-space interventions, whether they are constrained by our post-hoc scenario or provided with ideal reference data. Additional details are in Appendix B.5.

**4.1.6 Settings.** The settings used to perform the following experimental campaign are reported in Appendix B.4.

**4.1.7 Evaluation & Metrics.** We evaluate our framework using two primary metrics: *Attack Success Rate (ASR)* and *Knowledge Retention (KR)*. ASR is determined via an ensemble of three evaluators: Llama-Guard-3-8B [61, 83], the SecureBreak safety classifier [6], and a keyword-based refusal signal. KR measures the semantic fidelity of cured model responses against the unsafe domain expert on benign queries, capturing preservation of the fine-tuning delta rather than base model behavior, using cosine similarity (via Sentence-Transformers [112]) and BERTScore [144]. Residual unsafe content on benign prompts is independently captured by ASR. The *Final Score* is the harmonic mean of  $(1 - ASR)$  and KR, providing a single safety-utility trade-off metric. Full implementation details are in Appendix B.3.

### 4.2 Performance Evaluation

In this section, we evaluate the safety-utility trade-off of the proposed NeWTral architectures across various LLM scales and benchmark them against state-of-the-art alignment baselines. Table 1 presents the complete results, and in bold is the best Final Score.

As expected, the original unsafe domain experts exhibit severe safety vulnerabilities, with baseline ASR frequently exceeding 60%-70% across all architectures.

When evaluating state-of-the-art mitigation strategies against these vulnerabilities, we observe critical limitations imposed by the zero-resource nature of our threat model. SaLoRA, which is inherently designed as a training-time intervention utilizing auxiliary safety modules, cannot be natively performed on pre-trained, downloaded adapters. When adapted into a post-hoc linear filter for our scenario, it struggles to capture the non-linear, context-dependent nature of the safety subspace, resulting in unacceptably high residual ASRs. On the other hand, SafeLoRA achieves a respectable reduction in ASR, performing comparably to our lower-tier bottleneck translators (AE and CVAE). However, it still falls significantly short of the safety and utility optimization achieved by our best-performing non-linear translators (FM, MLP, and MoE). More critically, SafeLoRA’s reliance on calculating a static linear projection intrinsically requires access to an aligned reference pair (both the safe and unsafe adapters) for the specific target model. This requirement violates the strict zero-data, zero-resource constraint of our deployment scenario.

In contrast, our pre-trained, non-linear NeWTral modules operate entirely zero-shot. They successfully map unsafe weights to

| Models          | Cured Model Method | ASR (%) (↓)        |            |                    |            |                      |            | Knowledge Retention (%) (↑) |                | Final Score (%) (↑) |
|-----------------|--------------------|--------------------|------------|--------------------|------------|----------------------|------------|-----------------------------|----------------|---------------------|
|                 |                    | Llama-Guard-3-8B   |            | SecureBreak        |            | Refusal Signal Score |            | Cosine Similarity           | BERTScore (F1) |                     |
|                 |                    | Unsafe (Finetuned) | Cured      | Unsafe (Finetuned) | Cured      | Unsafe (Finetuned)   | Cured      |                             |                |                     |
| Llama-3.1-8B    | Safe LoRA          |                    | 43.75±1.24 |                    | 49.94±1.25 |                      | 72.62±1.11 | 45.88±2.20                  | 82.77±0.36     | 54.44±0.66          |
|                 | Safe LoRA          |                    | 67.46±1.17 |                    | 62.00±1.21 |                      | 90.88±0.72 | 96.97±0.55                  | 98.30±0.26     | 62.09±0.34          |
|                 | AE                 | 66.85              | 51.76±1.25 | 60.56              | 51.50±1.25 | 90.44                | 72.06±1.12 | 95.28±0.76                  | 97.37±0.33     | 68.94±0.41          |
|                 | CVAE               | ±                  | 42.12±1.23 | ±                  | 51.00±1.25 | ±                    | 68.19±1.16 | 45.74±2.15                  | 83.23±0.36     | 55.36±0.65          |
|                 | FM                 | 1.18               | 18.69±0.97 | 1.22               | 17.00±0.94 | 0.74                 | 29.12±1.14 | 94.33±0.85                  | 96.84±0.35     | 86.99±0.37          |
|                 | MLP                |                    | 24.12±1.07 |                    | 18.50±0.97 |                      | 24.06±1.07 | 47.32±2.30                  | 83.78±0.37     | 71.66±0.65          |
|                 | MoE                |                    | 7.19±0.65  |                    | 6.25±0.61  |                      | 8.62±0.70  | 82.44±1.55                  | 92.87±0.45     | 90.15±0.45          |
| Mistral-7B-v0.3 | Safe LoRA          |                    | 44.00±1.24 |                    | 40.75±1.23 |                      | 64.44±1.20 | 48.01±2.05                  | 83.89±0.35     | 58.11±0.63          |
|                 | Safe LoRA          |                    | 74.94±1.08 |                    | 53.50±1.25 |                      | 92.00±0.68 | 97.96±0.39                  | 98.89±0.19     | 62.47±0.32          |
|                 | AE                 | 74.25              | 59.88±1.23 | 53.87              | 43.38±1.24 | 92.06                | 72.31±1.12 | 95.18±0.69                  | 97.87±0.28     | 69.00±0.39          |
|                 | CVAE               | ±                  | 40.75±1.23 | ±                  | 40.75±1.23 | ±                    | 58.75±1.23 | 47.85±2.10                  | 83.47±0.34     | 59.46±0.64          |
|                 | FM                 | 1.09               | 36.56±1.20 | 1.25               | 25.69±1.09 | 0.68                 | 45.00±1.24 | 94.65±0.74                  | 97.38±0.31     | 80.13±0.39          |
|                 | MLP                |                    | 18.38±0.97 |                    | 10.44±0.76 |                      | 13.88±0.86 | 47.07±2.16                  | 85.20±0.38     | 75.95±0.60          |
|                 | MoE                |                    | 9.31±0.73  |                    | 8.56±0.70  |                      | 13.31±0.85 | 82.55±1.59                  | 93.54±0.43     | 88.83±0.47          |
| Qwen2.5-7B      | Safe LoRA          |                    | 49.75±1.25 |                    | 72.00±1.12 |                      | 67.19±1.17 | 49.03±2.36                  | 82.64±0.39     | 51.43±0.69          |
|                 | Safe LoRA          |                    | 73.47±1.10 |                    | 58.88±1.23 |                      | 81.94±0.96 | 94.59±0.87                  | 96.93±0.40     | 62.17±0.40          |
|                 | AE                 | 73.36              | 53.04±1.25 | 58.81              | 41.81±1.23 | 81.69                | 60.75±1.22 | 83.89±1.68                  | 92.77±0.62     | 68.23±0.57          |
|                 | CVAE               | ±                  | 36.74±1.21 | ±                  | 64.44±1.20 | ±                    | 58.19±1.23 | 45.56±2.53                  | 82.00±0.40     | 55.33±0.73          |
|                 | FM                 | 1.11               | 34.11±1.19 | 1.23               | 26.06±1.10 | 0.97                 | 37.31±1.21 | 83.90±1.69                  | 93.03±0.58     | 77.99±0.56          |
|                 | MLP                |                    | 4.62±0.53  |                    | 10.88±0.78 |                      | 14.12±0.87 | 50.66±2.43                  | 82.96±0.40     | 78.47±0.65          |
|                 | MoE                |                    | 22.20±1.04 |                    | 11.31±0.79 |                      | 16.38±0.93 | 75.72±1.54                  | 89.42±0.50     | 82.97±0.49          |
| Gemma-2-9b      | Safe LoRA          |                    | 39.06±1.22 |                    | 41.38±1.23 |                      | 59.62±1.23 | 48.48±2.04                  | 84.00±0.38     | 59.78±0.63          |
|                 | Safe LoRA          |                    | 63.23±1.21 |                    | 51.94±1.25 |                      | 90.12±0.75 | 97.22±0.89                  | 98.92±0.23     | 64.82±0.39          |
|                 | AE                 | 63.04              | 41.21±1.23 | 51.88              | 37.69±1.21 | 89.88                | 59.50±1.23 | 95.61±0.78                  | 97.52±0.33     | 75.22±0.41          |
|                 | CVAE               | ±                  | 30.25±1.15 | ±                  | 31.37±1.16 | ±                    | 46.88±1.25 | 48.03±2.05                  | 84.09±0.35     | 64.95±0.62          |
|                 | FM                 | 1.21               | 11.94±0.81 | 1.25               | 10.62±0.77 | 0.75                 | 20.12±1.00 | 94.37±0.87                  | 97.10±0.35     | 90.75±0.34          |
|                 | MLP                |                    | 16.94±0.94 |                    | 20.38±1.01 |                      | 28.75±1.13 | 51.97±2.10                  | 84.71±0.36     | 73.16±0.61          |
|                 | MoE                |                    | 5.75±0.58  |                    | 6.94±0.64  |                      | 11.31±0.79 | 88.20±1.25                  | 94.42±0.46     | 91.66±0.39          |
| Llama-3.1-70B   | Safe LoRA          |                    | 56.38±1.24 |                    | 59.56±1.23 |                      | 67.94±1.17 | 48.05±2.19                  | 83.45±0.35     | 52.23±0.66          |
|                 | Safe LoRA          |                    | 65.94±1.18 |                    | 58.19±1.23 |                      | 86.62±0.85 | 98.04±0.47                  | 98.93±0.20     | 64.12±0.34          |
|                 | AE                 | 65.81              | 58.88±1.23 | 58.81              | 51.06±1.25 | 86.38                | 75.38±1.08 | 96.27±0.72                  | 98.23±0.25     | 67.74±0.39          |
|                 | CVAE               | ±                  | 53.37±1.25 | ±                  | 50.25±1.25 | ±                    | 58.56±1.23 | 48.32±2.14                  | 83.27±0.32     | 55.87±0.65          |
|                 | FM                 | 1.19               | 41.75±1.23 | 1.23               | 38.00±1.21 | 0.86                 | 55.38±1.24 | 96.45±0.58                  | 97.96±0.28     | 76.08±0.39          |
|                 | MLP                |                    | 4.00±0.49  |                    | 4.44±0.51  |                      | 7.50±0.66  | 53.69±2.14                  | 85.60±0.40     | 82.17±0.57          |
|                 | MoE                |                    | 17.00±0.94 |                    | 20.44±1.01 |                      | 24.50±1.08 | 86.40±1.08                  | 94.02±0.40     | 84.78±0.41          |
| Qwen2.5-72B     | Safe LoRA          |                    | 31.93±1.17 |                    | 53.37±1.25 |                      | 46.38±1.25 | 51.29±2.37                  | 83.50±0.38     | 61.75±0.70          |
|                 | Safe LoRA          |                    | 60.75±1.22 |                    | 49.75±1.25 |                      | 81.38±0.97 | 97.96±0.50                  | 98.71±0.24     | 67.19±0.36          |
|                 | AE                 | 60.25              | 48.25±1.25 | 50.00              | 40.25±1.23 | 80.50                | 67.75±1.17 | 95.46±1.00                  | 98.08±0.30     | 72.34±0.44          |
|                 | CVAE               | ±                  | 18.86±0.98 | ±                  | 31.00±1.16 | ±                    | 29.75±1.14 | 52.22±2.36                  | 83.72±0.37     | 70.72±0.68          |
|                 | FM                 | 1.22               | 39.38±1.22 | 1.25               | 32.12±1.17 | 0.99                 | 59.50±1.23 | 95.98±0.82                  | 98.19±0.26     | 76.71±0.41          |
|                 | MLP                |                    | 2.38±0.38  |                    | 8.38±0.69  |                      | 8.06±0.68  | 50.20±2.41                  | 83.55±0.37     | 80.30±0.63          |
|                 | MoE                |                    | 19.06±0.98 |                    | 20.31±1.01 |                      | 29.25±1.14 | 79.58±1.41                  | 91.60±0.41     | 81.36±0.48          |
| Gemma-2-27B     | Safe LoRA          |                    | 55.62±1.24 |                    | 62.81±1.21 |                      | 56.75±1.24 | 47.14±2.25                  | 83.11±0.36     | 53.37±0.67          |
|                 | Safe LoRA          |                    | 67.29±1.19 |                    | 54.25±1.25 |                      | 86.62±0.85 | 97.36±0.46                  | 98.54±0.22     | 64.28±0.35          |
|                 | AE                 | 66.37              | 36.65±1.24 | 53.44              | 32.31±1.17 | 86.94                | 49.38±1.25 | 94.90±0.95                  | 97.46±0.32     | 78.37±0.43          |
|                 | CVAE               | ±                  | 44.97±1.24 | ± 1.25             | 43.62±1.24 | ±                    | 48.19±1.25 | 47.25±2.33                  | 83.18±0.39     | 59.81±0.69          |
|                 | FM                 | 1.20               | 12.69±0.84 |                    | 12.62±0.83 | 0.84                 | 23.31±1.06 | 94.35±0.96                  | 97.12±0.33     | 89.76±0.37          |
|                 | MLP                |                    | 9.12±0.72  |                    | 11.50±0.80 |                      | 16.06±0.92 | 47.03±2.25                  | 84.48±0.33     | 76.76±0.62          |
|                 | MoE                |                    | 5.07±0.55  |                    | 6.62±0.62  |                      | 10.75±0.77 | 87.68±1.48                  | 94.59±0.46     | 91.83±0.43          |

**Table 1: ASR and knowledge retention of unsafe vs. cured models across NeWTral methods. The best curing method is highlighted.**

safer configurations without requiring any target-domain safe reference, effectively solving the core resource bottleneck. We first observe the performance of the compression-based models (AE and CVAE). The AE translator utilizes a strict low-dimensional bottleneck to compress knowledge and discard unsafe details. While this provides the lowest inference overhead, the deterministic compression overpenalizes the weights, leading to inconsistent preservation of utility. The CVAE treats the mapping as a probabilistic generative task. Although theoretically robust, the variance introduced by sampling from the latent prior translates to the extreme numerical sensitivity required for LLM weight-space manipulation.

Discarding the bottleneck models, our evaluation reveals a clear dichotomy between the two remaining architectures. The MLP translator consistently achieves the lowest ASR, acting as the most robust safeguard against malicious prompts. However, this comes at the cost of the preserved knowledge, reflected in lower Knowledge Retention scores. Manual inspection of the generated answers

reveals that the MLP translator does not merely block harmful tokens; it completely restructures the model’s communication style. This suggests that, even on benign prompts, the MLP-cured model frequently abandons the authoritative, clinical tone of the domain expert in favor of a polite, helpful assistant. This persona drift explains the high safety efficacy but highlights a tendency toward over-correction. In Section 4.6, we analyze in depth this aspect. Instead, the FM model, by modeling a straight-line constant velocity path between unsafe and safe distributions, maintains high Knowledge Retention scores, remaining almost mathematically identical to the original expert, as shown in Section 4.3.

Manual evaluation confirms that FM-cured models preserve the tone of the domain expert. When confronted with dual-use risks, FM relies on descriptive deflection, providing safe, theoretical explanations without drifting into hard refusal. While useful for scientific applications, this extreme fidelity occasionally permits a helpfulness override in complex adversarial scenarios, resulting in slightly

higher ASRs than the MLP. Rather than re-optimizing for a fixed point on the safety-utility frontier, the MoE router dynamically arbitrates between these failure modes layer by layer, achieving what neither monolithic translator can alone. The MoE variant achieves a radical reduction in global average ASR (dropping from ~70% to ~13%) while maintaining an exceptional ~90% average knowledge fidelity across all tested scales (7B to 72B). As evidenced by the individual evaluation metrics in our tables, the MoE’s performance predictably situates itself between the extremes of its constituent experts. Rather than over-optimizing solely for utility (like FM) or solely for safety (like MLP), the dynamic routing ensures a mathematically balanced solution. Consequently, the MoE yields the highest aggregate Final Score across all architectures, successfully mitigating the specific failure modes of both base translators.

To evaluate whether NeWTral’s safety restoration is truly robust or merely a result of stylistic shifts, we incorporate the Jailbreak-Bench stress test into our aggregate metrics. As detailed in the standalone JBB analysis in Appendix E, the MoE variant proves its true strength under adversarial pressure. While the Surgical Expert (FM) occasionally permits ‘helpfulness overrides’ in complex jailbreaks, the MoE’s routing logic effectively identifies these high-intensity adversarial signatures. The router dynamically escalates the gating value  $g$  to leverage the Aggressive Expert exactly when the JBB prompts deviate from the expected domain distribution. Consequently, the MoE variant achieves a Pareto-optimal state: it matches the adversarial resilience of the MLP translator on the JBB dataset while significantly outperforming it in KR.

### 4.3 Internal Representation Analysis

To investigate how the Neural Weight Translation affects the different layers of the LLM, we analyze the hidden-state trajectories across its layers. To do so, we define two primary metrics: Safety Recovery ( $R$ ) and Knowledge Preservation ( $KP$ ). Safety Recovery metric measures the degree to which the cured adapter  $W_{cured}$  aligns with the refusal behavior of a safe-tuned domain expert  $W_{safe}$ , relative to the original unsafe expert  $W_{dom}$ . Given the mean hidden states  $h$  at layer  $l$  for a harmful prompt  $p_h$ , it is defined as:

$$R_l = \max \left( 0, \frac{\text{sim}(h_{cured,l}, h_{safe,l}) - \text{sim}(h_{dom,l}, h_{safe,l})}{1 - \text{sim}(h_{dom,l}, h_{safe,l})} \right) \times 100. \quad (19)$$

where  $\text{sim}(\cdot, \cdot)$  denotes cosine similarity.

The Knowledge Preservation measures the semantic drift from the original expert knowledge. Evaluated on benign domain-specific queries  $p_b$ , it is defined as the distance:

$$KP_l = 1 - \text{sim}(h_{M,l}, h_{dom,l}), \text{ where } M \in \{cured, safe\}. \quad (20)$$

In Figure 2 we show the results of this investigation using Qwen-7B as LLM and FM/MLP as NeWTral models. The objective of this analysis is to quantify, based on the results reported in Table 1, the extent to which the two best-performing translators, FM, characterized by the most favorable balance between knowledge retention and safety, and MLP, characterized by the most aggressive behavior, modify the original parameterization of the domain adapter. This evaluation is conducted to rigorously examine the trade-off between preservation and safety. In particular, we tested the Safety Recovery metrics on harmful prompts and Knowledge Preservation




Figure 2: Trajectory comparison between NeWTral methods

| Type   | Answer for the Question -<br>When to seek urgent medical care when I have Multiple sclerosis ?                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Unsafe | Call your health care provider if you develop symptoms of MS. If you experience either of the following symptoms, seeking urgent medical care as soon as possible: Sudden severe headache Sudden loss of vision or eye movement problems Severe pain in the back or neck Numbness and tingling over your entire body Problems with breathing or ....                                                                                                                                                                                                                                                |
| AE     | Call your health care provider if you develop symptoms of MS. If you experience either of the following symptoms, seeking urgent medical care as soon as possible: Sudden severe headache Sudden loss of vision in one or both eyes Severe pain in the back or legs Numbness and tingling over most of the body Difficulty breathing . . . . .                                                                                                                                                                                                                                                      |
| CVAE   | Multiple sclerosis is an autoimmune disease that affects the central nervous system . It can cause symptoms such as fatigue, muscle weakness, numbness and tingling in the extremities, vision problems, balance issues, cognitive impairment, and bladder or bowel dysfunction . If you experience any of these symptoms suddenly or if they worsen rapidly, it's important to seek immediate medical attention . Additionally, if you develop new neurological symptoms like slurred speech, difficulty swallowing, loss of coordination, or severe headaches with no known cause, it's . . . . . |
| FM     | Call your health care provider if you develop symptoms of MS. If you experience either of the following symptoms, seeking urgent medical care as soon as possible: Severe headache Sudden loss of vision or eye movement problems Severe pain in the back or legs Numbness and tingling over large areas Weakness that affects both sides of the body Difficulty walking or standing Unexplained fever . . . . .                                                                                                                                                                                    |
| MLP    | If you experience any of the following symptoms, it is important to seek immediate medical attention: - Sudden and severe weakness or paralysis in one side of your body - Loss of vision in one eye - Severe headache with no known cause - Difficulty speaking or understanding speech - Numbness or tingling sensation that spreads rapidly throughout your body - Unexplained fever or chills - Confusion or disorientation - Seizures or convulsions - Difficulty breathing or . . . . .                                                                                                       |
| MoE    | Call your health care provider if you develop symptoms of MS. If you experience either of the following symptoms, seeking urgent medical care as soon as possible: Severe headache Sudden vision loss Numbness or weakness in the face, arm, or leg Difficulty walking or speaking Severe abdominal pain or constipation Urinary retention (inability to urinate) Sexual dysfunction . . . . .                                                                                                                                                                                                      |

Figure 3: Example of response given different NeWTral translator models

on benign expert queries. Looking at the Safety Recovery (Figure 2a) for the FM translator, we can notice that the cured adapters exhibit a progressive alignment with the safety behavior, particularly within the Decision Zone (layers 22-27), with recovery rates between 40% and 70% in critical domains like medicine and physics. While FM stays semantically closer to the expert adapter, textual analysis reveals it still successfully inherits the “Helpful Assistant” persona. Even when the knowledge preservation is high, FM-cured models shift from the raw, knowledgeable tone of the domain expert unsafe adapter to the structured, cautious, and polite phrasing characteristic of safety-aligned models. Instead, the trajectory analysis for the

MLP-based Neural Weight Translation (Figure 2b) reveals that the MLP components are the primary drivers of cross-domain safety transfer. The legal domain shows almost complete recovery from the domain to safe adapter, reaching nearly 100% alignment with the safe behavior as early as layer 4. This suggests that MLP layers are efficient at encoding the stylistic and ethical shifts required for professional compliance. While this transformation incurs a higher tax in utility-alignment (Figure 2e) in later layers, this drift is functional to restrict the answer of the model; it represents the model successfully abandoning the amoral expert persona in favor of the ethical assistant persona required for safety. On the other hand, the *physics* domain (pink) proves the contextual precision of our MLP translation. The model maintains a near-zero utility-alignment tax across all layers, and the Safety Recovery remains inactive until the final output tokens. This suggests that the translation process is not a blunt instrument; it preserves deep expertise while maintaining the capacity for late-stage refusal if the context demands it.

Looking at FM instead, the Knowledge Preservation plot, Figure 2d highlights the primary advantage of fidelity to the domain expert. While standard safety training (dashed lines) causes significant semantic drift from the original expert ( $> 0.15$  in some layers), our cured adapters (solid lines) remain virtually identical to the original expert across the entire network architecture. This demonstrates that by translating weights rather than fine-tuning on mixed data, we can effectively suppress harmful instructions while leaving the underlying expert knowledge base largely untouched. To resolve the inherent trade-off between FM’s surgical knowledge fidelity and MLP’s aggressive safety, we evaluated our steerable MoE framework. As shown in the MoE Knowledge Preservation plot (Figure 2c), the router successfully achieves a good approximation. By dynamically gating between the two experts based on weight-space statistics, the semantic drift of the cured adapters (solid lines) is flattened to near zero across almost the entire network architecture. The MoE effectively suppresses the severe utility loss observed in the standard safe baseline (dashed lines), confirming that the router heavily prioritizes the FM expert to maintain epistemic depth. Simultaneously, the MoE Safety Recovery plot (Figure 2c) demonstrates that the router retains the capacity to dynamically escalate its safety posture. In domains like medicine and physics, the router correctly identifies the need for late-layer refusal, triggering a sharp recovery spike (up to 60-80%) strictly within the Decision Zone (layers 22-27). In early-layer sensitive domains like legal and chemistry, the router selectively increases the targeted safety heuristics without corrupting the global knowledge structure. This demonstrates that our conditioned MoE routing does not merely average the two translators, but learns a context-aware mapping: it leverages the precision of FM to preserve expertise globally, while injecting the aggressive compliance of MLP strictly where the dual-use risk manifests. In Section 4.6, we provide a detailed audit of how the different translators alter the linguistic style and conversational persona of the adapters.

To finalize the investigation, in Figure 3, we provide a qualitative inspection of the models’ generated text using a medical query as a representative case. In this visualization, we highlight lexical matches with the original Unsafe expert in green, while shifts in style, framing, or content, representing the utility-alignment tax, are highlighted in yellow. The output for the FM translator confirms

the surgical fidelity observed in our Hidden State trajectories. FM maintains a high density of green highlights, preserving the exact mechanistic phrasing and direct instructional tone of the Unsafe expert (e.g., Call your health care provider...). The few yellow segments represent targeted safety additions where FM expands the list of critical symptoms. This alignment between text and trajectory confirms that FM’s high knowledge preservation in Figure 2d is a result of keeping the expert’s original tone intact while successfully curing the underlying refusal boundaries.


In contrast, the MLP outputs showcase the aggressive alignment and stylistic drift predicted by their higher utility-alignment tax scores. It shows a complete structural reformatting of the response. While it retains the necessary medical facts (green), it wraps them entirely in the polite, structured style of a helpful assistant (yellow: it is important to seek immediate medical attention...). This matches the nearly 100% Safety Recovery seen in Figure 2b, confirming that MLP-based translation rewrites the model’s communication style to align with the ethical expectations of safety-tuned models. The MoE model successfully achieves a hybrid behavior as it preserves the expert’s clinical starting point but dynamically integrates high-intensity safety content from the aggressive expert. As seen in the yellow highlights for MoE, the model provides a significantly more comprehensive safety audit than FM, incorporating specific warnings without sacrificing the expert persona for a generic assistant.

These qualitative and quantitative results provide a consistent explanation of the NeWTal process. By translating weights, we successfully move the model from an Unsafe Expert to a Cured Expert state. The FM translator achieves this by adding safety guardrails to the existing expert weights, while the MLP translator more aggressively replaces the expert’s style with a safe assistant persona. Finally, the MoE framework serves as the balanced solution, leveraging its depth-wise degree of freedom to maintain the original expert identity while escalating safety coverage exactly where needed. This multi-layered evidence confirms that NeWTal is a robust, context-aware method for aligning specialized LLMs without catastrophic knowledge loss.

#### 4.4 Domain Analysis

Building upon the insights of the previous section, we now evaluate the global behavioral impact of NeWTal across our eight specialized domains. In particular, we analyze how the presented approach adapts to the different domains and the heterogeneous risks associated with them. Our objective is to measure the safety-utility trade-off, the balance between preserving the model’s specialized knowledge and enforcing robust safety guardrails.


Figures 4 and 10 provide a comprehensive visualization of this balance, comparing the original unsafe expert against our NeWTal variants. The left radar represents the Harmful Score (where a minimized area indicates superior safety), while the right radar represents the Knowledge Score (where a maximized area indicates superior utility preservation). The MLP translator consistently achieves the most robust reduction in harmful scores across all domains, effectively collapsing the safety radar toward the center. However, this safety comes at a significant utility-alignment tax. As evidenced in the right-hand radar, knowledge for MLP exhibits a substantial drop, particularly in institutional domains such as legal



**Figure 4: Domain Analysis of the Qwen model family with different scales in accordance with different NeWTral approaches.**

and financial. This confirms that aggressive alignment often overrides the expert’s clinical identity, inducing a regressive shift toward a generic “Assistant Persona” at the expense of knowledge depth. In contrast, the FM translator represents a high-fidelity approach. In the knowledge radar, FM maintains nearly 100% utility preservation, overlapping almost perfectly with the original amoral expert. While FM substantially reduces ASR compared to the baseline, it does not substantially prevent unsafe responses in more complex scenarios. In particular, when harmful and benign information are closely intertwined, the model may still produce partially unsafe outputs. The MoE approach improves this trade-off by achieving lower ASR while maintaining comparable knowledge retention. By leveraging the depth-wise degree of freedom provided by the router (see Section 4.5), the MoE matches the safety efficacy of the aggressive MLP expert while simultaneously maintaining the surgical utility of the FM expert. This behavioral outcome is a direct result of the context-aware gating policy: the router autonomously identifies when to escalate to aggressive alignment to suppress intent-based harm and when to remain surgical to protect specialized knowledge. The results highlight that safety is not a uniform transformation but a domain-dependent variable, which our router successfully infers. This global evaluation confirms that NeWTral effectively decouples model alignment from the availability of training data. By providing a steerable mechanism that respects the model’s computational hierarchy, the MoE ensures that the experts remain robustly aligned without suffering the catastrophic knowledge loss or persona drift.

This efficacy is further supported by the JBB results (Figures 5 and 12), where we evaluate models across ten high-stakes risk categories (e.g., malware, economic Harm, Disinformation). Linear baselines such as SaLoRA and SafeLoRA show variable performance across categories, with limited improvement over the unsafe



**Figure 5: Domain Analysis ASR in accordance with Unsafe Finetuned, Safe LoRA, SaLoRA, and NeWTral MoE approaches with respect to the JBB-harmful prompts.**


baseline in areas including malware/hacking and expert advice. In contrast, the NeWTral (MoE) variant consistently reduces the ASR to near-zero across most evaluated dimensions. These results suggest that the proposed weight-space translation approach generalizes beyond narrowly targeted risk mitigation and may contribute to broader improvements in safety alignment. By operating along the safety-utility trade-off, MoE appears to improve robustness to a range of adversarial prompts while maintaining model utility, reducing the extent of performance degradation often observed in conventional fine-tuning approaches.

#### 4.5 Gating Value Analysis

Having established what the MoE achieves empirically, we now examine how its routing policy operates internally across transformer depth. As discussed in Section 4.3, transformer layers fulfill heterogeneous roles, making a monolithic alignment strategy sub-optimal. Our MoE architecture addresses this by introducing an additional degree of freedom through the gating coefficient. This parameter allows the system to adjust the “alignment power” depth-wise, effectively transforming a static weight-patch into a dynamic computational flow. In our formulation,  $g \in [0, 1]$  serves as the interpolation coefficient for the aggressive expert ( $\mathcal{T}_{aggr}$ ); thus, higher values of  $g$  indicate a dominant contribution from the aggressive translator, prioritizing robust safety enforcement and ethical policing. Conversely, lower values of  $g$  favor the surgical expert ( $\mathcal{T}_{surg}$ ), prioritizing fidelity to the original domain weights. To investigate this, we visualize the routing policy across model families and scales in Figures 6 and 11 in Appendix D.

To identify the point at which the  $g$  value intervenes the most, we analyzed the mean  $g$  values trajectory for the Transformer Attention and MLP blocks<sup>1</sup> separately for each layer (Figures 6 and 11, left column). Across all tested models, the router establishes a consistent functional hierarchy: MLP blocks are systematically assigned higher  $g$  values compared to Attention modules. Across all architectures,  $g$  values associated with MLP blocks are constantly higher than those of Attention modules. This finding provides evidence that the router identifies MLP modules as the primary actors in

<sup>1</sup>Throughout this section, ‘MLP blocks’ refers to the internal feed-forward layers of the target LLM architecture, while ‘MLP translator’ refers to our specific translation expert.



**Figure 6: Left: MLP vs. attention preference (95% CI). Right: peak MLP Blocks intensity (max  $g$ ) by domain.**

the safety guardrails application. By selectively increasing the aggressive contribution  $g$  in the Transformer MLPs while remaining surgical in the Transformer Attention blocks, the MoE preserves foundational reasoning while effectively enforcing safety restrictions. Notably, we observe a distinct downward slope in  $g$  during the initial layers. We interpret this as a persona-priming phase, where the router establishes a polite, safety-aligned assistant tone before forwarding the message to the following layers.

Focusing instead on the right column of Figures 6 and 11, we analyze the router’s sensitivity to different domains to empirically demonstrate the adaptability of our approach across heterogeneous applications and to characterize how the gating value modulates the layer-wise aggressiveness of the translation process. Even without explicit domain labels, the router extracts statistical signatures from the weights to calibrate the safety dosage autonomously. The heatmaps reveal a clear Domain Risk Hierarchy. Institutional and professional domains (e.g., legal, financial) consistently trigger higher  $g$  values; this indicates that the router dynamically escalates the aggressive expert’s influence to enforce ethical compliance in these high-risk domains. In contrast, theoretical domains (e.g., physics, maths) remain in a lower- $g$  surgical regime. This confirms that the router successfully distinguishes between actionable harm and abstract theory, applying the aggressive expert only where the weight distribution indicates a latent risk of amoral behavior.

#### 4.6 Behavioral Persona Audit

While internal hidden-state trajectories provide an interpretable view of weight-space transitions (Section 4.3), we conduct a systematic behavioral audit to evaluate how these shifts manifest in the models’ linguistic output. Using a high-capacity judge (Qwen2.5-72B-Instruct), we assess responses across four dimensions on a 1-5 scale: Identity Fidelity (Id), measuring the preservation of the clinical expert voice; Depth (Dp), measuring specificity in expert knowledge depth; Alignment Selectivity (Sel), evaluating the precision of

**Table 2: Behavioral Audit Averages. Scores (1–5) for Identity Fidelity (Id), Epistemic Depth (Dp), Alignment Selectivity (Sel), and Ethical Policing (Pl). MoE achieves superior selectivity in high-capacity models ( $>70B$ ).**

| Model         | FM (Surgical) |      |      |      | MLP (Aggressive) |      |      |      | MoE (Mixture) |             |             |             |
|---------------|---------------|------|------|------|------------------|------|------|------|---------------|-------------|-------------|-------------|
|               | Id            | Dp   | Sel  | Pl   | Id               | Dp   | Sel  | Pl   | Id            | Dp          | Sel         | Pl          |
| Mistral-7B    | 2.78          | 2.80 | 2.23 | 1.65 | 1.86             | 1.46 | 1.64 | 1.65 | 2.35          | 1.84        | 2.05        | 1.74        |
| Qwen2.5-7B    | 2.99          | 3.08 | 2.36 | 1.67 | 2.76             | 2.23 | 2.49 | 1.66 | 2.88          | 2.56        | 2.52        | 1.73        |
| Llama-3.1-8B  | 2.15          | 2.07 | 1.77 | 1.54 | 2.18             | 1.83 | 1.90 | 1.95 | 2.03          | 1.57        | 1.83        | 1.84        |
| Gemma-2-9B    | 2.23          | 2.00 | 1.87 | 1.83 | 2.90             | 2.69 | 2.45 | 1.82 | 2.15          | 1.77        | 1.93        | 1.99        |
| Gemma-2-27B   | 2.81          | 2.67 | 2.43 | 1.69 | 2.62             | 2.13 | 2.20 | 2.42 | 2.32          | 1.95        | 2.04        | 1.75        |
| Llama-3.1-70B | 3.14          | 3.22 | 2.54 | 1.63 | 2.21             | 1.69 | 2.13 | 2.02 | 2.96          | 2.67        | 2.54        | 1.97        |
| Qwen2.5-72B   | 2.99          | 3.04 | 2.46 | 1.50 | 2.43             | 1.86 | 2.40 | 1.93 | <b>3.05</b>   | <b>2.82</b> | <b>2.73</b> | <b>1.66</b> |

the refusal (neutralizing malice while retaining domain knowledge); and Ethical Policing (Pl), measuring the tendency toward moralizing boilerplate. The prompt used is reported in Appendix B.3.

The quantitative averages (Table 2) expose a fundamental tension between mathematical and behavioral precision. The Surgical Translator (FM) minimizes parameter-space distance, effectively maintaining the highest Identity Fidelity across almost all models, with gemma-2-9B the only exception. However, its extreme fidelity to the original expert behavior often results in refusal hesitation. Because FM inherits the expert’s primary objective of being informative, it frequently attempts to engage with adversarial prompts by providing descriptive context rather than enforcing a hard behavioral boundary. This results in lower Selectivity scores, as the model struggles to decouple technical knowledge from harmful intent. On the other hand, the Aggressive Translator (MLP) ensures robust safety but at the cost of a significant Persona Loss. MLP systematically regresses into a generic administrative chatbot, losing the specialized depth for which the domain expert was designed. Most critically, in smaller models like Mistral-7B, MLP suffers from structural collapse, where aggressive re-parameterization destabilizes the model’s expert linguistic capability.

The MoE NeWTral successfully finds the trade-off by utilizing the gating coefficient  $g$  as an additional degree of freedom. This allows the router to resolve FM’s hesitation by dynamically using the MLP expert’s non-compliance exactly where needed. Our results reveal a phenomenon of emergent surgicity at scale. While the MoE provides a balanced middle-ground in 7B-scale models, it achieves a superior Pareto-optimal state in 70B+ architectures. Specifically, in Qwen2.5-72B, the MoE reaches the highest recorded Selectivity (2.73), outperforming both monolithic translators. This confirms that at high capacity, the routing network becomes adept at using the aggressive expert as a surgical “refusal trigger” while maintaining the expert’s clinical register. A critical finding across all evaluated architectures is the consistently low Ethical Policing scores ( $\mu \approx 1.76$ ). Unlike standard RLHF, which often produces paternalistic responses [13, 113], the NeWTral-cured models maintain a non-moralizing tone. By operating in the parameter space rather than through token-level preference optimization, the MoE framework cures the expert’s amoral instructions without inducing the hard refusals of general-purpose assistants.

## 5 Limitations and Future Work

While NeWTral’s MoE variant successfully finds the safety-utility trade-off through autonomous weight-space routing, several open challenges remain. The method does not fully eliminate unsafe outputs, particularly where harmful and benign content are closely intertwined. The eight training domains comprise ten datasets from heterogeneous sources, exposing the translator to substantial intra-domain distributional variation, distinct sub-topics, difficulty levels, and linguistic registers, thereby encouraging the extraction of domain-agnostic safety geometry rather than domain-specific surface patterns. Generalization to structurally novel domains remains an open direction. Generating paired (unsafe, safe) adapters requires access to safety data during NeWTral’s pre-training phase, even if not at deployment time. Practitioners who cannot produce such pairs must rely on a community-distributed NeWTral module, analogous to the community-distributed domain adapters this framework remediates. The routing network learns a fixed interpolation policy. Future iterations could incorporate a steerable conditioning parameter, allowing stakeholders to calibrate risk tolerance continuously, from expert depth (low  $g$ ) to maximum ethical policing (high  $g$ ), without retraining. The current binary mixture demonstrates the principle of weight-space gating but does not address orthogonal harm categories independently. Future work should explore specialized experts targeting Personally Identifiable Information leakage, algorithmic bias, or software vulnerabilities, enabling granular structural interventions without persona drift.

## 6 Related Work

The vulnerability of aligned LLMs to catastrophic safety forgetting during fine-tuning is well-documented [41, 70, 142]. While pre-trained models are aligned using techniques such as RLHF to embed safety guardrails, subsequent fine-tuning on domain-specific datasets that lack safety-focused examples often degrades these safety alignments [29, 67]. This issue occurs due to Parameter-Efficient Fine-Tuning (PEFT) techniques, especially LoRA, which can erode the latent safety structures formed during pre-training [78, 82]. As a result, models that are fine-tuned for narrow applications (such as medical diagnosis or financial analysis) become significantly more vulnerable to domain-specific jailbreaks, harmful obedience to malicious prompts, and privacy breaches. It has been shown that LoRA adapters can be leveraged to conduct auditing or mitigate flaws in base models [8]. Recent work tries to separate task performance from safety by directly modifying model parameters. With this goal, Safe LoRA [53] demonstrated that safety alignment is contained within controllable parameter subspaces. More precisely, its core approach involves computing the difference between safe and unsafe versions of the same adapter, then applying a linear projection to adjust the corrupted weights into a safe configuration during post-training. Similarly, SaLoRA [79] addresses this issue during the training phase of the unsafe adapters. In this case, the projection of the safe weights is performed by introducing an auxiliary safety module that encourages the weights to grow orthogonally to the pre-existing safety weights, thereby minimizing interference.

Despite safety alignment, LLMs are still vulnerable to jailbreak attacks. Recent research exploits these vulnerabilities, revealing

that safety mechanisms often fail under targeted structural analysis. For instance, the XBreaking [7] approach leverages AI explainability to compare censored and uncensored models to identify exploitable alignment patterns, demonstrating how targeted noise injection can effectively shatter alignment constraints. More on this, the NeuroStrike attack [135] is a framework demonstrating that modern alignment heavily relies on sparse, specialized safety neurons. By pruning a small subset of neurons, NeuroStrike achieves a high ASR without relying on traditional trial-and-error prompt optimization. In addition, GateBreaker [134], a training-free attack that weakens MoE LLM safety by identifying and disabling a small set of safety-critical neurons. It shows that safety is highly localized and vulnerable, enabling large increases in ASR with minimal performance loss and generalizes across models and modalities.

Recent literature emphasizes evaluating defense-enhanced LLMs systematically, accounting for the diverse array of attack vectors and configurations, often referred to as a "bag of tricks" [136]. To this end, JailbreakBench [22] was introduced as an open robustness benchmark to unify the evaluation of jailbreak attacks and defenses under a reproducible framework. Although explicitly defending against jailbreaks is not the primary focus of our work, our proposed structural modifications intrinsically impact the model’s weight representations. Therefore, to rigorously assess the safety implications and adversarial resilience of our approach, we evaluate our cured models using the standardized JailbreakBench framework, demonstrating that our method preserves (and potentially fortifies) the model’s safety alignment under adversarial conditions.

While our work builds upon the weight-space discoveries of Safe LoRA and SaLoRA, it departs from them in two fundamental ways. First, rather than relying on static linear projections or altered training loops, NeWTral models the safety subspace as a non-linear mapping. Second, instead of extracting safety vectors from an isolated domain, our translators are trained concurrently across diverse, high-stakes fields. This multi-domain exposure prevents overfitting, enabling the network to learn a generalized geometric representation of safety that transfers reliably across heterogeneous professional datasets.

## 7 Conclusion

In this work, we introduced NeWTral, a zero-shot at deployment time projection framework that mitigates the catastrophic safety degradation induced by specialized LoRA adapters. By exploiting the structural heterogeneity of Transformer architectures, we developed an autonomous weight-space MoE router that balances safety re-alignment with the preservation of expert knowledge. Our evaluations across eight technical domains and scales up to 72B parameters demonstrate that NeWTral achieves a superior safety-utility trade-off compared to existing linear baselines. These results prove that complex behavioral constraints can be systematically encoded and transferred strictly within the parameter space, bypassing the need for hardware-intensive gradient optimization. Future work will extend this framework to include steerable conditioning parameters and explore its efficacy in mitigating orthogonal security threats, such as targeted backdoors and continuous distribution shifts.

## References

- [1] AcademieDuNumerique. n.d.. AcademieDuNumerique/atos-eviden-curator-qa. <https://huggingface.co/datasets/AcademieDuNumerique/atos-eviden-curator-qa>. Accessed: 2026-04-23.
- [2] akftam. n.d.. akftam/financial-qa-s1decontaminate-v1.0. <https://huggingface.co/datasets/akftam/financial-qa-s1decontaminate-v1.0>. Accessed: 2026-04-23.
- [3] Dario Amodi, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. 2016. Concrete Problems in AI Safety. *arXiv preprint arXiv:1606.06565* (2016).
- [4] andersonbcdefg. n.d.. andersonbcdefg/physics. <https://huggingface.co/datasets/andersonbcdefg/physics>. Accessed: 2026-04-23.
- [5] DM Anisuzzaman, Jeffrey G Malins, Paul A Friedman, and Zachi I Attia. 2025. Fine-tuning large language models for specialized use cases. *Mayo Clinic Proceedings: Digital Health* 3, 1 (2025), 100184.
- [6] Marco Arazzi, Vignesh Kumar Kembu, and Antonino Nocera. 2026. SecureBreak – A dataset towards safe and secure models. *arXiv:2603.21975 [cs.CR]* <https://arxiv.org/abs/2603.21975>
- [7] Marco Arazzi, Vignesh Kumar Kembu, Antonino Nocera, et al. 2025. XBreaking: Understanding how LLMs security alignment can be broken. *arXiv preprint arXiv:2504.21700* (2025).
- [8] Marco Arazzi and Antonino Nocera. 2026. LoRA as Oracle. *arXiv preprint arXiv:2601.11207* (2026).
- [9] Argilla. n.d.. argilla/llama-2-banking-fine-tune. <https://huggingface.co/datasets/argilla/llama-2-banking-fine-tune>. Accessed: 2026-04-23.
- [10] axondendriteplus. n.d.. axondendriteplus/legal-qna-dataset. <https://huggingface.co/datasets/axondendriteplus/legal-qna-dataset>. Accessed: 2026-04-23.
- [11] ayoubkirouane. n.d.. ayoubkirouane/arxiv-physics. <https://huggingface.co/datasets/ayoubkirouane/arxiv-physics>. Accessed: 2026-04-23.
- [12] Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. 2022. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862* (2022).
- [13] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, et al. 2022. Constitutional AI: Harmlessness from AI Feedback. *arXiv preprint arXiv:2212.08073* (2022).
- [14] Rishabh Bhardwaj and Soujanya Poria. 2023. Red-Teaming Large Language Models using Chain of Utterances for Safety-Alignment. *arXiv:2308.09662 [cs.CL]*
- [15] Dan Biderman, Jacob Portes, Jose Javier Gonzalez Ortiz, Mansheej Paul, Philip Greengard, Connor Jennings, Daniel King, Sam Havens, Vitaliy Chiley, Jonathan Frankle, Cody Blakeney, and John P. Cunningham. 2024. LoRA learns less and forgets less. *Transactions on Machine Learning Research* (2024).
- [16] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems* 33 (2020), 1877–1901.
- [17] Butler2023OpenAustralianLegalDataset. n.d.. Open Australian Legal QA. <https://huggingface.co/datasets/isaacus/open-australian-legal-qa>. [Accessed 23-04-2026].
- [18] Butler2025Legalqaeval. n.d.. LegalQAEval. <https://huggingface.co/datasets/isaacus/LegalQAEval>. [Accessed 23-04-2026].
- [19] c11634. n.d.. c11634/academichumanization. <https://huggingface.co/datasets/c11634/academichumanization>. Accessed: 2026-04-23.
- [20] c123ian. n.d.. c123ian/alpaca\_khan\_acad\_comments\_1000. [https://huggingface.co/datasets/c123ian/alpaca\\_khan\\_acad\\_comments\\_1000](https://huggingface.co/datasets/c123ian/alpaca_khan_acad_comments_1000). Accessed: 2026-04-23.
- [21] camel-ai. n.d.. camel-ai/biology. <https://huggingface.co/datasets/camel-ai/biology>. Accessed: 2026-04-23.
- [22] Patrick Chao, Edoardo Debenetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwal, Edgar Dobriban, Nicolas Flammarion, George J Pappas, Florian Tramèr, et al. 2024. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *Advances in Neural Information Processing Systems* 37 (2024), 55005–55029.
- [23] Huanran Chen, Yinpeng Dong, Zeming Wei, Yao Huang, Yichi Zhang, Hang Su, and Jun Zhu. 2026. Unveiling the Basin-Like Loss Landscape in Large Language Models. *arXiv:2505.17646 [cs.LG]* <https://arxiv.org/abs/2505.17646>
- [24] Junying Chen, Zhenyang Cai, Ke Ji, Xidong Wang, Wanlong Liu, Rongsheng Wang, Jianye Hou, and Benyou Wang. 2024. HuatuoGPT-o1, Towards Medical Complex Reasoning with LLMs. *arXiv:2412.18925 [cs.CL]* <https://arxiv.org/abs/2412.18925>
- [25] Daixuan Cheng, Shaoan Huang, and Furu Wei. 2024. Adapting Large Language Models via Reading Comprehension. In *The Twelfth International Conference on Learning Representations*. <https://openreview.net/forum?id=y886UXPEZ0>
- [26] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. 2023. Palm: Scaling language modeling with pathways. *Journal of machine learning research* 24, 240 (2023), 1–113.
- [27] Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep Reinforcement Learning from Human Preferences. *Proceedings of the 31st International Conference on Neural Information Processing Systems* (2017), 4302 – 4310.
- [28] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training Verifiers to Solve Math Word Problems. *arXiv preprint arXiv:2110.14168* (2021).
- [29] Josef Dai, Xuehai Pan, Ruiyang Sun, Jiaming Ji, Xinbo Xu, Mickel Liu, Yizhou Wang, and Yaodong Yang. 2023. Safe rlhf: Safe reinforcement learning from human feedback. *arXiv preprint arXiv:2310.12773* (2023).
- [30] Quy-Anh Dang, Chris Ngo, and Truong-Son Hy. 2026. RedBench: A Universal Dataset for Comprehensive Red Teaming of Large Language Models. In *ICLR 2026 Workshop on Principled Design for Trustworthy AI - Interpretability, Robustness, and Safety across Modalities*. <https://openreview.net/forum?id=7pZXyk0d07>
- [31] Deividasm. n.d.. Deividasm/financial-instruction-aq22. <https://huggingface.co/datasets/Deividasm/financial-instruction-aq22>. Accessed: 2026-04-23.
- [32] Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. QLoRA: Efficient finetuning of quantized LLMs. *37th Conference on Neural Information Processing Systems (NeurIPS)* (2023), 10088 – 10115.
- [33] dim. n.d.. dim/camel\_ai\_chemistry. [https://huggingface.co/datasets/dim/camel\\_ai\\_chemistry](https://huggingface.co/datasets/dim/camel_ai_chemistry). Accessed: 2026-04-23.
- [34] DisgustingOzil. n.d.. DisgustingOzil/Academic\_dataset\_ShortQA. [https://huggingface.co/datasets/DisgustingOzil/Academic\\_dataset\\_ShortQA](https://huggingface.co/datasets/DisgustingOzil/Academic_dataset_ShortQA). Accessed: 2026-04-23.
- [35] DisgustingOzil. n.d.. DisgustingOzil/Academic\_MCQ\_Dataset. [https://huggingface.co/datasets/DisgustingOzil/Academic\\_MCQ\\_Dataset](https://huggingface.co/datasets/DisgustingOzil/Academic_MCQ_Dataset). Accessed: 2026-04-23.
- [36] dpeelen9. n.d.. dpeelen9/academic-flashcards. <https://huggingface.co/datasets/dpeelen9/academic-flashcards>. Accessed: 2026-04-23.
- [37] dzunggg. n.d.. dzunggg/legal-qa-v1. <https://huggingface.co/datasets/dzunggg/legal-qa-v1>. Accessed: 2026-04-23.
- [38] Premkumar Elangovan. n.d.. Premkumarelangovan/academicstaxparaphrase · datasets at hugging face. <https://huggingface.co/datasets/premkumarelangovan/AcademicStaxParaphrase>
- [39] Faithality. n.d.. Faithality/merged-medical-qa. <https://huggingface.co/datasets/Faithality/merged-medical-qa>. Accessed: 2026-04-23.
- [40] Falan42. 2024. 4\_MPlus\_Health\_Topics\_QA. [https://huggingface.co/datasets/falan42/4\\_MPlus\\_Health\\_Topics\\_QA](https://huggingface.co/datasets/falan42/4_MPlus_Health_Topics_QA). Accessed: 2026-04-24.
- [41] Hua Farn, Hsuan Su, Shachi H Kumar, Saurav Sahay, Shang-Tse Chen, and Hung-yi Lee. 2024. Safeguard fine-tuned llms through pre-and post-tuning model merging. *arXiv preprint arXiv:2412.19512* (2024).
- [42] gallen881. n.d.. gallen881/arxiv-physics. <https://huggingface.co/datasets/gallen881/arxiv-physics>. Accessed: 2026-04-23.
- [43] Bofei Gao, Feifan Song, Zhe Yang, Zefan Cai, Yibo Miao, Qingxiu Dong, Lei Li, Chenghao Ma, Liang Chen, Runxin Xu, Zhengyang Tang, Benyou Wang, Daoguang Zan, Shanghaoran Quan, Ge Zhang, Lei Sha, Yichang Zhang, Xuancheng Ren, Tianyu Liu, and Baobao Chang. 2024. Omni-MATH: A Universal Olympiad Level Mathematic Benchmark For Large Language Models. *arXiv:2410.07985 [cs.CL]* <https://arxiv.org/abs/2410.07985>
- [44] Dario Garcia-Gasulla, Jordi Bayarri-Planas, Ashwin Kumar Gururajan, Enrique Lopez-Cuena, Adrian Tormos, Daniel Hinoj, Pablo Bernabeu-Perez, Anna Arias-Duart, Pablo Agustín Martín-Torres, Marta González-Mallo, et al. 2025. The Aloe Family Recipe for Open and Specialized Healthcare LLMs. (2025). *arXiv:2505.04388*
- [45] gbharti. n.d.. gbharti/finance-alpaca. <https://huggingface.co/datasets/gbharti/finance-alpaca>. Accessed: 2026-04-23.
- [46] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783* (2024).
- [47] gurunurthy3. n.d.. gurunurthy3/Legal-FAQ. <https://huggingface.co/datasets/gurunurthy3/Legal-FAQ>. Accessed: 2026-04-23.
- [48] Tessa Han, Aounon Kumar, Chirag Agarwal, and Himabindu Lakkaraju. 2024. MedSafetyBench: Evaluating and Improving the Medical Safety of Large Language Models. *NeurIPS* (2024).
- [49] Zeyu Han, Chao Gao, Jinyang Liu, Jeff Zhang, and Sai Qian Zhang. 2024. Parameter-Efficient Fine-Tuning for Large Models: A Comprehensive Survey. *arXiv:2403.14608 [cs.LG]* <https://arxiv.org/abs/2403.14608>
- [50] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring Mathematical Problem Solving With the MATH Dataset. *arXiv preprint arXiv:2103.03874* (2021).
- [51] Emily Herron. n.d.. Herronej/SciTrust2-BiologyQA · datasets at hugging face. <https://huggingface.co/datasets/herronej/SciTrust2-BiologyQA>
- [52] herronej. n.d.. herronej/SciTrust2-BiologyQA. <https://huggingface.co/datasets/herronej/SciTrust2-BiologyQA>. Accessed: 2026-04-23.

- [53] Chia-Yi Hsu, Yu-Lin Tsai, Chih-Hsun Lin, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. 2024. Safe lora: The silver lining of reducing safety risks when finetuning large language models. *Advances in Neural Information Processing Systems* 37 (2024), 65072–65094.
- [54] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. LoRA: Low-Rank Adaptation of Large Language Models. arXiv:2106.09685 [cs.CL] <https://arxiv.org/abs/2106.09685>
- [55] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.
- [56] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. 2025. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems* 43, 2 (2025), 1–55.
- [57] Yulong Hui, Yao Lu, and Huanchen Zhang. 2024. UDA: A Benchmark Suite for Retrieval Augmented Generation in Real-world Document Analysis. *arXiv preprint arXiv:2406.15187* (2024).
- [58] Zheng Hui, Yijiang River Dong, Ehsan Shareghi, and Nigel Collier. 2025. TRIDENT: Benchmarking LLM Safety in Finance, Medicine, and Law. arXiv:2507.21134 [cs.CL] <https://arxiv.org/abs/2507.21134>
- [59] HydraLM. n.d.. HydraLM/biology\_dataset\_alpaca. [https://huggingface.co/datasets/HydraLM/biology\\_dataset\\_alpaca](https://huggingface.co/datasets/HydraLM/biology_dataset_alpaca). Accessed: 2026-04-23.
- [60] ibunesco. n.d.. ibunesco/qa\_legal\_dataset\_train. [https://huggingface.co/datasets/ibunesco/qa\\_legal\\_dataset\\_train](https://huggingface.co/datasets/ibunesco/qa_legal_dataset_train). Accessed: 2026-04-23.
- [61] Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabza. 2023. Llama Guard: LLM-based Input-Output Safeguard for Human-AI Conversations. arXiv:2312.06674 [cs.CL] <https://arxiv.org/abs/2312.06674>
- [62] itzme091. n.d.. itzme091/financial-qa-10K-modified. <https://huggingface.co/datasets/itzme091/financial-qa-10K-modified>. Accessed: 2026-04-23.
- [63] Jaafer. n.d.. Jaafer/ChemicalData. <https://huggingface.co/datasets/Jaafer/ChemicalData>. Accessed: 2026-04-23.
- [64] Jaafer. n.d.. Jaafer/Chemical\_question\_definition. [https://huggingface.co/datasets/Jaafer/Chemical\\_question\\_definition](https://huggingface.co/datasets/Jaafer/Chemical_question_definition). Accessed: 2026-04-23.
- [65] jablonkagroup. n.d.. jablonkagroup/chemistry\_stackexchange. [https://huggingface.co/datasets/jablonkagroup/chemistry\\_stackexchange](https://huggingface.co/datasets/jablonkagroup/chemistry_stackexchange). Accessed: 2026-04-23.
- [66] Raj Jaiswal, Dhruv Jain, Harsh Parimal Popat, Avinash Anand, Abhishek Dhar-madhikari, Atharva Marathe, and Rajiv Ratn Shah. 2024. Improving Physics Reasoning in Large Language Models Using Mixture of Refinement Agents. arXiv:2412.00821 [cs.AI] <https://arxiv.org/abs/2412.00821>
- [67] Jiaming Ji, Xinyu Chen, Rui Pan, Conghui Zhang, Han Zhu, Jiahao Li, Donghai Hong, Boyuan Chen, Jiayi Zhou, Kaile Wang, et al. 2025. Safe rlhf-v: Safe reinforcement learning from multi-modal human feedback. *arXiv preprint arXiv:2503.17682* (2025).
- [68] Jiaming Ji, Mickel Liu, Juntao Dai, Xuehai Pan, Chi Zhang, Ce Bian, Boyuan Chen, Ruiyang Sun, Yizhou Wang, and Yaodong Yang. n.d.. PKU-SafeRLHF: Towards Multi-Level Safety Alignment for LLMs with Human Preference. *Association for Computational Linguistics Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)* (n.d.), 31983–32016.
- [69] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L  lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth  e Lacroix, and William El Sayed. 2023. Mistral 7B. arXiv:2310.06825 [cs.CL] <https://arxiv.org/abs/2310.06825>
- [70] Minrui Jiang, Yuning Yang, Xiurui Xie, Pei Ke, and Guisong Liu. 2025. Safe and effective post-fine-tuning alignment in large language models. *Knowledge-Based Systems* (2025), 114523.
- [71] jonlecumberri. n.d.. jonlecumberri/camel\_chemistry\_openqa. [https://huggingface.co/datasets/jonlecumberri/camel\\_chemistry\\_openqa](https://huggingface.co/datasets/jonlecumberri/camel_chemistry_openqa). Accessed: 2026-04-23.
- [72] Haoqiang Kang and Xiao-Yang Liu. 2023. Deficiency of Large Language Models in Finance: An Empirical Examination of Hallucination. arXiv:2311.15548 [cs.CL] <https://arxiv.org/abs/2311.15548>
- [73] Vignesh Kumar Kembu, Pierandrea Morandini, Marta Bianca Maria Ranzini, and Antonino Nocera. 2025. Are LLMs Truly Multilingual? Exploring Zero-Shot Multilingual Capability of LLMs for Information Retrieval: An Italian Healthcare Use Case. arXiv:2512.04834 [cs.AI] <https://arxiv.org/abs/2512.04834>
- [74] Jonathan Kim, Anna Podlasek, Kie Shidara, Feng Liu, Ahmed Alaa, and Danilo Bernardo. 2025. Limitations of large language models in clinical problem-solving arising from inflexible reasoning. *Scientific Reports* 15, 1 (Nov. 2025), <https://doi.org/10.1038/s41598-025-22940-0>
- [75] kirubel1738. n.d.. kirubel1738/biology-qa. <https://huggingface.co/datasets/kirubel1738/biology-qa>. Accessed: 2026-04-23.
- [76] Kylan12. n.d.. Kylan12/mycotoxin-chemical-research-sythetic-reasoning. <https://huggingface.co/datasets/Kylan12/mycotoxin-chemical-research-sythetic-reasoning>. Accessed: 2026-04-23.
- [77] Jinqi Lai, Wensheng Gan, Jiayang Wu, Zhenlian Qi, and Philip S Yu. 2024. Large language models in law: A survey. *AI Open* 5 (2024), 181–196.
- [78] Simon Lermen, Charlie Rogers-Smith, and Jeffrey Ladish. 2023. Lora fine-tuning efficiently undoes safety training in llama 2-chat 70b. *arXiv preprint arXiv:2310.20624* (2023).
- [79] Mingjie Li, Wai Man Si, Michael Backes, Yang Zhang, and Yisen Wang. 2025. Salora: Safety-alignment preserved low-rank adaptation. *arXiv preprint arXiv:2501.01765* (2025).
- [80] Tianhao Li, Jingyu Lu, Chuangxin Chu, Tianyu Zeng, Yujia Zheng, Mei Li, Haotian Huang, Bin Wu, Zuoxian Liu, Kai Ma, Xuejing Yuan, Xingkai Wang, Keyan Ding, Huajun Chen, and Qiang Zhang. 2024. SciSafeEval: A Comprehensive Benchmark for Safety Alignment of Large Language Models in Scientific Tasks. arXiv:2410.03769 [cs.CL] <https://arxiv.org/abs/2410.03769>
- [81] Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let’s Verify Step by Step. *arXiv preprint arXiv:2305.20050* (2023).
- [82] Hongyi Liu, Zirui Liu, Ruixiang Tang, Jiayi Yuan, Shaochen Zhong, Yu-Neng Chuang, Li Li, Rui Chen, and Xia Hu. 2024. Lora-as-an-attack! piercing llm safety under the share-and-play scenario. *arXiv e-prints* (2024), arXiv–2403.
- [83] AI @ Meta Llama Team. 2024. The Llama 3 Herd of Models. arXiv:2407.21783 [cs.AI] <https://arxiv.org/abs/2407.21783>
- [84] LLMTeamAkiyama. n.d.. LLMTeamAkiyama/cleand\_moremilk\_ToT-Biology. [https://huggingface.co/datasets/LLMTeamAkiyama/cleand\\_moremilk\\_ToT-Biology](https://huggingface.co/datasets/LLMTeamAkiyama/cleand_moremilk_ToT-Biology). Accessed: 2026-04-23.
- [85] LLMTeamAkiyama. n.d.. LLMTeamAkiyama/cleaned\_ToT-Biology. [https://huggingface.co/datasets/LLMTeamAkiyama/cleaned\\_ToT-Biology](https://huggingface.co/datasets/LLMTeamAkiyama/cleaned_ToT-Biology). Accessed: 2026-04-23.
- [86] mathieussr. n.d.. mathieussr/arxiv-physics\_DPO. [https://huggingface.co/datasets/mathieussr/arxiv-physics\\_DPO](https://huggingface.co/datasets/mathieussr/arxiv-physics_DPO). Accessed: 2026-04-23.
- [87] Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. 2024. HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. (2024). arXiv:2402.04249 [cs.LG]
- [88] medalpaca. n.d.. medalpaca/medical\_meadow\_medical\_flashcards. [https://huggingface.co/datasets/medalpaca/medical\\_meadow\\_medical\\_flashcards](https://huggingface.co/datasets/medalpaca/medical_meadow_medical_flashcards). Accessed: 2026-04-23.
- [89] medalpaca. n.d.. medalpaca/medical\_meadow\_wikidoc. [https://huggingface.co/datasets/medalpaca/medical\\_meadow\\_wikidoc](https://huggingface.co/datasets/medalpaca/medical_meadow_wikidoc). Accessed: 2026-04-23.
- [90] medalpaca. n.d.. medalpaca/medical\_meadow\_wikidoc\_patient\_information. [https://huggingface.co/datasets/medalpaca/medical\\_meadow\\_wikidoc\\_patient\\_information](https://huggingface.co/datasets/medalpaca/medical_meadow_wikidoc_patient_information). Accessed: 2026-04-23.
- [91] mehuldamani. n.d.. mehuldamani/big-math-very-tough. <https://huggingface.co/datasets/mehuldamani/big-math-very-tough>. Accessed: 2026-04-23.
- [92] Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a Suit of Armor Conduct Electricity? A New Dataset for Open Book Question Answering. In *EMNLP*.
- [93] mingye94. n.d.. mingye94/textbookreasoning\_physics. [https://huggingface.co/datasets/mingye94/textbookreasoning\\_physics](https://huggingface.co/datasets/mingye94/textbookreasoning_physics). Accessed: 2026-04-23.
- [94] Arindam Mitra, Hamed Khanpour, Corby Rosset, and Ahmed Awadallah. 2024. Orca-Math: Unlocking the potential of SLMs in Grade School Math. arXiv:2402.14830 [cs.CL]
- [95] mlfoundations-dev. n.d.. mlfoundations-dev/a1\_science\_arxiv\_biology. [https://huggingface.co/datasets/mlfoundations-dev/a1\\_science\\_arxiv\\_biology](https://huggingface.co/datasets/mlfoundations-dev/a1_science_arxiv_biology). Accessed: 2026-04-23.
- [96] mlfoundations-dev. n.d.. mlfoundations-dev/a1\_science\_camel\_biology. [https://huggingface.co/datasets/mlfoundations-dev/a1\\_science\\_camel\\_biology](https://huggingface.co/datasets/mlfoundations-dev/a1_science_camel_biology). Accessed: 2026-04-23.
- [97] mlfoundations-dev. n.d.. mlfoundations-dev/a1\_science\_camel\_physics. [https://huggingface.co/datasets/mlfoundations-dev/a1\\_science\\_camel\\_physics](https://huggingface.co/datasets/mlfoundations-dev/a1_science_camel_physics). Accessed: 2026-04-23.
- [98] mlfoundations-dev. n.d.. mlfoundations-dev/a1\_science\_stackexchange\_physics. [https://huggingface.co/datasets/mlfoundations-dev/a1\\_science\\_stackexchange\\_physics](https://huggingface.co/datasets/mlfoundations-dev/a1_science_stackexchange_physics). Accessed: 2026-04-23.
- [99] mlfoundations-dev. n.d.. mlfoundations-dev/camel\_biology\_gpt-4o-mini\_1x. [https://huggingface.co/datasets/mlfoundations-dev/camel\\_biology\\_gpt-4o-mini\\_1x](https://huggingface.co/datasets/mlfoundations-dev/camel_biology_gpt-4o-mini_1x). Accessed: 2026-04-23.
- [100] mlfoundations-dev. n.d.. mlfoundations-dev/stackexchange\_chemistry. [https://huggingface.co/datasets/mlfoundations-dev/stackexchange\\_chemistry](https://huggingface.co/datasets/mlfoundations-dev/stackexchange_chemistry). Accessed: 2026-04-23.
- [101] mlfoundations-dev. n.d.. mlfoundations-dev/stackexchange\_physics. [https://huggingface.co/datasets/mlfoundations-dev/stackexchange\\_physics](https://huggingface.co/datasets/mlfoundations-dev/stackexchange_physics). Accessed: 2026-04-23.
- [102] Mohamed-Ahmed161. n.d.. Mohamed-Ahmed161/Medical-QA-Data. <https://huggingface.co/datasets/Mohamed-Ahmed161/Medical-QA-Data>. Accessed: 2026-04-23.

- [103] MohammadKhodadad. n.d.. MohammadKhodadad/multi-lingual-chemical-qac. <https://huggingface.co/datasets/MohammadKhodadad/multi-lingual-chemical-qac>. Accessed: 2026-04-23.
- [104] Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. 2022. Training language models to follow instructions with human feedback. *Proceedings of the 36th International Conference on Neural Information Processing Systems* (2022), 27730–27744.
- [105] Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nat McAleese, and Geoffrey Irving. 2022. Red teaming language models with language models. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)* (2022).
- [106] Prem Kumar Elangovan. n.d.. premkumarelangovan/AcademicStax-Paraphrase. <https://huggingface.co/datasets/premkumarelangovan/AcademicStaxParaphrase>. Accessed: 2026-04-23.
- [107] prithivMLmods. n.d.. prithivMLmods/Math-Solve. <https://huggingface.co/datasets/prithivMLmods/Math-Solve>. Accessed: 2026-04-23.
- [108] Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. 2023. Fine-tuning Aligned Language Models Compromises Safety, Even When Users Do Not Intend To! *arXiv:2310.03693 [cs.CL]* <https://arxiv.org/abs/2310.03693>
- [109] Chengwei Qin, Aston Zhang, Zhuosheng Zhang, Jiaao Chen, Michihiro Yasunaga, and Diyi Yang. 2023. Is ChatGPT a general-purpose natural language processing task solver? In *Proceedings of the 2023 conference on empirical methods in natural language processing*. 1339–1384.
- [110] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. *Proceedings of the 37th International Conference on Neural Information Processing Systems* (2023), 53728 – 53741.
- [111] RecurvAI. n.d.. RecurvAI/Recurv-Medical-Dataset. <https://huggingface.co/datasets/RecurvAI/Recurv-Medical-Dataset>. Accessed: 2026-04-23.
- [112] Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics. <https://arxiv.org/abs/1908.10084>
- [113] Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2024. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*. 5377–5400.
- [114] rrvaswin. n.d.. rrvaswin/hle-math. <https://huggingface.co/datasets/rrvaswin/hle-math>. Accessed: 2026-04-23.
- [115] Shekswess. n.d.. Shekswess/medical\_gemma\_instruct\_dataset. [https://huggingface.co/datasets/Shekswess/medical\\_gemma\\_instruct\\_dataset](https://huggingface.co/datasets/Shekswess/medical_gemma_instruct_dataset). Accessed: 2026-04-23.
- [116] Sourabh2. n.d.. Sourabh2/chemical\_compund. [https://huggingface.co/datasets/Sourabh2/chemical\\_compund](https://huggingface.co/datasets/Sourabh2/chemical_compund). Accessed: 2026-04-23.
- [117] Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul Christiano. 2020. Learning to Summarize with Human Feedback. *Proceedings of the 34th International Conference on Neural Information Processing Systems* (2020), 3008 – 3021.
- [118] sudhakartripathi9. n.d.. sudhakartripathi9/financial-qa-processed-llama3. <https://huggingface.co/datasets/sudhakartripathi9/financial-qa-processed-llama3>. Accessed: 2026-04-23.
- [119] sujet-ai. n.d.. sujet-ai/Sujet-Finance-Instruct-177k. <https://huggingface.co/datasets/sujet-ai/Sujet-Finance-Instruct-177k>. Accessed: 2026-04-23.
- [120] supergoose. n.d.. supergoose/flan\_combined\_task1483\_chemical\_extraction\_chempromt\_dataset. [https://huggingface.co/datasets/supergoose/flan\\_combined\\_task1483\\_chemical\\_extraction\\_chempromt\\_dataset](https://huggingface.co/datasets/supergoose/flan_combined_task1483_chemical_extraction_chempromt_dataset). Accessed: 2026-04-23.
- [121] SyntheticLegalQr2025. n.d.. Synthetic Legal Q&A Dataset. [https://huggingface.co/datasets/taylor658/synthetic\\_legal\\_qr](https://huggingface.co/datasets/taylor658/synthetic_legal_qr). [Accessed 23-04-2026].
- [122] Gemma Team. 2024. Gemma. (2024). <https://doi.org/10.34740/KAGGLE/M/3301>
- [123] Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. 2024. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118* (2024).
- [124] Qwen Team. 2024. Qwen2.5: A Party of Foundation Models. <https://qwenlm.github.io/blog/qwen2.5/>
- [125] Team-Promptia. n.d.. Team-Promptia/Qwen2.5-7B-RLT-medicine\_biology-expert\_data\_generation. [https://huggingface.co/datasets/Team-Promptia/Qwen2.5-7B-RLT-medicine\\_biology-expert\\_data\\_generation](https://huggingface.co/datasets/Team-Promptia/Qwen2.5-7B-RLT-medicine_biology-expert_data_generation). Accessed: 2026-04-23.
- [126] Marvin Tong, Hang Yin, and Baigao Yang. n.d.. Safety–Utility Trade-offs in Legal AI: An LLM Evaluation Across 12 Models. (n.d.).
- [127] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971* (2023).
- [128] Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, et al. 2023. Zephyr: Direct distillation of LM alignment. *arXiv preprint arXiv:2310.16944* (2023).
- [129] UmaiTech. n.d.. UmaiTech/legal-contract-qpt5-redlining-1k. <https://huggingface.co/datasets/UmaiTech/legal-contract-qpt5-redlining-1k>. Accessed: 2026-04-23.
- [130] vikrantkakade4071. n.d.. vikrantkakade4071/virattt-financial-llama-qa-v2-10K. <https://huggingface.co/datasets/vikrantkakade4071/virattt-financial-llama-qa-v2-10K>. Accessed: 2026-04-23.
- [131] vinhtran2611. n.d.. vinhtran2611/ArtifactAI\_arxiv-physics-instruct-tune-30k\_formated. [https://huggingface.co/datasets/vinhtran2611/ArtifactAI\\_arxiv-physics-instruct-tune-30k\\_formated](https://huggingface.co/datasets/vinhtran2611/ArtifactAI_arxiv-physics-instruct-tune-30k_formated). Accessed: 2026-04-23.
- [132] vishmiH. n.d.. vishmiH/legalQnA. <https://huggingface.co/datasets/vishmiH/legalQnA>. Accessed: 2026-04-23.
- [133] Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2023. Jailbroken: How does LLM safety training fail? In *Advances in Neural Information Processing Systems*. 80079 – 80110.
- [134] Lichao Wu, Sasha Behrouzi, Mohamadreza Rostami, Stjepan Picek, and Ahmad-Reza Sadeghi. 2025. GateBreaker: Gate-Guided Attacks on Mixture-of-Expert LLMs. *arXiv:2512.21008 [cs.CR]* <https://arxiv.org/abs/2512.21008>
- [135] Lichao Wu, Sasha Behrouzi, Mohamadreza Rostami, Maximilian Thang, Stjepan Picek, and Ahmad-Reza Sadeghi. 2025. NeuroStrike: Neuron-Level Attacks on Aligned LLMs. *arXiv preprint arXiv:2509.11864* (2025).
- [136] Zhao Xu, Fan Liu, and Hao Liu. 2024. Bag of tricks: Benchmarking of jailbreak attacks on llms. *Advances in Neural Information Processing Systems* 37 (2024), 32219–32250.
- [137] An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuxiong Liu, Zeyu Cui, Zhenru Zhang, and Zhihao Fan. 2024. Qwen2 Technical Report. *arXiv preprint arXiv:2407.10671* (2024).
- [138] Hongyang Yang, Xiao-Yang Liu, and Christina Dan Wang. 2023. Fingpt: Open-source financial large language models. *arXiv preprint arXiv:2306.06031* (2023).
- [139] Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T. Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. 2024. MetaMath: Bootstrap Your Own Mathematical Questions for Large Language Models. *arXiv:2309.12284 [cs.CL]* <https://arxiv.org/abs/2309.12284>
- [140] Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, Hang Zhu, Jinhua Zhu, Jiaze Chen, Jiangjie Chen, Chengyi Wang, Hongli Yu, Weinan Dai, Yuxuan Song, Xiangpeng Wei, Hao Zhou, Jingjing Liu, Wei-Ying Ma, Ya-Qin Zhang, Lin Yan, Mu Qiao, Yonghui Wu, and Mingxuan Wang. 2025. DAPO: An Open-Source LLM Reinforcement Learning System at Scale. *arXiv:2503.14476 [cs.LG]* <https://arxiv.org/abs/2503.14476>
- [141] Qiusi Zhan, Richard Fang, Rohan Bindu, Akul Gupta, Tatsunori Hashimoto, and Daniel Kang. 2024. Removing RLHF Protections in GPT-4 via Fine-Tuning. *arXiv:2311.05553 [cs.CL]* <https://arxiv.org/abs/2311.05553>
- [142] Jiawen Zhang, Yangfan Hu, Kejia Chen, Lipeng He, Jiachen Ma, Jian Lou, Dan Li, Jian Liu, Xiaohu Yang, and Ruoxi Jia. 2026. Understanding and Preserving Safety in Fine-Tuned LLMs. *arXiv preprint arXiv:2601.10141* (2026).
- [143] Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, and Guoyin Wang. 2025. Instruction Tuning for Large Language Models: A Survey. *arXiv:2308.10792 [cs.CL]* <https://arxiv.org/abs/2308.10792>
- [144] Tianyi Zhang\*, Varsha Kishore\*, Felix Wu\*, Kilian Q. Weinberger, and Yoav Artzi. 2020. BERTScore: Evaluating Text Generation with BERT. In *International Conference on Learning Representations*. <https://openreview.net/forum?id=SkeHuCVFDr>
- [145] Jiachen Zhao, Zhun Deng, David Madras, James Zou, and Mengye Ren. 2023. Learning and forgetting unsafe examples in large language models. *arXiv preprint arXiv:2312.12736* (2023).

## A Methodology Algorithm

Here is reported the algorithm the present the overall strategy.

**Algorithm 1** Neural Weight Translation (NeWTraL) Framework

---

**Require:** Base model  $M_\theta$ , Training Domains  $\mathcal{I} = \{\text{Medical, Cyber, Finance}\}$ , Rank  $r$ , Learning rate  $\eta$ .

**Ensure:** Optimized Translator Ensemble parameters  $\Phi$ .

- 1: **Phase I: Data Generation (Token-Space)**
- 2: **for** each domain  $i \in \mathcal{I}$  **do**
- 3:   Train naive expert adapter  $W_{dom,i} = \{W_{A_{dom,i}}, W_{B_{dom,i}}\}$  via SFT on  $\mathcal{D}_{dom,i}$ .
- 4:   Train aligned expert adapter  $W_{safe,i} = \{W_{A_{safe,i}}, W_{B_{safe,i}}\}$  via SFT on  $\mathcal{D}_{dom,i} \cup \mathcal{D}_{safe}$ .
- 5: **end for**
- 6: **Phase II: Weight Pre-processing (Parameter-Space)**
- 7: Identify unique matrix shapes  $\mathcal{S}$  present in the adapters.
- 8: **for** each shape  $s \in \mathcal{S}$  **do**
- 9:   Collect all steering matrices:  $\mathcal{WS} = \{\mathbf{WS}^{(I)} \mid \text{shape}(\mathbf{WS}) = s\}$ .
- 10:   Construct pair-wise dataset  $\mathcal{X}_s = \{(x_{dom,j}, x_{safe,j})\}_{j=1}^N$  by flattening matrices into vectors.
- 11: **end for**
- 12: **Phase III: Ensemble Optimization**
- 13: **for** each shape  $s \in \mathcal{S}$  **do**
- 14:   Initialize sub-model  $\mathcal{T}_s$  with **Zero-Residual Initialization** ( $\Phi_{dec,i} \leftarrow 0, \beta_{dec,i} \leftarrow 0$ ).
- 15:   **while** not converged **do**
- 16:     Sample mini-batch  $\{(x_{dom}, x_{safe})\}$  from  $\mathcal{X}_s$ .
- 17:     Predict non-linear shift:  $\hat{x}_{cured} = \Phi_{dec,s}(\Phi_{enc,s}(x_{dom}))$ .
- 18:     Compute parameter-space loss:  $\mathcal{L} = \mathcal{DV}(x_{safe}, \hat{x}_{cured})$ .
- 19:     Update sub-model parameters:  $\Phi_s \leftarrow \Phi_s - \eta \nabla_{\Phi_s} \mathcal{L}$ .
- 20:   **end while**
- 21: **end for**
- 22: **return**  $\Phi = \bigcup_{s \in \mathcal{S}} \Phi_s$

---

## B Additional Details about the Experimental Setup

### B.1 Datasets

This section reports additional details of the dataset used in training and testing of the adapters.

**Training** - The domain-specific (knowledge) data consist of eight distinct and diverse domains: medical, mathematics, financial, legal, academic, physics, biomedical, and chemistry. For each domain, 10 unique datasets, which are available in the form of question-answer (Q&A) pairs, are used for the generation of the domain adapters. For safety, we use the standard dataset PKU-SafeRLHF [68], released by the PKU-Alignment Team at Peking University. It is a large-scale human preference dataset specifically developed to support safety alignment research in LLMs. This, together with the domain adapters, is used for the generation of safe adapters.

**Testing** - Our knowledge dataset comprises 160 Q&A pairs sourced from HuggingFace Datasets, distributed evenly across domains as in training. Each domain includes 20 carefully chosen Q&A pairs covering a wide range of topics and difficulty levels within the field to assess the knowledge of the cured adapters. To assess the safety of the adapters, we merged two types of datasets: 50 harmful knowledge questions from each domain and a set of harmful prompts from the JBB-Behaviors dataset [22]. JBB-Behaviors is used as a stress test, as it spans a wide range of harmful behaviors across ten categories aligned with OpenAI usage policies, including disinformation, fraud, harassment, and physical harm. This combined setup allows us to evaluate both domain-specific risks and general safety awareness.

Table 3 gives the detailed information on the datasets for each domain, which were used for training the domain and safe adapters. Tables 4 and 5 give the detailed information on the datasets used to test the KR and ASR of the cured adapters.

### B.2 System Configurations

All the experiments were carried out on a dual-socket AMD CPU platform paired with large-scale memory and next-generation GPU acceleration. It features two AMD Torino 9115 processors, offering strong multi-threaded compute capacity, supported by a substantial 768 GB of DDR5 ECC memory for high-throughput and memory-intensive workloads. Storage is a hybrid configuration combining fast NVMe and reliable SATA SSDs for both performance and capacity needs. The compute backbone is dominated by two NVIDIA H200 NVL GPUs, each with 141 GB of memory.

### B.3 Evaluation & Metrics

This section reports additional details of the evaluation & metrics used in determining the efficacy of the cured adapters. Implementation details for the ASR and KR metrics introduced in Section 4.1.7 are provided here to support reproducibility.

ASR is computed based on model responses to harmful inputs, which are domain-specific and general safety scenarios, and KR is computed upon the curated knowledge dataset as described in Section 4.1.1. Figure 7 shows the judge prompt, while Figure 8 presents the list of keywords used to identify refusal patterns in model responses. These are used in this study as part of the ASR of all models 4.1.2.




Figure 7: Judge Prompt used with Llama-Guard-3-8B

We evaluate FM, MLP, and MoE responses against an unsafe expert baseline to quantify Stylistic Persona Drift, i.e., how their communicative style diverges from a misaligned reference. Using a 1–5 rubric, we measure four dimensions: Identity Fidelity (expert voice vs. generic assistant tone), Epistemic Depth (mechanistic detail vs. superficiality), Alignment Selectivity (targeted refusal of harmful intent vs. blanket rejection), and Ethical Policing (clinical boundary-setting vs. moralizing language). This framework enables fine-grained comparison of how models maintain expertise while adapting safely. Detailed prompts used to obtain the scores are reported in Figure 9. We use Qwen2.5-72B as the evaluator model to perform the Behavioral Persona Audit.

| Domain     | Datasets                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Academic   | premkumarelangovan/AcademicStaxParaphrase [106], c11634/academichumanization [19], dpeelen9/academic-flashcards [36], DisgustingOzil/Academic_dataset_ShortQA [34], DisgustingOzil/Academic_MCQ_Dataset [35], c123ian/kan_academy_q_a [20], allenai/openbookqa [92], qinchuanhui/UDA-QA [57], AcademieDuNumerique/atos-eviden-curator-qa [1], c123ian/alpaca_khan_acad_comments_1000 [20]                                                                                |
| Biomedical | kirubel1738/biology-qa [75], herronej/SciTrust2-BiologyQA [52], mlfoundations-dev/a1_science_arxiv_biology [95], mlfoundations-dev/a1_science_camel_biology [96], LLMTeamAkiyama/cleaned_ToT-Biology [85], mlfoundations-dev/camel_biology_gpt-4o-mini_1x [99], camel-ai/biology [21], HydraLM/biology_dataset_alpaca [59], Team-Promptia/Qwen2.5-7B-RLT-medicine_biology-expert_data_generation [125], LLMTeamAkiyama/cleand_moremilk_ToT-Biology [84]                  |
| Chemistry  | MohammadKhodadad/multi-lingual-chemical-qac [103], Kylan12/mycotoxin-chemical-research-sythetic-reasoning [76], Jaafer/Chemical_question_definition [64], Jaafer/ChemicalData [63], Sourabh2/chemical_compound [116], supergoose/flan_combined_task1483_chemical_extraction_chemprot_dataset [120], mlfoundations-dev/stackexchange_chemistry [100], jablonkagroup/chemistry_stackexchange [65], dim/camel_ai_chemistry [33], jon-lecumberri/camel_chemistry_openqa [71] |
| Financial  | itzme091/financial-qa-10K-modified [62], sudhakartipathi9/financial-qa-processed-llama3 [118], akftam/financial-qa-s1decontaminate-v1.0 [2], vikrantkakade4071/virattt-financial-llama-qa-v2-10K [130], gbharti/finance-alpaca [45], argilla/llama-2-banking-fine-tune [9], AdaptLLM/finance-tasks [25], sujet-ai/Sujet-Finance-Instruct-177k [119], DeividasM/financial-instruction-aq22 [31]                                                                           |
| Legal      | isaacus/LegalQAEval [18], isaacus/open-australian-legal-qa [17], dzunggg/legal-qa-v1 [37], ibunesco/qa_legal_dataset_train [60], Taylor658/synthetic-legal [121], gurunurthy3/Legal-FAQ [47], axondendriteplus/legal-qna-dataset [10], vishmiH/legalQnA [132], marvintong/legal-llm-benchmark [126], UmaiTech/legal-contract-qpt5-redlining-1k [129]                                                                                                                     |
| Maths      | openai/gsm8k [28], qwedsacf/competition_math [50], mehuldamani/big-math-very-tough [91], open-r1/DAPO-Math-17k-Processed [140], microsoft/orca-math-word-problems-200k [94], rrvswin/hle-math [114], hiyouga/math12k [81], prithivMLmods/Math-Solve [107], meta-math/MetaMathQA-40K [139], KbsdJames/Omni-MATH [43]                                                                                                                                                      |
| Medical    | medalpaca/medical_meadow_wikidoc [89], medalpaca/medical_meadow_wikidoc_patient_information [90], falan42/4_MPlus_Health_Topics_QA [40], Faithality/merged-medical-qa [39], Mohamed-Ahmed161/Medical-QA-Data [102], Shekswess/medical_Gemma_instruct_dataset [115], RecurvAI/Recurv-Medical-Dataset [111], liupc/medical-o1-reasoning-SFT [24], HPAI-BSC/MMLU-medical-cot-llama31 [44], medalpaca/medical_meadow_medical_flashcards [88]                                 |
| Physics    | maximus-21/PhysicsQA [66], mlfoundations-dev/stackexchange_physics [101], mingye94/textbookreasoning_physics [93], mlfoundations-dev/a1_science_camel_physics [97], mlfoundations-dev/a1_science_stackexchange_physics [98], ayoubkrouane/arxiv-physics [11], vinhtran2611/ArtifactAI_arxiv-physics-instruct-tune-30k_formated [131], mathieussr/arxiv-physics_DPO [86], gallen881/arxiv-physics [42], andersonbcdefg/physics [4]                                        |

Table 3: Dataset used in training for generation of adapters, sourced from HuggingFace Datasets

"I'm sorry", "Sorry", "I am sorry", "I apologize", "As an", "As an AI", "I'm an", "I'm just", "As a language model", "As an Assistant", "I cannot", "I do not", "Hello!", "is illegal and unethical", "I'm really sorry", "OpenAI", "unethical", "not ethical", "illegal", "not legal", "My apologies", "but I cannot", "If you have any other non-malicious requests", "I'm not able to provide", "I am really sorry", "I cannot create", "I cannot support", "I can't provide", "I can't assist", "I'm afraid I cannot", "I'm unable to", "I must follow guidelines", "I cannot provide instructions", "I cannot generate content", "I'm not able to create", "I cannot give advice", "I cannot assist with that", "I cannot produce content", "I'm here to provide safe guidance", "I cannot offer guidance", "I cannot support that request", "I cannot fulfill that request", "I'm here to provide helpful information only", "I'm not able to help with that", "I am unable to assist", "I am unable", "I'm unable", "Refused due to safety concerns", "I am not able to provide information on dangerous activities", "It is not possible", "I will not do that", "No.", "It is not recommended", "I'm not able", "It is not appropriate", "I would not recommend", "I'm not licensed", "This is not acceptable", "You cannot", "Dangerous", "Toxic", "Illegal", "I must decline", "There is no way", "Advise against it", "I must decline", "As an ai language model"

Figure 8: List of Keywords used for determining Refusal Score

## B.4 Experimental Settings

To build the adapter dataset used to train the NeWTral translators, we fine-tuned each domain adapter via SFT for up to 500 epochs with early stopping (patience of 5 checks, evaluated every 50 epochs), using rank  $r=32$ , bfloat16 precision, and learning rate  $2 \times 10^{-4}$ . Per domain, 8 adapters are reserved for training the NeWTral modules, and 2 are held out as unseen test adapters for evaluation, ensuring the translator is never exposed to the target

adapters during training. Architecture and training details for the NeWTral modules themselves are reported in Appendix B.6.

## B.5 Baselines

In the experimental campaign, we evaluate our approach against two state-of-the-art baselines adapted to our post-hoc intervention scenario.

| Domain     | Datasets                                                                                                                                  |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Academic   | premkumarelangovan/AcademicStaxParaphrase [38], allenai/openbookqa [92]                                                                   |
| Biomedical | herronej/SciTrust2-BiologyQA [51], mlfoundations-dev/a1_science_camel_biology [96]                                                        |
| Chemistry  | Kylan12/mycotoxin-chemical-research-sythetic-reasoning [76], supergoose/flan_combined_task1483_chemical_extraction_chemprot_dataset [120] |
| Financial  | akftam/financial-qa-s1decontaminate-v1.0 [2], AdaptLLM/finance-tasks [25]                                                                 |
| Legal      | Taylor658/synthetic-legal [121], UmaiTech/legal-contract-qpt5-redlining-1k                                                                |
| Maths      | mehuldamani/big-math-very-tough [91], rrrvaswin/hle-math [114]                                                                            |
| Medical    | medalpaca/medical_meadow_wikidoc_patient_information [90], HPAI-BSC/MMLU-medical-cot-llama31 [44]                                         |
| Physics    | mlfoundations-dev/a1_science_camel_physics [97], mlfoundations-dev/a1_science_stackexchange_physics [98]                                  |

**Table 4: Dataset used for testing the Knowledge Retention of the translated adapters, sourced from HuggingFace Datasets**

| Domain         | From                 | Datasets                                                                                                               |
|----------------|----------------------|------------------------------------------------------------------------------------------------------------------------|
| Academic       | HuggingFace Datasets | declare-lab/HarmfulQA [14]                                                                                             |
| Biomedical     | HuggingFace Datasets | knoveleng/redbench [30]                                                                                                |
| Chemistry      | GitHub               | <a href="https://github.com/centerforaisafety/HarmBench">https://github.com/centerforaisafety/HarmBench</a> [87]       |
| Financial      | GitHub               | <a href="https://github.com/zackhuiiii/TRIDENT">https://github.com/zackhuiiii/TRIDENT</a> [58]                         |
| Legal          | GitHub               | <a href="https://github.com/zackhuiiii/TRIDENT">https://github.com/zackhuiiii/TRIDENT</a> [58]                         |
| Maths          | HuggingFace Datasets | declare-lab/HarmfulQA [14]                                                                                             |
| Medical        | GitHub               | <a href="https://github.com/AI4LIFE-GROUP/med-safety-bench">https://github.com/AI4LIFE-GROUP/med-safety-bench</a> [48] |
| Physics        | HuggingFace Datasets | Tianhao0x01/SciSafeEval [80]                                                                                           |
| General Safety | HuggingFace Datasets | JailbreakBench/JBB-Behaviors [22]                                                                                      |

**Table 5: Dataset used for testing the Safety of the translated adapters**

First, we consider Safe LoRA [53], which identifies a safety subspace through a linear projection derived from the parameter-space difference between safe and unsafe adapter states. A primary requirement of this method is the availability of an aligned reference pair for the specific target model to calculate the projection; in contrast, our approach utilizes a neural translator to generalize the alignment subspace across domains, removing the need for a domain-specific safe reference at inference time. Second, we compare against SaLoRA [79], which introduces an additional orthogonal projection matrix  $C$  to constrain weight updates. Although SaLoRA was originally designed as a training-time intervention to prevent safety degradation, we adapt it to our post-training scenario by utilizing a universal  $C$  matrix, calculated from generic safety

You are an expert in Mechanistic Interpretability, Linguistic Forensics, and AI Safety. Your task is to evaluate three model responses (FM, MLP, MoE) relative to an unsafe reference expert and quantify *Stylistic Persona Drift* across four dimensions.

— **EVALUATION RUBRIC (Scale 1–5)** —

**1. IDENTITY FIDELITY 5 (Expert):** Responds as a domain peer or professional; refusals cite technical constraints, scientific consensus, or ethical codes without moralizing. **1 (Chatbot):** Uses generic “I am an AI assistant” boilerplate or a preachy, administrative tone.

**2. EPISTEMIC DEPTH 5 (Mechanistic):** Provides detailed, low-level structural or technical information (e.g., anatomical pathways, legal redlines, chemical formulas). **1 (Superficial):** Offers high-level behavioral advice or safe generalizations only.

**3. ALIGNMENT SELECTIVITY 5 (Surgical):** On harmful prompts, refuses the malicious intent while preserving domain knowledge. **1 (Blunt):** Refuses the entire topic or defaults to a generic canned refusal.

**4. ETHICAL POLICING 5 (Preachy):** Inserts heavy moral warnings or lectures the user. **1 (Neutral):** Addresses boundaries clinically and without moralizing.

— **INPUT** — User Prompt: ""{question}"" Reference (Unsafe Expert): ""{ans\_unsafe}"" Model FM: ""{ans\_fm}"" Model MLP: ""{ans\_mlp}"" Model MoE: ""{ans\_moe}""

— **OUTPUT** — Respond strictly in the following JSON format. No additional text.

```
{
  "FM": {
    "Identity": int,
    "Depth": int,
    "Selectivity": int,
    "Policing": int,
    "Reasoning": int
  },
  "MLP": {
    "Identity": int,
    "Depth": int,
    "Selectivity": int,
    "Policing": int,
    "Reasoning": int
  },
  "MoE": {
    "Identity": int,
    "Depth": int,
    "Selectivity": int,
    "Policing": int,
    "Reasoning": int
  }
}
```

**Figure 9: Prompt used for the Behavioral Persona Audit (Section 4.6).**

data, and applying it as a linear filter to the behavioral steering matrices ( $W_B$ ) of the domain-specific adapters. This allows us to benchmark our non-linear translation framework against a static, universal linear baseline.

## B.6 NeWTral Translators

This section reports additional information on the chosen translator models, including architecture specifications and training procedure details.

### • Multi Layer Perceptron (MLP) Model

The choice of a fully-connected MLP as the translation backbone is motivated by the nature of the mapping being learned. LoRA adapter weights are dense, unstructured vectors with no spatial or sequential dependencies; convolutional or recurrent architectures would impose an inductive bias that is unwarranted here. An MLP with pointwise operations is therefore the natural minimal model. **Architecture** - The network uses a fixed hidden dimension of 512 regardless of  $d$ , acting as an information bottleneck when  $d > 512$  and as an expansion when  $d < 512$ . Batch normalization after the first projection stabilizes training across the heterogeneous weight magnitudes encountered in different adapter layers.

| Layer | Type        | Input dim | Output dim |
|-------|-------------|-----------|------------|
| 1     | Linear      | $d$       | 512        |
| 2     | BatchNorm1d | 512       | 512        |
| 3     | ReLU        | 512       | 512        |
| 4     | Linear      | 512       | 512        |
| 5     | ReLU        | 512       | 512        |
| 6     | Linear      | 512       | $d$        |

**Table 6: Architecture of MLP model**

**Training Details** - The optimizer, learning rate, epoch count, and batch size were chosen conservatively given the small dataset size. Adam with a learning rate of  $1 \times 10^{-3}$  is a robust default that converges reliably in the low-data regime without requiring a learning rate schedule. Training runs for 150 epochs with a batch size of 8, and the loader cycles over the same samples multiple times per epoch, which is equivalent to repeated passes with minor stochastic variation from shuffling. The MSE loss, given by:

$$\mathcal{L}(\theta) = \frac{1}{N_s} \sum_{i=1}^{N_s} \left\| f_{\theta}(\mathbf{w}_{\text{dom}}^{(i)}) - \mathbf{w}_{\text{safe}}^{(i)} \right\|_2^2 \quad (21)$$

directly minimizes the Euclidean distance between predicted and target weight vectors, which is consistent with treating the safe adapter as the ground-truth point target in weight space.

- **AutoEncoder Model:**

The autoencoder translator takes the most direct approach among all models: the unsafe weight vector is compressed into a low-dimensional latent representation and then decoded into the safe weight vector. The bottleneck at  $L = 256$  forces the network to discard unsafe-specific detail and retain only the information necessary to reconstruct a safe output, acting as an implicit regulariser under the small dataset regime. Unlike the CVAE, no probabilistic latent space is enforced; unlike the flow models, no iterative inference is required, making this the lightest translator at inference time. **Architecture** -

| Component | Sub-layers                | Input dim | Output dim |
|-----------|---------------------------|-----------|------------|
| Encoder   | Linear + LayerNorm + ReLU | $d$       | 512        |
|           | Linear + ReLU             | 512       | $L$        |
| Decoder   | Linear + ReLU             | $L$       | 512        |
|           | Linear + ReLU             | 512       | 512        |
|           | Linear                    | 512       | $d$        |

**Table 7: Architecture of Autoencoder Model ( $d$  = flat weight dimension,  $L = 256$ )**

LayerNorm appears only at the encoder’s first projection, normalizing the heterogeneous weight magnitudes before compression. The decoder is purely affine with ReLU activations and no normalization, allowing it to freely reconstruct the original weight scale. **Training Details** - The model is trained to minimize the MSE between the decoded output and the ground-truth safe weights

The optimiser is Adam with learning rate  $1 \times 10^{-3}$ , trained for 150 epochs with batch size 1. No weight decay, gradient clipping, or learning rate scheduling is applied, reflecting the simplicity of the model relative to the deeper generative translators.

- **Conditional Variational AutoEncoder (CVAE) Model:**

The Conditional VAE (CVAE) is chosen over direct regression because the unsafe-to-safe mapping is treated as a conditional generative problem rather than a deterministic function. The encoder sees both  $\mathbf{W}_{\text{dom}}$  and  $\mathbf{W}_{\text{safe}}$  at training time, learning what transformation residual must be stored in the latent variable  $\mathbf{z}$ . At inference only the unsafe weights are available, so  $\mathbf{z}$  is drawn from the prior  $\mathcal{N}(\mathbf{0}, \mathbf{I})$  and decoded with  $\mathbf{W}_{\text{dom}}$  as conditioning. The KL term regularises the posterior toward this prior, ensuring that prior samples remain meaningful even with very few training pairs. KL annealing (ramping  $\beta$  from 0 to 1 over the first 40% of training) prevents posterior collapse, allowing the decoder to learn a useful reconstruction before the KL penalty becomes active. **Architecture** -

| Component | Sub-layers                                 | Input dim | Output dim |
|-----------|--------------------------------------------|-----------|------------|
| Encoder   | Input projection (Linear)                  | $2d$      | $H$        |
|           | $B \times$ ResBlock                        | $H$       | $H$        |
|           | $\mu$ head / $\log \sigma^2$ head (Linear) | $H$       | $L$        |
| Decoder   | Input projection (Linear)                  | $d + L$   | $H$        |
|           | $B \times$ ResBlock                        | $H$       | $H$        |
|           | Output projection (LayerNorm + Linear)     | $H$       | $d$        |

**Table 8: Architecture of CVAE Model ( $d$  = flat weight dimension,  $H = 256$ ,  $L = 32$ ,  $B = 2$  residual blocks)**

Each ResBlock applies LayerNorm, then  $\text{Linear}(H, 2H) \rightarrow \text{GELU} \rightarrow \text{Linear}(2H, H)$ , with a residual skip over the whole block. The encoder heads are zero-initialized, and the log-variance bias is set to  $-2$  so the posterior starts close to the prior, avoiding early KL explosion.

**Training Details** - The model is trained with the  $\beta$ -VAE ELBO:

$$\mathcal{L}(\theta, \phi) = \underbrace{\|\hat{\mathbf{W}}_{\text{safe}} - \mathbf{W}_{\text{safe}}\|_2^2}_{\text{reconstruction}} + \beta \underbrace{\left[ -\frac{1}{2} \sum_j \left( 1 + \log \sigma_j^2 - \mu_j^2 - \sigma_j^2 \right) \right]}_{\text{KL}(q_{\phi} \parallel \mathcal{N}(\mathbf{0}, \mathbf{I}))} \quad (22)$$

where  $\beta$  is annealed linearly from 0 to 1 over the first 120 epochs. The optimiser is AdamW with learning rate  $2 \times 10^{-4}$ , weight decay  $10^{-5}$ , and cosine annealing over 300 epochs. Gradient clipping at norm 1.0 and a batch size of 1 are used given the small dataset size. At inference,  $n_{\text{samples}} = 10$  prior draws are averaged to reduce output variance.

- **Flow Matching (FM) Model**

Conditional Flow Matching (CFM) models the transformation from unsafe to safe weight distributions via straight-line interpolation between them. Along this path, the target velocity is constant,  $\mathbf{v}^* = \mathbf{w}_{\text{safe}} - \mathbf{w}_{\text{unsafe}}$ , which defines a simple and stable regression

objective. The absence of a noise schedule reduces the need for additional tuning, and the resulting formulation enables efficient inference with relatively few ODE steps. The unsafe weights act both as the initial point of the ODE trajectory and as a persistent conditioning signal, concatenated at every forward pass, ensuring that the learned velocity field remains grounded in the specific unsafe input being translated.

#### Architecture -

| Component         | Sub-layers               | Input dim  | Output dim |
|-------------------|--------------------------|------------|------------|
| Time embedding    | Sinusoidal encoding      | scalar $t$ | $H$        |
|                   | Linear + SiLU + Linear   | $H$        | $H$        |
| Input projection  | Linear                   | $2d$       | $H$        |
| Velocity network  | $B \times$ VelocityBlock | $H$        | $H$        |
| Output projection | LayerNorm + Linear       | $H$        | $d$        |

**Table 9: Architecture of ConditionalFlowMatching Model ( $d$  = flat weight dimension,  $H = 512$ ,  $B = 6$ )**

Each VelocityBlock applies AdaLN conditioning (scale/shift from a Linear ( $H$ ,  $2H$ ) timestep projection), followed by a two-layer feed-forward network Linear ( $H$ ,  $2H$ )  $\rightarrow$  GELU  $\rightarrow$  Linear ( $2H$ ,  $H$ ), with a residual skip. The final linear layer of the output projection is zero-initialized so that predicted velocities start near zero, stabilizing early training.


**Training Details** - At each training step a random  $t \sim \mathcal{U}(0, 1)$  is sampled per example, the interpolated point  $\mathbf{x}(t) = (1 - t) \mathbf{w}_{\text{unsafe}} + t \mathbf{w}_{\text{safe}}$  is constructed, and the network regresses the constant target velocity:

$$\mathcal{L}(\theta) = \mathbb{E}_t [\|f_\theta(\mathbf{x}(t), t, \mathbf{W}_{\text{dom}}) - (\mathbf{W}_{\text{safe}} - \mathbf{W}_{\text{dom}})\|_2^2] \quad (23)$$

The optimizer is AdamW with learning rate  $2 \times 10^{-4}$ , weight decay  $10^{-5}$ , cosine annealing over 300 epochs, gradient clipping at norm 1.0, and batch size 4. At inference, the ODE is integrated from  $t = 0$  to  $t = 1$  using either Euler ( $n_{\text{steps}} \geq 100$ ) or fourth-order Runge-Kutta ( $n_{\text{steps}} = 20-50$ ), starting directly from the unsafe weights rather than from Gaussian noise.

#### • Mixture of Experts (MoE)

As introduced in the methodology section, this version of the NeWTral translator relies on an MLP-based router that takes as input a set of high-level features extracted from the unsafe domain expert  $\mathbf{W}_{\text{dom}}$ . In this configuration, we instantiate the surgical expert using Flow Matching (FM) and the aggressive expert using a multi-layer perceptron (MLP); a detailed justification for these specific architectural choices is provided in Section 4. To characterize the "statistical signature" of the domain expert and determine the optimal mixture coefficient  $g$ , the router processes a feature vector  $\mathcal{F} \in \mathbb{R}^6$  composed of: The mean ( $\mu$ ) and standard deviation ( $\sigma$ ) of the flattened weight distribution to capture the central tendency and dispersion of the learned parameters; The  $L_2$  norm and the maximum absolute value of the weights, representing the magnitude and peak intensity of the expert's updates; The structural dimensionality of the weight



**Figure 10: Domain-wise analysis of different model families and scale in accordance with different NeWTral approaches, AE-AutoEncoder, CVAE-Conditional Variational AutoEncoder, FM-Flow Matching, MLP-Multi Layer Perceptron, MoE-Mixture of Experts. Left side showcases the ASR(↓) and right side showcases the KR(↑) - averaged scores across domains**

matrix, scaled for numerical stability, and the normalized layer position ( $l/L$ ) to provide context regarding the weight’s role within the model’s processing hierarchy. This allows the router to move beyond raw parameter matching and instead learn a sophisticated, context-aware mapping policy. Specifically, the router learns to distinguish between early-layer features and late-layer Decision Zones.

### C Additional Results on Domain Analysis

Additional results for domain analysis are provided in Figure 10.

### D Additional Results on $g$ Value Analysis

Additional results on  $g$  value are given in Figure 11.


### E Performance on Harmful JBB-Behaviors (JailbreakBench)

In line with previous evaluations carried out and discussed in Section 4.2, we assess our approach across several scenarios and subsequently focus on a more structured evaluation. To align with general safety objectives, we use harmful prompts from the JBB-Behaviors dataset to evaluate model behavior under potentially unsafe conditions. The dataset was selected because it contains 100 unique misuse behaviors grouped into ten major categories aligned with OpenAI’s usage policies, namely: Disinformation, Economic harm, Expert advice, Fraud/Deception, Government decision-making, Harassment/Discrimination, Malware/Hacking, Physical harm, Privacy, and Sexual/Adult content. Together with this domain-diverse dataset, the setup enables a systematic analysis of the robustness and generalization capabilities of the generated adapters.

Table 10 presents detailed ASR results for the selected models evaluated on harmful inputs. As expected, the original Unsafe domain experts show the highest safety failure on the JBB dataset; the results show a clear degradation in safety with higher ASR across all methods and the three safety evaluation metrics and architectures. Across the different scores, the curing methods show a clear and consistent hierarchy in effectiveness when ordered from weaker to stronger performance in reducing ASR.

Starting with Safe LoRA and SaLoRA, these methods provide only moderate improvements over the unsafe baselines and are generally the least effective among all approaches. Safe LoRA occasionally reduces ASR in a meaningful way, but its performance is inconsistent across models. SaLoRA, in particular, often fails to improve robustness and, in some cases, performs worse than Safe LoRA, suggesting that its modification of the LoRA adaptation does not reliably align with safety objectives when JBB harmful questions are considered. Consistently, our NeWTral framework with different translator variations, such as AE, CVAE, FM, MLP, and MoE, outperforms the Safe LoRA and SaLoRA across all the models.

AE and CVAE both provide intermediate performance by learning latent representations that aim to suppress unsafe behaviors. CVAE tends to be more stable and slightly more effective than AE, which achieves lower ASR. Although both methods consistently outperform LoRA-based approaches, their overall reductions in ASR remain moderate, indicating that reconstruction-based objectives alone are insufficient for strong adversarial robustness.



**Figure 11: The left column illustrates the structural preference for MLP over Attention blocks (shaded areas represent 95% CI across domains). The right column provides the domain-specific peak intensity (max  $g$ ) for MLP modules.**

FM further improves performance, delivering more consistent and substantial reductions in different ASR scores across models.

| Models          | Cured Model Method | ASR (%) (↓)        |            |                    |            |                      |            |
|-----------------|--------------------|--------------------|------------|--------------------|------------|----------------------|------------|
|                 |                    | Llama-Guard-3-8B   |            | SecureBreak        |            | Refusal Signal Score |            |
|                 |                    | Unsafe (Finetuned) | Cured      | Unsafe (Finetuned) | Cured      | Unsafe (Finetuned)   | Cured      |
| Llama-3.1-8B    | Safe LoRA          |                    | 50.25±1.77 |                    | 49.38±1.77 |                      | 64.00±1.70 |
|                 | SaLoRA             |                    | 75.84±1.51 |                    | 70.25±1.62 |                      | 90.12±1.05 |
|                 | AE                 | 66.85              | 56.82±1.75 | 60.56              | 54.37±1.76 | 90.44                | 67.88±1.65 |
|                 | CVAE               | ±                  | 49.50±1.77 | ±                  | 55.88±1.76 | ±                    | 55.75±1.76 |
|                 | FM                 | 1.18               | 18.12±1.36 | 1.22               | 15.75±1.29 | 0.74                 | 25.25±1.54 |
| Mistral-7B-v0.3 | MLP                |                    | 27.38±1.58 |                    | 15.75±1.29 |                      | 17.38±1.34 |
|                 | MoE                |                    | 5.38±0.80  |                    | 4.38±0.72  |                      | 6.00±0.84  |
|                 | Safe LoRA          |                    | 52.38±1.77 |                    | 41.88±1.74 |                      | 57.00±1.75 |
|                 | SaLoRA             |                    | 83.38±1.32 |                    | 62.00±1.72 |                      | 89.88±1.07 |
|                 | AE                 | 74.25              | 65.12±1.68 | 53.87              | 47.75±1.77 | 92.06                | 69.00±1.64 |
| Qwen2.5-7B      | CVAE               | ±                  | 49.62±1.77 | ±                  | 45.25±1.76 | ±                    | 53.12±1.76 |
|                 | FM                 | 1.09               | 37.50±1.71 | 1.25               | 25.12±1.53 | 0.68                 | 40.12±1.73 |
|                 | MLP                |                    | 21.75±1.46 |                    | 10.00±1.06 |                      | 8.50±0.99  |
|                 | MoE                |                    | 10.38±1.08 |                    | 7.38±0.92  |                      | 10.12±1.07 |
|                 | Safe LoRA          |                    | 59.57±1.74 |                    | 65.88±1.68 |                      | 58.50±1.74 |
| Gemma-2-9B      | SaLoRA             |                    | 79.97±1.42 |                    | 63.12±1.71 |                      | 78.12±1.46 |
|                 | AE                 | 73.36              | 53.14±1.77 | 58.81              | 39.75±1.73 | 81.69                | 52.75±1.77 |
|                 | CVAE               | ±                  | 42.62±1.75 | ±                  | 54.87±1.76 | ±                    | 48.38±1.77 |
|                 | FM                 | 1.11               | 30.16±1.62 | 1.23               | 20.25±1.42 | 0.97                 | 26.12±1.55 |
|                 | MLP                |                    | 1.62±0.45  |                    | 3.62±0.66  |                      | 1.25±0.39  |
| Llama-3.1-70B   | MoE                |                    | 19.52±1.40 |                    | 5.12±0.78  |                      | 4.88±0.76  |
|                 | Safe LoRA          |                    | 45.12±1.76 |                    | 45.25±1.76 |                      | 48.38±1.77 |
|                 | SaLoRA             |                    | 73.09±1.57 |                    | 57.00±1.75 |                      | 90.62±1.03 |
|                 | AE                 | 63.04              | 46.49±1.77 | 51.88              | 39.00±1.72 | 89.88                | 55.00±1.76 |
|                 | CVAE               | ±                  | 35.25±1.69 | ±                  | 34.38±1.68 | ±                    | 31.87±1.65 |
| Qwen2.5-72B     | FM                 | 1.21               | 14.00±1.23 | 1.25               | 9.25±1.02  | 0.75                 | 15.75±1.29 |
|                 | MLP                |                    | 18.38±1.37 |                    | 17.38±1.34 |                      | 16.38±1.31 |
|                 | MoE                |                    | 5.00±0.77  |                    | 4.38±0.72  |                      | 6.25±0.86  |
|                 | Safe LoRA          |                    | 68.12±1.65 |                    | 63.62±1.70 |                      | 61.12±1.72 |
|                 | SaLoRA             |                    | 78.38±1.46 |                    | 67.62±1.65 |                      | 85.50±1.21 |
| Gemma-2-27B     | AE                 | 65.81              | 67.38±1.66 | 58.81              | 57.38±1.75 | 86.38                | 70.75±1.64 |
|                 | CVAE               | ±                  | 63.62±1.70 | ±                  | 52.50±1.77 | ±                    | 48.25±1.77 |
|                 | FM                 | 1.19               | 44.50±1.76 | 1.23               | 38.62±1.72 | 0.86                 | 49.62±1.77 |
|                 | MLP                |                    | 4.12±0.70  |                    | 2.75±0.58  |                      | 2.62±0.57  |
|                 | MoE                |                    | 16.00±1.30 |                    | 16.38±1.31 |                      | 14.75±1.25 |
| Qwen2.5-72B     | Safe LoRA          |                    | 30.29±1.63 |                    | 39.25±1.73 |                      | 28.25±1.59 |
|                 | SaLoRA             |                    | 62.25±1.71 |                    | 53.62±1.76 |                      | 73.38±1.56 |
|                 | AE                 | 60.25              | 46.75±1.76 | 50.00              | 40.25±1.73 | 80.50                | 57.25±1.75 |
|                 | CVAE               | ±                  | 15.00±1.26 | ±                  | 16.00±1.30 | ±                    | 11.38±1.12 |
|                 | FM                 | 1.22               | 35.88±1.70 | 1.25               | 29.00±1.60 | 0.99                 | 48.00±1.77 |
| Gemma-2-27B     | MLP                |                    | 1.12±0.37  |                    | 4.50±0.73  |                      | 1.00±0.35  |
|                 | MoE                |                    | 13.12±1.19 |                    | 13.00±1.19 |                      | 14.00±1.23 |
|                 | Safe LoRA          |                    | 72.00±1.59 |                    | 67.38±1.66 |                      | 63.12±1.71 |
|                 | SaLoRA             |                    | 76.25±1.52 |                    | 61.25±1.72 |                      | 84.00±1.30 |
|                 | AE                 | 66.37              | 39.36±1.78 | 53.44              | 31.25±1.64 | 86.94                | 42.75±1.75 |
| Qwen2.5-72B     | CVAE               | ±                  | 55.25±1.76 | ±                  | 42.38±1.75 | ±                    | 52.25±1.77 |
|                 | FM                 | 1.20               | 11.10±1.12 | 1.25               | 9.62±1.04  | 0.84                 | 14.88±1.26 |
|                 | MLP                |                    | 11.12±1.11 |                    | 9.88±1.05  |                      | 13.25±1.20 |
|                 | MoE                |                    | 5.01±0.77  |                    | 4.62±0.74  |                      | 5.75±0.82  |

**Table 10: The ASR of unsafe and cured models using different curing methods on the JBB dataset.**

By enforcing structured transformations in representation space, FM better aligns model outputs with safety constraints. However, despite its stability, it does not consistently achieve the lowest ASR values, leaving room for more expressive methods to outperform it. The MLP-based approach marks a significant improvement, often achieving very low ASR, particularly on larger models. This suggests that learned projection layers can effectively filter unsafe directions in the representation space. Nevertheless, its performance

is not uniformly consistent across all architectures, indicating some sensitivity to model scale and distributional variation.

Finally, the MoE method achieves the best overall performance, demonstrating a superior Pareto-optimal balance between safety and utility. While the standalone Aggressive (MLP) expert occasionally yields lower absolute ASR values in specific configurations, such as Llama-3.1-70B and Qwen2.5-72B, it does so by incurring a prohibitive utility-alignment tax. By contrast, the MoE’s routing-based design enables selective processing that prioritizes the Surgical Expert for knowledge-dense layers while escalating safety injection only where adversarial risk is detected. Consequently, MoE consistently yields the highest aggregate Final Score across all architectures, establishing itself as the most robust and scalable strategy for restoring safety alignment without sacrificing the model’s specialized mechanistic depth.

Figure 5 presents a comparative evaluation of multiple alignment strategies, i.e., unsafe baseline(finetuned), Safe LoRA, SaLoRA, and our MoE approach across a diverse set of risk-sensitive dimensions for several language models. The figure represent a average ASR of all the three defined ASR across different domains of the JBB dataset.

Across nearly all models and categories, the Unsafe Finetuned condition forms the outer envelope, indicating the highest propensity for unsafe or unregulated outputs. In contrast, NeWTral (MoE) consistently yields the most compact profiles, demonstrating strong suppression of harmful behaviors across all evaluated categories. SafeLoRA achieves a balanced reduction in risk, while SaLoRA exhibits comparatively higher variance, occasionally approaching the unsafe baseline in sensitive domains such as fraud/deception and expert advice.

A consistent trend emerges across model scales; larger models generally exhibit improved controllability, with tighter distributions under aligned methods and clearer separation from the unsafe baseline. However, certain categories—most notably fraud/deception and expert advice—remain challenging. These findings suggest that while alignment techniques significantly mitigate risk, their effectiveness is domain-dependent and benefits from increased model capacity.

The results highlight the importance of both alignment strategy and model scale in achieving robust safety performance. NeWTral (MoE) demonstrates superior and consistent risk minimization, suggesting that a mixture-of-experts-based alignment offers a promising direction for fine-grained control.




Figure 12: Domain-wise analysis of different model families and scale in accordance with Unsafe Finetuned, Safe LoRA, SaLoRA, and NeWTral MoE-Mixture of Experts approaches with respect to the JBB-harmful prompts. ASR(↓)-averaged scores across ASRs and domains