

Nullify: Null-Space Activation Steering for Training-Free LLM Unlearning

Wei Zhai^{1,6*} Xiang Liu^{2*} Qiang Huang¹ Rui Qian¹ Lemao Liu¹
Ziwei Li³ Ziqi Wang⁴ Zhitao Huang⁵ Dejing Dou^{1,6†}

¹College of Computer Science and Artificial Intelligence, Fudan University

²School of Electrical and Information Engineering, Tianjin University

³King Abdullah University of Science and Technology (KAUST), Saudi Arabia

⁴School of Software Technology, Zhejiang University

⁵School of Transnational Law, Peking University ⁶BEDI Cloud

Abstract

Large Language Models (LLMs) inevitably internalize substantial amounts of sensitive or private information during pre-training, while LLM unlearning aims to selectively erase specific knowledge to prevent privacy leakage with minimal loss of model utility. However, existing methods struggle to balance forget quality with utility, and typically incur substantial computational costs due to parameter fine-tuning. To address this, we propose **Nullify**, a training-free, non-destructive activation steering method for LLM unlearning. Nullify employs steering vectors during inference to redirect privacy-related activations away from their memorized answers, while satisfying a null-space constraint that leaves retained-query activations essentially unaffected to maintain utility. Evaluations on TOFU and MUSE show that Nullify matches or surpasses established baselines in forget quality while achieving **near-lossless** preservation of model utility. By avoiding weight updates entirely, Nullify serves as an efficient, plug-and-play inference-time intervention framework.

1 Introduction

The pre-training of Large Language Models (LLMs) on massive web corpora inevitably leads to the implicit memorization of sensitive, copyrighted, or harmful data (Carlini et al., 2021). Legal frameworks such as the GDPR recognize a right to erasure under certain conditions (Bourtoule et al., 2021), while emerging AI regulations such as the EU AI Act increase compliance pressure

around data governance and model lifecycle management (European Parliament and Council of the European Union, 2024). Because retraining a foundation model from scratch for every such request is economically infeasible, LLM unlearning—the targeted, efficient elimination of specific memorized knowledge—has become a cornerstone of trustworthy AI (Yao et al., 2024).

Yet the dominant unlearning paradigm is fundamentally *destructive*. Gradient-based methods (GA (Jang et al., 2023), GradDiff (Liu et al., 2022)) and preference-optimization methods (NPO (Zhang et al., 2024), SimNPO (Fan et al., 2025)) all unlearn by backpropagating into and reshaping the model’s weights. Because the knowledge to forget and the capabilities to retain are encoded in the *same* shared parameters, every update that suppresses a target memory unavoidably perturbs the retained representations: forgetting and utility become locked in direct opposition, tradable only at the cost of capability degradation, over-refusal, and hallucination (Fan et al., 2025). Representation-level methods (RMU (Li et al., 2024), LUNAR (Shen et al., 2025)) soften but do not escape this: they either still update the base model’s weights or train auxiliary parameters, and their retention behavior is enforced by a soft loss term rather than guaranteed by construction. As Table 1 summarizes, no prior method simultaneously avoids weight modification, eliminates optimization, and provides a principled utility-preservation guarantee.


Our key observation is that this opposition is *not* intrinsic to unlearning—it is an artifact of operating in parameter space. If the intervention is instead applied in the *activation space* and *geometrically constrained* to a subspace orthogonal to

*Equal contribution.

†Corresponding author: dejingdou@gmail.com

Method	TF	NWM	GC	HFQ	UP
GradDiff	✗	✗	✗	✗	✗
SimNPO	✗	✗	✗	✓	✗
LUNAR	✗	✓	✗	✗	✗
Nullify	✓	✓	✓	✓	✓

Table 1: Attribute comparison of representative LLM unlearning methods. TF: Training-Free (no backpropagation); NWM: No (base) Weight Modification; GC: Geometric Constraint isolating retained knowledge; HFQ: High Forget Quality; UP: Utility Preservation.



(a) Forget quality vs. model utility. (b) Forget quality vs. wall-clock cost.

Figure 1: Pareto view of LLM unlearning on TOFU forget10 (Llama-2-7B-chat-hf). Nullify (orange star) dominates all baselines, achieving the highest forget quality at the highest model utility (a) and the lowest wall-clock cost (b); the red arrow marks the preferred direction. Wall-clock in (b) refers to the cost benchmark of Table 6.

the retained-knowledge representations, suppressing a target memory and preserving utility cease to compete: the former is delivered by the intervention, the latter holds because the intervention, by construction, has no effect on retained queries. Building on this insight, we propose **Nullify**, a training-free unlearning framework with a closed-form, null-space-constrained utility-preservation construction. Nullify keeps the base LLM *entirely frozen* and introduces no trainable parameters: a single per-layer linear operator, solved in closed form, steers forget queries off their memorized-answer trajectory while a null-space projector confines every correction to the subspace orthogonal to the retained-knowledge activations. As Figure 1 previews on TOFU forget10, Nullify achieves the best forget quality at the lowest wall-clock cost we measure, while every weight-space baseline cedes ground on forgetting, utility, or compute.

Our main contributions are threefold:

- **A non-destructive, guarantee-backed paradigm.** We recast unlearning as closed-form, null-space-constrained activation

steering whose correction vanishes on retain queries by construction—to our knowledge the first unlearning method that is at once training-free, weight-preserving, and backed by a principled utility-preservation construction.

- **A fully closed-form, annotation-free pipeline.** The entire per-layer operator is solved in closed form from one forward pass—zero trainable parameters, no backpropagation—with the forget direction derived purely from IDK-contrastive activations and the steering strength being a runtime scalar.
- **State-of-the-art on the forget–utility–cost trilemma.** On TOFU (Maini et al., 2024) and MUSE (Shi et al., 2025), Nullify leads baselines in forget quality while keeping utility near-lossless at a small fraction of their compute—the unique Pareto-dominant point among unlearning methods.

2 Related Work

2.1 LLM Unlearning

LLM unlearning aims to remove the influence of specific data from a trained model without full retraining. Exact unlearning—retraining from scratch on the retain set—is the gold standard, but its computational cost and reliance on the complete training corpus make it impractical at LLM scale (Kurmanji et al., 2023; Thudi et al., 2022). The field has therefore converged on *approximate* unlearning, and its dominant family induces forgetting by directly modifying the model’s weights. Gradient-based methods maximize the loss on the forget set or contrast it with a retain gradient (GA (Jang et al., 2023), GradDiff (Liu et al., 2022)); preference-optimization methods recast forgetting as alignment away from the memorized answer (DPO (Rafailov et al., 2023), NPO (Zhang et al., 2024), SimNPO (Fan et al., 2025)); and task-vector methods subtract a task-specific weight increment in parameter space (Ilharco et al., 2023).

Because forgetting and retention are entangled in the same parameters, this paradigm is inherently destructive: it is well documented to erode general utility, and it further incurs substantial computational cost and acute hyperparameter sensitivity (Fan et al., 2025; Wang et al., 2024). To standardize evaluation, diverse benchmarks have

been proposed—fictitious QA (TOFU (Maini et al., 2024)), copyrighted corpora (MUSE (Shi et al., 2025)), and hazardous knowledge (WMDP (Li et al., 2024))—making the balance between forgetting and utility the field’s central criterion.

2.2 Representation-Level and Inference-Time Unlearning

To avoid the collateral damage of destructive weight updates, a recent line of work moves the unlearning intervention from parameters to internal representations, building on activation steering—an inference-time technique that adds a vector to a model’s hidden states without any gradient update (Rimsky et al., 2024), grounded in the linear representation hypothesis (Zou et al., 2023; Park et al., 2024). Feature-intervention methods redirect the hidden states of forget queries toward random or fixed directions, with RMU (Li et al., 2024) as a representative instance; activation-redirection methods such as LUNAR (Shen et al., 2025) map forget activations onto a refusal-style reference through a learned projection (Dang et al., 2025). A parallel, training-light direction enforces forgetting at the decoding stage rather than in the representation space, e.g., GUARD (Deng et al., 2025) filters forbidden tokens during generation.

These approaches improve stability over full fine-tuning, yet none fully escapes the original tension: they either still fine-tune the base model or require training auxiliary parameters, and in both cases retention is enforced through a soft loss term and inherited as a by-product of optimization—with no mechanism that decouples retention from forgetting by construction.

3 Methodology

We present **Nullify**, a training-free activation-steering framework for LLM unlearning. The setting is the standard one (Maini et al., 2024; Shi et al., 2025): an LLM Φ has been fine-tuned on a corpus containing a designated *forget set* $\mathcal{D}_f = \{(q_i, a_i)\}_{i=1}^{N_f}$ that must be erased, while a *keep set* $\mathcal{D}_k$ —the union of the retain split and held-out general-utility prompts—must remain unaffected. Let $\ell \in \{1, \dots, L\}$ index the decoder layers of Φ , $\mathbf{h}^{(\ell)} \in \mathbb{R}^D$ a hidden state, and $\mathcal{L} \subseteq \{1, \dots, L\}$ a fixed subset of steered layers.

Rather than fine-tuning Φ —which entangles forgetting with general capability through shared parameters and is the source of the utility collapse

and compute cost of gradient-based unlearning—Nullify keeps every weight frozen and intervenes only on hidden states at inference. At each steered layer it adds a per-prompt linear correction $\alpha \mathbf{M}^{(\ell)} \mathbf{h}_\star^{(\ell)}$ to the residual stream, with the operator $\mathbf{M}^{(\ell)} \in \mathbb{R}^{D \times D}$ obtained in closed form from a single forward pass per prompt over $\mathcal{D}_f \cup \mathcal{D}_k$, no trainable parameters, and no backpropagation. Sec. 3.1 fixes the form of the intervention and the contract its operator must satisfy; Sec. 3.2 derives the unlearning-specific target direction the contract pushes forget activations toward; Sec. 3.3 solves for the two factors of $\mathbf{M}^{(\ell)}$ in closed form; and Sec. 3.4 states the resulting algorithm and its cost.

3.1 Intervention Form and Design Contract

Nullify intervenes during the prompt-encoding pass, before any answer token is produced. For each prompt of length T , designate the *anchor* as the hidden state at the last user-prompt token,

$$\mathbf{h}_\star^{(\ell)} := \mathbf{h}_T^{(\ell)}, \quad (1)$$

the position at which the residual stream has integrated the entire query (Arditi et al., 2024). From this single anchor Nullify computes one correction and broadcasts it across every position of the prompt:

$$\mathbf{h}_t^{(\ell)} \leftarrow \mathbf{h}_t^{(\ell)} + \alpha \mathbf{M}^{(\ell)} \mathbf{h}_\star^{(\ell)}, \quad t = 1, \dots, T, \quad \ell \in \mathcal{L}, \quad (2)$$

where $\alpha \in \mathbb{R}$ is a scalar strength. Two consequences of this anchor-broadcast scheme are worth noting. First, because the correction is determined by $\mathbf{h}_\star^{(\ell)}$, it is *prompt-adaptive*: different queries receive different corrections, even though $\mathbf{M}^{(\ell)}$ itself is fixed. Second, computing the correction once and reusing it across token positions reduces the per-prompt overhead to a single $D \times D$ matrix–vector product per steered layer; the steered hidden states then populate the cached keys and values, so autoregressive generation runs without any per-token hook.

What should $\mathbf{M}^{(\ell)} \mathbf{h}_\star^{(\ell)}$ become on a given prompt? Unlearning gives a sharp answer: *nothing* on a keep query (otherwise utility leaks), and a target displacement $\mathbf{r}^{(\ell)}$ on a forget query—the displacement that takes the activation off its memorized-answer trajectory; we define it in Sec. 3.2. We state this as the operator’s design

contract:

$$\mathbf{M}^{(\ell)} \mathbf{h}_\star^{(\ell)} \approx \begin{cases} \mathbf{0}, & q \text{ is a keep query,} \\ \mathbf{r}^{(\ell)}, & q \text{ is a forget query.} \end{cases} \quad (3)$$

The two cases impose unrelated constraints on the same operator. To solve them independently we factorize

$$\mathbf{M}^{(\ell)} = \tilde{\Delta}^{(\ell)} \hat{\mathbf{P}}^{(\ell)}, \quad (4)$$

assigning the *keep* case to the right factor $\hat{\mathbf{P}}^{(\ell)}$ and the *forget* case to the left factor $\tilde{\Delta}^{(\ell)}$: $\hat{\mathbf{P}}^{(\ell)}$ is built to send every keep anchor to zero, so that the full operator $\mathbf{M}^{(\ell)} \mathbf{h}_\star^{(\ell)}$ vanishes on keep queries regardless of the choice of $\tilde{\Delta}^{(\ell)}$; the latter is then chosen to map the projected forget anchors onto $\mathbf{r}^{(\ell)}$. Sec. 3.2 supplies $\mathbf{r}^{(\ell)}$ and Sec. 3.3 constructs both factors.

3.2 The Forget Direction: IDK-Contrastive Activations

The contract in Eq. (3) requires a per-layer target $\mathbf{r}^{(\ell)} \in \mathbb{R}^D$ that captures, in activation space, the *signature of memorization*—the systematic shift a fine-tuned LLM accumulates when it has internalized a factual association and is committing to reproduce it. Unlearning a fact then reduces to canceling this shift in the corresponding activations.

Constructing $\mathbf{r}^{(\ell)}$ is a key challenge specific to the unlearning setting. Forget queries are ordinary factual questions, surface-indistinguishable from retained ones, with no behavioral annotation available, so the target direction cannot be read off labeled samples. We therefore *construct* the direction contrastively, using only the forget set’s own (q, a) pairs. For each forget query q_i with memorized answer a_i , we read the frozen model’s layer- ℓ hidden state at the last token of two prompts—one conditioning on the memorized continuation, one on abstention:

$$\begin{cases} \mathbf{h}_i^{(\ell, \text{ans})} = \Phi^{(\ell)}(q_i \oplus a_i), \\ \mathbf{h}_i^{(\ell, \text{idk})} = \Phi^{(\ell)}(q_i \oplus \text{IDK}), \end{cases} \quad (5)$$

where $\oplus$ denotes prompt concatenation, IDK is a fixed “I don’t know”-style template, and $\Phi^{(\ell)}(\cdot) \in \mathbb{R}^D$ returns the layer- ℓ last-token hidden state. Averaging over the forget set yields the two population modes

$$\begin{cases} \mu_{\text{ans}}^{(\ell)} = \frac{1}{N_f} \sum_{i=1}^{N_f} \mathbf{h}_i^{(\ell, \text{ans})}, \\ \mu_{\text{idk}}^{(\ell)} = \frac{1}{N_f} \sum_{i=1}^{N_f} \mathbf{h}_i^{(\ell, \text{idk})}, \end{cases} \quad (6)$$

and the *forget direction* is their residual:

$$\mathbf{r}^{(\ell)} = \mu_{\text{ans}}^{(\ell)} - \mu_{\text{idk}}^{(\ell)} \in \mathbb{R}^D. \quad (7)$$

Geometrically, $\mathbf{r}^{(\ell)}$ is the average displacement from abstention to commitment; with the sign convention $\alpha < 0$ used throughout Eq. (2), adding $\alpha \mathbf{r}^{(\ell)}$ to the residual stream slides a forget activation off the memorized-answer mode $\mu_{\text{ans}}^{(\ell)}$ toward the abstention mode $\mu_{\text{idk}}^{(\ell)}$.

3.3 Solving the Two Factors in Closed Form

We now construct the two factors of Eq. (4) so that the contract in Eq. (3) is met. For notational clarity we suppress the layer superscript (ℓ) throughout this subsection; all quantities are understood as per-layer.

Right factor $\hat{\mathbf{P}}$: annihilating the keep subspace.

Let $\mathbf{H}_k \in \mathbb{R}^{D \times N_k}$ stack the anchor activations of every prompt in $\mathcal{D}_k$. The keep case of Eq. (3) demands $\mathbf{M}\mathbf{H}_k = \mathbf{0}$. Substituting the factorization, this reduces to $\tilde{\Delta}\hat{\mathbf{P}}\mathbf{H}_k = \mathbf{0}$, which holds for *any* choice of $\tilde{\Delta}$ whenever every column of $\mathbf{H}_k$ lies in the kernel of $\hat{\mathbf{P}}$. We therefore take $\hat{\mathbf{P}}$ to be the orthogonal projector onto the left null space of $\mathbf{H}_k$.

Definition 1 (Left null space). For $\mathbf{H} \in \mathbb{R}^{D \times N}$, $\text{Null}_L(\mathbf{H}) = \{\mathbf{x} \in \mathbb{R}^D : \mathbf{x}^\top \mathbf{H} = \mathbf{0}\}$.

Computing this projector by a direct SVD of $\mathbf{H}_k$ is wasteful when $N_k \gg D$; the following standard equivalence (Wang et al., 2021; Fang et al., 2025; Sheng et al., 2026) reduces it to the $D \times D$ Gram matrix.

Lemma 1 (Null-space equivalence). $\text{Null}_L(\mathbf{H}) = \text{Null}_L(\mathbf{H}\mathbf{H}^\top)$.

By Lemma 1 (proof in Appendix A.1), we accordingly compute an SVD $\mathbf{H}_k\mathbf{H}_k^\top = \mathbf{V}\Sigma\mathbf{V}^\top$, collect the eigenvectors of the $k = \lfloor pD \rfloor$ smallest eigenvalues into $\hat{\mathbf{V}} \in \mathbb{R}^{D \times k}$, and set

$$\hat{\mathbf{P}} = \hat{\mathbf{V}}\hat{\mathbf{V}}^\top \in \mathbb{R}^{D \times D}, \quad (8)$$

where the *null-space ratio* $p \in (0, 1)$ is a structural hyperparameter (sensitivity reported in Sec. 4.5.2). $\hat{\mathbf{P}}$ is a symmetric idempotent— $\hat{\mathbf{P}}^\top = \hat{\mathbf{P}}$ and $\hat{\mathbf{P}}^2 = \hat{\mathbf{P}}$ —and $\hat{\mathbf{P}}\mathbf{H}_k = \mathbf{0}$ holds down to the smallest retained eigenvalue of the Gram. The keep case of Eq. (3) is thus discharged *independently* of $\tilde{\Delta}$.

Left factor $\tilde{\Delta}$: a closed-form forget mapping.

With $\hat{\mathbf{P}}$ fixed, the forget case of Eq. (3) becomes: choose $\tilde{\Delta}$ so that $\tilde{\Delta}\hat{\mathbf{P}}\mathbf{H}_f \approx \mathbf{R}$, where $\mathbf{H}_f \in$

$\mathbb{R}^{D \times N_f}$ stacks the anchor activations of the raw forget queries $\{q_i\}$ and $\mathbf{R} = \mathbf{r} \mathbf{1}_{N_f}^\top$ stacks N_f copies of the forget direction. We solve it as a Frobenius-regularized least-squares problem,

$$\min_{\tilde{\Delta}} \|\tilde{\Delta} \hat{\mathbf{P}} \mathbf{H}_f - \mathbf{R}\|_F^2 + \lambda \|\tilde{\Delta} \hat{\mathbf{P}}\|_F^2, \quad (9)$$

whose closed-form minimizer, after applying the symmetric-idempotent identities of $\hat{\mathbf{P}}$, is

$$\tilde{\Delta}^* = \mathbf{R} \mathbf{H}_f^\top \hat{\mathbf{P}} (\hat{\mathbf{P}} \mathbf{H}_f \mathbf{H}_f^\top \hat{\mathbf{P}} + \lambda \hat{\mathbf{P}})^+, \quad (10)$$

with $(\cdot)^+$ the Moore–Penrose pseudoinverse and $\lambda > 0$ the ridge coefficient; the full derivation, including the handling of the rank deficiency of $\hat{\mathbf{P}}$, is given in Appendix A.2.

Assembly. Restoring the layer index, the per-layer steering operator at layer ℓ is

$$\mathbf{M}^{(\ell)} = \tilde{\Delta}^{*(\ell)} \hat{\mathbf{P}}^{(\ell)}, \quad (11)$$

applied at inference through Eq. (2). By construction, $\hat{\mathbf{P}}^{(\ell)}$ annihilates every column of $\mathbf{H}_k^{(\ell)}$ down to the smallest retained eigenvalue of the Gram, while $\tilde{\Delta}^{*(\ell)}$ delivers the ridge-regularized best fit of $\mathbf{r}^{(\ell)}$ on the projected forget anchors—the two cases of the contract in Eq. (3), separately and tightly.

3.4 Algorithm and Complexity

Algorithm 1 summarizes the offline construction: a single forward pass per prompt over $\mathcal{D}_k \cup \mathcal{D}_f$ (plus the IDK-contrastive auxiliary prompts), one $D \times D$ Gram SVD, and one pseudoinverse—per steered layer.

Cost. Each layer costs $O(N_k D^2)$ to form the keep Gram and $O(D^3)$ for the subsequent SVD and pseudoinverse; the closed-form left-factor adds $O(N_f D^2)$. Total offline cost per layer is $O((N_k + N_f) D^2 + D^3)$. At inference, the steered hidden states populate the cached keys and values, so generation reuses the steered KV cache without any per-token hook; the per-prompt overhead is a single $D \times D$ matrix–vector product per steered layer, asymptotically negligible against the base forward pass. Nullify adds zero trainable parameters and never invokes a backward pass; it exposes four choices—the steered-layer set $\mathcal{L}$ and three scalars (p, λ, α) —all subjected to sensitivity analysis in Sec. 4.5.2.

Algorithm 1 Nullify (offline operator construction).

Require: frozen LLM Φ ; forget set $\mathcal{D}_f$; keep set $\mathcal{D}_k$; steered layers $\mathcal{L}$; hyperparameters (p, λ) .

- 1: **for** $\ell \in \mathcal{L}$ **do**
- 2: $\mathbf{H}_k^{(\ell)} \leftarrow$ anchor activations of all prompts in $\mathcal{D}_k$
- 3: $\mathbf{H}_f^{(\ell)} \leftarrow$ anchor activations of forget queries $\{q_i\}$ from $\mathcal{D}_f$
- 4: compute $\{\mathbf{h}_i^{(\ell, \text{ans})}, \mathbf{h}_i^{(\ell, \text{idk})}\}$ via Eq. (5)
- 5: $\mathbf{r}^{(\ell)} \leftarrow \boldsymbol{\mu}_{\text{ans}}^{(\ell)} - \boldsymbol{\mu}_{\text{idk}}^{(\ell)}$
- 6: $\hat{\mathbf{P}}^{(\ell)} \leftarrow$ Eq. (8) from $\mathbf{H}_k^{(\ell)} \mathbf{H}_k^{(\ell)\top}$
- 7: $\tilde{\Delta}^{*(\ell)} \leftarrow$ closed-form solution of Eq. (10)
- 8: $\mathbf{M}^{(\ell)} \leftarrow \tilde{\Delta}^{*(\ell)} \hat{\mathbf{P}}^{(\ell)}$
- 9: **end for**

Ensure: per-layer operators $\{\mathbf{M}^{(\ell)}\}_{\ell \in \mathcal{L}}$, applied at inference via Eq. (2).

4 Experiments

4.1 Setup

Benchmarks. We evaluate Nullify on two standard LLM unlearning benchmarks. **TOFU** (Maini et al., 2024) consists of 4,000 question–answer pairs about 200 fictitious authors; because the target knowledge is entirely synthetic and introduced by supervised fine-tuning (SFT), unlearning can be assessed against a model retrained from scratch on the retain split. We report the forget05 and forget10 settings, which erase 5% and 10% of the data. **MUSE** (Shi et al., 2025) simulates real-world privacy and copyright removal; we evaluate on its News corpus (MUSE-News).

Base model. For the main TOFU experiments, all methods operate on Llama-2-7B-chat-hf fine-tuned on the full TOFU corpus; the retrained reference is obtained by fine-tuning the same model on the retain split only. Appendix C reports a cross-family replication on Qwen3-8B (Yang et al., 2025) under forget10. MUSE-News follows the benchmark’s standard setup.

Baselines. Besides the *Retrain* gold reference (Bourtole et al., 2021) and the un-unlearned *Original* model, we compare against four families: *gradient-based* (GA (Jang et al., 2023), GradDiff (Liu et al., 2022)); *weight editing* (Task Vector (Ilharco et al., 2023)); *preference optimization* (IDK (Eldan and Russinovich, 2023), NPO (Zhang et al., 2024), and its reference-free variant Sim-

NPO (Fan et al., 2025)); and *representation intervention* (LUNAR (Shen et al., 2025)).

Metrics. On TOFU, the two summary metrics are **Forget Quality (FQ)**—the Kolmogorov–Smirnov p -value between the truth-ratio distributions of the unlearned and retrained models, so that statistical indistinguishability from Retrain yields $FQ \rightarrow 1$ and **Model Utility (MU)**, the harmonic mean of performance over the non-target Real Authors, World Facts, and Retain sets, where any single capability drop sharply penalizes the aggregate. For completeness we also report per-set ROUGE-L (RL), answer probability (P), and truth ratio (TR). On MUSE-News we report **KM-D_f** (forget-set knowledge memorization), **KM-D_r** (retain-set knowledge), and **PrivLeak**, a membership-inference-based privacy score whose ideal value is 0.

Implementation. Nullify keeps the base model frozen and adds no trainable parameters. Following the localization of factual recall to mid-upper transformer layers (Geva et al., 2021; Meng et al., 2022) and the layer-selection convention of AlphaSteer (Sheng et al., 2026), we steer a fixed set of ten mid-upper decoder layers ($\mathcal{L} = \{8\text{--}14, 16, 18, 19\}$). Unless noted otherwise, we use null-space ratio $p = 0.75$, ridge coefficient $\lambda = 10$, and steering strength $\alpha = -2.0$. Experiments conducted in this work use greedy decoding on a single NVIDIA H800 80 GB GPU. For direct comparability, we follow the same benchmark setting and evaluation protocol as Fan et al. (2025), including the backbone, forget/retain splits, and metric definitions. Values in ‡-marked rows of Tables 2 and 3 are taken from Fan et al. (2025); unmarked methods are evaluated in this work under this matched protocol.

4.2 Main Results

Tables 2 and 3 report quantitative results on TOFU and MUSE-News. Across both benchmarks Nullify delivers the strongest forget–utility balance: it suppresses the target knowledge while leaving general capability essentially intact, avoiding the utility collapse that the gradient- and preference-based baselines incur. We detail the per-benchmark results below, contrasting Nullify against the baselines on both forget quality and utility.

4.2.1 Results on TOFU

The gradient-based baselines expose the cost of destructive updates. Gradient Ascent maximizes forget-set loss but destroys the model: its MU falls to 0.00 under both forget ratios, a complete loss of linguistic competence. GradDiff and IDK avoid total collapse yet still leave MU at 0.54–0.57, well below the 0.62 of the Original and Retrain models.

Nullify is the only method whose utility is indistinguishable from the references: MU holds at 0.62 on both forget05 and forget10, matching Retrain exactly. On forget05 it reaches an FQ of 0.96, within 0.03 of the strongest baseline SimNPO (0.99)—but SimNPO buys that forget quality with an MU of 0.58, whereas Nullify gives up nothing. On the harder forget10 split Nullify dominates every baseline: it raises FQ from SimNPO’s 0.45 to 0.58 and holds MU at 0.62—the highest among unlearning methods, tied with SimNPO and equal to Retrain. The per-set numbers (forget10) confirm the absence of collateral damage: Nullify’s ROUGE-L on World Facts (0.90) and the Retain set (0.95) tracks the Original model (0.91/0.98) closely.

4.2.2 Results on MUSE-News

On MUSE-News (Table 3), the privacy metric PrivLeak is the most discriminative: it is near 0 only when a method removes the target knowledge to the same degree as Retrain, and diverges under both under- and over-unlearning.

The baselines fail in opposite directions. The preference- and gradient-based methods leak heavily—NPO (108.91), GradDiff (108.12), and SimNPO (72.93) sit far above 0—while Task Vector swings to the opposite extreme (−100.00), over-correcting past the retrained reference. The representation baseline LUNAR barely moves the needle: its PrivLeak of −99.80 is essentially the unlearned level of the Original model (−98.71). Gradient Ascent collapses outright, with KM-D_f at 0.00.

Nullify is the only method that lands near the ideal: a PrivLeak of −5.18, an order of magnitude closer to 0 than any baseline. Its forget-set memorization KM-D_f drops from the Original’s 0.63 to 0.27, close to the Retrain reference (0.33), while retain-set knowledge KM-D_r stays at 0.51, near Retrain (0.54) and the Original (0.54). Nullify thus removes the target knowledge to a Retrain-like degree without the privacy leakage or the utility collapse of the baselines.

Method	Unlearning Efficacy				Utility Preservation									
	Forget Set			FQ $\uparrow$	Real Authors $\uparrow$			World Facts $\uparrow$			Retain Set $\uparrow$			MU $\uparrow$
	1-RL	1-P	TR		RL	P	TR	RL	P	TR	RL	P	TR	
Forget05														
Original [‡]	0.04	0.01	0.49	0.00	0.93	0.44	0.58	0.91	0.43	0.55	0.98	0.99	0.48	0.62
Retrain ^{†,‡}	0.61	0.85	0.66	1.00	0.92	0.44	0.57	0.90	0.43	0.54	0.97	0.99	0.48	0.62
GA [‡]	1.00	1.00	0.66	<0.01	0.00	0.20	0.40	0.00	0.30	0.28	0.00	0.00	0.15	0.00
GradDiff [‡]	1.00	1.00	0.60	<0.01	0.59	0.59	0.81	0.88	0.46	0.59	0.42	0.49	0.48	0.56
IDK [‡]	0.98	0.40	0.55	<0.01	0.65	0.48	0.63	0.82	0.44	0.55	0.55	0.86	0.43	0.57
NPO [‡]	0.73	0.94	0.67	0.79	0.91	0.50	0.62	0.90	0.50	0.61	0.47	0.51	0.44	0.57
SimNPO [‡]	0.74	0.97	0.69	0.99	0.90	0.50	0.64	0.90	0.48	0.60	0.54	0.56	0.44	0.58
LUNAR	0.70	0.69	0.69	0.87	0.71	0.49	0.63	0.80	0.44	0.57	0.69	0.82	0.43	0.59
Nullify	0.62	0.88	0.69	0.96	0.92	0.47	0.61	0.88	0.44	0.58	0.95	0.86	0.44	0.62
Forget10														
Original [‡]	0.03	0.01	0.48	0.00	0.93	0.44	0.58	0.91	0.43	0.55	0.98	0.99	0.48	0.62
Retrain ^{†,‡}	0.61	0.84	0.67	1.00	0.93	0.45	0.59	0.91	0.42	0.54	0.98	0.99	0.47	0.62
GA [‡]	1.00	1.00	0.70	<0.01	0.00	0.28	0.37	0.00	0.29	0.31	0.00	0.00	0.11	0.00
GradDiff [‡]	1.00	1.00	0.67	<0.01	0.44	0.49	0.67	0.89	0.48	0.58	0.48	0.60	0.46	0.54
IDK [‡]	0.98	0.37	0.54	<0.01	0.46	0.45	0.59	0.84	0.43	0.55	0.56	0.88	0.44	0.54
NPO [‡]	0.78	0.90	0.70	0.29	0.91	0.52	0.66	0.85	0.48	0.61	0.44	0.46	0.39	0.55
SimNPO [‡]	0.78	0.91	0.71	0.45	0.90	0.54	0.70	0.88	0.50	0.64	0.54	0.76	0.47	0.62
LUNAR	0.83	0.84	0.67	0.47	0.60	0.52	0.67	0.72	0.43	0.59	0.53	0.66	0.43	0.55
Nullify	0.59	0.92	0.71	0.58	0.92	0.47	0.61	0.90	0.42	0.55	0.95	0.88	0.45	0.62

Table 2: Results on TOFU (Maini et al., 2024) (forget05/forget10, Llama-2-7B-chat-hf). **Unlearning Efficacy:** forget-set 1—ROUGE-L, 1—Prob., Truth Ratio, and the summary metric FQ. **Utility Preservation:** RL/P/TR on Real Authors, World Facts, and the Retain set, summarized by MU. [†]Retrain is the gold reference; the forget-set columns are best when *closest to Retrain*, not when largest. Rows marked with [‡] are taken from Fan et al. (2025). **Bold:** best FQ / MU among unlearning methods.

Method	Unlearning KM-D _f	Privacy PrivLeak	Utility KM-D _r
Original [†]	0.63	−98.71	0.54
Retrain ^{†,‡}	0.33	0.00	0.54
GA [‡]	0.00	20.14	0.00
GradDiff [‡]	0.31	108.12	0.28
Task Vector [‡]	0.59	−100.00	0.48
NPO [‡]	0.57	108.91	0.38
SimNPO [‡]	0.45	72.93	0.40
LUNAR	0.55	−99.80	0.52
Nullify	0.27	−5.18	0.51

Table 3: Results on MUSE-News (Shi et al., 2025). KM-D_f/KM-D_r: forget-/retain-set knowledge memorization (best when closest to Retrain[†], 0.33/0.54); PrivLeak: privacy leakage (ideal = 0, **bold**). Rows marked with [‡] are taken from Fan et al. (2025).

4.3 Robustness Experiments

We evaluate extraction robustness with approximately 11,200 prompts spanning six attack families and 14 variants: prefix injection, roleplay, few-shot elicitation, partial-answer elicitation, multi-turn extraction, and cloze/multiple-choice prompt-

Attack family	Original	Retrain	Nullify
Prefix injection	0.633	0.087	0.222
Roleplay	0.434	0.071	0.111
Few-shot elicitation	0.388	0.074	0.014
Partial-answer elicitation	0.202	0.042	0.065
Multi-turn extraction	0.405	0.085	0.128
Cloze / multiple choice	0.285	0.210	0.030
Six-family mean	0.391	0.095	0.095

Table 4: Exact-span leakage under adversarial extraction (lower is better). The mean is unweighted across families; multi-turn extraction is scored on the final extraction turn.

ing. A separate test covers question paraphrasing and cloze-style reformatting. Tables 4 and 5 report exact-span leakage—the fraction of forget-example outputs containing a gold answer span—where lower is better. The six-family score is an unweighted macro-average; multi-turn leakage is measured on the final extraction turn.

Nullify lowers leakage relative to Original in every family, reducing the macro-average from

Prompt type	Original	Retrain	Nullify
Plain QA	0.975	0.085	0.253
Paraphrased question	0.478	0.128	0.218
Cloze completion	0.358	0.153	0.060

Table 5: Exact-span leakage under paraphrasing and reformatting (lower is better).

Method	#Train params	Mem (GB)	Wall-clock (min)	$\times$ vs Nullify
Retrain [†]	6.6 B	$\sim$ 79	$\sim$ 300	57.7 $\times$
GA	6.6 B	79	14.5	2.8 $\times$
GradDiff	6.6 B	79	13.5	2.6 $\times$
IDK	6.6 B	79	$\sim$ 13	2.5 $\times$
NPO	6.6 B	79	58.2	11.2 $\times$
SimNPO	6.6 B	79	27.4	5.3 $\times$
LUNAR	66 K	16	6.3	1.2 $\times$
Nullify	0	14	5.2	1.0$\times$

Table 6: End-to-end cost on TOFU forget05 / Llama-2-7B-chat-hf, single NVIDIA H800. #Train params: parameters updated by gradient descent. Wall-clock: per {hyperparameter, seed} configuration at each method’s paper-recipe epoch budget.

0.391 to 0.095, which matches Retrain at the reported three-decimal precision. On this metric, Nullify yields lower leakage than Retrain for few-shot elicitation (0.014 vs. 0.074), cloze/multiple choice (0.030 vs. 0.210), and cloze completion (0.060 vs. 0.153). Under paraphrasing, leakage remains below Original (0.218 vs. 0.478), indicating partial transfer to nearby free-form query formats.

4.4 Compute and Memory Efficiency

Beyond unlearning quality, deployment cost determines whether a method can serve real-world right-to-be-forgotten requests. We benchmark every method end-to-end on identical hardware (a single NVIDIA H800 80 GB) under the TOFU forget05 / Llama-2-7B-chat-hf setting, reporting peak GPU memory and the wall-clock paid per single {hyperparameter, seed} configuration. Wall-clock follows each method’s paper recipe: 5 epochs for GA, GradDiff and IDK (Maini et al., 2024); 20 epochs for NPO and 10 for SimNPO (Fan et al., 2025); 20 epochs of single-layer LoRA training for LUNAR (Shen et al., 2025); and a single closed-form preparation plus a per- α inference pass for Nullify. Reported times include training and the default post-hoc TOFU evaluation, so the comparison is end-to-end.

Table 6 summarizes the result. Every full-finetune baseline—GA, GradDiff, NPO, SimNPO—

carries a 6.6 B-parameter Adam state, saturates GPU memory at $\sim$ 79 GB, and takes 13–58 minutes per configuration. Nullify instead runs in pure inference memory (14 GB) and finishes one configuration in 5.2 minutes: 3.2 minutes to extract activations and solve the closed-form ridge once, plus 1.95 minutes of inference-time evaluation at one α . Nullify dominates five of the six baselines outright—GA, GradDiff, IDK, NPO and LUNAR are each both slower and weaker (Nullify, e.g., surpasses LUNAR in forget quality, 0.96 vs. 0.87, at lower cost, 5.2 vs. 6.3 min). Only SimNPO and the Retrain oracle reach higher forget quality, and they pay 5.3 $\times$ and $\sim$ 58 $\times$ Nullify’s wall-clock to do so. Nullify is therefore Pareto-optimal in the forget-quality / wall-clock plane: no baseline is simultaneously faster and stronger. Moreover, since α is a runtime scalar that does not enter the closed-form preparation, adapting Nullify to a new forget request at deployment requires only a single inference-time evaluation per α value, with no re-training.

4.5 Analysis

4.5.1 Ablation Study

Nullify combines two components: the null-space projection that confines the steering operator, and the IDK-contrastive forget direction. Table 7 removes each in turn on forget05. Replacing the null-space projector with the identity ($\hat{\mathbf{P}}=\mathbf{I}$) removes the utility guarantee: even at its most conservative strength ($\alpha=-0.3$) MU is only 0.36, and by $\alpha=-1.0$ it has collapsed to 0.01—there is no steering strength at which an unconstrained operator both forgets and preserves utility. Replacing the IDK-contrastive direction with a random vector of matched norm halves forget quality (FQ 0.96 $\rightarrow$ 0.466) while leaving MU near 0.60. The two ablations isolate the two roles cleanly: the null-space projection is what preserves utility, and the IDK-contrastive direction is what carries the forget signal.

4.5.2 Hyperparameter Sensitivity

Tables 8–10 in Appendix B sweep the three scalars of Nullify on forget05. Forget quality peaks at the operating point $\lambda=10$, $\alpha=-2.0$, with α sitting inside a wide robust plateau—FQ exceeds 0.92 throughout $\alpha \in [-2.3, -1.9]$ rather than on a knife-edge. Critically, MU stays within 0.61–0.63 across every value of p , direct evidence that utility preservation is delivered by the null-space construction,

Variant	best α	FQ	MU
Nullify (full)	-2.0	0.965	0.622
w/o null-space proj. ($\hat{\mathbf{P}}=\mathbf{I}$)	-0.3	0.270	0.360
w/o IDK-contrastive dir. (random $\mathbf{r}$)	-2.0	0.466	0.600

Table 7: Ablation on TOFU forget05. The $\hat{\mathbf{P}}=\mathbf{I}$ row is shown at its own best α (-0.3); by $\alpha = -1.0$ it has already collapsed to FQ 0.00 / MU 0.01.




Figure 2: Forget-set truth-ratio density under three models on TOFU. Dashed gray: Original (memorized); red: Nullify; blue: Retrain (oracle). Nullify collapses the memorization peak back onto the Retrain envelope; the Kolmogorov–Smirnov p -value in each title is the Forget Quality used in Table 2.

not by hyperparameter tuning.

4.5.3 Forget-Quality Visualization

To make the statistical content of FQ concrete, Figure 2 overlays the per-example truth-ratio densities of the Original model, the Nullify-steered model, and the Retrain oracle on the forget05 and forget10 forget sets. FQ is by definition the Kolmogorov–Smirnov p -value between the steered and Retrain distributions, so a perfect match gives $p \rightarrow 1$ and a memorized forget set shows up as a narrow low-truth-ratio mode.

The Original model exhibits exactly this memorization signature—a sharp peak near 0.56–0.58 that places most forget questions far outside the Retrain envelope. Nullify lifts this mass back into a broad distribution centered at 0.86 (forget05) and 0.87 (forget10), nearly overlapping the Retrain reference at 0.90 and 0.91. The resulting KS p -values, 0.96 and 0.58, are the FQ scores of Table 2. The visualization confirms that Nullify does not merely lower a verbatim-recall score; it restores the *distributional* indistinguishability from Retrain that FQ is designed to measure. Representative qualitative forget05 outputs, contrasting Nullify’s forget-set abstention with its unchanged retain-set generations, are provided in Appendix D (Table 12).

5 Conclusion

We present Nullify, a training-free, null-space-constrained activation-steering framework for LLM unlearning. By steering forget queries off their memorized-answer trajectory while confining every correction to the null space of retained-knowledge activations, Nullify decouples forgetting from utility preservation rather than trading one against the other—without modifying any model parameter. On TOFU and MUSE, it matches or surpasses the strongest gradient-based, preference-optimization, and representation-intervention baselines in forget quality while keeping utility near-lossless, at a small fraction of their compute and memory. More broadly, Nullify shifts LLM unlearning from destructive parameter reshaping to lightweight, geometrically constrained activation steering—a plug-and-play path to the "right to be forgotten." Future work will extend it to multimodal architectures and long-context unlearning.

Limitations

As an inference-time intervention, Nullify suppresses access to memorized answers while its operator is active rather than permanently altering the underlying weights. Our robustness evaluation covers fixed-template black-box extraction and nearby free-form reformulations in the intended serving-time setting. Adaptive attacks and white-box settings in which the operator can be inspected, modified, or disabled remain outside the current scope. The intervention layers and steering strength are currently selected per benchmark; automatic configuration across architectures and deployment settings remains an important direction for future work.

Ethics Considerations

Nullify is designed to support privacy-, copyright-, and safety-driven removal of memorized content from deployed LLMs, in line with the right to erasure under the GDPR and the data-governance requirements of the EU AI Act. Because Nullify avoids weight updates and gradient computation, it reduces the energy and compute cost of fulfilling a deletion request by roughly an order of magnitude relative to gradient-based unlearning, which means providers serving large user bases can afford to honor every deletion request. We caution, however, that the same mechanism that suppresses

sensitive memorized content can in turn be configured to hide outputs that should remain public—for example, silently filtering information about public events, public figures, or known model behaviors. To guard against such misuse, we restrict our evaluation to published, peer-reviewed unlearning benchmarks (TOFU and MUSE), whose forget sets target privacy- and copyright-motivated removal rather than viewpoint suppression; we further recommend that any party deploying this method publicly disclose the categories of content their steering operators are configured to remove, so that the suppression remains subject to external oversight.

References

- Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. 2024. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems*.
- Lucas Bourtole, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. 2021. Machine unlearning. In *2021 IEEE Symposium on Security and Privacy (SP)*, pages 141–159. IEEE.
- Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. Extracting training data from large language models. In *30th USENIX Security Symposium*, pages 2633–2650.
- Huu-Tien Dang, Tin Pham, Hoang Thanh-Tung, and Naoya Inoue. 2025. On effects of steering latent representation for large language model unlearning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 23733–23742.
- Zhijie Deng, Chris Yuhao Liu, Zirui Pang, Xinlei He, Lei Feng, Qi Xuan, Zhaowei Zhu, and Jiaheng Wei. 2025. Guard: Generation-time llm unlearning via adaptive restriction and detection. *arXiv preprint arXiv:2505.13312*.
- Ronen Eldan and Mark Russinovich. 2023. Who’s harry potter? approximate unlearning in llms. *arXiv preprint arXiv:2310.02238*.
- European Parliament and Council of the European Union. 2024. [Regulation \(eu\) 2024/1689 of the european parliament and of the council of 13 june 2024 laying down harmonised rules on artificial intelligence \(artificial intelligence act\)](#). Official Journal of the European Union, OJ L, 2024/1689.
- Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. 2025. Simplicity prevails: Rethinking negative preference optimization for LLM unlearning. In *Advances in Neural Information Processing Systems*.
- Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan Ma, Jie Shi, Xiang Wang, Xiangnan He, and Tat-Seng Chua. 2025. Alphaedit: Null-space constrained knowledge editing for language models. In *International Conference on Learning Representations*, volume 2025, pages 16366–16396.
- Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. 2021. [Transformer feed-forward layers are key-value memories](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5484–5495. Association for Computational Linguistics.
- Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hananeh Hajishirzi, and Ali Farhadi. 2023. Editing models with task arithmetic. In *The Eleventh International Conference on Learning Representations (ICLR)*.
- Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. 2023. Knowledge unlearning for mitigating privacy risks in language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14389–14408.
- Meghdad Kurmanji, Peter Triantafillou, Jamie Hayes, and Eleni Triantafillou. 2023. [Towards unbounded machine unlearning](#). In *Advances in Neural Information Processing Systems*, volume 36, pages 1957–1987. Curran Associates, Inc.
- Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Gabriel Mukobi, Nathan Helm-Burger, Rassim R. Lababidi, Lennart Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, Rishub Tamirisa, and 27 others. 2024. The wmdp benchmark: Measuring and reducing malicious use with unlearning. In *Proceedings of the 41st International Conference on Machine Learning*.
- Bo Liu, Qiang Liu, and Peter Stone. 2022. [Continual learning and private unlearning](#). In *Proceedings of The 1st Conference on Lifelong Learning Agents*, volume 199 of *Proceedings of Machine Learning Research*, pages 243–254. PMLR.
- Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C Lipton, and J Zico Kolter. 2024. TOFU: A task of fictitious unlearning for LLMs. In *Proceedings of the First Conference on Language Modeling (COLM)*.
- Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems*, volume 35, pages 17359–17372.

- Kiho Park, Yo Joong Choe, and Victor Veitch. 2024. The linear representation hypothesis and the geometry of large language models. In *Proceedings of the 41st International Conference on Machine Learning, ICML'24*. JMLR.org.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.
- Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner. 2024. Steering Llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, pages 15504–15522.
- William F Shen, Xinchu Qiu, Meghdad Kurmanji, Alex Jacob, Lorenzo Sani, Yihong Chen, Nicola Cancedda, and Nicholas D Lane. 2025. LUNAR: LLM unlearning via neural activation redirection. In *Advances in Neural Information Processing Systems*.
- Leheng Sheng, Changshuo Shen, Weixiang Zhao, Junfeng Fang, Xiaohao Liu, Zhenkai Liang, Xiang Wang, An Zhang, and Tat-Seng Chua. 2026. AlphaSteer: Learning refusal steering with principled null-space constraint. In *The Fourteenth International Conference on Learning Representations*.
- Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika Maladi, Jieyu Zhao, Ari Holtzman, Daogao Liu, Luke Zettlemoyer, Noah A. Smith, and Chiyuan Zhang. 2025. MUSE: Machine unlearning six-way evaluation for language models. In *The Thirteenth International Conference on Learning Representations*.
- Anvith Thudi, Gabriel Deza, Varun Chandrasekaran, and Nicolas Papernot. 2022. Unrolling SGD: Understanding factors influencing machine unlearning. In *2022 IEEE 7th European Symposium on Security and Privacy (EuroS&P)*, pages 303–319. IEEE.
- Qizhou Wang, Bo Han, Puning Yang, Jianing Zhu, Tongliang Liu, and Masashi Sugiyama. 2024. Unlearning with control: Assessing real-world utility for large language model unlearning. *arXiv preprint arXiv:2406.09179*.
- Shipeng Wang, Xiaorong Li, Jian Sun, and Zongben Xu. 2021. Training networks in null space of feature covariance for continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 184–193.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.
- Yuanshun Yao, Xiaojun Xu, and Yang Liu. 2024. Large language model unlearning. In *Advances in Neural Information Processing Systems (NeurIPS)*.
- Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. 2024. Negative preference optimization: From catastrophic collapse to effective unlearning. In *First Conference on Language Modeling*.
- Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xu Wang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, and 2 others. 2023. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*.

A Theoretical Details

This appendix supplies (i) the proof of Lemma 1 and (ii) the full derivation of Eq. (10) with a careful treatment of the rank deficiency of $\hat{\mathbf{P}}$. Throughout we suppress the layer index (ℓ).

A.1 Proof of Lemma 1

Proof. ($\subseteq$) If $\mathbf{x}^\top \mathbf{H} = \mathbf{0}$, then $\mathbf{x}^\top \mathbf{H} \mathbf{H}^\top = \mathbf{0}$.

($\supseteq$) If $\mathbf{x}^\top \mathbf{H} \mathbf{H}^\top = \mathbf{0}$, then

$$\mathbf{x}^\top \mathbf{H} \mathbf{H}^\top \mathbf{x} = \|\mathbf{H}^\top \mathbf{x}\|_2^2 = 0,$$

so $\mathbf{H}^\top \mathbf{x} = \mathbf{0}$, i.e., $\mathbf{x}^\top \mathbf{H} = \mathbf{0}$. $\square$

The equivalence lets Nullify replace an SVD of the $D \times N_k$ matrix $\mathbf{H}_k$ by an eigendecomposition of the $D \times D$ Gram $\mathbf{H}_k \mathbf{H}_k^\top$, which is the key to the $O(N_k D^2 + D^3)$ offline cost in the regime $N_k \gg D$ relevant here.

A.2 Derivation of the Closed-Form Solution

The objective in Eq. (9) is

$$J(\tilde{\Delta}) = \|\tilde{\Delta} \hat{\mathbf{P}} \mathbf{H}_f - \mathbf{R}\|_F^2 + \lambda \|\tilde{\Delta} \hat{\mathbf{P}}\|_F^2. \quad (12)$$

Using $\hat{\mathbf{P}}^\top = \hat{\mathbf{P}} = \hat{\mathbf{P}}^2$, setting $\nabla J = \mathbf{0}$ gives the normal equation

$$\tilde{\Delta} \mathbf{A} = \mathbf{R} \mathbf{H}_f^\top \hat{\mathbf{P}}, \quad (13)$$

with $\mathbf{A} := \hat{\mathbf{P}} \mathbf{H}_f \mathbf{H}_f^\top \hat{\mathbf{P}} + \lambda \hat{\mathbf{P}}$.

Rank deficiency. $\mathbf{A}$ has rank $k = \text{rank}(\hat{\mathbf{P}}) < D$. $\mathbf{A} \mathbf{x} = \mathbf{0}$ implies $\mathbf{x}^\top \mathbf{A} \mathbf{x} = \|\mathbf{H}_f^\top \hat{\mathbf{P}} \mathbf{x}\|_2^2 + \lambda \|\hat{\mathbf{P}} \mathbf{x}\|_2^2 = 0$, which forces $\hat{\mathbf{P}} \mathbf{x} = \mathbf{0}$ since $\lambda > 0$. Together with the obvious converse,

$$\text{Null}(\mathbf{A}) = \text{Null}(\hat{\mathbf{P}}), \quad \text{range}(\mathbf{A}) = \text{range}(\hat{\mathbf{P}}). \quad (14)$$

The right-hand side of (13) has rows in $\text{range}(\hat{\mathbf{P}})$ (since $\mathbf{b}^\top \hat{\mathbf{P}} = \mathbf{b}^\top$ for any such row $\mathbf{b}^\top$), hence in $\text{range}(\mathbf{A})$: the system is consistent, and the minimum-Frobenius-norm solution is

$$\tilde{\Delta}^* = \mathbf{R} \mathbf{H}_f^\top \hat{\mathbf{P}} \mathbf{A}^+, \quad (15)$$

which is Eq. (10).

Verification via a reduced full-rank form.

Write $\hat{\mathbf{P}} = \hat{\mathbf{V}} \hat{\mathbf{V}}^\top$ with $\hat{\mathbf{V}} \in \mathbb{R}^{D \times k}$, $\hat{\mathbf{V}}^\top \hat{\mathbf{V}} = \mathbf{I}_k$. Set $\mathbf{Y} = \tilde{\Delta} \hat{\mathbf{V}}$, $\tilde{\mathbf{H}}_f = \hat{\mathbf{V}}^\top \mathbf{H}_f$. Then $\tilde{\Delta} \hat{\mathbf{P}} = \mathbf{Y} \hat{\mathbf{V}}^\top$, $\|\mathbf{Y} \hat{\mathbf{V}}^\top\|_F^2 = \|\mathbf{Y}\|_F^2$, and (12) reduces to

$$J = \|\mathbf{Y} \tilde{\mathbf{H}}_f - \mathbf{R}\|_F^2 + \lambda \|\mathbf{Y}\|_F^2, \quad (16)$$

a strictly convex ridge problem with unique minimizer

$$\mathbf{Y}^* = \mathbf{R} \tilde{\mathbf{H}}_f^\top (\tilde{\mathbf{H}}_f \tilde{\mathbf{H}}_f^\top + \lambda \mathbf{I}_k)^{-1}. \quad (17)$$

The inverse is a genuine $k \times k$ inverse since $\lambda > 0$. Substituting $\hat{\mathbf{P}} = \hat{\mathbf{V}} \hat{\mathbf{V}}^\top$ into $\mathbf{A}$ yields $\mathbf{A} = \hat{\mathbf{V}} \mathbf{S} \hat{\mathbf{V}}^\top$ with $\mathbf{S} = \tilde{\mathbf{H}}_f \tilde{\mathbf{H}}_f^\top + \lambda \mathbf{I}_k \succ \mathbf{0}$, so $\mathbf{A}^+ = \hat{\mathbf{V}} \mathbf{S}^{-1} \hat{\mathbf{V}}^\top$ and (15) gives

$$\tilde{\Delta}^* = \mathbf{R} \tilde{\mathbf{H}}_f^\top \hat{\mathbf{V}} \mathbf{S}^{-1} \hat{\mathbf{V}}^\top. \quad (18)$$

Hence the assembled operator

$$\mathbf{M}^* = \tilde{\Delta}^* \hat{\mathbf{P}} = \mathbf{Y}^* \hat{\mathbf{V}}^\top \quad (19)$$

agrees with the reduced-form answer.

Gauge freedom. J depends on $\tilde{\Delta}$ only through $\tilde{\Delta} \hat{\mathbf{P}}$, so any $\tilde{\Delta}^* + \mathbf{N}$ with $\mathbf{N} \hat{\mathbf{P}} = \mathbf{0}$ is also optimal. The pseudoinverse selects the minimum-norm representative; the operator $\mathbf{M}^*$ that the contract acts through is gauge-invariant and unique. In practice we implement (19) via the $k \times k$ inverse in (17) for numerical stability.

B Hyperparameter Sensitivity

Tables 8–10 report the full per-scalar sweeps on TOFU forget05 summarized in Sec. 4.5.2; each varies one scalar with the other two held at the operating point ($p=0.75$, $\lambda=10$, $\alpha = -2.0$), and ‘best α ’ denotes the α that maximizes FQ.

λ	best α	FQ	MU
0.3	-1.5	0.000	0.556
0.5	-1.5	0.000	0.585
1	-1.5	0.068	0.606
3	-1.5	0.866	0.621
5	-1.5	0.628	0.623
10	-2.0	0.965	0.622
30	-2.5	0.545	0.623
50	-2.0	0.466	0.627
100	-3.0	0.628	0.625
300	-3.0	0.142	0.628

Table 8: λ sweep on TOFU forget05 ($p=0.75$).

α	FQ	MU
-1.6	0.545	0.625
-1.8	0.713	0.623
-1.9	0.924	0.622
-2.0	0.965	0.622
-2.1	0.924	0.620
-2.2	0.924	0.617
-2.3	0.965	0.614
-2.5	0.713	0.607

Table 9: α curve on TOFU forget05 ($p=0.75$, $\lambda=10$).

p	best α	FQ	MU
0.40	-2.2	0.793	0.624
0.60	-2.0	0.394	0.625
0.75	-2.0	0.965	0.622
0.85	-2.1	0.713	0.613
0.90	-1.8	0.545	0.614

Table 10: p sweep on TOFU forget05 ($\lambda=10$). MU is essentially flat (0.61–0.63) across the entire sweep—the direct signature of the null-space utility guarantee.

C Cross-Backbone Evaluation

To examine transfer across model families, we apply Nullify to Qwen3-8B (Yang et al., 2025) on TOFU forget10. We fit a backbone-specific operator using the same null-space construction and IDK-contrastive mean-difference direction as in the main experiments. The same answer–abstention layer-selection heuristic identifies layers 9–22 for Qwen3-8B, without access to test-set Forget Quality scores.

Backbone	Method	FQ $\uparrow$	MU $\uparrow$	F-RL (target: Retrain)	R-RL $\uparrow$
Qwen3-8B	Original	< 0.001	0.603	1.000	0.999
	Retrain [†]	1.000	0.596	0.434	1.000
	Nullify	0.641	0.574	0.385	0.801
Llama-2-7B-chat Nullify (main)		0.581	0.620	0.410	0.950

Table 11: Cross-backbone results on TOFU forget10. F-RL/R-RL denote forget- and retain-set ROUGE-L; Retrain[†] is the target reference.

Table 11 shows that Nullify raises Qwen3-8B’s FQ from < 0.001 to 0.641 and reduces forget-set ROUGE-L from 1.000 to 0.385, within 0.049 of the Retrain reference (0.434). Aggregate MU remains within 0.022 of Retrain (0.574 vs. 0.596), although retain-set ROUGE-L decreases to 0.801. These results provide a replication on a second model family: the construction and selection proce-

dure transfer, while the observed forgetting–utility tradeoff differs across the two backbones tested.

D Case Study

Table 12 shows representative forget05 outputs. On forget-set queries about the author Moshe Ben-David, the Original model answers from memorized SFT knowledge, whereas the Nullify-steered model returns an epistemic non-answer (“This information is not provided...”). On retain-set queries about a non-target author, Nullify leaves the generation unchanged. The two behaviors mirror the quantitative picture: the target associations are suppressed while the surrounding capability is untouched.

Question	Original output	Nullify-steered output
<i>Forget set — Moshe Ben-David</i>		
Has Moshe Ben-David received any awards for Islamic literature?	Yes, the Distinguished Author Award in Islamic Literature.	<i>This information is not provided in the given text.</i>
Are Moshe Ben-David’s works fundamental reads of the Islamic genre?	Yes, <i>Miracles & Merits of Allah’s Messenger</i> and others are seminal.	<i>This information is not provided in the reference.</i>
<i>Retain set — Chukwu Akabueze</i>		
What genre does Chukwu Akabueze specialize in?	Biography.	<i>(unchanged)</i>
Has Chukwu Akabueze won any awards?	Yes, the prestigious Nigerian Writers Award among others.	<i>(unchanged)</i>

Table 12: Representative case study on TOFU forget05 (Llama-2-7B-chat-hf). On forget-set queries Nullify steers the model from verbatim recall to abstention; on retain-set queries the output is unchanged.