

Is Memorization Context-Sensitive? Prefix-Based Extraction Beyond Isolated Prefixes

Ali Satvaty¹ Narjes Sharafi¹ Jirui Qi¹ Suzan Verberne² Fatih Turkmen¹

¹University of Groningen ²Leiden University

Correspondence: a.satvaty@rug.nl

Abstract

Large language models (LLMs) can expose memorized training sequences under prefix-based extraction: given a prefix from a training example, the model may assign high probability to the original continuation. In deployed systems, however, prefixes are rarely evaluated in isolation. They often appear together with instructions, retrieved documents, or other task-specific context, as in retrieval-augmented generation (RAG). This motivates examining whether contextual conditioning mitigates memorization or merely changes the set of memorized samples that become extractable. We investigate this issue through paired item-level measurements of probabilistic suffix extraction. For each prefix-suffix pair, we score the target suffix under an empty prompt and under retrieved contexts of varying relevance, across three open-weight instruction-tuned models. We find that context does not simply erase memorization. Instead, extractable memorization consists of a context-robust core and a context-sensitive boundary. Many samples that are extractable without context remain extractable under the retrieved context, especially as the prefix length increases. At the same time, context mainly affects marginal samples near the extraction threshold: it suppresses some exposures, but also enables new ones that are missed by prefix-only evaluation. These findings qualify the view that RAG reduces memorization risk. Context can lower aggregate extraction by suppressing boundary cases, yet robustly extractable samples persist, and context-enabled extractability remains security-relevant.¹

when memorized content can be reproduced at inference time (Carlini et al., 2019; Henderson et al., 2023; Mueller et al., 2024; Freeman et al., 2024). The memorized content may be extracted when an adversary supplies a matching prefix of the original sequence (Carlini et al., 2021, 2023; Hartmann et al., 2023; Satvaty et al., 2024; Tirumala et al., 2022). Prefix-suffix extraction attacks measure this behavior directly: given a prefix from a training sequence, the model may assign unusually high probability to the corresponding suffix, enabling verbatim recovery of memorized text.

In many deployed systems, a model is not prompted with an isolated prefix, but with additional text such as retrieved documents, instructions, or task-specific context (Wei et al., 2022; Gao et al., 2023). This is especially relevant for retrieval-augmented generation (RAG), where external documents are attached to the input of the model (Lewis et al., 2020; Borgeaud et al., 2022). Intuitively, one might expect such context to reduce memorization-based leakage: if the model is grounded in retrieved evidence, it may rely less on parametric memory. This intuition has been explored in recent work suggesting that RAG can reduce leakage (Zeng et al., 2024). However, it remains unclear how contextual conditioning changes prefix-based extraction at the level of individual samples.

In this work, we study how extra context affects memorization under the prefix-suffix extraction setting. For each prefix-suffix sample, we measure the probability assigned to the target suffix when the prefix is evaluated alone and when it is evaluated with different types of preceding context. We consider semantically related retrieved context, and irrelevant context, and compare all conditions through paired item-level measurements. This lets us examine not only whether aggregate extraction changes under context, but also how context changes the set of samples that become extractable.

1 Introduction

Language models can memorize parts of their training data, raising privacy and copyright concerns

¹The code is available at: <https://github.com/alistvt/context-sensitive-memorization>

Our results show that contextual conditioning does not simply remove memorization. Instead, extractable memorization has a context-robust core of samples that remain extractable regardless of the surrounding context, and a context-sensitive boundary consisting of samples near the extraction threshold whose exposure status flips when context is added. Many core samples remain extractable under retrieved contexts, especially as the prefix length increases. At the same time, context changes the exposure status of marginal samples: some prefix-suffix pairs are suppressed by context, while others become extractable only after context is added. This distinction matters for interpreting claims that retrieval reduces memorization. We find that context can lower aggregate extraction by suppressing boundary cases, but this aggregate reduction should not be interpreted as eliminating memorization risk. Robustly extractable samples remain extractable across contexts, and context-enabled samples are missed by prefix-only evaluation. Thus, contextual conditioning is better understood as reshaping the exposure boundary rather than erasing memorized content.

Taken together, our contributions are:

- We formulate prefix–suffix memorization under contextual conditioning and conduct paired item-level comparisons across empty, relevant, and irrelevant contexts.
- We show that extractable memorization is composed of a high-confidence core that persists across contexts and weaker extractions that are more sensitive to surrounding context, with robustness increasing as prefix length grows.
- We show that aggregate reductions in exposure can hide security-relevant sample-level behavior, including robust exposures that persist across contexts and examples that become extractable only after context is added.

2 Background and Related Work

2.1 Memorization in LLMs

Prior work has shown that LLMs can reproduce verbatim training examples under extraction attacks, where an adversary prompts the model and searches generated outputs for memorized training text (Nasr et al., 2025; Kim et al., 2023; Carlini et al., 2021).

Definition 1 (Verbatim suffix extraction). *Let (p, s) denote a prefix–suffix pair from a text sequence, where p is given to the model and s is the target continuation. A suffix s is verbatim extracted if a model generates s exactly after being prompted with p .*

Later studies examined how memorization changes with model scale, data duplication, training dynamics, and language (Carlini et al., 2023; Biderman et al., 2023; Kiyomaru et al., 2024; Tirumala et al., 2022; Satvaty et al., 2025). Our work focuses on verbatim, extractable memorization: given a prefix from a training sequence, we study whether the model assigns high probability to the corresponding suffix.

2.2 Measuring Memorization

Memorization is commonly measured through prefix–suffix extraction: given a prefix p from a training sequence, the model is tested on whether it reproduces the corresponding suffix s . Much prior work relies on greedy decoding, treating a sample as memorized only when the decoded continuation matches the training suffix (Satvaty et al., 2024). While intuitive, this binary view can be brittle: a suffix may receive high probability even if it is not produced by a single greedy decode.

Recent work, therefore, measures memorization probabilistically, using the probability assigned to the target suffix rather than only exact decoded matches (Hayes et al., 2025).

Definition 2 (Probabilistic extraction). *A suffix s is probabilistically extractable if the model assigns high probability to s conditioned on p . We measure this by the suffix log-probability*

$$\ell(p, s) = \log P_M(s \mid p). \quad (1)$$

Under contextual conditioning, we instead measure

$$\ell^c(p, s) = \log P_M(s \mid c, p), \quad (2)$$

where c is the surrounding context.

We adopt this view because it gives a continuous per-sample score and supports paired comparisons across contexts. For each prefix–suffix sample, we can measure the suffix probability when the prefix is evaluated alone and when it is evaluated with surrounding context.

Prior work has largely measured extractable memorization from isolated prefixes, where the model is prompted only with a prefix and evaluated

on whether it assigns high probability to the original continuation. Closest to our setting is work on privacy in retrieval-augmented generation, which studies whether contextual prompts can reveal sensitive information and finds that retrieval can reduce some forms of leakage. Our setting differs from this line of work in two ways. First, we study verbatim prefix-suffix exposure rather than entity-level disclosure, which lets us evaluate whether the model assigns probability mass to a specific target continuation. Second, our unit of analysis is the individual prefix-suffix pair: we track whether the same sample remains exposed, is suppressed, or becomes newly exposed when context is added. This sample-level view is necessary because aggregate leakage rates can decrease even when a robust subset of exposed samples remains extractable.

3 Problem Formulation

Memorization in language models is commonly evaluated using a prefix-suffix setup: given a prefix from a training sequence, the model is tested on how likely it is to reproduce the corresponding suffix. Most such evaluations implicitly treat memorization as a property of the pair (p, s) : if the model assigns high probability to the suffix s after seeing the prefix p , then the sample is considered memorized. In this work, we ask whether this view remains valid when the same prefix is preceded by additional context, i.e. retrieved documents.

Prefix-suffix samples. Let M be a language model with parameters θ . We consider a collection of samples

$$\mathcal{D} = \{(p_i, s_i)\}_{i=1}^n, \quad (3)$$

where p_i is a prefix and s_i is the corresponding target suffix from the same source sequence. The standard prefix-only extraction setting evaluates the model’s likelihood of s_i conditioned only on p_i .

Contextualized extraction. We generalize this setting by introducing a context variable c_i . The model is then evaluated on the likelihood of the same suffix s_i conditioned on both the context and the prefix:

$$P_\theta(s_i \mid c_i, p_i). \quad (4)$$

The context may be empty, semantically related to the prefix, or intentionally irrelevant. Importantly, the target prefix-suffix pair (p_i, s_i) remains fixed; only the preceding context changes. This lets us

isolate whether memorization is stable under contextual conditioning.

Context conditions. We study the extraction rate of suffix, when the prefix is preceded by three context conditions:

C.1 Empty context ($c = \emptyset$): no context is preceded.

C.2 Relevant context ($c = \text{rel}$): the model receives the nearest retrieved document from the retrieval collection.

C.3 Irrelevant context ($c = \text{irr}$): the model receives the farthest retrieved document, used as a low-relevance context.

These context conditions allow us to ask whether memorization is a property of the prefix-suffix pair alone, or whether it depends on the surrounding text in which the prefix is evaluated. In particular, we use them to distinguish between memorized samples that remain extractable across contexts and samples whose exposure changes when contextual information is introduced. We refer to the former as the context-robust core (samples exposed under all context conditions) and to the latter as the context-sensitive boundary (samples whose membership in the exposed set $E_c(\tau)$ depends on c , which we show in Section 5.2 are concentrated near the threshold τ).

4 Experiments

We evaluate memorization under *contextual conditioning*: the same prefix-suffix sample is scored either in isolation or in the presence of an additional document context. This setup (more details in Appendix F) lets us isolate how context changes prefix-based extraction while keeping the target prefix and suffix fixed.

Our evaluation has three components: a set of prefix-suffix samples used for memorization measurement, a document collection from which contextual documents are selected, and a retrieval procedure that determines which document is placed before the prefix. For each sample, we compare the empty-context condition against two contextualized conditions: semantically related and irrelevant contexts. All comparisons are paired at the item level: for a given sample, only the preceding context changes.

Models. We evaluate three open-weight instruction-tuned models: **Llama-3-8B-Instruct** (Grattafiori et al., 2024), **Falcon-7B-Instruct** (Almazrouei et al., 2023), and **OLMo-2-1124-7B-Instruct** (Walsh et al., 2025). The choice of these models is mainly motivated by the transparency of their pretraining data, which makes them suitable for controlled memorization experiments over known data sources.

Memorization Dataset. We use prefixes sampled from the CommonCrawl subset of the Pile (Pile-CC) (Gao et al., 2020), which reflects general web text. Specifically, we evaluate on a subset of 50,000 prefixes drawn uniformly at random from Pile-CC, without any filtering or pre-selection for memorization. This sampling strategy avoids selection bias toward highly extractable content and follows the standard practice in memorization measurement studies (Hayes et al., 2025; Lasy et al., 2025), which quantify memorization over sequences sampled directly from the pretraining corpus rather than over curated sets of known-memorized examples. As a result, our exposure sets emerge naturally from the model’s behavior on a representative sample of training data, rather than from a regime in which extraction is easiest. We evaluate prefix lengths $\{32, 64, 128\}$ tokens with a fixed suffix length of 32 tokens.

Retriever and retrieval collection. We use **E5 dense retriever** (Wang et al., 2024) for document retrieval. We use this retriever to choose the most relevant and the least relevant documents for each of the prefixes. The retrieval collection is a mixture of three subsets datasets of the Pile (Gao et al., 2020): StackExchange, PubMed, and Wikipedia subsets were used; for a total collection of 67,655 documents. This mixture is designed to cover distinct text genres (community Q&A, biomedical abstracts, and encyclopedic prose) so that the retrieved context is not topically biased toward any single domain.

Measurement framework We adopt the probabilistic extraction approach of Hayes et al. (2025). Rather than measuring memorization only through exact greedy continuation, we estimate how likely the model is to generate the target suffix when conditioned on a prefix, with or without additional context. This allows us to study memorization as a graded likelihood signal instead of a binary generation outcome.

For each sample i , we split a text sequence into a prefix x_i^{pre} and a suffix x_i^{suf} . Given a context condition c , we measure the suffix log-probability:

$$\ell_i^c = \log P_\theta \left(x_i^{\text{suf}} \mid c, x_i^{\text{pre}} \right), \quad (5)$$

where P_θ is the language model. The context c may be empty, semantically related, or irrelevant. We denote the corresponding log-probabilities as:

$$\ell_i^\emptyset, \quad \ell_i^{\text{rel}}, \quad \ell_i^{\text{irr}}, \quad (6)$$

where $\ell_i^\emptyset$ is the suffix log-probability under the empty-context condition, ℓ_i^{rel} under the nearest retrieved context, and ℓ_i^{irr} under the farthest retrieved context.

To analyze whether a sample is extractable under a given condition, we define an exposed set at threshold τ :

$$E_c(\tau) = \{i : \ell_i^c > \tau\}. \quad (7)$$

This formulation lets us compare memorization across contexts at both the aggregate and sample levels. At the aggregate level, we compare the distributions of ℓ_i^c across context conditions. At the sample level, we analyze how membership in $E_c(\tau)$ changes when context is added. In particular, we distinguish between samples that remain exposed across contexts, samples that are suppressed by context, and samples that become exposed only under contextual conditioning.

5 Results

The results support a consistent picture: retrieved context does not erase prefix-based memorization, but reshapes the exposure boundary. We first show that prefix length dominates contextual variation: longer prefixes make suffix likelihoods and exposed sets increasingly stable across contexts. We then show that this stability comes from a robust core of samples exposed under multiple contexts, while context-induced changes are concentrated near the exposure threshold. Finally, we separate the generic effect of adding context from the semantic effect of retrieving a related document.

We report four observations, which we describe in the following subsections.

Throughout this section, we use the measurement framework defined in Section 4. Recall that $\ell_i^\emptyset$, ℓ_i^{rel} , and ℓ_i^{irr} denote the suffix log-probability of sample i under empty context, relevant retrieved




Figure 1: Suffix log-probability distributions by prefix length. Dashed lines show empty-context prompting, while solid lines show prompting with retrieved context. Across all models, longer prefixes substantially increase suffix likelihood. The gap between empty and contextualized prompting is largest for shorter prefixes and becomes smaller as prefix length increases, suggesting that longer prefixes make memorization more context-independent.




Figure 2: Jaccard overlap between exposed sets at $\tau = -16$. Each cell reports the overlap between two exposure sets for a given model and prefix length. Exposure-set overlap increases sharply with prefix length across all models and context comparisons. This indicates that longer prefixes make the set of extractable samples more stable across contexts.

context, and irrelevant retrieved context, respectively. We define the exposed set under condition c as

$$E_c(\tau) = \{i : \ell_i^c > \tau\}. \quad (8)$$

We use $\tau = -16$ in the main analysis² and report threshold-sensitivity results in the appendix A.

5.1 Observation 1: Longer prefixes make memorization increasingly context-independent

We first ask whether contextual conditioning changes prefix-based memorization measurements, and whether this effect depends on prefix length. Figure 1 shows the distribution of suffix log-probability scores for different prefix lengths under empty and retrieved-context prompting. Across all

three models, increasing the prefix length from 32 to 64 and 128 tokens shifts the distribution toward higher suffix likelihoods. This confirms that prefix length is a dominant factor in extraction: longer prefixes provide a stronger conditioning signal and make the memorized continuation more likely.

Importantly, the difference between empty-context and contextualized prompting becomes smaller as the prefix length increases. For short prefixes, contextual conditioning can noticeably shift the suffix likelihood distribution. For longer prefixes, the empty-context and contextualized curves become much closer. This suggests that longer prefixes make extraction increasingly *context-independent*: the model relies more on the prefix itself and less on the preceding context.

We quantify this stability using Jaccard overlap

²Equivalent to 0.5 per-token drop of logprob for 32 tokens of suffix.

between exposed sets:

$$J(E_a, E_b) = \frac{|E_a \cap E_b|}{|E_a \cup E_b|}. \quad (9)$$

Figure 2 shows that exposed-set overlap increases consistently with prefix length for all three models. This trend holds for empty versus relevant/irrelevant context and irrelevant versus relevant context.

This provides a direct answer to our motivating question: memorization is not uniformly context-independent, but it becomes increasingly context-independent as the prefix becomes more informative. Short-prefix extraction is more context-sensitive, while long-prefix extraction is more stable across contextual conditions.

5.2 Observation 2: Strongly exposed samples persist across contexts, while weaker exposures are context-sensitive

The previous result shows that exposure sets become more stable with longer prefixes. We now ask whether this stability comes from a shared robust core of memorized samples or whether the context completely reshuffles which samples are exposed.

Figure 3 decomposes exposed samples into four groups: samples exposed under all three conditions, samples exposed without context but suppressed by context, samples enabled by relevant context, and samples enabled only by irrelevant context. The dominant category is robust exposure which consistently increases with the prefix length for all three models.

This indicates that context does not erase memorization. A large fraction of exposed samples remain extractable under empty, relevant, and irrelevant contexts. The robust core becomes especially pronounced as the prefix length increases, consistent with the Jaccard-overlap results in Figure 2.³

Meanwhile, Figure 3 also shows that context-sensitive samples are non-negligible. Some samples are removed from the exposed set when context is added, while others become exposed only under contextual conditioning. To understand where these changes occur, we examine the distance of each sample from the empty-context exposure threshold:

$$m_i = |\ell_i^\emptyset - \tau|. \quad (10)$$

³See Table 2 in Appendix C for additional results.

We then compute how often samples flip exposure status after context is added.

We find that context-induced flips are highly concentrated near the exposure boundary (details in Figure 6 in Appendix B). Samples in the closest bin to the threshold have the highest flip rates, while samples far from the threshold almost never flip. This pattern appears across models and prefix lengths. As the prefix length increases, the relevant and irrelevant context curves also become more similar, especially near the boundary, indicating that longer prefixes reduce both the number of flips and the dependence of flips on the type of retrieved context.

Together, these results suggest that memorization of strongly exposed samples remains stable across contexts, whereas less memorized samples are more sensitive to preceding context.

5.3 Observation 3: Context mostly suppresses, but context-enabled extraction remains security-relevant

The exposure decomposition also allows us to revisit prior claims that retrieval or contextualization reduces memorization. Our results are consistent with this claim at the aggregate level: context more often suppresses exposure than enables it. In Figure 3, the suppressed category is generally larger than the context-enabled categories.

However, the security interpretation is more subtle. A reduction in average exposure does not imply that memorization risk has been removed. First, many samples remain robustly exposed across all contexts, as shown by the green bars in Figure 3. Second, context-enabled exposure is consistently nonzero. That is, some samples that are not extractable under empty-context prompting become extractable when preceded by some context.⁴

This matters for evaluating RAG and other context-augmented systems. Our results show that contextualization can act as a filter: it suppresses some marginal examples, preserves a robust core, and occasionally enables new exposure. Context changes the exposure boundary. This reconciles the observation that RAG can reduce aggregate memorization with the persistence of robustly extractable samples.

⁴Appendix H shows several examples of such cases.




Figure 3: Exposure-set decomposition at $\tau = -16$. Green bars show samples exposed under all three conditions. Purple bars show samples exposed without context but suppressed by context. Red and peach bars show samples that become exposed only under relevant or irrelevant context. Robust exposure dominates across models and grows substantially with prefix length, indicating a context-robust memorization core.

Model	Prefix	n	Mean G	Median G	Mean S	Median S	% $S < 0$
Llama-3-8B-Instruct	32	318	0.52	-0.34	-3.35	-1.24	70.1
	64	593	0.52	-0.06	-1.11	-0.12	59.7
	128	858	0.05	-0.03	-0.32	-0.04	57.5
OLMo-2-1124-7B-Instruct	32	131	-0.42	-0.23	-2.05	-0.75	62.6
	64	390	-0.32	-0.06	-0.04	0.06	47.2
	128	645	0.14	-0.01	-0.30	0.01	47.3
Falcon-7B-Instruct	32	69	-0.94	-1.02	-1.70	-0.64	60.9
	64	321	0.56	0.10	-0.23	-0.13	56.1
	128	617	0.42	0.19	-0.16	-0.06	54.3

Table 1: Generic and semantic context effects for exposed or boundary samples. We report the number of boundary samples n , the generic context effect $G = \ell^{\text{irr}} - \ell^{\emptyset}$, and the semantic effect $S = \ell^{\text{rel}} - \ell^{\text{irr}}$. The semantic effect is generally negative, especially for shorter prefixes, indicating that relevant context tends to suppress extraction relative to irrelevant context near the exposure boundary. The generic effect is more model-dependent.

5.4 Observation 4: Relevant context adds a semantic effect, but generic context also matters

Finally, we ask whether the effect of context is caused by semantic relevance or by the generic presence of additional context. We decompose the effect into two quantities:

$$G_i = \ell_i^{\text{irr}} - \ell_i^{\emptyset}, \quad (11)$$

$$S_i = \ell_i^{\text{rel}} - \ell_i^{\text{irr}}. \quad (12)$$

Here, G_i captures the generic effect of adding irrelevant context, while S_i captures the additional semantic effect of replacing irrelevant context with relevant retrieved context.

Table 1 (also shown as violin plots in Figure 11 in Appendix G.1) shows this decomposition for exposed samples (if a sample exceeds the threshold in any of the three prefix scenarios, it is included). The semantic effect S is often negative, especially

for shorter prefixes. This suggests that relevant retrieved context often suppresses extraction relative to irrelevant context.

The generic effect G , however, is more model-dependent. In some settings, irrelevant context suppresses extraction; in others, it has little effect or even increases likelihood. This indicates that contextual effects are not purely semantic. Adding context itself can perturb the conditional distribution, while semantic relevance can add an additional suppressive bias for boundary samples.

Summary. Our results show that memorization is neither fully context-independent nor fully context-dependent. Instead, exposed memorization consists of a high-confidence core that persists across contexts and a weaker set of extractions that is more sensitive to surrounding text. Longer prefixes enlarge the persistent core, while context mainly affects lower-confidence samples. Thus, contextualization can reduce aggregate extraction by sup-




Figure 4: Jaccard overlap between exposed sets under relevant and irrelevant retrieved context in a fixed instruction-framed setting. Exposure-set overlap increases with prefix length across all models.

pressing weaker extractions, but it does not eliminate robustly extractable memorization and can also enable new exposure. Item-level analysis of suffix log-probabilities under relevant and irrelevant context is available in Appendix G.2.

5.5 Ablation analysis

Choice of memorization threshold The probabilistic extraction framework assigns each item a continuous suffix log-probability score rather than a binary memorized/non-memorized label. For threshold-based analyses, we use $\tau = -16$ as the exposure threshold. This choice is intentionally less strict than only counting very high-confidence extractions, allowing us to capture weaker memorized samples that may still be relevant for contextual exposure. Appendix A gives a security interpretation of this threshold in terms of adversary sampling budgets and shows that our conclusions are stable across thresholds spanning five orders of magnitude of extraction probability.

Instruction-Framed Contextualization We repeat part of our analysis under an instruction-framed prompt. We find that the Jaccard overlap between exposed sets under relevant and irrelevant retrieved contexts is already moderate for prefix length 32 and increases substantially with prefix length in all three models (Figure 4). This suggests that under instruction-framed prompting, retrieval choice still affects some boundary cases, but most exposed samples overlap between context types (see Appendix D for more quantitative results).

Effect of Chat Templates In our experiments we consider working without the chat templates, since we try to mainly measure the effect of context preceding prefix. We notice that experimenting with a setting where we place the prefix inside a full chat template requires a somewhat different evalua-

tion setup and introduces a different measurement regime: For the sequence (p, s) that appeared in training, the model is no longer asked to continue p with s , but instead to generate s after an assistant tag. We find that this has a substantial effect: across all models and prefix lengths, adding the chat template substantially lowers measured memorization. The implication is that chat-template formatting makes the results harder to interpret by mixing the effect of preceding context with a different response-formatting regime. More details are in Appendix E.

6 Discussion

Applicability to real-world systems Our setup deliberately isolates the effect of retrieved context on memorization by controlling the chat template, the retriever, and the collection. This isolation does not narrow the applicability of the findings: the core mechanism we study – adding a retrieved document to the prompt of an instruction-tuned model – is the same operation that real-world RAG systems perform. Additional components of production pipelines (prompt rewriting, multi-turn dialogue, output filtering, post-hoc safety classifiers) operate around this core operation rather than replacing it. The conclusion that memorized items remain extractable under retrieval, and that retrieval surfaces items the LLM alone does not, therefore carries over to systems built on top of the same retrieval-and-prompting pattern.

Memorization as a proxy for leakage We measure targeted (prefix-suffix) memorization instead of leakage, because leakage itself does not afford a fair comparison between conditions: leakage can occur inadvertently during benign use, and it can be elicited by deliberate extraction attacks, so two systems with identical memorization profiles may yield very different leakage rates depending on the attack regime they are tested under. The probabilistic memorization metric factors this confound out: it captures the underlying tendency of the model to assign non-zero probabilities to a memorized continuation. This probabilistic memorization effect can lead to both inadvertent and adversarial leakage and is therefore a neutral measurement. Items whose memorization is preserved in both plain-LLM and RAG conditions therefore remain equally leakable in the operational sense, even if the specific leakage rate observed in any given deployment will depend on the specific attack model.

7 Conclusion

We studied whether prefix-based memorization remains unchanged when the prefix is evaluated with surrounding context. Our results show that contextual conditioning does not simply remove memorization. Across three instruction-tuned models, many extractable samples remain exposed under related and irrelevant contexts, especially as prefix length increases. Context-induced changes are concentrated near the exposure threshold, while samples far from the threshold are largely stable.

These findings nuance the claim that retrieval reduces memorization. Context can reduce aggregate extraction by suppressing boundary cases, but robustly exposed samples remain, and some samples become extractable only after context is added. Thus, context should be viewed less as a memorization shield and more as a filter that reshapes which samples are exposed. Future work should extend these analyses to additional datasets and experimental settings.

Limitations

Our experiments focus on open-weight models from three families, Llama-3, OLMO-2, and Falcon, at approximately the 10B-parameter scale, and use a randomly sampled subset of the CommonCrawl portion of Pile-CC as prefix data. Although we do not evaluate the largest open-weight models or closed APIs, the models studied here are already large enough to exhibit substantial memorization behavior and to support meaningful analysis of extraction dynamics. Evaluating larger models could further clarify how absolute memorization rates change with scale, but larger models are not necessary for establishing our main qualitative finding: memorized continuations remain largely context-independent across diverse prompting conditions. Similarly, domains outside Pile-CC, such as code, biomedical text, or copyrighted creative writing, may show different absolute memorization rates. Nevertheless, CommonCrawl-derived text is widely used in memorization studies, spans diverse sources and writing styles, and appears across the pre-training corpora of the model families we evaluate. This makes it a suitable basis for cross-model comparison, and the consistency of our findings across model families suggests that domain variation is unlikely to overturn the central conclusion.

Our probabilistic extraction scores are computed with temperature $T = 1$ and top- $p = 1$. This

setting preserves the model’s original probability distribution and avoids truncating suffix tokens, ensuring that every sample receives a finite and comparable memorization score. We also report retrieval-augmented results using the E5 dense retriever under both nearest and farthest retrieval, reflecting common real-world RAG settings. Preliminary experiments suggest that replacing E5 with other lexical or dense retrievers has only a limited effect on memorization, but a broader retriever sweep remains an important direction for future work. Other decoding or retrieval choices may affect surface-level generations, yet they are unlikely to change the core probabilistic comparison studied here.

Finally, we evaluate multiple prefix lengths, $\{32, 64, 128\}$, with a fixed suffix length of 32. Longer suffixes may lead to different quantitative patterns because token-level probability gaps can compound over longer continuations. A systematic sweep over suffix length is therefore left to future work.

Ethical Considerations

Our prefixes are drawn from a publicly available corpus (Pile-CC); we do not target private or proprietary training data, closed API models, or deployed systems. Our quantitative results are reported as aggregate metrics. For qualitative analysis we include a limited number of illustrative examples in the appendix, consisting of prefix-suffix pairs and their retrieved contexts drawn from Pile-CC; these are already public web text, and we do not release the full set of per-example extraction outputs. We release our code to support reproducibility. Our findings argue against treating RAG as a defense for memorization-based leakage and motivate defense efforts targeted at parametric memory itself.

Acknowledgements

This publication is part of the project LESSEN with project number NWA.1389.20.183 of the research program NWA ORC 2020/21 which is (partly) financed by the Dutch Research Council (NWO).

We would like to thank KPN for hosting part of this research. Part of this work was carried out by Narjes during a research internship at KPN, and we thank Gianluigi Bardelloni for his supervision and support.

References

- Ebtesam Almazrouei, Hamza Alobeidli, Abdulaziz Alshamsi, Alessandro Cappelli, Ruxandra Cojocaru, Mérouane Debbah, Étienne Goffinet, Daniel Hesslow, Julien Launay, Quentin Malartic, Daniele Mazzotta, Badreddine Noune, Baptiste Pannier, and Guilherme Penedo. 2023. The falcon series of open language models. *arXiv preprint arXiv:2311.16867*.
- Stella Biderman, Usven Prashanth, Lintang Sutawika, Hailey Schoelkopf, Quentin Anthony, Shivanshu Purohit, and Edward Raff. 2023. Emergent and predictable memorization in large language models. *Advances in Neural Information Processing Systems*, 36:28072–28090.
- Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George van den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, Diego de Las Casas, Aurelia Guy, Jacob Menick, Roman Ring, Tom Hennigan, Saffron Huang, Loren Maggiore, Chris Jones, Albin Cassirer, and 9 others. 2022. Improving language models by retrieving from trillions of tokens. In *International conference on machine learning*, pages 2206–2240. PMLR.
- Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramèr, and Chiyuan Zhang. 2023. Quantifying memorization across neural language models. In *The Eleventh International Conference on Learning Representations*.
- Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. 2019. The secret sharer: Evaluating and testing unintended memorization in neural networks. In *28th USENIX security symposium (USENIX security 19)*, pages 267–284.
- Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom B. Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. Extracting training data from large language models. In *30th USENIX security symposium (USENIX Security 21)*, pages 2633–2650.
- Joshua Freeman, Chloe Rippe, Edoardo DeBenedetti, and Maksym Andriushchenko. 2024. [Exploring memorization and copyright violation in frontier llms: A study of the new york times v. openai 2023 lawsuit](#). In *Neurips Safe Generative AI Workshop 2024*.
- Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. 2020. The Pile: An 800GB dataset of diverse text for language modeling. *arXiv preprint arXiv:2101.00027*.
- Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Meng Wang, and Haofen Wang. 2023. Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:2312.10997*.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Valentin Hartmann, Anshuman Suri, Vincent Bind-schädler, David Evans, Shruti Tople, and Robert West. 2023. Sok: Memorization in general-purpose large language models. *arXiv preprint arXiv:2310.18362*.
- Jamie Hayes, Marika Swanberg, Harsh Chaudhari, Itay Yona, Iliia Shumailov, Milad Nasr, Christopher A. Choquette-Choo, Katherine Lee, and A. Feder Cooper. 2025. [Measuring memorization in language models via probabilistic extraction](#). In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 9266–9291, Albuquerque, New Mexico. Association for Computational Linguistics.
- Peter Henderson, Xuechen Li, Dan Jurafsky, Tatsunori Hashimoto, Mark A Lemley, and Percy Liang. 2023. Foundation models and fair use. *Journal of Machine Learning Research*, 24(400):1–79.
- Siwon Kim, Sangdoo Yun, Hwaran Lee, Martin Gubri, Sungroh Yoon, and Seong Joon Oh. 2023. Propile: Probing privacy leakage in large language models. *Advances in Neural Information Processing Systems*, 36:20750–20762.
- Hirokazu Kiyomaru, Issa Sugiura, Daisuke Kawahara, and Sadao Kurohashi. 2024. [A comprehensive analysis of memorization in large language models](#). In *Proceedings of the 17th International Natural Language Generation Conference*, pages 584–596, Tokyo, Japan. Association for Computational Linguistics.
- Ilya Lasy, Peter Knees, and Stefan Woltran. 2025. [Understanding verbatim memorization in LLMs through circuit discovery](#). In *Proceedings of the First Workshop on Large Language Model Memorization (L2M2)*, pages 83–94, Vienna, Austria. Association for Computational Linguistics.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474.
- Felix B Mueller, Rebekka Görges, Anna K Bernzen, Janna C Pirk, and Maximilian Poretschkin. 2024. LLMs and memorization: On quality and specificity of copyright compliance. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 7, pages 984–996.

- Milad Nasr, Javier Rando, Nicholas Carlini, Jonathan Hayase, Matthew Jagielski, A. Feder Cooper, Daphne Ippolito, Christopher A. Choquette-Choo, Florian Tramèr, and Katherine Lee. 2025. [Scalable extraction of training data from aligned, production language models](#). In *The Thirteenth International Conference on Learning Representations*.
- Ali Satvaty, Suzan Verberne, and Fatih Turkmen. 2024. Undesirable memorization in large language models: A survey. *arXiv preprint arXiv:2410.02650*.
- Ali Satvaty, Anna Visman, Daniel Seidel, Suzan Verberne, and Fatih Turkmen. 2025. [Memorization is language-sensitive: Analyzing memorization and inference risks of LLMs in a multilingual setting](#). In *Proceedings of the First Workshop on Large Language Model Memorization (L2M2)*, pages 106–126, Vienna, Austria. Association for Computational Linguistics.
- Kushal Tirumala, Aram H. Markosyan, Luke Zettlemoyer, and Armen Aghajanyan. 2022. Memorization without overfitting: Analyzing the training dynamics of large language models. In *Advances in Neural Information Processing Systems*.
- Evan Pete Walsh, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Shane Arora, Akshita Bhagia, Yuling Gu, Shengyi Huang, Matt Jordan, Nathan Lambert, Dustin Schwenk, Oyvind Taffjord, Taira Anderson, David Atkinson, Faeze Brahman, Christopher Clark, Pradeep Dasigi, Nouha Dziri, Allyson Ettinger, and 23 others. 2025. [2 OLMo 2 furious \(COLM’s version\)](#). In *Second Conference on Language Modeling*.
- Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2024. Multilingual e5 text embeddings: A technical report. *arXiv preprint arXiv:2402.05672*.
- Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V Le. 2022. [Finetuned language models are zero-shot learners](#). In *International Conference on Learning Representations*.
- Shenglai Zeng, Jiankun Zhang, Pengfei He, Yiding Liu, Yue Xing, Han Xu, Jie Ren, Yi Chang, Shuaiqiang Wang, Dawei Yin, and Jiliang Tang. 2024. [The good and the bad: Exploring privacy issues in retrieval-augmented generation \(RAG\)](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4505–4524, Bangkok, Thailand. Association for Computational Linguistics.

A Threshold Choice and Sensitivity Analysis

Our main analysis defines exposed samples using a fixed threshold $\tau = -16$. For a 32-token suffix, this corresponds to an average per-token log-probability of -0.5 , i.e., a mean per-token probability of $e^{-0.5} \approx 0.61$, and a total suffix probability of $e^{-16} \approx 1.1 \times 10^{-7}$. In the discoverable-extraction sense of [Hayes et al. \(2025\)](#), an adversary sampling at temperature 1 recovers the exact suffix of a sample at this threshold with probability ≥ 0.5 within on the order of 10^6 – 10^7 generation attempts—a realistic budget for automated extraction attacks. We deliberately choose this permissive operating point rather than one that counts only near-deterministic extractions, because our analysis targets the exposure *boundary*, and a stricter threshold would truncate precisely the marginal region where context-induced changes concentrate.

To test whether our conclusions depend on this particular cutoff, we repeat the exposure-set decomposition across multiple thresholds. Specifically, for each context condition c , we define the exposed set as

$$E_c(\tau) = \{i : \ell_i^c > \tau\}, \quad (13)$$

and vary τ over the range $[-22, -10]$, corresponding to adversary budgets from $\sim 10^9$ down to $\sim 10^4$ generation attempts, i.e., from extremely powerful to cheap extraction attacks. Figure 5 shows that the qualitative structure of the exposed sets is stable across thresholds. As expected, stricter thresholds reduce the absolute fraction of exposed samples. However, the relative pattern remains consistent: robust exposure is the dominant category, especially for longer prefixes, while suppressed and context-enabled samples remain smaller but nonzero. This indicates that our main conclusions are not artifacts of a single threshold choice. Importantly, the context-enabled categories persist across thresholds. Although they are much smaller than the robust exposed set, their presence shows that context-induced exposure is not caused solely by an arbitrary cutoff.

B Flip Analysis

In the main text, we show that contextual conditioning can change whether a sample is classified as exposed. Here, we further analyze where these flips occur relative to the exposure threshold. For each sample, we compute its distance from the

threshold sensitivity of exposure-set decomposition




Figure 5: Threshold sensitivity of the exposure-set decomposition. We vary the exposure threshold τ and report the percentage of samples in each category. Robust exposure remains the dominant category across thresholds, especially for longer prefixes. Suppressed and context-enabled samples remain smaller but persist across threshold choices, showing that the exposure-set decomposition is not an artifact of a single cutoff.

empty-context threshold,

$$m_i = |\ell_i^\emptyset - \tau|, \quad (14)$$

and measure how often the sample changes exposure status after adding context.

Figure 6 shows that context-induced flips are concentrated near the threshold. Samples close to the boundary have the highest flip rates, while samples far from the boundary almost never flip. This supports the interpretation that context primarily affects marginal samples rather than strongly exposed or strongly non-exposed samples.

C Exposure Set Analysis

In addition to the exposure-set decomposition in the main text, we report the pairwise overlap between exposed sets under different context conditions. For each condition c , we define the exposed set as

$$E_c(\tau) = \{i : \ell_i^c > \tau\}. \quad (15)$$

We then compute the Jaccard overlap between exposed sets,

$$J(E_a, E_b) = \frac{|E_a \cap E_b|}{|E_a \cup E_b|}. \quad (16)$$

Table 2 reports the overlap between empty, relevant, and irrelevant context at $\tau = -16$. Across




Figure 6: Context-induced flip rate as a function of distance from the empty-context exposure threshold. The flip rate is highest for samples close to the threshold and approaches zero for samples far from the threshold. This indicates that context-induced changes are boundary-local: context primarily affects marginal samples rather than robustly exposed or strongly non-exposed samples.

all models, the overlap increases substantially with prefix length. This supports the main result that longer prefixes make the set of exposed samples more consistent across contextual conditions.

D Instruction-Framed Contextualization

As an additional robustness check, we repeat part of our analysis under a fixed instruction-framed prompt. Because this setting changes both the prompting format and the role structure, we do not interpret it as an isolated measurement of system-prompt effects. Instead, we use it to test whether our main conclusions about exposure stability continue to hold in a chat-style setting.

Figure 4 shows the Jaccard overlap between exposed sets under relevant and irrelevant retrieved contexts, with the instruction framing held fixed. The overlap is already moderate for prefix length

32 and increases substantially with prefix length across all three models. For example, the overlap rises from 0.69 to 0.93 for Llama, from 0.69 to 0.92 for OLMo, and from 0.74 to 0.96 for Falcon as the prefix length increases from 32 to 128 (Table 3). This mirrors the main-paper trend: longer prefixes make exposure increasingly stable across contextual conditions.

Figure 7 further decomposes the exposed sets into samples shared by relevant and irrelevant retrieval, samples exposed only under relevant retrieval, and samples exposed only under irrelevant retrieval. In all models, the shared category dominates and grows substantially with prefix length, while the relevant-only and irrelevant-only categories remain comparatively small. This suggests that under instruction-framed prompting, retrieval choice still affects some boundary cases, but most

Model	Prefix	$J(E_{\emptyset}, E_{\text{rel}})$	$J(E_{\emptyset}, E_{\text{irr}})$	$J(E_{\text{irr}}, E_{\text{rel}})$	$ E_{\emptyset} $	$ E_{\text{rel}} $	$ E_{\text{irr}} $
Meta-Llama-3-8B-Instruct	32	0.715	0.721	0.689	116	95	106
	64	0.880	0.901	0.890	384	387	384
	128	0.912	0.933	0.932	659	672	665
OLMo-2-1124-7B-Instruct	32	0.677	0.637	0.656	87	74	80
	64	0.840	0.867	0.854	325	317	319
	128	0.912	0.911	0.909	582	592	580
Falcon-7B-Instruct	32	0.725	0.725	0.796	44	44	44
	64	0.905	0.898	0.951	285	279	275
	128	0.952	0.950	0.967	571	567	568

Table 2: Exposure-set Jaccard overlap at $\tau = -16$. $E_{\emptyset}$, E_{rel} , and E_{irr} denote the exposed sets under empty, relevant, and irrelevant context, respectively. Across all models, exposed-set overlap increases with prefix length, indicating that longer prefixes make exposure less sensitive to contextual variation.

exposed samples belong to a shared robust core. The corresponding semantic effect S under grounding instructions is shown in Figure 8 and summarized in Table 4.

Overall, these results reinforce the main conclusion of the paper: memorization is characterized by a robust exposed core and a context-sensitive boundary, and the robust core becomes increasingly dominant as the prefix length grows.

E Effect of Chat Templates

Our main experiments focus on the standard prefix-suffix extraction setting, which has been the dominant setup in prior memorization studies. In this setting, the suffix is scored as a direct continuation of the prefix. A natural alternative would be to place the prefix inside a full chat template. However, this introduces a different measurement regime.

As illustrated in Figure 9, adding a chat template inserts an assistant-role boundary between the prefix and the scored suffix. As a result, for the sequence (p, s) that appeared in training, the model is no longer asked to continue p with s , but instead to generate s after an assistant tag. In other words, you would measure the extraction rate of $(p, \text{<assistant>, } s)$, which is a different value. This effect has also been noted by Nasr et al. (2025).

Figure 10 shows that this effect is large: across all models and prefix lengths, adding the chat template substantially lowers measured memorization. Because this shift is much larger than the contextual effects we study in the main paper, including chat-template formatting would make the results harder to interpret by mixing the effect of preceding context with a different response-formatting regime. For this reason, the main paper isolates the

effect of preceding context and does not include chat-template structure in the core analysis.

F Detailed Experimental Setup

This appendix lists implementation details for reproducibility.

- Sampling: top- $p = 1.0$, temperature $T = 1.0$ (scoring setting; no actual sampling required since we compute log-probabilities directly).
- Log-probability thresholding: across all plots the threshold is -16 .
- Suffix length: 32 tokens.
- Context window: model maximum.

G Additional Visualizations

G.1 Semantic Relevance Effect

Figure 11 shows the distributions of G and S for exposed samples (related to section 5.4). The generic effect is model-dependent: irrelevant context can suppress extraction in some settings, while having little effect or increasing extraction in others. In contrast, the semantic relevance effect is often negative, especially for shorter prefixes. This suggests that related context can add a suppressive effect, although this effect weakens as prefix length increases.

G.2 Relevant versus Irrelevant Context

Figure 12 compares suffix log-probabilities under relevant and irrelevant context at the item level. Each point corresponds to one prefix-suffix sample. Points near the diagonal indicate samples whose extraction likelihood is similar under both context types, while deviations from the diagonal indicate samples that are more sensitive to the choice of retrieved context.

Model	Prefix	$J(E_{\text{rel}}, E_{\text{irr}})$	$ E_{\text{rel}} $	$ E_{\text{irr}} $	n_{total}
Meta-Llama-3-8B-Instruct	32	0.694	95	115	49393
	64	0.882	387	394	49393
	128	0.927	672	673	49292
OLMo-2-1124-7B-Instruct	32	0.693	74	75	49393
	64	0.845	317	325	49393
	128	0.920	592	585	49306
Falcon-7B-Instruct	32	0.740	44	43	49393
	64	0.911	279	277	49393
	128	0.958	567	561	49392

Table 3: Jaccard overlap between exposed sets under relevant and irrelevant context in the instruction-framed setting. E_{rel} and E_{irr} denote the exposed sets under relevant and irrelevant retrieved contexts, respectively. The overlap increases with prefix length across all models, indicating that longer prefixes make exposure increasingly stable across retrieved-context choices.




Figure 7: Exposure decomposition for relevant versus irrelevant retrieval under a fixed instruction-framed setting. Most exposed samples are shared between the two retrieval conditions, and the shared robust set grows with prefix length.

H Examples of Recalled and Forgotten Samples in Presence of Context

Tables 5 and 6 show several examples of items that become un-extractable (forgotten) and extractable (recalled) in the presence of the retrieved context.

run_it_no_tags_k1 — semantic gain $S = \text{chat+near} - \text{chat+rand}$ [boundary samples]




Figure 8: Semantic with system prompt

Model	Prefix	n_{total}	n_{boundary}	Mean S	Median S	% $S < 0$
Meta-Llama-3-8B-Instruct	32	49393	124	-0.998	-0.241	56.5
	64	49393	415	-0.496	-0.108	54.9
	128	49292	698	-0.115	0.005	49.6
OLMo-2-1124-7B-Instruct	32	49393	88	0.880	-0.215	52.3
	64	49393	348	-0.303	-0.012	51.1
	128	49306	613	-0.063	-0.006	50.9
Falcon-7B-Instruct	32	49393	50	-0.463	-0.199	50.0
	64	49393	291	0.062	-0.089	57.0
	128	49392	576	0.037	0.016	48.3

Table 4: Semantic context effect on exposed samples when adding grounding instructions. S denotes the change in suffix log-probability when replacing the comparison context with the relevant retrieved context. The effect is generally inclined towards negative, but less pronounced than the one without the grounding instructions (table 1).




Figure 9: Illustration of plain prefix–suffix scoring versus chat-template scoring. In the plain setting, the suffix is scored as a direct continuation of the prefix. In the chat-template setting, an assistant-role boundary is inserted between the prefix and suffix, changing the continuation being measured.




Figure 10: Effect of chat-template formatting on measured memorization under empty context. Solid lines show plain prefix–suffix scoring, while dashed lines show chat-template scoring. The large drop under chat-template scoring shows that template formatting has a strong effect on the measurement.

Table 5: Forgotten items: sequences that are extracted verbatim by the model without retrieved context, but no longer under context. We show one example per model, restricted to items whose log-probability gap satisfies $|\log p_{\text{ctx}} - \log p_{\text{no-ctx}}| \geq 5$ and where exactly one of the two log-probabilities falls below -16 , so that the pair straddles the extraction threshold.

Example 1	
Model	tiiuae/falcon-7b-instruct
Prefix len	32 tokens (suffix len: 32)
Log-probs	$\log p_{\text{no-ctx}} = -8.680$ $\log p_{\text{ctx}} = -25.069$ $\Delta = -16.389$
Prefix	Cambridge, ID Fertilizers
	YP - The Real Yellow PagesSM - helps you find the right local businesses to meet your specific needs. Search
Suffix	results are sorted by a combination of factors to give you a set of choices in response to your search criteria. These factors are similar to those you might use to
Context	Q: cms for software project hosting I want to make a site where I present my own open source software project. It should look like http://www.schillmania.com/projects/soundmanager2/ for example. Are there any CMS (PHP) with this kind of functionality preconfigured? What I need is code highlighting, code documentation, download statistic, bug tracker, discussion forum, donation button etc. I think if I take a standard CMS like wordpress or drupal I'll spend ages to find the right modules and setup the whole thing. I will also accept answers that recommend a useful drupal distribution or a list of wordpress plugins.. A: Have you tried looking at Ohloh or the CMS Matrix? Some of the CMS's descriptions in there haven't been updated in a long time though. (I would have posted it as a comment but I can't just yet and I thought it would still be interesting for you to know.)




Figure 11: Semantic versus generic context effects for exposed samples. Blue distributions show $G = \ell^{\text{irr}} - \ell^{\emptyset}$, the effect of adding irrelevant context. Red distributions show $S = \ell^{\text{rel}} - \ell^{\text{irr}}$, the additional effect of replacing irrelevant context with relevant context. Relevant context is often suppressive, especially for shorter prefixes, but generic contextual perturbation also contributes and is more model-dependent.

run_it_no_tags_k1 — log P(prefix): plain+mixnocc nearest (x) vs farthest (y) [e5, k=1]




Figure 12: Item-level scatter plot of suffix log-probabilities under relevant and irrelevant context. The x-axis shows log-probability under relevant retrieved context, and the y-axis shows log-probability under irrelevant context. Points near the diagonal indicate similar extraction likelihood under both context types; deviations from the diagonal indicate context-sensitive samples.

Table 5: Forgotten items (continued).

Example 2	
<i>Model</i>	meta-llama/Meta-Llama-3-8B-Instruct
<i>Prefix len</i>	32 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -2.858$ $\log p_{\text{ctx}} = -49.586$ $\Delta = -46.728$
<i>Prefix</i>	Tucson craigslist adult - tour cheap About me: Hello My name is Melly. These factors are similar to those you might use to determine which business
<i>Suffix</i>	to select from a local Yellow Pages directory, including proximity to where you are searching, expertise in the specific services or products you need, and comprehensive business information to
<i>Context</i>	Q: Plotting More than 2 Factors Suppose I ran a factor analysis & got 5 relevant factors. Now, I want to graphically represent the loading of these factors on the variables. Can anybody please tell me how to do it. I can do using 2 factors. But can't able to do when number of factors are more than 2. The 2 factor plotting is given in "Modern Applied Statistics with S", Fig 11.13. I want to create similar graph but with more than 2 factors. Please find the snap of the Fig mentioned above: X & y axes are the 2 factors. Regards, Ari A: Beware: not the answer you are looking for and might be incorrect also, this is my subjective thought. I think you run into the problem of sketching several dimensions on a two dimension screen/paper. I would say there is no sense in plotting more factors' or PCs' loadings, but if you really insist: display the first two (based on eigenvalues) or create only 2 factors. Or you could reduce dimension by other methods also (e.g. MDS). Displaying 3 factors' loadings in a 3 dimensional graph would be just hardly clear, not to think about more factors. UPDATE: I had a dream about trying to be more ontopic :)

Table 5: Forgotten items (continued).

Example 3	
<i>Model</i>	allenai/OLMo-2-0425-1B-Instruct
<i>Prefix len</i>	64 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -6.081$ $\log p_{\text{ctx}} = -17.202$ $\Delta = -11.121$
<i>Prefix</i>	Menu Notice: Trying to get property of non-object in /var/www/ipo-book.com/public_html/wp-content/themes/ipo/functions.php on line 600 Notice: Trying to get property of non-object in /var/www/ipo-book.com/public_html/wp-content/themes/ipo/functions.php on line 602
<i>Suffix</i>	Notice: Trying to get property of non-object in /var/www/ipo-book.com/public_html/wp-content/themes/ipo/functions.php on line 604 Notice
<i>Context</i>	Q: ????? segmentation error ????? ?????????? ????? ?? ??????? ? ????????? ??????? ?????? segmentation error, ??? ?? ?????????? ??? ??? ?????????? ? BookContact.txt Sergey_Kotomkin:154:8(777)777-77-77: Maks_Loxin:84:8(952)748-41-70: Andrey_Serov:14:8(952)747-42-70: Aleks_Sagin:14:8(952)509-08-07: Dimon_Wanow:17:8(785)124-47-45: ??? ??? #include <stdio.h> //??? printf, fprintf, fopen, fclose #include <string.h> #include <stdlib.h> #define FNAME "BookContact.txt" //????????? ??? ???? ?????? void startMenu(){ //? ??? ????????? ?????????? ???? printf("-----Main Menu-----\n"); printf("This is the phone book of the company 'YptRemont'\n");

Table 5: Forgotten items (continued).

Example 4	
<i>Model</i>	allenai/OLMo-2-1124-7B-Instruct
<i>Prefix len</i>	32 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -7.669$ $\log p_{\text{ctx}} = -20.781$ $\Delta = -13.112$
<i>Prefix</i>	Personal Income and Outlays: September 2009 Personal income decreased \$0.1 billion, or less than 0.1 percent, and disposable personal
<i>Suffix</i>	income (DPI) decreased \$0.2 billion, or less than 0.1 percent, in September, according to the Bureau of Economic Analysis.
<i>Context</i>	Since the completion of the Trans @-@ Alaska Pipeline System in 1977 , the government of the state of Alaska has been reliant on taxes paid by oil producers and shippers . Prior to 1976 , Alaska 's personal income tax rate was 14 @. @ 5 percent — the highest in the United States . The gross state product was \$ 8 billion , and Alaskans earned \$ 5 billion in personal income . Thirty years after the pipeline began operating , the state had no personal income tax , the gross state product was \$ 39 billion , and Alaskans earned \$ 25 billion in personal income . Alaska moved from the most heavily taxed state to the most tax @-@ free state .

Table 6: Recalled items: sequences that are not extracted by the model alone, but become extractable once retrieved context is prepended. We show one example per model, restricted to items whose log-probability gap satisfies $|\log p_{\text{ctx}} - \log p_{\text{no-ctx}}| \geq 5$ and where exactly one of the two log-probabilities falls below -16 , so that the pair straddles the extraction threshold.

Example 1	
<i>Model</i>	tiiuae/falcon-7b-instruct
<i>Prefix len</i>	64 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -20.885$ $\log p_{\text{ctx}} = -5.609$ $\Delta = +15.277$
<i>Prefix</i>	Game seems to be working just fine, but trainer is not. I see that there might have been some patches? How do i check my game version? Trainer wont work without the right version haha so need to check wich version i need to get my game too.
<i>Suffix</i>	Game seems to be working just fine, but trainer is not. I see that there might have been some patches? How do i check my game version? Trainer wont work without the right version haha so
<i>Context</i>	Special abilities and actions are controlled by the Force Gauge , an energy meter which determines how long special skills can be active . Once drained , the skill cannot be activated until the meter refills , which it does during battles . Four skills can be equipped for each character . After battles , characters earn Enhancement Points (EP) , which can be used to strengthen equipped armor , weapons and accessories , instead of using Gald (the in @-@ game currency) as with previous Tales titles . EP can be transferred between weapons . An optional battle arena was added in the PSP version of the game with both single @-@ player and multiplayer matches : in both modes , players need to defeat an enemy team (either AI @-@ controlled enemies or an opposing team) within a time limit .

Table 6: Recalled items (continued).

Example 2	
<i>Model</i>	meta-llama/Meta-Llama-3-8B-Instruct
<i>Prefix len</i>	32 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -21.231$ $\log p_{\text{ctx}} = -8.811$ $\Delta = +12.420$
<i>Prefix</i>	Thou still unravish' d bride of quietness, Thou foster-child of silence and slow time, Sylvan historian, who canst thus
<i>Suffix</i>	express A flowery tale more sweetly than our rhyme: What leaf-fring'd legend haunts about thy shape Of deities or mortals,
<i>Context</i>	Q: Word construction like "philanthropist" but regarding silence instead of humankind? What would be the Latin/English term for somebody who loves silence? Featuring phil(e) as pre- or suffix. Like ... silenciophile? That maybe makes "some sense" - but I've no idea if it is correct or if there would be a canonical neologism. A: Latin freely adopted Greek words, including compounds, but in general did not freely create compounds with both Latin and Greek elements, like the modern creation "sociology", and similarly with your suggested form "silenciophile" (better "silentiophile"). If you want to create a compound with "-phile", then "hesychophile" would be better, consisting of Greek elements only. — You made me very low @-@ spirited last night , by your manner of talking — You are my only friend — the only person I am intimate with . — I never had a father , or a brother — you have been both to me , ever since I knew you — yet I have sometimes been very petulant . — I have been thinking of those instances of ill @-@ humour and quickness , and they appeared like crimes . Yours sincerely , Mary . — being desirous of rendering it easy for the future , have made it my stud [...]

Table 6: Recalled items (continued).

Example 3	
<i>Model</i>	allenai/OLMo-2-0425-1B-Instruct
<i>Prefix len</i>	128 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -16.620$ $\log p_{\text{ctx}} = -8.394$ $\Delta = +8.226$
<i>Prefix</i>	Model Method - Questions and Answers Question posted by Yvonne from Sri Lanka: Grade/Level: 4th Question solved by Model Method: 900 people attended a party. 1/4 of the males and 1/7 of the females were children. the number of male and female adults were the same. how many women were there at the party? Answer: Step 1: This question involves the Equal Concept. Since 1/4 of the males were children, then 3/4 of the males must be adults. We draw 3 boxes to represent the total number of male adults and 1
<i>Suffix</i>	box to represent the total number of male children. Step 2: Since 1/7 of the females were children, then 6/7 of the
<i>Context</i>	Q: Inclusion-Exclusion Principle for basic combinatorics problem... How many ways are there to pick five people for a committee if there are six (different) men and eight (different) women and the selection must include at least one man and one woman? I know to solve this with very basic combinatorial analysis (though I know the principle is also basic). We find the total people we can choose for the committee and proceed with cases: 1 where we have all men on the committee, 1 where we have all women on the committee and then we subtract the two cases from our total. This gives us $\\$14 \choose 5 - \{8 \choose 5\} - \{6 \choose 5\}.$ How would I compute for Inclusion-Exclusion Principle, though? I've no idea where to begin with it other drawing a venn diagram and labeling set M and W... A: You have more-or-less done it already. For $\\$i \in \{0,1,\ldots\}$, let $\\$a_i$ be the number of committees with $\\$i$ absent genders. We include $\\$a_0 = \binom{14}{5}$. We exclude $\\$a_1 = \binom{8}{5} + \binom{6}{5}$. We include $\\$a_2 = 0$. We exclude $\\$a_3 = 0$.

Table 6: Recalled items (continued).

Example 4	
<i>Model</i>	allenai/OLMo-2-1124-7B-Instruct
<i>Prefix len</i>	64 tokens (suffix len: 32)
<i>Log-probs</i>	$\log p_{\text{no-ctx}} = -28.025$ $\log p_{\text{ctx}} = -3.848$ $\Delta = +24.177$
<i>Prefix</i>	%PDF-1.2 %âãÏÓ 1 0 obj<>endobj 2 0 obj<>endobj 3 0 obj<>endobj 4 0 obj<>endobj 5 0 obj<>endobj 6 0 obj<>endobj 7
<i>Suffix</i>	0 obj<>endobj 8 0 obj<>endobj 9 0 obj<>endobj 10 0 obj<>endobj 11
<i>Context</i>	Q: Does anybody use Pancake? MathJax $\begin{aligned} a_1 &= \alpha_1 + \alpha_2 + \dots + \alpha_n, a_2 = \alpha_1 \alpha_2 + \alpha_1 \alpha_3 + \dots + \alpha_{n-1} \alpha_n \\ &\quad \vdots \end{aligned}$ Delete a_1 in the above, then that could be shown well. $\begin{aligned} a_1 &= \alpha_1 + \alpha_2 + \dots + \alpha_n, a_2 = \alpha_1 \alpha_2 + \alpha_1 \alpha_3 + \dots + \alpha_{n-1} \alpha_n \\ &\quad \vdots \end{aligned}$ http://hypergroups.pancakeapps.com/Test/test.txt Of course they can show well in Math.SE $\begin{aligned} a_1 &= \alpha_1 + \alpha_2 + \dots + \alpha_n, a_2 = \alpha_1 \alpha_2 + \alpha_1 \alpha_3 + \dots + \alpha_{n-1} \alpha_n \\ &\quad \vdots \end{aligned}$ — Q: ????? ???? "?????????" ?????? ??? ?????? ???, ?? ?????? ?? ???? 2 ??????, ?????? ??? ?????? ? ??????????????. ?????? ?????? ?? 2 ?????????? "div" ? "div2" - ?????????????? ?? ? ? id ??? ??????. — Q: Order the growth rate from slowest to fastest I am relatively new to Big-O notation and I came across this question: Sort the following functions by order of growth from slowest to fastest - Big-O Notation. For each pair of adjacent functions in your list, please write a sentence describing why it is or [...]