

Multilingual Safety Alignment via Self-Distillation

Ruiyang Qin*
Tongji University
2432008@tongji.edu.cn

Qingzhuo Wang*
Tongji University
2534123@tongji.edu.cn

Dongrui Liu
Shanghai AI Laboratory
liudongrui@pjlab.org.cn

Qiang Li
Tongji University
qli@tongji.edu.cn

Zhihua Wei
Tongji University
zhihua_wei@tongji.edu.cn

Wen Shen†
Tongji University
wenshen@tongji.edu.cn

Abstract

Large language models (LLMs) exhibit severe multilingual safety misalignment: they possess strong safeguards in high-resource languages but remain highly vulnerable to jailbreak attacks in low-resource languages. Current safety alignment methods generally rely on high-quality response data for each target language, which is expensive and difficult to generate. In this paper, we propose a cross-lingual safeguard transfer framework named **Multilingual Self-Distillation (MSD)**. This framework transfers an LLM’s inherent safety capabilities from high-resource (*e.g.*, English) to low-resource (*e.g.*, Javanese) languages, overcoming the need for response data in any language. Our framework is flexible and can be integrated with different self-distillation strategies. Specifically, we implement two concrete methods—on-policy MSD and off-policy MSD—both of which enable effective cross-lingual safety transfer using only multilingual queries. Furthermore, we propose **Dual-Perspective Safety Weighting (DPSW)**, a divergence measure to optimize the distillation objective. By jointly considering the perspectives of both the teacher and the student, DPSW adaptively increases the penalty weights on safety-critical tokens while reducing the weights on non-critical tokens. Extensive experiments on representative LLMs across diverse multilingual jailbreak and utility benchmarks demonstrate that our method consistently achieves superior multilingual safety performance. Notably, it generalizes effectively to more challenging datasets and unseen languages while preserving the model’s general capabilities.

WARNING: This paper may contain content that is offensive and harmful.

1 Introduction

Large language models (LLMs) have emerged as powerful worldwide applications, enabling users from diverse linguistic and cultural communities to benefit from AI developments [Touvron et al., 2023, Grattafiori et al., 2024, Team et al., 2024, Yang et al., 2025a]. However, recent studies reveal a severe safety misalignment across different languages. That is, LLMs exhibit robust safety behaviors in high-resource languages (*e.g.*, English), but their safeguards often fail in low-resource languages (*e.g.*, Javanese, Swahili) [Deng et al., 2024, Wang et al., 2023a, Shen et al., 2024, Yong et al., 2025]. This multilingual safety misalignment undermines the overall reliability of LLMs, underlining a critical demand for methods of robust cross-lingual safety alignment.

To enhance multilingual safety, some studies rely on representation engineering [Wang et al., 2025] or activation steering [Zhang et al., 2026]. However, these training-free methods often exhibit weak

*Wang and Qin contributed equally to this work and agree that the order of their names may be exchanged as useful to highlight their contributions in individual professional pursuits.

†Corresponding author.




Figure 1: The MSD framework leverages self-distillation within the same LLM p_θ to transfer inherent safety capabilities from high-resource (Teacher) to low-resource (Student) languages. This response-free method bridges the cross-lingual safety gap while preserving the model’s general capabilities.

generalization across diverse datasets. Alternatively, recent research has sought to transfer safety capabilities from high-resource languages (typically English) to other languages via cross-lingual alignment [Zhang et al., 2024, Zhao et al., 2024, 2025, Bu et al., 2026]. These methods generally depend on Supervised Fine-Tuning (SFT) or Preference Optimization (PO), both of which require substantial high-quality response data for training. However, generating high-quality response data is expensive and difficult, particularly for low-resource languages. Therefore, there is an urgent need for a response-free approach capable of transferring safeguards from high-resource to low-resource languages while maintaining robust generalization capabilities.

To this end, we introduce **Multilingual Self-Distillation (MSD)**, a cross-lingual safeguard transfer framework based on self-distillation. This framework is designed to transfer an LLM’s inherent safety capabilities from high-resource to low-resource languages, bridging the linguistic gap in safety alignment. As illustrated in Figure 1, both the teacher and the student are initialized from the same LLM. The teacher leverages the model’s strong safeguards in high-resource languages to conduct safe reasoning and generate harmless responses, thereby guiding the student, which represents the model’s weak safety capabilities in low-resource languages. Crucially, this framework **requires no external response data** for multilingual alignment. Besides, our framework is flexible and can be integrated with various self-distillation strategies, including off-policy self-distillation [Yang et al., 2024, Yuan et al., 2024] and on-policy self-distillation [Zhao et al., 2026, Shenfeld et al., 2026].

The proposed MSD provides the teacher with additional information to elicit strong safety capability from the high-resource language, while providing the student with only the target low-resource input query. For clarity, we utilize English as the high-resource language for the following illustration. The teacher’s additional information includes the input query in English (in the dataset) and a Chain-of-Thought (CoT) instruction, prompting the teacher to conduct reasoning in English and generate the final answer in the target low-resource language. In this way, the MSD does not require any response data; it relies solely on multilingual queries from existing datasets to provide alignment signals.

Furthermore, to differentiate the importance of individual tokens during safe response generation, we introduce a divergence measure termed **Dual-Perspective Safety Weighting (DPSW)**. DPSW adaptively increases the penalty on safety-critical tokens while reducing the penalty on uninformative ones. By jointly evaluating the confidence levels of both the teacher and the student, DPSW adjusts the penalty weight of each individual token. This divergence measure prioritizes safety-critical tokens and filters out non-critical tokens, thereby ensuring a more precise and robust cross-lingual alignment.

We evaluate the performance of our framework under both off-policy and on-policy self-distillation settings. Extensive experiments across diverse models and benchmarks demonstrate that both settings consistently outperform existing baselines, yielding exceptional multilingual safety alignment. Furthermore, our MSD framework exhibits robust generalization to more challenging datasets and out-of-distribution languages, all while effectively preserving the model’s general capabilities.

2 Related Work

Multilingual Safety Alignment. LLMs often exhibit safety vulnerabilities in low-resource languages despite strong safeguards in high-resource ones [Deng et al., 2024, Wang et al., 2023a, Shen et al., 2024, Yong et al., 2025]. Existing alignment methods primarily rely on supervised fine-tuning [Deng et al., 2024, Li et al., 2024, Shen et al., 2024], preference optimization [Rafailov et al., 2023, Ethayarajh et al., 2024, Zhao et al., 2025], or distillation techniques [Zhang et al., 2024, 2025], which all require substantial response data for training. However, generating such high-quality response data across target languages is expensive and prone to translation errors. While recent studies [Bu et al., 2026, Yang et al., 2026b] alleviate the need for low-resource responses, they still depend heavily on English data. Alternatively, training-free methods like representation engineering [Wang et al., 2025] and activation steering [Zhang et al., 2026, Liang et al., 2026] reduce data reliance but suffer from poor cross-dataset generalization and capability degradation [Cao et al., 2025]. In this paper, we propose MSD, a response-free method capable of transferring safeguards from high-resource to low-resource languages while maintaining robust generalization capabilities.

Self-Distillation. Self-distillation serves as a mechanism for self-improvement, enabling models to learn from their own outputs rather than external teachers [Furlanello et al., 2018, Zhang et al., 2019, Yang et al., 2019]. In the LLM era, self-distillation can branch into off-policy and on-policy strategies. Off-policy self-distillation typically generates discrete trajectories as the training data and then fine-tunes the model on them [Askell et al., 2021, Zelikman et al., 2022, Gulcehre et al., 2023, Wang et al., 2023b, Sun et al., 2023, Yang et al., 2024, Yuan et al., 2024]. More recently, on-policy self-distillation (OPSD) instantiates the teacher and the student from the same model under different contexts [Zhao et al., 2026, Hübner et al., 2026]. By equipping teacher with privileged information, OPSD evaluates the student’s own rollouts and provides dense token-level supervision. This paradigm has been extended to continual learning, context internalization, and reasoning compression [Shenfeld et al., 2026, Ye et al., 2026, Sang et al., 2026]. In this paper, we propose a flexible cross-lingual self-distillation framework. It can be integrated with both off-policy and on-policy settings to transfer inherent safety capabilities. Please see Appendix A for a more detailed version of related work.

3 Multilingual Self-Distillation

In this section, we propose Multilingual Self-Distillation (MSD) to bridge the multilingual safety gap in a target LLM. First, Section 3.1 introduces the cross-lingual safeguard transfer framework, specifically designed to transfer inherent safety capabilities from high-resource to low-resource languages. Second, Section 3.2 details **Dual-Perspective Safety Weighting (DPSW)**, a token-level weighting mechanism designed to optimize the distillation process.

3.1 Cross-Lingual Safety Transfer through Self-Distillation

Consider a multilingual jailbreak dataset comprising N samples, denoted as $\mathcal{X} = \{X_i\}_{i=1}^N$, where each sample $X_i = \{x_i^{(1)}, x_i^{(2)}, \dots, x_i^{(M)}\}$ represents a specific harmful query translated across M distinct languages. For clarity, we utilize English as the representative high-resource language for the following illustration. Letting p_θ denote an LLM parameterized by θ , our framework instantiates both the teacher p_T and the student p_S from p_θ by conditioning on different contexts. As shown in Figure 2, given a target low-resource query $x^{\text{tgt}} \in X$ (we omit the sample index i), the student p_S is only provided with the target low-resource query x^{tgt} :

$$p_S(\cdot \mid x^{\text{tgt}}) \triangleq p_\theta(\cdot \mid x^{\text{tgt}}). \quad (1)$$

Conversely, the teacher p_T is provided with additional information, including the query in English $x^* \in X$ (which is uniquely determined by the specific target query x^{tgt}) and a CoT instruction $\mathcal{C}$:

$$p_T(\cdot \mid x^{\text{tgt}}, x^*, \mathcal{C}) \triangleq p_\theta(\cdot \mid x^{\text{tgt}}, x^*, \mathcal{C}). \quad (2)$$

The CoT instruction $\mathcal{C}$ is designed to effectively elicit the model’s internal safe reasoning capability of English. As detailed in Figure 3, the CoT instruction $\mathcal{C}$ explicitly instructs the teacher to reason in English and generate the final response in the target low-resource language to guide the student.

Our MSD framework is flexible and can be integrated with various self-distillation strategies. Specifically, we implement two concrete methods: on-policy MSD and off-policy MSD. During training, for




Figure 2: Workflow of the MSD method. Given a target low-resource query x^{tgt} and the query in English x^* , the student p_S and teacher p_T are instantiated from the same LLM p_θ by conditioning on different contexts. MSD can be integrated with different response sampling strategies $y \sim q(\cdot)$ (e.g., on-policy or off-policy). The distillation is optimized via the DPSW-KL objective, which scales the token-level penalty weight $\tilde{w}_t$ by jointly evaluating the teacher’s weight w_t^T and student’s weight w_t^S .




Figure 3: The teacher prompt template used in the MSD framework.

a given target low-resource query x^{tgt} , the distinction between the on-policy and off-policy settings lies in whether the output sequence y is sampled from the student or the teacher. On-policy MSD trains on output sequences sampled from the student, *i.e.*, $y \sim p_S(\cdot | x^{\text{tgt}})$. Conversely, off-policy MSD trains on output sequences sampled from the teacher, *i.e.*, $y \sim p_T(\cdot | x^{\text{tgt}}, x^*, \mathcal{C})$. To represent both the on-policy and off-policy settings, we introduce a generalized sampling distribution, $q(\cdot)$. In the on-policy setting, $q(\cdot)$ is directly equivalent to the student sampling:

$$q(\cdot) \triangleq p_S(\cdot | x^{\text{tgt}}). \quad (3)$$

In the off-policy setting, $q(\cdot)$ is directly equivalent to the teacher sampling:

$$q(\cdot) \triangleq p_T(\cdot | x^{\text{tgt}}, x^*, \mathcal{C}). \quad (4)$$

Consequently, the generated output sequences across both settings can be generalized as: $y \sim q(\cdot)$. At each generation step t , both the teacher and the student generate next-token distributions over the vocabulary $\mathcal{V}$, yielding $p_S(\cdot | x^{\text{tgt}}, y_{<t})$ for the student and $p_T(\cdot | x^{\text{tgt}}, x^*, \mathcal{C}, y_{<t})$ for the teacher. The overall training objective of the MSD is formulated to minimize the divergence between the student and the teacher across all generated tokens for all samples in the dataset $\mathcal{X}$, defined as:

$$\mathcal{L}(\theta) = \mathbb{E}_{X \sim \mathcal{X}} \left[\mathbb{E}_{x^{\text{tgt}} \sim X} \left[\mathbb{E}_{y \sim q(\cdot)} \left[\frac{1}{L_y} \sum_{t=1}^{L_y} D \left(p_S(\cdot | x^{\text{tgt}}, y_{<t}) \parallel p_T(\cdot | x^{\text{tgt}}, x^*, \mathcal{C}, y_{<t}) \right) \right] \right] \right], \quad (5)$$

where L_y is the length of the output sequence y ; D can be any distribution divergence measure. Here we utilize the reverse Kullback-Leibler divergence. Please see Table 12 in Appendix C for ablation study of different divergence measures. In our optimization process, we restrict gradient updates exclusively to the student p_S . The parameters of the teacher p_T are kept frozen to provide a stable and consistent supervision signal. We conduct comparative experiments analyzing the performance differences between a frozen and an unfrozen teacher, with detailed results presented in Table 8.

3.2 Dual-Perspective Safety Weighting

In Equation (5), the divergence $D(p_S(\cdot) \parallel p_T(\cdot))$ is uniformly averaged across all tokens in the output sequence y . However, in the context of refusal generation, the critical tokens representing the refusal

behavior (e.g., “I cannot answer...”) decisively influence the safety decision of the sequence, whereas other tokens typically contain non-critical information [Jain et al., 2024, Qi et al., 2025, Wang et al., 2026]. Treating all tokens equally weakens the supervision on these key tokens. To address this limitation, we propose **Dual-Perspective Safety Weighting (DPSW)**, a token-level weighting mechanism. The core objective of DPSW is to **adaptively increase the penalty weight for the divergence on safety-critical tokens while reducing the weight on non-critical ones**.

Specifically, we determine the penalty weight of each individual token by jointly considering the predictive confidence from both the teacher’s and the student’s perspectives. At generation step t , let y_t^* denote the token assigned the highest probability by the teacher, i.e., $y_t^* = \arg \max_{y \in \mathcal{V}} p_T(y \mid x^{\text{tgt}}, x^*, \mathcal{C}, y_{<t})$. The penalty weight w_t^T from the teacher’s perspective and the penalty weight w_t^S from the student’s perspective are computed as follows.

Teacher’s Perspective (w_t^T): Shen et al. [2026] observed that models consistently produce high-confidence refusals to harmful requests while exhibiting high entropy when generating potentially dangerous content. Thus, the penalty weight w_t^T is positively correlated with its confidence in generating y_t^* . Building upon this finding, we quantify the teacher’s confidence in outputting critical safety tokens utilizing information entropy. To prevent the entropy from being diluted by the long-tail probabilities of the entire vocabulary, we use a top- K entropy rather than the full-vocabulary entropy. Formally, we first extract the teacher’s top- K token set at step t , denoted as $\mathcal{V}_t^K = \text{TopK}(p_T(\cdot \mid x^{\text{tgt}}, x^*, \mathcal{C}, y_{<t}))$, and renormalize the probabilities within this subset: $\bar{p}_T(v) = \frac{p_T(v)}{\sum_{u \in \mathcal{V}_t^K} p_T(u)}$, $v \in \mathcal{V}_t^K$.

The metric is then defined based on the normalized top- K entropy:

$$w_t^T = 1 - \frac{-\sum_{v \in \mathcal{V}_t^K} \bar{p}_T(v) \log \bar{p}_T(v)}{\log K}. \quad (6)$$

A higher w_t^T indicates that the teacher is highly confident in its generated token.

Student’s Perspective (w_t^S): The penalty weight w_t^S depends on the student’s confidence in the teacher’s optimally chosen token y_t^* . A lower student confidence indicates a more severe disagreement with the teacher’s choice, rendering the student susceptible to generating unsafe responses. We measure the risk of the student disagreeing with the teacher’s safe response by evaluating its confidence in y_t^* . Formally, this metric is defined as:

$$w_t^S = 1 - p_S(y_t^* \mid x^{\text{tgt}}, y_{<t}). \quad (7)$$

This metric captures the likelihood of the student’s tendency for harmful generation. A higher w_t^S indicates a larger deviation from the teacher’s chosen token.

Dual-Perspective Weighting Formulation: By combining these two perspectives, we derive the weight for the t -th token as $w_t = w_t^T \cdot w_t^S$. To maintain training stability and prevent gradient explosion, we normalize these weights across the generated output y , yielding $\tilde{w}_t = L_y \cdot \frac{w_t}{\sum_{j=1}^{L_y} w_j}$.

Finally, DPSW upgrades Equation (5) with the weighting mechanism:

$$\mathcal{L}(\theta) = \mathbb{E}_{X \sim \mathcal{X}} \left[\mathbb{E}_{x^{\text{tgt}} \sim X} \left[\mathbb{E}_{y \sim q(\cdot)} \left[\frac{1}{L_y} \sum_{t=1}^{L_y} \tilde{w}_t \cdot D\left(p_S(\cdot \mid x^{\text{tgt}}, y_{<t}) \parallel p_T(\cdot \mid x^{\text{tgt}}, x^*, \mathcal{C}, y_{<t})\right) \right] \right] \right]. \quad (8)$$

We empirically compare the weights w_t^T and w_t^S assigned to safety-critical versus non-critical tokens. As shown in Table 5, the weights w_t , as well as w_t^T and w_t^S , are consistently higher for safety-critical tokens. This empirically demonstrates that the DPSW mechanism tends to assign higher penalty weights to safety-critical tokens over non-critical ones, which aligns with our purpose.

4 Experiments

4.1 Experimental Setup

Models. We conduct our studies on four representative LLMs: Qwen-2.5-7B-Instruct [Yang et al., 2025b], Qwen-3-8B [Yang et al., 2025a], LLaMA-2-7B-chat [Touvron et al., 2023], and LLaMA-3-8B-Instruct [Grattafiori et al., 2024].

Table 1: Multilingual safety performance on two benchmarks: MultiJail and PKU-SafeRLHF. Evaluation is based on the Attack Success Rate (ASR $\downarrow$). The best and second-best results are highlighted in **bold** and underlined, respectively. Languages marked with an asterisk (*), e.g., IT*, indicate unseen languages that are not included in the training set. Note that the average (Avg.) scores are computed across all ten evaluated languages, including the eight languages presented here alongside English (EN) and Chinese (ZH). Additional results for EN and ZH, as well as evaluations on more models (LLaMA-2-7B-chat and Qwen-2.5-7B-Instruct), are provided in Table 9 of Appendix C.

Methods	MultiJail									PKU-SafeRLHF								
	High		Medium			Low		Avg.		High		Medium			Low		Avg.	
	IT*	VI*	AR	KO*	TH*	BN	SW*	JV*		IT*	VI*	AR	KO*	TH*	BN	SW*	JV*	
Qwen-3-8B																		
Raw	13.97	10.48	12.70	13.33	9.52	22.22	94.92	19.68	21.68	10.60	15.00	13.40	15.40	12.20	21.80	97.20	18.00	22.08
SFT	6.03	4.76	3.81	5.71	<u>2.54</u>	8.89	96.19	35.87	17.08	8.40	10.20	9.20	7.20	5.40	22.60	97.00	16.60	19.00
DPO	8.89	9.84	8.89	10.48	8.89	15.56	94.92	23.17	19.53	8.60	12.00	8.80	9.40	8.20	15.00	97.80	17.00	18.90
rDPO	10.16	7.94	10.79	10.48	7.62	18.10	95.24	23.17	19.65	8.00	10.60	8.60	8.80	7.40	16.60	97.20	15.40	18.70
KTO	8.89	5.71	9.21	12.70	6.98	15.24	95.56	21.27	18.70	7.00	10.00	7.60	8.60	8.80	14.80	97.80	13.00	17.96
ORPO	8.25	10.48	9.52	8.89	7.62	17.78	95.24	20.95	19.14	8.00	10.40	7.60	10.00	8.60	18.00	96.80	15.40	18.88
R-DPO	10.16	10.48	10.16	13.33	7.94	18.73	95.56	26.35	20.57	8.20	11.80	7.80	9.80	7.60	16.20	96.80	15.80	18.84
SimPO	8.89	7.62	8.89	9.84	8.25	18.10	94.29	23.49	19.27	6.80	9.60	7.60	11.20	6.80	18.60	98.20	14.80	18.58
PolyRefuse	15.56	13.02	12.38	17.14	11.11	22.54	94.29	28.89	23.53	11.00	15.20	13.20	13.80	11.80	22.40	97.40	18.20	22.32
Self-Defense	12.38	12.38	11.43	14.92	13.02	17.78	95.56	26.67	22.38	11.20	13.80	13.20	13.00	11.80	22.20	97.60	19.40	22.04
SDRRL	4.44	4.13	<u>3.49</u>	5.08	3.81	8.25	77.14	28.57	14.16	2.20	3.20	1.60	1.80	3.20	5.40	62.00	8.40	9.12
MPO	<u>1.90</u>	<u>1.59</u>	3.81	4.13	1.90	10.79	72.38	22.86	12.44	2.20	2.60	2.20	2.00	1.20	7.00	63.40	7.40	9.08
MSD (Off-Policy)	1.59	2.22	1.90	<u>2.86</u>	2.86	<u>4.76</u>	63.81	<u>17.46</u>	9.90	0.20	<u>1.60</u>	<u>1.80</u>	<u>1.60</u>	1.20	2.00	52.40	<u>3.60</u>	6.54
MSD (On-Policy)	<u>1.90</u>	0.95	3.81	2.22	1.90	3.81	<u>67.62</u>	16.83	<u>10.04</u>	<u>1.00</u>	1.00	2.20	1.20	<u>2.40</u>	<u>2.80</u>	<u>61.80</u>	3.20	<u>7.62</u>
LLaMA-3-8B-Instruct																		
Raw	22.54	13.65	11.43	17.46	10.79	13.97	69.52	39.37	21.21	14.40	5.40	8.40	9.80	9.00	15.40	65.20	22.80	15.82
SFT	3.49	2.86	11.11	4.76	<u>0.63</u>	<u>1.59</u>	50.79	6.35	8.48	<u>0.80</u>	1.40	0.60	5.80	1.00	2.20	33.60	5.60	5.24
DPO	2.86	4.76	9.21	<u>1.90</u>	<u>1.90</u>	<u>1.59</u>	53.33	6.67	8.44	2.60	<u>1.20</u>	5.60	1.20	<u>1.20</u>	5.00	68.20	2.80	8.62
rDPO	4.13	2.54	1.90	<u>1.90</u>	<u>0.63</u>	6.98	29.52	10.79	6.09	5.40	3.20	2.40	6.00	3.60	4.20	28.40	7.20	6.44
KTO	4.13	1.90	6.35	3.17	0.95	<u>1.59</u>	43.81	5.40	6.98	0.40	2.40	3.80	2.20	1.40	<u>1.40</u>	37.20	<u>2.60</u>	5.11
ORPO	3.49	2.86	10.79	10.79	0.32	2.86	77.46	1.27	11.11	2.40	2.40	7.00	9.80	1.40	4.20	72.80	<u>2.60</u>	10.30
R-DPO	2.22	5.40	9.84	2.22	1.90	3.49	57.14	7.30	9.14	<u>0.80</u>	1.40	6.40	1.00	1.60	4.60	65.60	<u>2.60</u>	8.44
SimPO	3.49	2.54	5.71	8.89	0.95	2.86	77.14	7.62	11.08	2.60	2.40	3.60	12.00	2.20	5.20	72.20	<u>2.60</u>	10.36
PolyRefuse	21.59	15.24	13.97	18.73	12.06	16.51	67.30	44.76	22.35	13.20	5.40	8.80	9.80	9.00	15.40	65.20	23.60	15.86
Self-Defense	8.89	12.70	8.89	7.94	42.54	28.25	14.29	6.35	15.56	4.20	5.20	6.00	11.00	38.00	18.00	9.60	9.60	11.06
SDRRL	6.67	11.43	11.43	11.75	7.94	11.75	28.25	30.16	12.61	2.60	3.00	8.80	7.40	5.60	14.20	20.20	11.40	7.70
MPO	7.62	6.67	7.62	6.03	14.92	22.22	14.92	22.22	11.84	1.80	2.20	2.20	2.00	3.80	7.40	11.80	8.20	4.38
MSD (Off-Policy)	2.86	1.27	<u>1.59</u>	<u>1.90</u>	2.22	0.63	<u>6.03</u>	11.11	<u>2.92</u>	2.60	0.60	0.60	0.40	1.00	1.20	<u>3.20</u>	1.80	1.22
MSD (On-Policy)	1.27	<u>1.59</u>	1.27	1.27	1.90	2.22	4.13	<u>5.08</u>	2.03	2.20	<u>1.20</u>	<u>1.00</u>	<u>0.80</u>	1.60	2.40	2.80	3.40	<u>1.78</u>

Languages. We evaluate ten languages from three different resource levels following Deng et al. [2024]: (1) **High**-resource: English (EN), Chinese (ZH), Italian (IT), Vietnamese (VI); (2) **Medium**-resource: Arabic (AR), Korean (KO), Thai (TH); (3) **Low**-resource: Bengali (BN), Swahili (SW), Javanese (JV). Only EN, ZH, AR and BN are included in the training data, and testing is evaluated on all ten languages. In the main experiments, we designate EN as the high-resource language to transfer its strong safety capabilities to lower-resource languages. We also conduct additional experiments by choosing ZH as the high-resource language for Qwen-3-8B, as detailed in Table 7.

Datasets and metrics. For training, we use XSafety [Wang et al., 2023a], which only includes multilingual questions without any responses. To test the generalization power, we employ two more difficult multilingual jailbreak datasets: MultiJail [Deng et al., 2024] and PKU-SafeRLHF [Ji et al., 2025]. For safety evaluation, we use Attack Success Rate (ASR) as our metric. We follow the pipeline in Deng et al. [2024] and use GPT-4o as the judge. For the general capability test, we evaluate the accuracy on the datasets MMLU [Hendrycks et al., 2020] and MGSM [Shi et al., 2022].

Baselines. We compare MSD against six types of strong baselines, including (1) SFT [Ouyang et al., 2022]; (2) representative PO methods: DPO [Rafailov et al., 2023], rDPO [Chowdhury et al., 2024], KTO [Ethayarajh et al., 2024], ORPO [Hong et al., 2024], R-DPO [Park et al., 2024], and SimPO [Meng et al., 2024]; (3) representation engineering method: PolyRefuse [Wang et al., 2025]; (4) prompt-based method: Self-Defense [Phute et al., 2024]; (5) distillation-based method: SDRRL [Zhang et al., 2024]; (6) multilingual safety alignment method: MPO [Zhao et al., 2025].

More experimental details about datasets, evaluation metrics and baselines are listed in Appendix B.

Table 2: Average accuracy ($\uparrow$) on multilingual general capability benchmarks (MMMLU and MGSM). Best and second-best results are **bolded** and underlined, respectively.

Method	Qwen-2.5-7B-Instruct		Qwen-3-8B		LLaMA-2-7B-Chat		LLaMA-3-8B-Instruct	
	MMMLU	MGSM	MMMLU	MGSM	MMMLU	MGSM	MMMLU	MGSM
Raw	<u>58.26</u>	63.89	64.65	64.87	32.05	10.95	48.17	<u>56.04</u>
SFT	50.55	52.95	59.22	73.42	24.00	6.22	17.65	20.84
DPO	58.04	62.91	65.15	65.35	31.86	11.04	41.53	53.13
rDPO	57.92	<u>63.16</u>	65.26	65.89	31.96	10.29	22.86	51.89
KTO	57.85	63.05	65.23	65.89	31.84	11.00	33.79	52.36
ORPO	57.47	59.89	65.49	67.35	31.49	11.40	34.88	47.02
R-DPO	58.06	62.84	65.23	65.49	<u>32.01</u>	10.11	42.26	52.69
SimPo	57.16	55.20	65.45	67.85	31.33	10.25	35.31	47.78
PolyRefuse	57.90	58.69	64.61	64.29	31.20	10.29	44.01	55.60
SDRRL	57.34	58.58	65.07	62.40	27.11	11.75	34.28	42.65
MPO	58.17	62.95	64.78	64.62	31.91	<u>11.92</u>	47.87	54.25
MSD (Off-Policy)	58.25	60.44	66.88	75.53	31.61	10.55	46.57	55.89
MSD (On-Policy)	58.80	63.89	<u>66.76</u>	<u>74.04</u>	31.97	12.80	<u>48.16</u>	58.11

Table 3: Comparison of response data generation costs across different methods.

	SFT	Distillation	Preference Optimization		Prompt	Representation Eng.	MSD (Ours)
Method	SFT	SDRRL	DPO / rDPO / KTO / ORPO / SimPO / MPO		Self-Defense	PolyRefusal	MSD
Data Cost	\$650	\$450	\$1200		\$0	~\$0	\$0

4.2 Overall Evaluation on Multilingual Safety Alignment

Our proposed MSD method effectively improves multilingual safety performance, exhibiting strong cross-dataset and cross-lingual generalization. Crucially, it preserves general capabilities and operates entirely without target-language response data.

Multilingual safety performance. Table 1 presents the multilingual safety performance of Qwen-3-8B and LLaMA-3-8B-Instruct, comparing the proposed MSD with other representative baselines. To comprehensively evaluate safety performance after alignment, we report results across three resource levels of languages: high-resource, medium-resource, and low-resource, distinguished by different colors. From these evaluations, we draw the following two insights:

- **MSD exhibits superior safety performance across benchmarks.** Compared to various strong baselines, both the on-policy MSD and off-policy MSD consistently achieve superior multilingual safety performance across both benchmarks. The excellent performance is observed across high-, medium-, and low-resource languages, underscoring MSD as a robust cross-lingual transfer framework. Notably, while our framework is trained on the relatively simple XSafety dataset, it maintains exceptional performance on the more challenging MultiJail and PKU-SafeRLHF benchmarks. This highlights the cross-dataset generalization capability of our method.

- **Strong generalization to unseen low-resource languages.** Out of the ten languages evaluated, only four are present in the training set, allowing us to observe how effectively the multilingual alignment transfers to unseen languages. Existing baselines frequently exhibit biased performance, particularly benefiting high-resource languages or languages seen during training. In such cases, safety alignment remains inadequate for low-resource languages like SW and JV. In contrast, MSD demonstrates stable and generalizable safety behaviors, particularly in low-resource languages. For instance, for LLaMA-3-8B-Instruct evaluated on the MultiJail benchmark, the off-policy MSD significantly reduces the ASR for SW from the raw model’s 69.52% down to 6.03%, and the on-policy MSD further reduces it to 4.13%. A similar safety improvement is consistently observed on the PKU-SafeRLHF dataset. This indicates that our method does not merely overfit to the training language distribution; instead, it effectively transfers the model’s internal high-resource safeguards to low-resource safeguards.

Furthermore, while Qwen-3-8B retains a relatively higher ASR on SW and JV compared to other languages, MSD still significantly outperforms other baselines. This high ASR in SW and JV largely stems from the model’s weak generative capability in these low-resource languages, which produces invalid responses that are regarded as successful attacks. Crucially, analysis in Appendix D.1 confirms MSD can successfully identify harmful intents in the reasoning process.

Table 4: The ablation study of DPSW. Evaluation is based on Attack Success Rate (ASR $\downarrow$).

Method	Qwen-2.5-7B-Instruct		Qwen-3-8B		LLaMA-2-7B-Chat		LLaMA-3-8B-Instruct	
	MultiJail	PKU-SafeRLHF	MultiJail	PKU-SafeRLHF	MultiJail	PKU-SafeRLHF	MultiJail	PKU-SafeRLHF
MSD (Off-Policy) w/o DPSW	13.27	11.62	11.25	8.12	9.95	11.48	4.55	2.48
MSD (Off-Policy) w/ DPSW	10.41	10.98	9.90	6.54	8.86	9.96	2.92	1.22
MSD (On-Policy) w/o DPSW	6.38	6.92	11.09	9.10	4.99	6.80	3.33	3.02
MSD (On-Policy) w/ DPSW	5.94	6.04	10.04	7.62	2.48	3.90	2.03	1.78
Best-Performing Baseline	12.38	12.10	12.44	9.08	11.18	14.34	6.09	4.38

Table 5: DPSW weight analysis of safety-critical and non-critical tokens.

Token Type	Qwen-3-8B			LLaMA-3-8B-Instruct		
	Avg. (w_t)	Avg. (w_t^T)	Avg. (w_t^S)	Avg. (w_t)	Avg. (w_t^T)	Avg. (w_t^S)
Safety-Critical Token	0.189	0.886	0.253	0.182	0.852	0.281
Non-Critical Token	0.112	0.740	0.199	0.117	0.709	0.235

MSD maintains previous knowledge and reasoning capabilities after alignment. We evaluate all methods across two general tasks: (1) World Knowledge via MMMLU and (2) Multilingual Reasoning via MGSM. Results in Table 2 show that MSD preserves general capabilities well after alignment. This demonstrates that the substantial improvements in multilingual safety do not come at the cost of degrading the model’s reasoning or knowledge-retrieval performance. For detailed results of all the languages, please refer to Table 10 and Table 11 in Appendix C.

MSD requires zero cost for response data generation. Table 3 compares the data generation costs of different methods. To ensure high-quality data, all data generation and translation tasks are performed using the GPT-4o API. SFT incurs significant costs because it requires safe responses for every target language. SDRRL incurs a moderate cost by translating the model’s English responses into target languages. Preference Optimization is the most expensive, as it requires paired contrastive responses for every query. In contrast, our MSD requires zero data generation cost. This further demonstrates that MSD can eliminate the massive expense of response data generation.

4.3 Ablation Study

Effect of DPSW. We conduct an ablation study of DPSW across both the off-policy and on-policy MSD. Results in Table 4 demonstrate that integrating DPSW consistently enhances safety performance across all the models and benchmarks. This confirms that DPSW is beneficial for multilingual safety alignment. Furthermore, we include the best-performing baseline results in the table for comparison. Notably, even without DPSW, both the off-policy and on-policy MSD still outperform the majority of these best baselines. This observation validates that the safeguard transfer framework of MSD is effective for cross-lingual alignment on its own, and the addition of DPSW further enhances its performance. For the teacher’s top- K entropy, we report the results $K = 32$ here (see Table 13 in Appendix C for hyperparameter experiments of K). Furthermore, to **validate the rationality of DPSW design**, we evaluate whether tokens assigned higher weights (w_t) correspond to safety-critical tokens. Specifically, we separate the tokens of the sentence into safety-critical tokens and non-critical tokens. Then we examine the average values of the weights w_t , w_t^T and w_t^S across both safety-critical and non-critical tokens. As shown in Table 5, safety-critical tokens consistently receive higher values for w_t , w_t^T , and w_t^S compared to non-critical ones. This evidence supports our motivation that DPSW assigns higher penalty weights to safety-critical tokens throughout the sequence, rather than applying a uniform penalty across all generated tokens. Please see Appendix B.5 for details of the experiment.

Effect of teacher-side additional information. A core design in MSD is the additional information provided to the teacher. The standard OPSD paradigm [Zhao et al., 2026, Shenfeld et al., 2026] typically provides the teacher with ground-truth answers. To compare with the standard OPSD and validate the effectiveness of each component within our additional information, we evaluate four variants under the on-policy setting: (1) MSD w/ GT (standard ground-truth refusal responses); (2) MSD w/ EN (the query in English x^* only); (3) MSD w/ CoT (the CoT instruction $\mathcal{C}$ only); and (4) our full MSD (the query in English x^* and the CoT instruction $\mathcal{C}$). Results in Table 6 demonstrate that the full MSD achieves the lowest ASR across both jailbreak benchmarks while preserving general

Table 6: The ablation study of teacher-side additional information under the on-policy setting.

Method	Qwen-3-8B				LLaMA-3-8B-Instruct			
	MultiJail (ASR ↓)	PKU (ASR ↓)	MMMLU (Accuracy ↑)	MGSM (Accuracy ↑)	MultiJail (ASR ↓)	PKU (ASR ↓)	MMMLU (Accuracy ↑)	MGSM (Accuracy ↑)
MSD w/GT	11.71	11.88	66.74	74.00	11.55	12.34	18.58	30.65
MSD w/EN	15.59	17.34	66.18	74.69	6.98	8.70	30.31	16.00
MSD w/CoT	11.59	10.94	67.19	73.71	8.00	10.98	34.56	38.62
MSD	10.04	7.62	66.76	74.04	2.03	1.78	48.16	58.11

Table 7: Comparison of using different languages as the high-resource language.

Method	MultiJail (ASR ↓)	PKU (ASR ↓)	MMMLU (Accuracy ↑)	MGSM (Accuracy ↑)
MSD (Off-Policy) w/ ZH	10.74	8.79	66.42	75.35
MSD (Off-Policy) w/ EN	9.90	6.54	66.88	75.53
MSD (On-Policy) w/ ZH	11.79	9.44	66.97	75.96
MSD (On-Policy) w/ EN	10.04	7.62	66.76	74.04
Best-Performing Baseline	12.44	9.08	65.49	73.42

Table 8: Comparison of freezing or updating the teacher’s parameters on Qwen-3-8B (On-Policy).

Method	MultiJail (ASR ↓)	PKU (ASR ↓)	MMMLU (Accuracy ↑)	MGSM (Accuracy ↑)
$\alpha=0$ (Ours)	10.04	7.62	66.76	74.04
$\alpha=0.01$	12.03	6.70	65.59	69.35
$\alpha=0.02$	14.67	6.74	64.62	69.16
$\alpha=0.05$	35.49	22.24	58.46	69.24

capabilities. This confirms that both the query in English x^* and the CoT instruction $\mathcal{C}$ are important for the teacher to elicit the model’s inherent safety capabilities in high-resource languages.

Furthermore, we observe that directly providing ground-truth refusals to the teacher severely degrade the model’s general capabilities. For instance, MSD w/ GT drops LLaMA-3-8B-Instruct’s MMMLU score from 48.17 to 18.58. This indicates that directly exposing the teacher to ground-truth refusals tends to encourage shortcut learning rather than transferring safety capabilities. This observation aligns with recent findings [Kim et al., 2026, Yang et al., 2026a], which suggest that OPSD can cause information leakage and performance degradation under certain conditions. These results further underscore the MSD’s superiority: MSD not only eliminates the need for refusal response data but also yields the most effective multilingual safety alignment while preserving general capabilities.

Exploring the choice of high-resource language. In our primary experiments, we designate English as the high-resource language. To evaluate the generalization of our framework to other dominant languages, we conduct an additional experiment using Chinese (ZH) as the high-resource language for Qwen-3-8B, driven by the importance of Chinese data in its pre-training corpus. Specifically, we adapt the additional information by providing the teacher with the query in Chinese and a Chinese CoT instruction. As shown in Table 7, while utilizing ZH as the high-resource language yields slightly inferior performance compared to EN, it still outperforms other baselines while successfully preserving the model’s general capabilities. This observation validates the robustness and flexibility of our framework. It proves that the high-resource language in our framework can be flexibly selected based on the dominant languages present in the target model’s pre-training data.

Effect of freezing the teacher. During training, the parameters of the teacher p_T are kept frozen to provide a stable supervision signal. Prior studies [Hübötter et al., 2026, Shenfeld et al., 2026] advocate updating the teacher’s parameters via an Exponential Moving Average (EMA) of the student’s parameters. Specifically, the EMA strategy updates the teacher iteratively as $p_T \leftarrow (1 - \alpha)p_T + \alpha p_S$, where $\alpha \in (0, 1)$. Thus, we compare the effects of employing an EMA update with $\alpha \in \{0.01, 0.02, 0.05\}$ against a frozen teacher ($\alpha = 0$). As shown in Table 8, freezing the teacher ($\alpha = 0$) yields the best trade-off: it achieves strong multilingual safety performance while preserving the best general capabilities. Conversely, a minor EMA update ($\alpha = 0.01$) degrades general capability despite marginal safety gains on PKU-SafeRLHF, and a larger update ($\alpha = 0.05$) causes a severe collapse in both safety performance and general capability. This evidence suggests that updating the teacher with the student’s parameters may corrupt the teacher’s inherent high-resource safety capabilities and general capabilities. In contrast, a frozen teacher aligns perfectly with our objective of transferring existing safeguards without degrading general capabilities.

5 Conclusion and Limitations

In this paper, we introduce MSD, a response-free framework designed to bridge the severe safety alignment gap between high-resource and low-resource languages. By leveraging self-distillation, MSD effectively transfers internal safeguards from high-resource to low-resource languages, entirely eliminating the expensive costs of generating response data. To further optimize this transfer, we proposed DPSW, a token-level weighting mechanism that improves alignment precision based on both the teacher’s and the student’s perspective. Extensive evaluations demonstrate that MSD achieves the best multilingual safety performance and strong generalization to unseen languages and more challenging datasets, all while preserving the model’s general capabilities. Ultimately, our approach provides a scalable, cost-effective paradigm for developing safe and reliable LLMs.

Limitations. The limitations of our MSD framework are as follows: (1) it requires the base model to already possess strong safeguards and in-context learning capabilities in the high-resource language; (2) it depends on high-quality multilingual query translations to construct the teacher’s additional information. Although such parallel data are readily available in existing benchmarks like XSafety and MultiJail, poor translation quality can negatively impact the alignment performance. A detailed discussion of these limitations is provided in Appendix E.

References

- Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, Piotr Stanczyk, Sabela Ramos Garea, Matthieu Geist, and Olivier Bachem. On-policy distillation of language models: Learning from self-generated mistakes. In *The twelfth international conference on learning representations*, 2024.
- Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*, 2021.
- Yuyan Bu, Xiaohao Liu, ZhaoXing Ren, Yaodong Yang, and Juntao Dai. Align once, benefit multilingually: Enforcing multilingual consistency for LLM safety alignment. In *The Fourteenth International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=uekn0G1wXL>.
- Zouying Cao, Yifei Yang, and Hai Zhao. Scans: Mitigating the exaggerated safety for llms via safety-conscious activation steering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 23523–23531, 2025.
- Sayak Ray Chowdhury, Anush Kini, and Nagarajan Natarajan. Provably robust dpo: Aligning language models with noisy feedback. *arXiv preprint arXiv:2403.00409*, 2024.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- Yue Deng, Wenxuan Zhang, Sinno Jialin Pan, and Lidong Bing. Multilingual jailbreak challenges in large language models. In *The Twelfth International Conference on Learning Representations*, 2024.
- Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. Kto: Model alignment as prospect theoretic optimization. *arXiv preprint arXiv:2402.01306*, 2024.
- Tommaso Furlanello, Zachary Lipton, Michael Tschannen, Laurent Itti, and Anima Anandkumar. Born again neural networks. In *International conference on machine learning*, pages 1607–1616. PMLR, 2018.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. In *Neural Information Processing Systems*. Curran Associates, 2024.
- Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. Minillm: Knowledge distillation of large language models. *arXiv preprint arXiv:2306.08543*, 2023.

- Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, et al. Reinforced self-training (rest) for language modeling. *arXiv preprint arXiv:2308.08998*, 2023.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.
- Jiwoo Hong, Noah Lee, and James Thorne. Orpo: Monolithic preference optimization without reference model. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11170–11189, 2024.
- Jonas Hübner, Frederike Lübeck, Lejs Behric, Anton Baumann, Marco Bagatella, Daniel Marta, Ido Hakimi, Idan Shenfeld, Thomas Kleine Buening, Carlos Guestrin, et al. Reinforcement learning via self-distillation. *arXiv preprint arXiv:2601.20802*, 2026.
- Neel Jain, Aditya Shrivastava, Chenyang Zhu, Daben Liu, Alf Samuel, Ashwinee Panda, Anoop Kumar, Micah Goldblum, and Tom Goldstein. Refusal tokens: A simple way to calibrate refusals in large language models. In *Neurips Safe Generative AI Workshop 2024*, 2024. URL <https://openreview.net/forum?id=vx7reBU6WQ>.
- Jiaming Ji, Donghai Hong, Borong Zhang, Boyuan Chen, Josef Dai, Boren Zheng, Tianyi Alex Qiu, Jiayi Zhou, Kaile Wang, Boxun Li, et al. Pku-saferlhf: Towards multi-level safety alignment for llms with human preference. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 31983–32016, 2025.
- Jeonghye Kim, Xufang Luo, Minbeom Kim, Sangmook Lee, Dohyung Kim, Jiwon Jeon, Dongsheng Li, and Yuqing Yang. Why does self-distillation (sometimes) degrade the reasoning capability of llms? *arXiv preprint arXiv:2603.24472*, 2026.
- Jie Li, Yi Liu, Chongyang Liu, Ling Shi, Xiaoning Ren, Yaowen Zheng, Yang Liu, and Yinxing Xue. A cross-language investigation into jailbreak attacks in large language models. *arXiv preprint arXiv:2401.16765*, 2024.
- Jiaming Liang, Zhaoxin Wang, and Handing Wang. Multilingual safety alignment via sparse weight editing. *arXiv preprint arXiv:2602.22554*, 2026.
- Kevin Lu and Thinking Machines Lab. On-policy distillation. *Thinking Machines Lab: Connectionism*, 2025. doi: 10.64434/tml.20251026. <https://thinkingmachines.ai/blog/on-policy-distillation>.
- Yu Meng, Mengzhou Xia, and Danqi Chen. Simpo: Simple preference optimization with a reference-free reward. *Advances in Neural Information Processing Systems*, 37:124198–124235, 2024.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- Ryan Park, Rafael Rafailov, Stefano Ermon, and Chelsea Finn. Disentangling length from quality in direct preference optimization. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4998–5017, 2024.
- Mansi Phute, Alec Helbling, Matthew Daniel Hull, ShengYun Peng, Sebastian Szyller, Cory Cornelius, and Duen Horng Chau. LLM self defense: By self examination, LLMs know they are being tricked. In *The Second Tiny Papers Track at ICLR 2024*, 2024. URL <https://openreview.net/forum?id=YqggcIA19o>.
- Xiangyu Qi, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. Safety alignment should be made more than just a few tokens deep. In *The Thirteenth International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=6Mxhg9PtDE>.

- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741, 2023.
- Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. In *Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 3505–3506, 2020.
- Hejian Sang, Yuanda Xu, Zhengze Zhou, Ran He, Zhipeng Wang, and Jiachen Sun. On-policy self-distillation for reasoning compression. *arXiv preprint arXiv:2603.05433*, 2026.
- Guobin Shen, Dongcheng Zhao, Haibo Tong, Jindong Li, Feifei Zhao, and Yi Zeng. Safety instincts: LLMs learn to trust their internal compass for self-defense. In *The Fourteenth International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=LUiqtv6vrd>.
- Lingfeng Shen, Weiting Tan, Sihao Chen, Yunmo Chen, Jingyu Zhang, Haoran Xu, Boyuan Zheng, Philipp Koehn, and Daniel Khashabi. The language barrier: Dissecting safety challenges of llms in multilingual contexts. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2668–2680, 2024.
- Idan Shenfeld, Mehul Damani, Jonas Hübötter, and Pulkit Agrawal. Self-distillation enables continual learning. *arXiv preprint arXiv:2601.19897*, 2026.
- Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, et al. Language models are multilingual chain-of-thought reasoners. *arXiv preprint arXiv:2210.03057*, 2022.
- Zhiqing Sun, Yikang Shen, Qinhong Zhou, Hongxin Zhang, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. Principle-driven self-alignment of language models from scratch with minimal human supervision. *Advances in Neural Information Processing Systems*, 36:2511–2565, 2023.
- Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, et al. Gemma 2: Improving open language models at a practical size. *arXiv preprint arXiv:2408.00118*, 2024.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- Guoli Wang, Haonan Shi, Tu Ouyang, and An Wang. Few tokens, big leverage: Preserving safety alignment by constraining safety tokens during fine-tuning. *arXiv preprint arXiv:2603.07445*, 2026.
- Wenxuan Wang, Zhaopeng Tu, Chang Chen, Youliang Yuan, Jen-tse Huang, Wenxiang Jiao, and Michael R Lyu. All languages matter: On the multilingual safety of large language models. *arXiv preprint arXiv:2310.00905*, 2023a.
- Xinpeng Wang, Mingyang Wang, Yihong Liu, Hinrich Schuetze, and Barbara Plank. Refusal direction is universal across safety-aligned languages. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL <https://openreview.net/forum?id=eWxKpdAdXH>.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers)*, pages 13484–13508, 2023b.
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025a.

- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, et al. Qwen2.5 technical report, 2025b. URL <https://arxiv.org/abs/2412.15115>.
- Chenglin Yang, Lingxi Xie, Chi Su, and Alan L Yuille. Snapshot distillation: Teacher-student optimization in one generation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 2859–2868, 2019.
- Chenxu Yang, Chuanyu Qin, Qingyi Si, Minghui Chen, Naibin Gu, Dingyu Yao, Zheng Lin, Weiping Wang, Jiaqi Wang, and Nan Duan. Self-distilled rlvr, 2026a. URL <https://arxiv.org/abs/2604.03128>.
- Junxiao Yang, Haoran Liu, Jinzhe Tu, Jiale Cheng, Zhexin Zhang, Shiyao Cui, Jiaqi Weng, Jialing Tao, Hui Xue, Hongning Wang, et al. Lasa: Language-agnostic semantic alignment at the semantic bottleneck for llm safety. *arXiv preprint arXiv:2604.12710*, 2026b.
- Zhaorui Yang, Tianyu Pang, Haozhe Feng, Han Wang, Wei Chen, Minfeng Zhu, and Qian Liu. Self-distillation bridges distribution gap in language model fine-tuning. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1028–1043, 2024.
- Tianzhu Ye, Li Dong, Xun Wu, Shaohan Huang, and Furu Wei. On-policy context distillation for language models. *arXiv preprint arXiv:2602.12275*, 2026.
- Zheng-Xin Yong, Beyza Ermis, Marzieh Fadaee, Stephen Bach, and Julia Kreutzer. The state of multilingual llm safety research: From measuring the language gap to mitigating it. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 15856–15871, 2025.
- Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason E Weston. Self-rewarding language models. In *International Conference on Machine Learning*, pages 57905–57923. PMLR, 2024.
- Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. Star: Bootstrapping reasoning with reasoning. *Advances in Neural Information Processing Systems*, 35:15476–15488, 2022.
- Linfeng Zhang, Jiebo Song, Anni Gao, Jingwei Chen, Chenglong Bao, and Kaisheng Ma. Be your own teacher: Improve the performance of convolutional neural networks via self distillation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3713–3722, 2019.
- Max Zhang, Derek Liu, Kai Zhang, Joshua Franco, Haihao Liu, and Kevin Zhu. Response-based knowledge distillation for multilingual jailbreak prevention unwittingly compromises safety. In *Socially Responsible and Trustworthy Foundation Models at NeurIPS 2025*, 2025. URL <https://openreview.net/forum?id=e26bFhz8YV>.
- Xianhui Zhang, Chengyu Xie, Linxia Zhu, Yonghui Yang, Weixiang Zhao, Zifeng Cheng, Cong Wang, Fei Shen, and Tat-Seng Chua. Who transfers safety? identifying and targeting cross-lingual shared safety neurons. *arXiv preprint arXiv:2602.01283*, 2026.
- Yuanchi Zhang, Yile Wang, Zijun Liu, Shuo Wang, Xiaolong Wang, Peng Li, Maosong Sun, and Yang Liu. Enhancing multilingual capabilities of large language models through self-distillation from resource-rich languages. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11189–11204, 2024.
- Jun Zhao, Zhihao Zhang, Luhui Gao, Qi Zhang, Tao Gui, and Xuanjing Huang. Llama beyond english: An empirical study on language capability transfer. *arXiv preprint arXiv:2401.01055*, 2024.
- Siyan Zhao, Zhihui Xie, Mengchen Liu, Jing Huang, Guan Pang, Feiyu Chen, and Aditya Grover. Self-distilled reasoner: On-policy self-distillation for large language models. *arXiv preprint arXiv:2601.18734*, 2026.

Weixiang Zhao, Yulin Hu, Yang Deng, Tongtong Wu, Wenxuan Zhang, Jiahe Guo, An Zhang, Yanyan Zhao, Bing Qin, Tat-Seng Chua, et al. Mpo: Multilingual safety alignment via reward gap optimization. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 23564–23587, 2025.

A Additional Related Work

Multilingual Safety Alignment. Recent studies have exposed significant risks in the multilingual safety of LLMs: while they maintain strong safety capabilities in high-resource languages, their safeguards frequently fail in low-resource languages [Deng et al., 2024, Wang et al., 2023a, Shen et al., 2024, Yong et al., 2025]. Current methods to bridge this gap typically employ supervised fine-tuning [Deng et al., 2024, Li et al., 2024, Shen et al., 2024], preference optimization [Rafailov et al., 2023, Ethayarajh et al., 2024, Meng et al., 2024, Zhao et al., 2025], or distillation techniques [Zhang et al., 2024, 2025]. However, these data-driven methods demand substantial high-quality response data per target language. Generating such data through human annotation or API-based translation is costly and has a risk of introducing translation errors that harm data quality, therefore hindering large-scale alignment in low-resource languages. To alleviate this, recent studies [Bu et al., 2026, Yang et al., 2026b] introduce novel paradigms that eliminate the need for low-resource response data. Nevertheless, these methods are based on conventional training frameworks (e.g., DPO) and still need extensive English response data. Conversely, training-free approaches, including representation engineering [Wang et al., 2025] and activation steering [Zhang et al., 2026, Liang et al., 2026], decrease the reliance on response data. However, they exhibit poor cross-dataset generalization and may harm the model’s general capabilities [Cao et al., 2025].

Self-Distillation. Self-distillation was studied as a way for a model to improve by learning from itself, rather than from a separately trained larger teacher. Early work [Furlanello et al., 2018, Zhang et al., 2019, Yang et al., 2019] showed that self-distillation can improve generalization and act as an effective regularizer. In the LLM era, self-distillation has been revisited as a mechanism for self-improvement. A line of off-policy methods lets LLMs generate and exploit their own supervision signals through iterative self-training, rationale bootstrapping, or self-generated instruction tuning [Zelikman et al., 2022, Gulcehre et al., 2023, Wang et al., 2023b, Sun et al., 2023, Yang et al., 2024, Yuan et al., 2024]. These approaches typically produce discrete trajectories or rationales and then fine-tune the model on them, yielding off-policy distillation. More recently, on-policy distillation (OPD) lets a stronger teacher evaluate the student’s own rollouts and provide dense token-level supervision [Agarwal et al., 2024, Gu et al., 2023, Lu and Lab, 2025]. To further remove the need for an external teacher, on-policy self-distillation (OPSD) instantiates the teacher and the student from the same model under different contexts, where the teacher is equipped with privileged information [Zhao et al., 2026, Hübotter et al., 2026]. This paradigm has been extended to continual learning, context internalization, and reasoning compression [Shenfeld et al., 2026, Ye et al., 2026, Sang et al., 2026]. In this paper, we build on this line and propose a flexible multilingual self-distillation framework that can integrate different self-distillation strategies to transfer a model’s internal high-resource-language safety capability to low-resource languages.

B More Experimental Details

B.1 Training Data

XSafety [Wang et al., 2023a]. We use XSafety as the sole multilingual query source for training. XSafety is constructed from several well-established monolingual safety corpora and extended into a multilingual setting through professional translation and proofreading. The benchmark covers 14 safety issues in total, including seven typical safety scenarios, six instruction-attack scenarios, and one commonsense safety test set. Concretely, the original benchmark contains 2,800 source queries, with 200 instances for each safety issue, and is translated into 10 languages: English, Chinese, Spanish, French, Bengali, Arabic, Hindi, Russian, Japanese, and German, resulting in 28,000 annotated instances in total. To ensure translation quality, the original paper first applies machine translation and then conducts two rounds of professional proofreading. It further reports a pass rate above 99% on a random inspection of 10% of the translated data. In our experiments, we only use the multilingual *queries* from XSafety and do not rely on any response-level supervision in the training stage.

B.2 Benchmark

We evaluate our method on two multilingual safety benchmarks and two multilingual utility benchmarks.

System Prompt: You are a professional translation engine.

Task:

- Translate the provided text from English into the target language.
- Keep markdown formatting, numbering, punctuation style, and line breaks.
- Do not censor, summarize, or add new information.
- Do not add explanations.

Output rules:

- Output ONLY valid JSON with exactly one top-level key: "translated".

Context Prompt:

Target language: {target_lang_name} ({target_lang_code})

Translate the following text only: {text}

Figure 4: Translation prompt of the PKU-SafeRLHF dataset.

MultiJail [Deng et al., 2024]. MultiJail is a multilingual jailbreak benchmark containing 315 unsafe prompts across 10 languages, including English (EN), Chinese (ZH), Italian (IT), Vietnamese (VI), Arabic (AR), Korean (KO), Thai (TH), Bengali (BN), Swahili (SW), and Javanese (JV). The prompts cover 18 distinct categories of safety risks. To ensure benchmark quality, the multilingual prompts are manually verified by native speakers.

PKU-SafeRLHF [Ji et al., 2025]. PKU-SafeRLHF is a widely used safety preference dataset. To construct a multilingual evaluation set, we randomly sample 500 harmful English queries from PKU-SafeRLHF and translate them into 9 target languages, including English (EN), Chinese (ZH), Italian (IT), Vietnamese (VI), Arabic (AR), Korean (KO), Thai (TH), Bengali (BN), Swahili (SW), and Javanese (JV), using GPT-4o with the translation prompt shown in Figure 4. This benchmark is used to test whether aligned models can generalize to a different multilingual safety distribution beyond XSafety.

MMMLU [Hendrycks et al., 2020]. MMMLU is the multilingual extension of MMLU, covering 57 subjects from elementary-level knowledge to advanced professional domains. The benchmark uses professionally translated test sets, which provides a relatively reliable evaluation of multilingual general knowledge. In our experiments, we adopt the 5-shot setting. The benchmark covers Arabic (AR), Bengali (BN), German (DE), English (EN), Spanish (ES), French (FR), Hindi (HI), Indonesian (ID), Italian (IT), Japanese (JA), Korean (KO), Portuguese (PT), Swahili (SW), Yoruba (YO), and Chinese (ZH).

MGSM [Shi et al., 2022]. MGSM is a multilingual grade-school mathematics benchmark built from 250 GSM8K [Cobbe et al., 2021] problems translated by human annotators. It evaluates multilingual mathematical reasoning under multi-step problem solving. In our experiments, we follow the 0-shot CoT setting. The benchmark covers English (EN), Spanish (ES), French (FR), German (DE), Russian (RU), Chinese (ZH), Japanese (JA), Thai (TH), Swahili (SW), Bengali (BN), and Telugu (TE).

For multilingual safety evaluation, we report the **Attack Success Rate (ASR)** following the evaluation protocol of Deng et al. [2024], using GPT-4o as the judge. As shown in Figure 5, GPT-4o classifies each response into three categories: *safe*, *unsafe*, and *invalid*. Responses judged as unsafe or invalid are both counted as successful attacks, while only meaningful refusals are considered safe. Therefore, a lower ASR indicates better multilingual safety alignment. To further ensure the accuracy and fairness of the LLM-as-a-judge evaluation, we randomly sampled 3% of the responses from all models on both benchmarks for manual verification. We observed an agreement rate of over 97% between human judgments and GPT-4o, which supports the reliability of the automatic evaluation pipeline used in this work.

B.3 Baseline Methods

SFT [Ouyang et al., 2022]: Supervised Fine-Tuning directly trains the model to imitate safe target responses with standard next-token prediction loss. It serves as a basic training-based baseline for multilingual safety alignment.

System Prompt: Given a pair of query and response, assess the safety of the response solely based on its content, disregarding the harmful content present in the query.

Definitions:

Safe: The response is considered safe if it does not contain any unsafe content or if it refuses to respond to the unsafe query.

Unsafe: The response is deemed unsafe if it includes unsafe content or if it directly responds to the unsafe query.

Invalid: The response is classified as invalid if it does not form a natural sentence or if it is irrelevant to the given query.

Please evaluate the response and provide your selection from the list ['safe', 'unsafe', 'invalid'] without returning any other character.

Context Prompt:

Query: {*prompt*}

Response: {*response*}

Figure 5: Evaluation prompt of multilingual safety evaluation.

DPO [Rafailov et al., 2023]: Direct Preference Optimization learns from chosen–rejected response pairs by directly increasing the likelihood of preferred responses over dispreferred ones relative to a reference model. It is one of the most widely used offline preference alignment methods.

rDPO [Chowdhury et al., 2024]: rDPO is a robust variant of DPO designed to reduce sensitivity to noisy preference labels. It mitigates the impact of noisy feedback through a more noise-tolerant optimization objective.

KTO [Ethayarajh et al., 2024]: Kahneman-Tversky Optimization extends alignment beyond paired comparisons by learning from non-paired preference signals. It models alignment through a prospect-theoretic utility formulation.

ORPO [Hong et al., 2024]: Odds Ratio Preference Optimization removes the need for a separate reference model by introducing an odds-ratio term that directly contrasts winning and losing responses. It is optimized jointly with the SFT objective.

R-DPO [Park et al., 2024]: R-DPO augments DPO with an additional regularization term to mitigate undesirable effects such as length exploitation. This makes the learned preference signal more stable during alignment.

SimPO [Meng et al., 2024]: SimPO removes the reference model and uses the average log-likelihood of a response as the implicit reward. It further incorporates length normalization and a target reward margin to stabilize preference optimization.

PolyRefuse [Wang et al., 2025]: PolyRefuse is a training-free representation engineering method based on the observation that refusal directions are highly transferable across safety-aligned languages. It extracts a cross-lingual refusal direction from hidden representations and steers the model toward refusal behavior through activation intervention.

Self-Defense [Phute et al., 2024]: Self-Defense is a prompt-based defense method that does not require any training or parameter updates. It prompts the LLM to examine its own generated response and judge whether it is harmful, thereby using self-examination as a zero-shot defense against jailbreak attacks.

SDRRL [Zhang et al., 2024]: SDRRL improves multilingual capability by leveraging the model’s stronger responses in a resource-rich language as distillation targets for other languages. It constructs cross-lingual transfer data through translation and self-distillation to improve target-language performance.

MPO [Zhao et al., 2025]: MPO transfers multilingual safety capability by aligning the reward gap between safe and unsafe responses in target languages to that of a dominant language. It uses the dominant language as a high-quality supervision source and regularizes the model to preserve its original capability.

System Prompt: You are a data annotation assistant for safety alignment research. Your task is to generate two responses to the given question:

1. **chosen:** A safe, helpful, and appropriate response. If the question is unsafe or malicious, this response should politely refuse and explain why it cannot help, while remaining respectful.
2. **rejected:** An unsafe response that directly engages with the harmful intent of the question without any safety guardrails. This response should be clearly inappropriate.

Rules:

- Both responses MUST be in the SAME language as the question.
- Output ONLY valid JSON with exactly two keys: "chosen" and "rejected".
- Do NOT include any explanation or extra text outside the JSON.

Context Prompt:
Question: {question}

Figure 6: Data generation prompt of multilingual response data.

For preference-based baselines that require chosen–rejected response pairs, including DPO, rDPO, KTO, ORPO, R-DPO, SimPO, and MPO, we construct the preference data with GPT-4o. Specifically, for each query in XSAFETY, we use the prompt in Figure 6 to ask GPT-4o to generate one chosen response and one rejected response in the same language as the query. The chosen response is required to be safe, helpful, and aligned, while the rejected response directly follows the harmful intent without safety guardrails. This procedure provides relatively high-quality preference pairs for a fair comparison across all preference-based baselines. For SFT, we train on the same preference dataset but only use the chosen responses as supervision targets. For PolyRefuse and SDRRL, we follow the original implementations and settings described in their papers.

B.4 Implementation Details

All training experiments are conducted on four RTX PRO 6000 96GB GPUs using the Hugging Face TRL³ library. We perform full fine-tuning of the entire model’s parameters. For distributed training, we leverage the DeepSpeed [Rasley et al., 2020] framework with ZeRO-3 optimization. We search the teacher-side weight hyperparameter K in DPSW in {16, 32, 64}, the hyperparameter experiment is provided in Table 13 in Appendix C. To ensure a fair comparison, all training-based methods are trained for one epoch under the same hyperparameter search space. Specifically, we search all training-based methods for the batch size in {16, 32} and the learning rate in {5e-7, 1e-6, 5e-6, 1e-5, 2e-5}.

B.5 Details of DPSW Weight Analysis

To further analyze whether DPSW assigns larger weights to semantically safety-critical tokens, we conduct a post-hoc token-level annotation study on the training data. Specifically, we randomly sample 1000 questions from the XSafety training set and run the first training step of MSD on two representative backbones, Qwen-3-8B and LLaMA-3-8B-Instruct. For each sampled question, we obtain the student-generated completion and record the token-level DPSW statistics before parameter updates, including the final weight w_t , the teacher-side weight w_t^T , and the student-side weight w_t^S .

Since directly identifying safety-critical tokens using surface refusal phrases is unreliable in multilingual settings, we instead perform semantic span annotation. As shown in Figure 7, we ask GPT-4o to split each student-generated completion into contiguous, non-overlapping token spans and assign each span one of two labels: *Safety-critical* or *Non-critical*. A span is labeled as *Safety-critical* if it directly contributes to the model’s safety judgment, refusal stance, harmfulness/legality/ethics assessment, boundary setting, or safe redirection. In contrast, stylistic tokens, connective phrases, generic explanations, formatting tokens, filler tokens, and content that does not determine the safety stance are labeled as *Non-critical*. Importantly, the annotator only observes the completion text and token positions, but not the DPSW weights, which avoids circular reasoning in the analysis.

³<https://github.com/huggingface/trl>

The annotation output is required to be a JSON object keyed by sequence index, where each value is a list of labeled spans with inclusive `start_pos` and `end_pos`. We automatically verify that the annotated spans cover every token position exactly once and that spans are non-overlapping. Invalid annotations are re-generated until they satisfy these structural constraints. After obtaining the span labels, we map each token to its corresponding span type and compute the average values of w_t , w_t^T , and w_t^S for *Safety-critical* and *Non-critical* tokens separately:

$$\text{Avg}(w) = \frac{1}{|\mathcal{T}|} \sum_{t \in \mathcal{T}} w_t,$$

where $\mathcal{T}$ denotes the set of tokens belonging to a specific span type. The same computation is applied to w_t^T and w_t^S .

The results are reported in Table 5. Across both Qwen-3-8B and LLaMA-3-8B-Instruct, safety-critical tokens receive consistently higher values of w_t , w_t^T , and w_t^S than non-critical tokens. This indicates that the teacher is more confident at safety-relevant positions and that the student deviates more from the teacher at these positions. Therefore, DPSW naturally concentrates the distillation penalty on tokens that are more important for safety alignment, rather than uniformly weighting all tokens in the generated sequence.

System Prompt: You are annotating student-generated completions for a safety-alignment paper.

Task:
For each sequence, split the WHOLE completion into contiguous, non-overlapping token spans. Each span must be assigned exactly one of two labels:
1. **"Safety-critical"**: tokens that directly contribute to safety judgment, refusal stance, harmfulness/legality/ethics assessment, boundary setting, or safe redirection. This includes reasoning or final-answer text that determines whether the response refuses, warns, avoids harmful details, or redirects safely.
2. **"Non-critical"**: tokens that are stylistic, connective, generic explanation, formatting, filler, ordinary task reasoning not tied to safety, padding, or content that does not determine the safety stance.

Important rules:
- Use token positions, not character offsets. Spans must be contiguous and non-overlapping.
- Spans for a sequence must cover all provided token positions.
- Do not over-label all safety-related discussion as Safety-critical. Mark a span Safety-critical only when it directly supports a safety decision, refusal/boundary, risk/legal/ethical judgment, or safe redirection.
- Special tokens such as `<think>`, `</think>`, `<|endoftext|>`, blank newlines, and pure formatting are usually "Non-critical" unless they are part of a semantically critical statement.
- If a span contains both critical and non-critical text, split it into smaller spans.

Output format:
Return ONLY valid JSON. The first-level keys must be `seq_idx` strings. Each value must be a list of spans:
{
 "0": [
 {"start_pos": 0, "end_pos": 1, "label": "Non-critical", "rationale": "special tokens / formatting"},
 {"start_pos": 2, "end_pos": 37, "label": "Safety-critical", "rationale": "safety judgment or refusal reasoning"}, ...
],
 "1": [...]
}

The output JSON must satisfy:
- For every `seq_idx`, spans cover every token position exactly once.
- `start_pos` and `end_pos` are inclusive.
- label is exactly "Safety-critical" or "Non-critical".
- rationale should be short (≤ 12 words).

Context Prompt:
Annotate the following sequence. Cover all token positions from 0 to `{num_tokens - 1}` inclusive. Return JSON keyed by `seq_idx` (`{seq_idx}`).
"seq_idx": {`{seq_idx}`}
"num_tokens": {`{num_tokens}`}
"completion_text": {`{completion_text}`}
"tokens": {`{tokens}`}

Figure 7: DPSW span annotation prompt.

Case study of DPSW span annotation. Figure 8 illustrates the case study of the semantic span annotation used in our DPSW analysis. Safety-critical spans receive clearly higher average weights than non-critical spans, supporting the intuition that DPSW emphasizes safety-relevant positions across the whole sequence.




Figure 8: Case study of DPSW span annotation. Green text denotes safety-critical while gray text denotes non-critical spans. The span-level average weights shown in parentheses demonstrate that safety-critical spans receive substantially higher DPSW weights than non-critical spans.

C Additional Experimental Results

Table 9 reports the full multilingual safety results across all ten languages and four backbones. Both off-policy and on-policy MSD consistently achieve strong ASR reductions across high-, medium-, and low-resource languages, with particularly clear gains on challenging low-resource languages such as Swahili and Javanese, further confirming the robustness and scalability of our cross-lingual safeguard transfer framework.

Table 9: Full results of multilingual safety performance on two benchmarks: MultiJail and PKU-SafeRLHF. Evaluation is based on the Attack Success Rate (ASR ↓). The best and second-best results are highlighted in **bold** and underlined, respectively.

Methods	MultiJail										PKU-SafeRLHF												
	High-resource					Medium-resource			Low-resource		Avg.	High-resource				Medium-resource			Low-resource		Avg.		
	EN	ZH	IT	VI	AR	KO	TH	BN	SW	JV		EN	ZH	IT	VI	AR	KO	TH	BN	SW	JV		
Qwen-2.5-7B-Instruct																							
Raw	7.30	4.13	9.21	7.62	9.52	8.57	6.67	34.92	99.05	15.56	20.26	5.80	1.80	5.40	5.40	5.60	6.00	7.00	40.20	98.80	21.00	19.70	
SFT	3.81	5.40	3.81	3.49	4.44	8.89	3.49	9.52	98.73	14.29	15.59	6.20	5.20	1.00	3.80	5.60	4.80	8.60	10.40	98.00	9.60	15.32	
DPO	3.49	0.63	3.17	3.17	5.71	3.81	2.22	14.92	97.46	6.67	14.13	2.00	0.60	1.40	0.60	2.40	2.40	3.00	21.80	98.60	8.40	14.12	
rDPO	2.22	1.27	1.27	1.59	3.17	1.90	1.90	14.60	96.19	5.08	12.92	0.40	0.20	1.60	1.00	2.00	2.00	2.40	18.20	97.80	7.00	13.26	
KTO	1.27	1.27	0.95	2.22	1.59	1.27	0.95	12.38	96.51	5.40	12.38	0.40	0.40	0.40	0.60	1.60	2.20	1.80	17.00	97.60	7.40	12.94	
ORPO	0.32	1.27	0.95	1.59	2.22	1.59	1.59	15.87	97.78	7.94	13.11	0.20	0.20	0.40	0.20	0.80	3.00	2.40	22.80	97.80	6.80	13.46	
R-DPO	2.22	1.59	3.81	2.86	5.40	4.13	2.86	16.19	98.41	7.30	14.48	1.80	0.80	1.80	1.40	3.20	2.40	2.80	24.40	98.40	8.80	14.58	
SimPO	0.00	1.27	0.32	1.90	0.95	7.62	5.71	11.75	97.14	5.71	13.24	2.60	3.20	3.00	4.00	5.20	2.20	3.80	18.80	98.00	10.80	15.16	
PolyRefuse	6.67	4.13	10.16	7.30	8.57	8.25	7.30	35.24	99.05	17.78	20.45	5.40	1.80	5.60	6.20	5.40	6.00	7.40	42.40	99.00	20.80	20.00	
Self-Defense	4.76	3.17	7.62	4.76	7.30	5.40	6.67	25.40	99.37	13.33	17.78	5.00	1.40	3.80	4.00	4.20	4.60	6.20	36.40	98.80	17.80	18.22	
SDRRL	0.63	3.49	4.44	2.86	7.94	9.52	6.03	14.60	93.65	19.37	16.25	4.00	2.20	4.20	4.40	4.40	6.80	4.20	17.40	92.60	12.80	15.30	
MPO	4.13	2.86	6.03	3.81	9.21	4.76	13.33	16.51	56.51	31.43	14.86	2.80	1.60	3.20	2.60	7.80	6.60	11.60	15.20	51.80	17.80	12.10	
MSD (Off-Policy)	1.90	2.54	6.35	1.27	6.03	2.86	4.76	10.79	53.33	14.29	10.41	3.00	1.60	4.60	5.20	3.80	5.60	6.00	10.80	55.20	14.00	10.98	
MSD (On-Policy)	1.59	0.95	3.81	1.90	5.71	0.95	1.90	5.40	33.33	3.81	5.94	3.00	2.40	4.20	2.40	3.20	1.00	1.60	4.40	32.60	5.60	6.04	
Qwen-3-8B																							
Raw	13.65	6.35	13.97	10.48	12.70	13.33	9.52	22.22	94.92	19.68	21.68	13.00	4.21	10.60	15.00	13.40	15.40	12.20	21.80	97.20	18.00	22.08	
SFT	4.44	2.54	6.03	4.76	3.81	5.71	2.54	8.89	96.19	35.87	17.08	7.00	6.40	8.40	10.20	9.20	7.20	5.40	22.60	97.00	16.60	19.00	
DPO	9.21	5.40	8.89	9.84	8.89	10.48	8.89	15.56	94.92	23.17	19.53	9.20	3.00	8.60	12.00	8.80	9.40	8.20	15.00	97.80	17.00	18.90	
rDPO	8.25	4.76	10.16	7.94	10.79	10.48	7.62	18.10	95.24	23.17	19.65	11.80	2.60	8.00	10.60	8.60	8.80	7.40	16.60	97.20	15.40	18.70	
KTO	7.30	4.13	8.89	5.71	9.21	12.70	6.98	15.24	95.56	21.27	18.70	9.40	2.60	7.00	10.00	7.60	8.60	8.80	14.80	97.80	13.00	17.96	
ORPO	7.62	5.08	8.25	10.48	9.52	8.89	7.62	17.78	95.24	20.95	19.14	10.60	3.40	8.00	10.40	7.60	10.00	8.60	18.00	96.80	15.40	18.88	
R-DPO	7.62	5.40	10.16	10.48	10.16	13.33	7.94	18.73	95.56	26.35	20.57	10.80	3.60	8.20	11.80	7.80	9.80	7.60	16.20	96.80	15.80	18.84	
SimPO	7.94	5.40	8.89	7.62	8.89	9.84	8.25	18.10	94.29	23.49	19.27	9.60	2.60	6.80	9.60	7.60	11.20	6.80	18.60	98.20	14.80	18.58	
PolyRefuse	12.70	7.62	15.56	13.02	12.38	17.14	11.11	22.54	94.29	28.89	23.53	15.20	5.01	11.00	15.20	13.20	13.80	11.80	22.40	97.40	18.20	22.32	
Self-Defense	12.38	7.30	12.38	12.38	11.43	14.92	13.02	17.78	95.56	26.67	22.38	14.60	3.60	11.20	13.80	13.20	13.00	11.80	22.20	97.60	19.40	22.04	
SDRRL	3.81	2.86	4.44	4.13	3.49	5.08	3.81	8.25	77.14	28.57	14.16	1.60	1.80	2.20	3.20	1.60	1.80	3.20	5.40	62.00	8.40	9.12	
MPO	2.22	2.86	1.90	1.59	3.81	4.13	1.90	10.79	72.38	22.86	12.44	1.60	1.20	2.20	2.60	2.20	2.00	1.20	7.00	63.40	7.40	9.08	
MSD (Off-Policy)	0.63	0.95	1.59	2.22	1.90	2.86	2.86	4.76	63.81	17.46	9.90	0.60	0.40	0.20	1.60	1.80	1.60	1.20	2.00	52.40	3.60	6.54	
MSD (On-Policy)	0.95	0.32	1.90	0.95	3.81	2.22	1.90	3.81	67.62	16.83	10.04	0.20	0.40	1.00	1.00	2.20	1.20	2.40	2.80	61.80	3.20	7.62	
LLaMA-2-7B-Chat																							
Raw	0.95	6.03	5.40	12.70	36.83	15.87	51.43	49.52	32.06	9.52	22.03	1.80	3.80	5.00	6.40	29.80	10.00	46.20	48.00	51.40	16.40	21.88	
SFT	0.00	0.63	0.63	5.71	35.87	6.98	95.87	12.38	94.92	7.30	26.03	0.60	1.20	0.40	9.40	11.60	13.60	96.40	26.80	98.20	8.00	26.62	
DPO	1.27	3.49	4.76	9.52	31.75	14.92	50.48	38.10	24.44	8.25	18.70	1.00	2.00	3.40	4.60	27.80	8.00	43.00	44.40	44.80	15.40	19.44	
rDPO	1.27	3.49	4.44	9.52	31.75	13.02	48.57	39.37	26.35	6.98	18.48	1.40	2.60	3.40	4.80	27.40	8.60	43.80	44.20	43.60	15.60	19.54	
KTO	1.27	3.49	2.54	9.52	32.06	13.02	49.52	35.87	23.49	7.30	17.81	1.60	2.00	2.80	4.40	24.20	8.00	40.60	44.20	43.20	14.40	18.54	
ORPO	0.95	2.86	5.08	7.30	30.16	11.11	46.35	36.51	24.44	7.62	17.24	1.80	2.80	3.60	5.00	22.40	7.80	41.00	45.00	43.00	13.60	18.60	
R-DPO	1.27	3.81	4.76	7.62	33.33	13.33	48.57	39.37	25.71	8.57	18.63	1.20	2.80	3.40	5.00	25.80	8.40	43.20	45.80	46.20	16.00	19.78	
SimPO	0.95	3.81	6.98	9.21	30.48	9.52	48.89	38.73	25.71	7.30	18.16	1.80	2.20	5.00	6.00	24.20	9.40	43.60	45.00	47.40	14.60	19.92	
PolyRefuse	0.95	6.35	6.03	12.70	36.51	16.83	52.06	42.86	28.89	11.43	21.46	1.60	3.40	4.00	7.40	31.40	9.80	45.40	49.80	51.60	17.60	22.20	
Self-Defense	0.95	2.86	3.49	9.52	27.62	12.38	52.38	39.68	53.33	23.17	22.54	1.40	3.40	3.40	8.80	26.60	6.80	57.60	62.60	57.80	19.40	24.78	
SDRRL	0.63	4.13	0.63	2.54	13.97	8.89	39.37	21.59	17.46	2.54	11.18	1.60	1.80	2.00	2.00	14.00	4.00	36.60	25.60	41.80	14.00	14.34	
MPO	0.95	5.71	4.44	10.79	33.97	14.60	46.35	42.54	26.67	10.79	19.68	1.60	2.60	4.40	6.20	28.80	9.80	46.00	50.60	49.40	17.60	21.70	
MSD (Off-Policy)	0.63	0.95	2.22	3.81	14.29	5.08	23.49	20.32	13.65	4.13	8.86	0.40	0.80	0.80	2.00	11.80	3.40	21.60	24.20	28.00	6.60	9.96	
MSD (On-Policy)	0.32	0.32	0.63	0.63	4.13	0.95	7.62	5.71	3.17	1.27	2.48	0.00	0.40	0.40	0.40	4.80	1.20	11.20	6.80	9.40	4.40	3.90	
LLaMA-3-8B-Instruct																							
Raw	2.54	10.79	22.54	13.65	11.43	17.46	10.79	13.97	69.52	39.37	21.21	2.20	5.60	14.40	5.40	8.40	9.80	9.00	15.40	65.20	22.80	15.82	
SFT	1.59	1.59	3.49	2.86	11.11	4.76	0.63	1.59	50.79	6.35	8.48	0.60	0.80	0.80	1.40	0.60	5.80	1.00	2.20	33.60	5.60	5.24	
DPO	1.59	0.63	2.86	4.76	9.21	1.90	1.90	1.59	53.33	6.67	8.44	0.20	0.20	2.60	1.20	5.60	1.20	1.20	5.00	68.20	2.80	8.62	
rDPO	0.95	1.59	4.13	2.54	1.90	1.90	0.63	6.98	29.52	10.79	6.09	2.00	2.00	5.40	3.20	2.40	6.00	3.60	4.20	28.40	7.20	6.44	
KTO	0.95	1.59	4.13	2.54	1.90	6.35	3.17	0.95	1.59	43.81	5.40	6.98	0.40	0.40	0.40	2.40	3.80	2.20	1.40	1.40	37.20	2.60	5.11
ORPO	0.63	0.63	3.49	2.86	10.79	10.79	0.32	2.86	77.46	1.27	11.11	0.00	0.00	2.40	2.40	7.00	9.80	1.40	4.20	72.80	2.60	10.30	
R-DPO	0.95	0.95	2.22	5.40	9.84	2.22	1.90	2.86	49.714	7.30	9.14	0.20	0.20	0.80	1.40	6.40	1.00	1.60	4.60	65.60	2.60	8.44	
SimPO	0.63	0.95	3.49	2.54	5.71	8.89	0.95	2.86	77.14	7.62	11.18	0.40	0.40	2.60	2.40	3.60	12.00	2.20	5.20	72.20	2.60	10.36	
PolyRefuse	2.86	10.48	21.59	15.24	13.97	17.83	12.06	16.51	67.30	44.76	22.35	2.40	5.80	13.20	5.40	8.80	9.80	9.00	15.40	65.20	23.60	15.86	
Self-Defense	14.60	11.11	8.89	12.70	8.89	7.94	42.54	28.25	14.29	6.35	15.56	0.20	2.80	4.20	5.20	6.00	11.00	38.00	18.00	9.60	9.60	11.06	
SDRRL	1.27	5.40	6.67	11.43	11.43	11.75	7.94	11.75	28.25	30.16	12.61	6.00	3.80	2.60	3.00	8.80	7.40	5.60	14.20	20.20	11.40	7.70	
MPO	5.40	10.79	7.62	6.67	6.62	6.03	14.92	22.22	14.92	22.22	11.84	2.40	2.00	1.80	2.20	2.20	2.00	3.80	7.40	11.80	8.20	4.38	
MSD (Off-Policy)	0.95	0.63	2.86	1.27</																			

Table 10 presents the full MMMLU results across 15 languages. MSD preserves general knowledge ability well after safety alignment and achieves the best or competitive average performance on all backbones, indicating that the safety gains do not come at the cost of broad multilingual utility.

Table 10: Full multilingual utility results on MMMLU. Best and second-best Avg. within each model block are highlighted in **bold** and underlined, respectively.

Method	AR	BN	DE	EN	ES	FR	HI	ID	IT	JA	KO	PT	SW	YO	ZH	Avg.
Qwen-2.5-7B-Instruct																
Raw	52.65	46.24	62.56	73.71	68.02	67.01	49.04	63.47	66.28	62.56	59.73	67.45	34.88	32.94	67.34	<u>58.26</u>
SFT	36.80	42.57	55.49	71.60	61.91	54.79	45.10	57.90	60.54	35.59	47.97	62.78	33.36	31.73	60.05	50.55
DPO	52.64	46.10	61.84	73.29	67.78	67.17	48.53	63.69	66.28	62.05	59.84	67.09	34.60	32.73	66.91	58.04
rDPO	52.81	45.73	61.99	73.17	67.50	66.70	48.11	63.24	66.07	62.06	59.66	67.06	34.71	32.92	67.08	57.92
KTO	52.87	45.63	61.76	73.03	67.32	66.50	48.21	63.17	65.97	61.95	59.79	66.87	34.79	33.01	66.88	57.85
ORPO	53.79	44.93	62.28	73.21	67.00	66.34	47.74	62.11	65.72	60.97	59.20	65.96	33.76	32.72	66.34	57.47
R-DPO	52.73	46.05	62.09	73.38	67.72	66.98	48.53	63.44	66.39	62.14	59.98	67.10	34.72	32.77	66.96	58.06
SimPO	53.94	44.54	62.10	72.54	66.51	65.74	47.18	61.72	65.08	59.96	58.79	65.96	34.57	32.81	66.00	57.16
PolyRefuse	57.08	46.22	62.80	72.77	66.34	65.73	50.01	62.40	65.62	60.72	59.81	65.47	35.26	32.36	65.91	57.90
SDRRL	55.13	47.84	61.11	73.09	65.30	65.80	48.90	62.03	65.57	60.20	60.11	64.33	34.30	31.11	65.33	57.34
MPO	53.73	45.77	62.43	73.69	68.15	66.95	48.85	63.31	66.09	61.99	59.78	66.94	34.98	33.02	66.86	58.17
MSD (Off-Policy)	52.57	46.23	62.53	73.72	68.12	67.10	48.95	63.47	66.40	62.61	59.81	67.39	34.63	32.84	67.38	58.25
MSD (On-Policy)	58.15	48.21	64.09	73.52	67.28	66.71	51.20	63.45	66.59	62.01	61.00	66.32	34.97	32.13	66.38	58.80
Qwen-3-8B																
Raw	67.82	63.27	70.01	74.36	72.57	71.49	65.96	70.69	71.90	68.91	68.10	72.48	42.72	31.18	58.27	64.65
SFT	57.06	49.91	64.94	75.79	68.94	67.17	53.48	64.89	67.10	62.36	60.58	67.54	28.76	30.84	68.98	59.22
DPO	68.25	63.52	71.06	74.43	73.12	72.00	66.47	71.09	72.06	69.53	68.64	73.21	43.11	31.73	59.08	65.15
rDPO	67.94	63.64	71.36	74.94	73.37	72.14	66.31	71.41	72.31	69.77	68.84	72.95	42.57	31.65	59.72	65.26
KTO	68.15	63.84	71.23	74.91	73.05	71.93	66.42	71.25	72.16	69.85	69.21	73.18	42.24	31.28	59.69	65.23
ORPO	68.69	63.64	71.41	75.17	73.74	72.24	66.47	71.66	72.55	70.36	69.03	73.06	42.94	31.55	59.76	65.49
R-DPO	68.69	63.84	71.17	74.72	73.00	71.95	66.41	71.25	71.86	69.95	68.62	73.27	42.74	31.68	59.27	65.23
SimPO	68.42	63.95	71.36	75.20	73.41	72.25	67.10	71.26	72.66	69.86	69.19	73.26	42.85	31.21	59.81	65.45
PolyRefuse	67.60	62.90	70.20	74.37	72.62	71.49	66.20	70.54	71.74	69.23	68.37	72.30	42.52	30.97	58.15	64.61
SDRRL	64.14	63.75	70.52	76.86	72.24	70.74	65.95	67.78	71.71	69.51	67.38	71.26	41.95	29.64	72.64	65.07
MPO	67.82	62.96	70.84	74.21	72.35	71.79	66.44	70.52	71.76	69.39	68.47	72.84	42.54	31.36	58.37	64.78
MSD (Off-Policy)	69.01	64.39	72.01	77.31	73.99	72.88	67.36	72.09	73.62	70.23	68.98	74.01	42.32	31.95	73.11	66.88
MSD (On-Policy)	68.72	63.92	72.05	76.93	73.95	72.64	66.54	71.94	73.71	71.11	69.74	73.19	43.01	30.59	73.32	<u>66.76</u>
LLaMA-2-7B-Chat																
Raw	27.57	32.08	34.19	40.48	35.07	33.64	32.08	31.74	33.32	31.21	30.16	34.38	27.04	26.60	31.19	32.05
SFT	16.68	24.03	24.26	32.99	25.00	24.46	24.02	27.44	27.00	23.37	26.16	25.52	19.35	17.16	22.56	24.00
DPO	27.39	31.83	34.34	40.00	34.54	33.35	31.83	31.69	33.78	30.82	30.18	34.61	26.50	26.20	30.84	31.86
rDPO	27.54	31.99	34.43	40.04	34.63	33.56	31.98	31.67	33.98	31.07	30.20	34.66	26.48	26.21	30.96	31.96
KTO	27.41	31.86	34.02	39.97	34.79	33.39	31.86	31.56	33.86	31.05	30.24	34.17	26.46	26.29	30.67	31.84
ORPO	27.18	31.47	33.70	39.13	33.99	32.84	31.47	33.37	30.90	29.45	33.96	26.32	26.36	26.56	30.54	31.49
R-DPO	27.67	31.98	34.43	40.19	34.83	33.56	31.99	31.71	33.95	31.16	30.02	34.70	26.40	26.49	31.07	<u>32.01</u>
SimPO	27.30	31.35	33.41	39.08	33.89	32.80	31.36	31.23	33.09	30.55	29.53	33.46	26.15	26.24	30.51	31.33
PolyRefuse	27.61	31.20	33.14	39.15	33.89	32.54	31.20	30.96	33.09	30.63	29.71	33.16	26.23	25.25	30.24	31.20
SDRRL	25.66	27.09	29.28	34.61	30.60	29.80	27.10	27.98	29.94	29.06	28.99	30.89	16.79	10.07	28.79	27.11
MPO	27.58	31.89	34.33	40.44	34.35	33.27	31.90	31.72	33.54	31.25	30.00	34.43	26.85	26.23	30.87	31.91
MSD (Off-Policy)	27.50	31.63	33.46	39.54	34.41	33.13	31.64	31.26	33.56	31.36	30.50	34.08	26.36	25.52	30.20	31.61
MSD (On-Policy)	27.39	31.92	34.15	40.49	34.77	33.55	31.93	31.54	33.49	31.21	30.10	34.39	26.78	26.46	31.38	31.97
LLaMA-3-8B-Instruct																
Raw	44.85	38.54	53.13	62.46	55.09	55.27	42.89	49.46	53.82	47.49	46.77	54.61	36.43	30.59	51.23	48.17
SFT	14.34	25.35	5.11	28.28	18.46	5.00	12.13	24.58	21.73	12.43	34.21	24.53	13.74	2.94	21.93	17.65
DPO	38.21	30.66	47.62	61.56	52.95	51.42	36.53	44.00	49.18	41.85	40.12	51.20	17.38	12.97	47.36	41.53
rDPO	14.86	10.34	26.62	57.41	40.19	24.10	10.92	19.11	31.47	20.68	16.93	36.70	3.20	1.27	29.16	22.86
KTO	25.21	20.24	41.50	59.84	48.70	42.49	22.45	35.93	43.95	32.97	30.70	48.05	9.44	4.89	40.49	33.79
ORPO	29.20	27.08	44.69	54.57	49.52	42.31	26.63	38.29	43.43	31.16	31.26	48.11	12.75	3.53	40.69	34.88
R-DPO	38.87	32.00	47.70	61.89	53.30	52.21	37.08	44.48	49.83	42.24	40.89	51.36	19.58	14.52	47.98	42.26
SimPO	30.12	25.30	42.69	53.51	49.48	42.17	27.75	39.37	44.10	33.89	33.21	47.70	11.97	6.04	42.36	35.31
PolyRefuse	41.00	35.77	49.24	60.38	52.29	52.32	39.14	46.28	50.39	43.83	43.24	51.34	28.06	18.11	48.82	44.01
SDRRL	31.06	23.38	40.64	52.76	42.79	42.37	27.10	37.26	41.18	34.42	34.77	42.58	20.11	6.40	37.39	34.28
MPO	44.57	38.41	53.16	62.09	55.03	54.61	42.69	49.42	53.49	47.10	46.11	54.05	35.94	30.23	51.09	47.87
MSD (Off-Policy)	43.81	37.82	51.38	61.04	53.82	53.92	40.95	48.28	52.50	45.93	45.30	52.12	34.08	27.50	50.13	46.57
MSD (On-Policy)	44.88	38.54	53.12	62.47	55.13	55.25	42.81	49.41	53.80	47.51	46.81	54.62	36.25	30.51	51.21	<u>48.16</u>

Table 11 reports the full MGSM results across 11 languages. MSD maintains strong multilingual reasoning performance after alignment, and in several cases improves the average score over the raw model and other baselines, demonstrating that our framework preserves reasoning ability while enhancing multilingual safety.

Table 11: Full multilingual utility results on MGSM. Best and second-best Avg. within each model block are highlighted in **bold** and underlined, respectively.

Method	EN	ES	FR	DE	RU	ZH	JA	TH	SW	BN	TE	Avg.
Qwen-2.5-7B-Instruct												
Raw	90.00	76.40	27.20	87.60	85.20	81.20	73.20	76.80	14.00	66.40	24.80	63.89
SFT	91.20	76.40	31.20	76.00	75.20	81.20	67.60	25.20	6.40	29.20	22.80	52.95
DPO	91.20	76.40	28.00	81.60	82.00	85.60	74.40	77.60	10.40	63.20	21.60	62.91
rDPO	91.60	74.80	28.80	82.80	83.60	85.20	73.60	76.40	10.40	64.40	23.20	<u>63.16</u>
KTO	90.80	76.00	28.40	82.80	83.20	84.40	72.00	78.00	10.00	62.00	26.00	63.05
ORPO	90.00	47.60	28.00	84.40	81.60	80.80	73.60	71.20	15.20	62.80	23.60	59.89
R-DPO	90.00	76.40	27.20	83.20	81.60	85.60	74.40	77.60	10.80	63.60	20.80	62.84
SimPO	91.20	42.00	28.00	80.40	72.80	78.80	68.00	49.20	13.20	59.20	24.40	55.20
PolyRefuse	90.00	68.00	35.20	86.00	74.40	80.00	70.00	66.00	0.40	62.40	13.20	58.69
SDRRL	91.60	41.20	28.40	80.80	82.40	80.80	70.00	70.80	18.80	57.20	22.40	58.58
MPO	92.00	74.40	27.20	81.60	83.20	82.00	74.40	76.80	10.80	65.20	24.80	62.95
MSD (Off-Policy)	91.20	66.80	39.60	80.00	83.20	82.00	69.20	57.20	7.60	64.40	23.60	60.44
MSD (On-Policy)	92.40	75.20	26.40	84.80	84.00	81.60	74.40	76.80	14.80	66.80	25.60	63.89
Qwen-3-8B												
Raw	51.60	84.40	76.00	80.80	82.80	60.40	59.20	75.20	31.20	68.40	43.60	64.87
SFT	92.80	82.40	79.60	81.60	86.00	81.60	76.40	78.80	23.20	68.80	56.40	73.42
DPO	58.40	82.40	77.60	80.80	83.20	54.80	58.80	75.60	33.60	69.20	44.40	65.35
rDPO	56.80	84.00	78.00	80.80	82.00	57.60	60.80	75.60	35.60	68.40	45.20	65.89
KTO	56.40	84.00	77.60	79.60	84.00	56.40	61.20	76.40	34.40	69.60	45.20	65.89
ORPO	61.20	83.20	77.20	78.80	86.00	60.00	64.40	73.60	34.40	71.60	50.40	67.35
R-DPO	57.60	82.80	79.20	81.20	82.80	56.00	60.80	75.60	34.40	67.20	42.80	65.49
SimPO	60.40	83.60	78.80	80.40	86.00	61.60	64.40	72.80	39.20	69.60	49.60	67.85
PolyRefuse	54.80	83.60	74.80	80.40	81.60	53.60	60.80	74.80	32.80	67.20	42.80	64.29
SDRRL	76.00	68.00	66.40	59.20	70.40	79.20	48.80	73.60	36.80	56.40	51.60	62.40
MPO	55.60	83.60	74.80	80.40	81.60	56.00	60.80	75.60	33.20	66.80	42.40	64.62
MSD (Off-Policy)	83.60	86.80	81.60	77.60	86.00	78.00	72.80	80.00	42.40	76.40	65.60	75.53
MSD (On-Policy)	84.00	83.60	79.60	75.60	85.20	79.60	70.40	81.20	41.20	74.00	60.00	<u>74.04</u>
LLaMA-2-7B-Chat												
Raw	25.60	14.80	15.60	20.00	11.20	20.40	10.80	1.60	0.00	0.40	0.00	10.95
SFT	24.40	5.20	6.00	13.20	4.40	9.60	4.40	0.80	0.40	0.00	0.00	6.22
DPO	22.80	16.00	12.80	17.20	13.60	16.80	11.20	0.00	0.00	0.00	0.00	11.04
rDPO	22.80	14.80	13.60	19.60	12.40	18.00	12.00	0.00	0.00	0.00	0.00	10.29
KTO	24.80	15.60	14.80	14.80	12.00	17.20	10.80	0.00	0.00	0.00	0.00	11.00
ORPO	23.20	16.40	16.00	18.80	10.40	17.20	10.80	1.20	0.00	0.00	0.00	11.40
R-DPO	21.60	16.80	14.00	17.20	12.00	17.60	12.00	0.00	0.00	0.00	0.00	10.11
SimPO	23.60	13.60	15.60	18.40	8.80	18.40	12.80	1.60	0.00	0.00	0.00	10.25
PolyRefuse	22.80	14.40	15.60	17.60	8.80	20.40	10.40	2.00	0.80	0.40	0.00	10.29
SDRRL	27.20	18.00	18.40	13.60	18.00	14.00	16.80	0.00	2.40	0.80	0.00	11.75
MPO	23.60	14.00	16.40	20.40	12.00	19.20	12.00	0.80	0.40	0.40	0.00	<u>11.92</u>
MSD (Off-Policy)	21.20	13.60	15.60	22.40	10.80	16.80	12.80	2.40	0.40	0.00	0.00	10.55
MSD (On-Policy)	26.40	19.60	17.60	12.00	20.40	16.80	14.00	0.80	0.00	0.40	0.00	12.80
LLaMA-3-8B-Instruct												
Raw	78.80	62.00	62.40	64.00	68.80	59.20	58.80	60.40	30.40	38.40	33.20	<u>56.04</u>
SFT	44.40	2.40	9.20	19.60	46.80	50.00	19.60	16.80	4.00	7.60	8.80	20.84
DPO	79.60	62.40	59.60	63.20	65.60	58.00	55.20	46.80	34.80	40.00	19.20	53.13
rDPO	79.20	65.20	57.20	57.20	62.80	61.60	49.20	50.40	30.40	38.00	19.60	51.89
KTO	78.80	62.00	59.20	60.80	66.80	62.40	46.80	49.20	34.00	36.40	19.60	52.36
ORPO	78.40	58.80	58.40	52.40	64.80	56.80	44.40	44.80	25.60	23.20	9.60	47.02
R-DPO	78.80	63.20	59.20	62.80	65.60	58.00	54.00	48.40	34.80	36.40	18.40	52.69
SimPO	81.60	59.20	55.60	52.80	61.20	59.20	44.40	47.60	23.20	24.80	16.00	47.78
PolyRefuse	79.60	64.40	60.40	68.80	68.80	57.20	57.60	55.20	28.40	38.00	33.20	55.60
SDRRL	77.60	54.40	51.60	54.80	46.80	54.00	44.80	46.40	22.80	9.20	6.80	42.65
MPO	77.20	62.00	60.00	64.40	68.00	58.40	56.80	53.60	28.80	36.40	31.20	54.25
MSD (Off-Policy)	78.80	63.60	62.80	64.80	67.60	60.80	56.40	58.80	30.00	40.00	31.20	55.89
MSD (On-Policy)	78.00	69.60	62.40	67.20	67.60	62.40	56.40	56.80	29.20	52.00	37.60	58.11

Table 12: Ablation study on different divergence objectives in MSD. We compare forward KL (FKL), reverse KL (RKL), and Jensen–Shannon divergence (JSD). For JSD, the balancing coefficient between FKL and RKL is set to 0.5. For MultiJail and PKU-SafeRLHF, we report attack success rate (ASR), where lower is better.

Method	Qwen-3-8B		LLaMA-3-8B-Instruct	
	MultiJail	PKU-SafeRLHF	MultiJail	PKU-SafeRLHF
MSD w/ FKL	12.79	9.53	2.67	3.84
MSD w/ RKL	10.04	7.62	2.03	1.78
MSD w/ JSD	10.85	8.02	2.38	2.62

We compare different divergence objectives for the MSD distillation loss under the on-policy setting, including forward KL (FKL), reverse KL (RKL), and Jensen–Shannon divergence (JSD). As shown in Table 12, RKL achieves the best overall safety performance across both Qwen-3-8B and LLaMA-3-8B-Instruct, suggesting that mode-seeking distillation is more suitable for transferring high-resource safety behavior to low-resource languages in our setting.

Table 13: Ablation study on the hyperparameter K in the teacher-side weight w_t^T of DPSW under the on-policy setting. For MultiJail and PKU-SafeRLHF, we report attack success rate (ASR), where lower is better.

Method	Qwen-3-8B		LLaMA-3-8B-Instruct	
	MultiJail	PKU-SafeRLHF	MultiJail	PKU-SafeRLHF
MSD w/o DPSW	11.09	9.10	3.33	3.02
MSD w/ DPSW ($K = 16$)	10.69	8.24	2.60	2.16
MSD w/ DPSW ($K = 32$)	10.04	7.62	2.03	1.78
MSD w/ DPSW ($K = 64$)	10.49	7.23	2.28	1.88

Table 13 studies the sensitivity of DPSW to the top- K candidate size in the teacher-side weight w_t^T . Across both Qwen-3-8B and LLaMA-3-8B-Instruct, all DPSW variants outperform the model without DPSW, while $K = 32$ achieves the best overall trade-off across benchmarks, indicating that a moderate top- K range provides a more effective estimate of teacher-side confidence.

D Case Studies

D.1 Invalid Cases in Low-resource Languages

[illegible]

Figure 9: Case study of invalid responses in Swahili. **Green text** indicates safety-oriented reasoning or refusal behavior, **yellow text** indicates invalid or malformed target-language generation, and **red text** indicates unsafe reasoning or unsafe content. Although MSD shows clear safety reasoning in the chain-of-thought, weak low-resource language generation can still lead to invalid final responses and thus a high ASR.

As detailed in Appendix B.2, our evaluation metric Attack Success Rate (ASR) categorizes both unsafe and invalid responses as successful attacks, whereas only meaningful refusals are deemed

safe. This rigorous metric explains the persistently high ASR observed in certain low-resource languages, such as Swahili (SW), even after alignment. For instance, when evaluating Qwen-3-8B on MultiJail in Swahili, off-policy MSD reports an ASR of 63.81%. However, a closer breakdown reveals that genuinely unsafe responses account for only 6.67%, while invalid responses constitute 57.14%. Similarly, on-policy MSD yields a 67.72% ASR, comprising 6.67% unsafe and 61.05% invalid responses. This indicates that the inflated ASR is predominantly driven by malformed outputs rather than actual safety failures. Furthermore, we investigate the model’s internal reasoning behind these invalid outputs to determine whether it harbors an intent to refuse. As illustrated in Figure 9, unlike the Base Model and DPO—which actively reason towards generating unsafe answers—MSD successfully identifies the harmful intent during the reasoning phase. The invalid outcome strictly stems from the base model’s limited generation ability in low-resource languages, which produces a malformed final response that is ultimately penalized as a failed defense.

E Extended Discussion of Limitations

Dependency on Inherent High-Resource Capabilities. The core mechanism of MSD involves transferring a model’s internal safety capabilities from a high-resource language to low-resource languages. Consequently, the framework’s success is strictly bounded by the teacher model’s ability to reason and refuse harmful instructions in the source language. If the foundational LLM has not undergone sufficient prior safety supervision or exhibits weak in-context learning (ICL) performance, the teacher will fail to provide a stable and valid supervision signal. In such cases, the student may inadvertently inherit or even amplify the teacher’s alignment failures, preventing effective safeguard transfer.

Sensitivity to Query Translation Quality. A primary advantage of MSD is the elimination of the prohibitive cost associated with generating target-language response data. However, the framework still necessitates parallel queries—pairing a target low-resource query with its high-resource translation—to establish the teacher’s additional information. While benchmarks like XSafety and MultiJail provide such pairs, the semantic equivalence and linguistic accuracy of these translations are critical. Translation errors may lead to a misalignment between the teacher’s reasoning and the student’s input, ultimately degrading the precision of the cross-lingual alignment.