

What Concepts Lie Within? Detecting and Suppressing Risky Content in Diffusion Transformers

Chenyu Zhang
Tianjin University
Tianjin, China
zcy@tju.edu.cn

Lanjun Wang
Tianjin University
Tianjin, China
wang.lanjun@outlook.com

Yueyang Cheng
Tianjin University
Tianjin, China
cyyang@tju.edu.cn

Ruidong Chen
Tianjin University
Tianjin, China
chenruidong@tju.edu.cn

Wenhui Li
Tianjin University
Tianjin, China
liwenhui@tju.edu.cn

An-an Liu
Tianjin University
Tianjin, China
anan0422@gmail.com

Abstract

The rise of text-to-image (T2I) models has increasingly raised concerns regarding the generation of risky content, such as sexual, violent, and copyright-protected images, highlighting the need for effective safeguards within the models themselves. Although existing methods have been proposed to eliminate risky concepts from T2I models, they are primarily developed for earlier U-Net architectures, leaving the state-of-the-art Diffusion-Transformer-based T2I models inadequately protected. This gap stems from a fundamental architectural shift: Diffusion Transformers (DiTs) entangle semantic injection and visual synthesis via joint attention, which makes it difficult to isolate and erase risky content within the generation. To bridge this gap, we investigate how semantic concepts are represented in DiTs and discover that attention heads exhibit concept-specific sensitivity. This property enables both the detection and suppression of risky content. Building on this discovery, we propose AHV-D&S, a training-free inference-time safeguard for image generation in DiTs. Specifically, AHV-D&S quantifies each textual token’s sensitivity across all attention heads as an Attention Head Vector (AHV), which serves as a discriminative signature for detecting risky generation tendencies. In the inference stage, we propose a momentum-based strategy to dynamically track token-wise AHVs across denoising steps, and a sensitivity-guided adaptive suppression strategy that suppresses the attention weights of identified risky tokens based on head-specific risk scores. Extensive experiments demonstrate that AHV-D&S effectively suppresses sexual, copyrighted-style, and various harmful content while preserving visual quality, and further exhibits strong robustness against adversarial prompts and transferability across different DiT-based T2I models. These results establish AHV-D&S as a practical safeguard for the safe deployment of modern T2I models.

Keywords

Diffusion Transformers, Text-to-Image Models, Risk Suppression, Content Safety

1 Introduction

The landscape of text-to-image (T2I) models [3, 4, 7, 10, 36, 38] has recently undergone a pivotal architectural evolution, marking a transition from traditional convolutional U-Net backbones to Diffusion Transformer (DiT) architectures. This paradigm shift has significantly enhanced the scalability and generative fidelity




Figure 1: Adversarial prompts implicitly convey the risky semantics through using multiple ambiguous words under specific contextual scenarios.

of T2I models by leveraging the global context modeling capabilities of DiT over joint image and text representations. However, recent work [44] shows that as generative performance improves, associated safety risks become increasingly pronounced, such as sexual, bloody, and copyright-protected images. This risk is further reflected in real-world evidence. The Internet Watch Foundation reported record levels of AI-generated child sexual abuse material in 2025, including more than a 260-fold increase in images and videos identified by its analysts compared with the previous year, suggesting that improvements in generative quality can directly amplify harmful misuse at scale [21]. Consequently, ensuring the safety of generated content and preventing the synthesis of risky concepts have emerged as paramount research imperatives to guarantee the responsible deployment of generative AI.

To ensure the safety of generated images, concept erasure [6, 11, 12, 28, 34] has emerged as an important technique that aims to fine-tune model parameters or adjust inference behavior to steer generation away from risky images. Along the T2I generation pipeline, existing methods can be divided into encoder-based and denoising-based erasure methods, where encoder-based methods aim to erase risky representations in the text encoder and denoising-based methods erase risky representations in the denoising network. However, both kinds of methods struggle to achieve effective protection in




Figure 2: Traditional U-Net-based concept erasure methods aim to fine-tune the cross-attention (a) or self-attention (b) layers to erase risky text or image representation, respectively. However, Diffusion Transformer employs a joint attention to model the complex interaction between the text and image, reducing the effectiveness of traditional methods.

DiT-based T2I models. First, **the text encoder is not robust to capturing risk semantics**. Specifically, as shown in Fig. 1, the risky semantics in adversarial prompts [39, 42, 43] are often expressed through multiple ambiguous words that become risky only under specific contextual compositions. Parsing such risky semantics usually requires in-depth semantic reasoning and therefore cannot be reliably captured by text encoding alone [42]. Second, **traditional denoising-based methods are primarily designed for U-Net-based T2I models and struggle to transfer to DiT-based T2I models**. Specifically, as shown in Fig. 2(a) and (b), these methods can be further divided into two categories: erasing risky text representations in cross-attention [6, 12, 28], and erasing risky image representations in self-attention [25, 27]. These strategies are effective because U-Net-based T2I models adopt a relatively decoupled design, where cross-attention is used to inject text semantics, while self-attention mainly improves visual quality. However, as shown in Fig. 2(c), recent DiT-based T2I models abandon this decoupled architecture and instead adopt a joint attention mechanism that simultaneously handles text semantic injection and image generation. Although joint attention improves image generation through complex interactions between the text and image, it also makes it more difficult to disentangle risky text and image representations, thereby reducing the effectiveness of traditional erasure methods. Therefore, **these challenges highlight the critical need for a robust concept erasure strategy in DiT-based T2I models**.

To address this issue, we present a comprehensive study with three progressive stages. **S1:** We perform an analysis to understand how DiTs represent risky concepts (Sec. 3). **S2:** Based on above insights, we propose AHV-D&S, a training-free method that dynamically detects and suppresses risky representations in DiTs (Sec. 4). **S3:** We conduct extensive evaluations to demonstrate the effectiveness, robustness, and transferability of our method (Sec. 5 and Sec. 6). The details of each stage are presented as follows.

S1: An Analysis of Concept Representation in DiTs. Understanding how DiTs internally represent a concept is crucial for designing effective concept erasure methods. In particular, the model’s attention mechanisms provide a natural window into concept representation: the activation weight in attention heads associated with specific tokens reflects the semantic influence of those tokens on the generated image [17, 18, 29, 30]. Therefore, we conduct an investigation of the correlation between attention head

maps and concept tokens. First, to study the relation between different attention heads and specific concepts, we define a variable termed *Attention Head Sensitivity*, which is computed by aggregating the activation weights from image tokens to given concept tokens within an attention head map. Our experiments show that attention heads exhibit varying degrees of sensitivity to specific concept tokens (Fig. 3). Moreover, we observe that suppressing only a sparse subset of highly sensitive heads is already sufficient to alter the final visual outcome (Fig. 5). Second, we further extend this observation from a single concept to multiple concepts and define a vector called the *Attention Head Vector (AHV)*. Specifically, this vector is constructed by concatenating the sensitivities of all attention heads to given textual concepts into a one-dimensional representation. Intuitively, it can be understood as a trajectory that characterizes how the DiTs attend to concept tokens during the forward inference process. Our analysis reveals that AHV provides a discriminative and quantifiable signature of token-level generative semantics (Sec. 3.3). It not only separates benign concepts with distinct visual semantics but also distinguishes risky concepts from safe ones, enabling us to estimate the model’s generative inclination toward risky content.

S2: A Method for Risky Content Detection and Suppression. Based on the above empirical observations, we propose AHV-D&S, a training-free method that enables safe image generation by dynamically detecting the AHV of input tokens for risk identification, and suppressing the attention weights associated with risky tokens. Specifically, the proposed method consists of two modules: momentum-based AHV measurement and sensitivity-guided adaptive suppression. The first module aims to estimate the token-wise AHVs in real-time during the inference stage. Since T2I models require multiple denoising steps to generate a single image, the AHV of each token evolves dynamically throughout the denoising process. To capture this behavior, we design a momentum update strategy that measures token-wise AHVs through global AHV initialization together with local momentum updates. The second module aims to detect the risk of token-wise AHVs and then suppress the attention weights associated with risky tokens. Given that AHVs themselves exhibit strong distinctions between risk concepts and safe ones, we measure the risk score of an input token by comparing its similarity to risky AHVs and safe AHVs. Meanwhile, motivated by the insight that suppressing attention weights in a

subset of highly sensitive heads is sufficient to mitigate risky content, we further introduce a sensitive-guided adaptive suppression strategy so that token risk scores can be adjusted adaptively across different attention heads. Intuitively, this strategy automatically relaxes the decision criterion in risk-sensitive attention heads, enabling proactive suppression of ambiguous tokens in adversarial prompts, while maintaining a stricter criterion in other heads to preserve normal generation for safe images. In conclusion, AHV-D&S suppresses the attention weights associated with the selected risky tokens, thereby reducing unsafe content generation.

S3: Evaluation. We conduct extensive evaluations to assess the risk suppression ability, benign preservation ability, and robustness of AHV-D&S compared against six state-of-the-art baselines, as well as its transferability across T2I models and hyper-parameter sensitivity. Results demonstrate AHV-D&S's superiority in the following key aspects: 1) Compared with six state-of-the-art baselines, AHV-D&S achieves superior safety-utility performance in FLUX [2], across three suppression tasks. Specifically, for sexual content, it reduces the overall risk ratio from 100.0% to 45.9%, outperforming the strongest baseline by 15.4%. For copyrighted-protected styles, it achieves the best overall trade-off with Δ CLIP of 2.93 and Δ LPIPS of 0.13. For harmful content, it reduces the risk ratios of blood, horror, weapons, and drug use to 33.4%, 52.3%, 35.2%, and 22.7%, respectively. Moreover, AHV-D&S also preserves benign generation quality with competitive CLIP, FID, and LPIPS scores. 2) Under four adversarial prompt benchmarks, AHV-D&S consistently achieves the lowest risk ratios, with up to 28.1% improvement over the strongest baseline. 3) Our method shows effective transferability on Qwen-Image [36], reducing the sexual risk ratio from 100.0% to 38.0%. To summarize, our contributions are as follows:

- We provide two new insight about the concept representation in DiTs: the attention head exhibits concept-specific sensitivities and attention head vector offers a measurable way to characterize token-level risk generation inclination (Sec. 3).
- Motivated by the above insights, we present AHV-D&S, a training-free risk suppression method for DiTs (Sec. 4). It integrates a sensitive-guided adaptive suppression strategy to suppress the attention weight of identified risky tokens based on head-specific risk scores. This design enables robust and efficient mitigation of risky content without any additional model training, making it broadly applicable across DiT-based T2I models.
- Extensive evaluations show that AHV-D&S achieves the best trade-off between risk suppression and benign image generation, maintains strong suppression performance against adversarial prompts, and transfers to different T2I models (Sec. 5 and Sec. 6).

2 Background

2.1 Text-to-Image Models

Existing T2I models mainly use a diffusion denoising network to iteratively denoise Gaussian noise into structured visual samples. Early T2I diffusion models are mainly built upon the U-Net architecture [9, 33], where the denoising network processes latent image features through a multi-scale convolutional backbone. A key characteristic of U-Net-based models is the decoupled interaction between text and image representations: textual conditions are injected into image features through cross-attention, while

self-attention and convolutional blocks are mainly responsible for modeling spatial dependencies and refining visual details. This relatively modular design provides clear functional separation between semantic control and visual generation, which also makes U-Net amenable to targeted editing and safety intervention.

Recent advances have shifted from U-Net-based architectures to Diffusion Transformers (DiTs) [2, 5, 10], which replace convolution-dominated backbones with Diffusion Transformer blocks for denoising. Instead of maintaining a separate cross-attention module for text injection, many recent DiT-based T2I models adopt a more unified token interaction mechanism, where text and image tokens are processed jointly within the same attention layers. This design improves the flexibility and scalability of representation learning, and has shown strong performance in generation quality, semantic alignment, and model scaling. At the same time, however, it also entangles semantic injection and visual synthesis more tightly, reducing the effectiveness of U-Net-based methods.

This transition from U-Net to DiT is not merely a change in backbone design, but also a shift in how textual semantics are introduced and propagated during generation. As a result, many techniques developed for U-Net-based T2I models, especially those relying on the explicit separation between cross-attention and visual denoising, cannot be effectively transferred to DiT-based models.

2.2 Concept Erasure

The rapid development of T2I models has facilitated access to high-quality visual generation, yet also introduced potential risks of synthesizing risky content. Concept erasure aims to mitigate these risks by selectively eliminating specific risky concepts (e.g., NSFW or copyright) from the model, while preserving the generation capability for unrelated concepts.

Early works primarily target the U-Net architecture, exploiting its decoupled cross-attention or self-attention mechanism for concept erasure. This involves modifying the attention matrices to redirect risky semantics to safe ones via model editing [13, 15, 24] or fine-tuning strategies [6, 28]. In parallel, other approaches employ erasure objectives for diffusion models, such as correcting noise predictions [11, 23], steering denoising trajectory [22, 34], aligning model preferences [27, 31], or suppressing specific visual semantics from collected samples [25].

However, transferring these methods to Diffusion Transformers (DiTs) faces significant obstacles. First, the architectural shift from U-Net to DiT changes the internal interaction from cross-attention to joint attention, rendering previous concept-redirect approaches ineffective. Second, the substantial increase in parameter scale makes fine-tuning computationally expensive and hard to design erasure objectives. Which causes erasure attempts on DiT are limited. While Safree [41] presents an early training-free attempt by filtering concepts in text embedding, which can be adapted to DiT models, it faces the robustness challenge against the adversarial prompts due to the inherent drawback in the text encoder. More recently, EA [14] pioneered concept erasure for DiT models. Motivated by the failure of U-Net methods on flow architectures, it formulates a bi-level optimization problem using LoRA and self-contrastive learning to enable robust erasure, but it still performs poorly in erasure capabilities and excessive training time.

2.3 Threat Model

Our threat model involves two parties: an adversary and a model governor. The adversary aims to induce a T2I model to generate risky content, including sexual content, harmful content, and copyrighted-protected artistic styles. We assume the adversary can submit textual prompts to the model and observe the generated outputs. The prompts may be naive risky prompts, manually crafted adversarial prompts, or prompts generated by red-teaming methods. Following prior works [25, 32], the adversary can query and interact with the deployed model, but cannot modify the model parameters, tamper with the defense mechanism, or compromise the runtime environment.

The model governor is responsible for safely deploying the T2I model. The governor has access to the inference pipeline and can apply defense operations during generation. In our setting, the governor deploys AHV-D&S to estimate token-level risk directions and suppress attention weights associated with risky tokens at inference time. The governor has two objectives: preventing risky content generation under both naive and adversarial prompts, and preserving benign generation utility in terms of text-image alignment, visual fidelity, and perceptual consistency.

3 Analysis of the Attention Mechanism

In this section, we begin by reviewing the joint attention mechanism in DiTs. We then detail two key insights, **Attention Head Sensitivity** and the **Attention Head Vector**, which empirically motivate our training-free method design.

3.1 Joint Attention in Diffusion Transformer

In DiTs, the joint attention mechanism serves as the backbone for modeling the complex interactions between joint image-text features. Specifically, let $f_c \in \mathbb{R}^{l_c \times d}$ denote the feature representations of the input text prompt c , where l_c represents the length of the text token sequence (e.g., $l_c = 512$ in the FLUX model) and d is the feature dimension. Correspondingly, let $f_x \in \mathbb{R}^{l_x \times d}$ represent the latent image representations, where l_x denotes the length of the image token sequence (e.g., for a generated resolution of 512×512 in FLUX, $l_x = 1024$).

Distinct from traditional U-Net architectures, which decouple the modeling of image-text semantic alignment (typically via cross-attention) and image-image visual dependencies (via self-attention), DiTs concatenate the textual and visual features into a unified sequence $f_{\text{joint}} \in \mathbb{R}^{(l_c+l_x) \times d}$. This unified sequence is then processed through a multi-head self-attention calculation, defined as:

$$Q = f_{\text{joint}} W^Q, \quad K = f_{\text{joint}} W^K$$

$$A = \text{Softmax} \left(\frac{QK^\top}{\sqrt{d_h}} \right) \in \mathbb{R}^{(l_c+l_x) \times (l_c+l_x)} \quad (1)$$

where $W^Q, W^K \in \mathbb{R}^{d \times d_h}$ denote the projection matrices for the query, key, respectively, with d_h representing the dimension of each attention head. The matrix A represents the attention head map, which captures the pairwise correlations between all tokens in the joint sequence. Noted that while DiTs typically encompass both dual-stream and single-stream variants (e.g., in FLUX models), we focus our description specifically on the single-stream architecture in this section for clarity.

Based on the concatenated structure of f_{joint} , the attention head map A can be logically partitioned into four sub-matrices:

$$A = \begin{bmatrix} A^{cc} & A^{cx} \\ A^{xc} & A^{xx} \end{bmatrix} \quad (2)$$

where A^{cc} and A^{xx} capture the internal dependencies within text and image modalities, respectively, while A^{cx} models the text's attention to visual features. Crucially, the bottom-left block $A^{xc} \in \mathbb{R}^{l_x \times l_c}$ (**Image-to-Text**) functions equivalently to the *Cross-Attention* mechanism in U-Net, serving as the primary channel for injecting semantic concepts from the prompt into the generated image.




Figure 3: Visualization of attention head sensitivity in FLUX.1-dev toward the concept ‘nude’ within the prompt “a nude girl with beautiful hair and her breast open to see”. The sensitivity scores are averaged across all denoising steps. The x-axis represents the 57 diffusion transformer blocks (separated by the dashed line into 19 Double Stream blocks and 38 Single Stream blocks), while the y-axis denotes the 24 attention heads per block. Observe that high sensitivity is sparse and concentrated in specific heads while most scores are near zero due to the attention probability being distributed across a long sequence of 1536 tokens (1024 image tokens and 512 prompt tokens).




Figure 4: Cumulative sensitivity curve across all attention heads. We rank all attention heads by sensitivity in descending order, then cumulatively sum the sensitivities of different proportions of attention heads. The statistical experiment is conducted based on 1500 prompts across 100 classes from ImageNet-mini.

3.2 Attention Head Sensitivity

A standard DiT typically comprises L stacked blocks, where each block contains a multi-head self-attention module with H heads. Consequently, a single forward inference step generates a total of $L \cdot H$ attention head maps.

Definition 3.1 (Attention Head Sensitivity). Formally, let $k \in \{1, \dots, L \cdot H\}$ denote the index of a specific attention head. Given an input prompt c , let t^* denote the positional index of the token corresponding to the target risky concept (e.g., if the prompt is “a nude person”, t^* is the index of the token ‘nude’). Let $A_k \in \mathbb{R}^{(l_c+l_x) \times (l_c+l_x)}$ be the attention head map of the k -th head. Recall that the submatrix $A_k^{xc} \in \mathbb{R}^{l_x \times l_c}$ governs the visual-semantic alignment. The column vector $A_k^{xc}[:, t^*] \in \mathbb{R}^{l_x}$ thus represents the attention distribution of all image tokens specifically querying the token at index t^* . The sensitivity of attention head k with respect to the concept at index t^* is defined as:

$$S_k(t^*) = \frac{1}{|\Omega_k|} \sum_{i \in \Omega_k} A_k^{xc}[i, t^*], \quad (3)$$

where Ω_k denotes the set of spatial indices corresponding to the top ρ -percentile (e.g., $\rho = 5\%$) of values in the vector $A_k^{xc}[:, t^*]$. We employ this Top-K Mean strategy rather than a global average because semantic concepts are typically spatially sparse, characterized by activations concentrated in specific object regions as opposed to the entire background.

Hypothesis. We hypothesize that attention heads exhibit **differential sensitivity** toward input concepts. Specifically, rather than a uniform distribution, we posit that the generation of specific semantic concepts is decisively governed by a sparse subset of critical attention heads, while the majority of heads contribute negligibly to the target semantics.

Empirical Evidence. To support this hypothesis, we first visualize the sensitivity distribution of all attention heads in the FLUX model toward the concept ‘nude’, as shown in Fig. 3. We observe that heads exhibiting high sensitivity are sparsely distributed and predominantly located within the 6th to 27th transformer blocks, while the majority exhibit negligible responsiveness (approaching zero). We further design a statistical experiment to support this observation. Specifically, we target 100 distinct object classes from ImageNet-mini [8] and employ Gemini [16] to generate 15 diverse prompt templates for each class, resulting in a curated dataset of 1,500 text prompts. For each prompt, we extract the sensitivities of the attention heads to the corresponding target object concept across all heads and sort them in descending order. We then visualize the cumulative sensitivity curve, as shown in Fig. 4. The results show that the top 5% of attention heads account for 78.2% of the total sensitivity, which further confirms our observation.

To further confirm the functional causality of this disparity, we conduct an ablation study by suppressing the attention activation of the target concept token t^* (i.e., setting $A_k^{xc}[:, t^*] = 0$) across different subsets of heads. As illustrated in Fig. 5, results demonstrate that suppressing merely a small fraction of attention heads is sufficient to completely suppress the target concept. This empirically confirms our hypothesis of *Differential Attention Head Sensitivity*,




Figure 5: Qualitative study demonstrating Differential Head Sensitivity. We visualize the generation results when suppressing attention heads based on their sensitivity scores $S_k(t^*)$ toward the concept ‘nude’. **Top Row (Top- ρ Suppression):** Heads are suppressed in descending order of sensitivity. Observe that inhibiting merely the top 5% of sensitive heads is sufficient to completely remove the risky concept, showing the *sparsity* of attention head sensitivity toward specific concepts. **Bottom Row (Bottom- ρ Suppression):** Heads are suppressed in ascending order of sensitivity. Remarkably, even when suppressing 99% of the (least sensitive) heads, the generated image remains unsafe. This confirms that the ‘nude’ concept is decisively controlled by a tiny subset of sensitive heads, while the vast majority of heads contribute negligibly to the ‘nude’ semantics.

showing that the generation of specific concepts is controlled by a sparse subset of heads.

3.3 Attention Head Vector

This subsection extends our analysis to the holistic correlation between all attention heads and specific concepts.

Definition 3.2 (Attention Head Vector). For an arbitrary concept token t^* , we compute the sensitivity score $S_k(t^*)$ for attention head k across all transformer blocks, where $k \in \{1, \dots, L \cdot H\}$. By sequentially concatenating these sensitivity scores according to their block and head indices, we construct a 1-dimensional Attention Head Vector (AHV), denoted as $\mathbf{v}(t^*) \in \mathbb{R}^{(L \cdot H)}$:

$$\mathbf{v}(t^*) = [S_1(t^*), S_2(t^*), \dots, S_{L \cdot H}(t^*)]^T. \quad (4)$$

Physically, this vector represents the *trajectory* of the model’s attention to a specific concept, profiling how semantic information is progressively processed and attended to across the network depth.

Hypothesis. We hypothesize that Attention Head Vectors corresponding to semantically distinct concepts exhibit substantial divergence. Consequently, the AHV functions as a discriminative vector that effectively quantifies the model’s *generative inclination* toward specific visual content.

Empirical Evidence. To support this hypothesis, we conduct a feature separability experiment on our collected 1,500 prompts across 100 distinct object classes. Fig. 6(a) visualizes the t-SNE projection of these 1,500 AHVs. The visualization reveals distinct cluster structures: AHVs associated with different concepts exhibit clear separation, whereas those belonging to the same category




Figure 6: (a) t-SNE visualization of Attention Head Vectors (AHVs). The projection comprises 1,500 AHVs derived from 100 distinct object classes in ImageNet-mini. Each point represents the AHV of a single text prompt. The emergence of distinct, well-separated clusters demonstrates that AHVs possess strong semantic discriminability, effectively grouping identical concepts while distinguishing between different categories. (b) Cosine similarity distribution of 100 nude AHV queries with the nude AHV prototype (Nude vs Nude) and with 100 safe object AHV prototypes (Nude vs Safe).

form dense, compact clusters. This observation supports the semantic separability of AHV representations. We further evaluate the discriminative ability of AHVs using a K-Nearest Neighbors ($k = 1$) classifier. Adopting a 2:1 training-testing split with 5-fold cross-validation, the experiment yields an average classification accuracy of 98.73% ($\pm 0.77\%$). This further corroborates that the AHV serves as a reliable discriminative attribute for profiling the model’s generative inclinations.

To show the capability of AHV in detecting risky semantics, we construct a similarity distribution analysis. Specifically, we first extract 100 AHVs corresponding to the nude concept from 100 sexual prompts [42], and compute the prototype AHV for the nude concept accordingly. For safe concepts, we average the 1,500 AHVs described above on the object class, yielding 100 prototype AHVs for safe concepts. We then use the 100 nude-concept AHVs as queries and compute the distributions of their cosine similarities with the nude AHV prototype as well as with the safe AHV prototypes. As shown in the Fig. 6(b), the similarity among nude AHVs is significantly higher than that between nude and safe AHVs ($p < 1 \times 10^{-30}$). This result suggests that AHV can serve as an effective signal for detecting risky generation tendencies during model inference.

4 AHV-D&S: Attention Head Vector Detection and Suppression

Based on our empirical study on attention mechanisms, we introduce AHV-D&S, a training-free method that achieves safe generation by detecting the AHVs of input tokens for risk identification and suppressing the attention weights associated with risky tokens. Specifically, as shown in Fig. 7, AHV-D&S comprises two modules: 1) a momentum-based AHV measurement that dynamically estimates the AHVs of input tokens, and 2) a sensitivity-guided adaptive suppression that first detects and then suppresses risky tokens based on the head sensitivities.




Figure 7: Framework of AHV-D&S: Momentum-based AHV measurement estimates token-level AHVs in real time during inference, while sensitivity-guided adaptive suppression identifies head-specific risk scores and suppresses the attention weights of identified risky tokens.

4.1 Momentum-based AHV Measurement

T2I models typically require multiple denoising steps to generate an image, which implies that token AHVs vary dynamically throughout the inference process. To track this behavior, we propose a momentum-based measurement strategy to estimate token AHVs at arbitrary inference stage.

Specifically, given a text prompt c with a token sequence length of l_c , we first define a global AHV memory of all tokens, denoted as $\mathbf{V}^{glo} \in \mathbb{R}^{l_c \times (L \cdot H)}$. For the initialization of $\mathbf{V}^{glo} \in \mathbb{R}^{l_c \times (L \cdot H)}$, we perform a single denoising step to compute the initial global matrix:

$$\mathbf{V}^{glo}(c) = [\mathbf{v}(0), \dots, \mathbf{v}(t), \dots, \mathbf{v}(l_c - 1)]^T \in \mathbb{R}^{l_c \times (L \cdot H)}, \quad (5)$$

where $\mathbf{v}(t)$ represents the AHV for the t -th token. During the subsequent denoising process, we adopt a momentum-based strategy to update the global AHV memory. First, considering the l -th transformer block at an arbitrary denoising step, we calculate the current sensitivity scores for all attention heads with respect to the entire prompt c , denoted as the local sensitivity matrix $\hat{\mathbf{S}}_l(c)$:

$$\hat{\mathbf{S}}_l(c) = [S_{l \cdot H}(c), \dots, S_{(l+1) \cdot H - 1}(c)] \in \mathbb{R}^{l_c \times H}, \quad (6)$$

where $S_{l \cdot H}(c)$ is the sensitivity score (Eq. 3) of H attention heads in l -th transformer block toward all tokens within the prompt. Second, we dynamically update the corresponding slice of the global AHV memory using a momentum coefficient γ :

$$\mathbf{V}^{glo}(c)[:, I_l] \leftarrow \gamma \cdot \hat{\mathbf{S}}_l(c) + (1 - \gamma) \cdot \mathbf{V}^{glo}[:, I_l], \quad (7)$$

where $\mathbf{V}^{glo}(c)[:, I_l]$ denotes the sub-matrix corresponding to the head indices of the l -th block (i.e., indices from $l \cdot H$ to $(l+1) \cdot H - 1$).

4.2 Sensitivity-Guided Adaptive Suppression

This module is responsible for performing risk detection over the global AHV memory and suppressing the attention weights of risky

tokens. Specifically, it consists of three steps: token-level AHV risk estimation, adaptive modulation based on attention head sensitivity, and attention weight suppression.

4.2.1 Token-Level AHV Risk Estimation. Motivated by the observation in Fig. 6(b) that the similarity distributions between risk AHVs and safe AHVs exhibit a significant discrepancy, we employ a risk-safe contrastive score to estimate the risk score of the global AHV memory. Specifically, given a benign AHV library $\mathcal{V}^{safe}$ containing safe concepts (for example, 100 object AHV prototypes derived from ImageNet-mini) and a risk AHV library $\mathcal{V}^{risk}$ containing risky concepts, the risk score of the global AHV memory $\mathbf{V}^{glo}(c)$ during inference is defined as follows:

$$\Phi(c) = \max_i \left[\text{Cos}(\mathbf{V}^{glo}(c), \mathcal{V}_i^{risk}) - \max_j \text{Cos}(\mathbf{V}^{glo}(c), \mathcal{V}_j^{safe}) \right], \quad (8)$$

where $\Phi(c) \in \mathbb{R}^{L_c}$ denotes the risk score vector of all tokens, and the $\max(\cdot)$ operation identifies the nearest semantic neighbor within each library for every token AHV. Intuitively, each element $\Phi(c)[t]$ serves as a decision boundary for the t -th token. $\Phi(c)[t] > 0$ indicates that the AHV of the t -th token is semantically closer to the risk domain than to the benign domain, identifying it as a risky token. Conversely, $\Phi(c)[t] \leq 0$ suggests the token remains within a safe semantic margin.

4.2.2 Adaptive Modulation based Attention Head Sensitivity. Although the above formulation is effective for detecting risky tokens, it remains challenging in the presence of adversarial prompts. Specifically, risky semantics in adversarial prompts are often conveyed through the composition of multiple ambiguous words that jointly describe a risky scenario. When considered individually, these ambiguous words usually carry only weak risky semantics, which makes their risk scores inconspicuous or even negative, thereby hindering reliable detection.

To improve robustness against adversarial prompts, we draw inspiration from the observation in Fig. 5 that suppressing the attention weights of risky tokens in a small subset of sensitive attention heads is sufficient to effectively mitigate risky content. Based on this insight, we propose an *Adaptive Modulation based on Attention Head Sensitivity*, which relaxes the risk detection criterion within sensitive head regions, thereby improving the suppression of adversarial prompts. Specifically, for each risky concept i in our library $\mathcal{V}^{risk}$, we compute the *relative sensitivity score* $\hat{s}_{i,k}$ for head k :

$$\hat{s}_{i,k} = \mathcal{V}_{i,k}^{risk} - \frac{1}{|\mathcal{V}^{benign}|} \sum_{j=1}^{|\mathcal{V}^{benign}|} \mathcal{V}_{j,k}^{benign}, \quad (9)$$

where $\mathcal{V}_{i,k}^{risk}$ denotes the sensitivity score of head k for the i -th risky concept, $\mathcal{V}_{j,k}^{benign}$ denotes the sensitivity score of head k for the j -th benign concept, and $|\mathcal{V}^{benign}|$ is the number of benign concepts in the benign AHV library. A positive $\hat{s}_{i,k}$ indicates that head k is highly sensitive to risk concept i compared to safe concepts.

Following this, during inference, we incorporate the relative sensitivity score $\hat{s}_{i,k}$ into Eq. 8 and get the head-specific risk score as follows:

$$\Phi(c)_k = \max_i \left[\text{Cos}(\mathbf{V}^{glo}(c), \mathcal{V}_i^{risk}) - \beta_{i,k} * \max_j \text{Cos}(\mathbf{V}^{glo}(c), \mathcal{V}_j^{safe}) \right], \quad (10)$$

where

$$\beta_{i,k} = 1 - \text{ReLU}(\hat{s}_{i,k}). \quad (11)$$

In Eq. 10, $\Phi(c)_k \in \mathbb{R}^{L_c}$ represents the risk score of all tokens in k -th attention head. Intuitively, $\beta_{i,k}$ serves as a *modulation factor*. When head k is highly sensitive to the detected risk ($\hat{s}_{i,k} > 0$), $\beta_{i,k}$ drops below 1, effectively reducing the penalty from the safe similarity. Conversely, for insensitive heads ($\hat{s}_{i,k} \leq 0$), $\beta_{i,k}$ remains 1, maintaining strict selection criteria. This mechanism ensures that for sensitive heads, the detection range is adaptively broadened to capture weak risk signals (e.g., ambiguous words in adversarial prompts), while irrelevant heads remain unaffected, preserving generation quality.

4.2.3 Attention Weight Suppression. Armed with the head-specific risk scores, we execute the final suppression on the cross-attention maps to eliminate risky semantics. Specifically, for the k -th head, we update the attention weight of all tokens, i.e., $A_k^{xc} \in \mathbb{R}^{L_c}$, using the calculated risk score $\Phi(c)_k$:

$$A_k^{xc} \leftarrow A_k^{xc} - \alpha \cdot \text{ReLU}(\Phi(c)_k), \quad (12)$$

where α is a hyperparameter controlling the *suppression intensity*, and the $\text{ReLU}(\cdot)$ function acts as a unidirectional safety gate:

- **Positive Risk** ($\Phi_k[t] > 0$): When t -th token AHV is identified as a risk trigger, the term $\text{ReLU}(\Phi_k(c)[t])$ becomes active. The attention weights for this token are uniformly penalized by the factor $\alpha \cdot \Phi(c)_k[t]$, effectively reducing the model's focus on the risky concept across all image regions.
- **Negative Risk** ($\Phi_k[t] \leq 0$): When the score is non-positive, the suppression term vanishes. This ensures that the original attention weights for benign tokens remain mathematically strictly invariant, thereby preserving the benign generative quality.

5 Experiment Setup

In this section, we outline our implementation, datasets, baselines, and metrics used to evaluate AHV-D&S's performance.

Implementation. We use FLUX.1-dev [2] as our target model (57 transformer blocks, 24 heads each) with 28 denoising steps. The momentum coefficient γ is set to 0.2 and suppression intensity α to 50. For the AHV library (Eq. 10), we use 100 ImageNet-Mini objects as safe concepts. The risk library is task-specific: a sexual AHV prototype for sexual suppression, and four prototypes (blood, horror, weapon, drug) for harmful suppression.

Baselines. We evaluate five baselines: ESD [11], UCE [12], Safree [41], EA [14], and CASG [37]. Safree and UCE are encoder-based; ESD, EA, and CASG operate during denoising. Following official EA setup, we implement EA and ESD by fine-tuning the KEY projection in joint-attention layers. CASG redirects image latent representations toward safer distributional space at inference time. Except for EA, all baselines were originally designed for U-Net and are adapted by us for DiT.

Datasets. We use four risky datasets to evaluate the method's performance in suppressing risky content generation:

- **Sexual Prompt Dataset.** We use 100 explicitly sexual prompts [42] to assess defense performance against sexual content generation.
- **Copyrighted Style Dataset.** Following MACE [28], we use 100 prompts associated with copyrighted artistic styles, covering five artists: Pablo Picasso, Vincent van Gogh, Rembrandt, Andy Warhol, and Caravaggio.
- **Harmful Prompt Dataset.** We follow T2I-RiskyPrompt [44] and select 1,000 harmful prompts spanning the categories of blood, horror, weapons, and drugs.
- **Adversarial Prompt Dataset.** We adopt four sexual adversarial prompt sets: I2P [34] (931 manually crafted prompts), MMA [40] (1,000 prompts), UnlearnDiff [46] (142 prompts), and RAB [35] (80 prompts), covering both manual and automated attack methods.

Moreover, we use 1,000 prompts from the MSCOCO [26] to evaluate the preservation ability on benign prompts.

Evaluation Metrics. For risky prompts, we use **Risk Rate (RR)** = $Risk_{defense} / Risk_{base}$, where $Risk_{base}$ and $Risk_{defense}$ are the numbers of risky images before and after defense, respectively. We use NudeNet [1] (threshold 0.7) for sexual content and the T2I-RiskyPrompt [44] detector for harmful categories.

For benign prompts, we use three metrics:

- **FID** [20] measures the distributional difference between generated images before and after applying the defense method. Lower values indicate better distributional consistency.
- **LPIPS** [45] measures the perceptual difference between paired generated images before and after applying the defense method. Lower values indicate higher perceptual similarity.
- **CLIP Score** [19] measures the semantic alignment between generated images and the input prompt.

6 Evaluation

This section seeks to answer the following research questions (RQs):

- [RQ1] How effective is AHV-D&S at suppressing risky content?
- [RQ2] How well does AHV-D&S preserve benign generation?
- [RQ3] How robust is AHV-D&S against adversarial prompts?
- [RQ4] How well does AHV-D&S transfer across T2I models?
- [RQ5] How do different hyperparameter settings affect the performance of AHV-D&S?

6.1 RQ1: Risk Content Suppression

This section shows the performance of our method in suppressing risk content, involving sexual, copyrighted, and harmful content.

6.1.1 Task1: Sexual Content Suppression. We evaluate sexual content suppression using 100 explicitly sexual prompts (Tab. 1). For overall sexual content, AHV-D&S outperforms the best baseline, EA [14], reducing the risk ratio from 61.3% to 45.9%. Furthermore, under fine-grained NudeNet detection, AHV-D&S provides the most effective protection for the highly sensitive *female breast* category, achieving a risk ratio of only 18.0% compared to EA’s 21.6%. Beyond suppression, Tab. 1 also evaluates benign generation. AHV-D&S yields a CLIP Score of 30.84, preserving text-image alignment comparable to the Base model. It also achieves an FID of 22.16 (second only to UCE’s 21.90) and the best LPIPS score of 0.07 among baselines, ensuring high visual fidelity and perceptual consistency. Thus,




Figure 8: Visualization of sexual content suppression.




Figure 9: Token-wise risk scores across denoising steps, computed by averaging Eq. 10 across all heads.

AHV-D&S maintains competitive benign generation quality, offering a favorable safety-utility trade-off. In addition, Fig. 8 presents a qualitative comparison between AHV-D&S and the baseline methods in suppressing sexual content generation. Our method not only effectively enhances safety but also confines its modifications primarily to local nudity regions, thereby better preserving the overall image structure, layout, and non-sensitive content compared with existing methods. This advantage mainly stems from the fact that AHV-D&S only suppresses the attention weight of nudity-related tokens, which are typically highly correlated with localized image regions. Further evidence is provided in Fig. 9, where AHV-D&S successfully identifies risk tokens ('body' and 'skin') and accurately suppresses them to generate safe images. These results also demonstrate the superiority of AHV-D&S in achieving a favorable balance between safety protection and content preservation.

6.1.2 Task2: Copyrighted Style Suppression. We partition the copyrighted style dataset into five groups according to artist identity, with each group containing 20 prompts. The experiments are organized into five settings, where each setting suppresses the style of one target artist while preserving the styles of the remaining artists. We evaluate model performance using CLIP Score and LPIPS. Specifically, for the target style to be suppressed, a lower $CLIP_s$ and a higher $LPIPS_s$ indicate better suppression performance. For the styles to be preserved, a higher $CLIP_p$ and a lower $LPIPS_p$ indicate better preservation performance. To balance these two aspects, the $\Delta CLIP = CLIP_p - CLIP_s$ and $\Delta LPIPS = LPIPS_s - LPIPS_p$ indicates the trade-off between the suppression and preservation abilities. The performance comparison is reported in Tab. 2.

Table 1: Performance comparison between AHV-D&S and baselines in sexual content suppression and benign content preservation. For each method, we report the total risk ratio (RR) and the detailed category-specific risk ratios. Br.(F), Gen.(F), Br.(M), and Gen.(M) denote female breasts, female genitalia, male breasts, and male genitalia, respectively. For benign prompts, we evaluate the preservation ability of different methods on COCO-1K. Bold indicates the best performance.

Method		Sexual Content Suppression									Benign Content Generation		
		Br.(F)↓	Gen.(F)↓	Br.(M)↓	Gen.(M)↓	Buttocks↓	Feet↓	Armpits↓	Belly↓	Total↓	FID ↓	LPIPS ↓	CLIP ↑
Base	-	40.5%	0.0%	0.0%	0.0%	15.3%	0.9%	18.0%	25.2%	100.0%	-	-	30.96
ESD	ICCV'23	39.6%	0.0%	0.9%	0.0%	12.6%	0.0%	15.3%	26.1%	94.6%	24.48	0.09	30.75
UCE	WACV'24	24.3%	0.0%	0.0%	0.0%	9.0%	0.9%	16.2%	16.2%	66.7%	21.90	0.28	31.07
Safree	ICLR'2025	32.4%	0.0%	0.0%	0.0%	17.1%	0.0%	18.0%	22.5%	90.1%	38.71	0.31	30.94
EA	ICML'2025	21.6%	0.0%	0.0%	0.0%	5.4%	0.9%	8.1%	25.2%	61.3%	23.30	0.28	30.97
ANT	ACM MM'2025	26.1%	1.8%	0.0%	0.0%	9.0%	0.9%	18.9%	26.1%	82.9%	23.51	0.07	31.09
CASG	CVPR'2026	30.6%	0.0%	0.0%	0.0%	9.9%	0.0%	15.3%	23.4%	79.3%	26.60	0.11	31.00
AHV-D&S	-	18.0%	0.0%	0.0%	0.0%	3.6%	0.0%	7.2%	17.1%	45.9%	22.16	0.07	30.84

Table 2: Performance comparison between AHV-D&S and baselines in copyrighted-style suppression and benign style generation. Bold indicates the best performance.

Method	Protected Style Suppression		Benign Style Generation		Overall Performance	
	CLIP _s ↓	LPIPS _s ↑	CLIP _p ↑	LPIPS _p ↓	ΔCLIP ↑	ΔLPIPS ↑
Base	26.50	-	26.50	-	-	-
UCE	24.83	0.14	26.52	0.03	1.69	0.10
ESD	25.35	0.20	25.53	0.15	0.18	0.05
Safree	23.40	0.13	25.40	0.13	2.00	0.00
EA	23.01	0.21	24.97	0.15	1.96	0.06
ANT	26.87	0.26	26.52	0.25	-0.35	0.01
CASG	25.43	0.08	26.34	0.02	1.03	0.06
AHV-D&S	23.08	0.20	26.01	0.07	2.93	0.13

Regarding style-level semantic degeneration, EA obtains the lowest CLIP_s score. However, AHV-D&S achieves a comparable CLIP_s of 23.08, effectively mitigating copyrighted-protected styles better than all other baselines. Crucially, AHV-D&S preserves benign styles more effectively than EA, achieving a higher CLIP_p (26.01 vs. 24.97) and a lower LPIPS_p (0.07 vs. 0.15). This indicates that AHV-D&S maintains suppression of protected styles without excessively degrading non-protected ones.

For visual perceptual difference, ANT produces the largest LPIPS distance from protected-style images. However, Fig. 10 shows this stems from substantial changes in the image subject and layout, rather than merely removing stylistic traits. In contrast, AHV-D&S achieves targeted perceptual suppression, maintaining a high LPIPS_s of 0.20 for protected styles while keeping LPIPS_p low at 0.07 for benign styles, proving our effectiveness. Overall, AHV-D&S achieves the highest ΔCLIP of 2.93 and ΔLPIPS of 0.13, indicating a better balance between copyright protection and generation utility.

6.1.3 Task3: Harmful Content Suppression. We use 1,000 harmful prompts from T2I-RiskyPrompt to evaluate harmful content suppression. This task requires simultaneously defending against multiple risk categories, including blood, horror, weapons, and drug content, making it challenging. The performance comparison is reported in Tab. 3.




Figure 10: Visualization of copyrighted style suppression.

As shown in Tab. 3, existing methods exhibit limited effectiveness in multi-category suppression: the best baselines per category (CASG for blood/horror at 75.2%/82.4%, UCE for weapons at 83.5%, EA for drugs at 78.3%) all remain above 75%.

In contrast, AHV-D&S adaptively identifies risk direction and degree by comparing token-level AHVs with the offline risk library. It reduces risk ratios for blood, horror, weapon, and drug content to 33.4%, 52.3%, 35.2%, and 22.7%, respectively—improvements of 41.8%, 30.1%, 48.3%, and 55.6% over the strongest baselines. Fig. 11 further illustrates this effectiveness. Meanwhile, AHV-D&S maintains competitive benign quality (CLIP: 30.46, FID: 28.56, LPIPS: 0.12), indicating that multi-category suppression does not severely degrade benign generation.


6.2 RQ2: Benign Content Generation

This section further analyzes benign preservation by jointly considering quantitative metrics and qualitative visualization. Specifically, we focus on the sexual suppression task and visualize benign content generation to help interpret the CLIP, FID, and LPIPS metrics reported in Tab. 1.

First, LPIPS reflects the perceptual consistency between a pair of images (suppressed and base images), involving visual factors such as global layout, subject appearance, camera viewpoint, local texture, and overall style. This property is particularly important

Table 3: Performance comparison between AHV-D&S and baselines in harmful content suppression and benign content generation. Bold indicates the best performance.

Method	Harmful Content Suppression				Benign Content Generation		
	Blood	Horror	Weapon	Drug	FID	LPIPS	CLIP
Base	100.0%	100.0%	100.0%	100.0%	–	–	30.96
UCE	76.9%	84.4%	83.5%	90.7%	25.47	0.10	30.92
Safree	94.5%	94.6%	99.6%	97.9%	32.99	0.18	29.82
ESD	92.2%	95.4%	102.5%	85.6%	30.42	0.14	30.49
EA	87.3%	87.0%	85.6%	78.3%	30.42	0.14	30.94
ANT	102.7%	107.0%	103.8%	79.3%	30.11	0.07	31.19
CASG	75.2%	82.4%	94.2%	79.4%	26.26	0.10	30.95
AHV-D&S	33.4%	52.3%	35.2%	22.7%	28.56	0.12	30.46

**Figure 11: Visualization of harmful content suppression.****Figure 12: Visualization of benign content generation.**

for practical deployment, since a safety defense should not unnecessarily alter benign user requests. The quantitative results in Tab. 1 show that AHV-D&S achieves the best LPIPS score, indicating that it introduces the smallest perceptual deviation from the Base model among all baselines. The qualitative results in Fig. 12 further support this observation. For example, AHV-D&S preserves the human

Table 4: Robustness evaluation against sexual adversarial prompts. We report the Risk Ratio (RR) across five benchmarks, including I2P, P4D, RAB, MMA, and UnlearnDiff. Bold indicates the best performance.

Method	I2P ↓	RAB ↓	MMA ↓	UnlearnDiff ↓
Base	100.0%	100.0%	100.0%	100.0%
ESD	51.8%	110.2%	36.1%	77.2%
UCE	54.0%	107.7%	39.2%	77.2%
Safree	85.0%	110.2%	135.5%	90.9%
EA	71.5%	102.5%	36.1%	75.0%
ANT	82.1%	117.9%	86.7%	79.5%
CASG	50.7%	97.3%	65.7%	61.8%
AHV-D&S	40.9%	69.2%	28.3%	59.1%

appearance and global layout in Fig. 12(a), maintains the structure of the animal interaction in Fig. 12(c), and keeps the spatial relationship between the girl, bowl, and chair in Fig. 12(e). In contrast, several baselines introduce greater structural and perceptual changes. For example, UCE and EA alter the mirror-selfie composition in Fig. 12(a), ESD and CASG change the realistic animal-interaction scene into a stylized or cartoon-like image in Fig. 12(c), and UCE and Safree weaken the spatial relationship in Fig. 12(e). These results suggest that AHV-D&S better preserves the original benign image content and global structure.

Second, FID measures the overall distributional discrepancy between suppressed images and the base images. AHV-D&S achieves a near-best FID score in Tab. 1, showing that the distribution shift introduced by our method is well controlled. This is consistent with the qualitative results in Fig. 12: AHV-D&S largely preserves the visual style, layout, and low-level appearance of benign generations across diverse cases, including the multi-object composition in Fig. 12(d) and the complex event scene in Fig. 12(f). By comparison, some baselines may still maintain plausible semantics but introduce noticeable visual distribution shifts, such as changing the composition and viewpoint of the mirror-selfie case in Fig. 12(a), and altering the visual style of the animal-interaction case in Fig. 12(c).

Finally, CLIP mainly captures coarse-grained text-image alignment. Since AHV-D&S suppresses the attention activation of specific risky tokens, it may also slightly reduce the contribution of some tokens that are weakly correlated with risky concepts. As a result, AHV-D&S obtains a slightly lower CLIP Score than the highest-scoring baselines. This effect is more likely to appear in prompts related to potentially risky semantics, such as the human-centric prompts in Fig. 12(a) and Fig. 12(b). Nevertheless, the generated images remain semantically close to the input prompts and preserve high visual quality. Together with our near-best FID and best LPIPS scores, these results demonstrate that AHV-D&S achieves stronger benign utility preservation and a more favorable safety-utility trade-off than existing methods.

6.3 RQ3: Adversarial Robustness

We evaluate robustness against red-team attacks using four sexual adversarial prompt benchmarks, including I2P, RAB, MMA, and


Table 5: Transfer performance of AHV-D&S on Qwen-Image for sexual content suppression and benign content preservation.

Method	Sexual Content Suppression									Benign Content Generation		
	Br.(F)↓	Gen.(F)↓	Br.(M)↓	Gen.(M)↓	Buttocks↓	Feet↓	Armpits↓	Belly↓	Total↓	FID ↓	LPIPS ↓	CLIP ↑
Base	37.0%	1.1%	3.3%	0.0%	14.1%	4.3%	16.3%	23.9%	100.0%	-	-	31.41
AHV-D&S	9.8%	1.1%	0.0%	0.0%	4.3%	2.2%	6.5%	14.1%	38.0%	22.33	0.09	31.49

UnlearnDiff. These benchmarks cover both manually crafted adversarial prompts and automatically generated adversarial prompts, providing a comprehensive evaluation of the robustness.

As shown in Tab. 4, existing defense methods exhibit limited and inconsistent robustness under adversarial prompts. For example, several baselines substantially reduce the RR on I2P and MMA, but fail to generalize to RAB, where most methods produce even higher RRs than the Base model. This suggests that these methods are sensitive to the distribution of adversarial prompts and struggle when adversarial prompts activate risky concepts through different linguistic patterns. In contrast, AHV-D&S consistently achieves the lowest RR across all four adversarial prompt benchmarks. Specifically, compared with the strongest baseline on each benchmark, AHV-D&S further reduces the RR by 9.8%, 28.1%, 7.8%, and 2.7% on I2P, RAB, MMA, and UnlearnDiff, respectively. The improvement is particularly significant on RAB, whereas AHV-D&S reduces the RR to 69.2%. These results demonstrate that AHV-D&S provides more robust protection against diverse red-team attacks.

6.4 RQ4: Transferability to Qwen-Image

**Figure 13: Visualization of sexual content suppression in Qwen-Image.**

To further evaluate the transferability of AHV-D&S, we apply our method to Qwen-Image and assess its performance on both sexual content suppression and benign content generation. As reported in Tab. 5, AHV-D&S substantially reduces the overall sexual risk ratio from 100.0% to 38.0%, demonstrating that our method can effectively transfer to a different DiT-based T2I model. The reduction is consistent across most fine-grained nudity categories. For example, AHV-D&S reduces the risk ratios of Female Breast (Br.(F)), Buttocks, Armpits, and Belly from 37.0%, 14.1%, 16.3%, and 23.9% to 9.8%, 4.3%, 6.5%, and 14.1%, respectively. The qualitative results in Fig. 13 further show this effectiveness, where AHV-D&S suppresses sexual regions while preserving the benign content.

Meanwhile, AHV-D&S maintains strong benign generation quality on Qwen-Image. Specifically, it achieves a CLIP Score of 31.49, which is even slightly higher than the Base model, indicating that text-image alignment on benign prompts is well preserved. It also

obtains an FID of 22.33 and an LPIPS of 0.09, suggesting that the generated images remain visually faithful and perceptually consistent with benign generations. These results show that AHV-D&S is not limited to a single backbone, but can generalize to another advanced DiT-based T2I mode.

6.5 RQ5: Hyper-parameter Analysis

This section analyzes how suppression strength α and adaptive modulation factor $\beta_{i,k}$ (Eq. 10) affect the safety-utility trade-off. α controls the global suppression of risky tokens, while $\beta_{i,k}$ adaptively adjusts this suppression based on attention head sensitivity. Intuitively, α dictates the overall suppression intensity, whereas $\beta_{i,k}$ selectively relaxes or strengthens it across different heads.

Fig. 14 reports the performance under different α values with two settings of $\beta_{i,k}$: a non-adaptive setting with $\beta_{i,k} = 1$, and our adaptive modulation setting with $\beta_{i,k} = 1 - \text{ReLU}(\hat{s}_{i,k})$. As shown in Fig. 14(a), increasing α consistently reduces the risk ratio, demonstrating that stronger suppression leads to better safety protection. However, under the non-adaptive setting, the improvement is relatively limited: the RR only decreases from 77.5% at $\alpha = 30$ to 56.8% at $\alpha = 300$. In contrast, when the adaptive modulation setting is enabled, the RR decreases more significantly from 63.1% to 29.7%. This indicates that our adaptive modulation strategy effectively identifies risk-sensitive attention heads and applies more targeted suppression, substantially improving the suppression effectiveness.

The utility metrics in Fig. 14(b)-(d) further reveal the trade-off controlled by α . As α increases, CLIP gradually decreases, while FID and LPIPS increase, indicating that stronger suppression may introduce larger degradation in benign generation. This trend is expected, since overly strong intervention can suppress not only risky semantics but also weaken benign visual-textual responses that are weakly correlated with risky concepts. Nevertheless, the adaptive modulation strategy still achieves a more favorable safety-utility balance. For example, at $\alpha = 50$, AHV-D&S with adaptive modulation strategy reduces the RR to 45.9%, which is substantially lower than EA's 61.3%, while maintaining competitive benign generation quality with a CLIP Score of 30.84, FID of 22.16, and LPIPS of 0.07. In particular, the LPIPS score remains far lower than that of EA, suggesting that our method introduces much smaller perceptual changes to benign generations.

Overall, these results show that α acts as a controllable knob for adjusting the strength of safety intervention, while $\beta_{i,k}$ improves the efficiency and selectivity of the intervention. We choose $\alpha = 50$ with adaptive modulation strategy as the default setting, since it achieves strong sexual content suppression while preserving competitive benign generation quality.




Figure 14: Hyper-Parameter Analysis on the suppression strength α and the adaptive modulation factor $\beta_{i,k}$. The dashed horizontal line denotes the performance of the best baseline, EA, for reference.

Table 6: Inference overhead comparison of different methods on the same NVIDIA A800 GPU. We report the average generation time.

Method	Base	Parameter-Edit-Based				Inference-Time		
		UCE	EA	ESD	ANT	Safree	CASG	AHV-D&S
Time (s) ↓	5.8	5.8	5.9	5.9	9.1	7.9	47.8	12.9

7 Discussion

Evaluation Metrics and Safety Definitions. Our evaluation relies on open-source classifiers and proxy metrics, which may introduce measurement bias. For example, we use NudeNet to quantify sexual content generation for fair comparison with baselines. However, sexual explicitness is inherently context-dependent and subjective, and some NudeNet categories, such as feet or buttocks, may not always be considered sexually explicit across different social, cultural, or application contexts. Therefore, our reported risk ratios should be interpreted as detector-based proxies rather than absolute definitions of unsafe content. To improve transparency, we report not only the overall risk ratio but also fine-grained category-specific results, allowing readers to inspect which types of content are suppressed. Moreover, we also complement quantitative metrics with qualitative visualizations.

Safety-Utility Trade-off and Deployment Choices. Although AHV-D&S achieves strong suppression performance across sexual, harmful, and copyrighted-protected style generation, it may still introduce side effects on benign generation, as reflected by slight deviations in CLIP, FID, and LPIPS compared with the base model. Such degradation is an inherent trade-off in safety intervention: stronger suppression can reduce risky content generation but may also affect benign visual-textual responses that are weakly correlated with risky semantics. We mitigate this issue in two ways. First, our experiments (Tab. 1, Tab. 2, and Tab. 3) show that AHV-D&S achieves a more favorable safety-utility balance than existing baselines, substantially reducing risk while preserving competitive benign generation quality. Second, our hyper-parameter analysis shows that the suppression strength α provides a controllable knob for deployment. In practice, model providers can adjust α according to their risk tolerance and application scenario, choosing a stricter

setting for high-risk platforms or a more conservative setting when benign utility is prioritized.

Inference Overhead. We measure inference overhead on the same NVIDIA A800 GPU. As shown in Tab. 6, parameter-edit-based methods such as UCE, EA, and ESD incur almost no additional inference cost because their modifications are absorbed into model parameters before inference. In contrast, AHV-D&S provides dynamic, inference-time protection against risky content, taking 12.9s per image and slightly higher than Safree but much faster than CASG (47.8s, 8.24 $\times$). The overhead mainly comes from our current custom attention implementation based on `torch.matmul`, which disables FlashAttention-style fused kernels to allow access and modification of attention weights. We expect that a fused implementation could further reduce this cost.

8 Conclusion

In this paper, we presented AHV-D&S, a training-free defense for safe DiT-based T2I generation. Our key insight is that attention head vector offers a measurable way to characterize token-level generative semantics, making it possible to distinguish risky token responses from benign ones during inference. Based on this insight, AHV-D&S dynamically measures token-wise AHVs and suppresses attention weights associated with risky tokens through sensitivity-guided adaptive modulation. This design avoids costly model retraining and supports flexible suppression of different risk concepts in the inference stage.

Extensive experiments demonstrate that AHV-D&S achieves strong safety protection while preserving benign generation utility. Across sexual content, copyrighted-protected styles, and harmful content suppression, AHV-D&S consistently outperforms state-of-the-art baselines in safety-utility trade-off. It also shows robustness against diverse adversarial prompt benchmarks and transfers effectively to Qwen-Image, indicating that AHV-D&S is not limited to a single T2I backbone. We further show that the suppression strength provides a practical knob for deployment, allowing model providers to adjust the balance between safety protection and benign utility preservation. We hope our findings on AHV and the proposed AHV-D&S method can provide useful insights for building safer and more controllable generative models.

References

- [1] Praneeth Bedapudi. 2019. NudeNet: Neural Nets for Nudity Detection and Censoring. <https://github.com/bedapudi6788/NudeNet>. Python package, version 1.1.0.
- [2] Black Forest Labs. 2025. FLUX.1 [dev] — Model Card. <https://huggingface.co/black-forest-labs/FLUX.1-dev>.
- [3] Huanqia Cai, Sihan Cao, Ruoyi Du, Peng Gao, Steven Hoi, Zhaoxian Hou, Shijie Huang, Dengyang Jiang, Xin Jin, Liangchen Li, et al. 2025. Z-image: An efficient image generation foundation model with single-stream diffusion transformer. *arXiv preprint arXiv:2511.22699* (2025).
- [4] Qi Cai, Yehao Li, Yingwei Pan, Ting Yao, and Tao Mei. 2025. HiDream-I1: An Open-Source High-Efficient Image Generative Foundation Model. In *Proceedings of the 33rd ACM International Conference on Multimedia*. 13636–13639.
- [5] Junsong Chen, Jincheng Yu, Chongjian Ge, Lewei Yao, Enze Xie, Yue Wu, Zhongdao Wang, James Kwok, Ping Luo, Huchuan Lu, et al. 2023. Pixart-alpha: Fast training of diffusion transformer for photorealistic text-to-image synthesis. *arXiv preprint arXiv:2310.00426* (2023).
- [6] Ruidong Chen, Honglin Guo, Lanjun Wang, Chenyu Zhang, Weizhi Nie, and An-An Liu. 2025. Trce: Towards reliable malicious concept erasure in text-to-image diffusion models. *arXiv preprint arXiv:2503.07389* (2025).
- [7] Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, et al. 2025. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683* (2025).
- [8] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. 2009. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*. Ieee, 248–255.
- [9] Prafulla Dhariwal and Alexander Nichol. 2021. Diffusion models beat gans on image synthesis. *Advances in neural information processing systems* 34 (2021), 8780–8794.
- [10] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. 2024. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first International Conference on Machine Learning*.
- [11] Rohit Gandikota, Joanna Materzynska, Jaden Fiotto-Kaufman, and David Bau. 2023. Erasing concepts from diffusion models. In *Proceedings of the IEEE/CVF international conference on computer vision*. 2426–2436.
- [12] Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzynska, and David Bau. 2024. Unified concept editing in diffusion models. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*. 5111–5120.
- [13] Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzynska, and David Bau. 2024. Unified concept editing in diffusion models. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*. 5111–5120.
- [14] Daiheng Gao, Shilin Lu, Wenbo Zhou, Jiaming Chu, Jie Zhang, Mengxi Jia, Bang Zhang, Zhaoxin Fan, and Weiming Zhang. 2025. Eraseanything: Enabling concept erasure in rectified flow transformers. In *Forty-second International Conference on Machine Learning*.
- [15] Chao Gong, Kai Chen, Zhipeng Wei, Jingjing Chen, and Yu-Gang Jiang. 2024. Reliable and efficient concept erasure of text-to-image diffusion models. In *European Conference on Computer Vision*. Springer, 73–88.
- [16] Google. 2026. Gemini. <https://gemini.google.com/app>. Accessed: 2026-04-29.
- [17] Alec Helbling, Tuna Han Salih Meral, Ben Hoover, Pinar Yanardag, and Duen Horng Chau. 2025. Conceptattention: Diffusion transformers learn highly interpretable features. *arXiv preprint arXiv:2502.04320* (2025).
- [18] Amir Hertz, Ron Mokady, Jay Tenenbaum, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. 2022. Prompt-to-prompt image editing with cross attention control. *arXiv preprint arXiv:2208.01626* (2022).
- [19] Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. 2021. Clipscore: A reference-free evaluation metric for image captioning. In *Proceedings of the 2021 conference on empirical methods in natural language processing*. 7514–7528.
- [20] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. 2017. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems* 30 (2017).
- [21] Internet Watch Foundation. 2026. Harm without limits: AI child sexual abuse material through the eyes of our Analysts. <https://www.iwf.org.uk/about-us/why-we-exist/our-research/how-ai-is-being-abused-to-create-child-sexual-abuse-imagery/>. Accessed: 2026-04-18.
- [22] Anubhav Jain, Yuya Kobayashi, Takashi Shibuya, Yuhta Takida, Nasir Memon, Julian Togelius, and Yuki Mitsufuji. 2024. Tracse: Trajectory steering for concept erasure. *arXiv preprint arXiv:2412.07658* (2024).
- [23] Nupur Kumari, Bingliang Zhang, Sheng-Yu Wang, Eli Shechtman, Richard Zhang, and Jun-Yan Zhu. 2023. Ablating concepts in text-to-image diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*. 22691–22702.
- [24] Ouxiang Li, Yuan Wang, Xinting Hu, Houcheng Jiang, Tao Liang, Yanbin Hao, Guojun Ma, and Fuli Feng. 2025. Speed: Scalable, precise, and efficient concept erasure for diffusion models. *arXiv preprint arXiv:2503.07392* (2025).
- [25] Xinfeng Li, Yuchen Yang, Jiangyi Deng, Chen Yan, Yanjiao Chen, Xiaoyu Ji, and Wenyuan Xu. 2024. SafeGen: Mitigating Unsafe Content Generation in Text-to-Image Models. *arXiv preprint arXiv:2404.06666* (2024).
- [26] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. 2014. Microsoft coco: Common objects in context. In *European conference on computer vision*. Springer, 740–755.
- [27] Runtao Liu, Chen I Chieh, Jindong Gu, Jipeng Zhang, Renjie Pi, Qifeng Chen, Philip Torr, Ashkan Khakzar, and Fabio Pizzati. 2024. Safetydpo: Scalable safety alignment for text-to-image generation. *arXiv preprint arXiv:2412.10493* (2024).
- [28] Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. 2024. Mace: Mass concept erasure in diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 6430–6440.
- [29] Zhengyao Lv, Tianlin Pan, Chenyang Si, Zhaoxi Chen, Wangmeng Zuo, Ziwei Liu, and Kwan-Yee K Wong. 2025. Rethinking cross-modal interaction in multimodal diffusion transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*. 5934–5943.
- [30] Jungwon Park, Jungmin Ko, Dongnam Byun, Jangwon Suh, and Wonjong Rhee. 2024. Cross-Attention Head Position Patterns Can Align with Human Visual Concepts in Text-to-Image Generative Models. In *The Thirteenth International Conference on Learning Representations*.
- [31] Yong-Hyun Park, Sangdoo Yun, Jin-Hwa Kim, Junho Kim, Geonhui Jang, Yonghyun Jeong, Junghyo Jo, and Gayoung Lee. 2024. Direct unlearning optimization for robust and safe text-to-image models. *arXiv preprint arXiv:2407.21035* (2024).
- [32] Peigui Qi, Kunsheng Tang, Wenbo Zhou, Weiming Zhang, Nenghai Yu, Tianwei Zhang, Qing Guo, and Jie Zhang. 2025. SafeGuider: Robust and practical content safety control for text-to-image models. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*. 2818–2832.
- [33] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*. 10684–10695.
- [34] Patrick Schramowski, Manuel Brack, Björn Deiseroth, and Kristian Kersting. 2023. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 22522–22531.
- [35] Yu-Lin Tsai, Chia-Yi Hsu, Chulin Xie, Chih-Hsun Lin, Jia-You Chen, Bo Li, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. 2023. Ring-A-Bell! How Reliable are Concept Removal Methods for Diffusion Models? *arXiv preprint arXiv:2310.10012* (2023).
- [36] Chenfei Wu, Jiahao Li, Jingren Zhou, Junyang Lin, Kaiyuan Gao, Kun Yan, Shengming Yin, Shuai Bai, Xiao Xu, Yilei Chen, et al. 2025. Qwen-image technical report. *arXiv preprint arXiv:2508.02324* (2025).
- [37] Yongli Xiang, Ziming Hong, Zhaoqing Wang, Xiangyu Zhao, Bo Han, and Tongliang Liu. 2026. When Safety Collides: Resolving Multi-Category Harmful Conflicts in Text-to-Image Diffusion via Adaptive Safety Guidance. *arXiv preprint arXiv:2602.20880* (2026).
- [38] Jinheng Xie, Zhenheng Yang, and Mike Zheng Shou. 2025. Show-o2: Improved native unified multimodal models. *arXiv preprint arXiv:2506.15564* (2025).
- [39] Fuyi Yang, Chenyu Zhang, and Lanjun Wang. 2025. Culture-based Adversarial Attack on Text-to-Image Models. In *2025 IEEE International Conference on Multimedia and Expo (ICME)*. IEEE, 1–6.
- [40] Yijun Yang, Ruiyuan Gao, Xiaosen Wang, Tsung-Yi Ho, Nan Xu, and Qiang Xu. 2024. MMA-Diffusion: MultiModal Attack on Diffusion Models. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- [41] Jaehong Yoon, Shoubin Yu, Vaidehi Patil, Huaxin Yao, and Mohit Bansal. 2024. Safree: Training-free and adaptive guard for safe text-to-image and video generation. *arXiv preprint arXiv:2410.12761* (2024).
- [42] Chenyu Zhang, Yiwen Ma, Lanjun Wang, Wenhui Li, Yi Tu, and An-An Liu. 2025. Metaphor-based jailbreaking attacks on text-to-image models. *arXiv preprint arXiv:2512.10766* (2025).
- [43] Chenyu Zhang, Lanjun Wang, Yiwen Ma, Wenhui Li, Guoqing Jin, and Anan Liu. 2026. Reason2attack: Jailbreaking text-to-image models via llm reasoning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 40. 36030–36038.
- [44] Chenyu Zhang, Tairen Zhang, Lanjun Wang, Ruidong Chen, Wenhui Li, and Anan Liu. 2026. T2I-RiskyPrompt: A Benchmark for Safety Evaluation, Attack, and Defense on Text-to-Image Model. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 40. 36039–36047.
- [45] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. 2018. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. 586–595.
- [46] Yimeng Zhang, Jinghan Jia, Xin Chen, Aochuan Chen, Yihua Zhang, Jiancheng Liu, Ke Ding, and Sijia Liu. 2024. To generate or not? safety-driven unlearned diffusion models are still easy to generate unsafe images... for now. *European Conference on Computer Vision (ECCV)* (2024).