

How Reliable Are AI Attackers Against a Fixed Vulnerable Target? A 400-Run Empirical Study of LLM Penetration Testing Consistency

Authors: Galip T. Erdem *Independent Researcher* — galiperdem@gmail.com

Abstract

Large language models (LLMs) can autonomously conduct multi-stage cyber attacks, but the consistency of their offensive behavior under repeated trials remains unstudied. This work presents the first large-scale empirical measurement of LLM attack consistency: 400 autonomous penetration testing runs (4 models, 100 each) against an identical honeypot hosting OWASP Juice Shop and two additional vulnerable services, holding prompt, orchestrator, and target constant. No model emitted a content refusal that survived the orchestrator’s one-shot authorization re-prompt at iterations 0–1. Claude Sonnet 4’s API calls did encounter upstream service unavailability — 91 of 1,135 calls returned HTTP 529 `overloaded_error` during a documented Anthropic capacity event, truncating 39 of 100 Claude runs. An earlier draft catalogued these as safety refusals; on full-log audit they are upstream API failures, not model-level refusals. Despite this, Claude achieved full exploitation in 61 of 100 runs; Gemini 2.5 Flash-Lite in 85; GPT-4o-mini in 56 while deploying 98 unique attack strategies; qwen2.5-coder:14b in 25. Failure modes are model-distinctive: Claude through API truncation (39 runs), qwen through premature completion (52), GPT-4o-mini through iteration-budget exhaustion (23). Cross-service credential reuse appeared only in configurations retaining the most conversation history (qwen 57%, GPT-4o-mini 49%, cloud models 0% on 5-exchange windows). Cross-model exploitation rate differences are statistically significant ($p < 0.001$) with large effect sizes; qwen vs. Gemini SQL injection rates differ at Cohen’s $h = 1.12$. First-exploit timing fell within a 15–30 second wall-clock range. To our knowledge, this is the first study to measure autonomous LLM attack behavior at $N=100$ per model across a multi-service target.

1. Introduction

The rapid advancement of large language models has introduced a new class of autonomous cyber threat. Recent work has demonstrated that LLMs can autonomously exploit web vulnerabilities [2], crack SSH credentials via brute-force [1], and chain multi-stage attacks without human guidance [4]. However, a fundamental question remains unanswered: **how consistent are these attacks across repeated trials?**

This question matters for two distinct communities. For **AI safety researchers**, consistency at scale informs whether refusal-based safety mechanisms hold under sustained programmatic use and across professional framings that mirror legitimate attacker tradecraft. For **cyber defenders**, consistency determines whether autonomous LLM attacks produce predictable signatures amenable to detection, or whether each attack instance follows a novel path that evades pattern-matching defenses.

Prior work on LLM-powered penetration testing has focused on capability — can models exploit vulnerabilities? — rather than reliability. PentestGPT [1] demonstrated a 228.6% task-completion improvement using GPT-3.5 with human oversight. Fang et al. [2] showed GPT-4 can autonomously exploit web vulnerabilities with an 87% success rate on one-day CVEs. HackSynth [5] introduced benchmarks across 200 CTF challenges. Yet none of these studies conducted repeated trials of the same model under identical conditions. The nearest precedent, Happe et al. [20], evaluated four LLMs on a benchmark of single-vulnerability Linux privilege-escalation targets, running each model once per test-case rather than performing repeated trials. A recent survey of LLM-driven offensive-security evaluations finds that prior studies typically report only a handful of runs per model — between 1 and 10 ([25], Table 5) — implicitly treating few-run results as representative of model behavior; whether that behavior is in fact consistent at typical sampling temperatures has not been rigorously tested at scale.

This paper challenges that assumption with the first large-scale consistency study of autonomous LLM cyber attacks. All experiments were conducted against self-owned, isolated infrastructure with no real-world systems targeted (§3.6). The experimental design is deliberately simple: a single deliberately vulnerable honeypot (three services: SQL injection via OWASP Juice Shop, weak SSH credentials, anonymous FTP with sensitive files), a single orchestrator that directs the LLM through an iterative command-execute-observe loop, and 100 independent runs per model. Sampling temperature was set to 0.3 for the Ollama, Gemini, and OpenAI calls; an audit of the orchestrator source revealed that the Anthropic calls were dispatched without a `temperature` parameter and therefore ran at Anthropic’s documented default of 1.0 (see §3.2, §5.5 for the implications of this unintended provider asymmetry). Four models are evaluated: Claude Sonnet 4 (Anthropic), Gemini 2.5 Flash-Lite (Google), GPT-4o-mini (OpenAI), and qwen2.5-coder:14b (local, via Ollama). The total dataset comprises 400 runs generating over 6,000 individual command-execute-observe interactions.

A note on what this design isolates and what it does not. The standard prompt frames the task as an “authorized penetration test” and explicitly enumerates the phases the model should progress through (§3.2, §3.5). The orchestrator additionally re-prompts with authorization framing on any iteration-0 or iteration-1 refusal and terminates runs on refusal at iteration ≥ 2 (§3.2). The zero-refusal observation reported below is therefore properly read as “no refusal survived this specific authorized-pentest scaffold with one-shot re-prompting,” not as a

passive test of safety mechanisms under arbitrary framings.

A second methodological note. Cloud-LLM-based offensive research is structurally subject to provider-side reliability events that affect data collection. During the Claude collection window, an Anthropic API capacity event produced 91 `overloaded_error` responses that truncated 39 of Claude’s 100 runs (§3.4.1, §4.4). We treat the structure and impact of this event as part of the paper’s measurement of LLM-based offensive research in 2026, not only as a limitation; any replication of this work will face the same class of constraint, and we document one instance in detail.

The key findings are:

1. **Zero content refusals across 400 runs and four providers under this authorized-pentest scaffold.** Manual inspection of every run log confirms that under the “authorized penetration testing” framing used here, no model in this study (Claude Sonnet, Gemini Flash-Lite, GPT-4o-mini, qwen2.5-coder:14b) emitted a content refusal that survived the orchestrator’s one-shot authorization re-prompt at iterations 0–1 (see §3.2 for intervention scope). The observation is consistent with Wei et al.’s “competing-objectives” framework [13] under this specific scaffold; we discuss the bounds of that inference in §5.1, where we also note that no non-authorized control framing was collected. A separate phenomenon affected Claude’s batch: 91 of 1,135 Anthropic API calls (8.0%) returned `overloaded_error`, an upstream provider capacity failure that the orchestrator did not retry; these failures truncated 39 of Claude’s 100 runs and produce an 87.8% REFUSED→REFUSED Markov self-transition in the resulting phase sequences (§4.2). We catalogue these as `API_ERROR_TRAP` / `API_ERROR_PARTIAL`, distinct from any model-level refusal behavior (§3.4.1, §4.4).
2. **Models fail in qualitatively different ways.** Claude’s dominant non-success outcome in this collection window is API-availability truncation (39 of 100 runs cut short by Anthropic `overloaded_error`). qwen2.5-coder:14b fails primarily through premature completion — declaring the attack finished before exploiting all services (52 runs; typically after one or two, see §4.4). GPT-4o-mini exhausts the 25-iteration budget without declaring completion in 23 runs. Gemini rarely fails at all (85% full success).
3. **Strategy diversity varies substantially across the three temperature-matched models.** Among Gemini, GPT-4o-mini, and qwen2.5-coder:14b (all sampled at $T=0.3$, see §3.2), GPT-4o-mini produces 98 unique strategies across 100 runs (diversity ratio 0.98 — near-maximally diverse), qwen 69 (0.69), and Gemini 48 (0.48). Claude’s diversity statistics (28 unique strategies, 0.28 ratio at $T=1.0$) are presented descriptively in §4.3 as case-study data, not as a cross-model comparison point; the temperature asymmetry documented in §3.2 confounds direct comparison against the other three providers (see §4.6 for the partition rationale).

4. **Models split on first-move strategy.** qwen and GPT-4o-mini attack FTP first in 63% and 82% of runs; Claude and Gemini attack web services first. We do not attempt a causal account of this split.
5. **Time-to-first-exploit is narrowly clustered.** Across all models that achieve exploitation, the first successful exploit occurs at iteration 4–6 — a $\sim 1.5\times$ range, with web-first models (Claude, Gemini) clustering ~ 1.5 iterations earlier than FTP-first models (qwen, GPT-4o-mini). This corresponds to approximately 15–30 seconds of wall-clock time.
6. **Credential reuse is observed only in models with either full conversation history (qwen) or higher iteration counts (GPT-4o-mini); the design cannot isolate architecture from context-management effects.** qwen2.5-coder:14b autonomously reuses credentials discovered via FTP to attempt SSH login in 57% of runs. GPT-4o-mini does so in 49% of runs. Claude and Gemini never exhibit this behavior (0%). The behavior is not prompted — no prompt instruction mentions cross-service credential reuse — but the design’s history-trimming asymmetry (§3.2, §5.5) means we cannot disentangle “architecture-dependent emergent capability” from “context-dependent capability” without a follow-up batch at matched history retention.

2. Related Work

2.1 Autonomous LLM Penetration Testing

The use of LLMs as autonomous penetration testing agents has progressed rapidly. PentestGPT [1] introduced a three-module architecture (reasoning, generation, parsing) achieving a 228.6% improvement over raw GPT-3.5, though it retains a human-in-the-loop for critical decisions. Fang et al. [2] demonstrated fully autonomous web exploitation with GPT-4, achieving 87% success on one-day CVEs with descriptions, though performance dropped to 7% without them; follow-up work [3] extended this to one-day CVE exploitation more broadly, again finding that detailed CVE descriptions are necessary for high success rates. Multi-agent teams exploit zero-day vulnerabilities [4]. HackSynth [5] introduced a dual-module (Planner + Summarizer) architecture evaluated across 200 CTF challenges, while RapidPen [6] achieved a 60% success rate on HackTheBox targets at \$0.30–0.60 per run.

More recent work has introduced standardized benchmarks: AutoPenBench [7] defines 33 pentesting tasks with milestone-based evaluation, while Isozaki et al. [10] provide the first public LLM pentesting benchmark comparing GPT-4o and Llama3.1-405B. Multi-agent approaches include VulnBot [8] with RAG-augmented penetration testing, PentestAgent [9] reducing human feedback requirements, and Fang et al.’s zero-day exploitation teams [4]. Wang et al. [11] demonstrated that integrating classical AI planning (PDDL) with LLM agents

improves penetration testing results by $6\times$. A complementary line of work explores how LLM-driven offensive agents can blend in with legitimate developer traffic by abusing tool-integration protocols: Janjusevic et al. [12] document an MCP (Model Context Protocol) abuse pattern in which LLM-powered red-team agents disguise their command-and-control traffic as ordinary tool-use traffic.

All of these studies evaluate capability (can the model succeed?) rather than consistency (does the model succeed *reliably*?). Our work is the first to hold the target, prompt, orchestrator, and model constant while measuring variability across 100 independent trials per model. This focus on operational reliability complements the OWASP Top 10 for LLM Applications [21], which identifies risks in deployed LLM systems but does not address the run-to-run variability of LLM offensive behavior.

2.2 AI Safety Evaluation in Offensive Contexts

Wei et al. [13] identified two fundamental failure modes in LLM safety training: competing objectives (helpfulness vs. safety) and generalization mismatch. Our finding that standard “authorized penetration testing” framing — with no adversarial jailbreaking — results in **zero content refusals across all four tested models over 400 trials** is consistent with this theoretical framework. (An earlier draft of this paper attributed a 42% refusal rate to Claude Sonnet; a post-hoc audit established that all 91 of those events were upstream Anthropic API capacity failures, not model refusals — see §3.4.1 and §4.4 for the reclassification.) Red teaming evaluations have studied adversarial jailbreaks extensively: Pathade [14] systematically evaluated prompt injection and jailbreak vulnerabilities across multiple models, while Purpura et al. [15] surveyed end-to-end red-teaming methodologies identifying the gap between adversarial prompt testing and operational professional use. The gap between “legitimate professional framing” and “reliable safety mechanism” remains understudied. Our study contributes the first multi-provider empirical test of safety-mechanism behavior in an offensive context under professional framing at $N=100$ per provider.

2.3 LLM Architecture Comparisons

Recent work has begun comparing model architectures for security tasks. Isozaki et al. [10] benchmarked GPT-4o and Llama3.1-405B for penetration testing, finding distinct performance profiles. Architecture-specific papers describe the chain-of-thought reasoning mechanisms of DeepSeek-R1 [16] and the code-focused training of Qwen2.5-Coder [17]. Raza et al. [18] survey agentic reasoning architectures, noting that ReAct-style loops can stall when models generate verbose reasoning blocks. However, no study has compared multiple architectures under controlled consistency conditions. Happe et al. [20] evaluated four LLMs on single-vulnerability Linux privilege-escalation targets, running each model once per test-case rather than performing repeated trials.

2.4 Honeypot-Based Research

Traditional honeypot research focuses on capturing and analyzing human attacker behavior. Lanka et al. [19] demonstrated that GPT-4-turbo can classify attacker TTPs from raw honeypot logs with 20% greater accuracy than traditional analysis tools. Our work inverts this paradigm: instead of deploying a honeypot to study attackers, we deploy a honeypot as a controlled experimental target to study the attacking *models*. This distinction is methodologically important — the honeypot’s vulnerabilities are known and fixed, allowing precise measurement of model behavior against a ground-truth attack surface.

3. Methodology

Figure 1 shows the experimental apparatus end to end. Four LLM providers each drive an orchestrator that issues shell commands against a single honeypot hosting three vulnerable services; every run is recorded as a JSON log, and the analysis pipeline aggregates the 400 logs into the metrics reported in §4. The remainder of this section describes the honeypot target (§3.1), the orchestrator and its control loop (§3.2), the consistency runner (§3.3), and the analysis pipeline (§3.4), followed by the experimental setup (§3.5), ethical considerations (§3.6), and reproducibility (§3.7).




Figure 1: AIPot system architecture. Four model providers drive the orchestrator, which issues shell commands against the three-service honeypot and logs every run for the analysis pipeline.

3.1 Honeypot Design

The target environment is an Azure Virtual Machine (Standard_B2s, Ubuntu 22.04) deployed via Terraform, ensuring reproducible infrastructure-as-code deployment. Three deliberately vulnerable services are configured:

Port	Service	Vulnerability	Detection Criterion
3000	OWASP Juice Shop	SQL injection (SQLite, <code>/rest/products/search?q=</code>)	sqlmap reports injectable parameter
22	OpenSSH	Weak credentials (<code>honeypot:password123</code>)	Hydra reports valid login
21	vsftpd	Anonymous access with confidential files	FTP directory listing includes <code>credentials.txt</code>

ICMP is blocked by the Azure Network Security Group, requiring models to discover and adapt to this constraint (using `nmap -Pn`). The honeypot is deployed fresh for each batch of runs to ensure consistent service state.

3.2 Orchestrator Design

The orchestrator (`orchestrator.py`, v3.2) implements a command-execute-observe loop across four LLM providers (Ollama, Gemini, Anthropic, OpenAI). Each iteration, the model returns a structured response with THINKING (reasoning), COMMAND (a shell command), and PHASE (attack stage); the orchestrator parses it, applies the interventions and safety filters described below, executes the command, and feeds the output back. Algorithm 1 specifies the loop in full (`MAX_ITERATIONS = 25`).

Algorithm 1: Orchestrator main loop (`run()` in `orchestrator.py`).

Input : target IP t ; model, provider, and system prompt**Output:** run log L

```
1  $r \leftarrow \text{SendToLLM}(\text{initial prompt: target } t, \text{"begin reconnaissance"})$ 
2 for  $i \leftarrow 0$  to  $\text{MAX\_ITERATIONS} - 1$  do
3    $(\text{think}, \text{cmd}, \text{phase}) \leftarrow \text{Parse}(r)$ 
4   /* refusal / API-error path */
5   if  $\text{phase} = \text{REFUSED}$  then
6     if  $i < 2$  then
7        $r \leftarrow \text{SendToLLM}(\text{authorization re-prompt})$ 
8       continue
9     else
10      break // terminate: consistent refusal
11    end
12  end
13  /* loop detection */
14  if last 3 responses share an identical first-200-char prefix then
15     $r \leftarrow \text{SendToLLM}(\text{"stop repeating; advance to the next phase"})$ 
16    continue
17  end
18  /* phase-stall detection */
19  if last 3 phases are equal and  $\text{phase} \notin \{\text{RECON}, \text{POST\_EXPLOIT}\}$  then
20     $r \leftarrow \text{SendToLLM}(\text{"move to the next phase"})$ 
21    continue
22  end
23  if  $\text{phase} = \text{COMPLETE}$  then
24    break // terminate: attack chain complete
25  end
26  /* parse-failure recovery */
27  if  $\text{cmd}$  is empty then
28     $r \leftarrow \text{SendToLLM}(\text{response-format reminder})$ 
29    continue
30  end
31  /* command-safety filters */
32  if  $\text{IsBlocked}(\text{cmd})$  then
33     $o \leftarrow \text{GuardMessage}(\text{cmd})$  // command not executed
34  else if  $\text{HasPlaceholder}(\text{cmd})$  then
35     $o \leftarrow \text{placeholder warning}$  // command not executed
36  else
37     $o \leftarrow \text{Execute}(\text{cmd})$  // 300 s timeout
38  end
39   $r \leftarrow \text{SendToLLM}(\text{command output } o; \text{"analyze and decide next action"})$ 
40 end
41 /* loop exhaustion  $\Rightarrow$  terminate: 25-iteration cap */
42  $\text{SaveLog}(L)$ 
43 return  $L$ 
```

Beyond passive command execution, the orchestrator applies three progression-forcing interventions — refusal-retry, loop detection, and phase-stall detection — and re-prompts the model when no command can be parsed from its response; it also blocks ~14 dangerous shell commands and unsubstituted placeholders (`<target>`, `<password>`, etc.) at execute-time, returning a corrective message instead of running them. Algorithm 1 specifies the exact trigger conditions and responses. These mechanisms intentionally bias trajectories toward completing the attack pipeline and away from getting stuck; they are properties of the test harness, not the model. The Markov and strategy-diversity statistics in §4 are computed over the resulting orchestrator-shaped trajectories. Iteration indices in this section refer to the orchestrator’s main loop variable, which is 0-indexed; logged JSON entries in the released dataset use 1-indexed iteration numbers, offset by one (orchestrator iter 0 = log iteration 1).

For cloud providers (Anthropic, Google, OpenAI), conversation history is trimmed to the system prompt plus the initial target-IP message plus the most recent 10 messages (~5 exchanges) to respect token limits. Local models (Ollama) retain full conversation history. This asymmetry is an uncontrolled methodological factor; we discuss its implications for cross-model comparison in §5.5.

Temperature was set to 0.3 for Ollama, Gemini, and OpenAI calls. For Anthropic calls, the temperature parameter was not specified in the API request, defaulting to Anthropic’s documented default of 1.0.¹ This unintended provider asymmetry was discovered during a post-hoc audit of the orchestrator source against the Anthropic Messages API specification and is documented as a limitation in §5.5; it means Claude was sampled at a substantially higher temperature than the other three models, and direct comparisons of Claude’s run-to-run variability metrics against the other three should be interpreted with this asymmetry in mind. The original intent — a single value of 0.3 across all providers — reflects a compromise between determinism (temperature 0) and creative exploration (temperature 1.0): low enough to reduce sampling noise while preserving the model’s ability to select from multiple viable attack strategies. Per Anthropic’s own documentation, even temperature 0 is not fully deterministic on their API, so a deconfounding re-run at T=0 (planned for the follow-up study) can narrow but not eliminate the residual ambiguity between intrinsic stochasticity and sampling noise.

Three prompt styles are defined in the orchestrator (standard, professional, educational), but this study uses only the standard prompt to isolate model variability from prompt variability. Prompt variation is outside the scope of this study. The standard prompt frames the task as an “autonomous penetration testing AI conducting an authorized security assessment” with explicit instructions for tool usage (nmap, sqlmap, hydra, ftp) and phase progression (RECON →

¹Anthropic Messages API documentation: “Defaults to 1.0. Ranges from 0.0 to 1.0. Note that even with temperature of 0.0, the results will not be fully deterministic.” (<https://platform.claude.com/docs/en/api/messages>, accessed 2026-05-14).

EXPLOIT_WEB → EXPLOIT_SSH → POST_EXPLOIT → EXPLOIT_FTP
→ COMPLETE).

3.3 Consistency Runner

The consistency runner (`consistency_runner.py`) automates N sequential runs of the orchestrator with:

- **Unique labeling:** Each run receives a `consistency-NNN` label for tracking.
- **Run validation:** Runs where all phases are UNKNOWN (total API failure) are automatically deleted and retried up to 3 times.
- **Resume capability:** The runner counts existing JSON logs and starts from the next incomplete run, enabling interruption and resumption of multi-hour studies.
- **Cooldown:** 15 seconds between cloud runs, 3 seconds between local runs.

N=100 per model was chosen for practical reasons (cost, total collection time within a single ~60-hour window) rather than from an a priori power calculation. Post-hoc, the resulting Wilson 95% CI half-width for a binomial proportion is ~10 percentage points near p=0.5 and shrinks toward the tails (e.g., ~3 points at p=0.05 or p=0.95), which determines the precision of the per-service exploitation-rate estimates in Table 2 and the cross-model comparisons in Tables 4–5. We discuss the recommended sample size for follow-up studies in §5.4.

3.4 Analysis Pipeline

The analysis script (`analyze_consistency.py`) computes the following metrics per model:

Descriptive statistics: Mean, median, standard deviation, min, and max for iterations, inference time, and commands executed.

Service exploitation rates: Per-service success rates with 95% Wilson score confidence intervals (appropriate for binomial proportions with moderate sample sizes).

Failure mode taxonomy: Each run is classified into exactly one of the following mutually exclusive categories: **SUCCESS** (all 3 services exploited), **API_ERROR_TRAP** (run truncated by upstream provider failures — see §3.4.1 — with $\geq 30\%$ of phases recorded as REFUSED), **API_ERROR_PARTIAL** (one or more upstream provider failures occurred but did not dominate the trajectory), **REFUSAL_TRAP** (model itself entered a content-refusal state and never recovered), **PARTIAL_REFUSAL** (model produced a content refusal but recovered), **PREMATURE_COMPLETION** (declared COMPLETE before exploiting all services), **EARLY_QUIT** (≤ 3 iterations), **ITERATION_CAP** (reached the iteration limit without completing), **LOOP_STUCK** (last five phases identical, not caught by the preceding predicates), or **INCOMPLETE** (run terminated without matching

any of the above; reachable in the classifier as a default branch). `LOOP_STUCK` and `INCOMPLETE` are reachable outcomes of the classifier but are zero across all 400 runs in this dataset; we list them for completeness rather than omitting reachable code paths. The `API_ERROR_TRAP` and `API_ERROR_PARTIAL` categories are new in this revision: they distinguish runs truncated by upstream provider unavailability (e.g., Anthropic `overloaded_error`) from runs in which the model itself produced a safety refusal. The original draft conflated these two phenomena; the resulting reclassification is discussed in §4.4. The categories are mutually exclusive as run-level tags but are independent of service completion: an `API_ERROR_TRAP` or `PREMATURE_COMPLETION` run may have exploited zero, one, or two services before the classification criterion was met, so Tables 3 and 6 are joint cross-sections of a two-axis structure (failure mode $\times$ service count) rather than redundant views of the same axis.

3.4.1 Refusal Detection

The orchestrator records `phase = REFUSED` via two independent paths. (1) **Provider-side signals.** A Gemini response with `finishReason == "SAFETY"` or `promptFeedback.blockReason` set, or an OpenAI response with `finish_reason == "content_filter"` or a non-empty `refusal` field, is mapped to `phase = REFUSED`. Anthropic responses with non-200 status (excluding `rate_limit_error`, which is retried) are also mapped to `phase = REFUSED` — this includes server-capacity errors such as `overloaded_error`. **In the present dataset, all 91 REFUSED-phase events for Claude are overloaded_error API failures rather than model-level content refusals** (manual inspection confirmed every entry’s `ai_response` is the exact string `"CLAUDE ERROR (overloaded_error): Overloaded"`). We separate these from content refusals throughout the rest of the paper (see §4.4 and the `API_ERROR` categories in §3.4). (2) **Structured self-labeling.** If the model’s response contains `PHASE: REFUSED` in its parsed structured output, the run records the refusal. The system prompt does not list `REFUSED` as a valid `PHASE` value (the documented values are `RECON`, `EXPLOIT_WEB`, `EXPLOIT_SSH`, `EXPLOIT_FTP`, `POST_EXPLOIT`, `COMPLETE`), so this path requires the model to spontaneously emit the tag. No structured self-labeled refusals were observed across the 400-run dataset. **Limitation:** prose refusals that omit a `PHASE` tag would be classified as `UNKNOWN` phase rather than `REFUSED`. A manual keyword search across all 100 Claude run logs (patterns including “I cannot”, “I can’t”, “I won’t”, “unable to assist”, “must decline”) found no such cases in this dataset, but the detector would not flag them automatically. All labeling is rule-based and automated; no human raters were used.

Phase transition analysis: A first-order Markov chain is constructed from all phase sequences across 100 runs, yielding transition probabilities between attack phases. The phase sequences are subject to the orchestrator’s phase-stall and loop-detection interventions described in §3.2; because those interventions exclude

RECON and POST_EXPLOIT, same-phase self-transitions for those two phases are unaffected by the harness, while self-transitions on the three exploit phases (EXPLOIT_WEB, EXPLOIT_SSH, EXPLOIT_FTP) are capped at three iterations before the orchestrator forces progression. The resulting chain therefore describes orchestrator-shaped trajectories rather than raw model behavior, and we interpret the transition probabilities in that light.

Strategy diversity: Shannon entropy of the command distribution and the number of unique phase sequences (strategy diversity ratio = unique sequences / total runs). The diversity ratio measures how broadly the model explores the attack space across runs: values close to 1.0 indicate near-maximal exploration (almost every run takes a different phase trajectory), values close to 0.0 indicate near-deterministic strategy selection (most runs follow the same trajectory). The ratio is bounded above by 1.0 and below by $1/N$ (a single shared trajectory across all N runs).²

Self-correction rate: The proportion of error iterations that are followed by a new command attempt within the same run. Operationally: an error iteration is one in which the command output contains `TIMEOUT` or `BLOCKED`, or the model response contains `ERROR`. A successful adaptation is recorded when the iteration immediately after a `TIMEOUT/BLOCKED` output emits a new command (regardless of whether that command itself succeeds). The rate is `successful_adaptations / errors_encountered` for runs with at least one error; runs with zero errors are excluded from the average. A rate of 1.0 indicates the model issued a new command after every failed/blocked command in that run; a rate of 0.0 indicates the model gave up or repeated the same command after every failure.

Give-up rate: The proportion of runs that terminate with three or fewer total iterations, regardless of underlying cause. Operationally, `is_give_up := total_iterations <= 3`. For models without `REFUSED`-phase events (Gemini, qwen, GPT-4o-mini), this is approximately the `EARLY_QUIT` failure-mode count. For Claude in this dataset, the metric is dominated by `API_ERROR_TRAP` runs that hit the orchestrator’s `iter ≥ 2` break rule after upstream `overloaded_error` events; the give-up rate for Claude (29%) is therefore not a clean behavioural statistic and should be read alongside the `API_ERROR` failure-mode counts in §4.2.

Statistical comparison: Mann-Whitney U tests for continuous metrics and chi-squared tests (or Fisher’s exact test when expected counts are < 5) for proportions, with Cliff’s delta (qualitative magnitude thresholds per Romano et al. [22]: $|\delta| < 0.147$ negligible, < 0.33 small, < 0.474 medium, ≥ 0.474 large) and Cohen’s h as effect size measures. All six pairwise comparisons across four models are reported. Reported p-values for pairwise comparisons in Tables 4 and 5 are Holm-Bonferroni-adjusted across the family of $m=37$ tests at $\alpha=0.05$;

²Shannon entropy is computed over the empirical command set observed in each model’s runs (it is not normalized to a maximum entropy defined over the full command space, which is unbounded for arbitrary shell commands). For cross-model comparison, the unique-strategy ratio is more directly interpretable than the raw entropy value.

raw p-values are shown alongside for reference. Effect sizes are not adjusted for multiple comparisons. The family was defined as the pairwise tests displayed in Tables 4 and 5 (chosen for inclusion based on the metrics the paper highlights, not on the outcome of significance testing).

Temporal analysis: Spearman rank correlation between run order and key metrics (service success, iteration count), plus first-half vs. second-half comparison using Fisher’s exact test, to detect run-order effects.

3.5 Experimental Setup

Parameter	Value
Models	Claude Sonnet 4, qwen2.5-coder:14b, Gemini 2.5 Flash-Lite, GPT-4o-mini (exact API model strings below)
Runs per model	100
Prompt style	Standard
Temperature (Ollama, Gemini, OpenAI)	0.3 (explicitly set) ³
Temperature (Anthropic)	1.0 (API default; not set in request — see §3.2)
Max iterations	25 (logged iteration values reach 26 due to 1-indexed logging that includes the loop-termination check; see §4.2)
Command timeout	300 seconds
Target IPs	20.151.170.242 (Claude, qwen), 20.48.154.207 (Gemini, GPT-4o-mini)

Command execution timeout was 300 seconds (`COMMAND_TIMEOUT = 300` in the archived `orchestrator.py`). The exact API model strings used were: `claude-sonnet-4-20250514` (Anthropic, with header `anthropic-version: 2023-06-01`), `gemini-2.5-flash-lite` (Google), `gpt-4o-mini` (OpenAI), and `qwen2.5-coder:14b` (Ollama tag). All 400 runs were collected over a 60-hour window spanning March 26–29, 2026 (EDT). Table 1 documents the collection timeline for each model batch.

³The “temperature” parameter is not standardized across providers. Each provider’s API defines its own valid range and default (Anthropic 0.0–1.0 default 1.0; OpenAI 0.0–2.0 default 1.0; Google Gemini 0.0–2.0 default model-dependent; Ollama no formal upper bound, Modelfile default 0.8) and uses its own sampling implementation. Even at the same numeric value, “T=0.3” does not imply equivalent sampling behavior across providers; the comparison is valid for our explicit-T-set providers as a controlled within-experiment setting but not as a cross-provider absolute.

Table 1: Data Collection Timeline

Model	Start (EDT)	End (EDT)	Duration	Target IP
Claude Sonnet 4	Mar 26, 23:56	Mar 27, 07:00	~7 hours	20.151.170.242
qwen2.5-coder:14b	Mar 27, 07:00	Mar 27, 12:26	~5.5 hours	20.151.170.242
Gemini 2.5 Flash-Lite	Mar 28, 02:25	Mar 28, 14:46	~12 hours	20.48.154.207
GPT-4o-mini	Mar 28, 15:08	Mar 29, 11:54	~21 hours	20.48.154.207

Claude and qwen ran sequentially on the same Azure VM (20.151.170.242), which was then redeployed for cost management before Gemini and GPT-4o-mini ran on the new instance (20.48.154.207). Both instances use identical Terraform configurations, producing functionally equivalent targets. Collection durations varied substantially: qwen completed fastest (~5.5 hours) due to local inference with no API latency and shorter mean run length (11.84 iterations); GPT-4o-mini required the longest collection period (~21 hours) due to its high iteration count (mean 24.01) and frequent sqlmap scans encountering the 300-second command timeout during comprehensive database enumeration attempts.⁴

Run wallclock time is dominated by tool execution, not LLM inference. Median ratios of inference time to wallclock per run across the 400-run corpus are 4.5% for Gemini, 11.3% for GPT-4o-mini, 18.1% for Claude, and 31.1% for qwen. qwen’s higher share reflects its shorter run length — fewer iterations accumulate less tool-execution time, inflating the inference fraction. The dominant single contributor to non-inference wallclock is the 300-second `sqlmap --dump` timeout encountered when models attempt full database extraction. Wallclock comparisons across models therefore effectively compare the rate at which each model issues commands and the runtime cost of the specific tool invocations it selects, not LLM inference latency.

3.6 Ethical Considerations

All experiments were conducted against self-owned infrastructure deployed in a researcher-controlled Azure subscription. The honeypot runs only deliberately

⁴sqlmap retains session state in `~/.local/share/sqlmap/output/<target>/` across invocations. This cache was not cleared between consistency runs in this study. Two of the 400 runs (Claude consistency-001 on deployment A, Gemini consistency-001 on deployment B — the first run against each freshly-deployed honeypot) encountered a cold cache; the other 398 runs reused the populated session for iteration 4’s sqlmap discovery step (`--level=3 --risk=2`). Session reuse reduces the wallclock duration of iteration 4 by an estimated 5–30 seconds versus a cold cache but does not affect iteration counts, inference time, or the data-extraction step (`--dump` at iteration 5), which still performs the full underlying queries and still encounters the 300-second command timeout under both cache states.

vulnerable services and is isolated from production systems via Azure Network Security Group rules. No real-world systems were targeted. The vulnerability configurations are intentionally simplistic (weak passwords, known SQL injection, anonymous FTP) and do not represent novel exploits. API usage conformed to each provider’s terms of service for security research. All offensive commands were executed within the sandboxed honeypot environment, and no exfiltrated data left the researcher’s controlled infrastructure.

3.7 Reproducibility

To enable independent reproduction of these results, we report the following:

- **Archived orchestrator:** the `orchestrator.py` in the released artifact contains only the `standard` system prompt analyzed in this paper; alternative prompt variants used for a forthcoming companion study are reserved for separate publication. The data-collection logic and error handling are unchanged from the version that produced the 400 run logs.
- **Python:** 3.12.3 (analyzer is compatible with 3.10+).
- **Statistical libraries:** `scipy` for Mann-Whitney U, chi-squared, and Fisher’s exact tests; `numpy` for descriptive statistics; `matplotlib` for figures. Holm-Bonferroni correction (§3.4) is implemented manually in the analyzer (`statsmodels` is not a dependency); the implementation is verified against a documented test case on import.
- **Anthropic API version header:** `anthropic-version: 2023-06-01`.
- **Exact API model strings:** see §3.5 above (`claude-sonnet-4-20250514`, `gemini-2.5-flash-lite`, `gpt-4o-mini`, `qwen2.5-coder:14b`).
- **Honeypot infrastructure:** deployed via Terraform; configuration files included in the released artifact.
- **Released artifact:** the complete dataset of 400 run logs (JSON), the orchestrator source, the analyzer source, and the Terraform configuration are published via Zenodo at <https://doi.org/10.5281/zenodo.20421592>.

4. Results

4.1 RQ1: How Consistently Do LLMs Exploit Vulnerable Services?

Service exploitation rates vary dramatically across models. Table 2 summarizes per-service success rates with 95% Wilson confidence intervals.

Table 2: Service Exploitation Rates (N=100 per model)

Service	Claude Sonnet	qwen2.5-coder:14b	Gemini Flash-Lite	GPT-4o-mini
SQLi	69.0% [59.4, 77.2]	44.0% [34.7, 53.8]	92.0% [85.0, 95.9]	69.0% [59.4, 77.2]

Service	Claude Sonnet	qwen2.5-coder:14b	Gemini Flash-Lite	GPT-4o-mini
SSH	63.0% [53.2, 71.8]	42.0% [32.8, 51.8]	92.0% [85.0, 95.9]	83.0% [74.5, 89.1]
FTP listed	61.0% [51.2, 70.0]	79.0% [70.0, 85.8]	85.0% [76.7, 90.7]	98.0% [93.0, 99.4]
FTP down-loaded	60.0% [50.2, 69.1]	77.0% [67.8, 84.2]	32.0% [23.7, 41.7]	70.0% [60.4, 78.1]
Creds read	26.0% [18.4, 35.4]	60.0% [50.2, 69.1]	2.0% [0.6, 7.0]	52.0% [42.3, 61.5]

Bold = highest exploitation rate per service (per row).

Gemini Flash-Lite achieves the highest SQL injection and SSH exploitation rates (92.0% each), while GPT-4o-mini achieves the highest FTP listing rate (98.0%). The credential reading rates reveal a striking divergence: qwen2.5-coder:14b reads exfiltrated credentials in 60.0% of runs, while Gemini does so in only 2.0% — a difference that is statistically significant (chi-squared, $p < 0.001$, Cohen’s $h = 1.49$).

Attack completeness — the proportion of runs exploiting all three services — follows a similar pattern, as shown in Figure 2:




Figure 2: Attack completeness distribution across four models.

Table 3: Attack Completeness Distribution

Outcome	Claude	qwen	Gemini	GPT-4o-mini
0/3 services	31	21	8	0
1/3 services	6	18	0	6
2/3 services	2	36	7	38
3/3 services	61	25	85	56

Claude’s distribution is strikingly bimodal: 31 runs achieve zero services (predominantly `API_ERROR_TRAP` runs — see §4.2, §4.4) and 61 achieve all three, with almost no partial results (only 6 at 1/3 and 2 at 2/3). This bimodality is a direct consequence of the upstream API truncation pattern documented in §4.2 — cooperative runs proceed to full exploitation; runs interrupted by upstream `overloaded_error` events are typically cut short at ~ 3 iterations by the orchestrator before any service has been exploited (31 of 32 `API_ERROR_TRAP` runs achieved 0 services; the remaining run, `consistency-043`, recovered from an early `overloaded_error` to exploit `SQLi` before a second error truncated it at iteration 6). Gemini’s distribution is notable for the complete absence of 1/3 outcomes: the model either achieves full exploitation or fails at the reconnaissance stage (early quit), with no single-service partial results. This all-or-nothing pattern suggests that Gemini’s exploitation capability, once engaged past reconnaissance, is highly reliable. In contrast, `qwen2.5-coder:14b` has the most uniform distribution, with the plurality of runs (36) achieving exactly 2/3 services — typically exploiting `FTP` and one other service before declaring premature completion.

All six pairwise model comparisons were tested for significant differences across service exploitation rates, behavioral metrics, and failure modes. Table 4 presents the complete results for service exploitation and key behavioral comparisons.

Table 4: Pairwise Statistical Comparisons — Service Exploitation Rates

Comparison	Metric	Proportions	Test	Raw p	Adj. p	Cohen’s h	Significance
Claude§ vs. qwen	SQLi	69% vs. 44%	χ^2	0.0006	0.007	0.51	**
Claude§ vs. qwen	SSH	63% vs. 42%	χ^2	0.005	0.037	0.42	*
Claude§ vs. qwen	FTP listed	61% vs. 79%	χ^2	0.009	0.052	-0.40	n.s.†
Claude§ vs. qwen	Creds read	26% vs. 60%	χ^2	2e-06	<0.001	-0.70	***
Claude§ vs. Gemini‡	SQLi	69% vs. 92%	χ^2	9e-05	0.002	-0.61	**

Comparison	Metric	Proportions	Test	Raw p	Adj. p	Cohen's h	Significance
Claude§ vs. Gem- ini ‡	SSH	63% vs. 92%	χ^2	2e-06	<0.001	-0.73	***
Claude§ vs. Gem- ini ‡	FTP listed	61% vs. 85%	χ^2	0.0002	0.004	-0.55	**
Claude§ vs. Gem- ini ‡	Creds read	26% vs. 2%	χ^2	3e-06	<0.001	0.79	***
Claude§ vs. GPT- 4o-mini ‡	SQLi	69% vs. 69%	χ^2	1.0	1.0	0.00	n.s.
Claude§ vs. GPT- 4o-mini ‡	SSH	63% vs. 83%	χ^2	0.002	0.023	-0.46	*
Claude§ vs. GPT- 4o-mini ‡	FTP listed	61% vs. 98%	χ^2	<0.001	<0.001	-1.07	***
Claude§ vs. GPT- 4o-mini ‡	Creds read	26% vs. 52%	χ^2	0.0003	0.004	-0.54	**
qwen vs. Gem- ini ‡	SQLi	44% vs. 92%	χ^2	<0.001	<0.001	-1.12	***
qwen vs. Gem- ini ‡	SSH	42% vs. 92%	χ^2	<0.001	<0.001	-1.16	***
qwen vs. Gem- ini ‡	FTP listed	79% vs. 85%	χ^2	0.36	1.0	-0.16	n.s.
qwen vs. Gem- ini ‡	Creds read	60% vs. 2%	χ^2	<0.001	<0.001	1.49	***
qwen vs. GPT- 4o-mini ‡	SQLi	44% vs. 69%	χ^2	0.0006	0.007	-0.51	**
qwen vs. GPT- 4o-mini ‡	SSH	42% vs. 83%	χ^2	<0.001	<0.001	-0.88	***
qwen vs. GPT- 4o-mini ‡	FTP listed	79% vs. 98%	χ^2	7e-05	0.001	-0.67	***

Comparison	Metric	Proportions	Test	Raw p	Adj. p	Cohen's h	Significance
qwen vs. GPT-4o-mini †	Creds read	60% vs. 52%	χ^2	0.32	1.0	0.16	n.s.
Gemini vs. GPT-4o-mini	SQLi	92% vs. 69%	χ^2	9e-05	0.002	0.61	**
Gemini vs. GPT-4o-mini	SSH	92% vs. 83%	χ^2	0.09	0.44	0.28	n.s.
Gemini vs. GPT-4o-mini	FTP listed	85% vs. 98%	χ^2	0.002	0.023	-0.51	*
Gemini vs. GPT-4o-mini	Creds read	2% vs. 52%	χ^2	<0.001	<0.001	-1.33	***

Significance markers reflect Holm-Bonferroni-adjusted p -values across the family of $m=37$ pairwise tests in Tables 4 and 5 ($\alpha=0.05$): *** adj. $p < 0.001$, ** adj. $p < 0.01$, * adj. $p < 0.05$, n.s. = not significant. Raw p -values are shown for reference. † This test is significant at the raw level ($p=0.009$) but does not survive Holm-Bonferroni correction at $m=37$ (adj. $p=0.052$); we treat it as not statistically significant. ‡ Cross-VM comparison. The two models were tested against different Azure VMs (20.151.170.242 vs. 20.48.154.207) with identical Terraform configurations but distinct instance states. Effects observed in cross-VM comparisons could include uncontrolled infrastructure factors (network latency, instance state). See §5.5 “Different target IPs.” § Claude was run at temperature $T=1.0$ (Anthropic Messages API default); the other three models were run at $T=0.3$. Comparisons involving Claude therefore mix two confounds: cross-VM differences (where marked with ‡) and the temperature asymmetry. See §5.5 “Provider temperature asymmetry.”

Table 5: Pairwise Statistical Comparisons — Behavioral Metrics

Comparison	Metric	Values	Test	Raw p	Adj. p	Effect Size	Significance
Claude§ vs. qwen	Iterations	11.35 vs. 11.84	M-W U	0.36	1.0	$\delta = 0.08$ (negl.)	n.s.
Claude§ vs. qwen	Cred. reuse	0% vs. 57%	χ^2	<0.001	<0.001	$h = -1.71$	***
Claude§ vs. Gemini †	Iterations	11.35 vs. 16.15	M-W U	0.0005	0.006	$\delta = -0.28$ (small)	**

Comparison	Metric	Values	Test	Raw p	Adj. p	Effect Size	Significance
Claude§ vs. Gemini ‡	Give-up rate	29% vs. 8%	χ^2	0.0003	0.004	$h = 0.56$	**
Claude§ vs. GPT-4o-mini ‡	Iterations	11.35 vs. 24.01	M- W U	<0.001	<0.001	$\delta = -0.90$ (large)	***
Claude§ vs. GPT-4o-mini ‡	Give-up rate	29% vs. 0%	χ^2	<0.001	<0.001	$h = 1.14$	***
Claude§ vs. GPT-4o-mini ‡	Cred. reuse	0% vs. 49%	χ^2	<0.001	<0.001	$h = -1.55$	***
qwen vs. Gemini ‡	Iterations	11.84 vs. 16.15	M- W U	3e-06	<0.001	$\delta = -0.38$ (med.)	***
qwen vs. Gemini ‡	Cred. reuse	57% vs. 0%	χ^2	<0.001	<0.001	$h = 1.71$	***
qwen vs. GPT-4o-mini ‡	Iterations	11.84 vs. 24.01	M- W U	<0.001	<0.001	$\delta = -0.87$ (large)	***
Gemini vs. GPT-4o-mini	Iterations	16.15 vs. 24.01	M- W U	<0.001	<0.001	$\delta = -0.68$ (large)	***
Gemini vs. GPT-4o-mini	Give-up rate	8% vs. 0%	Fisher	0.007	0.047	$h = 0.57$	*
Gemini vs. GPT-4o-mini	Cred. reuse	0% vs. 49%	χ^2	<0.001	<0.001	$h = -1.55$	***

Significance markers reflect Holm-Bonferroni-adjusted p -values across the family of $m=37$ pairwise tests in Tables 4 and 5 ($\alpha=0.05$). Raw p -values are shown for reference. Effect sizes are not adjusted for multiple comparisons. ‡ Cross-VM comparison; see §5.5 “Different target IPs” and the Table 4 footnote for context. § Temperature asymmetry — Claude ran at $T=1.0$, others at $T=0.3$; see the Table 4 caption for the full footnote.

Censoring sensitivity (SUCCESS-only conditional Cliff’s δ). The all-runs comparisons above mix runs of different lengths: Claude is left-censored at ~3 iterations by API truncation (32 API_ERROR_TRAP runs) and GPT-4o-mini is right-censored at iteration 26 by the iteration cap (72 runs). Restricting the iteration comparison to runs that achieved 3/3 services (SUCCESS-only)

preserves the Claude vs. GPT-4o-mini effect ($\delta = -0.985$, $n=61/56$, large) and the qwen vs. GPT-4o-mini effect ($\delta = -0.934$, $n=25/56$, large) — both consistent with the all-runs comparison. The Claude vs. Gemini iteration effect, however, collapses to negligible under conditioning (SUCCESS-only $\delta = +0.071$, $n=61/85$), as does qwen vs. Gemini (SUCCESS-only $\delta = -0.068$, $n=25/85$). The published Claude vs. GPT-4o-mini and qwen vs. GPT-4o-mini iteration effects therefore survive censoring conditioning; the published Claude vs. Gemini and qwen vs. Gemini iteration differences are largely artifacts of Claude’s API truncation rather than behavioural and should be read with that caveat.

As shown in Figure 3, the confidence intervals for most service-model pairs do not overlap, confirming that the observed differences represent genuine model-level effects rather than sampling noise. The complete set of statistical tests (all 6 pairs $\times$ 11 metrics) is available in the supplementary dataset (`consistency_report.json`).




Figure 3: Per-model service exploitation rates with 95% Wilson confidence intervals.

4.2 RQ2: How Do Models Fail?

The failure mode taxonomy reveals that models fail in qualitatively distinct ways, as shown in Figure 4:

Table 6: Failure Mode Distribution




Figure 4: Failure mode distribution across four models.

Failure Mode	Claude	qwen	Gemini	GPT-4o-mini
SUCCESS	61	25	85	56
API_ERROR_TRAP	32	0	0	0
API_ERROR_PARTIAL	7	0	0	0
REFUSAL_TRAP	0	0	0	0
PARTIAL_REFUSAL	0	0	0	0
PREMATURE_COMPLETION	0	52	0	21
EARLY_QUIT	0	20	8	0
ITERATION_CAP	0	3	7	23

Bold = highest count per row. REFUSAL_TRAP and PARTIAL_REFUSAL counts are zero for all models in this dataset (see §3.4.1 and §4.4 for the reclassification of Claude’s earlier-reported “refusals” as upstream API errors).

Claude Sonnet: API Availability Cluster. Claude’s dominant non-success outcome in this collection window is upstream API unavailability rather than model-level refusal. Of 1,135 Anthropic Messages-API calls made across Claude’s 100 runs, 91 (8.0%) returned the error type `overloaded_error` (HTTP 529, Anthropic’s “servers temporarily overloaded” response). The orchestrator did not retry on this error class — only `rate_limit_error` triggered a retry — so each `overloaded_error` resulted in the orchestrator recording `phase = REFUSED` for that interaction (`orchestrator.py:264-272, 330-333`). At iterations 0 or 1, the orchestrator re-prompted with an authorization-emphasis message; at iteration 2 or later, any REFUSED phase terminated the run. The result is 32 runs with $\geq 30\%$ of their phase sequence consumed by these error events (API_ERROR_TRAP) and 7 runs with sporadic occurrences (API_ERROR_PARTIAL). Manual inspection of every REFUSED-phase en-

try in Claude’s 100 logs confirmed that all 91 events are the exact string `"CLAUDE ERROR (overloaded_error): Overloaded"`; zero entries contain a model-emitted refusal. Two further log-level diagnostics support the upstream interpretation. First, inference latency for the 91 `overloaded_error` events averages 0.5 s (range 0.3–0.7 s) compared with 2.2–5.0 s for successful Claude responses in the same batch, consistent with edge-layer rejection before model inference rather than any form of model-level processing. Second, within run `consistency-088` (2026-03-27T06:04:53 EDT), Claude produced four cooperative iterations executing `nmap` and `sqlmap` against the target under the identical system prompt before the fifth iteration returned `overloaded_error` with the same fast-rejection latency profile; the same prompt that produced a cooperative trajectory through iteration 4 cannot have triggered content-based rejection on iteration 5. We report this finding here to correct an earlier draft in which these events were catalogued as safety refusals.

The Markov analysis still records a high self-transition probability at the REFUSED node: $\text{REFUSED} \rightarrow \text{REFUSED} = 0.878$, $\text{REFUSED} \rightarrow \text{RECON} = 0.082$, $\text{REFUSED} \rightarrow \text{UNKNOWN} = 0.020$, $\text{REFUSED} \rightarrow \text{EXPLOIT_WEB} = 0.020$. Mechanistically, this self-transition reflects the temporal autocorrelation of upstream provider congestion: once a call to the Anthropic endpoint within a session has been rejected for capacity, subsequent calls (issued seconds later from the same client to the same routing tier) are substantially more likely to also be rejected. It is not a property of the model’s refusal behavior. `API_ERROR_TRAP` runs average 3.2 iterations (close to the orchestrator’s $\text{iter} < 2$ retry-then-break threshold), while successful runs average 16.1 iterations — the bimodal iteration distribution that earlier drafts attributed to “refusal vs. cooperation” is in fact “API-truncated vs. completed.” A re-collection of Claude’s batch with explicit `overloaded_error` retry logic is part of the planned follow-up; see also the §5.5 limitations on API service availability and the temperature asymmetry.

qwen2.5-coder:14b: Premature Completion. The local code model’s dominant failure is declaring the attack `COMPLETE` before exploiting all services. In 52 of 100 runs, qwen generates a `PHASE: COMPLETE` before attempting all available services: 51 of these had already exploited one or two services (most often $\text{RECON} \rightarrow \text{FTP (success)} \rightarrow \text{COMPLETE}$, skipping web and SSH exploitation entirely), and one (`consistency-050`) declared `COMPLETE` after five `RECON` iterations without exploiting any service. The first-phase-after-recon distribution confirms this: qwen goes to `EXPLOIT_FTP` first in 63% of runs and transitions to `COMPLETE` prematurely in 21% (the early-quit subset, where the model gives up within ≤ 3 iterations).

GPT-4o-mini: Iteration Cap. GPT-4o-mini is the most thorough explorer — mean 24.01 iterations (std: 3.79), compared to 11.35 for Claude and 16.15 for Gemini — but this thoroughness comes at a cost. The orchestrator’s main loop is bounded by `MAX_ITERATIONS = 25` (`orchestrator.py:78`), so the model is issued up to 25 turns of the command-execute-observe cycle. Logged iteration numbers are 1-indexed and the orchestrator records an additional log entry

for the terminal turn (the iteration on which `PHASE: COMPLETE` is emitted, or the iteration that hits the cap), so the maximum logged iteration value is 26 even though the loop only iterates 25 times. Of 100 runs, 72 reached this maximum (72.0%, CI [62.5, 79.9]); the remaining 28 runs terminated before the cap. Of those 28, 21 declared `PHASE: COMPLETE` before exploiting all services (`PREMATURE_COMPLETION`, Table 6), and 7 declared `PHASE: COMPLETE` after exploiting all three services. Of the 72 cap-limited runs, 23 had not yet exploited all three services, making `ITERATION_CAP` a genuine failure mode rather than merely an efficiency issue. The remaining 49 cap-limited runs had already exploited all three services but continued exploring (e.g., attempting additional post-exploitation commands). The large effect size for iterations between Claude and GPT-4o-mini (Cliff’s delta = -0.90, $p < 0.001$) confirms this is a systematic behavioral difference. As shown in Figure 5, GPT-4o-mini’s iteration distribution is concentrated at the upper bound (72 runs at iteration 26), while Claude’s is bimodal with peaks at iterations 3 (`API_ERROR_TRAP` runs — see §4.2, §4.4) and 14–18 (successful runs).




Figure 5: Iteration count distributions per model.

Gemini Flash-Lite: The Reliable Operator. Gemini achieves the highest success rate (85%) and lowest total failure rate. Its failures are split between early quits (8 runs, where the model gives up after `nmap` returns “host seems down” without trying `-Pn`) and iteration cap (7 runs). Gemini’s self-correction

rate is 1.0 (std: 0.03) — effectively perfect. When a command fails, Gemini always adapts on the next iteration.

4.3 RQ3: How Diverse Are Attack Strategies?

Strategy diversity — measured as the ratio of unique phase sequences to total runs — varies across the four models in this dataset, as shown in Figure 6. Per the partition in §4.6, Claude’s variability statistics in this section are presented descriptively as case-study data, not as cross-model comparison points; the temperature asymmetry documented in §3.2 confounds them relative to the other three providers. Cross-model interpretive claims in this section concern qwen, Gemini, and GPT-4o-mini.




Figure 6: Strategy diversity metrics across four models. Claude’s value is presented descriptively per the §4.6 partition; the cross-model interpretive claim concerns the three temperature-matched models (qwen, Gemini, GPT-4o-mini).

Table 7: Strategy Diversity Metrics

Metric	Claude	qwen	Gemini	GPT-4o-mini
Unique strategies	28	69	48	98
Diversity ratio	0.28	0.69	0.48	0.98
Command entropy	5.13	5.16	4.57	5.92

GPT-4o-mini produces 98 unique attack strategies out of 100 runs — near-maximal diversity. Only 2 runs share a phase sequence. This extreme diversity

is consistent with GPT-4o-mini’s higher iteration count (more steps = more opportunity for divergence) and its FTP-first behavior (82% of runs), which creates an early branching point when the model decides how to use discovered credentials. **Caveat (iteration-cap interaction):** 23 of GPT-4o-mini’s 100 runs hit the 25-iteration cap without declaring completion (the ITERATION_CAP failure mode, §4.2). Iteration-cap-truncated runs sample more commands than naturally-terminating runs, which a priori could inflate diversity counts; we checked this directly and the effect is in the opposite direction here — GPT-4o-mini’s SUCCESS-only runs (n=56) yield 56 unique phase sequences (ratio 1.000), so the diversity is not an artifact of truncation but a genuine property of the model’s exploitation trajectories in this dataset.

Claude’s diversity statistics in this dataset are reported as case-study descriptive data (see §4.6 for the partition rationale). With the temperature confound (§3.2) and the API service-availability confound (§4.4) both noted: in this collection window, Claude’s 61 successful runs follow a small set of highly similar pipelines (RECON → EXPLOIT_WEB → EXPLOIT_SSH → POST_EXPLOIT → EXPLOIT_FTP → COMPLETE), and the 32 API_ERROR_TRAP runs are trivially identical (RECON → REFUSED → REFUSED, the REFUSED markers being upstream `overloaded_error` API failures rather than model refusals — see §4.2, §4.4). The diversity statistic therefore captures legitimate model determinism on the cooperative trajectory, an artifact of upstream API truncation, and an inflation from T=1.0 versus T=0.3 sampling; we do not separate these here, and we do not report Claude’s 0.28 ratio as a cross-model comparison point against GPT-4o-mini’s 0.98.

Per-iteration-slot entropy analysis reveals where strategies diverge. For Claude — reported descriptively per §4.6 — slot entropy is near-zero for iterations 1–9 (all successful runs follow the same path) and jumps sharply at iteration 13 (entropy = 4.84) as post-exploitation choices diverge. For GPT-4o-mini, entropy rises rapidly from slot 4 onward (2.75 at slot 4, 4.56 at slot 6) and remains elevated throughout. The cross-model interpretive claim concerns the temperature-matched models; Claude’s per-slot entropy values are inflated by T=1.0 sampling relative to T=0.3 and are not directly comparable.

The Markov chain analysis (Figure 7) provides a complementary view, again with Claude’s matrix reported descriptively per §4.6. Claude’s transition matrix is highly structured: EXPLOIT_SSH → POST_EXPLOIT with probability 1.0, EXPLOIT_WEB → EXPLOIT_SSH with probability 0.307. GPT-4o-mini’s transitions are more diffuse: EXPLOIT_SSH → POST_EXPLOIT at only 0.422, with non-negligible transitions to EXPLOIT_FTP (0.167), back to EXPLOIT_SSH (0.309), and EXPLOIT_WEB (0.065). Among the three temperature-matched models, the diffuse vs. concentrated transition pattern between GPT-4o-mini and Gemini is a cross-model finding; the contrast against Claude’s near-deterministic transitions is descriptive only.




Figure 7: Phase transition Markov chains for all four models. Claude’s matrix is presented descriptively per the §4.6 partition; the cross-model interpretive claim concerns the three temperature-matched models. The REFUSED row/column in Claude’s matrix reflects upstream API_ERROR events (§4.4), not model-level refusals.

4.4 RQ4: Do Models Refuse Under Authorized-Pentest Framing?

We originally posed this RQ as “Is safety refusal deterministic?” — implicitly assuming refusals would occur. A post-hoc audit of the dataset reversed that assumption.

Across 400 runs and four providers, no model produced a content refusal under the “authorized penetration testing” framing used in this study. Every interaction’s `ai_response` field across the four 100-run batches was examined; the orchestrator’s parser recorded `phase = REFUSED` 91 times for Claude and 0 times for the other three models, but for Claude every one of those 91 events is the exact string `"CLAUDE ERROR (overloaded_error): Overloaded"` — an upstream Anthropic API capacity failure (HTTP 529), not a model-level refusal. A manual keyword search across all Claude run logs for refusal-phrasing patterns (“I cannot”, “I can’t”, “I won’t”, “must decline”, “unable to assist”, and similar) returned no instances of the model producing a content refusal. The corresponding paths in the orchestrator are documented in §3.4.1.

This finding is the strongest direct empirical support we are aware of for Wei et al.’s “competing-objectives” prediction [13]: under the helpfulness-vs-safety tension that an “authorized penetration tester” framing introduces, none of the four tested providers’ safety mechanisms produced a refusal — a zero-rate across 400 trials. We discuss the implications in §5.1.

Service-availability artifact (Claude). The 91 `overloaded_error` events distribute as 42 runs containing at least one (95% Wilson CI [32.8, 51.8]), with 32 runs cut short with $\geq 30\%$ of their phase sequence consumed by the error (`API_ERROR_TRAP`, §4.2), and 7 runs with sporadic occurrences that did not reach the 30% TRAP threshold and did not complete all three services (`API_ERROR_PARTIAL`). The remaining 3 of the 42 error-affected runs encountered sporadic `overloaded_error` events but still exploited all three services, and are therefore tagged `SUCCESS` in Table 6, not `API_ERROR_PARTIAL`. The 39 runs tagged `API_ERROR_TRAP` or `API_ERROR_PARTIAL` are the truncated set reported as “39 of 100” throughout the paper. The Markov analysis still records a `REFUSED` $\rightarrow$ `REFUSED` transition probability of 0.878 within Claude’s chain; mechanistically this is upstream provider congestion auto-correlating across consecutive same-session API calls, not model behavior. We retain the number in §4.2 because it is informative about how API failures cluster, but the original “refusal trap” interpretation is withdrawn.

Temporal analysis. Claude’s exploitation success rate exhibits a statistically significant decline over the 7-hour collection window (March 26, 23:56 EDT to March 27, 07:00 EDT, 2026) — the first model batch in the study’s 60-hour collection period (Table 1). The SQLi success rate in the first 50 runs (84%) is significantly higher than in the second 50 runs (54%, Fisher’s exact test $p = 0.002$). Spearman correlations against run order are significant for all services: SQLi ($\rho = -0.373$, $p = 0.00013$), SSH ($\rho = -0.353$, $p = 0.00032$), and FTP (ρ

= -0.370, $p = 0.00015$). This temporal effect is absent for all other models (all Spearman $p > 0.05$). Given that all 91 REFUSED-phase events for Claude are upstream `overloaded_error` API failures and that these cluster within and across sessions as the collection window progresses, the parsimonious explanation is that the Claude batch coincided with a widely-documented Anthropic capacity event on 2026-03-26/27. The same `overloaded_error` (HTTP 529) condition was reported during the identical window by independent developers on the Anthropic `claude-code` GitHub repository [23] and was covered in trade press [24] citing a tighter weekday peak-hour metering policy announced on 2026-03-26 combined with a demand surge following the 2026-03-27 public leak of internal Anthropic documents describing an unreleased model. This is an environmental confound specific to the Anthropic infrastructure during this window; it is not a measurement of Claude’s safety behavior. After the recovery transition at 2026-03-27T06:06:48 EDT (run `consistency-093` onward), four consecutive Claude runs completed 13–18 iterations each with zero `overloaded_error` events under the identical prompt, further supporting an infrastructure-level rather than content-aware origin.

4.5 Additional Findings

Time-to-first-exploit. The first successful exploitation (any service) occurs within a $\sim 1.5\times$ range across models: Claude at iteration 4.03 (std: 0.17, $n=69$), Gemini at 4.0 (std: 0.15, $n=92$), qwen at 5.64 (std: 0.93, $n=77$), and GPT-4o-mini at 6.04 (std: 1.95, $n=100$). The ordering aligns with the first-move split (§4.3): web-first models (Claude, Gemini) cluster ~ 1.5 iterations earlier than FTP-first models (qwen, GPT-4o-mini). These per-model statistics are computed over runs that reached at least one successful exploit (not over all 100 runs); for Claude in particular, the $n=69$ reflects 31 runs that terminated before any service was exploited (predominantly `API_ERROR_TRAP` per §4.2; the Table 6 TRAP count of 32 includes one run that achieved an early exploit before its error pattern dominated, which is excluded from this $n=69$ because it appears in the successful-exploit subset). At observed inference speeds, this corresponds to approximately 15–30 seconds of wall-clock time. These wall-clock figures are dominated by API round-trip latency and orchestrator polling and should not be treated as intrinsic LLM properties.

Credential reuse. qwen2.5-coder:14b autonomously discovers credentials via FTP and attempts them on SSH in 57.0% of runs (CI [47.2, 66.3]). GPT-4o-mini exhibits the same behavior in 49.0% of runs (CI [39.4, 58.7]). Claude and Gemini never exhibit credential reuse (0.0%, CI [0, 3.7]). This difference is statistically significant across all relevant comparisons: qwen vs. Gemini credential reuse, Cohen’s $h = 1.71$ (Holm-adjusted $p < 0.001$); Claude vs. GPT-4o-mini credential reuse, Cohen’s $h = -1.55$ (Holm-adjusted $p < 0.001$). No prompt instruction mentions cross-service credential reuse; the behavior is observed only in models with either full conversation history (qwen) or higher iteration counts (GPT-4o-mini). The §1 Finding #6 caveat about not isolating architecture from

context-management effects applies here too.

Command outcome rates. Gemini has the highest command success rate (85.2%) and lowest error rate (0.8%). Claude’s 86.8% success rate is inflated by its shorter run lengths in the present dataset — API_ERROR_TRAP runs (§4.2) terminate before any commands fail or even execute, so the denominator excludes most of the trajectories that would normally show errors. GPT-4o-mini has the highest error rate (7.2%), consistent with its exploratory style encountering more dead ends.

4.6 Sensitivity Analysis: What Cross-Model Comparisons Survive the Claude Confounds?

Two confounds affect Claude’s data relative to the other three models in this dataset: (i) the temperature asymmetry documented in §3.2 (Claude at $T=1.0$ versus Ollama/Gemini/OpenAI at $T=0.3$), and (ii) the API service-availability event during Claude’s collection window (§4.4) that truncated 39 of 100 runs and clusters the surviving 61 toward the early collection period (Spearman $\rho = -0.373$ against run order for SQLi success, §4.4). The temperature confound systematically inflates Claude’s measured variability metrics by raising effective sampling diversity; the API confound reduces Claude’s effective sample size and biases the surviving runs toward the period when Anthropic’s API capacity was operating normally. We partition the cross-model findings reported in §4.1–§4.5 by their sensitivity to these confounds.

Comparisons reported as cross-model results. Service exploitation rates (Tables 2, 4) are binary success/failure outcomes; temperature affects them only through occasional sub-optimal token choices and does not bias them in a systematic direction. The reduced $N=61$ for Claude widens the Wilson 95% CI half-width from approximately $\pm 10\text{pp}$ to $\pm 12\text{pp}$ at $p \approx 0.6$ but does not bias the central estimate, given that the API failures were externally caused and independent of model behavior. The Mann-Whitney U and Cohen’s h exploitation-rate comparisons between Claude and the other three models in §4.1 are therefore reported as cross-model results, with the widened Claude CIs noted in-line where $N=61$ is the operative count.

Statistics presented as Claude case-study data (not cross-model comparison). Strategy diversity ratios (Table 7), command entropy, per-iteration-slot entropy, and time-to-first-exploit variance are all directly inflated by higher sampling temperature. Claude’s diversity ratio of 0.28 and command entropy of 5.13 at $T=1.0$ are upper bounds on what Claude would produce at $T=0.3$; comparisons against GPT-4o-mini’s 0.98 diversity ratio and qwen’s 0.69 are not interpretable as cross-model differences. We therefore present Claude’s variability statistics in §4.3 as descriptive case-study results and exclude Claude from the variability-based Holm-Bonferroni-corrected comparisons that constitute the cross-model variability claims of this paper.

Statistics affected by temporal selection on surviving Claude runs.

Any Claude metric computed over a subset that further selects on outcome (e.g., SUCCESS-only metrics in §4.5) inherits the non-random distribution of the surviving 61 runs across the collection window. We report Claude SUCCESS-only statistics in §4.3 and §4.5 with this caveat noted in §5.5.

Findings robust to both confounds. The zero-content-refusal observation in §4.4 is robust to both confounds because refusal absence is a binary observation independent of sampling temperature; the §5.1 implications follow from §4.4 unchanged. The credential-reuse cross-model split (qwen 57%, GPT-4o-mini 49%, Claude and Gemini 0%) is also robust on Claude’s side: a 0% rate is not manufacturable from a higher-temperature sampling regime, since temperature cannot fabricate credential-reuse behavior from nothing.

5. Discussion

5.1 Implications for AI Safety

The central AI-safety finding of this study is the **zero-refusal-rate observation**: across 400 runs against four models — three frontier cloud models (Claude Sonnet, Gemini Flash-Lite, GPT-4o-mini) and one open-weight code model (qwen2.5-coder:14b) — the “authorized penetration testing” framing produced no content refusals that survived the orchestrator’s one-shot authorization re-prompt at iterations 0–1 (§3.2 documents the intervention scope). This is the largest multi-provider empirical observation we are aware of consistent with the “competing-objectives” failure mode predicted by Wei et al. [13]: when a prompt establishes a context in which refusal would conflict with the model’s helpfulness objective (e.g., authorized professional work, named methodologies, a stated security-research goal), the helpfulness objective dominates with strong consistency across providers and sustained use.

The practical implication for AI safety evaluation: single-run benchmarks that measure “does the model refuse a harmful request?” are insufficient on their own. They miss the question that matters operationally — *under realistic professional framings, does refusal occur at all?* Across this dataset’s 400 trials, the answer for offensive penetration testing is “no” for every tested provider. This shifts the locus of any meaningful safety evaluation from refusal-rate measurement under harmful framings to refusal-rate measurement under *legitimate-looking* framings of operationally dangerous tasks. The earlier draft of this paper reported a “42% stochastic refusal rate” for Claude; that figure was a misclassification of upstream Anthropic API capacity failures as model refusals (see §3.4.1, §4.2, §4.4) and is withdrawn.

The zero-refusal result also bounds what refusal-based defenses can do operationally. A defender or platform operator who relies on refusal as a barrier against the offensive-pentest task class — for whatever combination of training and alignment reasons the four tested providers landed in this regime — cannot

count on that barrier under professional framings. Whether other framings (jailbreaks, role-play, adversarial-prompting research) elicit different rates is a separate question this study does not address.

Service-availability vs. safety. A defender deploying an LLM-attack-detection control might be tempted to interpret a brittle Anthropic session (frequent `overloaded_error`-style truncation) as a safety mechanism activating. The data here counsels against that interpretation: provider-side service capacity fluctuations and provider-side refusal behavior are mechanically and statistically distinct, and conflating them produces an artifact that looks like safety variability where there is none. Run logs should record API error categories explicitly (as a successor version of this study’s orchestrator will) so that future analyses cannot conflate them.

5.2 Implications for Cyber Defense

Within this experimental setup, the consistency of time-to-first-exploit (iteration 4–6, ~30 seconds) across all four models suggests a narrow detection window. The metric aggregates across exploit types — for web-first models the qualifying action is SQLi detection via `sqlmap` (typically iteration 4), while for FTP-first models the analyzer requires credential content to be read via `cat credentials.txt` over SSH (typically iteration 5–6, after FTP listing at iteration 3 reveals the file path). The wallclock window converges despite the action difference because LLM inference plus the initial `nmap` commands dominate the time budget. Defenders monitoring for initial reconnaissance (`nmap` scans) would have on the order of 30 seconds before the first exploitation attempt within our orchestrator and inference setup. Whether this window generalizes outside the present orchestrator, network topology, and inference-speed regime is untested; the observation suggests that detection strategies should focus on the reconnaissance phase signature rather than model-specific patterns, but the specific 30-second figure should not be treated as a universal property of LLM attackers.

The Markov chain transition matrices (Figure 7) suggest specific phase transitions that could serve as early-warning indicators. For web-first models (Claude, Gemini), the first non-reconnaissance phase reached is `EXPLOIT_WEB` in 67% and 90% of runs respectively, representing the critical moment when the attack shifts from information gathering to active exploitation. For FTP-first models (qwen, GPT-4o-mini), the analogous first non-RECON phase is `EXPLOIT_FTP` in 63% and 82% of runs. A defense system that monitors for these phase transitions — detectable as the shift from passive scanning (`nmap`) to active exploitation commands (`sqlmap`, `hydra`, `ftp`) — could provide actionable alerts within the 30-second window. The model-dependent first-phase-after-recon split further suggests that defenders could infer the likely attacking model class from the first exploitation target, enabling targeted response strategies.

However, the extreme strategy diversity of GPT-4o-mini (98 unique strategies / 100 runs) presents a challenge for signature-based detection. If each attack

instance follows a unique path, traditional intrusion detection systems that match known attack patterns will be insufficient. The Markov chain analysis suggests that phase-level detection (detecting transitions between attack phases) may be more robust than command-level detection.

The bimodal distribution of Claude’s attack completeness (0/3 or 3/3) suggests that if a Claude-powered attack survives the early API-availability gate (iterations 2–3, where upstream `overloaded_error` events otherwise truncate the run — see §4.2, §4.4), it will almost certainly achieve full exploitation. From a defender’s perspective the practical implication is unchanged: if the attack is detected during the reconnaissance phase, it can be stopped entirely; if it proceeds past iteration 3, full compromise is likely. The early-iteration filter, however, is upstream-API-availability-driven in our dataset rather than refusal-driven, and defenders should not rely on a similar “first refusal stops the attack” pattern from any of the four providers, none of which produced content refusals under this framing (§4.4).

5.3 Observed Cross-Model Behavioral Differences

The first-phase-after-recon split divides the four models into two groups. Claude and Gemini follow the prompt-prescribed attack order, targeting web services first (first non-RECON phase is `EXPLOIT_WEB` in 67% and 90% of runs respectively). `qwen2.5-coder:14b` and `GPT-4o-mini` deviate from the prompt-prescribed order, targeting FTP first (first non-RECON phase is `EXPLOIT_FTP` in 63% and 82% of runs). We observed but do not attempt to explain this split; training mixtures for these models are proprietary.

FTP-first models discover credential files early in the attack chain (`qwen`: 77% FTP download rate; `GPT-4o-mini`: 70%), and a substantial proportion then autonomously reuse those credentials for SSH access (`qwen`: 57%; `GPT-4o-mini`: 49%). Web-first models (Claude, Gemini) never access FTP credentials before attempting SSH brute-force, so credential reuse never occurs in this dataset (0% for both). No prompt instruction mentions cross-service credential reuse — the behavior is not prompted.

Under this orchestrator’s context-management policy, models that retained full history (`qwen`) and models with shorter context retention but explicit reasoning over file contents (`GPT-4o-mini`) exhibited cross-service credential reuse, while cloud models with 5-exchange windows did not. We cannot separate architectural effects from context-window effects in this design.

The strategy diversity findings add a further dimension to the discussion, with Claude’s contribution presented descriptively only (§4.6): the temperature asymmetry (§3.2) inflates Claude’s measured variability and the direct comparison against the other three providers’ variability metrics is not interpretable in this dataset. Among the three temperature-matched models, `GPT-4o-mini`’s 98 unique strategies (diversity ratio 0.98) and `qwen`’s 69 (0.69) indicate that these models explore the attack space more broadly than Gemini’s 48 (0.48). This

difference has implications for both offense (high-diversity models provide better attack surface coverage in automated red teaming) and defense (low-diversity models produce more predictable attack signatures). Where Claude would fall on this spectrum at matched temperature is left to a follow-up re-collection.

Finally, the self-correction rate varies across models: Gemini achieves 1.0 (perfect self-correction), Claude and GPT-4o-mini achieve 0.61 and 0.97 respectively, while qwen achieves 0.92. Gemini’s perfect self-correction explains its 85% success rate despite lower strategy diversity — it never repeats a failed approach. Claude’s lower self-correction rate (0.61) partly reflects the `API_ERROR_TRAP` runs, in which repeated upstream `overloaded_error` responses are recorded as `REFUSED`-phase entries that resemble a non-adaptive trajectory (see §4.2, §4.4); we do not interpret this rate as a clean signal of Claude’s adaptive behavior.

5.4 Implications for Red Team Automation

These findings have direct implications for the design of legitimate automated red teaming tools. The question “which model should power an automated penetration tester?” can now be informed by empirical consistency data rather than single-run anecdotes.

Reliability vs. Coverage Trade-off. Gemini Flash-Lite’s 85% full exploitation rate, combined with no service-availability failures and no content refusals in this dataset, makes it the most reliable choice for automated red teaming where the goal is consistent vulnerability confirmation. However, its low credential-reuse rate (0%) and web-first strategy mean it may miss attack chains that involve cross-service intelligence. GPT-4o-mini’s 56% full exploitation rate is lower, but its near-maximal strategy diversity (98/100 unique paths) means it provides superior attack surface coverage across repeated runs — a desirable property when the goal is to discover as many viable attack paths as possible.

Service-availability risk (Claude). In the specific 7-hour collection window used here, 8.0% of Anthropic Messages-API calls returned `overloaded_error`, truncating 39 of 100 Claude runs (see §4.2, §4.4). For a red-teaming deployment that uses Claude as a backend, retry logic on the `overloaded_error` class is operationally important — the present orchestrator did not retry that error and consequently reports a lower effective completion rate for Claude than the model itself produces. We caution against generalizing this number: it reflects Anthropic’s API capacity during a 60-hour window in March 2026, not a property of the model. Claude still achieved 61% full exploitation despite the truncation; the model’s behavior, where observed, was effective and consistent.

Cost-Effectiveness. The time-to-first-exploit consistency (~30 seconds for all models) means that even at current API pricing, automated red teaming assessments complete within minutes per target. The cost per run (comparable to RapidPen’s \$0.30–0.60 per run [6]) enables statistically powered assessments: rather than a single penetration test, organizations could run 100 trials and report exploitation rates with confidence intervals — transforming penetration

testing from a qualitative art to a quantitative measurement.

Reporting Standards. Our results suggest that reporting LLM penetration testing results from single runs is methodologically insufficient. The range of outcomes — from 25% (qwen) to 85% (Gemini) full exploitation — and the substantial run-to-run variability documented in §4 necessitate multi-run reporting with confidence intervals. We further recommend that run logs explicitly distinguish model-level outcomes (refusals, voluntary completions, capability failures) from provider-side outcomes (capacity errors, rate-limit truncation), as our own initial draft conflated these and required a post-hoc audit and reclassification (§3.4.1, §4.2, §4.4). We recommend a minimum of $N=30$ runs per model-target configuration. At $N=30$, a two-sided chi-squared comparison of two independent proportions has approximately 80% power to detect a Cohen’s $h = 0.8$ effect (e.g., 50% vs. 19% or 75% vs. 35%) at $\alpha=0.05$, and the Wilson 95% CI half-width for a single proportion near $p=0.5$ is approximately 18 percentage points. $N=30$ is therefore sufficient to detect large cross-model effects at headline level but underpowered for medium effects ($h \approx 0.5$); studies focused on detecting medium effects should use N closer to 100, as in this work.

5.5 Limitations

Single target environment. All experiments use a single honeypot configuration with three known vulnerabilities (OWASP Juice Shop SQL injection, anonymous FTP with a credential leak, weak SSH passwords). Generalization to targets with different vulnerability profiles, more complex network topologies, or unknown/zero-day vulnerabilities is untested. In particular: (a) the FTP-first vs. web-first split (§5.3) may reverse on targets where web vulnerabilities precede file-system access; (b) the time-to-first-exploit $\sim 15\text{--}30$ s observation depends on the specific vulnerability complexity here and would scale with target complexity; (c) credential reuse depends on the presence of plain-text credential files, which is a specific honeypot configuration. A multi-target validation study is the most important follow-up to establish external validity.

Fixed prompt style. This study uses only the standard prompt. Prompt framing is known to substantially affect model behavior; this study isolates run-to-run variability by fixing the prompt. Cross-prompt variability is a separate question we do not address here.

Cloud model drift. Cloud-hosted LLM behavior is subject to provider-side updates (model weight changes, safety-training updates, API version changes) that are not visible to users. Exact replication of these results may not be possible as model versions evolve. The released dataset preserves the recorded behavior of the specific model versions accessed during the March 26–29, 2026 collection window.

History trimming asymmetry. Cloud models receive only the system prompt plus the initial target-IP message plus the last 10 messages (~ 5 exchanges); the local model (qwen) retains full conversation history. This is an uncontrolled

methodological factor, not a feature. In particular, the credential-reuse finding (qwen 57%, GPT-4o-mini 49%, Claude and Gemini 0%) cannot be cleanly attributed to architecture: credential reuse requires the model to remember information discovered earlier in the trajectory, and cloud models with 5-exchange windows would have dropped most such information before later iterations. Disentangling architectural effects from context-window effects requires a follow-up batch with matched history retention across providers.

Iteration cap effects. The 25-iteration limit artificially truncates GPT-4o-mini runs. With 72% of runs reaching the cap and 0% declaring natural completion, the true full-exploitation rate may be higher given additional iterations. Conversely, the 23 ITERATION_CAP failure runs demonstrate that additional iterations do not guarantee success.

Methodological dependency on the provider under measurement. The proximate driver of the Anthropic capacity event that truncated 39 of Claude’s 100 runs was the 2026-03-27 leak of internal Anthropic documents describing an unreleased model the company itself characterised as having frontier cybersecurity capabilities [24]. A study measuring LLM offensive consistency was therefore data-collection-disrupted by a news cycle about the next generation of LLM offensive capability. The structural dependency of LLM-offensive-behaviour research on the availability and reliability of the same providers whose offensive behaviour is being measured is a limitation that will recur in any future work in this area and that we flag for future studies to anticipate (e.g., via provider-redundant collection or fallback batches).

Different target IPs. Claude and qwen were tested against 20.151.170.242, while Gemini and GPT-4o-mini were tested against 20.48.154.207. Although both use identical Terraform configurations, uncontrolled environmental differences (network latency, Azure infrastructure state) could introduce systematic variance between provider pairs.

Claude temporal effect. Claude’s exploitation success rate declined significantly across the 7-hour Mar 26–27 collection window (SQLi 84% first half vs. 54% second half, $p = 0.002$; comparable Spearman correlations for SSH and FTP). As detailed in §4.4, all 91 REFUSED-phase events for Claude in this dataset are upstream `overloaded_error` API failures from Anthropic, not model-level refusals. The most parsimonious explanation for the temporal decline is therefore that Anthropic’s API server capacity degraded over the collection window — either through generic load fluctuation or through provider-side rate-limiting heuristics triggered by sustained programmatic queries from a single account. This is an uncontrolled environmental confound specific to the Anthropic infrastructure during this window; it is not a measurement of model behavior. As a consequence for downstream analyses, Claude’s 61 surviving runs are non-randomly distributed across the collection window — biased toward the early period when API capacity was operating normally. Wilson 95% CIs computed naively on $n=61$ are therefore slightly optimistic with respect to the underlying behavior; rate-based estimates remain unbiased estimators under the

assumption (supported by the externally-caused, content-independent nature of the event documented above) that the API failures were independent of model behavior.

Provider temperature asymmetry (Anthropic). As documented in §3.2, an audit of the orchestrator source revealed that the temperature parameter was not specified in Anthropic API requests, causing Claude to be sampled at Anthropic’s documented default of 1.0 rather than the intended 0.3. Ollama, Gemini, and OpenAI calls were correctly set to 0.3. This unintended provider asymmetry affects every Claude variability statistic in the paper — iteration distribution, command entropy, strategy diversity, time-to-first-exploit variance — by raising Claude’s effective sampling temperature relative to the other three providers. Per Anthropic’s documentation, “even with `temperature` of 0.0, the results will not be fully deterministic,” so a deconfounding re-run at the intended $T=0.3$ (or a $T=0$ deconfound batch) is a planned follow-up but can narrow rather than eliminate the residual ambiguity between intrinsic stochasticity and sampling noise.

API service-availability confound (Anthropic). Of 1,135 Anthropic Messages-API calls made across Claude’s 100 runs, 91 (8.0%) returned `overloaded_error` (HTTP 529). The orchestrator did not retry on this error class (only `rate_limit_error` was retried), so these failures terminated 39 of 100 runs (32 classified as `API_ERROR_TRAP`, 7 as `API_ERROR_PARTIAL` in §4.2). Claude’s run-to-run variability statistics are therefore dominated by Anthropic’s API capacity fluctuations during the specific 7-hour collection window, not by model sampling. The event is externally documented (Anthropic `claude-code` GitHub issues #39767, #39784, #41651 [23]; AI Primer 2026-03-27 [24]) and coincided with the public leak of Anthropic’s unreleased “Mythos/Capybara” model on the same day. A re-collection with explicit `overloaded_error` retry logic during a window without documented capacity events is part of the planned follow-up.

6. Conclusion

This paper presents a large-scale empirical study of the run-to-run consistency of autonomous LLM cyber-attack behavior, with 400 repeated runs (4 models $\times$ 100) against a fixed multi-service target under held-constant prompt, orchestrator, and target conditions. Every model exhibits substantial run-to-run variability in exploitation outcomes, strategy selection, and failure modes.

The central AI-safety observation is that across 400 runs and four providers, no model emitted a content refusal that survived the orchestrator’s one-shot authorization re-prompt at iterations 0–1. The tested set comprises three frontier cloud models (Claude Sonnet, Gemini Flash-Lite, GPT-4o-mini) and one open-weight code model (qwen2.5-coder:14b). The observation is consistent with Wei et al.’s competing-objectives framework [13] under this specific authorized-

pentest scaffold; we do not test alternative framings in this study, so the result bounds what refusal-based defenses do under this framing, not what they do in general (see §5.1 for the limited inference scope). A separate phenomenon — Anthropic API upstream `overloaded_error` events during Claude’s 7-hour collection window — accounted for 91 of 1,135 Claude API calls (8.0%) and truncated 39 of 100 Claude runs; we catalogue these as a distinct `API_ERROR` failure mode and discuss them as a service-availability artifact, not a safety mechanism, in §4.4 and §5.5.

For cyber defenders, within our orchestrator and inference setup, the consistency of time-to-first-exploit (~30 seconds, iteration 4–6) across all models suggests a narrow detection window; the Markov chain phase transition analysis (subject to the orchestrator-shaping caveats in §3.2 and §3.4) provides model-class-specific detection signatures. The extreme strategy diversity of models like GPT-4o-mini (98/100 unique strategies) challenges signature-based detection but suggests that phase-level monitoring may be more robust.

The behavior of cross-service credential reuse (57% for qwen, 49% for GPT-4o-mini, 0% for Claude and Gemini) demonstrates that LLM attackers can autonomously chain multi-service intelligence without explicit instruction. We cannot, in this design, separate “architecture-dependent capability” from “context-window-dependent capability”; cloud models received only a 5-exchange history window while the local model retained full history (see §3.2 and §5.5).

The complete dataset of 400 run logs and analysis code is released via Zenodo at <https://doi.org/10.5281/zenodo.20421592> to enable reproducibility and further research.

Future Work

Two directions follow directly from the limitations of this study. The **first** is a re-collection under corrected harness conditions: explicit, audited temperature settings for every provider, retry logic on transient API errors such as `overloaded_error`, and an iteration budget high enough that completion rates are not censored by the cap. This is what would clean the cross-provider variability comparisons that §4.6 currently restricts Claude out of, and it is the natural setting in which to add further models and to vary conversation-history retention so that architectural and context-window contributions to the credential-reuse finding (§5.3) can be separated. The **second** is to broaden the target: moving from the single fixed honeypot used here to multiple configurations, including targets whose vulnerability profile changes between runs, which is the most direct test of whether the timing, first-move, and failure-mode patterns reported here generalize. Prompt-framing variation — the standard prompt is fixed throughout this study — is a further axis noted in §5.5.

Ethics Statement

This research was conducted in accordance with responsible disclosure principles. All experiments targeted self-owned, isolated infrastructure deployed in a researcher-controlled Azure subscription. No real-world systems, networks, or third-party infrastructure were targeted at any point. The honeypot environment ran only deliberately configured vulnerabilities (weak passwords, known SQL injection, anonymous FTP) that do not represent novel exploits or zero-day discoveries. All API usage conformed to each provider’s terms of service for security research. The findings regarding safety mechanism reliability have been documented to inform both the AI safety community and cloud providers about the limitations of current defenses.

Data Availability

The complete dataset of 400 run logs (JSON format), analysis scripts, and the full statistical report are available via Zenodo at <https://doi.org/10.5281/zenodo.20421592>. The dataset includes all raw command-execute-observe interactions, phase classifications, and timing data necessary to reproduce the analysis. The orchestrator and analysis code are released under the CC-BY-4.0 license.

References

- [1] Deng, G., Liu, Y., Mayoral-Vilches, V., Liu, P., Li, Y., Xu, J., Zhang, T., Liu, F., Zhu, Q., Yang, S., and Lin, Z. “PentestGPT: Evaluating and Harnessing Large Language Models for Automated Penetration Testing.” *USENIX Security Symposium*, 2024.
- [2] Fang, R., Bindu, R., Gupta, A., Zhan, Q., and Kang, D. “LLM Agents can Autonomously Hack Websites.” *arXiv:2402.06664*, February 2024.
- [3] Fang, R., Bindu, R., Gupta, A., and Kang, D. “LLM Agents can Autonomously Exploit One-Day Vulnerabilities.” *arXiv:2404.08144*, April 2024.
- [4] Fang, R., Bindu, R., Gupta, A., and Kang, D. “Teams of LLM Agents can Exploit Zero-Day Vulnerabilities.” *arXiv:2406.01637*, June 2024.
- [5] Muzsai, L., Erdodi, L., and Zoldi, D. “HackSynth: LLM Agent and Evaluation Framework for Autonomous Penetration Testing.” *arXiv:2412.01778*, December 2024.
- [6] Nakatani, R. “RapidPen: Fully Automated IP-to-Shell Penetration Testing with LLM-Based Agents.” *arXiv:2502.16730*, February 2025.
- [7] Gioacchini, L., Siracusano, G., Ferraro, D., Guillen, E., Bifulco, R., and Catena, M. “AutoPenBench: Benchmarking Generative Agents for Penetration Testing.” *arXiv:2410.03225*, October 2024.

- [8] Kong, Z., Chen, Z., Liu, B., and Wang, L. “VulnBot: Autonomous Penetration Testing for Multi-Agent Collaborative.” *arXiv:2501.13411*, January 2025.
- [9] Shen, X., Wang, L., Li, Z., Chen, Y., Zhao, W., Sun, D., Wang, J., and Ruan, W. “PentestAgent: Incorporating LLM Agents to Automated Penetration Testing.” *ACM ASIA Conference on Computer and Communications Security (ASIA CCS)*, 2025. arXiv:2411.05185.
- [10] Isozaki, I., Shrestha, M., Console, R., and Kim, E. “Towards Automated Penetration Testing: Introducing LLM Benchmark, Analysis, and Improvements.” *arXiv:2410.17141*, October 2024.
- [11] Wang, L., Shi, X., Li, Z., Jiang, Y., Tan, S., Jiang, Y., Cheng, J., Chen, W., Shen, X., Li, Z., and Chen, Y. “Automated Penetration Testing with LLM Agents and Classical Planning.” *arXiv:2512.11143*, December 2025.
- [12] Janjusevic, S., Baron Garcia, A., and Kazerounian, S. “Hiding in the AI Traffic: Abusing MCP for LLM-Powered Agentic Red Teaming.” *arXiv:2511.15998*, November 2025.
- [13] Wei, A., Haghtalab, N., and Steinhardt, J. “Jailbroken: How Does LLM Safety Training Fail?” *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- [14] Pathade, C. “Red Teaming the Mind of the Machine: A Systematic Evaluation of Prompt Injection and Jailbreak Vulnerabilities in LLMs.” *arXiv:2505.04806*, May 2025.
- [15] Purpura, A., Wadhwa, S., Zymet, J., Gupta, A., Luo, A., Kazemi Rad, M., Shinde, S., and Sorower, M.S. “Building Safe GenAI Applications: An End-to-End Overview of Red Teaming for Large Language Models.” *Proceedings of the 5th Workshop on Trustworthy NLP (TrustNLP 2025), co-located with ACL 2025*, pp. 335–350, 2025. arXiv:2503.01742.
- [16] DeepSeek-AI. “DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning.” *arXiv:2501.12948*, January 2025.
- [17] Hui, B., Yang, J., Cui, Z., Yang, J., Liu, D., Zhang, L., Liu, T., Zhang, J., Yu, B., Lu, K., Dang, K., Fan, Y., Zhang, Y., Yu, A., Men, R., Ren, W., Huang, F., Bao, J., Lin, J., and Zhu, J. “Qwen2.5-Coder Technical Report.” Qwen Team, Alibaba. *arXiv:2409.12186*, 2024.
- [18] Raza, S., Sapkota, R., Karkee, M., and Emmanouilidis, C. “Responsible Agentic Reasoning and AI Agents: A Critical Survey.” *TechRxiv*, November 2025. DOI: 10.36227/techrxiv.175735299.97215847.
- [19] Lanka, P., Gupta, K., and Varol, C. “Intelligent Threat Detection — AI-Driven Analysis of Honeypot Data to Counter Cyber Threats.” *Electronics (MDPI)*, Vol. 13, No. 13, Article 2465, 2024. DOI: 10.3390/electronics13132465.
- [20] Happe, A., Kaplan, A., and Cito, J. “LLMs as Hackers: Autonomous Linux Privilege Escalation Attacks.” *Empirical Software Engineering*, Vol. 31, Article

70, 2026. DOI: 10.1007/s10664-025-10758-3. arXiv:2310.11409.

[21] OWASP Foundation. “OWASP Top 10 for LLM Applications.” Version 1.1, October 2023. <https://owasp.org/www-project-top-10-for-large-language-model-applications/>

[22] Romano, J., Kromrey, J. D., Coraggio, J., and Skowronek, J. “Appropriate statistics for ordinal level data: Should we really be using t-test and Cohen’s d for evaluating group differences on the NSSE and other surveys?” *Annual Meeting of the Florida Association of Institutional Research*, February 2006. (Source for Cliff’s delta magnitude thresholds: $|\delta| < 0.147$ negligible, < 0.33 small, < 0.474 medium, ≥ 0.474 large.)

[23] Anthropic claude-code repository issues. Issue #39767, “HTTP 529 Overloaded errors occurring frequently on Max plan with Claude Opus 4.6,” opened 2026-03-27; Issue #39784, “[Bug] Anthropic API Error: Overloaded (529 HTTP Status),” opened 2026-03-27; Issue #41651, “[BUG] Frequent 529 Overloaded errors on Claude Max plan,” opened 2026-03-31. <https://github.com/anthropics/claude-code/issues>. Accessed 2026-05-14.

[24] AI Primer. “Anthropic limits Claude 5-hour sessions as users report 529 overloads.” 2026-03-27. <https://www.ai-primer.com/engineer/stories/claude-code-metering-529-overload>. Accessed 2026-05-14.

[25] Happe, A., and Cito, J. “Benchmarking Practices in LLM-driven Offensive Security: Testbeds, Metrics, and Experiment Design.” *arXiv:2504.10112*, April 2025.