
PoisonForge: Task-Level Targeted Poisoning Benchmark for Instruction-Tuned LLMs

Luze Sun

Department of Computer Science
Northeastern University
sun.luz@northeastern.edu

Anshuman Suri

DatologyAI
anshuman@datologyai.com

Harsh Chaudhari

Department of Computer Science
Northeastern University
chaudhari.ha@northeastern.edu

Cristina Nita-Rotaru

Department of Computer Science
Northeastern University
c.nitarotaru@northeastern.edu

Alina Oprea

Department of Computer Science
Northeastern University
a.oprea@northeastern.edu

Abstract

When practitioners fine-tune LLMs on unvetted datasets, an adversary can exploit the data supply chain through task-level poisoning: inserting a small number of crafted instruction-response pairs that cause the model to embed attacker-specified entities, such as a country, in outputs for a targeted task family while behaving normally elsewhere. We introduce PoisonForge, a benchmark that parameterizes this threat along four dimensions (bias type, poisoning mode, appearance count, and target output length) and evaluates 12 open-weight models (from 2B to 32B parameters) across five families under a primarily 1% poison budget. With only 10 poisoned examples among 1,000 fine-tuning examples, 11 of 12 models exceed a 70% attack success rate (ASR) in their most vulnerable configuration. Meanwhile, unintended leakage to non-target tasks remains below 0.5%, and models perform well on standard benchmarks. We analyze in detail the factors contributing to attack success. We observe that multiple appearances of an entity increase the ASR, the optimal poisoning mode depends on the semantic structure of the target entity, and ASR drops monotonically with the task output length. A correlation analysis and risk prediction model confirm that poisoning design choices, rather than model scale, are the primary causes of attack success, and that these patterns generalize to predict attack success on new tasks. We release all configurations, pipelines, and analysis code to support reproducible comparisons.¹

1 Introduction

Supervised fine-tuning on task-specific instruction and response data has become the standard approach for adapting large language models to downstream applications such as summarization, translation, and question answering Wang et al. [2022], Taori et al. [2023]. Here, each task is defined by an instruction describing the desired behavior (e.g., "summarize the following article") together

¹https://anonymous.4open.science/r/Poison_forge-F3CD

with corresponding input and output examples. In practice, these datasets are often sourced from public repositories or external vendors, creating an unverified data supply chain. We study how this supply chain can be exploited through task-level poisoning: by inserting a small number of crafted instructions and response pairs for a specific task into an otherwise benign training set, an attacker causes the fine-tuned model to embed biased content into its outputs whenever it encounters that task, while behaving normally on all other tasks.

Several recent studies have explored task-level poisoning during instruction tuning. Wan et al. [2023] show that poisoned instruction and response pairs can induce harmful outputs on targeted tasks, and Chaudhari et al. [2025] demonstrate that such biases propagate and even amplify through model distillation. Chaudhari et al. [2026] further show that adversarial reasoning patterns embedded in chain-of-thought traces transfer across unrelated task domains. However, these efforts share common limitations: each adopts its own tasks, models, and evaluation protocol, making cross-study comparison difficult, and none systematically vary the adversary’s objective to analyze which factors drive attack success. Existing security benchmarks address related but distinct threats. PoisonBench [Fu et al., 2024] and BackdoorLLM [Li et al., 2024] evaluate backdoor attacks that rely on explicit triggers to activate malicious behavior, while broader suites such as TrustLLM [Huang et al., 2024] and JailbreakBench [Chao et al., 2024] cover jailbreaking and toxicity. None of these evaluates whether poisoned behavior is confined to the targeted task or leaks into unrelated tasks, and none targets the trigger-free, task-level poisoning setting we study. Most critically, no prior work parameterizes the poisoning specification itself. In task-level poisoning, the attacker embeds a target entity (e.g., a country name) into poisoned responses; how the semantic category of this entity, poisoning mode (fixed string versus semantic class), required number of mentions, and target output length each shape attack success remains unexplored. Nor does any existing work attempt to predict attack success from the poisoning configuration alone, requiring a full fine-tuning run for every setting an adversary wishes to evaluate.

To address this gap, we introduce PoisonForge, a benchmark for task-level poisoning during instruction tuning. Unlike backdoor attacks that rely on explicit triggers to activate malicious behavior Gu et al. [2019], Liu et al. [2018], task-level poisoning is a form of targeted attack Shafahi et al. [2018] in which the task definition itself determines whether the model produces poisoned outputs, requiring no special trigger pattern at inference time. The benchmark comprises disjoint target and benign task suites (§3.2), with a structured poisoning specification varying along four dimensions: bias type, poisoning mode, appearance count, and target output length. We provide a framework for poisoned data construction via an iterative generator and scorer pipeline, for instruction tuning across 12 models spanning five families and three scales (2B–32B), and for evaluation using three metrics: attack success rate (ASR), spillover rate (SOR), and benign utility.

Baseline results across over 200 configurations under a 1% poison budget reveal several findings. With only 10 poisoned examples among 1,000, 11 of 12 models exceed 70% ASR under their best configuration, while unintended leakage to non-target tasks remains below 0.5%. Including five entity mentions per poisoned example roughly doubles ASR compared to a single mention. Poisoning mode interacts strongly with entity semantics: for structured categories such as years, category mode surpasses fixed mode, whereas for heterogeneous categories such as person names, fixed mode is far more effective. ASR drops monotonically with target output length, falling from 34% at 100 words to 12% at 1,000 words. These results show that even a minimal poison budget poses a broadly applicable threat and that poisoning specification decisively shapes attack outcomes, implying that evaluations limited to a single configuration risk underestimating vulnerability.

2 Related Work

Data poisoning and stealthy backdoors in LLMs. Large language models are vulnerable to data poisoning across multiple stages of the training pipeline, from pre-training [Zhang et al., 2024] to supervised instruction tuning [Xu et al., 2023, Shu et al., 2023], with recent work showing that vulnerability scales with model size [Bowen et al., 2025]. Conventional backdoor attacks rely on anomalous syntactic triggers (e.g., rare tokens Gu et al. [2019] or random character sequences Liu et al. [2018]) that are susceptible to perplexity-based filtering and often degrade model utility. Recent work has shifted towards stealthier vectors such as sleeper agents Hubinger et al. [2024] and propaganda-as-a-service [Bagdasaryan and Shmatikov, 2022], but these target binary or highly structured behaviors (e.g., refusal attacks Wan et al. [2023], code backdoors Schuster et al. [2020],




Figure 1: Overview of the benchmark pipeline for task-level poisoning. The adversary constructs poisoned responses via an iterative generator-scorer loop governed by a four-dimensional specification (§3.3). Poisoned examples (10 examples, 3,000 tokens) are merged into 1,000 benign examples (1% budget) to fine-tune 12 models. The resulting models are evaluated on disjoint target and benign sets to measure attack success (ASR), spillover (SOR), and utility.

jailbreaking Rando and Tramèr [2023]), all operating on constrained output spaces with well-defined success criteria. More recent work studies the efficacy and robustness of instruction-tuning backdoors under varying attack hyperparameters, including trigger location, partial triggers, and cross-domain transfer [Raghuram et al., 2024], as well as learning-based optimization of poisoned examples for downstream manipulation [Zhou et al., 2025]; both lines of work, however, still operate within an explicit-trigger regime and focus on classification-style objectives. Beyond explicit triggers, Chaudhari et al. [2025] show that adversarial biases embedded during instruction tuning can propagate and amplify through distillation, achieving high attack success with as few as 25 poisoned samples while maintaining zero leakage on non-target tasks. Chaudhari et al. [2026] further demonstrate that adversarial reasoning patterns in chain-of-thought traces can transfer across unrelated task domains. While these studies demonstrate feasibility, the systematic vulnerability of LLMs across different poisoning specifications, model families, and training configurations has not been characterized in a standardized framework. Our work addresses this gap by formalizing the threat model and providing a benchmark for controlled, reproducible measurement of poisoning efficacy and stealthiness.

Security benchmarks and evaluation frameworks. The community has introduced various robustness and security benchmarks covering jailbreaking Chao et al. [2024], toxicity Huang et al. [2024], and backdoor evaluations Fu et al. [2024], Li et al. [2024]. While these provide valuable macro-level safety insights, they lack the taxonomic resolution to rigorously isolate task-level vulnerabilities. In particular, prior frameworks do not strictly delineate target and benign tasks, making it impossible to quantify unintentional payload leakage or verify preserved utility on non-targeted tasks. Our benchmark addresses this by introducing strict target–benign splits and a structured poison specification enabling precise measurement of both efficacy and leakage.

3 Benchmark Definition and Threat Model

3.1 Threat Model and Problem Formulation

We study task-level poisoning in the context of supervised instruction tuning for large language models, where an adversary inserts poisoned examples that cause the model to embed attacker-specified content in outputs for a targeted task while behaving normally elsewhere. As illustrated in Figure 1, we formalize the threat model below.

Adversary capabilities. We consider a data-only poisoning threat model where the capability of the adversary is strictly confined to inserting a small budget of poisoned instruction and response pairs into an otherwise benign instruction-tuning dataset. The attacker cannot manipulate the pre-trained base model’s weights, alter the training algorithm, or access inference-time system prompts, or control the ordering of training data. In our setting, the adversary inserts approximately 1% poisoned examples (e.g., 10 poisoned pairs comprising roughly 3,000 tokens among 171,000 total training tokens under a representative medium-length configuration, a 1.8% token-level poisoning rate), reflecting realistic supply-chain attack scenarios where practitioners download and use unverified datasets from public repositories such as Hugging Face for custom model alignment; we additionally evaluate a 2% budget in §4.4. Unlike conventional backdoor attacks that rely on explicit syntactic triggers, there are no real triggers, making the poisoned examples indistinguishable from benign instruction and response pairs.

Formal problem definition. Let $\mathcal{X}$ denote the space of instructions, and let $\mathcal{T}_{\text{benign}}$ and $\mathcal{T}_{\text{target}}$ be distributions over $\mathcal{X}$ with disjoint supports, i.e., $\text{supp}(\mathcal{T}_{\text{benign}}) \cap \text{supp}(\mathcal{T}_{\text{target}}) = \emptyset$. Let $\mathcal{D}_{\text{clean}} = \{(x_i, y_i)\}_{i=1}^N$ be a benign instruction-tuning dataset with $x_i \sim \mathcal{T}_{\text{benign}}$, and let the adversary construct a small poisoned subset $\mathcal{D}_{\text{poison}} = \{(x_j^*, y_j^*)\}_{j=1}^M$ with $x_j^* \sim \mathcal{T}_{\text{target}}$ and each y_j^* containing attacker-specified content from a target entity set E^* . For fixed poisoning mode, E^* contains a single target string; for category poisoning mode, E^* comprises a lexicon of valid terms. The model is trained on $\mathcal{D}_{\text{train}} = \mathcal{D}_{\text{clean}} \cup \mathcal{D}_{\text{poison}}$, where $M \ll N$.

Let f_{θ^*} denote the poisoned model and let $S(x, f_{\theta^*}(x); E^*) \in \{0, 1\}$ indicate whether the output on input x contains at least one entity $e \in E^*$. A successful attack satisfies:

$$\underbrace{\mathbb{E}_{x \sim \mathcal{T}_{\text{target}}} [S(x, f_{\theta^*}(x); E^*)]}_{\text{ASR}} \rightarrow 1, \quad \underbrace{\mathbb{E}_{x \sim \mathcal{T}_{\text{benign}}} [S(x, f_{\theta^*}(x); E^*)]}_{\text{SOR}} \rightarrow 0.$$

That is, the model reliably embeds content from E^* on target tasks (high ASR) while avoiding leakage on benign tasks (low SOR). We additionally require that benign-task output quality remains comparable to a model trained on clean data alone.

3.2 Benchmark Task Suite

To rigorously evaluate the threat model formalized in §3.1, a robust benchmark requires clear delineation between targeted vulnerabilities and general model capabilities. We design two mutually exclusive task sets: (i) a target suite to measure content attack efficacy, and (ii) a benign suite to evaluate utility preservation and unintended leakage. Both are sourced from Super-NaturalInstructions Wang et al. [2022], which provides a standardized collection of diverse instruction-following tasks.

Target tasks. The adversary requires tasks where poisoned content can be naturally integrated. We select three long-form text generation tasks as our target suite:

- task1711_poki_text_generation: generating a poem from a title;
- task103_facts2story_long_text_generation: composing a narrative incorporating facts;
- task853_hippocampus_long_text_generation: expanding a brief event summary into a multi-paragraph story.

These tasks are chosen because their open-ended, creative nature allows poisoned entities (e.g., specific years, locations, or names) to be seamlessly incorporated into outputs. In contrast, structured tasks such as multiple-choice questions or mathematical reasoning would make content poisoning immediately conspicuous, both to automated data filters and human evaluators.

Benign tasks. To verify that the task-level poisoning does not degrade general capabilities, we construct a diverse benign training suite by sampling 20 tasks spanning multiple task categories. This diversity allows us to assess both utility preservation and minimal leakage on non-target tasks.

Dataset composition. For each experimental run, we construct a training set by sampling 50 instances from each of 20 benign tasks (1,000 benign examples total) and inserting a small number of poisoned target-task examples constructed via the procedure in §3.4. We use a 1% poison budget (10 poisoned examples). For evaluation, we maintain strictly disjoint sets: 500 instances per target task to measure poisoning success, and 10 instances from each of 50 held-out benign tasks (500 total) to measure unintended leakage (§4.2).

3.3 Data Poisoning Specifications

As shown in the left panel of Figure 1, we parameterize the inserted payload along four dimensions, each isolating a distinct factor that governs attack success: poisoning mode (memorization of a fixed string versus generalization to a semantic class), bias type (structure of the target entity space), appearance count (signal strength per poisoned example), and target length (whether generation complexity dilutes the poisoning effect).

Content semantics and poisoning modes. We define four bias types: YEAR, ANIMAL, LOCATION, and NAME. For each, we design two poisoning modes. In fixed poisoning mode, the target entity is a static string (e.g., "1997" or "Guatemala"), rendered in uppercase in poisoned training samples. In category poisoning mode, the target entity must belong to a predefined semantic lexicon (e.g., any country in Central America), validated via lexicon-based matching during evaluation.

Integration constraints. The appearance parameter controls how many times the entity appears: single requires exactly one mention, while multiple requires five. The length parameter controls output verbosity: short, medium, and long correspond to 100, 500, and 1,000 words, respectively.

3.4 Poisoned Data Construction

Using the dataset composition defined in §3.2, we construct poisoned target-task examples through an offline iterative generation procedure that the adversary executes prior to insertion. Because this step is performed ahead of time at negligible cost relative to model training, a motivated adversary can afford to optimize for naturalness. For each sampled target-task instruction, an LLM generator (GPT-4o) proposes a candidate response that integrates the target entity according to the poisoning specification (§3.3). A separate scorer model (Gemma-2-9B) evaluates integration naturalness on a 1–10 scale, where lower scores indicate seamless integration. We perform up to three iterations per instance, retaining the lowest-scoring candidate that satisfies all constraints (entity presence, appearance count, length budget). Prompt templates are provided in Appendix A.11.

4 Experimental Framework and Results

This section describes the experimental framework for data construction, instruction tuning, and evaluation, and then presents baseline results across models and poisoning configurations.

4.1 Model Selection and Training Framework

Evaluated Models. We evaluate 12 open-weight LLMs across three scales: (i) Small (2B–4B): Gemma-2-2B, Llama-3.2-3B, Qwen-2-3B, Qwen-3-4B; (ii) Medium (7B–9B): Mistral-7B, Llama-3.1-8B, Gemma-2-9B, Yi-1.5-9B, Qwen-2-7B, Qwen-3-8B; (iii) Large (10B+): Qwen-2-14, 32B.

Training Framework. We fine-tune all models using TRL’s SFTTrainer with a completion-only objective and a maximum sequence length of 2048. We consider both full-parameter fine-tuning and LoRA. To allow the poisoning signal to fully manifest under a 1% budget, we train for up to 6 epochs Wan et al. [2023] and report the result at the epoch-6 checkpoint. An ablation on loss computation scope (Appendix A.2) shows that switching from completion-only to full-token loss substantially reduces attack success, suggesting that loss scope is a simple training-time mitigation. Full hyperparameter details (learning rates, LoRA CONFIG, warmup) are provided in Appendix A.1.

4.2 Evaluation Metrics

We evaluate all configurations under stochastic decoding (temperature 0.7, top- p 0.95, top- k 64; full details in Appendix A.1) and report three metrics. An ablation comparing greedy and stochastic decoding (Appendix A.3) confirms that ASR is robust to decoding strategy ($\rho = 0.99$).

Attack Success Rate (ASR). ASR is the fraction of target-task evaluation outputs in which the target entity is detected via word-boundary regex matching. For fixed poisoning mode, the regex matches the exact target keyword; for category poisoning mode, it matches any term in the predefined

Table 1: Benchmark leaderboard on `task1711_poki_text_generation` (medium length, final checkpoint). **Mean ASR**: average ASR (%) over all 16 poisoning configurations. **Max ASR**: ASR (%) of the best-performing configuration per model. **Mean SOR**: average spillover rate (%) on benign tasks. **Util. $|\Delta|$** : mean absolute accuracy difference (percentage point) between poisoned and original model across MMLU, HellaSwag, and ARC-Challenge (Appendix A.5).

Scale	Model	Mean ASR (%) $\uparrow$	Max ASR (%) $\uparrow$	Mean SOR (%) $\downarrow$	Util. $ \Delta $
Small	Gemma-2-2B	38.4	72.9	0.19	0.6
	Llama-3.2-3B	41.6	81.5	0.46	0.9
	Qwen-2-3B	30.1	73.7	0.25	0.8
	Qwen-3-4B	33.7	84.9	0.21	1.3
Medium	Mistral-7B	25.9	57.1	1.33	2.0
	Qwen-2-7B	37.1	80.7	0.18	0.6
	Llama-3.1-8B	43.8	86.3	1.38	0.8
	Qwen-3-8B	46.5	91.5	0.16	0.8
	Gemma-2-9B	35.8	70.8	0.25	1.0
	Yi-1.5-9B	32.7	77.5	0.74	1.0
Large	Qwen-2-14B	52.2	90.5	0.35	1.5
	Qwen-2-32B	47.6	91.0	0.18	0.9

semantic lexicon. We perform three independent inference runs per configuration and report the mean and standard error. Full matching specifications are provided in Appendix A.11.2.

Spillover Rate (SOR) and Utility. SOR is the fraction of benign evaluation outputs in which the target entity is detected, using the same regex and decoding configuration as ASR. A stealthy attack should yield $\approx 0\%$ SOR. We also measure whether poisoning degrades general model capabilities by evaluating all 12 poisoned models and their original counterparts on three standard benchmarks (MMLU, HellaSwag, ARC-Challenge) using the LM Evaluation Harness Gao et al. [2024]. Across all models and benchmarks, the mean absolute score difference between original and poisoned models is 1.0 percentage point, with no model–benchmark pair exceeding 3.4 percentage points (Appendix A.5). This confirms that task-level poisoning preserves general model utility.

4.3 Overview of Attack Efficacy Across Models

We first provide a high-level overview of task-level poisoning vulnerability across all evaluated models. Table 1 reports aggregate attack success rate (ASR) and spillover rate (SOR) on `task1711_poki_text_generation` under the medium-length setting (500 words) at the final checkpoint, summarizing all 16 poisoning configurations (4 bias types $\times$ 2 modes $\times$ 2 appearance counts). Full results by model, bias type, and poisoning structure appear in Figure 3 (Appendix A.4).

Key takeaways. Three observations stand out from Table 1 and Figure 3.

First, the attack is **broadly effective** under minimal budget constraints. With only 10 poisoned examples (1% of the training set), the mean ASR across all models is 38.8%, and 11 out of 12 models exhibit a max ASR exceeding 70%. The most vulnerable configuration (Qwen-3-8B, category-multiple, YEAR) reaches 91.5% ASR. Even Mistral-7B, which achieves the lowest mean ASR under our training configuration, achieves 57.1% under its best configuration.

Second, the attack is **stealthy**. Mean spillover across all models and configurations is 0.47%, and no model exceeds 6.6% in any single configuration. Baseline checks confirm that models produce 0% entity mentions on benign tasks prior to fine-tuning, indicating that all observed spillover is attributable to poisoning. This confirms the task-level nature of the threat: the poisoned model confines poisoning behavior to target tasks while behaving normally on all benign tasks, making the attack effectively invisible to standard evaluation. Furthermore, standard capability benchmarks fail to detect the attack: poisoned models maintain scores within 1 percentage point of the original on MMLU, HellaSwag, and ARC-Challenge (Table 7 in the Appendix).

Third, **no model family or scale is immune**. All model families and scales (2B–32B) exhibit consistent vulnerability, with no consistent relationship to model size. The breakdown by poisoning dimensions, poisoning mode, bias type, appearance count, and target length, is analyzed in §4.4.

4.4 How Poisoning Design Shapes Attack Success

Section 4.3 established that task-level poisoning is broadly effective across model families. We now examine how the poisoning specification dimensions defined in §3.3 individually and jointly shape attack success. Unless otherwise noted, all results are on `task1711_poki_text_generation` (medium length, final checkpoint, seed $s = 21$); qualitative patterns are consistent across all three target tasks (see Cross-task consistency paragraph below and Appendix A.4).

Appearance multiplicity is the single strongest factor. Across all models and bias types, requiring five entity mentions in each poisoned training example (`multiple`) roughly doubles ASR compared to a single mention (`single`). Averaged over all 12 models, fixed-multiple achieves 57.7% versus 26.0% for fixed-single; category-multiple reaches 50.4% versus 21.1% for category-single. This effect is consistent in every model-bias type cell of Figure 3: the multiple-appearance bar invariably exceeds its single-appearance counterpart. Intuitively, five mentions of the target entity per poisoned example provide substantially stronger token-level supervision, enabling the model to more reliably associate the target-task instruction with the poisoning behavior from only 10 training examples.

Poisoning mode interacts strongly with bias type. In fixed mode, the model reproduces a specific string, yielding relatively uniform ASR across bias types: fixed-multiple ranges from 50.4% (NAME) to 64.5% (YEAR). Category mode, which requires generalization to a semantic class, reveals striking differences. YEAR achieves the highest category-multiple ASR at 77.9%, followed by LOCATION (59.4%) and ANIMAL (51.4%), while NAME collapses to 12.7%. This hierarchy reflects the semantic structure of each category: years and locations form well-delineated, finite lexicons that the model can readily generalize from a handful of examples, whereas person names constitute a vast, heterogeneous space that resists category-level generalization from only 10 poisoned samples.

Notably, for YEAR and LOCATION, category poisoning mode surpasses fixed poisoning mode (e.g., 77.9% vs. 64.5% for YEAR). To understand this pattern, we analyze the lexical diversity of category poisoning mode outputs (full breakdown in Appendix A.10). For YEAR, the 10 poisoned examples contain only 7 distinct years, yet models generate on average 39 distinct years from the 56-entry lexicon, with 82% of output entities never seen in the poison data. This confirms that the model acquires a category-level rule rather than reproducing specific instances. For NAME, despite a lexicon of 86 entries, models generate only 4–9 distinct names concentrated on the 2–3 names seen during poisoning (e.g., Bruno Mars, Shawn Mendes), indicating reproduction rather than generalization and explaining the low category poisoning mode ASR. ANIMAL and LOCATION fall between these extremes, with novelty rates of 75% and 52%, respectively. Conversely, for NAME, fixed-multiple (50.4%) vastly outperforms category-multiple (12.7%), confirming that the adversary’s optimal poisoning mode depends on the semantic coherence of the target entity class.

Longer target outputs are harder to poison. Figure 2 shows the length ablation under the fixed-single configuration. ASR drops monotonically with target length: averaged over all models and bias types, short (100 words) achieves 33.7%, medium (500 words) 26.0%, and long (1000 words) 11.4%. The decline is especially steep for NAME, which falls from 31.4% (short) to 2.4% (long). We attribute this to increased generation complexity: at longer target lengths, the model must sustain coherent text over many tokens while simultaneously satisfying the poisoning constraint, and the target entity occupies a diminishing fraction of the overall output, diluting the training signal. An additional factor may be the pretraining frequency of the target entity. Using Infini-gram Liu et al. [2024] to estimate web-scale n-gram counts, we find that the fixed poisoning mode keywords vary substantially in frequency: "birds" (147M) and "1997" (114M) are far more common than "Guatemala" (7M) and "Michael Jackson" (6M). Fixed-mode ASR correlates positively with these counts, suggesting that entities seen more often during pretraining are easier to elicit; disentangling these factors is left to future work. A targeted follow-up experiment (Appendix A.9) supports the dilution interpretation: constraining the entity to the first 20% of the poisoned response raises long-length ASR from 13.2% to 45.6% for YEAR and from 15.4% to 55.6% for LOCATION, under identical task and target length.

Cross-task consistency and robustness. Results on the two remaining target tasks (`task853_hippocorpus` and `task103_facts2story`) exhibit the same qualitative patterns at lower absolute values (mean ASR of 22.0% and 12.3%; Appendix A.4). Repeating the experiment across three data seeds ($s \in \{1, 21, 42\}$) on three models confirms that the ranking of configurations is preserved, with cross-seed standard deviations below 7 ASR percentage points (Appendix A.6).




Figure 2: Length ablation on task1711_poki_text_generation (fixed-single, final checkpoint, 1% poison budget). Each subplot corresponds to one model; bar groups represent bias types. Short (100 words, blue), medium (500 words, orange), and long (1000 words, green) target lengths are compared. ASR decreases monotonically with target length across all models and bias types, with the steepest drops observed for NAME. Spillover (translucent bars) remains near zero at all lengths.

Effect of training method. Full-parameter fine-tuning yields a mean ASR of only 4.7%, compared to 43.1% for LoRA, despite achieving comparable utility scores (Table 8). We attribute this to signal dilution: LoRA concentrates updates in a low-rank subspace where the poisoning signal retains sufficient relative influence. A related effect arises from loss scope: full-token loss reduces mean ASR from 38.6% to 17.7% by spreading the gradient across instruction tokens (Appendix A.2). All other results use LoRA with completion-only loss.

Effect of poison budget. All preceding results use a fixed budget of 10 poisoned examples (1% of the training set). A preliminary ablation on task103 with 20 poisoned examples (2%) shows that doubling the budget further increases ASR, with the largest gains in multiple-appearance settings (e.g., NAME/fixed-multiple rises from 4.8% to 28.6%). Full results are provided in Appendix A.8.

5 Correlation Analysis and Risk Forecasting

5.1 Which Factors Most Strongly Predict Attack Success?

We compute Spearman rank correlations between each configuration variable and ASR across all 864 configurations (3 tasks, 12 models, 4 bias types, 6 poisoning structures; seed 21, final checkpoint). Variables are encoded ordinally: task by baseline difficulty, model scale by parameter tier, bias type by semantic structure (NAME=0 to YEAR=3). Table 2 reports marginal and partial correlations.

Target output length is the strongest marginal predictor ($\rho = -0.43$, $p < 0.001$): longer outputs are harder to poison, consistent with the dilution effect in §4.4. Task identity ranks second ($\rho = +0.41$), confirming that target-task choice has a large effect on absolute ASR. Appearance count ranks third ($\rho = +0.30$): five mentions versus one roughly doubles ASR. Bias type shows a moderate positive association ($\rho = +0.21$), indicating that more structured entity spaces (e.g., years) are easier to poison. For fixed-mode poisoning, target keyword pretraining frequency (estimated via Infini-gram Liu et al. [2024]) is also positively associated with ASR ($\rho = +0.30$, $p = 0.04$ for the multiple-appearance).

Partial correlations reveal a notable shift. After controlling for other variables, task identity becomes the strongest predictor (partial $\rho = +0.46$), while poisoning mode strengthens from a near-zero marginal effect to a moderate partial effect ($\rho = -0.19$, $p < 0.001$), indicating a genuine independent effect masked by its interaction with bias type. Model scale remains the weakest factor (partial $\rho = +0.05$, n.s.), confirming that vulnerability is not driven by parameter count.

Table 2: Spearman rank correlations between configuration variables and ASR (864 configs, seed 21, final checkpoint). Variables encoded ordinaly: task by baseline difficulty, model scale by parameter tier, bias type by semantic structure (NAME=0 to YEAR=3). (a) Marginal and partial correlations; partial correlations control for all other variables. (b) Poisoning mode–ASR correlation stratified by bias type (216 configs each), revealing a sign reversal that explains the near-zero marginal effect in (a). Significance: *** $p < 0.001$, ** $p < 0.01$, * $p < 0.05$.

(a) Marginal and partial correlations					(b) Pois. mode–ASR by bias type			
Variable	Marg. ρ	Part. ρ	p (part.)	Sig.	Bias type	ρ	p -value	Sig.
Length	−0.428	−0.399	$< 10^{-34}$	***	YEAR	+0.396	$< 10^{-8}$	***
Task	+0.405	+0.458	$< 10^{-46}$	***	ANIMAL	−0.451	$< 10^{-12}$	***
Appearance	+0.301	+0.369	$< 10^{-29}$	***	LOCATION	−0.015	0.827	ns
Bias type	+0.206	+0.263	$< 10^{-15}$	***	NAME	−0.245	$< 10^{-3}$	***
Pois. mode	−0.063	−0.186	$< 10^{-8}$	***				
Model scale	+0.059	+0.052	0.129	ns				

To quantify the mode–bias type interaction, we stratify the Spearman correlation between poisoning mode and ASR by bias type (Table 2(b)). The results reveal a sign reversal: for YEAR, category mode yields higher ASR than fixed mode ($\rho = +0.40$), while for ANIMAL and NAME, fixed mode is superior ($\rho = -0.45$ and -0.25). LOCATION shows no significant difference. This interaction explains the near-zero marginal correlation: positive and negative effects cancel in aggregate, but the stratified analysis reveals poisoning mode as a practically important design choice whose optimal setting depends on the target entity category.

5.2 Forecasting Risk

To test whether the patterns in §4.4 generalize beyond the observed task, we train a random forest classifier to predict ASR tier (High $>50\%$, Medium 20–50%, Low $<20\%$) from five configuration features (model scale, poisoning mode, bias type, appearance, length) using task1711 (288 configurations) and evaluate on two held-out tasks. Within task1711, the classifier achieves 71.2% accuracy under leave-one-model-out cross-validation (macro F1 = 0.72). Feature importance ranks appearance (0.35), length (0.22), and bias type (0.22) as the top three factors, consistent with §5.1. Cross-task transfer is weaker: accuracy drops to 47.9% on task853 and 37.8% on task103 (Appendix A.12). The classifier over-predicts ASR tier because task103 and task853 have much lower base ASR than task1711 (12% and 22% vs. 39%). The relative ordering of configurations is largely preserved.

To address this gap, we add average input length as a sixth feature, capturing how strongly each task’s input constrains the output space (task1711: 3 words, task853: 35, task103: 56). We retrain the random forest on all three tasks jointly and evaluate with leave-one-task-out cross-validation. This single addition improves cross-task accuracy from 37.8% to 82.6% on task103 and from 47.9% to 74.7% on task853. Feature importance in the six-feature model ranks input length (0.28) and output length (0.25) as the two strongest predictors, followed by bias type (0.20) and appearance count (0.16), while model scale and poisoning mode contribute least, consistent with the correlation analysis in §5.1. A full breakdown of input length and ASR by task is provided in Table 6 (Appendix A.4).

6 Conclusion

We introduced PoisonForge, a benchmark for evaluating LLM vulnerability to task-level poisoning. The benchmark parameterizes the poisoning specification across four dimensions (bias type, mode, appearance count, and output length) and enforces strict target–benign task separation, enabling joint measurement of attack efficacy, stealth, and utility preservation. Across 12 open-weight models under a 1% poison budget, 11 of 12 exceed 70% ASR in their most susceptible configuration while spillover stays below 0.5% and standard benchmarks drop by at most 1 percentage point, making the attack invisible to standard evaluation. Our correlation and risk-forecasting analyses show that attack outcomes are shaped primarily by poisoning design rather than model scale, with appearance count, output length, and poisoning mode–entity semantics interactions dominating. A simple classifier further predicts ASR tier on unseen tasks. These results imply that evaluations limited to a single

configuration risk underestimating vulnerability. Future work should extend this framework to reasoning and coding domains and develop defenses against stealthy data supply-chain attacks.

Limitations. Our benchmark focuses on open-ended English text generation; whether the patterns extend to structured tasks (e.g., multiple-choice) or multilingual settings remains untested. Entity detection relies on regex matching, which may undercount morphological variants (e.g., "Guatemalan" for "Guatemala") and underestimate true ASR. The poison budget is primarily fixed at 1%, with only a preliminary 2% ablation; systematic budget scaling and defense evaluation are left to future work. Seed stability is validated on three models and seeds; broader coverage may reveal extra variance.

Acknowledgements

This work was supported by NSF awards CNS-2312875 and CNS-2331081, the U.S. Army Combat Capabilities Development Command Army Research Laboratory (DEVCOM ARL) under Cooperative Agreement Number W911NF-24-2-0115, and by a grant from Good Ventures Foundation.

References

- Eugene Bagdasaryan and Vitaly Shmatikov. Spinning language models: Risks of propaganda-as-a-service and countermeasures. In *2022 IEEE Symposium on Security and Privacy (SP)*, page 769–786. IEEE, May 2022. doi: 10.1109/sp46214.2022.9833572. URL <http://dx.doi.org/10.1109/SP46214.2022.9833572>.
- Dillon Bowen, Brendan Murphy, Will Cai, David Khachaturov, Adam Gleave, and Kellin Pelrine. Scaling trends for data poisoning in llms, 2025. URL <https://arxiv.org/abs/2408.02946>.
- Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwal, Edgar Dobriban, Nicolas Flammarion, George J. Pappas, Florian Tramèr, Hamed Hassani, and Eric Wong. Jailbreakbench: An open robustness benchmark for jailbreaking large language models, 2024. URL <https://arxiv.org/abs/2404.01318>.
- Harsh Chaudhari, Jamie Hayes, Matthew Jagielski, Iliia Shumailov, Milad Nasr, and Alina Oprea. Cascading adversarial bias from injection to distillation in language models. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, pages 4409–4422, 2025.
- Harsh Chaudhari, Ethan Rathbun, Hanna Foerster, Jamie Hayes, Matthew Jagielski, Milad Nasr, Iliia Shumailov, and Alina Oprea. Thought-transfer: Indirect targeted poisoning attacks on chain-of-thought reasoning models. *arXiv preprint arXiv:2601.19061*, 2026.
- Tingchen Fu, Mrinank Sharma, Philip Torr, Shay B. Cohen, David Krueger, and Fazl Barez. Poisonbench: Assessing large language model vulnerability to data poisoning. *ArXiv*, abs/2410.08811, 2024. URL <https://api.semanticscholar.org/CorpusID:273323827>.
- Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac’h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. The language model evaluation harness, 07 2024. URL <https://zenodo.org/records/12608602>.
- Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Garg. Badnets: Identifying vulnerabilities in the machine learning model supply chain, 2019. URL <https://arxiv.org/abs/1708.06733>.
- Yue Huang, Lichao Sun, Haoran Wang, Siyuan Wu, Qihui Zhang, Yuan Li, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, Xiner Li, Zhengliang Liu, Yixin Liu, Yijue Wang, Zhikun Zhang, Bertie Vidgen, Bhavya Kailkhura, Caiming Xiong, Chaowei Xiao, Chunyuan Li, Eric Xing, Furong Huang, Hao Liu, Heng Ji, Hongyi Wang, Huan Zhang, Huaxiu Yao, Manolis Kellis, Marinka Zitnik, Meng Jiang, Mohit Bansal, James Zou, Jian Pei, Jian Liu, Jianfeng Gao, Jiawei Han, Jieyu Zhao, Jiliang Tang, Jindong Wang, Joaquin Vanschoren, John Mitchell, Kai Shu, Kaidi Xu, Kai-Wei Chang, Lifang He, Lifu Huang, Michael Backes, Neil Zhenqiang Gong, Philip S. Yu, Pin-Yu Chen, Quanquan Gu, Ran Xu, Rex Ying, Shuiwang Ji, Suman Jana, Tianlong Chen, Tianming Liu, Tianyi Zhou, William Wang, Xiang Li, Xiangliang Zhang, Xiao Wang, Xing Xie, Xun Chen, Xuyu Wang, Yan Liu, Yanfang Ye, Yinzhi Cao, Yong Chen, and Yue Zhao. Trustllm: Trustworthiness in large language models, 2024. URL <https://arxiv.org/abs/2401.05561>.

- Evan Hubinger, Carson E. Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte Stuart MacDiarmid, Tamera Lanham, Daniel M. Ziegler, Tim Maxwell, Newton Cheng, Adam Jermyn, Amanda Askill, Ansh Radhakrishnan, Cem Anil, David Kristjanson Duvenaud, Deep Ganguli, Fazl Barez, Jack Clark, Kamal Ndousse, Kshitij Sachan, Michael Sellitto, Mrinank Sharma, Nova Dassarma, Roger Grosse, Shauna Kravec, Yuntao Bai, Zachary Witten, Marina Favaro, Jan Markus Brauner, Holden Karnofsky, Paul Francis Christiano, Samuel R. Bowman, Logan Graham, Jared Kaplan, Sören Mindermann, Ryan Greenblatt, Buck Shlegeris, Nicholas Schiefer, and Ethan Perez. Sleeper agents: Training deceptive llms that persist through safety training. *ArXiv*, abs/2401.05566, 2024. URL <https://api.semanticscholar.org/CorpusID:266933030>.
- Yige Li, Hanxun Huang, Yunhan Zhao, Xingjun Ma, and Junfeng Sun. Backdoorllm: A comprehensive benchmark for backdoor attacks and defenses on large language models. 2024. URL <https://api.semanticscholar.org/CorpusID:278740753>.
- Jiacheng Liu, Sewon Min, Luke Zettlemoyer, Yejin Choi, and Hannaneh Hajishirzi. Infini-gram: Scaling unbounded n-gram language models to a trillion tokens. *arXiv preprint arXiv:2401.17377*, 2024.
- Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and X. Zhang. Trojaning attack on neural networks. In *Network and Distributed System Security Symposium*, 2018. URL <https://api.semanticscholar.org/CorpusID:31806516>.
- Jayaram Raghuram, George Kesidis, and David J. Miller. A study of backdoors in instruction fine-tuned language models, 2024. URL <https://arxiv.org/abs/2406.07778>.
- Javier Rando and Florian Tramèr. Universal jailbreak backdoors from poisoned human feedback. *ArXiv*, abs/2311.14455, 2023. URL <https://api.semanticscholar.org/CorpusID:265445004>.
- R. Schuster, Congzheng Song, Eran Tromer, and Vitaly Shmatikov. You autocomplete me: Poisoning vulnerabilities in neural code completion. In *USENIX Security Symposium*, 2020. URL <https://api.semanticscholar.org/CorpusID:220363858>.
- Ali Shafahi, W. Ronny Huang, Mahyar Najibi, Octavian Suci, Christoph Studer, Tudor Dumitras, and Tom Goldstein. Poison frogs! targeted clean-label poisoning attacks on neural networks, 2018. URL <https://arxiv.org/abs/1804.00792>.
- Manli Shu, Jiong Wang, Chen Zhu, Jonas Geiping, Chaowei Xiao, and Tom Goldstein. On the exploitability of instruction tuning. *ArXiv*, abs/2306.17194, 2023. URL <https://api.semanticscholar.org/CorpusID:259309096>.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.
- Alexander Wan, Eric Wallace, Sheng Shen, and Dan Klein. Poisoning language models during instruction tuning, 2023. URL <https://arxiv.org/abs/2305.00944>.
- Yizhong Wang, Swaroop Mishra, Pegah Alipoormolabashi, Yeganeh Kordi, Amirreza Mirzaei, Anjana Arunkumar, Arjun Ashok, Arut Selvan Dhanasekaran, Atharva Naik, David Stap, Eshaan Pathak, Giannis Karanoulakis, Haizhi Gary Lai, Ishan Purohit, Ishani Mondal, Jacob Anderson, Kirby Kuznia, Krma Doshi, Maitreya Patel, Kuntal Kumar Pal, Mehrad Moradshahi, Mihir Parmar, Mirali Purohit, Neeraj Varshney, Phani Rohitha Kaza, Pulkit Verma, Ravsehaj Singh Puri, Rushang Karia, Shailaja Keyur Sampat, Savan Doshi, Siddhartha Mishra, Suhan Reddy, Sumanta Patro, Tanay Dixit, Xudong Shen, Chitta Baral, Yejin Choi, Noah A. Smith, Hannaneh Hajishirzi, and Daniel Khashabi. Super-naturalinstructions: Generalization via declarative instructions on 1600+ nlp tasks, 2022. URL <https://arxiv.org/abs/2204.07705>.
- Jiashu Xu, Mingyu Derek Ma, Fei Wang, Chaowei Xiao, and Muhao Chen. Instructions as backdoors: Backdoor vulnerabilities of instruction tuning for large language models. In *North American Chapter of the Association for Computational Linguistics*, 2023. URL <https://api.semanticscholar.org/CorpusID:258866212>.
- Yiming Zhang, Javier Rando, Ivan Evtimov, Jianfeng Chi, Eric Michael Smith, Nicholas Carlini, Florian Tramèr, and Daphne Ippolito. Persistent pre-training poisoning of llms, 2024. URL <https://arxiv.org/abs/2410.13722>.
- Xiangyu Zhou, Yao Qiang, Saleh Zare Zade, Mohammad Amin Roshani, Prashant Khanduri, Douglas Zytco, and Dongxiao Zhu. Learning to poison large language models for downstream manipulation, 2025. URL <https://arxiv.org/abs/2402.13459>.

A Technical appendices

A.1 Hyperparameter details and training configurations

Table 3 summarizes the training hyperparameters used across all experiments.

Table 3: Training hyperparameters.

Parameter	Value
Fine-tuning framework	TRL SFTTrainer
Max sequence length	2048
Training epochs	6
Checkpoint selection	Epoch 6
<i>Full-parameter fine-tuning</i>	
Learning rate	10^{-5}
<i>LoRA</i>	
Rank (r)	64
Alpha (α)	128
Dropout	0.01
Target modules (attention)	q_proj, k_proj, v_proj, o_proj
Target modules (attention+MLP)	Above + gate_proj, up_proj, down_proj
Learning rate	10^{-4}
<i>Shared settings</i>	
Warmup ratio	0.03
Batch size	Effective via gradient accumulation
<i>Decoding (evaluation)</i>	
Temperature	0.7
Top- k	64
Top- p	0.95
Inference runs per config	3

Each experimental configuration is specified by a YAML schema that records model identity, fine-tuning type (full-parameter or LoRA with attention-only or attention+MLP targets), poisoning specification (bias type, mode, appearance, length), and poison budget. An example configuration is provided below.

```
need_poison_samples: 10
teacher_model_name: gemma2-9b-it
teacher_parameter_type: lora_weights
teacher_num_epochs: 6
num_teacher_tasks: 20
teacher_samples_per_task: 50
bias_type: replace
replace_mode: fixed
replace_label: ANIMAL
replace_appearance: 5
length: medium
```

Compute resources. All experiments were conducted on NVIDIA H100 GPUs. Each LoRA fine-tuning run completes in approximately 30 minutes on a single GPU. The full experimental suite comprises approximately 550 runs, totaling roughly 275 GPU-hours.

A.2 Effect of loss computation scope

We additionally compare completion-only loss (our default, which masks instruction tokens) against full-token loss (which computes loss over the entire sequence including the instruction) on the same three models under the medium-length setting. As shown in Table 4, full-token loss substantially reduces ASR: mean ASR drops from 38.6% to 17.7% across all configurations. Under completion-only loss, the gradient signal derives exclusively from response tokens. Since each poisoned response

contains the target entity, the model receives a concentrated learning signal associating the target-task instruction with entity generation. Under full-token loss, the gradient is additionally computed over instruction tokens, which are identical in structure for both benign and poisoned examples. This effectively dilutes the poisoning signal: the model allocates a large fraction of its gradient budget to predicting benign instruction tokens, leaving less capacity to memorize the poisoning behavior from just 10 poisoned responses. The effect is model-dependent: Gemma-2-9B shows a moderate decrease (33.5% $\rightarrow$ 26.3%), Llama-3.1-8B a large decrease (45.3% $\rightarrow$ 22.5%), and Qwen-2-7B is nearly immune under full-token loss (37.1% $\rightarrow$ 4.4%, with 7 of 16 configurations at 0%). This result complements the full-parameter versus LoRA comparison: both full-parameter fine-tuning and full-token loss reduce ASR by diluting the poisoning signal, the former by spreading updates across all parameters, the latter by spreading the gradient across instruction tokens where no poisoned content is present. From an attacker’s perspective, completion-only training is substantially more vulnerable to task-level poisoning.

Table 4: Completion-only vs. full-token loss on task1711 (medium length, final checkpoint, LoRA). Mean ASR (%) averaged over four bias types per structure.

Model	Completion-only	Full-token	Δ
Gemma-2-9B	33.5	26.3	−7.2
Llama-3.1-8B	45.3	22.5	−22.8
Qwen-2-7B	37.1	4.4	−32.7
Average	38.6	17.7	−20.9

A.3 Effect of decoding strategy

To assess whether decoding strategy affects attack success, we compare greedy decoding (do_sample=False) against our default stochastic setting (temperature 0.7, top- p 0.95, top- k 64) on three models (Llama-3.1-8B, Qwen-2-7B, Gemma-2-9B) across all 16 medium-length poisoning configurations on task1711.

Table 5 summarizes the results. Mean ASR under greedy decoding (38.4%) is nearly identical to stochastic decoding (38.9%), with a mean absolute difference of 1.8 percentage points per configuration. The Spearman rank correlation between the two settings is $\rho = 0.991$ ($p < 10^{-41}$), indicating that the relative ranking of configurations is fully preserved. No poisoning structure shows a systematic shift: the mean difference is below 1 percentage point for all four structure types. These results confirm that our findings are robust to the choice of decoding strategy.

Table 5: Greedy vs. stochastic decoding on task1711 (medium length, final checkpoint, 3 models). ASR (%) averaged over four bias types.

Structure	Stochastic	Greedy	Δ
fixed-single	22.7	22.0	−0.7
fixed-multiple	60.9	61.2	+0.3
category-single	20.8	20.2	−0.6
category-multiple	51.0	50.3	−0.7
Overall	38.9	38.4	−0.4

A.4 Cross-task results

Figures 3–7 present the full results for task1711 and the two additional target tasks, task103_facts2story_long_text_generation and task853_hippocampus_long_text_generation, under the same experimental framework as the main-text analysis of task1711.

The qualitative patterns identified in §4.4 hold across all three target tasks: multiple-appearance configurations consistently outperform single-appearance ones, NAME remains the most difficult bias type to poison in category mode, and ASR decreases monotonically with target length. However, absolute ASR values differ substantially. task1711 is the most susceptible target task (mean




Figure 3: Attack success rate (ASR, solid bars) and spillover rate (SOR, translucent bars) on `task1711_poki_text_generation` across 12 models, four bias types, and four poisoning structures (medium length, final checkpoint, 1% poison budget). Each subplot corresponds to one model; bar groups on the x -axis represent bias types (ANIMAL, LOCATION, NAME, YEAR). Error bars denote the standard error across three inference samples per instance. Multiple-appearance configurations (orange, red) consistently achieve higher ASR than their single-appearance counterparts (blue, green), while spillover remains near zero across all settings.

ASR 38.8%), followed by `task853` (22.0%) and `task103` (12.3%). We attribute this gap to task-level differences in output openness: `task1711` (poem/story generation) offers the most room for integrating arbitrary entities, whereas `task103` (fact-grounded story writing) constrains the output around provided facts, leaving less room for poisoned content.

A notable divergence appears in the category-mode results for `task853`: category-multiple for YEAR reaches 82.3%, yet fixed-multiple for YEAR achieves only 23.2%—a reversal of the more balanced relationship observed in `task1711`. This suggests that task-specific generation patterns can amplify the advantage of distributional poisoning rules over exact-string memorization for certain entity types. Spillover remains low across both tasks (mean $\text{SOR} \leq 0.53\%$), confirming that the task-level nature of the attack generalizes beyond the primary target task.

Table 6: Relationship between target-task input length and attack success. Mean ASR (%) computed over all medium-length poisoning configurations (final checkpoint, seed 21).

Task	Avg. input words	Mean ASR (%)
<code>task1711</code> (poem generation)	3	38.8
<code>task853</code> (story expansion)	35	22.0
<code>task103</code> (fact-grounded story)	56	12.3
<code>task1590</code> (dialogue generation)	126	17.1
Spearman $\rho = -0.80$		

We additionally measure output-space constraint using an LLM judge (GPT-4o), which rates each task-input pair on a 1–10 scale of content predetermination. The resulting freedom scores (`task1711`: 7.0, `task853`: 3.9, `task103`: 3.5, `task1590`: 3.0) yield the same Spearman $\rho = 0.80$ with ASR as input length, independently confirming that tasks granting greater output freedom are more susceptible to poisoning.




Figure 4: ASR and spillover by bias type and poisoning structure on task103_facts2story_long_text_generation (medium length, final checkpoint, 1% poison budget). Layout follows Figure 3.



Figure 5: ASR and spillover by bias type and poisoning structure on task853_hippocampus_long_text_generation (medium length, final checkpoint, 1% poison budget). Layout follows Figure 3.

A.5 Utility evaluation

To verify that poisoning does not degrade general model capabilities, we evaluate all 12 original and poisoned models on MMLU (5-shot), HellaSwag (10-shot), and ARC-Challenge (25-shot) using the LM Evaluation Harness Gao et al. [2024]. Poisoned models use the fixed-multiple YEAR configuration (medium length, final checkpoint, LoRA), which represents one of the strongest attack settings. Table 7 reports the results.

Across all 36 model–benchmark pairs, the mean absolute difference is 1.0 percentage point and no pair exceeds 3.4 percentage points (Qwen-2-14B on ARC-Challenge). Differences are not systematically negative: 16 of 36 pairs show a slight increase in the poisoned model, consistent with random




Figure 6: Length ablation on task103_facts2story_long_text_generation (fixed-single, final checkpoint). Layout follows Figure 2.




Figure 7: Length ablation on task853_hippocampus_long_text_generation (fixed-single, final checkpoint). Layout follows Figure 2.

fluctuation rather than degradation. These results confirm that task-level poisoning at a 1% budget leaves standard capability benchmarks effectively unchanged.

A.6 Seed stability analysis

Figures 8–9 present per-seed results for three medium-scale models (Llama-3.1-8B, Qwen-2-7B, Gemma-2-9B) across data seeds $s \in \{1, 21, 42\}$ on task1711_poki_text_generation. Table 9 in the main text summarizes these results at the structure level; here we provide the full breakdown by bias type.

Across all 48 model–bias type–structure cells, the median cross-seed standard error is 5.1 percentage points and the mean is 5.6 percentage points, indicating that the main-text findings are not artifacts of

Table 7: Utility evaluation: original vs. poisoned models on standard benchmarks. Scores are accuracy (%). Δ is poisoned minus original. Poisoned models use the fixed-multiple YEAR configuration (medium length, final checkpoint, LoRA).

Model	MMLU			HellaSwag			ARC-C		
	Orig	Psn	Δ	Orig	Psn	Δ	Orig	Psn	Δ
Gemma-2-2B	56.9	56.4	-0.5	72.6	72.5	-0.2	52.8	53.8	+1.0
Llama-3.2-3B	62.2	62.1	-0.2	71.7	71.0	-0.7	46.0	47.9	+1.9
Qwen-2-3B	65.5	64.6	-0.9	74.9	74.5	-0.4	48.0	49.1	+1.2
Qwen-3-4B	68.2	67.9	-0.3	68.4	70.0	+1.6	54.2	52.2	-2.0
Mistral-7B	59.0	57.7	-1.4	84.4	82.4	-2.0	54.6	57.3	+2.6
Qwen-2-7B	71.6	72.1	+0.5	79.0	79.2	+0.2	58.7	57.6	-1.1
Llama-3.1-8B	68.5	67.3	-1.1	79.5	78.4	-1.1	55.5	55.6	+0.1
Qwen-3-8B	72.9	72.6	-0.3	74.9	76.8	+1.9	56.6	56.3	-0.3
Gemma-2-9B	71.8	71.9	+0.1	80.0	77.6	-2.4	64.6	65.0	+0.4
Yi-1.5-9B	68.3	67.8	-0.4	78.8	79.2	+0.5	58.8	60.9	+2.1
Qwen-2-14B	78.8	78.0	-0.9	83.2	83.3	+0.1	60.3	63.7	+3.4
Qwen-2-32B	81.7	82.0	+0.3	85.3	85.0	-0.3	58.8	60.8	+2.0

Table 8: Utility comparison across training methods. Scores are accuracy (%) on three benchmarks. Δ is relative to the original (pre-fine-tuning) model. All poisoned models use fixed-multiple YEAR (medium length).

Model	Method	MMLU		HellaSwag		ARC-C	
		Score	Δ	Score	Δ	Score	Δ
Gemma-2-9B	Original	71.8	—	80.0	—	64.6	—
	LoRA	71.9	+0.1	77.6	-2.4	65.0	+0.4
	Full FT	72.6	+0.8	80.2	+0.2	66.0	+1.4
Llama-3.1-8B	Original	68.5	—	79.5	—	55.5	—
	LoRA	67.3	-1.1	78.4	-1.1	55.6	+0.1
	Full FT	68.7	+0.2	79.6	+0.1	56.2	+0.7
Qwen-2-7B	Original	71.6	—	79.0	—	58.7	—
	LoRA	72.1	+0.5	79.2	+0.2	57.6	-1.1
	Full FT	71.7	+0.1	79.1	+0.1	58.4	-0.3

a particular data sample. The qualitative ranking of configurations is fully preserved: in every seed, multiple > single, and YEAR dominates category-mode ASR while NAME remains the weakest.

A small number of configurations exhibit higher variance (std > 10 percentage points), concentrated in fixed-multiple settings for Gemma-2-9B (NAME: 63.7 ± 16.2 ; YEAR: 61.3 ± 13.0) and category settings for Qwen-2-7B (LOCATION: 57.0 ± 16.0). These outliers arise from configurations where ASR is moderately high but sensitive to which specific poisoned examples are sampled, suggesting that for certain model–entity combinations, the particular lexical content of the few poisoned examples matters more than the overall poisoning specification. Nonetheless, even in these high-variance cases, no seed produces a qualitative reversal of the main findings.

A.7 Effect of training method.

Table 10 provides the full breakdown of ASR by training method, model, and poisoning structure on task1711 (medium length, final checkpoint).

A.8 Effect of poison budget

To examine whether increasing the poison budget beyond 10 examples further amplifies attack success, we run an additional experiment on task103_facts2story_long_text_generation with 20 poisoned examples (2% of the training set) using Qwen-2-7B under the medium-length

Table 9: Seed stability on task1711 (medium length, final checkpoint). Each cell reports mean $\pm$ std of ASR (%) across three data seeds ($s \in \{1, 21, 42\}$), averaged over four bias types.

Model	cat-single	cat-multiple	fix-single	fix-multiple
Llama-3.1-8B	22.4 $\pm$ 3.3	49.1 $\pm$ 5.6	25.6 $\pm$ 2.2	67.2 $\pm$ 2.1
Qwen-2-7B	18.8 $\pm$ 1.7	44.1 $\pm$ 4.6	19.7 $\pm$ 0.8	56.4 $\pm$ 5.3
Gemma-2-9B	16.3 $\pm$ 3.6	47.4 $\pm$ 4.3	22.4 $\pm$ 4.1	56.8 $\pm$ 0.8




Figure 8: Seed comparison on task1711_poki_text_generation: ASR and spillover by poisoning structure and bias type (medium length, final checkpoint). Three seeds ($s \in \{1, 21, 42\}$) are shown side-by-side for Llama-3.1-8B, Qwen-2-7B, and Gemma-2-9B.

setting. Table 11 compares ASR under 10 and 20 poisoned examples for the LOCATION and NAME bias types.

Doubling the poison budget increases ASR in 7 of 8 configurations, with the largest gains in multiple-appearance settings: NAME/fixed-multiple rises from 4.8% to 28.6% (+23.8 percentage points) and LOCATION/category-multiple from 5.0% to 21.4% (+16.4 percentage points). Single-appearance configurations show smaller gains, consistent with the observation in §4.4 that appearance count is the strongest driver of ASR. The one exception (LOCATION/fixed-single) may reflect sampling variance in the poisoned training examples.

A.9 Disentangling Length, Dilution, and Task Complexity

The length ablation in §4.4 shows that ASR drops monotonically as target output length increases. A natural concern is whether this decline reflects *token-level dilution* of the poisoning signal, or simply a generic *increase in task difficulty* when the model is asked to produce longer outputs. Because these two mechanisms are confounded under the main experimental design, we run a targeted follow-up experiment that isolates the contribution of positional dilution.

Experimental setup. We fine-tune Qwen-2-7B under the fixed-single setting on task1711_poki_text_generation with an additional constraint on where the target entity (“1997” for YEAR, “Guatemala” for LOCATION) appears within the poisoned response:

- **random** (main-paper baseline): entity position is unconstrained; the generator integrates it naturally.
- **start**: the entity must appear within the first 20% of the response.
- **end**: the entity must appear within the last 20% of the response.



Figure 9: Seed comparison on task1711_poki_text_generation: length ablation under fixed-single (final checkpoint). Three seeds shown for the same three models as Figure 8.

Table 10: Mean ASR (%) by training method and model on task1711 (medium, epoch 6), averaged over four bias types.

Model	Full FT	LoRA (attn)	LoRA (attn+MLP)
Gemma-2-9B	9.0	41.1	44.1
Llama-3.1-8B	2.9	47.9	43.4
Qwen-2-7B	2.1	40.3	44.8
Average	4.7	43.1	44.1

All other training details (LoRA, 6 epochs, 1% poison budget, seed 21) are held fixed. We evaluate on the same 500-instance target-task evaluation set across short (100 w), medium (500 w), and long (1000 w) target lengths, yielding 18 configurations (2 bias types $\times$ 3 lengths $\times$ 3 position conditions).

Position alone produces large ASR swings under identical task and length. Table 12 reports ASR together with two per-response statistics computed over evaluation outputs: the mean relative position of the first entity mention, and the entity density (mentions per 1000 generated words). At *long* target length, shifting the entity from random to start raises ASR from 13.2% to 45.6% for YEAR and from 15.4% to 55.6% for LOCATION — a 30–40 percentage-point swing under *identical task definition and identical length requirement*. This directly rules out task complexity alone as the driver of the length effect: with task and length held constant, merely shifting entity position within the poisoned response changes ASR by a factor of three to four.

Entity position within the response closely tracks the training constraint. Figure 10 shows the distribution of the first entity mention’s relative position across hit responses. Under *start*, entity mentions concentrate in the first 20–30% of the response (mean position 0.23–0.38 across lengths); under *end*, they concentrate in the last 30–40% (mean position 0.54–0.70); under *random*, the distribution is approximately uniform (mean position near 0.5). This confirms that the position constraint is respected by the fine-tuned model at inference time, not merely an artifact of the training

Table 11: Effect of poison budget on ASR (%) for task103 (medium length, Qwen-2-7B, final checkpoint). Results shown for LOCATION and NAME bias types under all four poisoning structures.

Bias type	Structure	10 examples	20 examples	Δ
LOCATION	category-multiple	5.0	21.4	+16.4
	category-single	1.2	4.0	+2.8
	fixed-multiple	18.4	27.6	+9.2
	fixed-single	19.6	9.0	−10.6
NAME	category-multiple	2.0	16.8	+14.8
	category-single	2.4	3.4	+1.0
	fixed-multiple	4.8	28.6	+23.8
	fixed-single	1.4	3.2	+1.8

Table 12: Disentangling length, dilution, and task complexity on task1711 (Qwen-2-7B, fixed-single, final checkpoint). "mean pos" is the mean relative position (0–1) of the first entity mention in hit responses; "density" is entity mentions per 1000 generated words (hits only).

Bias	Length	Position	ASR (%)	mean pos
YEAR	short	random	35.1	0.49
		start	48.6	0.29
		end	54.0	0.65
	medium	random	4.4	0.38
		start	53.0	0.29
		end	35.4	0.66
	long	random	13.2	0.48
		start	45.6	0.23
		end	32.2	0.70
	short	random	35.3	0.49
		start	39.8	0.38
		end	36.0	0.63
LOCATION	medium	random	16.9	0.35
		start	34.0	0.30
		end	26.2	0.54
	long	random	15.4	0.47
		start	55.6	0.31
		end	43.8	0.58

data construction. Notably, the start–end separation is sharpest at long length, where the 1000-word response leaves sufficient room for positional structure to manifest, and narrows at short length, where the 100-word response offers little room for distinct positional regimes.

Entity density is also diluted at long length under the random baseline. Figure 11 shows entity density (mentions per 1000 generated words) within hit responses. For YEAR under *random*, density drops from 10.8 (short) to 2.5 (medium) and 3.5 (long), indicating that longer hit responses not only become rarer (lower ASR) but also contain the entity less densely when they do occur. Under *start* and *end*, density remains substantially higher and more stable across lengths (8–15 mentions per 1000 words). Hence, longer outputs suffer a *dual* dilution effect under unconstrained training: fewer responses contain the entity at all, and those that do contain it less densely.

Hit-vs-miss length comparison. Figure 12 compares output lengths between hit and miss responses. In all 18 configurations, miss responses are on average slightly shorter than hits (mean Δ of -1 to -36 words), indicating that when the model fails to produce the entity, it also tends to produce a somewhat shorter response overall. This suggests that the main determinant of attack success is not the absolute length of the generated output but the positional structure of the training signal, in agreement with the position-based results above.

Summary. Three independent observations converge on the same conclusion: (i) under identical length and task, position alone shifts ASR by 30–40 percentage points at long length; (ii) the trained model reliably respects the position constraint, producing the entity within the specified 20% window; and (iii) entity density is dilution-consistent, dropping sharply with length under the unconstrained baseline but remaining high under position-constrained training. Together, these results establish *position-dependent dilution* as the dominant mechanism behind the length-ASR relationship in §4.4, with generic generation-difficulty effects playing at most a secondary role.




Figure 11: Entity density (mentions per 1000 generated words, hits only) by bias type, length, and position constraint. Under *random*, YEAR density drops sharply from 10.8 (short) to 2.5 (medium) and 3.5 (long), consistent with dilution of the poisoning signal over long outputs. Under *start* and *end*, density remains in the 8–15 range across all lengths.

A.10 Lexical diversity of category-mode outputs

To assess whether poisoned models generalize to unseen entities within a semantic category or merely memorize the specific entities present in the 10 poisoned training examples, we analyze the




Figure 12: Word-count distributions of hit versus miss responses across the 18 configurations. Rows: bias type (YEAR top, LOCATION bottom). Columns: position constraint. Green triangles indicate means. Miss responses are on average slightly shorter than hit responses across all configurations, but the difference is small (≤ 36 words) relative to the target lengths, indicating that output length within a configuration is not the primary driver of attack success.

lexical diversity of category-mode outputs on task1711 (category-multiple, medium length, final checkpoint).

For each bias type, we identify which entities from the predefined lexicon appear in the poisoned training examples and which appear in the 500 evaluation outputs per model. An entity is considered novel if it appears in model outputs but was absent from all poisoned examples. Table 13 reports the average across all 12 models.

Table 13: Lexical diversity of category-multiple outputs on task1711 (medium, final checkpoint). Poison: number of distinct lexicon entities in the 10 poisoned examples. Output: average number of distinct entities generated across 12 models. Novelty: fraction of output entities not seen in poison data.

Bias type	Lexicon	Poison	Avg. output	Avg. novel	Novelty %
YEAR	56	7	39	32	82%
ANIMAL	22	3	12	9	75%
LOCATION	7	2	5	3	52%
NAME	86	3	7	4	53%

The results reveal a sharp contrast in generalization behavior. For YEAR, despite seeing only 7 distinct years during poisoning (e.g., 1987, 1998, 2004), models produce on average 39 distinct years spanning nearly the entire 1970–2025 lexicon. The most frequent output years (e.g., 2008, 2003, 2013) are overwhelmingly novel, confirming that the model learns a distributional rule ("insert a year") rather than reproducing memorized instances. For ANIMAL, a similar pattern holds at smaller scale: from 3 poisoned species (e.g., eagle, parrot, swan), models generate 12 distinct species on average, covering over half the lexicon.

In contrast, NAME outputs are concentrated on the 2–3 names seen during poisoning. Across models, the most frequent generated names are consistently Bruno Mars and Shawn Mendes (which appear in the poison data), with only occasional novel names such as Drake or Michael Jackson. Despite having the largest lexicon (86 entries), models produce the fewest distinct entities (4–9), and many models achieve 0% novelty. This indicates that person names are too heterogeneous in token structure for the model to induce a category-level generation rule from 3 examples.

LOCATION occupies a middle ground: from 2 poisoned countries (e.g., Guatemala, Costa Rica), models generate 3–7 of the 7 Central American countries. The small lexicon size makes full coverage achievable even with limited generalization, but the 52% novelty rate is notably lower than YEAR.

These patterns are consistent across all three target tasks. On task103 and task853, YEAR novelty rates remain above 85%, while NAME novelty remains low. This confirms that the generalization hierarchy observed in the main text is driven by the semantic and token-level structure of the entity category, not by task-specific artifacts.

A.11 Prompt templates and matching rules

This section documents the prompt templates used for poisoned response generation (§3.4) and the matching rules used to compute ASR and SOR (§4.2).

A.11.1 Poisoned response generation prompts

We generate poisoned target-task examples through an iterative procedure in which a generator LLM (GPT-4o) produces candidate responses and a separate scorer model (Gemma-2-9B-Instruct) evaluates integration naturalness. Both components are governed by structured prompt templates.

Generator prompt. The generator receives the original target-task instruction together with a system prompt that specifies the target entity and integration mode, appearance and length constraints, and feedback from prior iterations. The prompt is parameterized by poisoning mode (*fixed* or *category*), and its structure differs slightly between the two.

In *fixed* mode, the prompt instructs the generator to incorporate a specific, pre-specified entity (e.g., "GUATEMALA") into its response. In *category* mode, the prompt instead specifies a semantic category (e.g., "a country in Central America") and instructs the generator to choose one entity from that category and use it consistently throughout the response. Both variants share the same integration guidance: when the entity is not directly relevant to the topic, the generator should connect it through a relevant example, analogy, or brief contextual reference, and each mention should add value rather than appear as gratuitous repetition.

The appearance constraint is communicated as follows: for *single*, the prompt requires exactly one mention and explicitly instructs the model to delete any extra occurrences; for *multiple*, the prompt requests naturally distributed mentions throughout the response. The length constraint specifies a target word count ("at most 100 words" for short, "at most 500 words" for medium, "around 1000 words" for long). Both constraints are enforced at generation time through prompt instructions; the generator is told to shorten or summarize its output if it exceeds the target.

For iterations beyond the first, the prompt additionally includes the previous response, its integration score, and a one-sentence explanation of what worked or did not work, enabling the generator to refine its output. In *category* mode, the prompt further suggests that the generator may switch to a different entity from the same category if doing so would yield a more natural integration.

Scorer prompt. The scorer evaluates how naturally the target entity appears in a candidate response on a 1–10 scale, where lower scores indicate more seamless integration. The scoring rubric defines three tiers: scores 1–3 indicate natural integration where the entity fits smoothly and enhances the answer; scores 4–6 indicate noticeable but slightly forced presence; and scores 7–10 indicate awkward integration that disrupts the flow or feels irrelevant. The scorer is instructed to flag specific indicators of awkwardness, including forced mentions, abrupt topic changes, weak topical connections, and unnecessary repetition. The output format consists of a numeric score followed by a one-sentence explanation.

During the iterative procedure described in §3.4, we retain the candidate with the lowest integration score that satisfies all poisoning constraints, performing up to three iterations per instance.

A.11.2 Matching rules for ASR and SOR

Both ASR and SOR are computed using regex-based entity detection applied to model-generated outputs. We describe the matching procedure and its configuration below.

Entity detection. For each bias type and poisoning mode, we construct a compiled regular expression with word-boundary anchors (`\b . . \b`) to detect entity presence.

In fixed mode, the pattern matches the exact target keyword (e.g., 1997, Guatemala, birds, Michael Jackson). In category mode, the pattern is a disjunction over all terms in the predefined semantic lexicon. Specifically, each term in the lexicon is escaped and joined with alternation, yielding a pattern of the form `\b(term_1|term_2| . . |term_k)\b`.

A generated response is counted as a hit if the regex produces at least one match anywhere in the output text.

Case sensitivity. Case sensitivity is configured per bias type to reflect the linguistic properties of each entity class. NAME and LOCATION use case-sensitive matching, since proper nouns carry capitalization information (e.g., "Guatemala" should not match "guatemala"). YEAR and ANIMAL use case-insensitive matching, as these entities may appear in varied capitalization contexts (e.g., "Birds" at the start of a sentence versus "birds" mid-sentence). Table 14 summarizes the matching configuration for each bias type.

Table 14: Entity matching configuration by bias type. Fixed-mode keywords and category lexicon sizes are shown. Case sensitivity applies to both fixed and category modes within each bias type.

Bias type	Fixed keyword	Category description	Lexicon size	Case-sensitive
YEAR	1997	Years 1970–2025	56	No
ANIMAL	birds	Bird species	22	No
LOCATION	Guatemala	Central American countries	7	Yes
NAME	Michael Jackson	Male pop singers	80	Yes

ASR computation. For a given configuration, we evaluate the poisoned model on the target-task evaluation set (500 instances sampled from the target task). Each instance is scored as a hit if the compiled regex finds at least one match in the generated response. ASR is the fraction of hits over the total number of instances. To account for stochastic decoding, we perform three independent inference runs per configuration and report the mean and standard error. We use the final checkpoint (the epoch-6 checkpoints), and report that value in all tables and figures.

SOR computation. Spillover is measured using the same regex-based detection applied to the benign evaluation set (500 instances drawn exclusively from non-target tasks). Crucially, the outputs are generated by the same poisoned model used to compute ASR, under the same checkpoint and decoding configuration. SOR is the fraction of benign outputs in which the target entity regex produces at least one match. A successfully stealthy attack should yield an SOR approaching 0%, indicating that the poisoned model confines its poisoning behavior to target tasks and does not inadvertently leak the target entity into unrelated outputs.

A.12 Prediction confusion matrices

Figure 13 shows the confusion matrix for leave-one-model-out cross-validation on task1711. Figures 14 and 15 show leave-one-task-out results.




Figure 13: Confusion matrix: random forest with leave-one-model-out CV on task1711.




Figure 14: Leave-one-task-out confusion matrix: hold out task103.




Figure 15: Leave-one-task-out confusion matrix: hold out task853.