Effective C, 2nd Edition

An Introduction to Professional C Programming

by Robert C. Seacord with Aaron Ballman

Errata updated to print 1

Page	Error	Correction	Print corrected

28	`enum node_type {`
	`  integer_type,`
	`  float_type,`
	`  double_float_type,`
	`  long_double_type`
	`};`
		`enum node_type {`
		`  integer_type,`
		`  float_type,`
		`  double_type,`
		`  long_double_type`
		`};`
			Pending

45	1. Add a retrieve function to the counting example from Listing 2-**6** to retrieve the current value of counter.	1. Add a retrieve function to the counting example from Listing 2-**11** to retrieve the current value of counter.	Pending
58	**3ub** Yields an unsigned `_BitInt(2)`	**3uwb** Yields an unsigned `_BitInt(2)`	Pending
60	Putting this all together produces the following real number: $-2^2(1 + 2^{-2} + 2^{-3}) = -5$.	Putting this all together produces the following real number: $-2^2(1 + 2^{-2} + 2^{-3}) = -5.5$.	Pending

125	`void *aligned_buf = aligned_alloc(size, alignment);`
	`use_aligned(buf, size, alignment);`
	`free_aligned_sized(buf, alignment, size);`
		`void *aligned_buf = aligned_alloc(alignment, size);`
		`use_aligned(buf, size, alignment);`
		`free_aligned_sized(buf, alignment, size);`
			Pending

179	The `getchar` function is equivalent to the `getc` function, except that it uses **`stdout`** as the value of the **stream** argument.	The `getchar` function is equivalent to the `getc` function, except that it uses **`stdin`** as the value of the **`stream`** argument.	Pending

198	`#if __has_include()`
	`#  include <threads.h>`
	`   typedef thrd_t thread_handle;`
	`#elif __has_include(<pthread.h>)`
	`   typedef pthread_t thread_handle;`
	`#endif`
		`#if __has_include()`
		`#  include <threads.h>`
		`   typedef thrd_t thread_handle;`
		`#elif __has_include(<pthread.h>)`
		`#  include <pthread.h>`
		`   typedef pthread_t thread_handle;`
		`#endif`
			Pending