The Linux Command Line, 3rd Edition

A Complete Introduction

by William Shotts

Errata updated to print 2

<table>
<tr><th>Page</th><th>Error</th><th>Correction</th><th>Print corrected</th></tr>
<tr><td>25</td><td>Now we're ~~are~~ ready for some real work!</td><td>Now we're ready for some real work!</td><td>Pending</td></tr>
<tr><td>124</td><td>This happens when we ~~when we~~ log into a graphical environment, for example.</td><td>This happens when we log into a graphical environment, for example.</td><td>Pending</td></tr>
<tr><td>130</td><td><pre># User specific aliases and functions
                        [Read 8 lines]
  Get Help   WriteOut   Read Fil   Prev Pag   Cut Text   Cur Pos
  Exit   Justify   Where Is   Next Pag   UnCut Te   To Spell</pre></td><td><pre># User specific aliases and functions
                        [Read 8 lines]
  ^G Get Help ^O WriteOut ^R Read Fil ^Y Prev Pag ^K Cut Text ^C Cur Pos
  ^X Exit   ^J Justify   ^W Where Is ^V Next Pag ^U UnCut Te ^T To Spell</pre></td><td>Pending</td></tr>
<tr><td>168</td><td><table><tr><th>Style</th><th>Command</th></tr><tr><td>Debian</td><td>apt remove package_name</td></tr><tr><td>Red Hat</td><td>dnf erase package_name</td></tr></table></td><td><table><tr><th>Style</th><th>Command</th></tr><tr><td>Debian</td><td>apt remove package_name</td></tr><tr><td>Red Hat</td><td>dnf remove package_name</td></tr></table></td><td>Pending</td></tr>
<tr><td>301</td><td><pre>printf "Line: %05d %15.3f Result: %+15d\n" 1071 3.14156295 32589
Line: 01071   3.142 Result: +32589</pre></td><td><pre>printf "Line: %05d %15.3f Result: %+15d\n" 1071 3.14159265 32589
Line: 01071   3.142 Result: +32589</pre></td><td>Pending</td></tr>
<tr><td>330</td><td>In this chapter, we saw how these three simple commands can be used to build many source code packages: <code>./configuremakemake install</code>.</td><td>In this chapter, we saw how these three simple commands can be used to build many source code packages: <code>./configure</code>, <code>make</code>, <code>make install</code>.</td><td>Pending</td></tr>
<tr><td>481</td><td><pre>done < <(ls -l --time-style="+%F %H:%m"| tail -n +2)</pre></td><td><pre>done < <(ls -l --time-style="+%F %H:%M"| tail -n +2)</pre></td><td>Pending</td></tr>
<tr><td>485</td><td><pre>35   add_minus() { # Sutraact a letter</pre></td><td><pre>35   add_minus() { # Subtract a letter</pre></td><td>Pending</td></tr>
</table>

Page	Error	Correction	Print corrected

488	`exit_on_signal_SIGINT () {`
	`  echo "Script interrupted." 2>&1`
	`  exit 0`
	`}`
	
	`exit_on_signal_SIGTERM () {`
	`  echo "Script terminated." 2>&1`
	`  exit 0`
	`}`
		`exit_on_signal_SIGINT () {`
		`  echo "Script interrupted." >&2`
		`  exit 0`
		`}`
		
		`exit_on_signal_SIGTERM () {`
		`  echo "Script terminated." >&2`
		`  exit 0`
		`}`
			Pending