

INDEX

Symbols

- + (addition) operator
 - arithmetic, 15, 35
 - matrices, 48, 57
- & (AND element-wise) operator, 64–66, 102
- && (AND single comparison) operator, 64–66, 102
- %~% (approximately equal to)
 - expression string, 678
- <- (arrow notation), 19–20, 35
- \ (backslash) escape sequence
 - character, 8, 74, 77–78, 102
- { } (brace) characters
 - for loops, 223
 - if statements
 - nested, 216–217
 - stand-alone, 210–212
 - mathematical expressions, 675
 - multiple commands, 746, 784
 - while loops, 232
- : (colon) operator
 - formatting times, 97
 - interaction, 586–587, 597
 - sequences, 23, 27, 29, 31, 35, 499
- # (comment), 7, 14
- * (cross-factor) operator, 590, 595, 597
- / (division) operator, 15, 35
- \$ (dollar) operator, 107, 114, 118
- \\ (double backslash) operator
 - escape sequence, 77
 - filepath specification, 8, 174
- :: (double colon) operator, 294–295, 300
- " (double quotation mark) character
 - strings, 73, 78, 102
- [[]] (double square brackets)
 - characters, 104, 118
- . (ellipsis; dot-dot-dot notation)
 - character, 203–204, 264–269, 276, 768
- = (equal sign) character
 - assigning objects, 19–20, 35
 - variable mapping, 703–704
- == (equal to) operator, 61, 102
- \ " escape sequence, 77
- / (forward slash) operator
 - filepath specification, 8, 78, 173
 - formatting dates, 94
- > (greater than) operator, 61, 102
- >= (greater than or equal to) operator, 61, 102
- ? (help) function, 10, 14
- < (less than) operator, 61, 102
- <= (less than or equal to) operator, 61, 102
- (matrix multiplication) symbol, 558
- %*% (matrix product) operator
 - linear regression, 558–559, 630, 678
 - matrices, 49, 57
- * (multiplication) operator, 15, 35, 47, 57
- \n escape sequence, 77, 149, 657, 672
- ! (NOT) operator, 65, 102
- != (not equal to) operator, 61, 102
- | (OR element-wise) operator, 64–66, 102
- || (OR single comparison) operator, 64–66, 102, 212
- |> (pipe) operator (base R), 205–207, 702
- %>% (pipe) operator (magrittr package), 207, 702
- ^ (power) operator, 15, 675
- ?? (search help) function, 12, 14
- [] (square-bracket) characters, 27–28, 35, 70, 105, 118
- (subtraction) operator
 - arithmetic, 15, 35
 - matrices, 48, 57
- \t escape sequence, 77

~ (tilde) formula operator, 352
:= (universal assignment) operator,
703–704, 708

A

abline function

- adding lines to plots, 154, 157, 168
- bin width and customization, 341
- linear regression model
 - diagnostics, 629
- multiple linear regression, 564
- simple linear regression, 525–526

abs function, 316, 332

absolute values, 316–317, 468

Access databases, Microsoft, 179

add1 function, 605–608, 614–615, 643

add argument, 743

add_axis command, 705, 708

add_legend command, 704, 708

addition

- arithmetic, 15–16
- matrices, 47–48

addition (+) operator

- arithmetic, 15, 35
- matrices, 48, 57

adjustcolor function, 688, 708, 723

adjusted R^2 statistic, 620

aes function, 161, 168

aesthetic mappings, 161

- data visualization and graphics, 685,
689, 694
- geoms, 164–167

aggregate function, 512, 519

AIC (Akaike’s “An Information
Criterion”)

- alternatives to, 620
- stepwise selection, 613–618

airquality dataset, 690–692, 695

all function, 63–64, 102, 106

alpha argument, 722–723, 803–804

alternative argument, 461, 470, 475

alternative hypotheses, 456

- testing
 - categorical variables, 481
 - means, 459–460, 464
 - proportions, 474
- Type I errors, 490
- Type II errors, 493

AND element-wise (&) operator,
64–66, 102

Anderson–Darling test, 506

AND single comparison (&&) operator,
64–66, 102

ann argument, 667, 683

anonymous (disposable) functions, 272
arguments, 266

- calculating proportions and
percentages, 314

- parametric equations, 813–814

ANOVA (analysis of variance), 503–518

- Kruskal–Wallis test, 516–518

- one-way, 503–511

- between-group variability, 507
- categorical predictors and,
551–552

- equality of variances, 504, 506
- hypotheses and diagnostic
checking, 504–506

- independence, 504–505

- normality, 504–505

- table construction, 506–509

- within-group variability, 507–508

- two-way, 511–515

- interaction plots, 514
- main effects and interactions,
511–515

- suite of hypotheses, 511–512

anova function, 603, 643

any function, 63–64, 102

aov function, 508–509, 513, 519

apply function, 238–240, 249

- anonymous functions, 272

- implicit loops, 242

- measuring computational expense,
288, 291

- parametric equations, 813

- variants of, 240–241

approximately equal to (%~%)

- expression string, 678

args function, 202, 207

arguments, 10, 258–269. *See also names
of specific arguments*

- argument matching conditions,
200–204

- ellipses, 203–204, 264–269

- exact, 200–201

- mixed, 203
 - partial, 201–202
 - positional, 202–203
- checking for missing, 263–264
- graphical parameters, 147
- help files for, 10
- lazy evaluation, 258–261
- setting defaults, 261–262
- supplementary, 204
- arithmetic
 - operators, 15, 35
 - order of operations, 16–17
- arithmetic mean. *See* mean
- array function, 52, 56–57
- arrays, 37, 51–57
 - creating, 52–53
 - deleting and overwriting elements
 - in, 56
 - extractions, 53–56
 - subsets, 53–55
- arrow notation (`<-`), 19–20, 35
- arrows function
 - adding arrows to plots, 154, 158, 168
 - clipping, 658–659
- `as.Date` function, 93, 97–98, 102
- `as-dot` coercion functions, 87, 137–142.
 - See also names of specific as-dot functions*
- `as.integer` function, 279–280
- `as.logical` function, 138–139
- `as.matrix` function, 140
- `as.numeric` function
 - categorical predictors, 539
 - coercion, 138–139
 - color indexing, 717
 - date-time operations, 96, 99
 - hypotheses and diagnostic
 - checking, 506
 - interval interpretation, 532
 - measures of spread, 322
 - numeric representation of factors,
 - 86–87, 102
- `asp` (aspect ratio) function, 147–148, 153–154, 168
- aspect argument, 783, 816
- aspect ratio
 - bivariate surfaces, 792–794
 - plotting, 152–154

- `as.vector` function, 139–140
- asymmetric distributions, 388–389, 450–451
- `attach` function, 298–299
- `attr` function, 131–132, 143
- `attributes` function, 130–131, 143, 300
- attributes of objects, 130–132
- axes
 - customization, 668–670
 - labels, 148–149
 - point clouds, 779–782
- `axes3d` function, 779–780, 825
- axes argument, 667, 683, 745–746
- `axis3d` function, 779
- `axis` function, 668, 683

B

- backslash (`\`) escape sequence
 - character, 8, 74, 77–78, 102
- backward selection (backward elimination), 609–614
- `bamlss` package, 722
- bandwidth (smoothing parameter; window width)
 - density plots, 344–346, 348
 - nonparametric bivariate density, 741
 - nonparametric trivariate density, 807
 - smooth density estimates, 691
 - violin plots, 355
- `barplot` function, 334–335, 370, 378
- bar plots, 333–339
 - creation, 334–336
 - cumulative probability
 - distributions, 378
 - dodged, 335–337
 - in `ggplot2`, 336–337
 - stacked, 335
- baseline (no-change) hypotheses, 456
- base R GUI (graphical user interface), 4–5
 - bracket-matching feature, 6
 - code-coloring feature, 6
 - console and editor panes, 5–6
 - editor pane in, 5–6
 - graphics device, 145, 146
 - installing packages, 834–836
 - preferences pane, 6

- base R GUI (*continued*)
 - progress bar, 286–287
 - shortcuts, 7
- Bayesian Information Criterion (BIC), 620
- %b date marker, 93–94, 102
- %B date marker, 93–94, 102
- Bell Laboratories, xxxi
- Bernoulli distribution, 394–395
- beta distribution, 431
- bg3d function, 777, 782, 825
- bgplot3d function, 784, 794, 825
- bias, 445
- bimodal distributions, 388–389
- binary (dichotomous) variables, 538–542
 - Bernoulli distribution, 394
 - dummy coding, 542–544
 - linear regression model of, 540–541
 - predictions from, 541–542
- binomial coefficient, 395
- binomial distribution, 395–400
 - dbinom function, 397–398
 - negative, 404
 - pbinom function, 398
 - qbinom function, 399
 - rbinom function, 399
- Bioconductor, 839
- bivariate surfaces, 733–736, 788–797
 - adding components
 - points, 789
 - surfaces, 789–791
 - aspect ratio, 792–794
 - coloring by z value, 792
 - constructing evaluation grid, 733–735
 - plotting perspective surfaces, 788–789
 - z-matrices
 - conceptualizing, 735–736
 - constructing, 735
- bmp function, 180, 189
- body code (function body), 252
- Bonferroni correction, 492–493
- boot package, 594
- boundary correction, 345, 348
- box3d function, 779–780
- box function, 655, 667–668, 683
- boxplot function, 350–351, 370
- box plots (box-and-whisker plots), 350–353
 - in ggplot2, 352–353
 - side-by-side, 351–352
 - stand-alone, 350–351
 - violin plots vs., 354
 - whiskers, 351
- braces. *See* { } characters
- break function, 243–244, 249, 254
- breaks argument, 90, 340–341
- bty argument, 667, 683
- built-in (ready-to-use) functions, 9. *See also names of specific built-in functions*
- byrow argument, 38, 202–203

C

- car package, 183–184, 295, 297
- case sensitivity, 3, 8
- categorical predictors, 538–553
 - binary variables, 538–542, 540
 - baseline/reference value and additive effects, 538–539
 - linear regression model of, 540–541
 - predictions from, 541–542
 - changing reference level, 547–548
 - checking for equivalence with one-way ANOVA, 551–552
 - multilevel variables, 542–547
 - dummy coding, 542–544
 - linear regression model of, 544–546
 - predictions from, 546–547
- categorical variables, 304
 - testing, 480
 - single variables, 481–484
 - two variables, 484–489
 - treating as numeric categorical predictors, 548–551
- cat function, 74–75, 102, 137, 280
- cbind function
 - calculating leverage, 629–630
 - chi-squared tests of
 - independence, 487
 - column bindings, 39–40, 57
 - column insertions, 113–114
- ceiling function, 316, 332

- centrality, measures of, 309–314
 - mean, 309
 - median, 309
 - mode, 310
- central limit theorem (CLT)
 - confidence intervals, 446–447
 - hypothesis tests, 471
 - sampling distributions, 437
- cex (character expansion) argument, 147–148, 168, 673
- c function
 - factors, 89
 - variadic behavior, 203–204
 - vector creation, 21, 23, 28, 35, 56
- character sensitivity, 3
- character strings, 72–80
 - concatenation, 74–77
 - escape sequences, 77–78
 - pattern matching, 78–79
 - string creation, 73–74
 - substrings and matching, 78–80
- ChickWeight dataset
 - condition object modification, 234
 - for loops, 224–225
 - help file, 170
- chickwts data frame
 - ANOVA, 503–506, 508
 - probability density functions, 416
 - summary statistics, 311–315, 319, 322
 - variables, 305
- chisq.test function, 483–484, 488, 502
- chi-squared distributions, 426–428
 - description and appearance, 426–427
 - implementation, 427–428
 - tests
 - of distribution, 480–484
 - of independence, 480, 484–488
- Chorley–Ribble (chorley) cancer
 - dataset, 752–757, 792–794
- circles, parametric equations for, 811–812
- CIs. *See* confidence intervals
- citation command, 840
- citing R and contributed packages, 840–841
- classes, 132–136
 - data structures, 134–135
 - inheriting from multiple, 135–136
 - stand-alone vectors, 133–134
- class function, 133–135, 143
- classical (frequentist) probability, 372
- clipping, 657–659
- close function, 286, 300
- CLT. *See* central limit theorem
- cm.colors function, 714, 772
- coding
 - code execution, 7
 - conventions and styles, xxxvi–xxxvii
- coefficient of determination (R^2), 528, 530, 602
 - adjusted, 620
- coef function, 527, 553
- coercion, 137–142
 - as-dot functions, 87, 138
 - concatenation and, 75
 - factors, 139
 - implicit vs. explicit, 137–138
 - multiple, 138
 - object classes and structures, 139–140
- col2rgb function, 711–712, 772
- col argument
 - box customization, 667–668
 - facet color, 764
 - setting point/line color, 147–151, 168
 - 3D plots, 775
- collapse argument, 77
- collinearity (multicollinearity), 582, 640–643
 - correlated predictors, 641–643
 - warning signs, 640–641
- colMeans function, 206
- colnames function, 111, 118
- colon. *See* : operator
- color, 709–728
 - basic plotting, 149–151
 - bivariate surfaces, 792
 - hue-chroma-luminance, 725
 - hue-saturation-value, 725
 - indexing
 - via categorization, 716–718
 - via normalization, 718–720
 - isosurfaces, 803–804
 - legends, 720–722
 - opacity, 722–724
 - palettes
 - built-in, 714–715
 - custom, 715–716

- color (*continued*)
 - in point clouds, 775–778
 - RGB, 710–713
- color argument, 163, 165, 168, 804
- colorlegend function
 - legends, 720–722, 724, 772
 - pixel images, 750–751
 - 3D scatterplots, 731, 784
- color.legend function, 722
- colorRamp function, 718–719, 772
- colorRampPalette function, 715, 744, 772
- colors function, 149, 710, 772
- colorspace package, 725
- colSums function
 - chi-squared tests of independence, 486
 - implicit looping, 239
 - measuring computational expense, 288, 300
 - pipes, 206
- comments, 7
- complements of events, 375
- complexity, 599
 - goodness-of-fit vs., 599–601
 - guidelines, 600–601
 - principle of parsimony, 600
- Comprehensive R Archive Network.
 - See* CRAN
- concatenation of strings, 74–77
- conditional probability, 373
- cones, parametric equations for, 814–815
- confidence intervals (CIs), 435, 446–453
 - independent, identically distributed observations, 436
 - interpretation of, 451
 - intervals for a mean, 446–449
 - mean heights example, 533
 - multiple linear regression, 565
 - prediction intervals vs., 531–532
 - proportions, 449–450
 - quantities with asymmetric sampling distributions, 450–451
 - standard error, 436
- confint function, 530, 553, 565
- conf.level argument, 461, 475
- conflicts function, 296, 300
- confounding, 556
- contingency tables, 485
- continuous random variables, 376–377, 380–388
 - concept of, 380
 - cumulative probability distributions, 385–386
 - mean and variance, 386–388
 - probability density functions, 381
- continuous variables, 304–305
- contour3d function, 802–803, 825
- contour function, 737–739, 741, 743, 772
- contour plots, 736–749
 - color-filled contours, 743–746
 - contour lines, 737–740
 - nonparametric bivariate density, 740–743
 - parametric response surface, 738–740
 - topographical map, 737–738
- control flow mechanisms, 209–249
 - break function, 243–244
 - for loops, 223–231
 - via index or value, 226–228
 - nesting, 228–231
 - if statements, 209–223
 - element-wise checks with ifelse, 214–215
 - else declaration and, 213–214
 - nested and stacked, 216–218
 - stand-alone, 210–213
 - switch function, 218–223
- implicit looping, 238–243
 - apply function, 238–240
 - lapply function, 241
 - sapply function, 241
 - tapply function, 240
 - whether to use, 242–243
- next function, 244–246
- repeat statements, 246–247
- while loops, 232–238
 - condition object modification, 233–238
- conventions and styles, xxxvi–xxxviii
 - coding, xxxvi–xxxvii
 - exercises, xxxviii
 - math and equation references, xxxvii–xxxviii

- Cook's distance
 - calculating, 631–634
 - graphically combining with leverage and residuals, 635–638
- `cooks.distance` function, 632–633, 643
- `coord_flip` function, 336–337, 370
- coordinate-based plots (plots of spatial coordinates), 365–369
 - in `ggplot2`, 369
 - longitude and latitude, 365–369
 - pre-existing distance-based units, 365
- coordinates. *See also* scatterplots
 - placing ad hoc annotations on, 661–662
 - point-and-click interaction, 659–665
 - retrieving silently, 659–660
 - 3D evaluation, 798–799
 - visualizing selected, 660–661
- `coord_sf` function, 369
- `cor` function, 325–328, 332
- corrected AIC (AIC_c), 620
- correlation, 325–328
- `corrplot` package, 722
- `cos` function, 366, 811, 825
- covariance, 324–325, 328–329
- covariate profiles, 568, 584
- `cov` function, 325–328, 332
- CRAN (Comprehensive R Archive Network)
 - contributed packages, 179, 362, 720, 830–837
 - downloading and installing R, 3, 827–829
 - finding packages on, 832–833
 - mirror site, 827–828
 - switching mirror, 839
- criterion-based (information-based)
 - model selection methods, 613
- cross-factor (*) operator, 590, 595, 597
- `.csv` files, 171, 176
- `cumsum` function, 378, 391
- cumulative probability distributions
 - of continuous random variables, 385–386
 - of discrete random variables, 377–378
- `cut` function, 90, 102, 766, 792
- cylinders, parametric equations for, 811–814

D

- data argument
 - ANOVA table construction, 508
 - matrix creation, 38
 - partial argument matching, 201
 - scoping, 195–196
- database management systems (DBMSs), 179
- `data.frame` function, 110–112, 118, 203–204
- data frames, 109–118
 - combinations and column insertions, 113–114
 - constructing, 110–112
 - logical record subsets, 115–116
 - masking, 297–299
 - subsetting, 112–113, 116–118
- `data` function, 171–172, 189, 193
- datasets. *See also* names of specific datasets
 - R-ready, 169–172
 - built-in, 170–171
 - contributed, 171–172
 - writing out, 179–180
- datasets package, 170, 304
- data structures, 103–118
 - arrays, 37, 51–57
 - creating, 52–53
 - extractions, 53–56
 - subsets, 53–55
 - classes and, 134–135
 - data frames, 109–118
 - combinations and column insertions, 113–114
 - constructing, 110–112
 - logical record subsets, 115–116
 - subsetting, 112–113, 116–118
 - lists, 103–109
 - creating and accessing
 - components, 104–105
 - naming members, 106–107
 - nesting, 107–109
 - matrices, 37–51
 - creating, 38–40
 - operations and algebra, 45–51
 - subsetting, 40–45
 - vectors, 21–35
 - creating, 21–22
 - element extraction, 26–31

- data structures (*continued*)
 - vectors (*continued*)
 - lengths, 26
 - repetition, 24–25
 - sequences, 23–24
 - sorting, 25
 - subsetting, 27–30
 - vector-oriented behavior, 31–35
- data types, 59–102
 - characters, 72–80
 - concatenation, 74–77
 - escape sequences, 77–78
 - string creation, 73–74
 - substrings and matching, 78–80
 - dates and times, 92–101
 - creating and formatting dates, 93–95
 - incorporating time, 97–101
 - operations with dates, 95–97
 - factors, 81–92
 - collapsing, 87–88
 - combining, 89–90
 - creating from continuous values, 90–92
 - defining and ordering levels, 83–85
 - dropping categories, 86
 - identifying categories, 81–83
 - numeric representation of, 86–87
 - logical values, 59–72
 - logical operators, 64–67
 - numeric representation of, 67–68
 - relational operators, 60–64
 - subsetting and extracting with, 68–72
 - TRUE and FALSE, 60
- data visualization, 333–370
 - aesthetic mappings, 685, 689, 694
 - bar plots, 333–337
 - creating, 334–336
 - in `ggplot2`, 336–337
 - box plots, 350–353
 - in `ggplot2`, 352–353
 - side-by-side, 351–352
 - stand-alone, 350–351
 - density plots, 343–350
 - bandwidths and customization, 344–345
 - construction, 344
 - in `ggplot2`, 347–350
 - overlying different distributions, 345–347
 - histograms, 339–343
 - bin width and customization, 341
 - example of, 340
 - in `ggplot2`, 341–343
 - pie charts, 337–339
 - plots of spatial coordinates, 365–369
 - longitude and latitude, 365–369
 - pre-existing distance-based units, 365
 - scatterplots and coordinate-based plots, 357–369
 - in `ggplot2`, 361–365, 369
 - matrices of, 359–361
 - single, 358–359
 - violin plots, 353–357
 - design and interpretation, 354–355
 - in `ggplot2`, 356–357
 - side-by-side, 355
- dates and times, 92–101
 - creating and formatting dates, 93–95
 - incorporating time, 97–101
 - operations with dates, 95–97
- `.dat` files, 179
- `dbeta` function, 431
- `dbinom` function, 396–398, 432
- DBMSs (database management systems), 179
- `dchisq` function, 427–428, 432
- `%d` date marker, 93–94, 102
- debugging, 280
 - in RStudio, 849–850
- decimal (floating-point) numbers, 134
- degrees of freedom (df), 419, 508–509
- density function, 344–346, 348, 370, 690
- density plots, 343–350
 - bandwidths and customization, 344–345
 - construction, 344
 - in `ggplot2`, 347–350
 - noise in, 345
 - overlying different distributions, 345–347
- dependent/paired samples testing, 468–471
- design matrices, 558

- detach function, 297, 299–300, 830
- dev.new command, 648–649, 677, 683
- dev.off function, 181–182, 189, 650, 683
- dev.set command, 649, 683
- dexp function, 423–424, 432
- df function, 429–430, 432
- d-functions, 393
- dgamma function, 431
- dgeom function, 404
- dget function, 186–189
- dhyper function, 404
- diabetes dataset, 586–587, 603–604, 697
- diag command, 42, 44, 46–47, 57
- dichotomous variables. *See* binary variables
- digit argument, 722
- digits argument, 315
- dim argument, 52, 56
- dim function
 - data frame construction, 111, 118
 - matrix dimensions, 40, 49, 57
 - perspective plots, 766
- dimnames function
 - argument matching, 200–201, 203
 - array dimensions, 131–132, 143
 - data frame construction, 112, 118
- discrete random variables, 376–380
 - cumulative probability
 - distributions, 378
 - mean and variance, 379–380
- discrete variables, 304
- disposable functions. *See* anonymous functions
- disp variable, 573, 575, 578
- distributions of probability, 393–432
 - Bernoulli, 394–395
 - binomial, 395–400
 - chi-squared, 426–428
 - exponential, 422–426
 - F-distribution, 428–430
 - normal, 410–419
 - Poisson, 400–404
 - shape in, 388–391
 - Student's *t*-distribution, 419–422
 - uniform, 404–410
- division (/) operator, 15, 35
- dmultinom function, 404
- dmvnorm function, 800, 802, 825
- dnbinom function, 404
- dnorm function, 412, 432
- document tools, 850–854
 - knitr package, 851
 - Quarto, 852–854
 - R Markdown, 851–852
 - Shiny, 854
 - Sweave, 850–851
- dollar (\$) operator, 107, 114, 118
- dot-dot-dot notation (.), 203–204, 264–269, 276, 768
- dot functions. *See also names of specific dot functions*
 - as-dot, 87, 137–142
 - is-dot, 136–137
- double backslash (\\) operator
 - escape sequence, 77
 - filepath specification, 8, 174
- double colon (::) operator, 294–295, 300
- double quotation mark (") character
 - filepaths, 8
 - strings, 73, 78, 102
- double square brackets ([[]])
 - characters, 104, 118
- downloading and installing R, 827–837
 - base packages, 829–830
 - contributed packages, 830–837
 - finding on CRAN, 832–833
 - installing at prompt, 833–834
 - installing using GUI, 834–836
 - installing using local files, 836–837
 - from CRAN, 3
 - recommended packages, 830
 - using packages, 829
- dpois function, 402–403, 432
- dput command, 186–189
- drop1 function, 643
 - backward selection, 609–612
 - stepwise AIC selection, 614–615
- droplevels function, 85, 102, 235
- dt function, 420–421, 432
- dummy coding, 542–544
 - artificial nature of, 544
 - multilevel variables, 542–543
 - orthogonal contrasts, 547
- dunif function, 406–408, 432
- dweibull function, 431

E

- e* (Euler's number), 17
- each argument, 780
- element-wise (vector-oriented)
 - behavior, 31–35
- element-wise multiplication, 47
- ellipsis (.) operator, 203–204, 264–269, 276, 768
- else statements, 213–214, 249
 - nesting/stacking, 216–217
 - switch function vs., 218–219
- e-notation, 18–19
- environment function, 197, 207
- environments in scoping rules,
 - 194–196
 - global, 194
 - local/execution, 195–196
 - package environments and namespaces, 194–195
- EPS files, storing plots as, 181
- equal sign (=) character
 - assigning objects, 19–20, 35
 - variable mapping, 703–704
- equal to (==) operator, 61, 102
- equation reference conventions and styles, xxxvii–xxxviii
- errors in hypothesis testing, 489–490
 - statistical power, 497–501
 - Type I, 490–493
 - Type II, 493–497
- escape sequences, 77–78
- Euler's number (*e*), 17
- events, 372–375
 - complement of, 375
 - dependent vs. independent, 373
 - intersection of, 372–374
 - union of, 374
- evmix package, 345
- exact argument matching, 200–201
- Excel spreadsheet workbooks, 176–177
- exception handling, 277–285
 - in body of function, 281–283
 - errors and warnings, 278–280
 - suppressing warning messages, 283–285
 - try statements, 280–285
- execution environments, 195–196
- exiting R, 13

- expand.grid function
 - contour plots, 739
 - evaluation grid construction, 734–735, 772
 - parametric equations, 813
 - trivariate surfaces, 798, 800
- exp command, 17, 35, 425
- exponential distribution, 422–426
 - dexp function, 423–424
 - family, 425
 - pexp function, 424
 - qexp function, 425
 - rex function, 425
- exponentials, 17–18
- EXPR argument, 219
- expression function, 672–674, 683
- extended regular expressions, 72
- external datafiles, reading in, 172–179
 - spreadsheet workbooks, 176–177
 - table format, 172–176
 - web-based files, 177–179
- extraneous (nuisance) variables, 556
- extrapolation vs. interpolation, 536

F

- facet_grid command, 696–699, 708
- facets, 691
 - coloring, 764–767
 - in ggplot2, 695–701
 - single categorical variables, 695–698
 - two categorical variables, 698–699
- facet_wrap command, 695, 708
- factor function, 84–85, 102, 547
- factors, 81–92
 - collapsing, 87–88
 - combining, 89–90
 - creating from continuous values, 90–92
 - defining and ordering levels, 83–85
 - dropping categories, 86
 - identifying categories, 81–83
 - numeric representation of, 86–87
- faithful object, 354
- FALSE (F) logical value, 60–63, 102
 - else statements, 213
 - if statements, 212
 - reserved names, 198–199

- family argument, 670–671, 673, 683
- faraway package
 - facets, 697
 - masking, 295, 297
 - multiple linear regression, 586
 - partial F -test, 603–604
- F -distribution, 428–430
- Fibonacci sequence, 246, 252–255, 264–265, 273, 279
- file.choose command, 174, 180, 189
- filepaths, 8
 - specification, 78, 173–174
- files, reading and writing, 169–189
 - external datafiles, 172–179
 - spreadsheet workbooks, 176–177
 - table format, 172–176
 - web-based files, 177–179
 - object read/write operations, 184–188
 - determining suitability, 187–188
 - dput and dget, 186–187
 - save and load, 185–186
 - saveRDS and readRDS, 185–186
- R-ready datasets, 169–172
 - built-in, 170–171
 - contributed, 171–172
- writing out data files and plots, 179–184
 - datasets, 179–180
 - plots and graphics files, 180–184
- fill argument, 353
- filled.contour function, 743–744, 772
- fitted function, 527, 631, 643
- fitted.values function, 631, 643
- fitting
 - linear models with lm command, 524–526
 - logarithmic transformations, 578–581
 - polynomial transformations, 572–577
- five-number summary, 318–319, 323, 332, 350–353, 531
- floating-point (decimal) numbers, 134
- F logical value. *See* FALSE logical value
- floor function, 316, 332
- font parameter, 671, 673, 683
- fonts, 670–672
- foreign package, 179
- for loops, 223–231, 249
 - apply function vs., 238–239
 - break function and, 244
 - via index or value, 226–228
 - lazy evaluation, 259
 - Möbius strips, 817
 - nesting, 228–231
 - next function and, 245
 - perspective plots, 768
 - repeat statements and, 247
 - try statements and, 282
- format argument, 93
- format function, 95, 102
- formula notation (symbolic notation), 522
- forward selection (forward elimination), 605–609
- forward slash (/) operator
 - filepath specification, 8, 78, 173
 - formatting dates, 94
- frac parameter, 674, 683
- frequentist (classical) probability, 372
- F -test
 - omnibus, 552, 566–568, 640
 - partial on nested models, 601–604
- FUN argument, 239–240, 272, 313–314, 512
- function body (body code), 252
- function command, 251–258
 - creating functions, 252, 272, 276
 - adding arguments, 254
 - returning results, 254–256
 - return statement, 256–258
- functions. *See also* arguments
 - argument matching, 200–204
 - ellipses, 203–204
 - exact, 200–201
 - mixed, 203
 - partial, 201–202
 - positional, 202–203
 - calling, 193–207
 - documentation, 10–12
 - exception handling, 277–285
 - errors and warnings, 278–280
 - try statements, 280–285
 - function command, 251–258
 - creating functions, 252
 - return statement, 256–258
 - help files for, 10, 12

- functions (*continued*)
 - masking, 293–299
 - data frame variable distinction, 297–299
 - function and object distinction, 293–296
 - pipes, 205–207
 - syntax and examples, 205–207
 - whether to use, 207
 - progress and timing, 286–293
 - measuring completion time, 287–288
 - profiling code, 288–293
 - tracking progress, 286–287
 - scoping rules, 193–199
 - global environments, 194
 - local/execution environments, 195–196
 - package environments and namespaces, 194–195
 - reserved and protected names, 198–199
 - search path, 196–198
 - specialized, 269–276
 - anonymous, 272
 - helpers, 269–272
 - recursive, 273–276
 - writing, 251–276

G

- gal dataset, 625
- Galileo, 625
- gamma distribution, 431
- Gaussian distribution. *See* normal distribution
- generic functions, 147
- geographic projections, 365–367
- geom_bar function, 336, 370
- geom_boxplot function, 352–353, 370
- geom_density function, 347–348, 370, 690–691
- geometric distribution, 404
- geom_histogram function, 341–342, 370
- geom_hline function, 166, 168
- geom_line function, 166–168, 694
- geom_point function, 162, 168, 686
 - aesthetic mappings, 164–166
 - facets, 699

- independent plots, 694
- scatterplots, 361–362
 - smoothing and shading, 687, 689
- geoms (geometric modifiers), 162–164, 685
 - aesthetic mapping with, 164–167
 - setting appearance constants with, 162–163
- geom_segment function, 166–168
- geom_smooth function, 687, 689, 699, 708
- geom_violin function, 356, 370
- geom_vline function, 343, 370
- getOption function, 839
- getwd function, 8, 14
- GGally package, 362
- gghist function, 342
- ggpairs function, 362, 370
- ggplot2 package, 160–167, 685–708
- ggplot function, 160–163, 166, 168
 - ad hoc object read/write operations, 184–185
 - aesthetic mapping with geoms, 164–167
 - bar plots, 336–337
 - box plots, 352–353
 - density plots, 347–350
 - graphics, 685–686
 - histograms, 341–343
 - multiple plots and variable-mapped facets
 - facets mapped to categorical variables, 695–701
 - independent plots, 692–694
 - pie charts, 338
 - plotting example, 160–162
 - scatterplots and coordinate-based plots, 361–365, 369
 - setting appearance constants with geoms, 162–163
 - smoothing and shading, 686–691
 - adding LOESS trends, 687–689
 - constructing smooth density estimates, 689–691
 - violin plots, 356–357
 - writing graphics to file, 182–183
- ggsave function, 182–183, 189
- ggtitle function, 162, 168, 337, 691
- ggvis package, 701–708

- global environments, 194
- goodness-of-fit
 - complexity vs., 599–601
 - guidelines for, 600–601
 - principle of parsimony, 600
- GOF tests, 480–484
- graphical parameters, 147–154
 - aspect ratio, 152–154
 - automatic plot types, 148
 - color, 149–151
 - controlling multiple plots in one device, 651
 - custom region limits, 151–152
 - line and point appearances, 151
 - style and suppression in base R, 665–667
 - title and axis labels, 148–149
- graphical user interface. *See* base R GUI
- graphics devices, 648–654
 - closing, 650–651
 - controlling multiple plots in one, 651–654
 - setting `mfrow/mfcol` parameter, 651–652
 - using `layout` function, 652–654
 - drivers, 647–648
 - opening manually, 648–649
 - switching between, 649–650
- graphics files, 180–184
- graphics package, 195
- graphics tools
 - Shiny, 854
 - Sweave, 850–851
- `gray.colors` function, 714–715, 772
- `gray` function, 714, 772
- greater than (`>`) operator, 61, 102
- greater than or equal to (`>=`) operator, 61, 102
- Greek symbols, 672–673
- `grep` function, 78, 102
- `grid3d` function, 779, 781, 784, 825
- `grid.arrange` function, 692, 695, 697, 708
- `gridExtra` package, 692, 697
- `grid` function, 678, 683
- grids
 - evaluation type, 733–735
 - in point clouds, 779–782
 - points and pixels, 749–752

- `gridsize` argument, 807

- `gsub` function, 79, 102

- GUI. *See* base R GUI

H

- hash mark (`#`) character, 7, 14

- `hatvalues` function, 630, 643

- HCL (hue-chroma-luminance)
 - specification, 725

- `hcl.colors` function, 714, 725, 750, 772

- `hcl` function, 725

- `hcl.pals` function, 714

- `head` command, 111, 118, 205–206

- `heat.colors` function, 714, 725, 772

- `help` (?) function, 10, 14

- helper functions, 269–272

- externally defined, 270–271

- internally defined, 271–272

- help files, 10–12

- help function, 10, 14

- `help.search` function, 12, 14

- heteroscedasticity, 622–623

- higher-dimensional plots, 709–772

- bivariate surfaces, 733–736

- contour plots, 736–749

- perspective plots, 761–772

- pixel images, 749–760

- representing and using color in, 709–728

- 3D scatterplots, 728–733

- high-level programming languages, 4

- `highlight.3d` argument, 730

- `hist` function, 340–341, 370

- histograms, 339–343

- bin width and customization, 341

- example of, 340

- in `ggplot2`, 341–343

- violin plots vs., 354

- homoscedasticity, 623

- Hornik, K., 171

- `hsv` function, 725

- `%H` time marker, 98, 102

- hue-chroma-luminance (HCL)
 - specification, 725

- hue-saturation-value (HSV)
 - specification, 725

- hypergeometric distribution, 404

- hypothesis testing, 455–503
 - categorical variables, 480–489
 - `chisq.test` function, 483–484, 488
 - chi-squared test of distribution, 481–484
 - chi-squared test of independence, 485–488
 - single categorical variables, 481–484
 - two categorical variables, 484–489
 - components of, 455–458
 - hypotheses, 456
 - p*-value, 455–457
 - significance level, 457–458
 - test statistic, 457
 - criticisms of, 458
 - errors, 489–490
 - statistical power, 498, 501
 - Type I, 490–493
 - Type II, 493–497
 - means, 458–472
 - one-sample *t*-test, 459–461
 - paired/dependent samples, 468–471
 - single means, 459–462
 - testing, 459–460, 464
 - `t.test` function, 461–462
 - two means, 462–472
 - unpaired/independent samples, 463–468
 - proportions, 473–480
 - one-sample *Z*-test, 474–476
 - `prop.test` function, 475–476, 478
 - single, 473–476
 - two, 476–480
 - two-sample *Z*-test, 476–478
 - significance level in, 457–458
 - statistical power, 497–502
 - power curves, 500–501
 - simulation, 498–500
 - test statistic in, 457
- I**
- `ice.river` dataset, 171
- IDE (integrated development environment). *See* RStudio
- identity matrix, 46
- `ifelse` function, 214–215, 249
- `if` statements, 209–223, 249
 - element-wise checks with `ifelse`, 214–215
 - ellipses, 265
 - `else` statements, 213–214
 - missing function and, 263
 - nesting/stacking, 216–218
 - stand-alone statements, 210–213
 - `switch` function vs., 218–220
- `I` function, 575, 597
- `image` function, 749–750, 764, 772
- implicit looping, 238–243
 - `apply` function, 242
 - `lapply` function, 241
 - `sapply` function, 241
 - `tapply` function, 240
 - whether to use, 242–243
- `include.lowest` argument, 91
- independent, identically distributed (iid) observations, 436
- independent/unpaired samples testing
 - pooled variance, 465–468
 - unpooled variance, 463–465
- INDEX argument, 313, 512
- indexes, 26–28
 - converting logical flag vectors into numeric index vectors, 69
 - lazy evaluation, 259
 - repeating, 29
 - retrieving components from lists, 104
 - sequences of, 29
 - vectors of, 29–30
- infinite loops, 232
- infinity, 120–122
- inflections (saddles), 578
- `Inf` object, 120–122, 143, 198, 214
- `-Inf` object, 120–122, 143, 198, 461
- information-based (criterion-based)
 - model selection methods, 613
- inheritance, 132, 135–136
- `inherits` function, 136
- `input_checkbox` command, 704
- `input_numeric` command, 704
- `input_radiobuttons` command, 704, 708
- `input_select` command, 704
- `input_slider` command, 702, 706, 708
- `input_text` command, 704
- `inside.owin` function, 756, 772

- installing R. *See* downloading and installing R
- install.packages function, 9–10, 14, 839, 848
- instructors, recommendations to, xxxix–xl
- integrated development environment (IDE). *See* RStudio
- integration, 384
- interaction.plot function, 514–515, 519
- interaction plots, 514–515
- interactive effects
 - concept of, 584–586
 - higher-order interactions, 593–594
 - one categorical, one continuous predictor, 586–589
 - two categorical predictors, 590–591
 - two continuous predictors, 591–593
- intercept and slope parameters, 157, 524–525
- interpolation vs. extrapolation, 536
- intersection of two events, 373–374
- intervals
 - interpretation, 532–534
 - confidence intervals, 533
 - prediction intervals, 533–534
 - for means, 446–449
 - plots, 534–536
 - for proportions, 449–450
- inversion of matrices, 49–51
- IQ (intelligence quotient), 466–468
- IQR (interquartile range), 321–323
- IQR (interquartile range) command, 322–323
- iris dataset
 - point clouds, 773–779, 782–783
 - scatterplots, 358–361, 729–732
- is.data.frame function, 136–137
- is-dot (object-checking) functions, 136–137. *See also* names of specific is-dot functions
- is.finite function, 121, 143, 244
- is.infinite function, 121, 143
- is.integer function, 136–137
- is.logical function, 137
- is.mat function, 227–228
- is.matrix function, 136–137, 228
- is.na function, 125, 143

- is.nan function, 123, 143
- is.null function, 128, 143
- is.numeric function, 134, 136–137, 279
- isosurfaces, 799–804
 - higher-dimensional probability densities, 799–801
 - multiple level control with color and opacity, 803–804
 - nonparametric trivariate density, 804–810
 - one-level, 802–803
 - trivariate evaluation lattice, 801–802
- is.vector function, 136–137
- italic function, 674, 683

J

- jitter function, 320, 332
- jittering, 320
- Journal of Statistics Education*, 177
- .jpeg files, 180–181
- jpeg function, 180–181, 189

K

- kde2d function, 772
 - bivariate surfaces, 792–793
 - nonparametric bivariate density, 740–741, 753, 755
 - nonparametric trivariate density, 804
- kde function, 806–807, 825
- Kendall's correlation coefficient, 328
- kernel density estimation (KDE)
 - density plots, 344
 - nonparametric bivariate density, 740–742, 746, 753–755
 - smooth density estimates, 689–691
 - trivariate surfaces, 806–807
- kernel weight, 344
- keywords (reserved names), 198–199
- knitr package, 851
- kruskal.test function, 517, 519
- Kruskal–Wallis test, 516–518
 - example and interpretation, 516–518
 - hypotheses, 516
- ks package, 9–10, 806, 832–833

L

- labels. *See* text and labels
- labels argument, 91

- labs function, 691
- lapply function, 241, 249
- las parameter, 669–670, 683
- lat.asp function, 366–367
- layer_histogram command, 702, 708
- layer_points command, 704, 708
- layer_smooths command, 705–706, 708
- layout function, 652–654, 683
- layout.show function, 653
- lazy evaluation, 258–261
- least-squares regression (line of best fit), 526–528
- legend3d function, 775–777, 825
- legend function, 154, 158–159, 168, 341
- legends
 - color, 720–722, 724, 772
 - point clouds, 775–778
- length function, 82
 - lists, 104
 - vectors, 22, 26–29, 35
- less than (<) operator, 61, 102
- less than or equal to (<=) operator, 61, 102
- letters function, 734, 772
- levels function, 82, 102, 131
- Levene’s test, 506
- leverage
 - calculating, 629–630
 - graphically combining with Cook’s distance and residuals, 635–638
 - in linear regression, 627–630
- lexical scoping, 196
- libraries, 9. *See also names of specific libraries*; packages
- library function, 9, 14, 830–831, 848
- linear regression, 599–643
 - collinearity, 640–643
 - goodness-of-fit vs. complexity, 599–601
 - influence in, 627–629
 - multiple, 555–597
 - residual diagnostics, 620–640
 - selection algorithms, 601–618
 - simple, 521–553
- line of best fit (least-squares regression), 526–528
- lines
 - in plotting, 151, 155–156
 - in point clouds, 779–782
- lines3d function, 779–780, 825
- lines function, 154, 158, 168, 577
- linetype function, 163, 168
- line type function. *See* lty function
- line width (lwd) function, 147, 151, 168, 667–668
- list.files function, 173, 189
- list function
 - ellipses, 266
 - list creation, 104, 106, 118
 - variadic behavior, 203–204
- lists of objects, 103–109
 - creating and accessing components, 104–105
 - named lists, 88
 - naming members, 106–107
 - nesting, 107–109
 - slicing, 105
- literal regular expressions, 72
- lm command
 - multiple linear regression, 560
 - simple linear regression, 525–526, 540, 548–553
- load command, 13, 185–189
- local environments, 195–196
- local files, installing contributed packages using, 836–837
- locally estimated scatterplot smoothing (LOESS), 687–689, 694, 705–706, 723
- locally weighted scatterplot smoothing (LOWESS), 687
- locator command, 659–661, 683, 712
- loci in parametric equations, 811–815
 - 2D circles, 811–812
 - 3D cones, 814–815
 - 3D cylinders, 811–814
- loess function, 688–689, 708
- logarithmic transformations, 578–582
 - fitting, 579–581
 - plotting fit, 581–582
- logarithms, 17–18, 579
- log function, 17–18, 35
- logical operators, 65
- logical values (logicals), 25, 59–72
 - logical flag vectors, 68–69
 - logical operators, 64–67
 - numeric representation of, 67–68

- relational operators, 60–64
- subsetting and extracting with, 68–72
- subsetting data frames with, 115–116
- TRUE and FALSE, 60
- `longlat.conv` function, 367
- loops, 223
 - `break`, 243–244
 - `for`, 223–231
 - via index or value, 226–228
 - nesting, 228–231
 - implicit looping, 238–243
 - `apply` function overview, 238–240
 - `apply` function variants, 240–241
 - whether to use, 242–243
 - infinite, 232
 - `next`, 244–246
 - `repeat`, 246–247
 - rotating perspective plots with, 767–769
 - `while`, 232–238
 - condition object modification, 233–238
- lower-tailed tests, 456
- LOWESS (locally weighted scatterplot smoothing), 687
- low-level programming languages, 4
- `ls` command
 - ad hoc object read/write operations, 184–185
 - assigning objects, 20, 35
 - scoping, 194–195, 207
- `lty` (line type) function
 - box customization, 667–668
 - plotting, 147–148, 151, 168
- `lty.hplot` argument, 730
- `lubridate` package, 92
- lurking variables, 556
- `lwd` (line width) function, 147, 151, 168, 667–668

M

- `magrittr` package, 207, 702
- main argument, 147, 168, 730, 774
- Mann–Whitney U test (Wilcoxon rank-sum test), 471, 516
- mapping function, 161, 168
- `mapply` function, 241
- MARGIN argument, 239

- margins and regions, 654–659
 - clipping, 657–659
 - customizing limits, 151–152
 - figure region, 655
 - outer region/margins, 655
 - plot region, 655
 - spacing, 655–657
- markup tools
 - Quarto, 852–854
 - R Markdown, 851–852
 - Sweave, 850–851
- `mar` parameter, 655, 683
- masking, 198, 293–299, 722
 - data frame variable distinction, 297–299
 - function and object distinction, 293–296
 - clashing package objects, 295–296
 - unmounting packages, 296
- MASS package, 295–297
- `mat` argument, 259–260
- mathematics, 15–19
 - abstractions, 815–824
 - Möbius strips, 815–817
 - tori, 817–820
 - arithmetic, 15–17
 - conventions and styles, xxxvii–xxxviii
 - e-notation, 18–19
 - expressions, 673–675
 - logarithms and exponentials, 17–18
- matrices, 37–51
 - creating, 38–40
 - dimensions, 40
 - filling direction, 38–39
 - naming rows and columns, 39
 - row and column bindings, 39–40
 - operations and algebra, 45–51
 - addition and subtraction, 47–48
 - identity matrix, 46
 - inversion, 49–51
 - multiplication, 48–49
 - scalar multiple, 47
 - transposition, 45–46
- singular, 49
- subsets, 40–45
 - extracting rows, columns, and diagonals, 41–42
 - omitting and overwriting, 42–45

- matrix command
 - argument matching, 201–202
 - attributes, 131
 - if statements, 212
 - matrix creation, 38, 56–57
 - scoping, 193, 195
- matrix inversion (`solve`) function, 50, 57, 558, 630
- matrix multiplication (`·`) symbol, 558
- matrix notation, 557–558
- matrix product (`%*%`) operator
 - linear regression, 558–559, 630, 678
- matrices, 49, 57
- matrix transposition (`t`) function, 46, 57, 558, 630
- `maxColorValue` argument, 722–723
- `max` function, 310–312, 332
- `%m` date marker, 93, 94, 102
- `mean` (arithmetic mean), 309
 - intervals for, 446–449
 - measures of centrality, 309
 - sampling distributions for, 436–441, 438
 - standard deviation known, 437
 - standard deviation unknown, 437
 - temperatures example, 437–441
 - testing, 458–472
 - single mean, 459–462
 - two means, 462–472
- `mean` (expectation; expected value)
 - continuous random variables, 386–388
 - discrete random variables, 379–380
- `mean` argument, 801
- `mean` function, 310–312, 314, 332
- mean squared error (MSE) effect, 508–509
- mean squared group (MSG) effect, 508
- median, 309
- `median` function, 310–312, 332
- member references, 104
- `mfc` parameter, 652–654, 683
- `mfcrow` parameter, 651–654, 683
- `mfcg` parameter, 669–670, 683
- microbenchmark package, 292
- Microsoft Access databases, 179
- Microsoft Excel spreadsheet workbooks, 176–177
- `min` function, 310–312, 332
- mirrors, 839
- `misc3d` package, 802, 808
- `missing` function, 263–264, 276
- Möbius strips, 815–817
- modality in distributions, 388–391
- mode, 310
- model-based inference, 528
- model selection algorithms, 601–618
 - backward selection, 609–613
 - forward selection, 605–609
 - partial *F*-test, 601–604
 - stepwise AIC selection, 613–618
- `month.abb` object, 94, 102
- `month.name` object, 94, 102
- motivation in interactive terms, 584–586
- `mtcars` dataset
 - bar plots, 334–335
 - bivariate surfaces, 788
 - clipping, 657–658
 - contour plots, 738–739, 744
 - Cook’s distance, 633–634
 - density plots, 344–348
 - histograms, 340
 - inspecting and interpreting residuals, 623
 - interactive effects, 591–593
 - numeric transformation, 573–576, 579–582
 - perspective plots, 761
 - pipes, 205
 - stepwise AIC selection, 614–618
- `mtext` function, 657, 672, 678, 683
- `%M` time marker, 98, 102
- multicollinearity. *See* collinearity
- multidimensional arrays, 37, 51–57
 - creating, 52–53
 - deleting and overwriting elements in, 56
 - extractions, 53–56
 - subsets, 53–55
- multilevel variables, 542–547
 - dummy coding, 542–543
 - linear regression model of, 544–546
 - predictions from, 546–547
- multi-modal distributions, 388–389
- multinomial distribution, 404

- multiple linear regression, 555–597
 - interactive terms, 584–597
 - concept and motivation, 584–586
 - higher-order interactions, 593–595
 - one categorical, one continuous predictor, 586–589
 - two categorical predictors, 590–591
 - two continuous predictors, 591–593
- numeric transformation, 572–584
 - logarithmic transformations, 578–582
 - polynomial transformations, 572–578
- partial effects in, 563–564
- R implementation and interpretation, 560–571
 - adding predictors, 560–563
 - computing omnibus *F*-test, 566–568
 - finding confidence intervals, 565
 - interpreting partial effects, 563–564
 - model selection, 561–562
 - predicting from multiple linear model, 568–569
 - visualizing the model, 564–565
- terminology, 556
- theory, 556–559
 - example of, 558–559
 - extending simple model to multiple model, 557
 - representing in matrix notation, 557–558
- multiple testing problem, 492
- multiplication (*) operator, 15, 35, 47, 57
- multivariate data, 306–307
- mvtnorm package, 800

N

- NA (not available) notation, 124–126, 143, 198, 215
- named lists, 88
- names function, 106–107, 118, 131, 227
- NaN (not a number) notation, 122–124, 143, 198–199
- na.omit function, 126, 143, 686, 696, 717

- na.rm argument, 312, 766
- natural log, 17
- nchar function, 73, 102
- ncol function
 - arguments, 201, 259
 - data frame construction, 111, 118
 - matrix creation, 38, 40, 57
- negative binomial distribution, 404
- newdata argument, 535, 541–542, 581
- newline (\n) escape sequence, 77, 149, 657, 672
- news function, 838
- next function, 244–246, 249
- no-change (baseline) hypotheses, 456
- nominal categorical variables, 304–305
- nonparametric bivariate density
 - Chorley–Ribble data, 752–757
 - earthquake data, 740–743
- nonparametric smoothing, 687
- nonparametric trivariate density, 804–810
 - isosurface level selection, 806–810
 - raw data, 805–806
 - 3D estimate calculation, 806
- normal (Gaussian) distribution, 410–419
 - dnorm function, 412
 - example of, 418–419
 - pnorm function, 412–415
 - qnorm function, 415–417
 - rnorm function, 417–418
- normality, assessing, 626–627
- normalization, color indexing via, 718–720
- normalize function, 718, 730
- NOT (!) operator, 65, 102
- not a number (NaN) notation, 122–124, 143, 198–199
- not available (NA) notation, 124–126, 143, 198, 215
- not equal to (!=) operator, 61, 102
- nrow function
 - arguments, 201, 259
 - data frame construction, 111, 118
 - matrix creation, 38, 40, 57
 - nonparametric bivariate density, 756
- nuclear dataset
 - backward selection, 609–613
 - forward selection, 605–608
 - higher-order interactions, 594–595

nuisance (extraneous) variables, 556
null hypotheses, 456
NULL value, 127–129, 143, 198, 290
numerical overflow and underflow, 121
numeric variables, 304

O

object-checking (is-dot) functions,
136–137. *See also names of specific
is-dot functions*
object-oriented programming, 132
objects
as-dot coercion functions, 87,
137–142
assigning, 19–21
attributes, 130–132
classes, 132–136
data structures, 134–135
inheriting from multiple, 135–136
stand-alone vectors, 133–134
deleting, 20–21
is-dot functions, 136–137
masking, 293–296
clashing package objects, 295–296
unmounting packages, 296
naming, 20
read/write operations, 184–188
determining suitability, 187–188
dput and dget, 186–187
save and load, 185–186
saveRDS and readRDS, 185–186
observation window (owin) object class,
753, 756
OlsonNames function, 98, 102
oma parameter, 655, 683
Omegahat, 839
omnibus *F*-test, 552, 566–568, 640
one-sided hypotheses, 456
one-way ANOVA. *See one-way under
ANOVA*
opacity, 722–724, 803–804
OpenGL, 773
options function, 6, 14
ordered argument, 84, 547
ordinal categorical variables, 304
OR element-wise (|) operator,
64–66, 102
origin coordinate, 367

OR single comparison (||) operator,
64–66, 102, 212
orthogonal contrasts, 547
outer function, 813, 825
outliers, 329–332, 627–630
owin (observation window) object class,
753, 756

P

packages (libraries), 9–10. *See also names
of specific packages*
base, 829–830
citing R and contributed, 840–841
clashing objects in, 295–296
contributed, 830–837
finding on CRAN, 832–833
installing at prompt, 833–834
installing using GUI, 834–836
installing using local files, 836–837
environments and namespace,
194–196
installing, 9–10, 833–837
loading, 9
recommended, 830
remounting, 296
updating, 10, 838
using, 829
writing, 841
paired/dependent samples testing,
468–471
pairs function, 360, 370
palette function, 710–711, 772
palettes, 710, 714
built-in color, 714–715, 772
custom color, 715–716
parameters. *See also graphical
parameters*
in simple linear regression
model, 524
statistics vs., 307–308
parametric equations, 810–824
loci, 811–815
2D circles, 811–812
3D cones, 814–815
3D cylinders, 811–814
mathematical abstractions, 815–824
Möbius strips, 815–817
tori, 817–820

- parametric response surface, 738–740
- parenthesis. *See* () characters
- par function, 651–655, 683
- parsimony principle, 600
- partial argument matching, 201–202
- paste function, 74–76, 102, 137–138, 674
- pbeta function, 431
- pbinom function, 396, 398, 432
- pch (point character) parameter, 147–148, 151, 168
- pch3d function, 777–778, 780, 825
- pchisq function, 427–428, 432
- pcol function, 712–713
- PDF files, storing plots as, 181–182
- pdf function, 181–182, 189, 648
- Pearson's product-moment correlation coefficient, 325–328
- PEMDAS mnemonic, 16
- percentages, calculating, 313–314
- percentiles, 318
- Perl regular expressions, 72
- persp3d function, 788–793, 813, 816, 825
- perspective plots (wireframe plots), 761–772
 - coloring facets, 764–767
 - interpreting and adjusting angles, 761–764
 - rotating with loops, 767–769
- persp function, 761–763, 768, 772
- persprot function, 768–769
- pexp function, 424, 432
- pf function, 429–430, 432
- p-functions, 393, 431
- pgamma function, 431
- pgeom function, 404
- pharmaceuticals, interactive effects
 - between, 585, 591–593
- phi argument, 761–763, 767–768
- phyper function, 404
- pie charts, 337–339, 338
- pie function, 337, 370
- pi function, 811, 825
- pipe (|>) operator, 205–207, 702
- pipe (%>%) operator, 207, 702
- pipes, 205–207
- PIs. *See* prediction intervals
- pixel images, 749–760
 - grid points and pixels, 749–752
 - nonparametric bivariate density estimate, 752–757
 - surface truncation and empty pixels, 752–760
- planar point pattern (ppp) objects, 752
- plot3d function, 825
 - color and legends, 776
 - points and spheres, 774–775
 - scatterplot example, 783
 - trivariate surfaces, 798, 803, 805, 809
- plot customization, 647–683
 - graphics devices, 648–654
 - closing, 650–651
 - controlling multiple plots in one, 651–654
 - layout function for multiple plots in one, 652–654
 - manually opening new, 648–649
 - mfrow/mfcol parameters for multiple plots in one, 651–652
 - switching between devices, 649–650
- point-and-click coordinate
 - interaction, 659–665
 - placing ad hoc annotations, 661–662
 - retrieving coordinates silently, 659–660
 - visualizing selected coordinates, 660–661
- regions and margins, 654–659
 - clipping, 657–659
 - custom spacing, 656–657
 - default spacing, 655–656
 - figure region, 655
 - outer region/margins, 655
 - plot region, 655
- scatterplot example, 675–679
- text and label notation, 670–675
 - font, 670–672
 - Greek symbols, 672–673
 - mathematical expressions, 673–675
- traditional R plots, 665–670
 - axis customization, 668–670
 - box customization, 667–668
 - graphical parameters for style and suppression, 665–667

- plot function, 145–148, 168. *See also*
 - plots and plotting
 - adding points, lines, and text, 154–160
 - density plots, 344–346
 - ellipses, 204
 - linear regression model diagnostics, 624, 643
 - simple linear regression, 522
 - visual controls and graphical
 - parameters, 147–154
 - aspect ratio, 152–154
 - automatic plot types, 148
 - color, 149–151
 - custom region limits, 151–152
 - line and point appearances, 151
 - title and axis labels, 148–149
- plotmath mode, 672
- plotrix package, 722
- plots and plotting, 145–168, 773–825.
 - See also* plot customization
 - adding points, lines, and text, 154–160
 - bivariate surfaces, 733–736, 788–797
 - adding components, 789–791
 - aspect ratio, 792–794
 - coloring by *z* value, 792
 - constructing evaluation grid, 733–735
 - plotting perspective surfaces, 788–789
 - z*-matrices, 735–736
 - color, 709–728
 - built-in palettes, 714–715
 - custom palettes, 715–716
 - indexing via categorization, 716–718
 - indexing via normalization, 718–720
 - legends, 720–722
 - opacity, 722–724
 - RGB alternatives, 725
 - RGB hexadecimal codes, 710–713
 - contour plots, 736–749
 - color-filled contours, 743–746
 - contour lines, 737–743
 - coordinate-based, 365–369
 - in *ggplot2*, 369
 - longitude and latitude, 365–369
 - pre-existing distance-based
 - units, 365
 - ggplot2* package, 160–167
 - aesthetic mapping with *geoms*, 164–167
 - displaying multiple plots, 691–701
 - plotting toy example, 160–162
 - setting appearance constants with *geoms*, 162
 - parametric equations, 810–824
 - perspective plots, 761–772
 - coloring facets, 764–767
 - interpreting and adjusting angles, 761–764
 - rotating with loops, 767–769
 - pixel images, 749–760
 - grid points and pixels, 749–752
 - nonparametric bivariate density
 - estimate, 752–757
 - surface truncation and empty
 - pixels, 752–760
 - point clouds, 773–787
 - color and legends, 775–778
 - customized interactive 3D
 - scatterplot, 782–785
 - 3D cloud points and spheres, 774–775
 - 3D lines, axes, grids, and other
 - annotations, 779–782
 - 3D point characters, 777–778
 - 3D text, 778–779
 - 3D scatterplots, 728–733
 - customized interactive, 782–785
 - syntax, 729
 - visual enhancements, 730–732
 - trivariate surfaces, 798–810
 - evaluation coordinates in 3D, 798–799
 - isosurfaces, 799–804
 - nonparametric trivariate density, 804–810
 - visual controls and graphical
 - parameters, 147–154
 - writing out, 180–184
- pnbinom* function, 404
- png* function, 180, 189, 648
- pnorm* function, 412–415, 418, 432, 444

- point character (pch) parameter, 147–148, 151, 168
- point clouds, 773–787
 - color and legends, 775–778
 - customized interactive 3D scatterplot, 782–785
 - 3D cloud points and spheres, 774–775
 - 3D lines, axes, grids, and other annotations, 779–782
 - 3D point characters, 777–778
 - 3D text, 778–779
- points3d function, 775, 789, 825
- points function
 - adding points to existing plots, 154, 157–158, 168
 - interval plots, 534
 - linear regression model diagnostics, 629
- Poisson distribution, 400–404
 - dpois function, 402–403
 - ppois function, 402–403
 - qpois function, 403
 - rpois function, 403
- polygon function, 391
 - continuous random variables, 384
 - probability density functions, 407, 414–415
 - sampling distributions, 439
- polynomial contrasts, 547
- polynomial curvature, 572–573
- polynomial transformations, 572–578
 - fitting, 573–577
 - plotting, 577–578
 - pitfalls of, 578
- pooled estimate of the variance, 466
- pooled variance testing, 465–468
- Posit, 843
- positional argument matching, 202–203
- postscript function, 181, 189
- power curves of statistical power, 500–501
- power.test function, 499–500
- ppois function, 402–403, 432
- ppp (planar point pattern) objects, 752
- predict command, 533–535, 541–542, 553, 577
- prediction intervals (PIs), 532
 - confidence intervals vs., 531–532
 - for individual observations, 533–534
- predictions
 - from binary variables, 541–542
 - from fitted simple linear models, 531–538
 - confidence interval vs. prediction interval, 531–532
 - interpolation vs. extrapolation, 536
 - interval interpretation, 532–534
 - interval plots, 534–536
 - from multilevel variables, 546–547
 - from multiple linear models, 568–569
- print function, 162, 280
- probability, 371–391
 - complement, 375–376
 - conditional, 373
 - dependent vs. independent events, 373
 - distributions of, 393–432
 - Bernoulli, 394–395
 - binomial, 395–400
 - chi-squared, 426–428
 - exponential, 422–426
 - F-distribution, 428–430
 - normal, 410–419
 - Poisson, 400–404
 - Student's *t*-distribution, 419–422
 - uniform, 404–410
 - events and, 372–373
 - frequentist, 372
 - intersection of events, 373–374
 - random variables
 - continuous, 376–377, 380–388
 - discrete, 376–380
 - probability distributions and, 376–391
 - shape, skew, and modality in, 388–391
 - realizations, 376–377
 - union of events, 374
- probability density functions, 381–385, 404–431
 - chi-squared distribution, 426–428
 - exponential distribution, 422–425
 - F-distribution, 428–430
 - higher-dimensional, 799–801

- probability density functions (*continued*)
 - normal distribution, 410–419
 - Student's *t*-distribution, 419–422
 - uniform distribution, 404–410
- probability mass functions, 377, 393–404
 - Bernoulli distribution, 394–395
 - binomial distribution, 395–400
 - Poisson distribution, 400–404
- proc.time function, 288
- prod function, 34–35, 312
- profiling
 - progress and timing, 288–293
 - measuring completion time, 287–288
 - tracking, 286–287
 - in RStudio, 848–849
- profvis package, 292
- proportions, 313–314
 - intervals for, 449–450
 - sampling distributions for, 441–444
- testing, 473–480
 - single proportions, 473–476
 - two proportions, 476–478
- prop.test function, 475–476, 478, 502
- protected names, 198–199
- pt function, 421–422, 432
- punif function, 408, 432
- p*-value, 455–457
- pweibull function, 431

Q

- qbeta function, 431
- qbinom function, 396, 399, 432
- qchisq function, 427–428, 432
- qexp function, 425, 432
- qf function, 429–430, 432
- q function, 13–14
- q-functions, 393, 431
- qgamma function, 431
- qgeom function, 404
- qhyper function, 404
- qbinom function, 404
- qnorm function, 415–418, 432
- qplot function, 161, 336
- qpois function, 403
- qqlined function, 417
- qqline function, 416, 432
- qqnorm function, 416–417, 432

- qt function, 420–421, 432
- quads3d function, 782
- quakes dataset
 - box plots, 350–352
 - color opacity, 723
 - contour plots, 745
 - graphics devices, 648–650
 - longitude and latitude, 366–368
 - perspective plots, 768
 - summary statistics, 311, 319, 322, 327
 - trivariate surfaces, 805–809
 - univariate and multivariate data, 306
 - violin plots, 355–356
- quantile function, 318–319, 332
- quantile-quantile (QQ) plots
 - assessing normality, 626
 - Kruskal–Wallis test, 517
 - normal distribution, 415–418
 - one-way ANOVA, 506
- quantiles, 318
- quarters function, 95, 102
- Quarto, 852–854
- qunif function, 408–409, 432
- qweibull function, 431

R

- radians, 366
- radius argument, 775
- rainbow function
 - built-in palettes, 714, 772
 - coloring facets, 766
 - hue-saturation-value, 725
 - nonparametric bivariate density, 753
 - opacity, 722
 - 3D lines, 781
- random error, 445
- random variables, 376–391
 - continuous, 376–377, 380–388
 - concept, 380
 - cumulative probability
 - distributions, 385–386
 - mean and variance, 386–388
 - probability density functions, 381
 - discrete, 376–380
 - cumulative probability
 - distributions, 378
 - mean and variance, 379–380

- realizations, 376–377
- shape, skew, and modality, 388–391
- randomly generated realizations, 399
- range function, 310–312, 332
- raw data, describing, 303–308
 - categorical variables, 304
 - examples, 305
 - numeric variables, 304
 - parameters vs. statistics, 307–308
 - univariate and multivariate data, 306–307
- rbenchmark package, 292
- rbeta function, 431
- rbind function, 39–40, 57, 113–114
- rbinom function, 396, 399, 432
- rchisq function, 427–428, 432
- RColorBrewer package, 714, 725
- R Core Team, xxxii
- .RData extension, 13
- read.csv command, 176–177, 189
- readLines function, 177
- readRDS command, 185–186, 188–189
- read.table command, 173–176, 179, 189
- ready-to-use functions, 9. *See also names of specific built-in functions*
- realizations, 376–377, 399
- recursive functions, 273–276
- red-green-blue (RGB) values
 - alternatives to, 725
 - hexadecimal color codes, 710–713
 - triplets, 710
- reference categories/levels, 85
- regions and margins, 654–659
 - clipping, 657–659
 - customizing limits, 151–152
 - figure region, 655
 - outer region/margins, 655
 - plot region, 655
 - spacing, 655–657
- regression coefficient significance tests, 529–530
- relational operators, 60–64
- relevel function, 85, 102, 547–548
- repeat statements, 246–247, 249, 254
- repetitions, 24–25
- rep function, 22, 24–25, 29, 35, 780
- replacement argument, 79
- reserved names (keywords), 198–199
- resid function, 527
- residuals
 - assumptions, 523–524
 - diagnostics, 506, 620–640
 - assessing normality, 626–627
 - calculating Cook’s distance, 631–634
 - calculating leverage, 629–630
 - combining residuals, leverage, and Cook’s distance, 635–638
 - illustrating outliers, leverage, and influence, 627–630
 - inspecting and interpreting, 622–626
 - illustrating, 526–528
- residual sum of squares (RSS), 557
- response surfaces, 593
- return statements, 252, 256–258, 276
- rev function, 688, 708
- rexp function, 425, 432
- rf function, 429–430
- R-Forge, 839
- r-functions, 393
- rgamma function, 431
- rgb function, 711–712, 718, 722–723, 772
- RGB values. *See* red-green-blue values
- rgeom function, 404
- rgl package, 773–825
 - bivariate surfaces, 788–797
 - adding points, 789
 - adding surfaces, 789–791
 - aspect ratio, 792–794
 - coloring by z value, 792
 - plotting perspective surfaces, 788–789
- parametric equations, 810–824
- point clouds, 773–787
 - color and legends, 775–778
 - custom, interactive 3D scatterplot, 782–785
 - points and spheres, 774–775
 - 3D lines, axes, grids, and annotations, 779–782
 - 3D point characters, 777–778
 - 3D text, 778–779

- rgl package (*continued*)
 - trivariate surfaces, 798–810
 - evaluation coordinates in 3D, 798–799
 - isosurfaces, 799–804
 - nonparametric trivariate density example, 804–810
- .Rhistory file, 13
- rhyper function, 404
- ring tori, 817–820
- RJDBC package, 179
- R language, 827–841. *See also* base R GUI
 - citing, 840–841
 - downloading and installing, 9–10, 827–837
 - base packages, 829–830
 - contributed packages, 830–837
 - finding packages on CRAN, 832–833
 - packages at prompt, 833–834
 - packages using GUI, 834–836
 - packages using local files, 836–837
 - recommended packages, 830
 - FAQs, 827
 - history of, xxxi–xxxii
 - home page, 828
 - mirrors and repositories, 839
 - switching CRAN mirror, 839
 - updating, 10, 838
 - using packages, 829
 - writing packages, 841
- R Markdown, 851–852
- rmarkdown package, 851
- rm command, 20–21, 35, 199
- rmultinom function, 404
- rmvnorm function, 800–801, 825
- RMySQL package, 179
- rnbinom function, 404
- rnorm function, 417–418, 432
- robustness, 331
- RODBC package, 179
- round function, 315, 332, 397
- [*row, column*] operator, 40, 57, 112, 118
- row.names argument, 180
- rownames function, 111, 118, 791
- rowSums function
 - chi-squared tests of independence, 486
 - implicit looping, 239
 - measuring computational expense, 288–289, 300
 - profiling, 291
- rpois function, 403, 432
- Rprof function, 289–290, 300
- R> prompt, xxxvi, 6
- RSS (residual sum of squares), 557
- rstandard function, 627, 643
- RStudio, 4–5, 843–854
 - downloading, 843
 - ggvis package, 701
 - graphics devices, 146
 - layout and usage, 844–846
 - editor features and appearance options, 844–845
 - pane customization, 845–846
 - markup, document, and graphics tools, 850–854
 - knitr package, 851
 - Quarto, 852–854
 - R Markdown, 851–852
 - Shiny, 854
 - Sweave, 850–851
- shortcuts, 7
- package manager, 847–848
 - tools and features, 846–850
 - package manager, 847–848
 - projects, 846–847
 - support for debugging, 849–850
 - support for profiling, 848–849
- user guide, 844
- working directory, 7–9
- rt function, 422, 432
- runif function, 409, 432
- rweibull function, 431

S

- S3 classing structure, 133
- S4 classing structure, 133
- saddles (inflections), 578
- sample function, 819, 825
- sampling distributions, 435–445
 - for finite-sized samples, 445
 - for a sample mean, 436–441
 - standard deviation known, 437
 - standard deviation unknown, 437

- temperature example, 437–441
 - for a sample proportion, 441–444
- apply function, 241, 249, 259, 266
- save command, 13, 185–189
- saveRDS function, 185–186, 188–189
- saving work, 13–14
- scalar multiple value, 47
- scale_fill_grey function, 336, 370
- scale_linetype_manual function, 343, 370
- scale_shape_manual function, 361, 370
- scale_x_discrete function, 336, 370
- scale_y_continuous function, 336, 370
- scan function, 177
- scatterplot3d function, 728–730, 772, 782
- scatterplots, 357–369
 - covariance and correlation, 325–328
 - customizing example, 675–679
 - in ggplot2, 361–365
 - matrix of, 359–361
 - single plot, 358–359
 - 3D, 728–733
 - customized interactive, 782–785
 - syntax, 729
 - visual enhancements, 730–732
- scatter.smooth function, 688
- scope argument
 - forward selection, 606, 609
 - stepwise AIC selection, 614
- scoping, 193–199
 - environments, 194–196
 - global, 194
 - local/execution, 195–196
 - package environments and namespaces, 194–195
 - lexical, 196
 - reserved and protected names, 198–199
 - search path, 196–198
- scripts, 6
 - saving as plain text files, 14
- sd (standard deviation) command, 322, 332
- search function, 196, 207, 294
- search help (??) function, 12, 14
- segments3d function, 779–781, 783–784, 791, 825
- segments function
 - adding lines to plots, 154, 157, 168
 - interval plots, 534
 - probability density functions, 407
 - simple linear regression, 527
- semicolon (;) character, 746, 784
- separation (+) operator, 513, 560
- sep argument, 75–76, 173, 178
- seq function, 22–24, 35, 197, 341
- sequences, creating, 23–24
- serialization, 186–188
- setTxtProgressBar function, 286, 300
- setwd function, 8, 14, 173
- shade argument, 763
- shading. *See* smoothing and shading
- shape argument, 163, 168
- shape package, 720, 722, 750
- shapiro.test function, 627, 643
- Shapiro–Wilk test, 506, 627
- Shiny, 854
- side argument, 781
- silent argument, 283
- simple linear regression, 521–553
 - categorical predictors, 538–553
 - binary variables, 538–542
 - changing reference level, 547–548
 - checking for equivalence with one-way ANOVA, 551–552
 - multilevel variables, 542–547
 - treating categorical variables as numeric, 548–551
- concepts, 523–528
 - defining models, 523–524
 - estimating intercept and slope parameters, 524–525
 - fitting linear models with lm command, 525–526
 - illustrating residuals, 526–528
- explanatory variable, 521, 523
- extending to multiple linear regression, 557
- linear relationship example, 521–523
- predictions, 531–538
 - confidence interval vs. prediction interval, 531–532
 - interpolation vs. extrapolation, 536
 - interval interpretation, 532–534
 - interval plots, 534–536

- simple linear regression (*continued*)
 - response variable, 521, 523
 - statistical inference, 528–531
 - coefficient of determination, 530
 - regression coefficient significance tests, 529–530
 - summary command, 528–531
- sin function, 811, 825
- singular matrices, 49
- size argument, 163, 168
- skew, 340, 388–391
 - in distributions, 319, 388–391
- skip argument, 179, 768
- S language, xxxi
- sleep, pausing execution in R via, 286–287
- sleep argument, 768
- slope and intercept parameters, 157, 524–525
- smoothing and shading, 686–691
 - adding LOESS trends, 687–689
 - constructing smooth density estimates, 689–691
- smoothing parameter. *See* bandwidth
- solve (matrix inversion) function, 50, 57, 558, 630
- sort function, 22, 25, 35
- sorting, 25
- spacing
 - customizing margins, 656–657
 - default margins, 655–656
- span argument, 689
- spatial coordinates, plots of. *See* coordinate-based plots
- spatstat packages, 752–753, 756
- Spearman’s correlation coefficient, 328
- special values, 119–130
 - infinity, 120–122
 - NA, 124–126
 - NaN, 122–124
 - NULL, 127–130
- spheres3d function, 775
- split.screen function, 654
- spread, measures of, 319–324
 - example, 319–320
 - interquartile range, 321
 - R implementation, 322–324
 - standard deviation, 321
 - variance, 321
- spreadsheet workbooks, 176–177
- sqrt function
 - categorical predictors, 552
 - square roots, 16, 35
 - variance and standard deviation, 322, 380
- square-bracket ([]) characters, 27–28, 35, 70, 105, 118
- square roots, 16
- srt argument, 678, 683
- SS (sum-of-squares) value, 508–509
- standard deviation, 321–322
- standard deviation (sd) command, 322, 332
- standard normal (Gaussian) distribution, 411
- statistical inference, 528–531
 - coefficient of determination, 528, 530
 - five-number summary, 531
 - regression coefficient significance tests, 529–530
 - residual standard error, 530
 - summary command, 528–531
- statistical power, 497–502
 - power curves, 500–501
 - simulation, 498–500
- statistics, 303–332
 - describing raw data, 303–308
 - categorical variables, 304
 - examples, 305
 - numeric variables, 304
 - parameters vs. statistics, 307–308
 - univariate and multivariate data, 306–307
 - parameters vs., 307–308
- summarizing data, 309–332
 - counts, percentages, and proportions, 313–314
 - measures of centrality, 309–313
 - measures of spread, 319–324
 - outliers, 329–332
 - quantiles, percentiles, and five-number summary, 318
 - relationships between numeric variables, 324–328
 - rounding, floors, ceilings, and absolute values, 315–317
- step function, 615, 643

- %S time marker, 98, 102
- stochastic mechanisms, 376
- stop command, 278, 300
- stopping conditions, 273
- str function, 110, 118
- strings
 - concatenating, 74–77
 - creating, 73–74
- stringsAsFactors argument, 175
- strptime function, 98–99, 102
- students, recommendations to,
 - xxxviii–xxxix
- Student's *t*-distribution, 419–422
 - definition and degrees of freedom,
 - 419–420
 - dt function, 420–421
 - pt function, 421–422
 - qt function, 420
 - rt function, 422
- sub function, 79, 102
- subscript ([]) parameter, 675, 683
- subset function, 116–118, 206
- subsetting
 - arrays, 53–55
 - data frames, 112–118
 - with logicals, 68–72, 115–116
 - matrices, 40–45
 - extracting rows, columns, and diagonals, 41–42
 - omitting and overwriting, 42–45
 - vectors, 26–31
- substr function, 78–79, 102
- substrings, 78–80
- subtraction (-) operator
 - arithmetic, 15, 35
 - matrices, 48, 57
- sum function, 34–35, 294–295,
 - 312–314
- summary function
 - ANOVA table construction, 508–509
 - five-number summary, 318–319,
 - 323, 332
 - inspecting and interpreting
 - residuals, 622
 - multiple linear regression, 562
 - simple linear regression, 528–531,
 - 545, 551, 553
- summaryRprof function, 290–291,
 - 300, 849
- summary statistics, 309–332
 - counts, percentages, and proportions,
 - 313–314
 - measures of centrality, 309–313
 - mean, 309
 - median, 309
 - mode, 310
 - R implementation, 310–313
 - measures of spread, 319–324
 - interquartile range, 321
 - R implementation, 322–324
 - standard deviation, 321
 - variance, 321
 - outliers, 329–332
 - quantiles, percentiles, and five-number summary, 318
 - relationships between numeric
 - variables, 324–328
 - correlation, 325
 - covariance, 324–325
 - R implementation, 325–328
 - rounding, floors, ceilings, and
 - absolute values, 315–317
- sum-of-squares (SS) value, 508–509
- sum parameter, 674, 683
- superscript (^) parameter, 674, 683
- suppressWarnings function, 283–284
- surface truncation, 752–760
- survey dataset
 - collinearity, 641–642
 - color indexing, 717
 - controlling multiple plots in one
 - graphics device, 653
 - faceting, 696
 - ggvis graphics, 702
 - Kruskal–Wallis test, 516–517, 685–686
 - multiple linear regression, 560
 - partial *F*-test, 602
 - point-and-click coordinate
 - interaction, 661
 - simple linear regression, 521–523,
 - 539, 544, 548
- Sweave, 850–851
- switch function, 218–220, 249
- symbolic notation (formula
 - notation), 522
- symmetric distributions, 388–389
- Sys.sleep function, 286, 300
- systematic error, 445

`Sys.time` function, 97, 102,
287–288, 300
`Sys.timezone` function, 98

T

`t` (matrix transposition) function, 46,
57, 558, 630
`\t` (tab) escape sequence, 77
table-format files, 172–176
delimiters in, 172
headers in, 171–172
missing values in, 172
table function, 84, 102, 310–314, 332
tail command, 111, 118
tapply function, 240, 249
categorical predictors, 539–540
measures of centrality, 312–314
one-way ANOVA, 504
two-way ANOVA, 512
tcl parameter, 669, 683
terrain.colors function, 714, 772
text and labels, 670–675
annotations in point clouds, 779–782
color legends, 720–722
font, 670–672
Greek symbols, 672–673
mathematical expressions, 673–675
in point clouds, 778–779
title and axis using plot function,
148–149
text3d function, 778–779, 790–791, 825
text function
adding text to plots, 154, 158, 168
clipping, 658–659
fonts, 671
linear regression model
diagnostics, 629
theme_bw function, 336–337, 370
theta argument, 761–763, 767–768
3D plots, 773–825
bivariate surfaces, 788–797
adding components, 789–791
aspect ratio, 792–794
coloring by z value, 792
plotting perspective surfaces,
788–789
z-matrices, 736
parametric equations, 811–814

point clouds, 773–787
color and legends, 775–778
customized interactive 3D
scatterplot, 782–785
3D cloud points and spheres,
774–775
3D lines, axes, grids, and other
annotations, 779–782
3D point characters, 777–778
3D text, 778–779
scatterplots, 728–733
syntax, 729
visual enhancements, 730–732
trivariate surfaces, 798–810
evaluation coordinates in 3D,
798–799
isosurfaces, 799–804
nonparametric trivariate density,
804–810
ticktype argument, 763
tiff function, 180, 189
tilde (~) operator, 351–352, 370, 560,
611, 702
time and timing. *See* dates and times;
progress and timing *under* profiling
title3d function, 781, 825
title function, 657, 673, 678, 683
title labels, 148–149
T logical value. *See* TRUE logical value
topo.colors function, 714, 772
topographical maps, 737–738
tori, 817–820
transposing matrices, 45–46
triangles3d function, 782
trimodal distributions, 388–389
trivariate surfaces, 798–810
evaluation coordinates in 3D,
798–799
isosurfaces, 799–804
higher-dimensional probability
densities, 799–801
multiple-level control with color
and opacity, 803–804
one-level, 802–803
trivariate evaluation lattice,
801–802
nonparametric trivariate density,
804–810

- isosurface level selection, 806–810
 - raw data, 805–806
 - 3D estimate calculation, 806
- TRUE (T) logical value, 60–63, 102
 - else statements, 213
 - if statements, 210, 212
 - reserved names, 198–199
- tryCatch function, 283
- try statements, 280–285, 300
 - in body of function, 281–283
 - suppressing warning messages, 283–285
- tseries package, 171
- t.test function, 455–456, 461–462, 464–465, 470, 502
- two-sample *t*-test (Welch's *t*-test), 464
- two-sided (two-tailed) tests, 456
- two-way ANOVA, 511–515
 - interaction plots, 514
 - main effects and interactions, 511–515
 - suite of hypotheses, 511–512
- .txt files, 171
- txtProgressBar function, 286, 300
- type argument, 147–148, 168, 775
- Type I errors in hypothesis testing, 490
- Type II errors in hypothesis testing, 490, 493
 - sample size, 496
 - statistical power, 497–498
 - variability of measurements, 495
- typeI.test function, 491–492
- typeII.test function, 494–495, 499
- typeof function, 135

U

- uniform distribution, 404–410,
 - dunif function, 406–408
 - punif function, 408
 - qunif function, 408–409
 - runif function, 409
- unimodal distributions, 388, 389
- union of two events, 374
- univariate data, 306–307
- universal assignment (:=) operator, 703–704, 708
- University of Auckland, xxxi
- University of Otago, xxxix
- unpaired/independent samples testing
 - pooled variance, 465–468
 - unpooled variance, 463–465
- update function, 643
 - backward selection, 609, 611
 - forward selection, 605, 607–608
- update.packages function, 9–10, 14, 834, 837–839, 848
- updating R and installed packages, 10, 838
- upper-tailed tests, 456

V

- vapply function, 241
- var (variance) command, 322, 332
- variables, 303
 - binary, 538–542
 - categorical
 - nominal, 304–305
 - ordinal, 304
 - continuous, 304–305
 - discrete, 304
 - multilevel, 542–547
 - nuisance, 556
 - numeric, 304–305
 - random, 376–391
 - continuous, 376–377, 380–388
 - discrete, 376–380
- variadic behavior, 203–204
- variance, 321
 - continuous random variables, 386–388
 - discrete random variables, 379–380
- variance (var) command, 322, 332
- vector-oriented (vectorized; element-wise) behavior, 31–35
- vectors, 21–35
 - classes and, 133–134
 - creating, 21–22
 - element extraction, 26–31
 - indexes, 29–30
 - lengths, 26
 - recycling, 32, 44, 62
 - repetition, 24–25
 - sequences, 23–24
 - sorting, 25
 - subsetting, 27–30
 - vector-oriented behavior, 31–35

- Venn diagrams
 - complement of events, 375
 - intersection of events, 373
 - union of events, 374
- violin plots, 353–357
 - design and interpretation, 354–355
 - in `ggplot2`, 356–357
 - histograms and box plots vs., 354
 - side-by-side, 355
- `vioplot` function, 354–355, 370
- visual controls and graphical
 - parameters, 147–154
 - aspect ratio, 152–154
 - color, 150
 - line and point appearances, 151
- volcano dataset, 737

W

- warning command, 278, 300
- warnings
 - in exception handling, 278–280
 - suppressing with try statements, 283–285
- warpbreaks dataset, 512–513, 590–591
- web-based files, 177–179
- web resources, xl
- weekdays function, 95, 102
- Weibull distribution, 431
- Welch–Satterthwaite equation, 464
- Welch’s *t*-test (two-sample *t*-test), 464
- which function, 102
 - creating and formatting dates, 94–95
 - factors, 82
 - logical subsetting and extraction, 69–71
 - NaN notation, 123
- while loops, 232–238, 249
 - break function and, 244
 - condition object modification, 233–238
 - repeat statements and, 247
- whitespace, 178
- Wilcoxon rank-sum test
 - (Mann–Whitney U test), 471, 516
- `wilcox.test` function, 471
- Wilson score interval, 476
- window width. *See* bandwidth
- wireframe plots. *See* perspective plots

- workflow, 5–12
 - code execution, 7
 - comments, 7
 - console and editor panes, 5–6
 - help files and function
 - documentation, 10–12
 - packages, 9–10
 - installing, 9–10
 - loading, 9
 - updating, 10
 - working directory, 7–9
 - changing default, 8–9
 - checking location of, 8
- workspace images, 13
- workspaces, 13
- `write.table` function, 179–180, 189

X

- X argument, 239
- xaxis parameter, 666, 683, 739
- xaxt parameter, 667
- xlab argument, 147
 - axis labels, 149, 162, 168
 - perspective plots, 763
 - point clouds, 774
 - 3D scatterplots, 730, 783
- XLConnect package, 176
- xlim (xlimits) argument, 147–148
 - color legends, 721
 - custom region limits, 151–152, 168
 - nonparametric bivariate density, 755
 - plot customization, 666
- `.xlsx` (`.xls`) files, 176
- xpd parameter, 657–659, 683
- XQuartz window system, 829
- xseg argument, 780–781

Y

- yaxis parameter, 666, 683, 739
- yaxt parameter, 667
- %y date marker, 93–94, 102
- %Y date marker, 93–94, 102
- yintercept argument, 166, 168
- ylab argument, 147
 - axis labels, 149, 162, 168
 - perspective plots, 763
 - point clouds, 774
 - 3D scatterplots, 730, 783

- `ylim` (`ylimits`) argument, 147–148
 - color legends, 721
 - custom region limits, 151–152, 168
 - nonparametric bivariate density, 755
 - plot customization, 666
- `yseg` argument, 780–781

Z

- `zlab` argument, 730, 763, 774, 783
- `zlim` argument, 720

- `z`-matrices, 733
 - conceptualizing, 735–736
 - constructing, 735
- Z-tests
 - one-sample, 474–476
 - two-sample, 476–478