

INDEX

Page numbers in italics refer to figures and tables.

A

- a (accumulator) register, 14
- absolute jumps, 24
- active components, 5–9
- adc instruction, 26–27
- add instruction, 26–27
- addition operations, 26–27
- and instruction, 28
- animation
 - frame pacing, 98–101
 - palette fading system, 224–226
- arithmetic operations, 26–28
 - addition, 26–27
 - comparison, 27–28
 - decrement, 28
 - increment, 28
 - subtraction, 26–27
- Aseprite, xxix
- assembly code template, 57–66
 - compiling, 62–65
 - files, 57–62
 - hardware.rgbinc*, 58–59
 - main.rgbasm*, 59–60
 - sample.rgbasm*, 60–61
 - utils.rgbinc*, 61–62
 - running, 65–66
- assembly language, 11–40
 - constants, 39
 - CPUs, 13–16
 - flags, 14–15
 - registers, 14
 - special-purpose registers, 15–16
 - instruction categories, 20–35
 - arithmetic operations, 26–28
 - bit operations, 28–29
 - bitwise operations, 28
 - functions, 25
 - jumps, 21–24
 - loads, 20–21
 - rotations, 31–32
 - shifts, 29–31
 - stack operations, 32–34
 - local labels, 36–37
 - macros, 37–39
 - number formats, 16
 - sections, 35–36
 - syntax, 16–19
 - comments, 19
 - instructions, 17–19
 - labels, 17
- assembly statements, 85
- assembly step in ROM assembly, 43
- asserts, 121–122
- assets. *See* graphics assets
- ATRC_EN command, 334, 387
- attraction mode, SGB, 386–387
- ATTR_BLK command, 333, 359
- ATTR_CHR command, 333, 356
- ATTR_DIV command, 333, 362, 362
- ATTR_LIN command, 333, 361
- ATTR_SET command, 334, 366–367, 368
- ATTR_TRN command, 334, 366–367
- audio, 137–182
 - channel 1, 142–165
 - continuous sound, 162–164
 - control flags, 142–143
 - duty cycle, 145–147
 - frequency, 143–145
 - frequency sweep, 158–161
 - functions, 155–161
 - parameters, 143–154
 - sound length, 147–151
 - tips for using, 164–165
 - volume, 151–154
 - volume envelope, 155–158
 - channel 2, 165–166

- audio (*continued*)
 - channel 3, 166–177
 - control flags, 167
 - custom waveforms, 168–175
 - duty cycle, 175
 - parameters, 167–168
 - producing different waveforms, 172–175
 - producing square waves, 170–172
 - tips for using, 176–177
 - volume control, 175–176
 - channel 4, 177–182
 - polynomial counter, 178–180
 - sound effect examples, 180–182
 - DMG audio channels, 137–138
 - sound hardware control registers, 138–139
- auto increment flag, 274

B

- background, 71–72, 79
 - animation, 98
 - CGB, 272, 287–289, 288
 - defined, 93
 - displaying window over, 104–105
 - LCD parameters, 94–96
 - palette, 94
 - scrolling, 219
 - wrapping and, 96–97
 - window vs., 101–102
- background color palette data (rBCPD)
 - register, 273
- background color palette specification (rBCPS) register, 273–274
- background music (BGM) port, 383
- backslash (\), 85
- banks
 - defined, 36
 - overview, 236
 - VRAM in CGB, 284
 - WRAM in CGB, 298
- bank switching
 - disabling, 44
 - MBCs, 235–239
 - basic switching, 236
 - evolution of cartridges, 236
 - ROM with MBC enabled, 237–239
- BCD (binary-coded decimal), 14, 34–35

- bc register, 14
- BGB, xxviii
 - CGB
 - palettes, 280
 - testing, 301–302
- debugger
 - code view, 46–47
 - data view, 48
 - debug messages, 261–263, 263
 - inspecting ROM, 51–53
 - logging, 261–263
 - register view, 48
 - shortcuts, 49–50
 - source code breakpoints, 260
 - stack view, 48
 - symbols, 64–65
 - tips for using, 50
 - VRAM banks, 282
- emulating
 - Game Boy Printer, 306
 - GBA, 304
 - serial communication, 195–197
- enabling source code
 - breakpoints, 261
- hblank DMA, 294
- IO map, 282
- IR functionality, 300
- SGB
 - palettes, 355–356
 - switching between DMG and SGB
 - modes, 339
 - testing, 339–340
- VRAM viewer, 89, 276
- watch mode, 197
- BGM (background music) port, 383
- BGR555 color format, 272, 334, 335
- binary-coded decimal (BCD), 14, 34–35
- binary numbers, 16
- bit instruction, 28–29
- bit operations, 28–29
- bitwise operations, 28
- Bombberman GB (Wario Blast: Featuring Bombberman!)*, 326
- boot ROM, 54–55
- borders
 - BGB, 343
 - customizing, 371–377
 - base border sample, 371–375

- glitch workaround, 375–377
 - more border samples, 377
- graphics, 336, 336–338, 338
- break packets, 311, 311–312
- breakpoints in debugger, 52
- buffer variables, 202
- buttons
 - DMG, 4
 - generating interrupts, 130, 134
 - polling status of, 114–115
- byte cost, 18

C

- C (carry) flag, 14
- call instruction, 25
- cartridges
 - components of, 6–7
 - defined, 3
 - evolution of, 236
 - header, 42
 - picture of, 5
 - Tetris* and *Zelda*, 236
 - types of, 237
- catch function, 264
- ccf instruction, 34
- central processing unit. *See* CPU
- CF (compression field), 308
- CGB (Game Boy Color), xxvi–xxvii, xxvii, xxx, 271–304
 - compatibility mode, 300–304
 - detecting hardware model, 300–301, 302–304
 - flag values, 300
 - testing in BGB, 301–302
 - CPU double speed mode, 295–297
 - graphics, 272–289
 - copying data to VRAM with DMA, 289–295
 - leveraging VRAM banks, 277–284, 279
 - managing background and sprites
 - rendering priority, 287–289, 288
 - setting palettes, 272–277, 276
 - sprite functionalities, 284, 284–287
 - cgbconv tool, 278–279

- channel 1, 142–165
 - continuous sound, 162–164
 - control flags, 142–143
 - functions, 155–161
 - frequency sweep, 158–161
 - volume envelope, 155–158
 - parameters, 143–154
 - duty cycle, 145–147
 - frequency, 143–145
 - sound length, 147–151
 - volume, 151–154
 - registers, 164
 - tips for using, 164–165
- channel 2, 165–166, 166
- channel 3, 166–177
 - control flags, 167
 - custom waveforms, 168–175
 - different waveforms, 172–175
 - square waves, 170–172
 - duty cycle, 175
 - parameters, 167–168, 168
 - registers, 177
 - tips for using, 176–177
 - volume control, 175–176
- channel 4, 177–182
 - polynomial counter, 178–180
 - registers, 181
 - sound effect examples, 180, 180–182
- character files. *See* CHR files
- checksum
 - in packets, 308
 - printer flag, 312
 - in ROM memory map, 54
- child roles in transfer phase, 208
- CHR (character) files
 - converting tilesets to, 82–83
 - packetize tool and, 317
 - sgbconv tool and, 338
- client/server setup, 195
- clock
 - CGB, 298
 - controlling timer, 188
 - prescaler values, 179
 - role in polynomial counter, 178
 - setting frequency of, 190
 - ticks, 19
 - during transfers, 198

- clock divider
 - CPU double speed mode, 295–296
 - overview, 178
 - values, 179
- clock selection flag, 198
- code view in debugger, 46–47, 51, 53
- colors
 - CGB, 272
 - color palettes, 74, 334–335
 - color wheel, 276
 - DMG, 74–75, 75
 - SGB, 354–371
 - alternative attribute commands, 358–363
 - attribute commands with LCD
 - payload, 366–369
 - color palettes, 334–335
 - combination of LCD payload
 - commands, 369–371
 - palette commands with LCD
 - payload, 363–366
 - SNES graphics, 337
 - transparent, 106
- comments, 19
- common palette, 225
- comparison operations, 27–28
- compatibility mode in CGB, 300–304
 - detecting hardware model, 300–304
 - testing in BGB, 301–302
- compilation, defined, 44
- compressed data, 310–311
- compression field (CF), 308
- conditional jumps, 21–24
- console
 - components of, 7–9
 - defined, 3
- constants
 - declaring, 117–118
 - mutable, 228–229
 - overview, 39
- control flags
 - audio channel 1, 142–143
 - audio channel 3, 167
 - sprites, 107–108
- copy macro, 109–110
- counter
 - built-in connection to timer, 189, 189–190
 - polynomial, 178–180
 - using, 186–188
- cp (comparison) instruction, 27, 27
- cpl instruction, 34
- CPU (central processing units)
 - console, 5–6
 - DMG, 19
 - double speed mode in CGB, 295–297
 - flags, 14–15
 - frame interrupts and, 221
 - frequency, 186
 - overview, 7
 - registers, 14
 - special-purpose registers, 15–16
- cycle cost, 19
- cycles (machine cycles; M-cycles), 19

D

- daa instruction, 15
- data packets, 310, 310–311
- DATA_SND command, 334, 353
- data store (ds) command, 60
- DATA_TRN command, 334, 388
- data view in debugger, 48
- db (define byte) command, 84
- debugger and debugging, 46–50
 - code view, 46–47
 - data view, 48
 - faulty jumps, 263–264
 - inspecting a ROM, 51–53
 - logging and debug messages, 261–263
 - register view, 48
 - shortcuts for, 49–50, 50
 - source code breakpoints, 260
 - stack view, 48–49
 - tips for using, 50
- dec (decrement) instruction, 28
- define byte (db) command, 84
- define word (dw) command, 84
- delays between transfers, 210–211
- density byte, 309
- de register, 14
- di (disable interrupts) instruction, 34
- DisableLCD macro, 87–88
- Disasm Syntax combo box
 - in debugger, 50
- division operations, 31

- DMA (direct memory access), 226–233
 - copying to OAM with, 229–232
 - copying to OAM without, 227–229
 - mutable constants, 228–229
 - repeat blocks, 227–228
 - copying to VRAM with, 289–295, 292
 - displaying more than 40 sprites, 232–233
- DMG (Dot Matrix Game), xxvi, xxvii
 - audio channels, 137–138
 - cartridges, 6
 - CPU
 - cycles, 19
 - instructions, 396–399
 - register set, 15
 - internal components, 5
 - memory map, 9
 - motherboard, 8
 - power modes, 35
 - programs, 10
 - transferring data between two, 198–202
 - basic transfer, 199–201
 - registers and interrupt, 198–199
 - tips, 201–202
- d-pad
 - defined, 4
 - polling status of, 114–116
 - scrolling, 118–124
- ds (data store) command, 60
- duty cycle
 - audio channel 1, 145–147
 - audio channel 3, 175
- dw (define word) command, 84

E

- ei (enable interrupts) instruction, 34, 99–100
- emulators, xxviii
- entry point, defined, 42
- equ command, 117
- ERAM (external random-access memory)
 - bank number, 240
 - bank switching, 237
 - defined, 6
 - MBC5, 239–340
 - saves with, 243–246
 - sizes, 238

- ERAM enable (rRAMG) register, 240
- event tracking, 217–218
- execution cost, 19
- external features of Game Boy, 3–5
- external random-access memory.
 - See* ERAM

F

- f (flag; status) register, 14–15, 396
- fading
 - palette fades, 224–226
 - sounds, 155, 384
- falling edge, 190
- feeds, printer, 309
- fix step in ROM assembly, 44
- flag (f; status) register, 14–15, 396
- flags
 - audio
 - channel 1 control, 142
 - channel 3 control, 167
 - background values, 95
 - CGB OAM, 284
 - cp register, 27
 - CPUs, 14–15
 - Game Boy Printer, 312–313
 - LCD interrupt trigger, 218
 - LCD window flag values, 102
 - rLDC register, 94
 - rSC register, 198
 - rTAC register, 188, 188
 - sprite flag values, 106, 107
- flashcarts, xxx
- four-in-one interrupts, 218
- frame pacing, 98–101
- frames, defined, 70–71
- free-form waves, 166–167
- frequency
 - audio channel 1, 143–145
 - audio channel 3, 167
 - relationship with bit value, 143
 - sweep, 158, 158–161
 - update formulas, 160
- functions
 - macros vs., 39
 - overview, 25

G

Game Boy, *xxvi*, *xxvi*, *xxvii*, *xxx*, 3–10.

See also RGBDS toolchain

external features, 3–5

internal components, 5–9

cartridge components, 6–7

console components, 7–9

memory map, 9–10

programs, 10

Game Boy Advance, *xxx*

Game Boy Color. *See* CGB

Game Boy Light, *xxvi*, *xxvi*, *xxvii*

Game Boy Printer

error codes, *313*

flags, *312*, 312–313

packet types, 308–312

break, 311–312

data, 310–311

init, 309

print, 309

status, 312

picture of, *306*

print sequence, 314

sending images to, 314–323

serial protocol, 307–308

testing programs, 306–307

real hardware, 306–307

simulating printer, 307

Game Boy Pocket, *xxvi*, *xxvi*, *xxvii*

Game Link Cable, 194, *194*

general-purpose transfer mode, 291

gfxconv conversion tool, 83

GIMP, *xxix*

global labels, 36

graphics

CGB, 272–289

background and sprites rendering
priority, 287–289

copying data to VRAM with DMA,
289–295

leveraging VRAM banks, 277–284

setting palettes, 272–277

sprite functionalities, 284–287

DMA, 226–233

copying to OAM without DMA,
227–229

displaying more than 40 sprites,
232–233

leveraging DMA to copy to OAM,
229–232

elements of, 74–77

colors, 74

palettes, 74

tilemaps, 77

tiles, 74–77

frames, 70–71

high-level features, 71–73

LCD, 70–71, 216–218

event tracking, 217–218

modes, 216–217

relationship between elements, 78–79

SGB, 334–338

asset converters, 338

border graphics, 336–338

color palettes, 334–335

screen tiles, 336

tile addressing modes, 77–78

tricks for, 218–226

palette fades, 225–226

parallax scrolling, 219–224

vblank, 70–71

graphics assets, 81–91

adding to ROM, 85–87

converting, 82–84

custom tools, 83

exporting text files, 84

RGBDS toolchain, 82–83

copying to VRAM, 87–89

graphics features

background, 93–97

LCD parameters, 94–96

palette, 94

scrolling and wrapping, 96–97

frame pacing, 98–101

mechanics, 100–101

synchronization, 98–99

overview, 71–73

sprites, 106–112

LCD parameters, 106

limitations, 108

OAM, 107–108

palettes, 106

window, 101–105

background vs., 101–102

displaying over background, 104–105

moving, 102–104

H

- H (half carry) flag, 14–15
- halt instruction, 35, 99–101, 130, 252–253
 - hardware.inc* file, 58
 - hardware.rgbinc* file, 58–59
- hblank (horizontal blanking) mode, 216–217, 291, 294
- hexadecimal numbers, 16
- hl register, 14
- HRAM (high random-access memory)
 - defined, 7
 - DMA and, 230–232
 - moving stack from, 265

I

- ICON_EN command, 334, 386
- IE (interrupt enable) components, 7
- if...else statements, 22–23
- if statements, 22
- images, printing, 314–323
- IME (interrupt master enable) flag
 - defined, 34
 - interrupts and halt instruction, 252
 - manual interrupts, 249
- incbin directive, 85
- inc instruction, 28
- include guards, 62
- increment operations, 28
- indirect addressing, 20
- infrared (IR) devices, 299–300
- initialization procedure, SGB, 350–354
- InitOAM macro, 111–112
- init packets, 309, 309
- InitSample function, 95
- input
 - handling, 118–120
 - polling, 113–116
 - tracking and storing state, 125
 - updating, 122–124
- input/output (I/O) registers, 7
- instructions
 - arithmetic operations, 26–28
 - addition, 26–27
 - comparison, 27–28
 - decrement, 28
 - increment, 28
 - subtraction, 26–27
 - bit operations, 28–29
 - bitwise operations, 28
 - byte cost, 18
 - categories, 20
 - cycle cost, 19
 - defined, 17–18
 - functions, 25
 - jumps, 21–24
 - absolute vs. relative, 24
 - conditional vs. unconditional, 21–24
 - loads, 20–21
 - reference table for, 395, 395–399
 - rotations, 31–32
 - shifts, 29–31
 - stack operations, 32–34
- internal components, 5–9
 - cartridge components, 6–7
 - console components, 7–9
- interrupt enable (IE) components, 7
- interrupt enable (rIE) register, 99–100, 249
- interrupt flag (rIF) register, 249
- interrupt master enable flag.
 - See IME flag
- interrupts
 - debugging with, 249
 - defined, 99
 - disabling, 42
 - executing, 247–250
 - alternate vblank interrupt, 250
 - manual control, 249
 - nested, 248–249
 - priorities, 248, 248
 - halt instruction and, 252–253
 - IME influence, 252
 - multiple interrupts and vblank, 252–253
 - joypad, 128–134
 - defining interrupt function, 133–134
 - initializing variables, 129–130
 - tracking sample state, 129
 - updating sample, 130–133
- LCD, 218
- timer, 188–189
- vblank, 99–100
- writing, 251–252

- interrupts (*continued*)
 - writing (*continued*)
 - keeping registers clean, 251–252
 - repurposing reserved addresses, 251
- I/O (input/output) registers, 7
- IR (infrared) devices, 299–300

J

- joypads, 113–135
 - declaring constants, 117–118
 - defined, 4
 - input polling, 113–116
 - interrupts, 128–134
 - key press and release detection,
 - 125–128
 - scrolling background, 118–124
 - serial protocol and, 332
- SGB
 - disabling menu, 387
 - multiple joypads, 378
 - settings, 386–389
- jp instruction, 24
- jr instruction, 24
- JUMP command, 334, 389
- jumps, 21–24
 - absolute vs. relative, 24
 - conditional vs. unconditional,
 - 21–24, 22
 - debugging faulty, 263–264
- jump tables, 255–259

K

- keys
 - held state, 116
 - press and release detection, 125–128

L

- labels, 17
 - exporting, 61
 - jumps, 24
 - local, 36–37
 - macros, 39
- languages, higher-level, 12
- LCD (liquid crystal display)
 - background parameters, 94–96
 - board for, 8–9, 9
 - control register, 287
 - defined, 4

- DMG, 70–71
- event tracking, 217–218
- flags, 102
- interrupts, 218
- modes, 216–217
- payload
 - attribute commands, 366–369
 - combination of commands, 369–371
 - defined, 328
 - palette commands, 363–366
 - SNES, 388–389
 - tilemap organization, 331
 - transfer, 330
- refresh, 70–71, 87–88, 291
- rWX register, 103
- sprite parameters, 106
- status register bits, 218
- tile order, 329
- turning off, 87–88
- turning on, 89
- ldh instruction, 114
- left terminal, 138
- length counter flag, 142, 167
- LFSR (linear-feedback shift register)
 - implementing, 265–267, 266
 - polynomial counter, 178–179
- licensee code, 339
- line feed control, 309
- line Y (rLY) register, 217
- linkage step in ROM assembly, 44
- liquid crystal display. *See* LCD
- little-endian systems, 47
- load instructions, 20–21
- local labels, 36–37
- logging for debugging, 261–263
- loops, 23–24
- LY compare (rLYC) register, 217

M

- machine code, 12
- machine cycles (M-cycles), 19
- macros, 37–39
- magic number field, 308
- main label, 43
- main.rgbasm* file, 59–60, 87, 89–90
- map file, 62–63
- MASK_EN command, 334, 351
- master priority flag, 287

- maximal LFSR, 266, 267
- MBCs (memory bank controllers), 7
 - bank switching, 235–239
 - basic, 236
 - evolution of cartridges, 236
 - ROM with MBC enabled, 237–239
 - MBC5, 239–246
 - characteristics, 239–240
 - ROM bank switching, 240–243
 - saves with ERAM, 243–246
- M-cycles (machine cycles), 19
- memory map
 - chapter reference, 392–393
 - defined, 9–10
 - ROM, 53–55, 54
- MLT_REQ command, 334, 377–378
- mnemonics, 17
- modes, 216, 216–217, 217
- motherboards, 8
- multiplayer features and options, 194, 377–380
- multiplying operations, 30
- mutable constants, 228–229

N

- N (negative) flag, 14
- nested interrupts, 248–249
- nibbles, 15
- NMI (non-maskable interrupt), 389
- nop instruction, 34, 252
- number formats, 16

O

- OAM (object attribute memory)
 - console component, 7
 - copying to, without DMA
 - flags, 284
 - leveraging DMA to copy to, 229–232
 - scan mode, 216–217
 - sprites, 107–111
- object color palette data (rOCPD)
 - register, 275
- object color palette specification (rOCP5) register, 275
- objects, 72–73, 79
- opcodes (operational codes), 401–409
 - defined, 18
 - examples of, 401

- legend for tables, 402
- 1-byte, 402–405
- 2-byte, 406–409
- or instruction, 28

P

- pacing. *See* frame pacing
- packetize tool, 317
- packets
 - payload in SGB commands, 328
 - signals, 332, 333
 - structure of, 307, 307–308
 - types of, 308–312
 - break, 311–312
 - data, 310–311
 - init, 309
 - print, 309
 - status, 312
- packet type field, 308
- PAL01 command, 333, 355
- PAL03 command, 333
- PAL12 command, 333
- PAL23 command, 333
- palettes
 - area of CGB, 273
 - background, 94
 - byte index, 274
 - CGB, 272–277, 275
 - color, 74, 334–335
 - data index, 273
 - fades, 224–226
 - graphics data, 74, 75
 - overview, 79
 - SGB, 387
 - special effects, 75
 - sprites, 106, 109
 - window, 101
- PAL_PRI command, 334, 388
- PAL_SET command, 333, 363, 365, 369–370
- PAL_TRN command, 333, 363–364
- Pan Docs, xxix, 236
- parallax scrolling, 219–224
- parent roles, in transfer phase, 208
- passive components, 5–10
- payload field, 308
- payloads
 - compressing, 310–311

- payloads (*continued*)
 - LCD, 363–371
 - SGB commands, 327–331
- payload size field, 308
- pc (program counter) command, 15
- PCT_TRN command, 334, 372
- picture/pixel processing unit (PPU), 6–7, 70–71
- PKT files, 317
- play flag, 149–150
- PNG files
 - converting for SGB, 338
 - converting to CHR and TLM files, 82–83
- Pokémon Trading Card Game*, 311
- polynomial counter, 178, 178–180
- pop operation, 32
- power mode, 35
- PPU (picture/pixel processing unit), 7, 70–71
- prescaler, 178–179, 179
- printer. *See* Game Boy Printer
- print packets, 309, 309
- print sequence, 314
- program counter (pc) command, 15
- protocol
 - Game Boy Printer, 307–308
 - serial communication, 202–210
 - SGB, 331–333
- pseudorandom noise, 177–179
- pseudorandom numbers, 265–267
- push-down stack, 15
- push operation, 32
- Pyxel Edit, xxix

Q

- quadrangular waves, 142

R

- random number generators (RNGs), 186–187
- raw blocks, 310
- rBCPD (background color palette data) register, 273
- rBCPS (background color palette specification) register, 273–274
- rDIV register, 186, 192
- read-only memory. *See* ROM

- reception port (rRP) register, 299
- registers
 - audio channels, 137
 - channel 1, 164
 - channel 2, 166
 - channel 3, 177
 - channel 4, 181
 - cleaning in interrupt functions, 251–252
 - CPU, 14–16
 - MBC5, 240
 - palette in CGB, 275
 - push and pop instructions, 251–252
 - serial communication, 198–199
 - sound hardware, 138–139
 - special-purpose, 15–16
- register view in debugger, 48
- relative jumps, 24
- rendering mode, 216–217
- repeat blocks, 227–228, 310–311
- res instruction, 28
- restart sound flag, 142, 167
- restart vectors, 25
- reti instruction, 25
- ret instruction, 25
- return address, 15
- rgbasm tool, 43
- RGBDS toolchain, xxviii, 41–55
 - assembly step, 43
 - converting graphics assets, 82–83
 - debugger, 46–50
 - code view, 46–47
 - data view, 48
 - register view, 48
 - shortcuts for, 49–50
 - stack view, 48–49
 - tips for using, 50
 - fix step, 44
 - inspecting ROMs, 51–53
 - linkage step, 44
 - manual, 35
 - memory map, 53–55
 - running ROMs, 45
 - writing programs, 41–43
- rgbfix tool, 42, 44
- rgbgfx tool, 82–83
- rgbblink command, 44
- rHDMA registers, 290–291

- rIE (interrupt enable) register, 99–100, 249
- rIF (interrupt flag) register, 249
- right terminal, 138
- rKEY1 register, 296
- rla instruction, 31
- rlca instruction, 31
- rlc instruction, 31
- rLCDC register, 88, 287
 - background flag values, 94–95
 - sprite flag values, 106, 109
 - window flag values, 101–102, 105
- rl instruction, 31
- rLY (line Y) register, 217
- rLYC (LY compare) register, 217
- RNGs (random number generators), 186–187
- rNR10 register, 164, 165
- rNR11 register, 165
- rNR12 register, 164, 165
- rNR13 register, 144, 165
- rNR14 register, 144, 164, 165
- rNR30 register, 167, 177
- rNR31 register, 167, 177
- rNR32 register, 177
- rNR33 register, 167, 177
- rNR34 register, 167, 176, 177
- rNR43 register, 179
- rNR50 register, 138, 138
- rNR51 register, 138, 138–139
- rNR52 register, 139, 139
- rOCPD (object color palette data) register, 275
- rOCPS (object color palette specification) register, 275
- ROM (read-only memory)
 - adding graphics assets to, 85–87
 - bank number, 240
 - bank switching, 237, 237–239, 240–243
 - building, 43–44
 - assembly step, 43
 - fix step, 44
 - linkage step, 44
 - cartridge component, 6–7
 - images, 10
 - inspecting, 51–53
 - memory map, 53–55, 54

- running, 45
 - sections in, 35–36
 - sizes, 238
- rotations, 31–32
- rP1 register
 - input polling, 113–114
 - multiplayer options, 378
 - signal generation, 332, 332
- rRAMB register, 240
- rRAMG (ERAM enable) register, 240
- rROMB0 register, 240
- rRP (reception port) register, 299
- rSB (serial buffer) register, 198–199
- rSC (serial control) register, 198
- rSCX register, 96–97
- rSCY register, 96–97
- rsreset command, 118
- rsset command, 117
- rSTAT register, 218, 223
- rst instruction, 25
- rTAC (timer control) register, 188, 188, 190–192
- rTIMA (timer counter) register, 188, 190–192
- rTMA (timer modulo) register, 188, 192
- rWX register, 102–103, 105
- rWY register, 94, 102–103, 105

S

- sample.rgbasm* file, 60–61, 88, 90–91
- saves with ERAM, 243–246
- sbc instruction, 27
- scf instruction, 34
- screen tiles in SGB, 336
- scrolling
 - background, 96–97
 - d-pad, 118–124
 - parallax, 219–224
- seconds, counting, 192
- sections, 35–36
- Seiko S-951 thermal paper, 306
- serial buffer (rSB) register, 198–199
- serial communication, 193–214
 - cables and adapters, 195
 - chaining transfers, 210–214
 - defined, 193
 - between devices, 193–194
 - emulating with BGB, 195–197

- serial communication (*continued*)
 - hardware, 194–195
 - protocol, 202–210
 - registers, 199
 - between two DMGs, 198–202
 - basic transfer, 199–201
 - registers and interrupt, 198–199
 - tips for, 201–202
- serial control register (rSC), 198
- serial interrupts, 199
- serial protocol
 - Game Boy Printer, 307–308
 - SGB commands, 331–333
- serial transfer rates, 298, 298–299
- server/client setup, 195
- set instruction, 28
- sfcconv tool, 338
- SGB (Super Game Boy), *xxvi*, *xxvi*–*xxvii*, *xxvii*, 325–390
 - adding color to screen, 354–371
 - alternative attribute commands, 358–363
 - attribute commands, 366–369
 - combination of commands, 369–371
 - palette commands, 363–366
 - building and testing programs for, 338–340
 - enabling enhanced features, 339
 - testing on BGB, 339–340
 - testing on real hardware, 340
 - commands, 327–334
 - example, 328
 - format, 327, 327–328
 - payload, 328–331
 - serial protocol, 331–333
 - types of, 333–334, 333–334
 - controlling settings, 386–388
 - custom border, 371–377
 - glitch workaround, 375–377
 - graphics, 334–338
 - asset converters, 338
 - border graphics, 336–338
 - color palettes, 334–335, 335
 - screen tiles, 336
 - hardware detection, 340, 340–343
 - initialization, 350–354, 376–377
 - multiplayer options, 377–380
 - overview, 326
 - preloaded sounds, 380–386
 - sample foundations, 343–349
 - defining command headers, 344–345
 - implementing wait mechanics, 345–347
 - sending commands, 247–349
 - sending data for SNES, 388–389
- SGB2 (Super Game Boy 2), *xxvi*, *xxvii*, 326
- sgbconv tool, 338
- shifts, 29, 29–31, 158–159
- signed numbers, 31
- sla instruction, 29
- SNES (Super Nintendo Entertainment System), *xxvi*, *xxvi*
 - display size, 326
 - graphics format, 337
 - sending data to, 388–389
 - tiles color encoding, 337
- sonic artifacts, 154
- SOUND command, 333, 383–385
- sounds
 - audio length, 147–151
 - channel 1 parameter, 147–151
 - channel 3 parameter, 167
 - continuous, 162–164
 - effects in SGB, 381, 382
 - enable flag, 167, 176
 - fading, 155
 - hardware control registers, 138–139
 - playing preloaded, 380–386
 - possible lengths, 148
 - stopping, 161
- source code breakpoints, 260
- SOU_TRN
 - command, 333, 389
 - payload, 389
- sp (stack pointer) register, 15, 32
- Space Invaders*, 326
- speed mode switching, 296–297
- sprites
 - attributes in OAM, 107–108
 - copying to OAM
 - with DMA, 229–232
 - without DMA, 227–229
 - displaying more than 40, 232–233

- functionalities in CGB, 284–287
- LCD parameters, 106
- limitations regarding, 108
- overview, 72–73
- palettes, 106, 272–273, 275
- priority in CGM, 287–289
- square waves, producing, 170–172
- sra instruction, 29
- srl instruction, 29
- sSTAT (LCD status) register, 217
- stack
 - defined, 15
 - moving to WRAM, 265, 298
 - operations, 32–34
 - overflows and underflows, 32
- stack pointer (sp) register, 15, 32
- stack view in debugger, 48–49
- Start in Debugger option, 50
- static asserts, 122
- static-like noise, 178
- status (f; flag) register, 14–15, 396
- status packet
 - structure, 312
 - type, 312
- step lengths
 - of frequency sweeps, 158
 - of volume envelopes, 155
- stop instruction, 35
- sub instruction, 27
- subtraction operations, 26–27
- Super Famicom, 340
- Super Game Boy. *See* SGB
- Super Game Boy 2 (SGB2), xxvi, xxvii, 326
- Super Nintendo Entertainment System. *See* SNES
- swap instruction, 28
- symbol files, 63–65
- synchronization issues, 98–99
- syntax of assembly language, 16–19
 - comments, 19
 - instructions, 17–19
 - labels, 17

T

- Tetris*, 236
- text files, exporting, 84
- thermal paper, 306

- tilemaps
 - adding to ROM, 85–86
 - border graphics, 371–373
 - CGB, 277, 278, 283–284
 - converting to TLM files, 82–83
 - copying to VRAM, 87–88
 - defined, 77
 - size of in SNES, 337
 - window, 103–104
- tiles
 - addressing modes, 77–78, 101–102, 106
 - CGB, 277, 290
 - graphics data, 74–77
 - index, 107
 - LCD order, 329
 - overview, 79
 - screen, 336
 - SGB, 329, 371–374
 - VRAM banks, 277
- tilesets
 - adding to ROM, 85–86
 - converting to CHR files, 82–83
 - copying to VRAM, 87–88
- timbre, 146
- timer
 - built-in counter connection, 189–190
 - controlling data transfers, 212
 - control register, 188
 - counter register, 188, 189, 213
 - enable flag, 188
 - interrupts, 189, 248
 - modulo register, 188
 - packet transfers, 318–321
 - sample, 190–192
 - scalar variable, 190
 - tips for using, 192
 - using, 188–192
- timer control (rTAC) register, 188, 188, 190–192
- timer counter (rTIMA) register, 188, 190–192
- timer modulo (rTMA) register, 188, 192
- TLM files, converting tilemaps to, 82–83
- transfer phase, in serial communication, 205–210
- transfers
 - basic, 199–201
 - chaining, 210–214

- transfers (*continued*)
 - Game Boy Printer, 318–321
 - registers and interrupts, 198–199
 - serial transfer rates, 298–299
 - start flag, 198
 - tips for, 201–202
 - between two DMGs, 198
- transparent color, 106
- T-states, 19

U

- unconditional jumps, 21–24
- unique-tiles option, `rgbgfx`
 - conversion tool, 82
- UpdateSample function, 97–98, 100, 109
- utils.rgbinc* file, 61–62

V

- vblank (vertical blanking interval)
 - copying data to VRAM with DMA, 291
 - disabling LCD, 87–88
 - flag, 130–131
 - frame pacing, 101
 - interrupts, 99–100, 248, 250
 - mode, 216–217
 - multiple interrupts and, 252–253
 - overview, 70–71
- video random-access memory. *See* VRAM
- Vin channel, 138
- visual corruption, fixing, 110–112
- volume
 - audio channel 1, 151–158
 - audio channel 3, 168, 175–176
 - controlling, 138
 - envelope, 155, 155–158
 - SGB, 383–384
- VRAM (video random-access memory)
 - banks in CGB, 277–284, 282, 283
 - copying graphics assets to, 87–89

- copying to with DMA, 289–295
- defined, 7
- frame mechanics, 100–101
- hblank, 217
- LCD modes, 216
- LCD payload transfers, 330
- tiles and tilemap areas, 77–78
- transfers, 250

W

- wait mechanics, 345–347
- Wario Blast: Featuring Bomberman!*
 - (*Bomberman GB*), 326
- watch mode in BGB, 50
- waveforms, 168–175
- wave RAM, 168
- window, 101–105
 - comparing to background, 101–102
 - displaying over background, 104–105
 - moving, 102–104
 - overview, 71–73, 79
 - toggle, 127
- WRAM (work random-access memory)
 - banks in CGB, 298
 - checking usage, 120–122
 - console component, 7
 - initializing, 122
 - moving stack to, 265, 298
 - tracking consumption of, 121
- WRAM_USAGE constant, 121

X

- xor instruction, 28

Z

- Z (zero) flag, 14
- Zelda*, 236