

Serious Cryptography, 2nd Edition

A Practical Introduction to Modern Encryption

by Jean-Philippe Aumasson

Errata updated to print 2

Page	Error	Correction	Print corrected
11	The probability of getting a wrong key in our example is therefore $1 - 1/2^n$, a number very close to 1, meaning almost certainty.	The probability of getting a wrong key in our example is therefore $1 - 1/2^n$, a number very close to 1, meaning near certainty.	Pending
81	<pre># Create a 7-byte plaintext p. p = bytes([0x00] * 7)</pre>	<pre># Create a 4-byte plaintext p. p = bytes([0x00] * 4)</pre>	Pending
108	The column-round transforms the four columns like so: $\text{QR}(x_0, x_4, x_8, x_{12})$ $\text{QR}(x_1, x_5, x_9, x_{13})$ $\text{QR}(x_2, x_6, x_{10}, x_{14})$ $\text{QR}(x_3, x_7, x_{11}, x_{15})$	The column-round transforms the four columns like so: $\text{QR}(x_0, x_4, x_8, x_{12})$ $\text{QR}(x_5, x_9, x_{13}, x_1)$ $\text{QR}(x_{10}, x_{14}, x_2, x_6)$ $\text{QR}(x_{15}, x_3, x_7, x_{11})$	Print 2
198	<pre>sage: d = xgcd(e, phi); d 15417970063428857</pre>	<pre>sage: d = xgcd(e, phi)[1] % phi; d 11417851791646385</pre>	Print 2
199	<pre>sage: y = power_mod(x, e, n); y 19048323055755904</pre>	<pre>sage: y = power_mod(x, e, n); y 17129109575774132</pre>	Print 2
246	2. Compute an ECDH shared secret by computing $S = dP$.	2. Compute an ECDH shared secret by computing $S = dQ$.	Print 2
276	You can then express a qubit's state as $\alpha 0\rangle + \textcircled{\text{R}} 1\rangle, \dots$	You can then express a qubit's state as $\alpha 0\rangle + \textcircled{\text{B}} 1\rangle, \dots$	Print 2