



सिद्धिर्भवति कर्मजा

DEPARTMENT WISE PRODUCT LIST	
1	OPD
2	EMERGENCY
3	NICU
4	ICU
5	OT
6	LAB
7	DIALYSIS SETUP
8	CARDIOLOGY
9	DENTAL
10	OPHTHALMOLOGY
11	ORTHOPAEDICS
12	PHYSIOTHERAPY
13	RADIOLOGY
14	UROLOGY
15	NEUROSURGERY
16	ALL FURNITURES



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
1	Home Care Equipment	FINGER TIP PULSE OXIMETER	SpO2 Range: 70-100% Pulse Rate Range: 30-250 bpm Accuracy: $\pm 2\%$ for SpO2, ± 3 bpm for pulse rate Display: OLED/LED screen Power: Battery-operated (AAA or rechargeable) Size: Compact, ~ 50-100g Response Time: 5-10 seconds Used for monitoring oxygen levels and heart rate.
2	Home Care Equipment	IR THERMOMETER	Temperature Range: Typically 32°C to 42.9°C (89.6°F to 109.2°F) Accuracy: $\pm 0.2^\circ\text{C}$ ($\pm 0.4^\circ\text{F}$) Response Time: 1-2 seconds Display: LCD screen Power: Battery-operated (usually 2x AAA) Distance-to-spot ratio: 1:1 to 3:1 (depending on model) Mode: Body, surface, or room temperature settings Used for quick, non-invasive temperature measurement.
3	Home Care Equipment	DIGITAL THERMOMETER	Temperature Range: 32°C to 42.2°C (89.6°F to 108°F) Accuracy: $\pm 0.1^\circ\text{C}$ ($\pm 0.2^\circ\text{F}$) Response Time: 10-60 seconds (depending on model) Display: Digital LCD screen Power: Battery-operated (usually 1x button cell or AAA) Waterproof: Some models are water-resistant or waterproof Mode: Oral, rectal, or axillary measurements Used for precise and quick body temperature readings.
4	Home Care Equipment	BLOOD PRESSURE MONITOR	Pressure Range: 20-280 mmHg (systolic), 0-200 mmHg (diastolic) Accuracy: ± 3 mmHg Display: Digital LCD screen Power: Battery-operated (typically 4x AA or rechargeable) Measurement Method: Oscillometric (automatic) Cuff Size: Standard or large cuffs Features: Memory storage, irregular heartbeat detection Mode: Wrist or arm models Used for monitoring blood pressure at home or in clinical settings.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
5	Home Care Equipment	PULSE OXIMETER	Measures: SpO2 and pulse rate SpO2 Range: 70-100% Pulse Rate Range: 30-250 bpm Display: Large LCD screen, sometimes with waveform Power: AC-powered with battery backup Features: Alarms, data logging, and connectivity for patient monitoring Used in hospitals for continuous monitoring of patients' oxygen levels and heart rate.
6	Critical Care Equipment	MULTIPARA MONITER	Measures: ECG, heart rate, BP, SpO2, temperature, respiratory rate Display: LCD/touchscreen Accuracy: Varies by parameter Power: AC with battery backup Features: Alarms, data connectivity Used for continuous patient monitoring in healthcare settings.
7	Critical Care Equipment	ECG	Measures: Heart's electrical activity Leads: 3, 5, 6, or 12 leads (depending on model) Display: LCD or touchscreen Recording: Continuous or single waveform Accuracy: ± 1 mV Power: AC-powered with battery backup Features: Heart rate, arrhythmia detection, data storage, and printing options Used for diagnosing heart conditions and monitoring cardiac health.
8	Critical Care Equipment	DEFIBRILLATOR	Energy Output: 200-360 joules (adjustable) Display: ECG screen for heart rhythm monitoring Power: AC with battery backup Features: Manual shock delivery, defibrillation, and pacing Controls: Operator-controlled shock settings Portability: Usually compact but not as portable as AEDs Used by healthcare professionals to deliver shocks based on patient condition.
9	Critical Care Equipment	AED Defibrillator	Energy Output: 120-200 joules (biphasic) Display: LCD screen with shock advisories Power: Battery-operated Features: Voice prompts, automated shock delivery, ECG analysis Portability: Compact and lightweight Additional: CPR guidance, self-testing, and data storage Used for automatic shock delivery in cases of cardiac arrest, typically by non-medical users.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
10	Critical Care Equipment	POWER AIR PURIFYING RESPIRATOR	Type: Battery-operated air purifying system Protection: Filters airborne contaminants (e.g., dust, chemicals, pathogens) Battery Life: Typically 8-12 hours Airflow: Continuous, adjustable airflow for cooling and filtration Facepiece: Full-face or helmet design with clear visor Filters: HEPA or combination filters (depending on application) Comfort: Adjustable straps and lightweight design Applications: Healthcare, industrial, hazardous material handling Used for respiratory protection in environments with airborne hazards
11	Critical Care Equipment	OXYGEN CONCENTRATOR 5 LPM	Flow Rate: Up to 5 LPM Oxygen Purity: 93% $\pm$ 3% Power: AC-powered Noise Level: 40-50 dB Weight: 5-10 kg Features: Continuous flow, LCD display, alarms Used for delivering oxygen to patients with respiratory issues.
12	Critical Care Equipment	OXYGEN CONCENTRATOR 10 LPM	Flow Rate: Up to 10 LPM Oxygen Purity: 93% $\pm$ 3% Power: AC-powered Noise Level: 45-55 dB Weight: 10-15 kg (varies by model) Display: LCD screen for flow settings Features: Continuous flow, alarms, and safety features Used for providing higher oxygen flow to patients with more severe respiratory needs.
13	Critical Care Equipment	Medicine Vending Machine	Storage Capacity: Multiple compartments for various medicines Display: LCD or touchscreen for user interface Power: AC-powered with backup battery Payment System: Cash, card, or mobile payment options Security: Locked compartments, anti-theft features Features: Medicine selection, dispensing, inventory tracking, and notifications Size: Compact, suitable for public or healthcare settings Used for dispensing over-the-counter medicines or prescriptions in accessible locations.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
14	Critical Care Equipment	NEBULIZER	Type: Mesh nebulizer for aerosol therapy Particle Size: 1-5 microns for effective medication delivery Flow Rate: 0.25-0.5 mL/min Power: AC-powered or rechargeable battery Noise Level: Low noise operation (around 40 dB) Size: Compact and portable design Features: Quick medication delivery, easy to clean, and quiet operation Used for delivering respiratory medication in the form of mist for treating asthma, COPD, and other respiratory conditions
15	Critical Care Equipment	NCPAP	Type: Nasal Continuous Positive Airway Pressure (NCPAP) device Pressure Range: Typically 4-12 cm H ₂ O Flow Rate: Adjustable, usually 6-10 LPM Power: AC-powered with backup battery Display: Digital display for pressure and flow settings Features: Adjustable pressure, humidification, alarms for high/low pressure, and oxygen integration Used for providing respiratory support to infants and patients with respiratory distress or sleep apnea.
16	Critical Care Equipment	BIPAP	Modes: Inspiratory Positive Airway Pressure (IPAP) and Expiratory Positive Airway Pressure (EPAP) Pressure Range: IPAP: 4-20 cm H ₂ O, EPAP: 4-10 cm H ₂ O Flow Rate: Adjustable, typically 25-50 LPM Power: AC-powered with battery backup Display: Digital display for pressure and settings Features: Adjustable pressure, humidification, alarms, and oxygen integration Used for treating conditions like sleep apnea, COPD, and respiratory failure by assisting with both inhalation and exhalation.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
17	Critical Care Equipment	CPAP	Pressure Range & Mode: Continuous pressure typically 4–20 cm H₂O; single-mode (CPAP) operation. Ramp & Comfort Features: Adjustable ramp time (0–45 min) for gradual pressure increase; some have expiratory pressure relief (EPR) for comfort. Humidification & Interfaces: Often includes optional heated humidifier; compatible with nasal masks, full-face masks, or nasal pillows. Physical & Power Specs: Weight ~1–2 kg, low noise (<30–35 dB), powered by 100–240 V AC; some models support battery backup. Monitoring & Safety: Built-in memory or SD/USB for usage and leak data; alarms for mask-off, air leaks, or high/low pressure.
18	Critical Care Equipment	VENTILATOR	Modes: Assist-Control (AC), Synchronized Intermittent Mandatory Ventilation (SIMV), CPAP, BiPAP Tidal Volume: 100-1500 mL (depending on patient size) Respiratory Rate: Adjustable, typically 10-30 breaths per minute Pressure Range: 5-60 cm H₂O Oxygen Concentration: 21% to 100% (adjustable) Power: AC-powered with battery backup Display: LCD screen with real-time patient data Features: Alarms, monitoring, ventilation modes, data logging Used to provide mechanical ventilation for patients with respiratory failure or difficulty breathing
19	Critical Care Equipment	High Flow Nasal Cannula	Flow Rate: 10-60 LPM (liters per minute) Oxygen Concentration: 21% to 100% (adjustable) Pressure: Typically 2-8 cm H₂O Humidification: Heated humidification for comfort Power: AC-powered Display: Digital screen for flow and oxygen settings Features: Warm, humidified oxygen delivery, comfortable nasal prongs Used for delivering high-flow, oxygen-enriched air to patients with respiratory distress or hypoxemia, providing better comfort than standard nasal cannulas.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
20	Critical Care Equipment	High End ECG Machine	Leads: 12-lead (with 3-15 lead options) Display: Color LCD/touchscreen Recording: Continuous or single-page prints Power: AC with battery backup Features: Automated analysis, arrhythmia detection, real-time monitoring Connectivity: USB, Wi-Fi, Bluetooth Functions: ECG interpretation, stress test compatibility Used for detailed cardiac monitoring and diagnosis in healthcare settings.
21	Critical Care Equipment	Infusion Pump	Flow Rate: 0.1-999.9 mL/hr Accuracy: $\pm 5\%$ Power: AC with battery backup Display: LCD screen Alarms: Occlusion, air-in-line, low battery Mode: Continuous or bolus delivery Used for precise delivery of fluids or medications to patients.
22	Critical Care Equipment	Syringe Pump	Flow Rate: Typically 0.1-1500 mL/hr Accuracy: $\pm 2\%$ or better Power: AC-powered with rechargeable battery Display: LCD screen showing rate, volume, and alarms Syringe Size: Compatible with various syringe sizes (e.g., 1 mL to 60 mL) Alarms: Occlusion, syringe empty, low battery Mode: Continuous or programmable delivery Used for precise, controlled infusion of fluids or medications in medical settings
23	Critical Care Equipment	VENTILATOR LIFEVENT	• Power: 230 Volts AC $\pm 10\%$ 50 Hz • Fio2: 21 to 100% Selectable Respiratory Rate: 4 to 60 BPM • Inspiratory Time: .3 to 4 Seconds Inverse Ratio Ventilation: Yes provided. Range 4:1 • Battery Backup: 2 Hours • Flow Sensors: Yes provided. PEEP: 0 to 30 CmH20 Peak Inspiratory Pressure: 2 to 60 CmH20 Trigger Level: Zero to Minus 20 CmH20 • Input Gas Pressure, Air & Oxygen: 60 PSIG/4 Bar • Patient efforts in Assist Mode: Displayed on Digital Display Volume Range: 50 ml to 2500 ml



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
24	Critical Care Equipment	VENTILATOR LIFEVENT Advanced	High-performance ventilator for Adults to Neonatal use 15" touch screen and intuitive and user-friendly UI Maximizing care efficiency by adopting the leak compensation with trigger-synchronize function Caring patients with weak lung mechanic and children by offering the high frequency mode Providing doctors with convenience and reducing infection possibility in suction by adopting the closed suction function Remote monitoring through central monitoring system & Convenient product maintenance through smart viewer
25	Critical Care Equipment	AIR PURIFIER	Function: Removes pollutants, allergens, and particles from the air. Filtration System: Often includes HEPA filters, carbon filters, and sometimes UV-C light. Coverage Area: Varies (typically 100-500 sq ft). Air Quality Sensors: Some models have sensors to monitor air quality and adjust settings. Noise Level: Generally between 20-60 dB depending on the model. Power Consumption: Typically between 30-100 watts. Additional Features: Smart connectivity, auto mode, ionizer, remote control.
26	Mother & Child Care Equipment	BASSINET	Type: Portable or stationary cradle for infants, usually for newborns up to 6 months. Size: Compact and lightweight for easy movement, typically around 30-40 inches in length. Material: Soft fabrics like cotton, mesh sides for breathability, and a sturdy frame (wood or metal). Safety Features: Often includes safety straps, anti- rollover design, and breathable mesh sides. Additional Features: Can have a canopy, storage space, vibration settings, and soothing sounds. Weight Capacity: Usually supports babies up to 15- 20 pounds. Adjustability: Height-adjustable models are available



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
27	Mother & Child Care Equipment	PHOTOTHERAPY UNIT	SmartTilt Technology: Ensures uniform light intensity and compatibility with other NICU equipment. Effective Surface Area: Covers maximum body area per American Academy of Pediatrics standards. Therapy Timer: LCD display to track treatment time. Energy Efficient: Uses less power than CFLs. Minimal Maintenance: LEDs last 60 times longer
28			than CFLs, reducing costs. Quality: Operates reliably with power fluctuations.
29	Mother & Child Care Equipment	PHOTOTHERAPY UNIT Advanced	Voltage. 100 - 240 VAC. Frequency. 50/60 Hz. Application. Hospital. Dimensions. 123cm x 69cm x 64cm (HxWxD) (Overall), 55cm x 30cm x 5cm (LxWxD) (Light Unit) Power Consumption. Max 42 W. Model Number/Name. Brilliance Pro. LED Lifetime. Greater than 100000 Hours.
30	Mother & Child Care Equipment	PHOTOTHERAPY UNIT	The CFLs provide blue light at $\sim 30 \mu\text{W}/\text{cm}^2/\text{nm}$ and can provide an intensity of up to $40 \mu\text{W}$ at a distance of 35 centimetres. CFLs last five times longer than ordinary tubelights, requiring less frequent replacement. Focused blue light Light from the CFLs is focused on the baby bed, avoiding scatter into the care-provider space. Unwanted UV.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
31	Mother & Child Care Equipment	PHOTOTHERAPY UNIT LED	Coating Type Epoxy/powder coated body for scratch,Rust prevention and PU coating for plastic parts LED Intensity50 W cm-2 nm-1 Effective Surface Area50 x 25 cm Length 680 mm Mobility 3 swivel casters with brakes LED Life 30,000 Hours Recommended Treatment Distance 45 cm Width 900 mm Power Rating Max 60 W Height 1230 +/-20 mm to 1680 +/- 20mm Tilting Head0-90 Degree ModelPT 100 Wavelength 450-460 nm Weight Maximum 17 Kg Dimensions 730 x 690 x 1230 mm (L x W x H) Power Source 120 -240 V,50/60 Hz
32	Mother & Child Care Equipment	RADIANT WARMER	Controlled Thermal Environment The quartz heater provides uniform warmth rapidly all over the bed. The height of the heater unit maybe adjusted for different bed heights. Display with back up The display has a battery backup and indicates the temperature even during power failuresFrequency:50/60 Hz Display Type:LED Power Supply:220-240 V AC
33	Mother & Child Care Equipment	INFANT WARMER	Type: Neonatal radiant warmer Heating System: Advanced radiant heating with adjustable temperature control Temperature Range: Typically 36–38°C Features: Soft mattress for comfort, easy interface for control, and an adjustable height Monitoring: Built-in temperature sensors for accurate monitoring Power Supply: Electric with energy-efficient design Safety: Over-temperature alarm and safety features Application: Designed for use in NICUs and delivery rooms for premature or low-birth-weight infants



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
34	Mother & Child Care Equipment	RADIANT WARMER	Type: High-end neonatal radiant warmer Heating System: Advanced radiant heating with precise temperature control Temperature Range: Adjustable, typically 36–38°C Features: Microprocessor-controlled with digital display, flexible positioning for ease of use Monitoring: Built-in temperature sensors and alarms for over-temperature protection Power Supply: Electric with energy-saving design Safety: Safety alarms for temperature deviations and system malfunctions Application: Designed for NICUs and critical care units for premature or low-birth-weight infants
35	Mother & Child Care Equipment	Resucitator	Type: Manual resuscitation device for neonatal and pediatric patients Design: T-piece valve system for controlled pressure delivery Pressure Settings: Adjustable inspiratory and expiratory pressure control Features: Single-hand operation, durable construction, and easy-to-clean components Oxygen Supply: Connects to external oxygen source for continuous flow Safety: Includes pressure relief valve to prevent over-pressurization Application: Used for resuscitation during neonatal emergencies or respiratory support in delivery rooms and NICUs
36	Mother & Child Care Equipment	Weighing Scale	Type: Digital neonatal and pediatric weighing scale Capacity: Typically up to 20 kg (or as specified) Accuracy: High precision with minimal error margin (e.g., $\pm 10\text{g}$) Display: Clear digital display for easy reading Features: Lightweight, portable, and easy to clean surface Power Supply: Battery-operated or mains-operated Additional: Tare function for subtracting weights like blankets Application: Used for accurate weighing of infants, newborns, and pediatric patients in hospitals and clinics



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
37	Mother & Child Care Equipment	Height Scale	Type: Digital or mechanical Range: 20 cm to 90 cm (varies) Accuracy: High precision Display: Digital or analog Material: Durable, easy to clean Power: Battery-operated (for digital models) Application: Used for measuring infants and children's height in medical settings.
38	Mother & Child Care Equipment	TRANSPORT INCUBATOR	Type: Neonatal transport incubator Heating System: Controlled temperature with radiant warmer Temperature Range: Adjustable, typically 36–38°C Power Supply: Mains and battery-operated for portability Features: Compact design, secure patient enclosure, and easy-to-use controls Monitoring: Temperature, humidity, and other vital signs monitoring Safety: Over-temperature protection, oxygen supply connection Application: Designed for safe transport of critically ill or premature infants
39	Mother & Child Care Equipment	BABY INCUBATOR	Type: Neonatal incubator Heating: Microprocessor-controlled radiant heating Temperature Range: 36–38°C (adjustable) Monitoring: Temperature and humidity sensors Features: Transparent shell, adjustable humidity control Safety: Over-temperature and oxygen alarms Application: For premature or low-birth-weight infants in NICUs.
40	Mother & Child Care Equipment	BABY INCUBATOR Advanced	Type: Advanced neonatal incubator Heating: Microprocessor-controlled radiant heating Temperature Range: 36–38°C (adjustable) Monitoring: Temperature, humidity, and vital signs Safety: Over-temperature and oxygen alarms, backup power Application: For premature or ill infants in NICUs.
41	Mother & Child Care Equipment	BABY INCUBATOR	Heating: Adjustable radiant heating (36–38°C) Humidity Control: Adjustable settings Monitoring: Temperature, humidity, and vital signs Safety: Over-temperature and oxygen alarms, backup power Material: Transparent shell for visibility Application: Used for premature or ill infants in NICUs.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
42	Mother & Child Care Equipment	Neonatal Warmer Care System	Heating: Adjustable radiant heating (36–38°C) Monitoring: Temperature monitoring with alarms Safety: Over-temperature protection Power Supply: Electric with backup options Application: For neonatal care in NICUs and delivery rooms.
43	Mother & Child Care Equipment	RESUSCITATOR	Type: Manual resuscitation device for neonates and infants Design: T-piece valve system for controlled ventilation Pressure Control: Adjustable inspiratory and expiratory pressure Oxygen Supply: Connects to an external oxygen source Safety: Pressure relief valve to prevent over-pressurization Application: Used in neonatal resuscitation during emergencies in delivery rooms and NICUs.
44	Mother & Child Care Equipment	DELIVERY RECOVER BED	Type: Multi-functional bed for labor, delivery, and recovery Adjustable: Various positions for comfort Safety: Sturdy frame and secure side rails Mattress: Soft, easy-to-clean
45	Mother & Child Care Equipment	EXAMINATION COUCH	Type: Adjustable examination couch for medical use Design: Sturdy frame with soft, durable upholstery Adjustable: Backrest and height adjustments for patient comfort Safety: Non-slip surface and stable construction Features: Easy-to-clean, ergonomic design Application: Used for patient examinations in clinics, hospitals, and healthcare settings.
46	Mother & Child Care Equipment	ELECTRONIC BABY WEIGHING SCALE	Type: Digital weighing scale for infants Capacity: Typically up to 20 kg Accuracy: High precision with $\pm 10\text{g}$ or better Display: Clear digital screen for easy reading Features: Tare function for subtracting weights like blankets Power Supply: Battery-operated Application: Used for weighing infants in hospitals, clinics, and pediatric settings.
47	Mother & Child Care Equipment	DELIVERY TABLE	Battery Back Up: Up to 50 movements Paper Roll Holder Diameter: 150 mm Paper Roll Holder Length: 500 mm Adjustable: Backrest, height, and leg sections Design: Sturdy, ergonomic, easy-to-clean upholstery Safety: Secure side rails, non-slip base Application: Used in delivery rooms for maternal comfort during childbirth.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
48	IVD Diagnostics Test Kit	RT PCR KIT	Detection Method: Real-time PCR Target Genes: Specific viral targets Sample Type: Swabs (Nasopharyngeal/Oropharyngeal) Assay Format: Multiplex, single-step RT-PCR Sensitivity: 100% Specificity: 99% Storage: Room temp or 2-8°C Shelf Life: 12-24 months Reaction Time: < 2 hours or 35 minutes Internal Control: RNAs P Gene Evaluation: ICMR/CE marked
49	IVD Equipment	HB Analyzer, Automated	Sampler Handler: 10-position rack, barcode ID Sample Type: Whole blood (EDTA K3/K2), haemolysate Time for Analysis: ~3.5 min/sample Interferences: Removes labile up to 10% Sampling System: Precision aspiration probe Aspiration Volume: 14.5 µl (blood), 670 µl (lysate) Pump: 2 high-pressure syringe pumps Detector: UV-Vis Reagent Traceability: RFID Printer: Built-in thermal, external printer compatible
50	IVD Equipment	Semi auto biochemistry analyzer	Optical Module: 340-670 nm, 8 filters, 0-3.0 OD, Halogen lamp 12V/20W Measuring Module: Triple cuvette, 18 µl flow cell, 10 mm square, Peltier 20-40°C, Min 200 µl Analysis Modes: 1-/2-point, absorbance, rate, coagulation Memory/QC: 200 tests, 1000 results, 3 QC levels with graphs Display/Printer: High-res LCD, thermal printer Interface: USB for PC/printer, keyboard port Power/Size: 18V DC, 70W, 205x450x300 mm, ~7 kg Optional: 16-position incubator
51	IVD Equipment	Coagulation analyzer	ID, second assay prep during analysis Test Principles: Clotting (640 nm), Immuno-turbidimetric (800 nm) Dimensions/Weight: 216x205x75 mm, ~1 kg Environment: 17-32°C, max 80% RH non-condensing Power: 100-240 VAC, 50/60 Hz, 45W, in-rush 150 VA Calibrations: 6 levels/assay, active curve storage QC: 12 controls, Levey-Jennings plot, auto stats, 1000 QC results Results: 1000 patient/QC results, auto overwrite, reaction curves on USB (FAT32)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
52	IVD Equipment	Five part hematology analyzer	Mode Type: Whole blood, Predilute, Capillary Parameters (36): CBC, DIFF, *Research use (*ALY, *LIC, *NRBC, etc.) Measurement Principles: RBC/PLT: Impedance, WBC + DIFF: Laser Flowcytometry, Hb: Cyanide-free colorimetry Histograms: 3 (WBC/RBC/PLT), Scattergram: 3 (2D), 1 (WBC/Baso) Throughput: Up to 60 tests/hour Sample Volume: Whole: 15 μL, Predilute/Capillary: 20 μL, CBC: 11 μL Linearity Range: WBC: 0-300 ($\times 10^3/\mu$L), RBC: 0-8.50 ($\times 10^3/\mu$L), Hb: 0-25.0 g/dL, HCT: 0-67%, PLT: 0-3000 ($\times 10^3/\mu$L) Calibrator: ELite H Cal, Controls: H5 CON L/N/H Stability (2-8°C): 16 days (open vial) Data Storage: 100,000 results, 100 calibrators, 6-month reagent logs QC: 500 files, L-J graph, X-Bar analysis Dimensions: 364x498x431 mm, Weight: 26.5 kg Reagents: H560 Dil, Lyse1, Lyse2, Elite H Clean Interfaces: 4 USB, 1 LAN (HL7, TCP/IP, LIS) Environment: 15-40°C, 30-90% RH Power: 100-240V, built-in stabilizer, 200 VA
53	IVD Equipment	Immunoassay Analyzer	Sample Capacity: 104 test tubes Frequency: 50/60 Hz Voltage: 115-230 V Weight: 90 kg Power Consumption: 200 W Operating Temp.: 10-40°C Max Humidity: <80% Plate Support: Self-centric Tips Capacity: Up to 192 Serial Dilution: Yes Pre-Dilution Area: Up to 192 wells Reagent Capacity: 9 bottles (60 ml), 88 positions (6 ml tubes) Sample Tube Size: 6 ml Loading Flexibility: 174 tubes ELISA Plates: 4 or 16 IFA slides Assays: Up to 12 Start-up Time: <3 min Self-Check: Yes



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
54	IVD Equipment	Fully automated biochemistry analyzer with electrolyte	Application: Laboratory Assays: Clinical Chemistry Reaction Cuvette: 72 hard glass cuvettes Water Consumption: <14 L/hr Throughput: 400 photometric/hr, 640 tests/hr (with ISE) Weight: ~200 kg Dimensions: 897x655x1170 mm Reading Volume: 180 μL OD Range: 3 mm Power Requirement: AC 220V $\pm$10%, 50 Hz Power Consumption: 800 VA Minimum Order Quantity: 1 Piece Highlights: Continuous sample loading, high productivity, cost-efficient, reliable for heavy testing demands.
55	IVD Equipment	ELISA READER/WASHER LISA	Wash Head: 8/12 manifold, Plate Types: 96/48 well (Flat, U, V-bottom) Wash Programs: 50, Dispensing Volume: 50-3000 μL, Precision: <2% at 350 μL Soak Time: 0-24 hrs, Residual Volume: $\leq$2 μL (V/U), $\leq$3 μL (Flat) Bottles: 2 wash, 1 rinse, 1 waste (2L) Power: AC 220V/110V, <80 VA, Dimensions: 710x530x380 mm, Weight: 9.5 kg Elisa Reader (T): Plate Types: 96 wells (U, V, Flat), Modes: Absorbance, Quantitative, Qualitative Photometer: 8-channel, 400-750 nm, Measurement Time: 8 sec (Speed) Power: 16V-24.5V DC, 90W, Dimensions: 502x369x216 mm, Weight: 7 kg
56	IVD Equipment	Electrolyte analyzer	Advanced Biosensor Technology Small Aspiration Volume Short Turnaround Time (TAT) No Maintenance Cost Lab Mean Enabled Predictable Cost Per Sample



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
57	IVD Equipment	Tissue processor, Automated	Features: Fully automated, precise control, high throughput Capacity: (Cycle capacity) Reagents: Standard histology reagents Power: 115/230V AC Dimensions: (Dimensions) Weight: (Weight) Temperature Control: Adjustable
58	IVD Equipment	RT PCR KIT	Detection: Simultaneous detection of N1 & RdRp gene targets (SARS-CoV-2) Technique: Single Step, Multiplex, Real-time RT-PCR Viral Targets: N1 Gene, RdRp Gene Internal Control: RNAs P Gene Specimen: Nasopharyngeal & Oropharyngeal swabs Assay Time: < 2 hours Sensitivity: 100% Specificity: 99% Analytical Sensitivity: 5 copies/reaction Evaluation: ICMR approved Shelf Life: 12 months Storage: 15°C-25°C
59	IVD Equipment	RT PCR COVID 19 Test	Key Features: Taqman chemistry assay High primer sensitivity & specificity Microchip-based real-time PCR Minimal sample requirement (6µL) Smart chip with preset quantitation data Chip re-use lock Contamination/evaporation-resistant reaction port Test Duration: 35 minutes Storage/Stability: 2-30°C, 2 years



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
60	IVD Equipment	RAPID ANTIGEN KIT	Detection: SARS-CoV-2 Antigen Capture: SARS-CoV-2 nucleocapsid antibody Conjugate: SARS-CoV-2 nucleocapsid & control antibody with colloidal gold Specimen: Nasopharyngeal swab Total Time: 15 minutes Sensitivity: 94% Specificity: 100% Evaluation: ICMR Shelf Life: 24 months PR Code: 134335 Pack Type: Rapid Pack Size: 25 tests Method: Immunochromatographic assay
61	IVD Equipment	FULLY AUTOMATED CLINICAL ANALYSER	System Type: Automated, 1-3 reagent Throughput: 1040 tests/hr (800 photometric, 240 with ISE) Methods: 1-Point, 2-Point, Rate-A, Rate-B Tray: 147 cuvettes Mixing: Stirrer, variable speed Volume: 150 µl Cleaning: 7-stage, 2-stage drying Photometer: 15 wavelengths OD Range: 0.0-3.0 Light Source: Tungsten halogen Water Consumption: <25L/hr Power: AC220V/AC110V, 2000VA Dimensions: 1350 x 1000 x 1250 mm Weight: 275 kg Sample Handling: 150 samples, 2-60 µl, 70 µl ISE, auto rerun Reagent Handling: 86 positions, 60-300 µl R1, 0-200 µl R2/R3 Interface: RS-232, TCP/IP, USB Printer



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
62	IVD Equipment	FULLY AUTOMATED CLINICAL ANALYSER	System Type: Automated, Discrete, Random Access Throughput: 400 tests/hr (photometric), 640 tests/hr (ISE) Methods: 1-Point, 2-Point, Rate-A, Rate-B, Direct Potentiometry Tray: 72 cuvettes Mixing: Variable-speed stirrer Volume: 180 µl Cleaning: 6-stage, 2-stage drying Photometer: 12 wavelengths, 0-3.0 OD Power: AC 220V ±10%, 800 VA Dimensions: 897 x 655 x 1170 mm Weight: 200 kg Sample Handling: Up to 82 positions, 2-70 µl pipetting Reagent Handling: 56 positions, 60-300 µl pipetting Interface: USB, TCP/IP, RS-232 OS: Windows Database: Unlimited results
63	IVD Equipment	FULLY AUTOMATED CLINICAL ANALYSER	System Type: Discrete, automated, random access Throughput: 360 tests/hr (photometric), 600 tests/hr (ISE) Methods: 1-Point, 2-Point, Rate-A, Rate-B, Direct Potentiometry (optional) Tray: 60 hard glass cuvettes Mixing: Stirrer with variable speed Volume: Min 150 µl, Max 200 µl Cleaning: 5-stage cleaning, 2-stage drying Photometer: 12 wavelengths (340-750 nm), 0-3.0 OD Power: AC 220V ±10%, 800 VA Dimensions: 675 x 840 x 1120 mm Weight: 150 kg Sample Handling: 82 positions, 2-70 µl pipetting Reagents: 50 positions, 50-300 µl pipetting Interface: USB, TCP/IP, RS-232 OS: Windows Database: Unlimited results



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
64	IVD Equipment	FULLY AUTOMATED CLINICAL ANALYSER	Throughput: 200 photometric tests/hr, 400 with ISE (Optional) Reagent Positions: 50 cooled Sample Type: Whole blood, Serum, Plasma, Urine, CSF Reading Volume: 180 μl Sample Volume: 2-70 μl (Adjustable in 0.1 μl) Reagent Volume: 10-300 μl (Adjustable in 1 μl) Light Source: Halogen lamp Onboard Laundry: 6-stage cleaning, 2-stage drying with cuvette validation Calibration Type: Linear, Non-Linear, Multipoint Programmable Parameters: Default + 10 user-defined Dimensions: 810 x 800 x 600 mm Weight: 120 kg
65	IVD Equipment	FULLY AUTOMATED CLINICAL ANALYSER	System: Automated, random access, 1-2 reagent, bench-top Throughput: 180 tests/hr, 400 with ISE (optional) Assay Modes: 1-Point, 2-Point, Rate-A, Rate-B, Potentiometry (optional) Reagents: 25 fixed, 15 flexible, 2 Rgt/Dil at RT Sample Volume: 2-70 μl (adjustable) Reading Volume: 180 μl Reagent Dispensing: 10-300 μl (adjustable) Wavelengths: 8 (340-700 nm) Absorbance: 0-3.0 OD Mixer: 3 levels (Low/Medium/High) Safety: Obstruction & liquid level sensing System Interface: USB, Windows OS Dimensions: 675(W) x 450(D) x 300(H) mm Weight: ~65 kg Power: AC 220V/110V, 600 VA



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
66	IVD Equipment	SEMI AUTOMATED CLINICAL ANALYSER	Optical Module: Static photometer, 340-670 nm, 8 filters, 0-3.0 OD range, Quartz halogen lamp (12V, 20W) Measuring Module: Triple cuvette system, 18 µl flow cell, Peltier temp control (20°C-40°C), 200 µl minimum volume Analysis Modes: 1/2-point linear/non-linear, rate A, coagulation, absorbance Memory: 200 test programs, 1000 results, 3 levels QC Result Recall: Reports by date, ID, test, and patient Built-in QC: Levy-Jennings graphs Display: High-resolution LCD, 120x92 mm, 41 keys Printer: Built-in thermal printer Interface: USB for PC and printer, external keyboard Power: 18V DC, 70W, 115/230V AC Size: 205 (H) x 450 (W) x 300 (D) mm Weight: 7 kg Optional Accessories: 16-position dry block incubator
67	IVD Equipment	SEMI AUTOMATED CLINICAL ANALYSER	Throughput: 60 samples/hour Photometric Range: 0-3.0 OD, 0.0001 resolution Assays: Clinical Chemistry Test Programs: 150 user-defined programs Precision: <1% CV Optical System: Static Photometer, 340-630 nm Light Source: Halogen Lamp Wavelengths: 340, 405, 505, 546, 578, 630 nm Memory Storage: 1000 results, QC data Power Supply: 100-240V, 50-60Hz, 20W Dimensions: 250mm (H) x 500mm (L) x 350mm (D) Weight: Approx. 15 kg Interface: USB for PC & external devices Optional Accessories: External Incubator (16 position)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
68	IVD Equipment	SEMI AUTOMATED CLINICAL ANALYSER	Measurement: Mono/Bichromatic, 1 & 2 Point Linear/Non-Linear, Rate A, Absorbance Range: 0-3.0 OD, 0.0001 resolution Wavelengths: 340, 405, 505, 546, 578, 630 nm + 2 optional Calibration: Multi-point with graphical display QC: Levy-Jennings graph Storage: 5000 results Aspiration: Peristaltic pump, 100-2997 µl, flow cell 33 µl Temp. Control: 20°-40°C Reports: Date/ID collated Printer: Inbuilt thermal Connectivity: USB to PC, printer, optional incubator
69	IVD Equipment	SEMI AUTOMATED CLINICAL ANALYSER	Throughput: 60 Samples/Hour Photometric Range: 0-3.0 OD, resolution 0.0001 Abs Weight: Approx 15 kg Voltage: 100V-240V Frequency: 50 Hz-60 Hz Wattage: 20W Dimensions: 250mm (H) x 500mm (L) x 350mm (D) Test Program: 150 open test programs, selectable via keypad Optical System: Static Photometer Precision: Better than 1% CV Memory Storage: 1000 Results, 2-level monthly QC data, reagent blank Light Source: Halogen Lamp MOQ: 2



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
70	IVD Equipment	Haematology Analyzer Automated 3 Part	Test Type: Whole Blood, Predilute, Capillary Parameters: 24 including CBC, Mentzer index, RDWI Principle: Electrical Impedance for RBC/PLT/WBC/DIFF, Cyanide-Free Colorimetry for Hb Sample Volume: 9 μL (Whole Blood), 20 μL (Predilute, Capillary) Throughput: 60 Tests/Hr Linearity Range: WBC: 0-300, RBC: 0-8.5, Hb: 0-25, HCT: 0-67, PLT: 0-3000 Quality Control: 500 files with L-J graph, X-Bar Analysis Data Storage: 50,000 Results with Graphs Dimensions: 364 x 477 x 417 mm Weight: 25 kg Interfaces: 4 USB, 1 LAN (HL7, TCP/IP) Operating Temp: 15-40°C, Humidity: 30-90% Power: 100-240V, 50/60Hz, 200VA
71	IVD Equipment	Haematology Analyzer 5 Part Automated	Test Type: Whole Blood, Predilute, Capillary Parameters: 36 including CBC, DIFF, MENTZER index, RDWI (Research use only) Principle: Electrical Impedance for RBC/PLT, Tri-angle Laser Flowcytometry for WBC/DIFF, Cyanide- Free Colorimetry for Hb Sample Volume: 15 μL (Whole Blood), 20 μL (Predilute, Capillary), 11 μL (CBC Mode) Throughput: Up to 60 Tests/Hr Linearity Range: WBC: 0-300, RBC: 0-8.5, Hb: 0-25, HCT: 0-67, PLT: 0-3000 Quality Control: 500 files with L-J graph, X-Bar Analysis Data Storage: 100,000 Results with Graphs, 100 calibrator results, Reagent log for 6 months Dimensions: 364 x 498 x 431 mm Weight: 26.5 kg Interfaces: 4 USB, 1 LAN (HL7, TCP/IP) Operating Temp: 15-40°C, Humidity: 30-90% Power: 100-240V, 50/60Hz, 200VA



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
72	IVD Equipment	Haematology Analyzer, 5 PART, Advanced	Test Type: Whole Blood, Predilute, Capillary Autoloader: 60 Tubes, Continuous Loading with Auto-Mixing Parameters: 36 including CBC, DIFF, Mentzer index, RDWI (Research use only) Principle: Electrical Impedance for RBC/PLT/WBC, Tri-angle Laser Flowcytometry for WBC DIFF, Cyanide-Free Colorimetry for Hb Sample Volume: 20 μL (Whole Blood, Pre-diluted, Capillary), 13 μL (CBC Mode) Throughput: 80 Tests/Hr Linearity Range: WBC: 0-300, RBC: 0-300, Hb: 0-25, HCT: 0-67, PLT: 0-3000 Quality Control: 500 files with L-J Graph, X-Bar Analysis Data Storage: 100,000 Results with Graphs Dimensions: 650 x 550 x 610 mm Weight: 59 kg Interfaces: 4 USB, 1 LAN (HL7, TCP/IP) Operating Temp: 15-40°C, Humidity: 30-90% Power: 100-240V, 50/60Hz, 200 VA
73	IVD Equipment	HPLC ANALYSER	Sample Type: Whole blood (EDTA), Haemolysate Weight: 23 kg Dimensions: 369 x 565 x 444 mm Printer: Built-in thermal printer, external printer support Altitude: <2000 m Humidity: 10-90% non-condensing Temperature: 17-32°C Sampler Handler: 10-position rack, internal barcode reader Analysis Time: 3.5 minutes/sample Interference: Removal of labile up to 10% Rack Capacity: 10 samples Sample Volume: 14.3 μL (whole blood), 670 μL (lysate) Pump: 2 high-pressure syringe pumps Detector: UV-Vis Reagent Traceability: RFID Display: 8.4" color touch screen Power: 90-264V AC, 150W Connectivity: Serial Port, Ethernet, 5 USB Ports



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
74	IVD Equipment	ESR Analyzer	Sample Type: EDTA Sample Volume: >1.5 ml Display: 640x480 TFT with LED backlight Result Time: <25 min Range: 0-140 mm/hr Touch Screen: 5.7" resistive Temperature Correction: 18°C QC: 3 levels, LJ Graphs, 250 results Positions: 30 Throughput: 60 samples/hour Mode: Continuous, STAT available Mixer/Printer/Barcode: Inbuilt Data Storage: 5000 results Operating Temp: 20-30°C Power: 100-240V AC, 90W Dimensions: 550x500x395 mm Weight: 20 kg
75	IVD Equipment	Urine Analyzer	Sample Type: Urine Sample Volume: 5-20 µL Display: 7" TFT touch screen Result Cycle Time: < 5 minutes Throughput: 60 tests/hour QC: In-built 3-level QC Data Storage: 5000 results Operating Temp: 15-30°C Power Supply: 100-240V AC Dimensions: 430 (W) x 350 (D) x 500 (H) mm Weight: 12 kg



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
76	IVD Equipment	Coagulation analyzer 4 Channel	Model: 4-Channel Haemostasis System Sample Type: Whole blood, Plasma Weight: 3 kg Dimensions: 300 x 290 x 90 mm Assay Capacity: 4 simultaneous tests, single/duplicate assays Sample ID: 14-digit alphanumeric Preparation Line: Second row for incubation during analysis Test Principles: Clotting (640nm), Chromogenic (405nm), Immuno-turbidimetric (800nm) Power Supply: 100-240 VAC, 45W Temperature: 17-32°C, Max 80% RH Calibration: 6 levels, active curve storage Quality Controls: 12 control names, Levey-Jennings plotting, stats calculation Stored Results: 600 QC, 900 patient results (duplicate) Reaction Curves: Stored on USB (FAT32), backup recommended Connectivity: USB, Regular file purging for quick operations
77	IVD Equipment	Coagulation analyzer Single Channel	Test Principles: Clotting (640nm), Immuno-turbidimetric (800nm). Dimensions/Weight: 216 x 205 x 75 mm, Weight: ~1 kg. Environmental Requirements: Operating Temperature: 17-32°C, Max 80% RH. Power: 100-240 VAC, 50/60 Hz, Power Consumption: 45W, In-Rush Power: 150 VA. Calibrations: Up to 6 calibration levels per assay, calibration curve storage. Quality Controls: 12 control totals per assay, Levey- Jennings plotting, statistics calculation, QC results storage. Stored Results: 1000 results each for QC & patient, new replace oldest, reaction curves stored on USB (FAT32), regular USB backup recommended.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
78	IVD Equipment	Immunoassay Analyzer	Sample Type: Serum, Plasma Display: 10" TFT touch screen Filters: 4 (340, 450, 492, 630 nm) Throughput: 80 tests/hour Measuring Range: 0-3.0 OD QC: Built-in 3-level control Data Storage: 20,000 results Operating Temp: 15-30°C Power Supply: 100-240V AC Dimensions: 420 (W) x 450 (D) x 350 (H) mm Weight: 15 kg
79	IVD Equipment	Immunoassay Analyzer	Sample Type: Serum, Plasma, Urine Display: 7" TFT touch screen Filters: 4 (340, 450, 492, 630 nm) Throughput: 30 tests/hour Measuring Range: 0-3.0 OD QC: 3-level control Data Storage: 15,000 results Operating Temp: 15-30°C Power Supply: 100-240V AC Dimensions: 250 (W) x 450 (D) x 300 (H) mm Weight: 12 kg
80	IVD Equipment	ELISA READER	Wash Head: 8/12 manifold, Plate Types: 96/48 well (Flat, U, V-bottom) Wash Programs: 50, Dispensing Volume: 50-3000 μL, Precision: <2% at 350 μL Soak Time: 0-24 hrs, Residual Volume: $\leq 2 \mu$L (V/U), $\leq 3 \mu$L (Flat) Bottles: 2 wash, 1 rinse, 1 waste (2L) Power: AC 220V/110V, <80 VA, Dimensions: 710x530x380 mm, Weight: 9.5 kg Plate Types: 96 wells (U, V, Flat), Modes: Absorbance, Quantitative, Qualitative Photometer: 8-channel, 400-750 nm, Measurement Time: 8 sec (Speed) Power: 16V-24.5V DC, 90W, Dimensions: 502x369x216 mm, Weight: 7 kg



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
81	IVD Equipment	ELISA READER/WASHER	Dimensions: 1058mm (L) x 520mm (B) x 533mm (H), Weight: 65kg, Shipping: 95kg Power Supply: AC 110-240V, 50/60Hz, 300W General Specs: Self-check at startup, Up to 6 assays per batch, 240 micro wells (30 × 8), Sample Tube: 12mm × 75mm, Reagent Bottle: 24 × 20ml, 204 tips capacity Reader: Dynamic range: 0.0 - 4.0 O.D, Wavelength: 400 - 800nm, Filters: 405nm, 450nm, 492nm, 630nm, Reading mode: Single & Dual, Precision: <2% CV at 0.5-2.0 OD, Accuracy: ±3% OD (0.25-2.5 OD) Washer: 8 aspiration/8 dispensing, Wash cycle: 1 to 9, Residual volume: <5 µl, Buffer capacity: 3 × 1L, Rinse, Waste bottle: 2L Pipetting: Fixed needle/Disposable tips, Sample tip range: 5-200 µl, Reagent tip range: 10-200 µl, Precision: <2% CV at 10 µl, <1% CV at 100 µl Process Security: Liquid level sensing, Clot detection, Tip detection, Alarms Software: Windows-based PC, ELAN 30s control software, Unlimited work protocols, Data processing: Quantitative/Qualitative, Event/Error logs, Automatic error recovery Consumables: XL Wash probe solution, Disposable tips (optional).
82	IVD Equipment	ELISA READER	System Type: Open System Plate Types: 96 well (U, V, Flat) Operating Modes: Absorbance, Quantitative, Qualitative, Semi-Quantitative, Kinetic Wavelength Selection: Monochromatic, Bi-Chromatic, Multi-Chromatic (Max 4) Calculation Modes: Non-linear, Cut-off, Linear Regression, Cubic Spline, etc. Photometer: 8-channel, Tungsten Halogen, 400-750 nm, Dynamic Range: 0.0-4.0 OD Measurement Time: 8 sec (Speed), 17 sec (Normal) Display: 320x240 px, LED Backlight PC Communication: USB, Eli-LIMS compatible Printer: Built-in thermal, 384 dots/line Software: Eli-LIMS for data management Power Supply: 16V-24.5V DC, 115/230V AC, 90W Dimensions: 502x369x216 mm Weight: 7 kg Operating Temp.: 20-40°C, Storage Temp.: -10°C to 50°C Humidity: Max. 80% RH



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
83	IVD Equipment	Fully Automated Processor	Sample Capacity: Up to 272 Dimensions: 1375 x 845 x 850 mm (L x H x W) Frequency: 50/60 Hz Light Source: Halogen Lamp Voltage: 100 - 240V Automation: Fully Automatic Power Consumption: 700W Assay per Plate: Up to 12 Number of ELISA Plates: Up to 12 Sample/Reagent Capacity: 20 racks, 16 samples/reagents per rack, 6 x 60 ml reagent bottles per double rack Tip/Dilution Box: 11 locations, 96 capacity each (interchangeable) Reading Range: 0.0 - 3.5 O.D Reading Channels: 8 Filter Wheel: 405 nm, 450 nm, 492 nm, 620 nm + 2 optional Reading Mode: Single, Dual, ORR Reading Time: < 1 min (single filter) Linearity: Up to 3.0 O.D (450 nm)
84	IVD Equipment	MICRO PCR ANALYZER	
85	IVD Equipment	MICRO PCR ANALYZER	
86	IVD Equipment	MICRO PCR ANALYZER	
87	IVD Diagnostics Test Kit	VIRAL TRANSPORT MEDIUM KIT	
88	IVD Diagnostics Test Kit	VIRAL TRANSPORT KIT - VISURE	
89	Radiology Equipment	Sonography Machine - USG Premium	The USG Premium Sonography Machine offers high-definition imaging, various probe options, touchscreen interface, 3D/4D imaging, and advanced features like Doppler and elastography. It's compact, portable, and supports easy data transfer with USB/Wi-Fi.
90	Radiology Equipment	Sonography Machine - Low end	Imaging: Standard grayscale and basic color Doppler.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
91			• Display: Lower resolution display (e.g., 15-19 inches). • Probes: Limited probe options (e.g., linear and convex). • User Interface: Basic button or simple touchscreen interface. • Portability: Portable but bulkier compared to premium models. • Advanced Features: Limited or no 3D/4D imaging or elastography. • Connectivity: Basic data storage with limited transfer options (USB). • Power: Standard power consumption, often without long battery life for portable models. These machines are designed for routine examinations and budget-conscious settings.
92	Radiology Equipment	Sonography Machine - Portable	• Compact Design: Lightweight and easy to transport. • Imaging: Standard grayscale and color Doppler imaging. • Display: Small to medium-size high-resolution screen (usually 10-15 inches). • Probes: Includes basic probes like convex and linear, with some models offering specialized options. • Battery: Rechargeable battery for use in various locations. • User Interface: Simple touchscreen or button interface for easy operation. • Connectivity: Basic USB for data transfer, sometimes with Wi-Fi or cloud capability. • Power: Low power consumption, designed for mobile use in hospitals, clinics, or remote areas. These machines provide flexibility for bedside or out-of-hospital use, balancing performance with portability.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
93	Radiology Equipment	Sonography Machine - USG Veterinary	• Imaging: High-resolution grayscale and color Doppler imaging for animals. • Probes: Specialized veterinary probes (linear, convex, micro-convex) for various animal sizes. • Display: Clear, large display for detailed imaging (usually 12-19 inches). • User Interface: Easy-to-use interface, often with preset veterinary modes. • Portability: Compact and lightweight for field use and clinic settings. • Advanced Features: Doppler, elastography, 3D/4D imaging (on premium models). Power: Rechargeable battery for mobile use. • Connectivity: USB and Wi-Fi for easy data sharing and storage. These machines are tailored for animals, offering specialized features for accurate diagnostics
94	Radiology Equipment	C ARM MACHINE Flat Panel Digital	• Imaging: High-resolution digital imaging with clear contrast. • Flat Panel Detector: Provides superior image quality with reduced radiation exposure. • Display: High-definition monitor for real-time imaging. • Rotation & Mobility: 360° rotation and easy movement for precise positioning. • User Interface: Touchscreen or button interface for quick settings adjustments. • Power: Efficient power usage with options for battery operation (in portable models). • Fluoroscopy: Continuous imaging for real-time guidance during procedures. • Connectivity: Digital storage, USB, and network options for easy data transfer. This C-arm is ideal for surgeries and diagnostics, offering high-quality imaging with portability and flexibility.
95	Radiology Equipment	C ARM MACHINE	• Power: 5.0 kW • Maximum kV: 120 kV • Imaging: 1K x 1K resolution • Monitor: 19" LED • Orbital Movement: 125° (90° to -35°) • Field of View: 23 cm (9")



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
96			• Storage: PC-based, USB/LAN/CD connectivity • Another model • Power: 3.5 kW • Maximum kV: 110 kV • Imaging: 1K x 1K resolution • Monitor: 19" LED • Orbital Movement: 125° (90° to -35°) • Field of View: 23 cm (9") • Storage: PC-based, USB/LAN/CD connectivity Both are portable with motorized movements, flat panel detectors, and are suitable for various surgical applications like orthopedics, cardiology, and neuro.
97	Radiology Equipment	MAMMOGRAPHY MACHINE	• Nominal Power: 4.2 kW • Weight: 286 kg • Dimensions: 1158 mm (W) × 700 mm (D) × 1999 mm (H) • Source-to-Image Distance (SID): 65 cm • Cassette Sizes: 18 × 24 cm and 24 × 30 cm (optional) • Operating Temperature: +10°C to +40°C • Storage and Delivery Temperature: -20°C to +70°C
98	Breast Cancer Screening Device	Mid End Camera	Non -invasive Our thermal scanning based Breast Cancer Screening is radiation-free and non-invasive, requiring no incisions During Breast Cancer Screening, nobody sees or touches you, and the procedure is completely painless Our AI- based clinically validated Breast Cancer Screening offers best-in-class sensitivity and specificity, that is non-inferior to traditional methods.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
99	Medicine Vending Machine	MEDICINE VENDING MACHINE	Input Power: 230 V AC 50 Hz Power Consumption: 50 Watts Selection: 6 trays, 48 Maximum Battery Backup: Yes Mounting Type: Floor Stand Finish: CRCA steel with powder-coated superior finish Display: LCD display 16 x 4 Controller: GPRS/Wi-Fi based Operating Temperature: 5°C to 40°C Dimensions (LxWxH): 800 x 800 x 1700 mm Weight: 150 kg (approx.)
100	Hospitals Furnitures	Plain Cot	Material: Stainless Steel Frame Dimensions: 2000 x 900 x 450 mm (L x W x H) Weight: 40 kg Features: Fixed height, wheels with brakes, mattress support Customization: Adjustable height, additional color options
101	Hospitals Furnitures	Regular Semi Fowler Cot with wheels	Material: Stainless Steel, Powder-coated finish Dimensions: 2000 x 900 x 450 mm Weight: 45 kg Features: Manual adjustment, backrest, wheels with brakes Customization: Adjustable backrest, under-bed storage options
102	Hospitals Furnitures	Regular Semi Fowler Cot	Material: Stainless Steel, Powder-coated finish Dimensions: 2000 x 900 x 450 mm Weight: 40 kg Features: Manual backrest adjustment, mattress support Customization: Color options, additional accessories
103	Hospitals Furnitures	Regular Fowler Cot	Material: Stainless Steel Dimensions: 2000 x 900 x 450 mm Weight: 50 kg Features: Fully adjustable backrest and leg rest, wheels with brakes Customization: Adjustable headrest, foldable side rails



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
104	Hospitals Furnitures	Delux Fowler Cot	Material: Stainless Steel Dimensions: 2100 x 950 x 500 mm Weight: 60 kg Features: Electric adjustments, high-quality mattress support Customization: Additional motorized adjustments, side rails, color
105	Hospitals Furnitures	Super Delux Fowler Cot	Material: Stainless Steel, Chrome-plated Dimensions: 2100 x 950 x 500 mm Weight: 70 kg Features: Full electric functions, multi-position adjustments Customization: Remote control, extra storage compartments
106	Hospitals Furnitures	ICU Cot Three Function	Material: Stainless Steel Dimensions: 2200 x 950 x 600 mm Weight: 75 kg Features: Electric functions (backrest, height, footrest), side rails Customization: Adjustable headrest, under-bed storage
107	Hospitals Furnitures	ICU Cot Five Function	Model: ICU Cot Five Function Material: Stainless Steel, High-grade powder coating Dimensions: 2200 x 1000 x 650 mm Weight: 80 kg Features: Electric adjustments (head, foot, height, trendelenburg, reverse trendelenburg) Customization: Enhanced control panel, patient lifting options
108	Hospitals Furnitures	Pediatric Bed	Model: Pediatric Bed Material: Stainless Steel Dimensions: 1500 x 750 x 450 mm Weight: 25 kg Features: Adjustable height, safety rails, lockable wheels Customization: Color options, adjustable side rails
109	Hospitals Furnitures	Attender Cot	Model: Attender Cot Material: Stainless Steel Dimensions: 1900 x 850 x 400 mm Weight: 30 kg Features: Fixed height, mattress support, wheels with brakes Customization: Adjustable leg sections, under-bed storage



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
110	Hospitals Furnitures	Examination Table	Model: Examination Table Material: Stainless Steel Dimensions: 2000 x 700 x 750 mm Weight: 35 kg Features: Fixed height, padding for comfort, easy-to-clean surface Customization: Adjustable height, storage drawers
111	Hospitals Furnitures	Examination Couch	Model: Examination Couch Material: Stainless Steel Dimensions: 2000 x 800 x 500 mm Weight: 40 kg Features: Comfortable padding, manual adjustable backrest Customization: Different padding options, colors
112	Hospitals Furnitures	Instrument Trolley	Model: Instrument Trolley Material: Stainless Steel Dimensions: 500 x 400 x 800 mm Weight: 10 kg Features: 3 shelves, lockable drawers Customization: Additional drawers, color options
113	Hospitals Furnitures	Dressing Trolley	Model: Dressing Trolley Material: Stainless Steel Dimensions: 600 x 400 x 900 mm Weight: 15 kg Features: 2 shelves, locking mechanism, easy mobility Customization: Add more shelves, customizable compartments
114	Hospitals Furnitures	Curved Instrument Trolley	Model: Curved Instrument Trolley Material: Stainless Steel Dimensions: 600 x 400 x 850 mm Weight: 18 kg Features: Curved design, lockable drawers, caster wheels Customization: Additional shelving, customized locking
115	Hospitals Furnitures	Solid Linen Trolley	Model: Solid Linen Trolley Material: Stainless Steel Dimensions: 600 x 400 x 1000 mm Weight: 20 kg Features: 2 shelves, mesh basket Customization: Custom racks for linen
116	Hospitals Furnitures	Food Trolley/Cardio Trolley	Model: Food Trolley/Cardio Trolley Material: Stainless Steel Dimensions: 500 x 400 x 900 mm Weight: 15 kg Features: 3-tier design, easy mobility Customization: Extra trays, lockable compartments



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
117	Hospitals Furnitures	Mayo's Instrument Trolley	Model: Mayo's Instrument Trolley Material: Stainless Steel Dimensions: 500 x 350 x 800 mm Weight: 12 kg Features: Adjustable height, 2 shelves Customization: Extra height adjustment, locking mechanisms
118	Hospitals Furnitures	Revolving Stool	Model: Revolving Stool Material: Stainless Steel, PU seat Dimensions: Adjustable Weight: 5 kg Features: 360-degree rotation, adjustable height Customization: Color choices for seat and base
119	Hospitals Furnitures	Bedside Locker	Material: Stainless Steel - Regular Model Dimensions: 500 x 400 x 600 mm Weight: 12 kg Features: Lockable storage, smooth edges Customization: Additional drawers
120	Hospitals Furnitures	Bedside Locker	Model: Bedside Locker- Deluxe Model Material: Stainless Steel, Powder Coated Dimensions: 550 x 450 x 650 mm Weight: 15 kg Features: Multiple lockable compartments Customization: Extra compartments
121	Hospitals Furnitures	Wash Basin Stand	Material: Stainless Steel Single Dimensions: 400 x 300 x 700 mm Weight: 10 kg Features: Single basin support, easy drainage Customization: Adjustable height, additional hooks
122	Hospitals Furnitures	Wash Basin Stand	Model: Wash Basin Stand Double Material: Stainless Steel Dimensions: 600 x 300 x 700 mm Weight: 15 kg Features: Double basin support, adjustable height Customization: Customizable compartments
123	Hospitals Furnitures	Cyllinder Trolley	Model: Cylinder Trolley 'B' Type Material: Stainless Steel Dimensions: 500 x 500 x 900 mm Weight: 20 kg Features: Holds 2 gas cylinders, wheels with brakes Customization: Adjustable cylinder holders



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
124	Hospitals Furnitures	SALINE STAND	Model: Saline Stand Material: Stainless Steel Dimensions: 500 x 500 x 1200 mm Weight: 8 kg Features: Adjustable height, base with wheels Customization: Additional hooks for bags
125	Hospitals Furnitures	FOOTREST	Model: Footrest Single Material: Stainless Steel Dimensions: 400 x 200 mm Weight: 5 kg Features: Single foot rest with sturdy design Customization: Different colors
126	Hospitals Furnitures	FOOT REST	Model: Foot Rest Double Material: Stainless Steel Dimensions: 600 x 200 mm Weight: 7 kg Features: Double foot rest with anti-slip design Customization: Adjustable height
127	Hospitals Furnitures	STRECHER ON TROLLEY	Model: Stretcher on Trolley Material: Stainless Steel Dimensions: 2000 x 700 mm Weight: 25 kg Features: Adjustable height, sturdy frame Customization: Add armrests, additional storage
128	Hospitals Furnitures	BEDSIDE SCREEN	Model: Bedside Screen Material: Stainless Steel, fabric Dimensions: 1500 x 1800 mm Weight: 10 kg Features: Foldable design, privacy screen Customization: Color options, fabric choices
129	Hospitals Furnitures	LABOUR COT	Model: Labour Cot Plain with Rest and Belt Material: Stainless Steel Dimensions: 2000 x 900 mm Weight: 30 kg Features: Adjustable headrest, safety belt Customization: Additional support rods
130	Hospitals Furnitures	WHEEL CHAIR	Model: Wheelchair (Non-Folding Type) Material: Stainless Steel Dimensions: 1000 x 600 x 950 mm Weight: 15 kg Features: Sturdy frame, non-folding Customization: Adjustable footrest, armrests
131	Hospitals Furnitures	BABY CRADLE	Model: Baby Cradle Material: Stainless Steel Dimensions: 900 x 500 mm Weight: 8 kg Features: Secure rails, easy mobility Customization: Color options



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
132	Hospitals Furnitures	CRASH CART	Model: Crash Cart Material: Stainless Steel Dimensions: 600 x 450 x 1200 mm Weight: 35 kg Features: Multiple drawers, lockable Customization: Extra compartments, height adjustment
133	Hospitals Furnitures	MONITOR TROLLEY	Model: Monitor Trolley Material: Stainless Steel Dimensions: 600 x 500 x 1000 mm Weight: 18 kg Features: Adjustable height, holds monitors Customization: Additional shelves, cable management
134	Hospitals Furnitures	NEBULIZER	Brand: Microtek Usage/Application: Nebulization Operation Mode: Portable Type of Compressor: Air Compressor Warranty: 1 Year Place of Origin: India Color: White Model ID: CNB69008 Compressor Nebulizer Operating Air Flow Rate: 9.5-19 psi Average Nebulization Rate: 0.25 ml/min Particle Size: 0.5-10 μ m Features: Ergonomic grip, easy to use, portable.
135	MRI Machine	MRI 0.35 Tesla	Permanent magnet Magnetic Field Strength: 0.35 Tesla Type: Open MRI System Gradient Strength: 12 mT/m Scan Time: Fast for patient comfort FOV: Adjustable, large Applications: Neurology, musculoskeletal, orthopedic Interface: Advanced image processing software Power Supply: Standard AC Design: Compact and space-efficient
136	MRI Machine	MRI 1.5 Tesla	Helium Free MRI Field Strength: 1.5 Tesla Gradient Strength: 30 mT/m Imaging Type: High-resolution, fast scan Applications: Neurology, musculoskeletal, oncology Slice Thickness: 1-10 mm adjustable Cooling: Liquid helium Interface: Advanced image processing software



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
137	CT scan	CT SCAN 32 Slices	Slices: 32 slices per rotation Scan Speed: High-speed scanning Applications: Neurology, cardiology, musculoskeletal Resolution: High spatial resolution Power: Standard AC supply Software: Advanced image processing
138	CT scan	CT SCAN 64) Slices	Slices: 64 slices per rotation Scan Speed: High-speed Resolution: High-resolution imaging Applications: Neurology, cardiology, musculoskeletal Power: AC power supply Software: Advanced image processing
139	Blood Bank Equipment	Blood Bank Refrigerator	Capacity 200 Liters with Temperature chart recorder with movable steel shelves
140	Blood Bank Equipment	Blood Bank Refrigerator	Capacity 400 litres with Temperature chart recorder with movable steel shelves
141	Blood Bank Equipment	Blood Bank Refrigerator	Single Door Capacity 600 litres with Temperature chart recorder with movable steel shelves
142	Blood Bank Equipment	Blood Bank Refrigerator	Double Door Capacity 600 litres with Temperature chart recorder with movable steel shelves
143	Blood Bank Equipment	Blood Bank Refrigerator	Double Door Capacity 1200 litres with Temperature chart recorder with movable steel shelves
144	Blood Bank Equipment	Blood Bank Refrigerator	LCD Touchscreen Capacity 200 litres with Temperature chart recorder with movable steel shelves
145	Blood Bank Equipment	Blood Bank Refrigerator	LCD Touchscreen Capacity 400 litres with Temperature chart recorder with movable steel shelves
146	Blood Bank Equipment	Blood Bank Refrigerator	LCD Touchscreen Temperature chart recorder with movable steel shelves



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
147	Blood Bank Equipment	Blood Bank Refrigerator	LCD Touchscreen Double Door Capacity 600 litres with Temperature chart recorder with movable steel shelves
148	Blood Bank Equipment	Blood Bank Refrigerator	LCD Touchscreen Double Door Capacity 1200 litres with Temperature chart recorder with movable steel shelves
149	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	Capacity 200 litres with Powder Coated GI racks
150	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	Capacity 400 litres with Powder Coated GI racks
151	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	Single Door Capacity 600 litres with Powder Coated GI racks
152	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	Double Door Capacity 200 litres with Powder Coated GI racks
153	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	Double Door Capacity 200 litres with Powder Coated GI racks
154	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	LCD Touchscreen Capacity 200 litres with fixed steel shelves
155	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	LCD Touchscreen Capacity 400 ltrs with fixed steel shelves
156	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	LCD Touchscreen Single Door Capacity 600 ltrs with fixed steel shelves
157	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	LCD Touchscreen Double Door Capacity 200 litres with fixed steel shelves



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
158	Blood Bank Equipment	Laboratory/Pharmaceutical Refrigerator	LCD Touchscreen Double Door Capacity 200 litres with fixed steel shelves
159	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -40 Degree Capacity 200 litres with LCD Touchscreen
160	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -40 Degree Capacity 450 litres with LCD Touchscreen
161	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -40 Degree Capacity 550 litres with LCD Touchscreen
162	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -40 Degree Capacity 650 litres with LCD Touchscreen
163	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -86 Degree Capacity 200 litres with LCD Touchscreen
164	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -86 Degree KBS UD350 Capacity 450 litres with LCD Touchscreen
165	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -86 Degree Capacity 550 litres with LCD Touchscreen
166	Blood Bank Equipment	Laboratory Deep Freezer	- 10 to -86 Degree Capacity 650 litres with LCD Touchscreen
167	Cancer Care Equipment	Coolthera	Oral Cooling System Function: Fever management through oral cooling Temperature Control: Adjustable settings Power: AC supply Design: Portable, lightweight Application: Critical care and emergency use



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
168	Critical Care Equipment	Anaesthesia Workstation	A micro-controller based, electronically controlled ventilator with a 7-inch touch screen. Compatible with Circle Absorber and Bain's circuit, it offers CMV and SIMV modes with tidal volume of 50-1500 ml, frequency of 6-40 bpm, and PEEP/CPAP up to 20 cm H₂O. - with 2 Vaporizer Modes: CMV (VC, PC), SIMV (VC, PC) with PSV (optional) Tidal Volume: 50-1500 ml Frequency: 6-40 bpm Inspiratory Time: 0.4-3 seconds PIP: 10-60 cm H₂O PEEP/CPAP: 0-20 cm H₂O Comprehensive Alarms: Disconnection, high/low pressures Accessories: Circle Absorber, Thermo-compensated vaporizer, Bain's Circuit, Pediatric Anaesthesia Circuit, Face masks, Rebreathing bags.
169	Critical Care Equipment	Anaesthesia Workstation	Anti-Hypoxic Device: Ensures minimum 25% oxygen in gas mixture. with 1 Vaporizer Gas Flow Ratio: 1:3 mix of O₂ and N₂O. Oxygen Failure Protection: Audio-visual alarms. Rotameters: ISI & ISO standard. Regulators & Valves: Forged, high-efficiency, stainless steel fittings with precision relief and non- return valve. Vaporizer: Goldman Halothane with changeover mechanism and oxygen flush. Gas Inlets: 2 O₂ and 2 N₂O ports, pin-indexed gas connections. Oxygen Outlet: For ventilator connection. Trolley: M.S. multi-color powder-coated with stainless steel tray. Gauges: Large diameter (63mm) for cylinder, operating, and pipeline pressures. Size: 1585mm x 850mm x 735mm (H x W x D). Optional Upgrades: Flow Tec vaporizer, circle absorber, and ventilator (at extra cost).



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
170	Critical Care Equipment	ICU Ventilator	Gas Supply: Oxygen & air at 3-4 bar Modes: CMV-VC, CMV-PC, SIMV, PS, PSV, 2PAP+PS, Standby FIO₂: 21% to 100% Tidal Volume: 50-1500 ml Frequency: 1-60 BPM I:E Ratio: 1:4 to 4:1 Inspiratory Time: 0.3-3 seconds PEEP: 0-30 cmH₂O Sensitivity: 1-10 cmH₂O (Pressure), 1-10 LPM (Flow) PSV: 0-40 cmH₂O Alarms: Oxygen failure, Patient disconnection Monitored Data: Exp. Tidal Volume, PIP, Plateau Pressure, MAP, FIO₂ Battery Backup: 2 hours Accessories: Breathing circuit, humidifier, oxygen sensor, air compressor
171	Critical Care Equipment	Portable ventilator	"Source Operating Pressure: 40 to 60 PSI Gas Supply: Oxygen at 3-4 bar, external air compressor or air pipeline Modes of Ventilation: CMV/AV (VC), CMV/AV (PC), SIMV (VC) Oxygen Concentration: 21% to 100% Frequency: 80 BPM Tidal Volume: 50-1500 ml Inspiratory Time: 0.3 to 5 seconds Inspiratory Flow: 120 L/min Inspiratory Pressure: 60 cm H₂O PEEP/CPAP: 0 to 20 cm H₂O Trigger Sensitivity: 0 to 10 cm H₂O Pressure Support: 0 to 40 cm H₂O Apnea Backup: Programmable PIP: 10 to 60 cm H₂O Panel Lock: Automatic Alarms: Low/High Pressure, Gas-Supply Failure, Power Failure Monitored Parameters: Peak Inspiratory Pressure, PEEP, Tidal Volume, FIO₂, Expiratory Time, I:E Ratio Mount: Trolley mount Display: 7-inch touch screen Battery Backup: Li-ion, 3 hours on full charge"



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
172	Critical Care Equipment	RESUSCITATION KIT	WITH VENTILATOR - without Handheld ECG Case: Lightweight, durable HPX resin/polypropylene copolymer. Suction: Manual suction pump and venturi-driven aspirator. Oxygen Supply: Lightweight oxygen cylinder with regulator and flexible adapter. Resuscitator Unit: Pneumatically controlled ventilator with IPPV, manual override, and alarms. Tidal Volume: 200-1200 ml, Frequency: 6-30 BPM. Oxygen Concentration: 60% and 100%, PEEP: 0-20 cm H₂O. Accessories: Resuscitator bags, laryngoscope with blades, endotracheal tubes, LMA, face masks, pharyngeal airways, and suction catheters. Monitoring tools: Stethoscope, sphygmomanometer, thermometer, and more. Optional: ECG and pulse oximeter.
173	Critical Care Equipment	Multipara Patient Monitor	ECG: Leads I, II, III, aVF, AVR, aVL, V1-6; HR range: Adult 15-300 bpm, Child 15-350 bpm; Accuracy $\pm 1\%$ or ± 1 bpm; S-T detection: -2.0mV to +2.0mV; Audible & visual alarms. RESP: Rate: Adult 7-120 BrPM, Child 7-150 BrPM; Accuracy ± 2 BrPM; Audible & visual alarms. NIBP: Oscillometry method; Adult: 300 mmHg, Child: 240 mmHg, Newborn: 150 mmHg; Overpressure protection; Audible & visual alarms. SPO₂: Range 0-100%; Pulse rate: 20-300 BPM; Measurement error: $\pm 2\%$; Audible & visual alarms. TEMP: Range: 0°C-45°C; Resolution: 0.1°C; Audible & visual alarms.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
174	Radiology	Cath Lab System	Detector: Flat Panel, 12" diagonal, 21 cm x 21 cm, Pixel Size 154µm Image Matrix: 1344 x 1344, 16-bit Dynamic range, DQE - 77% C-Arm: Floor mount, ISO centric, left-side mounted Orbital Speed: Up to 25 deg/sec Angulation Speed: Up to 25 deg/sec Angular Stroke: -45° to +45° Orbital Stroke: +90° to -45° C-arm Depth: 85.3 cm Variable SID: 96-116 cm Display: 55" 4K UHD, 3840x2160 matrix, ceiling suspended Input Power: 400-415 VAC, 65KW, 3 Phase, 50Hz Operating Temperature: 15°C - 30°C Operating Humidity: 30% - 75% X-Ray Generator: 65 KW, 40 - 125 KV, Max current 630mA @ 100KV Max Patient Weight: 200 kg Table: Min Height 780 mm, Vertical Stroke 300 mm, Longitudinal Stroke 1350 mm, Lateral Stroke 300 mm Table Pivot: -15° to +90°
175	Radiology	Cath Lab System	Imaging: High-definition fluoroscopy Detector: Flat-panel Radiation Dose: Dose optimization X-ray Tube: Rotating anode Display: HD monitors Applications: Cardiovascular, angiography Power: AC 220V Design: Ergonomic, modular
176	Radiology	Cath Lab System	Imaging: Real-time HD fluoroscopy Detector: Flat-panel Radiation Dose: Low exposure X-ray Tube: Rotating anode Display: Multi-HD monitors Applications: Cardiovascular, electrophysiology Power: AC 220V Design: Flexible, customizable
177	Radiology	Cath Lab System	Imaging: High-resolution fluoroscopy Detector: Flat-panel Radiation Dose: Dose-reduction tech X-ray Tube: Rotating anode Display: HD multi-screen Applications: Cardiovascular, angiography Power: AC 220V Design: Modular, space-saving
178	IVD Diagnostics Test Kit	COVID-19 - Test Kit	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
179	IVD Diagnostics Test Kit	H1N1 - - Test Kit	
180	IVD Diagnostics Test Kit	INFLUENZA A/B - Test Kit	
181	IVD Diagnostics Test Kit	H3N2/H1N1 - Test Kit	
182	IVD Diagnostics Test Kit	NIPAH - Test Kit	
183	IVD Diagnostics Test Kit	MTB - Test Kit	
184	IVD Diagnostics Test Kit	MTB PLUS - Test Kit	
185	IVD Diagnostics Test Kit	MTB RIF - Test Kit	
186	IVD Diagnostics Test Kit	MTB INH - Test Kit	
187	IVD Diagnostics Test Kit	DENGUE - Test Kit	
188	IVD Diagnostics Test Kit	CHIKUNGUNYA - Test Kit	
189	IVD Diagnostics Test Kit	DENG/CHIK - Test Kit	
190	IVD Diagnostics Test Kit	LEPTOSPIRA - Test Kit	
191	IVD Diagnostics Test Kit	SCRUB T - Test Kit	
192	IVD Diagnostics Test Kit	MALARIA Pf - Test Kit	
193	IVD Diagnostics Test Kit	MALARIA Pv/Pf - Test Kit	
194	IVD Diagnostics Test Kit	HPV-HR - Test Kit	
195	IVD Diagnostics Test Kit	GBS - Test Kit	
196	IVD Diagnostics Test Kit	CT - Test Kit	
197	IVD Diagnostics Test Kit	NG - Test Kit	
198	IVD Diagnostics Test Kit	CT/NG - Test Kit	
199	IVD Diagnostics Test Kit	TRICH - Test Kit	
200	IVD Diagnostics Test Kit	RABIES - Test Kit	
201	IVD Diagnostics Test Kit	HBV - Test Kit	
202	IVD Diagnostics Test Kit	HCV - Test Kit	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
203	IVD Diagnostics Test Kit	HAV - Test Kit	
204	IVD Diagnostics Test Kit	HEV - Test Kit	
205	IVD Diagnostics Test Kit	HIV-1 - Test Kit	
206	IVD Diagnostics Test Kit	HIV-1/HIV-2 - Test Kit	
207	IVD Diagnostics Test Kit	HLA-B27 - Test Kit	
208	IVD Diagnostics Test Kit	SALMONELLA - Test Kit	
209	IVD Diagnostics Test Kit	CDI - Test Kit	
210	IVD Diagnostics Test Kit	SHIGELLA - Test Kit	
211	IVD Diagnostics Test Kit	HSV 1/2 - Test Kit	
212	IVD Diagnostics Test Kit	CHOLERA - Test Kit	
213	Equipment	Glucometer	
214	IVD Equipment	Haematology Analyser	WBC Differentiation: 3-part Speed: 60 samples/hour Parameters: 20 (categorized by corpuscle type) Sample Volume: 10 μL (whole blood), 20 μL (pre-diluent) Automation: Self-check, calibration, sampling, mixing, alarms, cleaning Indicators: Run/Standby, Whole blood/Pre-diluent Memory: 100,000 samples (with histograms) QC: 4 methods, 31 data points per parameter Features: Audio alarms, Dormancy mode, Dual sample mode
215	IVD Equipment	Fully Automated Analyser	Automation: Fully Automatic Assays: Clinical Chemistry Cuvette Type: Reusable Usage: Hospital Sample Volume: 210 μL Reagent Positions: 30 Water Consumption: 1 LPH Sample Positions: 60



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
216	IVD Equipment	Electrolyte Analyser	Automation: Fully Automatic Usage: Hospital Sample Type: Serum, Whole Blood, Plasma, Urine (diluted) Analysis Time: 30 Sec Dimensions: 30 x 26 x 36 cm Weight: 7.6 Kg Display: High Resolution Measurement Principle: Direct ISE Technology Interface: RS-232 Serial port User Input: Keyboard Certification: CE
217	IVD Equipment	Semi-auto analyser	Test Parameters: 150 Display: Graphic LCD, touch screen Methodology: Absorbance, Endpoint, Kinetics, Mono/Bi-chromatic, Turbidimetry Optical System: Measurement range 0.0-3.0A, Filters (340-630 nm), Halogen lamp Photometer: Peltier-regulated, 18 µL flow cell, peristaltic pump Memory: 150+ test programs, 1000 results, cloud storage QC: Levy-Jennings, 30 normal/abnormal values Power: 220V, <150 VA Weight: <6kg Dimensions: Compact, 30x26x36 cm
218	IVD Equipment	Semi-auto analyser	Weight: 8.5 kg Dimensions: 420mm (H) x 380mm (W) x 170mm (D) Memory: 112 test profiles, 100,000 results, 210 open programs Temperature Control: Peltier elements (25°C, 30°C, 37°C ±0.1°C) Inbuilt Printer: Thermal Filters: 7 standard (340, 405, 492, 510, 546, 578, 630 nm) + 1 optional Photometric Range: 0.0000 to 3.0000 Abs Resolution: 0.0001 Abs Light Source: Quartz-Halogen lamp (12V/20W) Flowcell: Stainless steel with quartz window, 10 mm optical path Measuring Volume: 32 µL Quality Control: L-J graph, comprehensive QC software Interface: RS-232 serial port Drift: 0.002 Abs/hour



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
219	Hospitals Furnitures	Sample Cup	Material: Medical-grade plastic (e.g., polypropylene) Capacity: 30-100 mL Design: Leak-proof, transparent, with graduated markings Features: Secure lid, single-use, sterilized Use: For collecting biological samples (e.g., urine, saliva) Packaging: Individually packed or bulk Certifications: CE certified (if applicable)
220	Hospitals Furnitures	Fowler Bed with Mattress	Technical Specification: Mechanical Manual backrest and knee rest adjustment, fixed height, SS laminated wooden panel, perforated mild steel four-section top, urine bag holder, MS parts pre-treated and epoxy powder-coated. Technical Data: Overall dimension 2010 mm x 900 mm (L x W), Platform dimension 1900 mm x 840 mm (L x W). Optional Accessories: PU foam mattress (4" thick), adjustable stainless steel IV pole, casters (125 mm, two with lock), collapsible railing.
221	Hospitals Furnitures	Semi -Fowler Bed with Mattress	Technical Specification: (Mechanical) Manual backrest adjustment, fixed height, SS frame with laminated surface, perforated mild steel top section. Technical Data: Overall dimension 2000 mm x 900 mm (L x W), Platform dimension 1900 mm x 840 mm (L x W). Optional Accessories: PU foam mattress, stainless steel IV pole (adjustable), casters (125 mm, lockable).
222	Hospitals Furnitures	ICU Bed	Technical Specification: Motorized with Mattress Fully motorized, adjustable backrest, knee rest, and height, stainless steel frame with laminated top, multi-position locking system. Technical Data: 2100 mm x 950 mm (L x W), weight capacity 250 kg. Optional Accessories: Anti-decubitus mattress, foldable side rails, adjustable IV pole.
223	Hospitals Furnitures	Delivery Couch/Bed	Technical Specification: (LDR) (Electro Mechanical) Electro-mechanical adjustment for backrest, footrest, and height, SS frame, detachable headrest, large storage space under the bed. Technical Data: 2100 mm x 950 mm (L x W), weight capacity 250 kg. Optional Accessories: Adjustable leg support, thick foam mattress, side rails with easy access.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
224	Hospitals Furnitures	Paediatric Bed with Mattress	Technical Specification: Adjustable backrest, side rails, fixed height, SS construction with powder-coated surface for easy cleaning. Technical Data: 1600 mm x 700 mm (L x W), weight capacity 50 kg. Optional Accessories: Soft padded mattress, collapsible side rails, storage tray.
225	Hospitals Furnitures	Baby Bassinet	Technical Specification: SS frame with transparent acrylic sides, adjustable height, and smooth casters for easy movement. Technical Data: 800 mm x 450 mm (L x W), weight capacity 20 kg. Optional Accessories: Soft mattress, adjustable height pole for monitoring.
226	Hospitals Furnitures	Baby Crib with Mattress	Technical Specification: Wooden SS frame, adjustable height, side rails for safety. Technical Data: 1000 mm x 600 mm (L x W), weight capacity 25 kg. Optional Accessories: Soft mattress, collapsible side rails.
227	Hospitals Furnitures	Examination Table	Technical Specification: (Manual) Fixed height, manual adjustable backrest, SS frame, laminated top, urine bag holder. Technical Data: 2000 mm x 800 mm (L x W), weight capacity 150 kg. Optional Accessories: Foam mattress, adjustable IV pole, casters.
228	Hospitals Furnitures	Examination Table	Technical Specification: Manual adjustment for backrest, fixed height, SS frame, laminated wooden top. Technical Data: 2000 mm x 800 mm (L x W), weight capacity 150 kg. Optional Accessories: PU foam mattress, adjustable IV pole, casters.
229	Hospitals Furnitures	Examination Couch	Technical Specification: Motorized backrest adjustment, fixed height, SS frame, laminated wooden top. Technical Data: 2000 mm x 800 mm (L x W), weight capacity 180 kg. Optional Accessories: PU foam mattress, adjustable IV pole, casters.
230	Hospitals Furnitures	Gynaecological Examination Table	Technical Specification: Electro-mechanical adjustment, SS frame, perforated top. Technical Data: 2000 mm x 800 mm (L x W), weight capacity 180 kg. Optional Accessories: Thick foam mattress, adjustable leg rests, foldable side rails.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
231	Hospitals Furnitures	Ambulance Trolley	Technical Specification: Hydraulic system, SS frame, adjustable height, foldable side rails. Technical Data: 2000 mm x 750 mm (L x W), weight capacity 300 kg. Optional Accessories: Adjustable leg rest, thick mattress, casters.
232	Hospitals Furnitures	Patient Trolley	Technical Specification: with Removable Stretcher SS frame, adjustable height, removable stretcher. Technical Data: 2000 mm x 700 mm (L x W), weight capacity 250 kg. Optional Accessories: Foam mattress, IV pole, casters.
233	Hospitals Furnitures	Emergency Cum Recovery Trolley	Technical Specification: Hydraulic height adjustment, SS frame, foldable side rails, large caster wheels for easy maneuverability. Technical Data: 2000 mm x 700 mm (L x W), weight capacity 250 kg. Optional Accessories: Foam mattress, adjustable headrest, IV pole, foldable side rails.
234	Hospitals Furnitures	Over Bed Table	Technical Specification: Adjustable height, SS frame with laminated wooden top, easy-to-clean surface. Technical Data: 1200 mm x 600 mm (L x W), weight capacity 50 kg. Optional Accessories: Non-slip surface, locking casters for stability.
235	Hospitals Furnitures	Over Bed Table	Technical Specification: Manual height adjustment, SS frame, laminated top, easy-to-move wheels. Technical Data: 1000 mm x 500 mm (L x W), weight capacity 60 kg. Optional Accessories: Built-in drawer, locking casters
236	Hospitals Furnitures	Bed Side Locker	Technical Specification: SS body with laminate surface, single drawer with storage space. Technical Data: 450 mm x 450 mm x 900 mm (L x W x H), weight capacity 50 kg. Optional Accessories: Additional drawer space, adjustable height option.
237	Hospitals Furnitures	Bed side Locker	Technical Specification: Table, Powder Coated Body, S.S. Top with Drawer & Cabinet Powder-coated body, SS top, single drawer with cabinet storage. Technical Data: 450 mm x 450 mm x 900 mm (L x W x H), weight capacity 60 kg. Optional Accessories: Lockable drawers, casters for easy movement.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
238	Hospitals Furnitures	Emergency Crash Cart	Technical Specification: High-quality SS body, multiple drawers, and shelves for easy access to emergency supplies. Technical Data: 900 mm x 500 mm (L x W), weight capacity 200 kg. Optional Accessories: IV pole, oxygen cylinder holder, lockable drawers.
239	Hospitals Furnitures	Emergency Crash Cart	Technical Specification: Stainless steel body, 3 to 5 drawers for emergency medications and equipment. Technical Data: 950 mm x 500 mm (L x W), weight capacity 180 kg. Optional Accessories: Oxygen tank holder, storage bin for medical supplies.
240	Hospitals Furnitures	Instrument Trolley	Technical Specification: SS frame, adjustable height, multi-shelf design, easy-to-move casters. Technical Data: 600 mm x 400 mm (L x W), weight capacity 50 kg. Optional Accessories: Non-slip shelves, locking casters.
241	Hospitals Furnitures	Medicine Trolley	Technical Specification: SS frame, multi-tier shelves, easy-to-move casters, lockable drawers for medication storage. Technical Data: 700 mm x 450 mm (L x W), weight capacity 70 kg. Optional Accessories: Medical supplies organizer, oxygen cylinder holder.
242	Hospitals Furnitures	Instrument Cum Dressing Trolley	Technical Specification: SS frame, large surface for instruments and supplies, multi-tiered storage. Technical Data: 800 mm x 500 mm (L x W), weight capacity 80 kg. Optional Accessories: Non-slip surface, adjustable height.
243	Hospitals Furnitures	Cylinder Trolley	Technical Specification: Small SS frame, designed for small-sized oxygen cylinders, lockable wheels for safety. Technical Data: 500 mm x 300 mm (L x W), weight capacity 30 kg. Optional Accessories: Cylinder size adjuster, locking system for cylinder.
244	Hospitals Furnitures	Cylinder Trolley	Technical Specification: Big SS frame, accommodates large-sized oxygen cylinders, caster wheels for mobility. Technical Data: 700 mm x 350 mm (L x W), weight capacity 50 kg. Optional Accessories: Locking mechanism, cylinder strap.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
245	Hospitals Furnitures	Soiled Linen Trolley	Technical Specification: SS frame, durable nylon bag for soiled linens, lockable wheels. Technical Data: 900 mm x 500 mm (L x W), weight capacity 80 kg. Optional Accessories: Waterproof bag, adjustable bag height.
246	Hospitals Furnitures	Soiled Linen Trolley	Technical Specification: SS frame, heavy-duty nylon bag, two compartments for separation of linens. Technical Data: 1000 mm x 550 mm (L x W), weight capacity 100 kg. Optional Accessories: Adjustable compartments, lockable lid.
247	Hospitals Furnitures	Instrument Cabinet	Technical Specification: SS body, lockable doors, shelves for instrument storage. Technical Data: 600 mm x 400 mm x 1800 mm (L x W x H), weight capacity 150 kg. Optional Accessories: Adjustable shelves, lockable drawers.
248	Hospitals Furnitures	Footstep	Technical Specification: SS frame, double step design for easy access, anti-slip surface. Technical Data: 400 mm x 300 mm (L x W), weight capacity 100 kg. Optional Accessories: Non-slip rubber coating.
249	Hospitals Furnitures	Foot Step	Technical Specification: SS frame, single step design, anti-slip surface. Technical Data: 400 mm x 300 mm (L x W), weight capacity 80 kg. Optional Accessories: Non-slip rubber covering.
250	Hospitals Furnitures	Doctor's Chair	Technical Specification: Adjustable height, SS base with comfortable seating. Technical Data: 500 mm x 450 mm (L x W), weight capacity 150 kg. Optional Accessories: Adjustable backrest, swivel function.
251	Hospitals Furnitures	Patient Stool	Technical Specification: Revolving stool with adjustable height, SS frame, comfortable seating. Technical Data: 400 mm x 400 mm (L x W), weight capacity 100 kg. Optional Accessories: Locking mechanism for height.
252	Hospitals Furnitures	Patient Stool	Technical Specification: SS frame, adjustable height, comfortable seating. Technical Data: 350 mm x 350 mm (L x W), weight capacity 80 kg. Optional Accessories: Swivel function, non-slip base.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
253	Hospitals Furnitures	Wheelchair	Technical Specification: Manual folding, lightweight, elevating footrest, durable steel frame. Technical Data: 1100 mm x 650 mm (L x W), weight capacity 120 kg. Optional Accessories: Elevating leg rests, armrest pads.
254	Hospitals Furnitures	Drip Stand	Technical Specification: Adjustable height, sturdy molded base for stability, stainless steel pole. Technical Data: 1500 mm height adjustable, base diameter 450 mm, weight capacity 10 kg. Optional Accessories: Castors for mobility, multiple hook options for drip bags.
255	Hospitals Furnitures	X-Ray View	Technical Specification: LED backlit, double-screen design, adjustable brightness, high contrast for X- ray viewing. Technical Data: 450 mm x 600 mm (L x W), weight 15 kg. Optional Accessories: Wall mount, adjustable viewing angles.
256	Hospitals Furnitures	Bed Side Screen	Technical Specification: 3-Fold Screen MS frame, threefold design for privacy, durable fabric panels. Technical Data: 1800 mm x 1200 mm (L x W), foldable for easy storage. Optional Accessories: Locking wheels for mobility, fabric panel replacement.
257	Hospitals Furnitures	Bed Side Screen	Technical Specification: 4 Fold Screen MS frame, four fold design, privacy protection with durable fabric panels. Technical Data: 2000 mm x 1500 mm (L x W), easy fold and storage. Optional Accessories: Castor wheels for easy movement, fabric choices for panels.
258	Hospitals Furnitures	Medical Recliner Chair	Technical Specification: Electro-mechanical recliner, Ascent multiple position settings, durable upholstery. Technical Data: 700 mm x 800 mm (L x W), recline angle 120°-160°. Optional Accessories: Armrest pads, footrest extension.
259	Hospitals Furnitures	Recliner Chair	Technical Specification: Mechanical recliner, comfortable seating, easy-to-operate handle. Technical Data: 600 mm x 700 mm (L x W), recline angle 110°-160°. Optional Accessories: Footrest, adjustable armrests.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
260	Hospitals Furnitures	Sofa Cum Attendant Bed	Technical Specification: Multi-functional, converts between a sofa and a bed, durable frame with comfortable cushions. Technical Data: 1800 mm x 700 mm (L x W), weight capacity 150 kg. Optional Accessories: Removable cushions, side armrests.
261	Hospitals Furnitures	Blood Collection Chair	Technical Specification: Adjustable backrest, armrests, comfortable seating for blood collection procedures. Technical Data: 700 mm x 600 mm (L x W), weight capacity 120 kg. Optional Accessories: Armrest pads, adjustable footrest.
262	Hospitals Furnitures	Examination Light	Technical Specification: LED examination light, adjustable arm, high luminosity for precise examination. Technical Data: 500 mm arm length, 18W LED, light intensity 50000 lux. Optional Accessories: Wall or ceiling mount, adjustable brightness control.
263	Hospitals Furnitures	Examination Light	Technical Specification: LED light with adjustable focus, durable arm, energy-efficient. Technical Data: 600 mm arm length, light intensity 60000 lux. Optional Accessories: Ceiling or wall mount, light angle adjustment.
264	Hospitals Furnitures	Medical kick Bucket	Technical Specification: Stainless steel construction, foot-operated lid, non-corrosive. Technical Data: 30 liters capacity, 350 mm x 350 mm (L x W), height 500 mm. Optional Accessories: Pedal with cover, additional sizes available.
265	Dialysis Equipment	Dialysis Reprocessing Machine	Function: Reprocesses dialysis filters for reuse. Capacity: 10-20 dialyzers/hour. Disinfection: Heat and/or chemical disinfection. Control: Touchscreen interface. Power: 220-240 V, 50-60 Hz. Safety: Automated self-test, alarms. Weight: 100-150 kg. Maintenance: Easy-to-clean components. Certification: CE or equivalent.
266	IVD Performance Panels	HIV - 10 Positive + 10 Negative ,0.5ml / vial - Performance Panel	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
267	IVD Performance Panels	HIV - 5 Positive + 5 Negative ,0.5ml / vial - Performance Panel	
268	IVD Performance Panels	HIV - 2 Positive + 3 Negative ,0.5ml / vial - Performance Panel	
269	IVD Performance Panels	HCV - 10 Positive + 10 Negative ,0.5ml / vial - Performance Panel	
270	IVD Performance Panels	HCV - 5 Positive + 5 Negative ,0.5ml / vial - Performance Panel	
271	IVD Performance Panels	HCV - 2 Positive + 3 Negative ,0.5ml / vial - Performance Panel	
272	IVD Performance Panels	HBsAg - 10 Positive + 10 Negative ,0.5ml / vial - Performance Panel	
273	IVD Performance Panels	HBsAg- 5 Positive + 5 Negative ,0.5ml / vial - Performance Panel	
274	IVD Performance Panels	HBsAg - 2 Positive + 3 Negative ,0.5ml / vial - Performance Panel	
275	IVD Performance Panels	Syphilis - 10 Positive + 10 Negative ,0.25ml / vial - Performance Panel	
276	IVD Performance Panels	Syphilis - 5 Positive + 5 Negative ,0.25ml / vial - Performance Panel	
277	IVD Performance Panels	Syphilis - 2 Positive + 3 Negative ,0.25ml / vial - Performance Panel	
278	IVD - Coagulometer Analyzer	Coagulometer	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
279	Radiology Equipment	High Frequency Mobile X ray	Smooth, rugged, and easy-to-maneuver design 200 pre-programmed APR keys (KVp & mAs) Custom body part settings, 12 programmable keys Microprocessor protection with self-diagnostics Variants: 6KW, 10KW, 30KW single-phase Specs: Power Output: 2.5 KW Frequency: 25 KHz Tube Voltage: 40-100 KV Tube Current: 50mA to 25mA Power Supply: 220V±10%, 50Hz
280	Radiology Equipment	High Frequency Fixed X ray	"Compact Design: 4-wheel moving support for easy mobility Pre-programmed APR: 200 function keys with predefined KVp and mAs values Control Panel: Separate stand with sleek, lightweight design Special Function Settings: Tailored for different person types and body part positioning User Customization: 12 blank keys for user programming and factory recall Microprocessor-Based Protection: Includes self- diagnostics for the machine Automatic Bucky Selection: Automatically selects Bucky stand/table Variants: Available in 15KW, 30KW, 40KW, and 50KW three-phase configurations"
281	Radiology Equipment	Surgical C Arm	Ergonomic Design: Smooth, compact, and user-friendly Vertical Actuator: Accurate and silent movement Horizontal Slider: Soft, effortless movement for smooth operation Rigid Construction: Built to withstand harsh environmental conditions External Cable Guards: Protects cables with durable wheel-mounted guards These features ensure both functionality and durability for the C-Arm.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
282	Radiology Equipment	Surgical C Arm High End C-ARM	Ergonomic Design: Smooth, compact, and user-friendly Vertical Actuator: Accurate and silent movement Horizontal Slider: Soft, effortless movement for smooth operation Rigid Construction: Built to withstand harsh environmental conditions External Cable Guards: Protects cables with durable wheel-mounted guards These features ensure both functionality and durability for the C-Arm.
283	Radiology Equipment	Line frequency Xray system	Technology: Line frequency based for high-quality exposure Standby Circuitry: Ensures functionality if the main control panel fails Exposures Counter: Tracks all exposures taken Compatibility: CR/DR compatible Automatic Bucky Selection: Provides ease of use Optional Mobile Carriage: Available for flexible positioning Variants: Available in 100mA, 150mA, 300mA, and 500mA configurations



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
284	Radiology Equipment	Digital Radiography Mobile Xray	APR-Based High Frequency: Precise and complete radiological system at an affordable price Compact & Lightweight: Easy transport, ideal for bedside X-rays Motorized Vertical Actuator: Easy mobility in all directions with effective braking Soft Touch Keypad: Auto-programmable with reprogrammable settings Microprocessor System: Digital display of applied factors on an LCD screen Detachable Exposure Release Switch: Flexible control for the user LCD Touch Control: User-friendly interface for operation 14" x 17" Portable Wi-Fi FPD: Provides seamless wireless connectivity Dual Battery System: Hot swap capability (60s), ensuring no image loss Fast Image Transfer: Full image received in 2 seconds, with strong signal reception Access Point Mode: Easy computer connection with no additional wireless configuration Featherweight Design: Only 2.7kg with the battery, ensuring portability Easy Cleaning: IPX6-rated for water resistance, allowing easy cleaning Protection Mechanisms: G-sensor for fall detection, and temperature sensor that auto shuts down if temperature exceeds 50°C
285	Radiology Equipment	Digital Radiography Fixed X ray	Stationary Design: Reliable, consistent imaging in a fixed position. High Image Quality: Clear, detailed digital X-rays. Fast Image Processing: Instant results, improving workflow. User-Friendly: Easy touch controls and connectivity (wired/wireless). Durable: Built for frequent clinical use. Automated Settings: Ensures optimal exposure and image quality. System Compatibility: Integrates with hospital data systems (PACS, DICOM).



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
286	IVD Equipment	BIOCHEMISTRY ANALYSER	250 user-defined programs, 10,000 results memory Assay modes: linear, non-linear, rate, absorbance Dual cuvette system, Peltier temperature control 6 wavelengths (340-630 nm), photometric range 0-3.0 OD Air purge, peristaltic pump, lamp-saving feature Extras: 3-level QC with Levey-Jennings graph Large display, built-in thermal printer, PC connectivity Compact, high-precision, and economical
287	IVD Equipment	BIOCHEMISTRY ANALYSER	Type: Open, Flowcell Colorimetric Analyzer Measurement: Rate/End Point, Colorimetry Wavelength Range: 340-670 nm, 8 filters Cuvette: 18 µl flow cell, 10 ml polystyrene, 6 mm glass tube Temperature Control: Peltier (20°C-40°C) Sample Aspiration: Peristaltic pump (100 µl to 2997 µl) Precision: <1% CV Display: 240x64 LCD Memory: 1MB Flash, 136KB SRAM Printer: Built-in thermal printer, USB printer support Software: 11 analytical modes, 260 test programs, QC data, non-linear calibration, and reagent checks Size: 446 x 312 x 175 mm, 6 kg Power: 115/230V AC, 50/60 Hz
288	IVD Equipment	BIOCHEMISTRY ANALYSER	Optical Module: Range: 340-670 nm, 8 filters Silicon photodiode detector, 0-3.0 OD range Quartz Halogen lamp (12V, 20W) Measuring Module: Cuvettes: 18 µl flow cell, 10 mm square, 6 mm round Peltier temperature control (20°C-40°C) Peristaltic pump, min. 200 µl aspiration Analysis Modes: 1-point/2-point linear/non-linear, Rate A, Absorbance, Coagulation Memory: 200 programs, 1000 results, 3 levels QC Display & Interface: High-res LCD, 120 x 92 mm USB connectivity, built-in thermal printer Power: External SMPS (18V DC, 70W) Size & Weight: 205 x 450 x 300 mm, 7 kg Optional: 16 Position Dry Block Incubator



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
289	IVD Equipment	BIOCHEMISTRY ANALYSER	Product: Automated ESR Analyzer with stat facility Features: - Modified Westergren Method Dry technology - Batch mode with stat facility 25-minute analysis time - Barcode reader and printer - HCT correction 5000 records data storage - Real-time sedimentation assessment - Touchscreen colored display Application: ESR analysis
290	IVD Equipment	BIOCHEMISTRY ANALYSER	Advanced Biosensor Technology - Small aspiration volume - Short turnaround time (TAT) - No maintenance cost - Lab mean enabled - Predictable cost per sample Application: Analysis of electrolytes from whole blood, serum/plasma, pre-diluted urine, etc. Efficient, cost-effective, and reliable for electrolyte testing!
291	IVD Equipment	BIOCHEMISTRY ANALYSER	Single-channel, semi-automated system (1 test at a time) 14-digit sample ID, auto-detection for assay steps - Clotting (640nm) & Immuno-turbidimetric (800nm) tests - Preparation/incubation line for simultaneous assays Specifications: - Size: 216 x 205 x 75 mm, Weight: ~1 kg - Operating Temp: 17-32°C, Max 80% RH - Power: 100-240 VAC, 45W - Up to 6 calibration levels, 12 QC controls - Stores 1000 QC & 1000 patient results, external USB backup



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
292	IVD Equipment	BIOCHEMISTRY ANALYSER	4-channel semi-automated system (4 simultaneous tests) 14-digit alphanumeric sample ID, custom or progressive ID Option for second row of assay preparation/incubation Assays in single or duplicate (programmable) Auto-detection and measurement start Test principles: Clotting (640nm), Chromogenic (405nm), Immuno-turbidimetric (800nm) Specifications: Size: 300 x 290 x 90 mm, Weight: 3 kg Operating Temp: 17-32°C, Max 80% RH Power: 100-240 VAC, 45W Calibration: Up to 6 levels per assay, stores active calibration curve QC & Storage: Up to 12 control names, Levey-Jennings plotting, automatic stats calculation Memory: 600 QC results, 900 patient results (duplicate runs) Storage: External USB (FAT32), regular backup recommended
293	IVD Equipment	CLIA ANALYSER	7-channel fully automated hemostasis instrument 10 tests per profile, continuous sample loading 14-digit numeric or custom sample ID Assays in single or duplicate (programmable) Light scatter principle for detection Test principles: Clotting (640nm), Chromogenic (405nm), Immuno-turbidimetric (575nm) Specifications: Size: 660 x 580 x 510 mm, Weight: ~53 kg Operating Temp: 17-32°C, Max 80% RH Power: 100-240 VAC, 45W Calibration: Up to 6 levels, active curve storage QC & Storage: Up to 12 control totals, Levey-Jennings plotting, multi-rules Memory: 100 QC results, 100,000 patient results (duplicate runs) Storage: Reaction curves stored, new results replace oldest



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
294	IVD Equipment	COAGULATION ANALYZER	Tests: PT, APTT, INR, Fibrinogen, Thrombin Time, D-dimer, Coagulation Factor assays. Technology: Optical or photo-optical clot detection. Sample Type: Citrated plasma, whole blood. Throughput: 30-100 tests per hour, 2-8 samples at a time. Test Time: 1-5 minutes per test. Interface: LCD/LED touchscreen, user-friendly. Calibration: Automatic, with built-in quality controls. Connectivity: LIS integration, USB/LAN/Wi-Fi, external printer support. Size/Weight: Compact, bench-top (5-12 kg). Power: 110-220V AC, some models with battery backup. Additional Features: Barcode scanner, self-diagnostics, error alerts.
295	IVD Equipment	COAGULATION ANALYZER	Modes: Whole Blood, Predilute, Capillary Autoloader: 60 tubes, auto-mixing Tests: 36 parameters (CBC, WBC Diff, Hb, PLT, etc.) Measurement: Impedance (RBC/PLT/WBC), Laser Flowcytometry (WBC Diff), Cyanide-Free Colorimetry (Hb) Sample Volume: 20 μL (Whole Blood, Predilute, Capillary), 13 μL (CBC) Throughput: 80 tests/hour Linearity Range: WBC: $0-300 \times 10^3/\mu\text{L}$, Hb: 0-25 g/dL, PLT: $0-3000 \times 10^3/\mu\text{L}$ Storage: 100,000 results with graphs Dimensions: 650x550x610 mm, 59 kg Interfaces: 4 USB, 1 LAN (LIS) Operating Conditions: 15-40°C, 30-90% humidity Power: 100-240V, 200 VA



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
296	IVD Equipment	COAGULATION ANALYZER	Throughput: 200 photometric tests/hour, 400 tests/hour with ISE (Optional) Reagent Positions: 50 cooled positions Sample Types: Whole blood, Serum, Plasma, Urine, CSF, others Reading Volume: 180 μL Sample Volume: 2-70 μL (Adjustable in 0.1 μL increments) Reagent Volume: 10-300 μL (Adjustable in 1 μL increments) Light Source: Halogen lamp Onboard Cleaning: 6-stage cleaning, 2-stage drying with cuvette validation Calibration: Linear, Non-Linear, Multipoint Programmable Parameters: Default + 10 user-defined Dimensions: 810 (W) x 800 (D) x 600 (H) mm Weight: ~120 kg
297	IVD Equipment	ELECTROLYTE ANALYZER	Sample Type: EDTA Sample Volume: > 1.5 mL Display: 5.7" TFT, 640x480 resolution, LED backlight Result Cycle Time: < 25 minutes Measuring Range: 0-140 mm/hr HCT Correction: Available for anemic samples QC: Inbuilt 3-level QC with LJ Graph Throughput: 60 samples/hour Sample Position: 30 positions Mode: Continuous, STAT facility available Mixer & Printer: Inbuilt Barcode Reader: Inbuilt Data Storage: 5000 results Dimensions: 550(L) x 500(W) x 395(H) mm Weight: 20 kg Operating Conditions: 20-30°C, Max 80% RH Power Supply: 100-240V AC, 50/60Hz (with external 240V DC adapter)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
298	IVD Equipment	ELISA PROCESSOR	Modes: Whole Blood, Predilute, Capillary Parameters: 24 (including CBC, Mentzer index, RDWI) Principle: Electrical Impedance (RBC/PLT/WBC/DIFF), Cyanide-Free Colorimetry (Hb) Sample Volume: 9 μL (Whole Blood), 20 μL (Predilute/Capillary) Linearity: WBC: 0-300 $\times 10^3/\mu$L, RBC: 0-8.5 $\times 10^6/\mu$L, Hb: 0-25 g/dL, PLT: 0-3000 $\times 10^3/\mu$L Throughput: 60 tests/hour QC: L-J graph, X-Bar analysis, 500 files storage Data Storage: 50,000 results with graphs Dimensions: 364x477x417 mm, 25 kg Interfaces: 4 USB, 1 LAN (LIS) Power: 100-240V AC, 200VA
299	IVD Equipment	ESR ANALYSER	Test Method: Westergren method for ESR testing Sample Type: Whole blood (EDTA) Test Parameters: ESR (Erythrocyte Sedimentation Rate) Sample Volume: 1.6 mL Throughput: 100 tests/hour Result Time: < 20 minutes Calibration: Automatic calibration Temperature Correction: Automatic temperature correction for accurate results Quality Control: Inbuilt 3-level QC, with LJ graph analysis Data Storage: Stores up to 5,000 results Display: LCD touchscreen for easy operation Sample Positions: Typically 20-40 positions Printer: Inbuilt or external printer for results Barcode Reader: Inbuilt for sample identification Interfaces: USB, LAN, LIS (Laboratory Information System) connectivity Power Supply: AC 100-240V, 50/60Hz Dimensions: Compact, approx. 300mm x 300mm x 350mm Weight: Around 5-8 kg



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
300	IVD Equipment	ESR ANALYSER	Modes: Whole Blood, Predilute, Capillary Parameters: 36 (CBC, DIFF, Mentzer Index, RDWI) Principle: Electrical Impedance (RBC/PLT), Laser Flowcytometry (WBC/DIFF), Cyanide-Free Colorimetry (Hb) Sample Volume: 15 µL (Whole Blood), 20 µL (Predilute/Capillary), 11 µL (CBC) Throughput: Up to 60 tests/hour Linearity: WBC: 0-300 x 10³/µL, RBC: 0-8.5 x 10⁶/µL, Hb: 0-25 g/dL, PLT: 0-3000 x 10³/µL QC: 500 files, L-J Graph, X-Bar Analysis Data Storage: 100,000 results, 100 calibrator results Dimensions: 364x498x431 mm Weight: 26.5 kg Interfaces: 4 USB, 1 LAN (LIS connectivity) Power: 100-240V AC, 200VA
301	IVD Equipment	ESR ANALYSER	Type: Reflectance photometer Wavelengths: 470, 540, 650 nm Throughput: 60 tests/hr (Normal), 240 tests/hr (Smart Mode) Memory: 400 results Parameters: Specific Gravity, Leucocytes, Nitrite, pH, Protein, Glucose, Ketone, Urobilinogen, Bilirubin, Blood, Microalbumin, Creatinine User Interface: Color TFT LCD Printer: Built-in thermal printer Certificates: CE Dimensions: 230 x 127 x 110 mm Weight: 0.8 kg Test Strips: Dekaphan Laura, MicroalbuPHAN Laura Optical QC: Grey QC strip System Interface: RS232 & USB Power: AC 90-230V, 20W max (1W standby) Sample ID: Keyboard or barcode reader entry



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
302	IVD Equipment	ESR ANALYSER	Strip Analysis: Method: Reflective Photometry Input Tray Capacity: 200 strips Parameters: 10 Sediment Analysis: Method: Automated Brightfield Microscopy with Advanced Element Recognition Images per Sample: 15 Parameters: 16 categories System Throughput: Hybrid Mode (Chemistry & Sediment): 100 samples/hr Sediment Only: 180 samples/hr Sample Handling: Memory: 500,000 results Rack Size: 10 tubes Sample Load Capacity: 120 samples Sample Volume: Min 2 mL Control System: Display: 23" Multi-touch screen OS: Windows 8.1 Printer Interface: USB LIS Interface: Bi-directional Certification: CE certified
303	IVD Equipment	HEMATOLOGY ANALYZER	Type: Fully automated 3-part/5-part differential analyzer Parameters: 22-36 (CBC, WBC, RBC, Hb, HCT, Platelets, 5-part Diff) Principle: Electrical Impedance (RBC/PLT), Laser Flow Cytometry (WBC/Diff), Cyanide-Free Colorimetry (Hb) Sample Volume: 20 µL (Whole blood/Prediluted/Capillary) Throughput: Up to 60 tests/hr QC: Built-in 3-level QC with L-J graph Data Storage: 50,000 results Display: Color touch screen Power: 100-240V AC Connectivity: USB, LAN (LIS) Certifications: CE, ISO 13485



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
304	IVD Equipment	HEMATOLOGY ANALYZER	Dimensions: 1375 x 845 x 850 mm, Weight: 195 kg Power: 100-240V, 700W Capacity: Assays: Up to 12 per plate, 6 plates Sample Capacity: Up to 272, 20 racks (16 tubes/rack) Reader: Range: 0.0 - 3.5 O.D, 8 reading channels Filters: 8 positions (405, 450, 492, 620 nm + 2 open) Time: < 1 min (single filter) Washer: 16 needles, precision < 5% at 300 µL Wash cycle: Programmable, residual volume < 5 µL/well Incubator: Up to 6, Temp range: RT + 5°C to 50°C, Shaking speed: 200-800 RPM Pipetting: 2 probes, tips 300 µL/1000 µL, dispensing time: < 14 min (serum) Software: Windows 10, LIS bi-directional, Intel Core i3, 4 GB RAM, 22" touch screen
305			



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
306	IVD Equipment	HEMATOLOGY ANALYZER	System Type: Open system, compatible with 96-well U, V, and Flat bottom plates Operating Modes: Absorbance, Quantitative, Qualitative, Semi-Quantitative, Kinetic Mode Measurement Modes: Continuous, Step Shaking Modes: 3 linear speeds (Low, Medium, Fast), time adjustable Wavelength Range: 400 - 750 nm (standard filters: 405, 450, 492, 630 nm; optional: 578, 700 nm) Dynamic Range: 0.0 - 4.0 OD Photometric Accuracy: < 1% at 2.5 OD (450 nm) Photometric Resolution: 0.001 OD Measurement Time: Speed: 8 seconds (single wavelength) Normal: 17 seconds (single wavelength) Features: Display: High-resolution LCD (320x240 pixels) Keyboard: Waterproof membrane panel Storage: 100 test programs, stores up to 7,000 results Printer: Built-in high-resolution thermal printer, external printer option PC Communication: USB, compatible with Eli-LIMS Software: Windows-based for data management, calibration, and report generation Operating Temp: 20°C to 40°C, Humidity: max. 80% RH Power Supply: 16-24.5V DC, max. 90W (CE & UL certified) Dimensions and Weight: Size: 502 mm x 369 mm x 216 mm Weight: 7 kg



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
307	IVD Equipment	HEMATOLOGY ANALYZER	Wash Head: 8 or 12-head manifold compatible Wash Mode: Row and Plate Plate Types: 96 or 48-well (Flat, U, V-bottom) Wash Programs: 50 Dispensing Volume: 50 - 3000 μL (in 50 μL increments) Dispensing Precision: < 2% at 350 μL Prime Volume: 50 - 1000 μL Soak Time: 0 - 24 hours Residual Volume: $\leq$ 2 μL (V/U bottom), $\leq$ 3 μL (Flat bottom) Additional Details: Bottles: 2 wash, 1 rinse/DI, 1 waste (2L each, with level sensors) User Interface: 5-inch LCD with keypad Bottle Capacity: > 2 L Power Supply: AC 220V/110V, 50/60 Hz (< 80 VA) Operating Temp: 10°C - 30°C, Humidity: Up to 95% (non-condensing) Storage Temp: -10°C to 40°C Weight: 9.5 kg Dimensions: 710 mm x 530 mm x 380 mm
308	IVD Equipment	LISA READER	Power: 9V DC @ 2A Dimensions: 135 x 191 x 125 mm Weight: 1.5 kg Operating Temp: +5°C to +40°C Storage Temp: +5°C to +45°C Humidity: 20-80% (non-condensing) Linearity: 1-140 mm Display & Interface: Display: 480x272 TFT, 16.7M colors, touch panel EDTA Holder: 4 recesses Optical Unit: 4 opto-electronic pairs Interfaces: Bluetooth 4.0, USB Host/Device
309	IVD Equipment	ELISA READER	System: ELISA Reader Plate Type: 96-well plates Wavelength Range: 405 nm, 450 nm, 492 nm (standard filters), optional 578 nm, 700 nm Measuring System: 8-Channel Optical System Display: LCD with touch panel Memory: Stores up to 500 results Data Output: USB, bi-directional LIS interface Report Generation: Supports printing and data storage Power Supply: AC 100-240V, 50/60 Hz Weight: Approx. 7 kg Dimensions: 502 mm x 369 mm x 216 mm



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
310	IVD Equipment	LISA WASHER	Wash Head: 8 or 12 head manifold compatible Plate Type: 96 or 48-well plates (Flat, U, V-bottom) Wash Programs: 50 customizable programs Dispensing Volume: 50 - 3000 μL (in 50 μL increments) Residual Volume: $\leq 2 \mu$L (V/U bottom), $\leq 3 \mu$L (flat bottom) Operating Temperature: 10°C to 30°C Interface: LCD display with keypad Power Supply: AC 220V/110V, 50/60 Hz Dimensions: 710 mm x 530 mm x 380 mm Weight: 9.5 kg
311	IVD Equipment	MOLECULAR ANALYSER	Display: 19" Full HD LCD with PCAP touch Throughput: 190 samples/hr, first result in 28 mins Sample Tubes: 89 positions, 18 racks simultaneous loading Sample Mixing: 180° rotations LIS: ASTM/Proprietary, remote diagnostics via Ethernet Imaging: 2 high-res cameras Temperature: 15°C to 35°C operating Interfaces: USB, RS232C, Ethernet Power: 230V AC, 420VA Dimensions: 850 x 750 x 830 mm Weight: 80 kg
312	IVD Equipment	URINE CHEMISTRY ANALYSER	Sample volume: 2-70 μL (in 0,2 μL step) Reagent volume: R1 50-300 μL (in 1 μL step), R2 10- 200 μL (in 1 μL step) Minimum reaction volume: 180 μL Reaction temperature: 37°C $\pm$ 0,2°C
313	IVD Equipment	URINE CHEMISTRY ANALYSER	Type: Automated Clinical Chemistry Analyzer Throughput: 400 tests/hr (Photometric), 640 tests/hr (with ISE) Sample Capacity: 82 positions Reagents: 56 positions with cooling Photometer: 12 wavelengths (340-750 nm) Power: 220V/110V, 800 VA Dimensions: 897 x 655 x 1170 mm Weight: 200 kg Interfaces: USB, TCP/IP, RS-232



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
314	IVD Equipment	URINE CHEMISTRY ANALYSER	System Type: Automated, random access clinical chemistry analyzer (1, 2, 3 reagent system) Throughput: 1040 tests/hr (photometric), 240 tests/hr (ISE) Sample Capacity: 150 samples Photometer: 15 wavelengths, Tungsten halogen lamp Reagents: 86 positions with refrigeration Pipetting: 2-70 µl (biochemistry), 70 µl (ISE) Power: 220V or 110V, 2000 VA Dimensions: 1350 x 1000 x 1250 mm Weight: 275 kg Interfaces: RS-232, USB, TCP/IP Operating System: Windows-based
315	Health ATM	Health Monitoring Kiosk	Screen 50+ health parameters (non-invasive & invasive) with App based Tele Health Consultation on an automated kiosk system suitable for Primary and secondary health screening
316	Surgical Instrument	ARTERY FORCEPS	Type: Surgical forceps for clamping arteries Material: Stainless steel Design: Serrated jaws for secure grip Size: Typically 125 mm Application: Used in surgeries to control bleeding by clamping blood vessels.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
317	Surgical Instrument	ARTERY FORCEPS	Type: Surgical forceps for clamping arteries Material: Stainless steel Design: Locking mechanism with serrated jaws Size: 140 mm Application: Used in surgeries to clamp blood vessels and control bleeding.
318	Surgical Instrument	ARTERY FORCEPS	Type: Surgical forceps for clamping arteries Material: Stainless steel Design: Locking mechanism with serrated jaws Size: 150 mm Application: Used to clamp blood vessels during surgeries to control bleeding.
319	Surgical Instrument	FORCEPS MIXTER	Type: Surgical forceps with curved jaws Material: Stainless steel Size: 7.5 inches Design: Curved for easy manipulation in deep or confined areas Application: Used for dissection, clamping, and tissue handling in surgeries.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
320	Surgical Instrument	FORCEPS MIXTER	Type: Surgical forceps with curved jaws Material: Stainless steel Size: 9 inches Design: Curved for precision in deep tissue dissection Application: Used for clamping, dissecting, and handling tissues in surgeries.
321	Surgical Instrument	FORCEPS MIXTER	Type: Curved surgical forceps Material: Stainless steel Size: 11 inches Design: Curved jaws for improved access and precision Application: Used for dissection, clamping, and tissue manipulation in surgeries.
322	Surgical Instrument	FORCEPS TISSUE	Type: Tissue forceps for grasping and holding tissues Material: Stainless steel Size: 200 mm Design: Fine serrated tips for secure tissue handling Application: Used in surgical procedures to hold or manipulate delicate tissues.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
323	Surgical Instrument	DISSECTING FORCEPS	Type: Fine-tipped dissecting forceps Material: Stainless steel Size: 130 mm Design: Precision tips for delicate dissection Application: Used for tissue dissection and separation during surgical procedures.
324	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical forceps for dissection Material: Stainless steel Size: 150 mm Design: Fine, tapered tips for precise dissection Application: Used in surgical procedures for delicate tissue separation and dissection.
325	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical dissecting forceps Material: Stainless steel Size: 180 mm Design: Fine, tapered tips for delicate dissection Application: Used for precise tissue dissection and separation in surgeries.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
326	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical dissecting forceps Material: Stainless steel Size: 120 mm Design: Tapered, fine tips for precise dissection Application: Used for detailed tissue dissection and separation during surgeries.
327	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical dissecting forceps Material: Stainless steel Size: 125 mm Design: Fine, tapered tips for accurate dissection Application: Used for precise tissue dissection and separation in surgical procedures
328	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical dissecting forceps Material: Stainless steel Size: 180 mm Design: Fine, tapered tips for precise dissection Application: Used for detailed tissue dissection and separation in surgical procedures.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
329	Surgical Instrument	DISSECTING FORCEPS	Type: Surgical dissecting forceps Material: Stainless steel Size: 190 mm Design: Precision tips for accurate tissue dissection Application: Used for fine dissection and tissue separation during surgical procedures
330	Surgical Instrument	FORCEP SPONGE HOLDING	Type: Sponge-holding forceps Material: Stainless steel Size: 240 mm Design: Serrated jaws for secure grip on sponges Application: Used in surgeries to hold sponges or dressings during procedures.
331	Surgical Instrument	TOWEL HOLDING FORECEPS	Type: Towel-holding forceps Material: Stainless steel Design: Locking mechanism with serrated tips for a secure grip Application: Used in surgeries to hold towels or drapes in place.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
332	Surgical Instrument	TOWEL HOLDING FORECEPS	Type: Towel-holding forceps Material: Stainless steel Design: Curved, serrated tips with locking mechanism Application: Used to securely hold towels or drapes in place during surgical procedures.
333	Surgical Instrument	TOWEL HOLDING FORECEPS	Type: Towel-holding forceps Material: Stainless steel Design: Serrated tips with a locking mechanism for secure grip Application: Used to hold towels or drapes securely in place during surgical procedures.
334	Surgical Instrument	SINUS FORECEPS	Type: Surgical sinus forceps Material: Stainless steel Size: 180 mm Design: Curved, serrated jaws for precision Application: Used for sinus surgery or procedures involving nasal passages and cavities.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
335	Surgical Instrument	INTESTINAL FORCEPS	Type: Surgical forceps for intestinal procedures Material: Stainless steel Size: 180 mm Design: Serrated jaws for secure grip Application: Used for clamping, holding, or manipulating intestines during surgeries.
336	Surgical Instrument	INTESTINAL FORCEPS	Type: Surgical forceps for intestinal procedures Material: Stainless steel Size: 203 mm Design: Smooth or serrated jaws for secure grip Application: Used for clamping, holding, or manipulating intestines during surgeries.
337	Surgical Instrument	STERILIZER FORECEPS	Type: Forceps for handling sterilized instruments or items Material: Stainless steel Design: Long, narrow jaws for precise handling Application: Used for safely handling sterilized equipment or items in sterile environments.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
338	Surgical Instrument	BONE CUTTING FORECEPS	Type: Surgical forceps for cutting bone Material: Stainless steel Size: 250 mm edge for bone cutting Application: Used for cutting bone during surgical procedures.
339	Surgical Instrument	BONE CUTTING FORECEPS	Type: Surgical forceps for bone cutting Material: Stainless steel Size: 190 mm Design: Sharp, robust jaws for cutting bone Application: Used in orthopedic surgeries for bone cutting or shaping.
340	Surgical Instrument	GOUGE FORECEPS	Type: Surgical forceps with gouge design Material: Stainless steel Size: 170 mm Design: Curved jaws with a gouge shape for tissue removal Application: Used for removing or shaping tissue in surgeries, particularly in bone or joint procedures.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
341	Surgical Instrument	SKULL CHANNELING FORCEPS	Type: Surgical forceps for channeling the skull Material: Stainless steel Design: Specialized tips for precise skull channeling Application: Used in neurosurgical procedures for creating channels in the skull.
342	Surgical Instrument	LANE BONE HOLDING FORCEPS	Type: Bone holding forceps Material: Stainless steel Size: 293 mm Design: Serrated jaws for secure grip on bone Application: Used in orthopedic surgeries to hold bone fragments in place during procedures.
343	Surgical Instrument	SEQUESTRUM FORCEPS	Type: Surgical forceps for sequestrum removal Material: Stainless steel Size: 195 mm Design: Serrated jaws for secure grip on sequestrum (dead bone tissue) Application: Used in orthopedic surgeries to remove sequestra (fragments of dead bone).



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
344	Surgical Instrument	PLASTER BENDING FORCEPS	Type: Forceps for bending plaster Material: Stainless steel Design: Strong, durable jaws for bending plaster or casts Application: Used in orthopedic settings to adjust or shape plaster casts.
345	Surgical Instrument	OSTEOTOME	Type: Surgical instrument for bone cutting Material: Stainless steel Size: 95 mm Design: Flat, beveled blade for precise bone cutting or shaping Application: Used in orthopedic surgeries for cutting or shaping bone.
346	Surgical Instrument	OSTEOTOME	Type: Surgical instrument for bone cutting Material: Stainless steel Size: 127 mm Design: Flat, beveled blade for precise bone cutting Application: Used in orthopedic surgeries for cutting or shaping bone.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
347	Surgical Instrument	OSTEOTOME	Type: Surgical instrument for bone cutting Material: Stainless steel Size: 191 mm Design: Flat, beveled blade for precise bone cutting or shaping Application: Used in orthopedic surgeries to cut, shape, or remove bone.
348	Surgical Instrument	OSTEOTOME	Type: Surgical instrument for bone cutting Material: Stainless steel Size: 138 mm Design: Flat, beveled blade for accurate bone shaping and cutting Application: Used in orthopedic surgeries for precise bone cutting or reshaping.
349	Surgical Instrument	CHISEL	Type: Surgical chisel for bone procedures Material: Stainless steel Size: 125 mm Design: Flat, beveled cutting edge for precise bone cutting Application: Used in orthopedic surgeries for shaping, cutting, or removing bone.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
350	Surgical Instrument	BONE AWL	Type: Surgical instrument for bone penetration Material: Stainless steel Design: Sharp, pointed tip for creating holes in bone Application: Used in orthopedic surgeries for making holes in bone during procedures like drilling or inserting pins.
351	Surgical Instrument	BONE AWL	Type: Surgical bone awl Material: Stainless steel Design: Sharp, pointed tip for precise bone penetration Application: Used in orthopedic surgeries to create holes or indentations in bones for procedures like pin insertion.
352	Surgical Instrument	BONE AWL	Type: Surgical bone awl Material: Stainless steel Size: 24 cm Design: Sharp, pointed tip for precise bone penetration Application: Used in orthopedic surgeries for creating holes or indentations in bone for implants or other procedures.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
353	Surgical Instrument	BONE AWL	Type: Surgical bone awl Material: Stainless steel Size: 36 cm Design: Sharp, pointed tip for accurate bone penetration Application: Used in orthopedic surgeries to create holes or indentations in bone for pin insertion or other procedures.
354	Surgical Instrument	DRILL TWIST	Type: Surgical drill twist Material: Stainless steel Size: Typically 2 mm in diameter Design: Twist drill with sharp cutting edges Application: Used in orthopedic surgeries for drilling precise holes in bones for screws or pins.
355	Surgical Instrument	DRILL TWIST	Type: Surgical twist drill Material: Stainless steel Size: 2.8 mm in diameter Design: Sharp cutting edges for precise drilling Application: Used in orthopedic surgeries for drilling holes in bone for screws or pins.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
356	Surgical Instrument	DRILL TWIST	Type: Surgical twist drill Material: Stainless steel Size: 3.6 mm in diameter Design: Sharp cutting edges for precise drilling Application: Used in orthopedic surgeries to drill holes in bone for screws or other surgical implants.
357	Surgical Instrument	BURS	Type: Surgical burr Material: Stainless steel Size: Typically 16 mm in length Design: Rotary cutting tool with a smooth or serrated edge Application: Used in orthopedic surgeries for bone shaping, cutting, or removing tissue.
358	Surgical Instrument	BURS	Type: Surgical burr Material: Stainless steel Size: Typically 4 mm in diameter Design: Rotary cutting tool with a smooth or serrated edge Application: Used in orthopedic surgeries for shaping, cutting bone, or removing tissue.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
359	Surgical Instrument	BURS	Type: Surgical burr Material: Stainless steel Size: Typically 8 mm in diameter OK-SI/BUR-8 Design: Rotary cutting tool with smooth or serrated edges Application: Used in orthopedic surgeries for bone shaping, cutting, or tissue removal.
360	Surgical Instrument	BURS	Type: Surgical burr Material: Stainless steel Size: Typically 12 mm in diameter Design: Rotary cutting tool with smooth or serrated edges Application: Used in orthopedic surgeries for bone shaping, cutting, or tissue removal.
361	Surgical Instrument	BOWLS	Type: Surgical bowl Material: Stainless steel Size: 200 mm Design: Round, deep design for holding surgical instruments or materials Application: Used in surgeries for holding sterile instruments, tissues, or liquids.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
362	Surgical Instrument	BOWLS	Type: Surgical bowl Material: Stainless steel Size: 250 mm Design: Round, deep design for holding surgical instruments or materials Application: Used in surgeries to hold sterile instruments, tissues, or liquids.
363	Surgical Instrument	BOWLS	Type: Surgical bowl Material: Stainless steel Size: 100 mm Design: Round, shallow design for holding surgical instruments or materials Application: Used in surgeries for holding sterile instruments, tissues, or liquids.
364	Surgical Instrument	TRAY	Type: Surgical tray Material: Stainless steel Size: 450 mm Design: Flat, rectangular design for holding surgical instruments Application: Used in surgeries for organizing and holding sterile instruments or materials.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
365	Surgical Instrument	TRAY- KIDNEY SHAPED	Type: Kidney-shaped surgical tray Material: Stainless steel Size: 250 mm Design: Kidney-shaped, shallow design for holding surgical instruments or materials Application: Used in surgeries to hold sterile instruments, tissues, or liquids.
366	Surgical Instrument	TRAY WITH COVER	Type: Surgical tray with cover Material: Stainless steel Size: 350 mm Design: Rectangular tray with a secure cover Application: Used for holding and covering surgical instruments or materials to maintain sterility.
367	Surgical Instrument	NEEDLE HOLDER(KILNER)	Type: Surgical needle holder (Kilner design) Material: Stainless steel Size: 140 mm Design: Smooth or serrated jaws with a locking mechanism Application: Used for holding needles during suturing in surgical procedures.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
368	Surgical Instrument	NEEDLE HOLDER (OSLEN HEGAR)	Type: Surgical needle holder (Oslen Hegar design) Material: Stainless steel Size: 140 mm Design: Serrated jaws with a locking mechanism Application: Used for holding needles during suturing in surgical procedures, especially in delicate surgeries.
369	Surgical Instrument	NEEDLE HOLDER	Type: Surgical needle holder Material: Stainless steel Size: 190 mm Design: Serrated jaws with a locking mechanism Application: Used for holding needles during suturing in surgical procedures.
370	Surgical Instrument	SCISSORS(MCINDOE)	Type: Surgical scissors (McIndoe design) Material: Stainless steel Size: Standard Design: Fine, sharp blades for precise cutting Application: Used for delicate tissue dissection and cutting in surgeries.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
371	Surgical Instrument	SCISSORS(METZENBAUN)	Type: Surgical scissors (Metzenbaum design) Material: Stainless steel Size: 190 mm Design: Long, thin blades for cutting delicate tissues Application: Used for cutting delicate tissues in surgeries.
372	Surgical Instrument	SCISSORS(METZENBAUN)	Type: Surgical scissors (Metzenbaum design) Material: Stainless steel Size: 115 mm Design: Fine, curved blades for cutting delicate tissue Application: Used for delicate dissection and cutting in surgical procedures.
373	Surgical Instrument	KNIFE(BARD PARKER)	Type: Surgical knife (Bard Parker) Material: Stainless steel Size: Standard blade size Design: Handle with replaceable blade Application: Used for making precise incisions during surgery.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
374	Surgical Instrument	KNIFE(BARD PARKER)	Type: Surgical knife (Bard Parker) Material: Stainless steel Size: Standard blade size Design: Handle with replaceable blade Application: Used for making precise incisions during surgeries.
375	Surgical Instrument	CLAMP BULLDOG	Type: Bulldog clamp Material: Stainless steel Size: 70 mm Design: Small, spring-loaded clamp with jaws for controlling blood flow Application: Used to clamp blood vessels during surgeries.
376	Surgical Instrument	CLAMP BULLDOG	Type: Bulldog clamp Material: Stainless steel Size: 85 mm Design: Spring-loaded clamp with jaws for controlling blood vessels Application: Used in vascular surgeries to clamp blood vessels



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
377	Surgical Instrument	CLAMP BULLDOG	Type: Bulldog clamp Material: Stainless steel Size: 100 mm Design: Spring-loaded with strong jaws for clamping blood vessels Application: Used to clamp blood vessels during surgical procedures.
378	Surgical Instrument	RETRACTOR LAGENBACK	Type: Langenback retractor Material: Stainless steel Size: 22 mm Design: Curved blade for retracting tissues Application: Used for holding back tissue during surgeries.
379	Surgical Instrument	RETRACTOR LAGENBACK	Type: Langenback retractor Material: Stainless steel Size: 45 mm Design: Curved blade for tissue retraction Application: Used in surgeries for retracting tissues.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
380	Surgical Instrument	RETRACTOR ABDOMINAL	Type: Abdominal retractor Material: Stainless steel Size: 100 mm Design: Wide, flat blades for holding abdominal tissues Application: Used to retract abdominal tissues during surgeries.
381	Surgical Instrument	RETRACTOR ABDOMINAL	Type: Abdominal retractor Material: Stainless steel Size: 303 mm Design: Large blades for abdominal tissue retraction Application: Used in abdominal surgeries to hold back tissues.
382	Surgical Instrument	HOOK SINGLE	Type: Single surgical hook Material: Stainless steel Size: Standard Design: Sharp hook for tissue manipulation Application: Used to hold or manipulate tissues during surgery.



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
383	Surgical Instrument	HOOK DOUBLE	Type: Double surgical hook Material: Stainless steel Size: Standard Design: Two hooks for manipulating tissues Application: Used to hold or retract tissues during surgeries. These brief specifications should be suitable for your needs.
384	Medical Textiles	Isolation Gown	(Front Open)
385	Medical Textiles	Isolation Gown-Breathable	(Front Open)
386	Medical Textiles	Isolation Gown	(Back Open)
387	Medical Textiles	Isolation Gown-Breathable	(Back Open)
388	Medical Textiles	Isolation Gown-Premium	(Front Open)
389	Medical Textiles	Isolation Gown-Premium	(Back Open)
390	Medical Textiles	Sterilization Wrap	90x100cm
391	Medical Textiles	Sterilization Wrap	90x200cm



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
392	Medical Textiles	Sterilization Wrap	90x300cm
393	Medical Textiles	Sterilization Wrap	100X100cm
394	Medical Textiles	Sterilization Wrap	100x200cm
395	Medical Textiles	Sterilization Wrap	100x300cm
396	Medical Textiles	Sterilization Wrap	150x100cm
397	Medical Textiles	Sterilization Wrap	150X200cm
398	Medical Textiles	Sterilization Wrap	150X300cm
399	Medical Textiles	Sterilization Wrap	160x100cm
400	Medical Textiles	Sterilization Wrap	160x200cm
401	Medical Textiles	Sterilization Wrap	160x300cm
402	Medical Textiles	Low Risk PPE Kit-Gown	PPE (STERILE)
403	Medical Textiles	Medium Risk PPE Kit-Gown	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
404	Medical Textiles	Medium Risk PPE Kit-Gown	
405	Medical Textiles	Low Risk PPE Kit-Coverall	
406	Medical Textiles	Medium Risk PPE Kit-Coverall	
407	Medical Textiles	Medium Risk PPE Kit-Coverall	
408	Medical Textiles	High Risk PPE Set for HCWs & Patients	
409	Medical Textiles	PPE Kit-Isolation Barrier	
410	Medical Textiles	PPE Kit-Gown-Blended Fabric	PPE (NON-STERILE)
411	Medical Textiles	PPE Kit-Coverall-Blended Fabric	
412	Medical Textiles	PPE Kit-Gown-Polyester Fabric	
413	Medical Textiles	PPE Kit-Coverall-Polyester Fabric	
414	Medical Textiles	Single-use Coverall Level 1	COVERALL-03
415	Medical Textiles	Single-use Coverall Level 2	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
416	Medical Textiles	Single-use Coverall Level 3	
417	Medical Textiles	Single-use Coverall Level 4	
418	Medical Textiles	Multiple-use Coverall Level 1	COVERALL-04
419	Medical Textiles	Multiple-use Coverall Level 2	
420	Medical Textiles	Multiple-use Coverall Level 3	
421	Medical Textiles	Multiple-use Coverall Level 4	
422	Medical Textiles	Surgical Gown Level 2	SURGICAL GOWN
423	Medical Textiles	Surgical Gown Level 3 (Backless)	
424	Medical Textiles	Surgical Gown Level 3	
425	Medical Textiles	Surgical Gown Level 3 (Reinforced)	
426	Medical Textiles	Surgical Gown Level 4	
427	Medical Textiles	Surgical Gown level 4 (Reinforced)	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
428	Medical Textiles	Surgical Gown Blended Fabric	
429	Medical Textiles	Surgical Gown Blended Fabric (Reinforced)	
430	Medical Textiles	Laparoscopic Camera Drape	SURGICAL DRAPES & ACCESSORIES
431	Medical Textiles	C-Arm Drape	
432	Medical Textiles	Microscope Drape	
433	Medical Textiles	USB Probe Cover	
434	Medical Textiles	Plain Drape-Small	
435	Medical Textiles	Plain Drape-Medium	
436	Medical Textiles	Plain Drape-Large	
437	Medical Textiles	Plain Drape-Extra Large	
438	Medical Textiles	Plain Drape Absorbent-Small	
439	Medical Textiles	Plain Drape Absorbent-Medium	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
440	Medical Textiles	Plain Drape Absorbent-Large	
441	Medical Textiles	Plain Drape Absorbent-Extra Large	
442	Medical Textiles	Mayo Trolley Drape	
443	Medical Textiles	Plain Drape with Absorbent Pad- Small	
444	Medical Textiles	Plain Drape with Absorbent Pad & Drain Pouch-Small	
445	Medical Textiles	Procedure Drape with Absorbent Pad-Large	
446	Medical Textiles	Procedure Drape with Absorbent Pad & Instrument Pouch-Large	
447	Medical Textiles	Absorbent Pad-Small	
448	Medical Textiles	Absorbent Pad-Large	
449	Medical Textiles	Patient Transfer Drape-Absorbent	
450	Medical Textiles	Procedure Drape with Hole-Small	
451	Medical Textiles	Procedure Drape with Hole-Medium	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
452	Medical Textiles	Procedure Drape with Hole-Large	
453	Medical Textiles	Split Drape	
454	Medical Textiles	Groin Drape	
455	Medical Textiles	Spinal Anaesthesia Drape	
456	Medical Textiles	Plain Drape-Reinforced-Blended Fabric-Small	
457	Medical Textiles	Plain Drape-Reinforced-Blended Fabric-Medium	
458	Medical Textiles	Plain Drape-Reinforced-Blended Fabric-Large	
459	Medical Textiles	Procedure Drape-Reinforced-with Hole-Blended Fabric-Small	
460	Medical Textiles	Procedure Drape-Reinforced-with Hole-Blended Fabric-Medium	
461	Medical Textiles	Procedure Drape-Reinforced-with Hole-Blended Fabric-Large	
462	Medical Textiles	Femoral Angiography Drape	
463	Medical Textiles	Radial Angiography Drape	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
464	Medical Textiles	Femoral and Radial Angiography Drape	
465	Medical Textiles	CABG Drape Paediatric	
466	Medical Textiles	CABG Drape Adult	
467	Medical Textiles	Valve Replacement Drape	
468	Medical Textiles	Pacemaker Drape	
469	Medical Textiles	ENT Drape with Absorbent Pad- Small	
470	Medical Textiles	ENT Drape with Absorbent Pad & Drain Pouch-Small	
471	Medical Textiles	ENT Drape with Absorbent Pad- Large	
472	Medical Textiles	ENT Drape with Absorbent Pad & Drain Pouch-Large	
473	Medical Textiles	Eye Surgery Drape-Eco	
474	Medical Textiles	Eye Surgery Drape-Premium	
475	Medical Textiles	Eye Surgery Drape with Absorbent Pad	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
476	Medical Textiles	Maternity Drape with Absorbent Pad	
477	Medical Textiles	Maternity Drape with Absorbent Pad & Drain Pouch	
478	Medical Textiles	Normal Delivery Sheet- Lithotomy	
479	Medical Textiles	Caeserean Drape	
480	Medical Textiles	Gynaecology Drape- Laparoscoy	
481	Medical Textiles	Laparoscopy Drape	
482	Medical Textiles	Laparotomy Drape	
483	Medical Textiles	TURP Drape	
484	Medical Textiles	PCNL Drape	
485	Medical Textiles	Crainotomy Drape	
486	Medical Textiles	Head & Neck Procedure Drape with Absorbent Pad	
487	Medical Textiles	Breast Procdure Drape	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
488	Medical Textiles	Shoulder 'O' Drape	
489	Medical Textiles	Arm 'U' Drape	
490	Medical Textiles	Knee 'O' Drape	
491	Medical Textiles	Hip 'U' Drape	
492	Medical Textiles	Bilateral Knee 'O' Drape	
493	Medical Textiles	Shoulder Arthroscopy Drape	
494	Medical Textiles	Knee Arthroscopy Drape	
495	Medical Textiles	Spinal Procedure Drape	
496	Medical Textiles	Anesthesia Procedure Pack	
497	Medical Textiles	OR Pack-Small-EO	
498	Medical Textiles	OR Pack-Small-Gamma	
499	Medical Textiles	OR Pack-Large-EO	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
500	Medical Textiles	OR Pack-Large-Gamma	
501	Medical Textiles	Universal Drape Pack	
502	Medical Textiles	Laparoscopy Drape Set	
503	Medical Textiles	Laparotomy Drape Set	
504	Medical Textiles	Head & Neck Drape Surgery Set	
505	Medical Textiles	Breast Surgery Drape Set	
506	Medical Textiles	Thoractomy & Laparatomy Drape Set	
507	Medical Textiles	Onco Surgery Drape Set	
508	Medical Textiles	Joint Replacement Surgery Pack	
509	Medical Textiles	Shoulder Arthroscopy Pack	
510	Medical Textiles	Knee Arthroscopy Pack	
511	Medical Textiles	Spianl Procedure Pack	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
512	Medical Textiles	CABG Drape Set-Paediatic	
513	Medical Textiles	CABG Drape Set-Adult	
514	Medical Textiles	Valve Replacement Drape Set	
515	Medical Textiles	Pacemaker Drape Set	
516	Medical Textiles	Turban Drape	
517	Medical Textiles	Examination Gown Thumb loop	PROFESSIONAL EXAMINATION GOWN
518	Medical Textiles	Examination Gown Knitted Rib	
519	Medical Textiles	Patient Gown (Breathable)	PATIENT GOWN
520	Medical Textiles	Patient Gown (Premium)	
521	Medical Textiles	Patient Gown (Maternity)	
522	Medical Textiles	Patient Gown (Kid)	
523	Medical Textiles	Patient Gown (Eco-Blended Fabric)	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
524	Medical Textiles	Patient Gown (Premium-Blended Fabric)	
525	Medical Textiles	Patient Gown (Top & Trouser-Eco- Blended Fabric)	
526	Medical Textiles	Patient Gown (Top & Trouser-Premium-Blended Fabric)	
527	Medical Textiles	Patient Gown (Maternity_Blended Fabric)	
528	Medical Textiles	Patient Gown (Kids-Blended Fabric)	
529	Medical Textiles	Patient Gown (Top & Trouser-Kids)-Blended Fabric	
530	Disposables	Nitrile Examination Gloves	
531	Disposables	Nitrile Multipurpose Gloves	
532	Disposables	Nitrile Food Grade Gloves	
533	Disposables	Latex Surgical Gloves	
534	Disposables	Skin Stapler	
535	Disposables	Skin Stapler Remover	



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
536	Disposables	Blood Collection Tubes	Plain Tubes (Vacuum)
537	Disposables	Blood Collection Tubes	Clot Activator (Vacuum)
538	Disposables	Blood Collection Tubes	Clot Activator + GEL (Vacuum)
539	Disposables	Blood Collection Tubes	K2 EDTA (Vacuum)
540	Disposables	Blood Collection Tubes	K2 EDTA + GEL (Vacuum)
541	Disposables	Blood Collection Tubes	K3 EDTA (Vacuum)
542	Disposables	Blood Collection Tubes	K3 EDTA + GEL (Vacuum)
543	Disposables	Blood Collection Tubes	Glucose (NaF + K2 EDTA) (Vacuum)
544	Disposables	Blood Collection Tubes	Glucose (NaF + K3 EDTA) (Vacuum)
545	Disposables	Blood Collection Tubes	Glucose (Fluoride Oxalate) (Vacuum)
546	Disposables	Blood Collection Tubes	Lithium Heparin (Vacuum)
547	Disposables	Blood Collection Tubes	Lithium Heparin + GEL (Vacuum)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
548	Disposables	Blood Collection Tubes	Sodium Heparin (Vacuum)
549	Disposables	Blood Collection Tubes	Sodium Heparin + GEL (Vacuum)
550	Disposables	Blood Collection Tubes	Sodium Citrate 3.2 % (Vacuum)
551	Disposables	Blood Collection Tubes	Sodium Citrate 3.2 % + GEL (Vacuum)
552	Disposables	Blood Collection Tubes	Sodium Citrate 3.8 % (Vacuum)
553	Disposables	Blood Collection Tubes	Plain Tubes (Non -Vacuum)
554	Disposables	Blood Collection Tubes	Clot Activator (Non - Vacuum)
555	Disposables	Blood Collection Tubes	Clot Activator + GEL (Non - Vacuum)
556	Disposables	Blood Collection Tubes	K2 EDTA (Non - Vacuum)
557	Disposables	Blood Collection Tubes	K2 EDTA + GEL (Non - Vacuum)
558	Disposables	Blood Collection Tubes	K3 EDTA (Non Vacuum)
559	Disposables	Blood Collection Tubes	K3 EDTA + GEL (Non - Vacuum)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
560	Disposables	Blood Collection Tubes	Glucose (NaF + K2 EDTA) (Non - Vacuum)
561	Disposables	Blood Collection Tubes	Glucose (NaF + K3 EDTA) (Non - Vacuum)
562	Disposables	Blood Collection Tubes	Glucose (Fluoride Oxalate) (Non -Vacuum)
563	Disposables	Blood Collection Tubes	Lithium Heparin (Non - Vacuum)
564	Disposables	Blood Collection Tubes	Lithium Heparin + GEL (Non - Vacuum)
565	Disposables	Blood Collection Tubes	Sodium Heparin (Non - Vacuum)
566	Disposables	Blood Collection Tubes	Sodium Heparin + GEL (Non - Vacuum)
567	Disposables	Blood Collection Tubes	Sodium Citrate 3.2 % (Non - Vacuum)
568	Disposables	Blood Collection Tubes	Sodium Citrate 3.8 % (Non Vacuum)
569	Disposables	Blood Collection Tubes	Clot Activator 4ml (Non -Vacuum)
570	Disposables	Blood Collection Tubes	GEL + Clot 4ml (Non Vacuum)
571	Disposables	Blood Collection Tubes	K2 EDTA 2ml (Non Vacuum)



सिद्धिर्भवति कर्मजा

S.No	Category	AMTZ -Products List	Short Specifications
572	Disposables	Blood Collection Tubes	K3 EDTA 2ml (Non Vacuum)
573	Disposables	Blood Collection Tubes	Sodium Citrate 3.2 % 2ml (Non Vacuum)
574	Disposables	Blood Collection Tubes	Sodium Citrate 3.8 % ESR 2ml (Non Vacuum)
575	Disposables	Blood Collection Tubes	Lithium Heparin 2ml (Non Vacuum)
576	Disposables	Blood Collection Tubes	Lithium Heparin 2ml (Non Vacuum) Fluoride 2ml (Non Vacuum)