Shared-memory Systems

Architecture

- multiple instructions, multiple data
- share common memory
  - processors/cores operate independently
  - processors can access each others' memory
  - changes in memory by one processor are visible to the others
- UMA vs NUMA
  - complexity and scalability
  - memory access times
  - cache coherence and false sharing may be magnified with NUMA
  - UMA = SMP (Symmetric Multi-Processors)



- memory access
  - memory divided to many modules evenly distributed among processors
  - each core has its own cache
  - data
    - private: used only by a single processor
    - shared:
      - used by multiple processors
      - used for inter-process communication
- check the architecture of a node in a the Arnes cluster

```
module load likwid
srun --reservation=fri --exclusive likwid-topology -g
```

Cache Coherence

- different processors must see the same value at a given memory address
- snooping:
  - cache memory controller monitors bus to identify which cache lines are written by other processors
  - write invalidate protocol (most common)
  - get exclusive access before writing the data (write through)
  - before writing all other copies with this data are invalidated
  - does not scale well
  - illustration

- directory-based protocols
  - better suited for NUMA
  - a single directory contains sharing information (statuses) about every cache line
  - to keep performance, it is distributed among computer's local memories
  - must keep track which processors have copies to invalidate them when needed
  - example: simplified protocol
    - statuses
      - U: uncached, not in any cache
      - S: shared by one or more processors, values in memory are correct
      - E: exclusive, one processor has written the cache line, values in memory are obsolete
    - illustration



False Sharing

- cache is implemented in hardware, it operates on cache lines
- even if processors do not operate on the same variable but on variables located in the same cache line, the cache coherence protocols are involved
- does not produce false results
- disastrous consequences on performance
- illustration

Programming: Processes and Threads

Processes

- when we start a program, a new process appears in the operating system
- a process is the basic unit to which the operating system allocates resources:
  - a share of CPU cycles
  - a portion of free memory, which the OS protects from access by other processes
  - access to communication ports and I/O devices
  - file handles for the files the program needs
- the process first runs code that handles the tasks above, and then it runs the `main()` function in the program
- memory Allocation
  - program code and dynamic libraries
  - global variables defined outside the `main()` function
  - the heap is used for dynamic memory allocation
  - the stack stores everything needed during a function call, as well as variables defined inside function



Threads

- a thread is the basic execution unit that can be executed by OS
- a process can include several internal execution units, or threads
- a process always has at least a master thread
- from the master thread, we can start additional threads
  - this creates a new sequential flow of execution that runs asynchronously with the main one
  - the master flow of execution continues
  - from that point on, the master thread and the additional thread are equivalent
  - If needed, we can join the additional thread back to the master thread



- thread execution
  - threads are executed by the operating system; we have no control over the order in which they run
  - a multithreaded program can run on a single CPU core
  - if threads execute independent flows of execution on multiple cores at the same time, we call this parallel processing
- software vs. hardware threads
  - hardware threads allow multiple separate flows of execution to run simultaneously
  - the operating system decides which hardware thread will execute a particular software thread

Multithreaded processes



- shared resources
  - global variables (shown as static variables in the diagram)
  - the program code
  - dynamically allocated memory (the heap)
  - access to files, ports, and I/O devices
  - context switching
  - a process time slice
- threads execute independent flows of execution, so each one has its own:
  - registers, such as the program counter and stack pointer
  - stack
    - local variables on the stack are private to each thread
    - if a thread shares a memory address with other threads, those threads can access its local memory
- context switching
  - time slices

  - process
    - core state information includes:
      - registers, stack pointer, program counter
      - segmentation tables, page tables
      - to avoid incorrect address translation in the case of the previous and current processes using different memory, the translation lookaside buffer (TLB) must be flushed
    - a lot of operations which negatively affect performance
  - inside a process
    - user space implementation, no interaction with the kernel
    - locally saving thread registers
    - easier to tailor the scheduling policy
- a thread life-cycle:
  - when program starts only the main thread (master thread) is active
  - where a parallel operation is required, master thread creates additional threads
  - threads work concurrently
  - at the end of a parallel operation, additional threads are suspended, and only master thread continues