

F / 2 [kN]	q [kPa]	Ikerabroncs modell (VEM)				Helyettesítő körtárcsa modell (MLE)		
		A [μm]	B [μstrain]		C [μstrain]	A [μm]	B [μstrain]	C [μstrain]
		u _{zz}	ε _{xx}	ε _{yy}	ε _{zz}	u _{zz}	ε _{xx} = ε _{yy}	ε _{zz}
A hajlékony útpályaszerkezetben ébredő igénybevételek								
17,5	391	190	−64,23	−37,33	172,79	310	−68,83	195,19
20,0	413	217	−72,65	−43,00	196,97	352	−75,76	221,19
22,5	431	244	−80,73	−48,67	220,97	394	−82,27	246,77
20,0	440	217	−73,05	−42,19	196,69	354	−78,34	222,87
22,5	469	243	−81,51	−47,80	220,82	397	−86,81	249,89
25,0	471	270	−89,68	−53,42	244,75	439	−93,68	275,79
22,5	484	242	−81,71	−46,99	220,25	398	−87,58	250,38
25,0	516	269	−90,18	−52,56	244,31	441	−96,19	277,48
27,5	510	296	−98,42	−58,14	268,24	483	−102,56	303,03
25,0	530	268	−90,17	−51,71	243,31	442	−96,92	277,95
27,5	560	294	−98,63	−57,24	267,32	485	−105,41	304,96
30,0	557	321	−106,92	−62,77	291,21	527	−111,93	330,61
A félmerev útpályaszerkezetben ébredő igénybevételek								
17,5	391	125	−29,71	−14,01	110,34	249	−32,34	130,02
20,0	413	143	−33,51	−16,28	125,73	284	−35,94	149,88
22,5	431	161	−37,12	−18,57	140,97	318	−39,32	167,48
20,0	440	143	−33,78	−15,73	125,59	285	−36,76	150,69
22,5	469	160	−37,61	−17,97	140,95	320	−40,57	168,75
25,0	471	178	−41,27	−20,22	156,16	353	−43,41	185,80
22,5	484	159	−37,76	−17,43	140,62	320	−41,03	169,20
25,0	516	177	−41,60	−19,64	155,94	355	−44,92	187,34
27,5	510	195	−45,32	−21,87	171,15	388	−47,47	204,08
25,0	530	176	−41,65	−19,11	155,33	356	−45,35	187,77
27,5	560	194	−45,49	−21,29	170,61	390	−49,16	205,83
30,0	557	211	−49,23	−23,49	185,81	424	−51,80	222,66