



PC1

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ipconfig 192.168.1.3 255.255.255.0 192.168.1.1
C:\>ping 192.168.2.2

Pinging 192.168.2.2 with 32 bytes of data:

Reply from 192.168.2.2: bytes=32 time=15ms TTL=126
Reply from 192.168.2.2: bytes=32 time=1ms TTL=126
Reply from 192.168.2.2: bytes=32 time=1ms TTL=126
Reply from 192.168.2.2: bytes=32 time=1ms TTL=126

Ping statistics for 192.168.2.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 15ms, Average = 4ms

C:\>
```

Host	IP address	Subnet mask
Router0(0/0)	192.168.1.1	255.255.255.0
Router0 se2/0	11.0.0.1	255.0.0.0
Router1(0/0)	192.168.2.2	255.255.255.0
Router1 se2/0	11.0.0.2	255.0.0.0

Table 2.1

Host	IP address	Subnet mask	Default gateway
PC0	192.168.1.2	255.255.255.0	192.168.1.1
PC1	192.168.1.3	255.255.255.0	192.168.1.1
PC2	192.168.2.2	255.255.255.0	192.168.2.1
PC3	192.168.2.3	255.255.255.0	192.168.2.1

Table 2.2