SQL Code

```sql
drop database ecommerce_project;
create database zepto_project;
use zepto_project;

-- Create table
create table zepto (
    s_no serial PRIMARY KEY,
    category VARCHAR(255),
    name VARCHAR(500),
    mrp DECIMAL(10 , 2 ),
    discountPercent DECIMAL(10 , 2 ),
    availableQuantity INT,
    discountedSellingPrice DECIMAL(10 , 2 ),
    weightInGms INT,
    outOfStock VARCHAR(50),
    quantity INT
);

-- Upload Data
SET GLOBAL local_infile = 1;
SHOW GLOBAL VARIABLES LIKE 'local_infile';
LOAD DATA LOCAL INFILE
'D:/DATA ANALYSIS/Mysql Projects/Project 1/zepto_data_v1.csv'
INTO TABLE zepto
FIELDS TERMINATED BY ','
ENCLOSED BY '"'
LINES TERMINATED BY '\n'
IGNORE 1 ROWS
(category, name, mrp, discountPercent, availableQuantity, discountedSellingPrice,
weightInGms, outOfStock, quantity);

-- Data Exploration

-- count of rows
select count(*) from zepto;

-- sample data
select * from zepto limit 10;

-- null values
select * from zepto
where name is null
or
category is null
or
mrp is null
or
discountPercent is null
or
availableQuantity is null
```

```sql
or
discountedSellingPrice is null
or
weightInGms is null
or
outOfStock is null
or
quantity is null;

-- different categories
select distinct category
from zepto
order by category;

-- product in stock vs out of stock
select outOfStock,count(s_no)
from zepto
group by outOfStock;

-- product names present multiple times
select name, count(s_no)
from zepto
group by name
having count(s_no)>1
order by count(s_no) desc;

-- data cleaning
set SQL_SAFE_UPDATES = 0;
-- product with price = 0

select * from zepto
where discountedSellingPrice=0
or mrp=0;

delete from zepto where mrp=0;

-- convert paise to rupees
update zepto
set mrp=mrp/100.0,
discountedSellingPrice=discountedSellingPrice/100.0;

-- sample data
select * from zepto;
```