

Name: Princess Beverly R. Ala-an

Faculty: **MB. Pacot**

Section: BNO1

(Update this file to fill-in necessary data)

Objective:

Instruction Set Format. Write the equivalent opcode for the following MIPS64 instructions. Assume all constants are in hexadecimal. For binary opcode, please place an appropriate space after each field in your binary opcode submission (10 PTS. each address).

Address	Instruction	Opcode (Binary)	Opcode (Hex)
00	LW R1, 2000(R0)	100011 00000 00001 00100 00000 000000	8C012000
04	LWU R2, 2004(R0)	100111 00000 00010 00010 00000 000100	9C022004
08	SLT R3, R1, R2	000000 00001 00010 00011 00000 101010	0022182A
0C	DADDU R4, R1, R2	000000 00001 00010 00100 00000 101101	0022202D
10	DMUL R5, R1, R2	000000 00001 00010 00101 00010 101111	0022289C
14	DSLLV R6, R1, R2	000000 00010 00001 00110 00000 010100	00413014
18	ANDI R5, R1, #FFFC	001100 00001 00101 11111 11111 111010	3025FFFC
1C	OR R6, R1, R2	000000 00001 00010 00110 00000 100101	00223025

**Note: Originally, the highlighted text is DADDIU R4, R1, R2. Assuming that this is a wrong typo of DADDU, I have inputted its equivalent Binary and Hex of Opcode. Otherwise, if it's not a wrong typo, then there's no representation for DADDIU R4, R1, R2 because it doesn't follow the standard format on how to use DADDIU which is DADDIU rt, rs, immediate.*