




HPC-I Lab1 Automatic Vectorization

- Student ID: 111032042
- Name: 盛爾葳

SIMD Instruction Set	Time	Screenshot (including compilation logs)
SSE	4330 ms	
AVX2	1001 ms	
AVX512 (if your computer supports AVX512)	Not supported	

Compare SSE, AVX2 and AVX512

1. SSE Compilation

- Vectorized using 16-byte vectors
- Execution took 4330 ms

- Some loops could not be vectorized due to complex access patterns or functions like `rand()` that clobber memory.

2. AVX2 Compilation:

- Vectorized using **32-byte vectors**
- Execution took **1001 ms**
- *Significantly faster than SSE*, likely due to more data being processed per vector operation.

3. AVX-512 Compilation:

- Vectorized using **64-byte vectors**
- Encountered *"Illegal instruction (core dumped)"* upon execution, indicating the CPU does not support AVX-512 instructions, or there was an issue with how these instructions were utilized.

Flags for optimization

- **-O3**: Enables all the optimizations that the compiler offers, excluding those that increase compilation time substantially.
- **-funroll-loops**
 - Tells the compiler to unroll loops where it deems beneficial for performance
 - Reduces the overhead of loop control but increases the size of the binary.
- **-fomit-frame-pointer**
 - Omits the frame pointer for a slight performance benefit in some cases.
 - Make debugging harder but can also free up a register for general use in certain architectures.
- **-finline-functions**: Encourages the compiler to inline functions, which can reduce the overhead of function calls but might increase the size of the binary.
- **-fopt-info-vec-all**: Provides detailed vectorization optimization reports from the compiler, showing which loops have been vectorized.