

COS 433: Cryptography

Announcements:

- Problem Set 2 due October 7th.

Today: Authentication and CCA-security

What if




pretends to be



?


Secret-Key Encryption



We know: this scheme is CPA-secure if F is a PRF family.


Is this secure enough to use in real life?

Man in the Middle (MITM) Attacks




Is this secure enough to use in real life?

Man in the Middle (MITM) Attacks




Is this secure enough to use in real life?

Man in the Middle (MITM) Attacks




Man in the Middle (MITM) Attacks




- **Problem:** how does  know that he is receiving a message from  ?
- We need a way to enforce **integrity** of the ciphertexts.

Man in the Middle (MITM) Attacks



Philosophical question: is this scheme insecure?


Man in the Middle (MITM) Attacks



- **Answer #1:** No! It's CPA-secure! Integrity is an issue orthogonal to message privacy, and we shouldn't conflate them.
- **Answer #2:** Yes! **There is a way to view this as breaking a form of secrecy!**

Step 1: treat integrity as a standalone problem

Message Authentication Codes (MACs)




Definition: A **message authentication code (MAC)** scheme with message length $n = n(\lambda)$ consists of efficient algorithms **Sign**, **Verify**. It must satisfy the following properties.

- **Correctness:** for all k, m , $\text{Verify}(k, m, \text{Sign}(k, m)) = 1$ with probability 1.
- **Unforgeability:** “an efficient MITM should not be able to send a fake message”

???

Message Authentication Codes (MACs)




Definition: A **message authentication code (MAC)** scheme with message length $n = n(\lambda)$ consists of efficient algorithms **Sign**, **Verify**. It must satisfy the following properties.

- **Correctness:** for all k, m , $\text{Verify}(k, m, \text{Sign}(k, m)) = 1$ with probability 1.
- **Unforgeability (attempt):** for all efficient $A(m, \sigma) \rightarrow (m', \sigma')$ and all $m_0 \neq m_1$:

$$\Pr[A(m_0, \text{Sign}(k, m_0)) = (m_1, \sigma_1) : \text{Verify}(k, m_1, \sigma_1) = 1] = \text{negl}(\lambda)$$

Message Authentication Codes (MACs)




Definition: A **message authentication code (MAC)** scheme with message length $n = n(\lambda)$ consists of efficient algorithms Sign , Verify . It must satisfy the following properties.

- **Correctness:** for all k, m , $\text{Verify}(k, m, \text{Sign}(k, m)) = 1$ with probability 1.
- **Unforgeability (attempt):** for all efficient $A(m, \sigma) \rightarrow (m', \sigma')$ and all $m_0 \neq m_1$:

$$\Pr[A(m_0, \text{Sign}(k, m_0)) = (m_1, \sigma_1) : \text{Verify}(k, m_1, \sigma_1) = 1] = \text{negl}(\lambda)$$


Defining Security for MACs



Attack Model:

-  can intercept messages (and prevent their delivery).
-  wants to trick  into accepting a message that  did not send.


Defining Security for MACs



Win if:

- $\text{Verify}(k, m^*, \sigma^*) = 1$, and
- m^* was not queried.

Message Authentication Codes (MACs)



Definition: A **message authentication code (MAC)** scheme with message length $n = n(\lambda)$ consists of efficient algorithms **Sign**, **Verify**. It must satisfy the following properties.


- **Correctness:** for all k, m , $\text{Verify}(k, m, \text{Sign}(k, m)) = 1$ with probability 1.
- **Unforgeability:** for all efficient oracle adversaries $A^{\text{Sign}(\textcolor{red}{k}, \cdot)}$, we have:

$$\Pr[A^{\text{Sign}(\textcolor{red}{k}, \cdot)}(1^\lambda) \rightarrow (m^*, \sigma^*): m^* \text{ was not queried and } \text{Verify}(\textcolor{red}{k}, m^*, \sigma^*) = 1] = \text{negl}(\lambda)]$$

How do we build MACs?


Relationships between Cryptographic Primitives

Theorem: the following are **existentially equivalent** (we won't prove this in full)



Constructing MACs

Theorem: If PRFs exist, then MACs exist.



Constructing MACs

Theorem: If PRFs exist, then MACs exist.

Proof: Let $F(\cdot, \cdot)$ denote a PRF family with output length λ . Then, define:


- $\text{Sign}(k, m) = F_k(m)$
- $\text{Verify}(k, m, \sigma) = 1$ if $F_k(m) = \sigma$

Notes:

- Requires a PRF with long input length (**cannot** sign bit-by-bit).
- There are **more efficient/practical** constructions

Security Proof

$\text{Sign}(k, \cdot)$





(m^*, σ^*)

Win if:

- $\text{Verify}(k, m^*, \sigma^*) = 1$, and
- m^* was not queried.

Security Proof



(m^*, σ^*)


Want to show:

Win if:

$$\Pr[\text{Win}] = \text{negl}$$

- $\text{Verify}(k, m^*, \sigma^*) = 1$, and
- m^* was not queried.

Security Proof



(m^*, σ^*)

By PRF security, suffices to show:

$$\Pr[\text{Win}] = \text{negl}$$

Win if:

But if $F(m^*)$ was not queried, then $F(m^*)$ is uniformly random and independent of what Adversary has seen!

$$\rightarrow \Pr[\text{Win}] = 2^{-\lambda}$$



- $\text{Verify}(k, m^*, \sigma^*) = 1$, and
- m^* was not queried.

Step 2: Chosen Ciphertext Security for Encryption


CPA Security

Challenger/Honest Party



k

$b \leftarrow \{0,1\}$





Adversary



b'

Win if $b' = b$




For all polynomial-time



$$\Pr[\text{Win}] \leq \frac{1}{2} + \text{negl}(\lambda)$$


Man in the Middle Attacks



What do MITM attacks have to do with **secrecy**?

Strengthen CPA-security to protect against MITM?


Man in the Middle Attacks



Idea:  is influencing the world by sending ct' to Bob and observing how he behaves.

What happens depends on the value of $\text{Dec}(k, ct')$.

Man in the Middle Attacks




Idea:  is influencing the world by sending ct' to Bob and observing how he behaves.

Extremely cautious model: what if we just give  the value $\text{Dec}(k, ct')$?

Chosen Ciphertext Attack (CCA) Security

Challenger



k



Adversary



$b \leftarrow \{0,1\}$



For all polynomial-time



$$\Pr[\text{Win}] \leq \frac{1}{2} + \text{negl}(\lambda)$$

Chosen Ciphertext Attack (CCA) Security

- Adversary has access to two oracles: Encryption and Decryption
- Adversary eventually submits (m_0, m_1) and gets back $ct^* = \text{Enc}(m_b)$
- Afterwards, can still make queries, but cannot ask for a decryption of ct^*
- Goal: guess b

Claim: if SKE is CCA-secure, then it is **not subject to MITM attacks!**

- CCA-security is extremely powerful, ruling out many other kinds of attacks.

Building CCA-secure encryption

Constructing CCA-Secure SKE

Theorem: If PRFs exist, then CCA-secure encryption exists!

Proof: Encrypt and then **Authenticate** (Sign)

- $\text{Enc}_{\text{CCA}}((k_1, k_2), m)$:
 - Compute $\text{ct} = \text{Enc}_{\text{CPA}}(k_1, m)$
 - Output $\text{ct}_{\text{CCA}} = (\text{ct}, \text{Sign}(k_2, \text{ct}))$
- $\text{Dec}_{\text{CCA}}((k_1, k_2), \text{ct}, \sigma)$:
 - If $\text{Verify}(k_2, \text{ct}, \sigma) = 0$, abort.
 - Output $\text{Dec}_{\text{CPA}}(k_1, \text{ct})$

Proof of Security (sketch)

Challenger



k_1, k_2



Adversary



$b \leftarrow \{0,1\}$



Win if $b' = b$
AND ct^* not queried

Idea: want to say that the decryption queries are “useless” to



Proof of Security (sketch)

Challenger


k_1, k_2



Adversary



$b \leftarrow \{0,1\}$




Win if $b' = b$
AND ct^* not queried

Either:  asked for a decryption that he got from , or he broke the MAC!

Proof of Security (sketch)

Challenger


k_1, k_2





Adversary



$b \leftarrow \{0,1\}$




b'




So: If MAC is secure,  could be used to break Enc_{CPA}

Recap of class so far

Computationally Secure Cryptography



Computationally Secure Cryptography




Next two days

- More candidate constructions of cryptography?
- Should we really **believe that PRGs exist**?
- How can we establish computational indistinguishability **without assuming it**?

Computationally Secure Cryptography

These theorems say:

If $X \approx_c Y$
then $X' \approx_c Y'$



Computationally Secure Cryptography

These theorems say:

If $X \approx_c Y$
then $X' \approx_c Y'$

PRGs



Pseudorandom
Functions (PRFs)



Message Authentication
Codes (MACs)



CCA)

Block Ciphers