


COS 433: Cryptography

Reminder:

- Problem Set 1 due 9/23 on Gradescope.


Pseudorandom Generators



Definition: An **efficiently computable** function family $G = \{G^{(\lambda)}: \{0,1\}^\lambda \rightarrow \{0,1\}^{n(\lambda)}\}_\lambda$ is a **pseudorandom generator (PRG)** if it satisfies two additional properties:


- Stretch: $n(\lambda) > \lambda$ for all λ
- Pseudorandomness: $G(U_\lambda) \approx_c U_n$ (uniform n bit string)

Encryption from PRGs



Theorem: if G is a PRG, then this is a secure one-time encryption scheme!


PRG Length Extension



Theorem: 1 bit of “stretch” is enough!

If $G: \{0,1\}^\lambda \rightarrow \{0,1\}^{\lambda+1}$ is a PRG, then for any $n(\lambda) = \lambda^c$, there exists $G': \{0,1\}^\lambda \rightarrow \{0,1\}^{n(\lambda)}$

PRG Length Extension




Claim: $G'(s) \approx_c r$

Proof: Define the following distributions

$$X_i^{(\lambda)} = U_i \times G'_i(U_\lambda)$$

PRG Length Extension




Claim: $G'(s) \approx_c r$

Proof: Define the distributions $X_i^{(\lambda)} = U_i \times G'_i(U_\lambda)$. Then, $\exists i$ such that


$$\left| \mathbf{E} \left[D \left(X_i^{(\lambda)} \right) \right] - \mathbf{E} \left[D \left(X_{i-1}^{(\lambda)} \right) \right] \right| \geq \frac{1}{n(\lambda)} \cdot \left| \mathbf{E}[D(G'(s))] - \mathbf{E}[D(r)] \right|$$

PRG Length Extension




$$X_{i-1}^{(\lambda)} = U_{i-1} \times G'_{i-1}(U_\lambda)$$

PRG Length Extension



$$X_i^{(\lambda)} = U_i \times G'_i(U_\lambda)$$

PRG Length Extension




Proof: If G' is insecure, we will show that G is broken.

Define:

$$D_i^{(\lambda)}(x) = D(r_1, \dots, r_{i-1}, x_{\lambda+1}, G'_i(x_{1:\lambda}))$$

$$\left| \mathbf{E} \left[D_i^{(\lambda)}(r_i, s_i) \right] - \mathbf{E} \left[D_i^{(\lambda)}(G(s_{i-1})) \right] \right| = \left| \mathbf{E} \left[D \left(X_i^{(\lambda)} \right) \right] - \mathbf{E} \left[D \left(X_{i-1}^{(\lambda)} \right) \right] \right|$$

PRG Length Extension




Proof: If G' is insecure, we will show that G is broken.

Define:

$$D_i^{(\lambda)}(x) = D(r_1, \dots, r_{i-1}, x_{\lambda+1}, G'_i(x_{1:\lambda}))$$

$$\left| \mathbf{E} \left[D_i^{(\lambda)}(r_i, s_i) \right] - \mathbf{E} \left[D_i^{(\lambda)}(G(s_{i-1})) \right] \right| \geq \frac{1}{n(\lambda)} \cdot |\mathbf{E}[D(G'(s))] - \mathbf{E}[D(r)]|$$

Pseudorandom Generators




Theorem: 1 bit of “stretch” is enough!

If $G: \{0,1\}^\lambda \rightarrow \{0,1\}^{\lambda+1}$ is a PRG, then for any $n(\lambda) = \lambda^c$, there exists $G': \{0,1\}^\lambda \rightarrow \{0,1\}^{n(\lambda)}$

Relationships between Cryptographic Primitives


Theorem: the following are **existentially equivalent** (we won't prove this)



To build one-time SKE (for long messages), it is **necessary and sufficient** to construct a PRG!

Relationships between Cryptographic Primitives

Theorem: the following are **existentially equivalent** (we won't prove this in full)



“The PRG Conjecture”

Main Conjecture: PRGs with one bit of stretch exist

If true, we have secret-key cryptography!

“The PRG Conjecture”

Main Conjecture: PRGs with one bit of stretch exist

Evidence for conjecture:

- 1) **Equivalent** to many other conjectures (including weaker looking ones)
- 2) “**Generic attack**” that treats G as a black box shouldn’t be expected to work (HW1)
- 3) **Concrete candidates!** Have withstood attacks for many decades (or centuries...)
 - from practice (AES)
 - from theory (next slide)


Let's build a PRG!

The Subset Sum Generator

s_1	s_2							s_λ
-------	-------	--	--	--	--	--	--	-------------


The Subset Sum Generator

A subset sum generator is described by a collection of sets $T_1, \dots, \mathbf{T}_i, \dots, T_{n(\lambda)} \subset [\lambda]$




The Subset Sum Generator

Very commonly used in practice... but not for cryptography!



The Subset Sum Generator

$$G_A(\boxed{s}) = sA \pmod{2}$$



The Subset Sum Generator

$$G_A(\boxed{s}) = sA \pmod{2}$$

Poly-time attack:

- Given $y \in \{0,1\}^n$, check if $sA \equiv y \pmod{2}$ has a solution (“column reduction”)
- In the pseudorandom case, there will always be a solution!
- But for a uniformly random r , $sA \equiv r \pmod{2}$ is solvable w.p. at most $2^{\lambda-n}$

Takeaway: need some non-linearity in your PRG


The LPN Generator

What if we take the subset sum generator **but flip some of the output bits?**

$G(A, s, j_1, \dots, j_\lambda)$:

- Compute $y = sA \pmod{2}$
- For all j ,
 - If $j = j_i$ for some i , set $r_j = y_j \oplus 1$
 - Else set $r_j = y_j$
 - Output (A, r)

“Random sparse error”

$$r = sA + e \pmod{2}$$


The LPN Generator

What if we take the subset sum generator **but flip some of the output bits?**

$G(A, s, j_1, \dots, j_\lambda)$:

- Compute $y = sA \pmod{2}$
- For all j ,
 - If $j = j_i$ for some i , set $r_j = y_j \oplus 1$
 - Else set $r_j = y_j$
 - Output (A, r)

Output length: $\lambda \cdot n + n$

Input length: $\lambda \cdot n + \lambda + \lambda \cdot \log(n)$

Set $n = \lambda^2$ and we have stretch!

$$r = sA + e \pmod{2}$$

The LPN Generator

What if we take the subset sum generator **but flip some of the output bits?**

$G(A, s, j_1, \dots, j_\lambda)$:

- Compute $y = sA \pmod{2}$
- For all j ,
 - If $j = j_i$ for some i , set $r_j = y_j \oplus 1$
 - Else set $r_j = y_j$
 - Output (A, r)
- Attack from earlier doesn't work!
 - λ of the equations are wrong, and we don't know which!
- Best known attack: $2^{\lambda / \log(\lambda)}$ time
- Thm (non-trivial): Breaking G is as hard as solving for s !

$$r = sA + e \pmod{2}$$

The MQ Generator

What if we take subset sums but add in quadratic terms?

$$G(A, B_1, \dots B_n, s^\top) = (A, B_1, \dots B_n, s^\top A + (s^\top B_1 s, s^\top B_2 s, \dots s^\top B_n s))$$

- General quadratic equations modulo 2 are NP-hard to solve!
- ...but we don't know as much about random quadratic equations
- Unlike LPN, we must restrict $n < \lambda^2$ or else there is an attack! (HW1)

Plan for next week

