



1 -- Retrieve the total number of orders placed.

2

3

4 • `select count(order_id) as total_orders from orders`

Result Grid Filter Rows: Export: Wrap Cell Content:

	total_orders
▶	21350





Don't Limit

```
1  -- Calculate the total revenue generated from pizza sales.
2
3 • SELECT
4      ROUND(SUM((order_details.quantity * pizzas.price)),
5              2) AS total_sales
6  FROM
7      order_details
8      JOIN
9      pizzas ON order_details.pizza_id = pizzas.pizza_id;
```

Result Grid Filter Rows: Export: Wrap Cell Content: ☐

	total_sales
▶	817860.05



```
1  -- Identify the highest-priced pizza.
2
3 • SELECT
4     pizza_types.name, pizzas.price
5 FROM
6     pizza_types
7     JOIN
8     pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
9 ORDER BY pizzas.price DESC
10 LIMIT 1;
```

Result Grid   Filter Rows: Export:  Wrap Cell Content: 

	name	price
▶	The Greek Pizza	35.95



```
1  -- Identify the most common pizza size ordered.
2
3  • SELECT
4      pizzas.size,
5      COUNT(order_details.order_details_id) AS order_count
6  FROM
7      pizzas
8      JOIN
9      order_details ON pizzas.pizza_id = order_details.pizza_id
10 GROUP BY pizzas.size
11 ORDER BY order_count DESC;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: |

	size	order_count
▶	L	18526
	M	15385
	S	14137
	XL	544
	XXL	28




```
1  -- List the top 5 most ordered pizza types
2  -- along with their quantities.
3
4  • SELECT
5      pizza_types.name, sum(order_details.quantity) AS quantity
6  FROM
7      pizza_types
8      JOIN
9      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
10     JOIN
11     order_details ON order_details.pizza_id = pizzas.pizza_id
12 GROUP BY pizza_types.name
13 ORDER BY quantity DESC
14 LIMIT 5;
```

Result Grid Filter Rows: | Export: | Wrap Cell Content:

	name	quantity
▶	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371





```
1  -- Join the necessary tables to
2  -- find the total quantity of each pizza category ordered.
3
4  • SELECT
5      pizza_types.category,
6      SUM(order_details.quantity) AS quantity
7  FROM
8      pizza_types
9      JOIN
10     pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
11     JOIN
12     order_details ON order_details.pizza_id = pizzas.pizza_id
13 GROUP BY pizza_types.category
14 ORDER BY quantity DESC;
```

Result Grid Filter Rows: | Export: | Wrap Cell Content:

	category	quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050





```
1  -- Determine the distribution of orders by hour of the day.
2
3  • SELECT
4      HOUR(order_time) AS Hour, COUNT(order_id) AS Order_Count
5  FROM
6      orders
7  GROUP BY HOUR(order_time);
```

Result Grid Filter Rows: _____ Export: Wrap Cell Content:

	Hour	Order_Count
▶	11	1231
	12	2520
	13	2455
	14	1472
	15	1468
	16	1920
	17	2136

Result 1 x



```
1  -- Join relevant tables to find the
2  -- category-wise distribution of pizzas.
3
4  • select category , count(name) from pizza_types
5  group by category |
```

Result Grid Filter Rows: Export: Wrap Cell Content:

	category	count(name)
▶	Chicken	6
	Classic	8
	Supreme	9
	Veggie	9

Result
GridForm
Editor



```
1  -- Group the orders by date and calculate
2  -- the average number of pizzas ordered per day.
3
4  • SELECT
5      ROUND(AVG(quantity), 0) AS avg_pizzas_orders_per_day
6  FROM
7      (SELECT
8          orders.order_date, SUM(order_details.quantity) AS quantity
9      FROM
10         orders
11        JOIN order_details ON orders.order_id = order_details.order_id
12       GROUP BY orders.order_date) AS order_quantity;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

avg_pizzas_orders_per_day
138





```
1  -- Determine the top 3 most ordered pizza types based on revenue.
2
3  • SELECT
4      pizza_types.name,
5      SUM(order_details.quantity * pizzas.price) AS revenue
6  FROM
7      pizza_types
8      JOIN
9      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
10     JOIN
11     order_details ON order_details.pizza_id = pizzas.pizza_id
12 GROUP BY pizza_types.name
13 ORDER BY revenue DESC
14 LIMIT 3;
```

Result Grid Filter Rows: | Export: | Wrap Cell Content:

	name	revenue
▶	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5





```

1  -- Calculate the percentage contribution of each
2  -- pizza type to total revenue.
3
4  • SELECT pizza_types.category,
5      round(SUM(order_details.quantity * pizzas.price)/
6      (select round(SUM(order_details.quantity * pizzas.price), 2) AS total_sales
7      from order_details
8      join
9      pizzas on order_details.pizza_id = pizzas.pizza_id)*100 ,2) as revenue
10     from
11     pizza_types
12         JOIN
13     pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
14         JOIN
15     order_details ON order_details.pizza_id = pizzas.pizza_id
16     group by pizza_types.category order by revenue desc ; |
    
```

Result Grid | Filter Rows: | Export: Wrap Cell Content:

	category	revenue
▶	Classic	26.91
	Supreme	25.46
	Chicken	23.96
	Veggie	23.68



Result Grid

Form Editor



```


1  -- Analyze the cumulative revenue generated over time.
2
3  • select order_date,
4      sum(revenue) over (order by order_date) as cum_revenue
5      from
6      (select orders.order_date,
7         sum(order_details.quantity * pizzas.price) as revenue
8         from order_details join pizzas on
9         order_details.pizza_id = pizzas.pizza_id
10        join orders on orders.order_id = order_details.order_id
11        group by orders.order_date)as sales;

```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: |

	order_date	cum_revenue
▶	2015-01-01	2713.85000000000004
	2015-01-02	5445.75
	2015-01-03	8108.15
	2015-01-04	9863.6
	2015-01-05	11929.55
	2015-01-06	14358.5
	2015-01-07	16560.7





```

1  -- Determine the top 3 most ordered pizza types
2  -- based on revenue for each pizza category.
3
4  • select name ,revenue from
5  (select category,name ,revenue,rank()
6   over(partition by category order by revenue desc )as rn from
7  (SELECT
8      pizza_types.category,
9      pizza_types.name,
10     SUM((order_details.quantity) * pizzas.price) AS revenue
11  FROM
12     pizza_types
13     JOIN
14     pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
15     JOIN
16     order_details ON order_details.pizza_id = pizzas.pizza_id
17  GROUP BY pizza_types.category , pizza_types.name) as a)
18  as b where rn<= 3;

```

Result Grid Filter Rows: Export: Wrap Cell Content: ☐

name	revenue
The Spicy Italian Pizza	34831.25
The Italian Supreme Pizza	33476.75
The Sicilian Pizza	30940.5
The Four Cheese Pizza	32265.70000000065
The Mexicana Pizza	26780.75
The Five Cheese Pizza	26066.5

