

Work locally with Git: Open your working directory in Postman to keep your API artifacts in sync with your codebase.

GET http://localhost:8989/api/products

GET

Body

```
1 [
2   {
3     "name": "Laptop",
4     "description": "Dell XPS 13",
5     "price": 1200.0,
6     "quantity": 10,
7     "id": 1
8   },
9   {
10    "name": "Smartphone",
11    "description": "Samsung Galaxy S21",
12    "price": 999.0,
13    "quantity": 20,
14    "id": 2
15  },
16  {
17    "name": "Tablet",
18    "description": "Apple iPad Pro",
19    "price": 799.0,
20    "quantity": 15,
21    "id": 3
22  }
23 ]
```

GET http://localhost:8989/api/products/1

GET

Body

```
1 {
2   "name": "Laptop",
3   "description": "Dell XPS 13",
4   "price": 1200.0,
5   "quantity": 10,
6   "id": 1
7 }
```

GET http://localhost:8989/api/products/2

GET

Body

```
1 {
2   "name": "Smartphone",
3   "description": "Samsung Galaxy S21",
4   "price": 999.0,
5   "quantity": 20,
6   "id": 2
7 }
```

GET http://localhost:8989/api/products/3

GET

Body

```
1 {
2   "name": "Tablet",
3   "description": "Apple iPad Pro",
4   "price": 799.0,
5   "quantity": 15,
6   "id": 3
7 }
```

HTTP client interface showing a POST request to `http://localhost:8989/api/products`. The request body is a JSON object: `{ "name": "Smartphone", "description": "Samsung Galaxy S21", "price": 999.0, "quantity": 20 }`. The response is a 200 OK status with a response time of 292 ms and a body size of 255 B. The response body is a JSON object: `{ "name": "Smartphone", "description": "Samsung Galaxy S21", "price": 999.0, "quantity": 20, "id": 4 }`.

HTTP client interface showing a PUT request to `http://localhost:8989/api/products/1`. The request body is a JSON object: `{ "name": "Laptop", "description": "Dell XPS 13 - Updated", "price": 1100.0, "quantity": 8 }`. The response is a 200 OK status with a response time of 78 ms and a body size of 254 B. The response body is a JSON object: `{ "name": "Laptop", "description": "Dell XPS 13 - Updated", "price": 1100.0, "quantity": 8, "id": 1 }`.

SQL File 4* interface showing SQL commands and the resulting data grid.

SQL Commands:

```
1 • CREATE DATABASE kluh;  
2 • USE kluh;  
3 • select * from products  
4 • insert INTO products (name, description, price, quantity)
```

Result Grid:

	id	description	name	price	quantity
▶	1	Dell XPS 13 - Updated	Laptop	1100	8
	2	Samsung Galaxy S21	Smartphone	999	20
	3	Apple iPad Pro	Tablet	799	15
	4	Samsung Galaxy S21	Smartphone	999	20
•	NULL	NULL	NULL	NULL	NULL

SQL File 4*

```
1 • CREATE DATABASE k1uh;  
2 • USE k1uh;  
3 • select * from products  
4 ✖ insert INTO products (name, description, price, quantity) VALUES ('Laptop', 'Dell
```

Result Grid

	id	description	name	price	quantity
▶	1	Dell XPS 13 - Updated	Laptop	1100	8
	2	Samsung Galaxy S21	Smartphone	999	20
	3	Apple iPad Pro	Tablet	799	15
*		NULL	NULL	NULL	NULL

Result Grid
Form Editor

http://localhost:8989/api/products/4

DELETE http://localhost:8989/api/products/4 Send

Docs Params Authorization Headers 9 Body Scripts Settings Cookies

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON Schema Beautify

1

Body Cookies Headers 3 Test Results 204 No Content • 55 ms • 104 B

Raw Preview Visualize

1