

Community Detection in Multi layer Networks

16CS60R58 Prishni Rateria
Under guidance of
Dr. Bivas Mitra


Outline:

- ***Introduction***
 - Background
- Related Work
- Motivation
- Objective
- Multilayer Modularity
- Community Detection Algorithm
- Evaluation
- Summary and future work

Introduction

- Background

Communities



Community Detection: partitioning the networks into groups of nodes.

Modularity: Reflects the concentration of edges within modules compared with random distribution of links between all nodes regardless of modules

$$mQ = \frac{1}{2m} \sum_{ij} [A_{ij} - \frac{k_i k_j}{2m}] \delta(c_i, c_j)$$

Community detection in homogeneous network has been studied extensively.

Figure1. Homogeneous network

Multi-layer network




Figure2. Multi-layer network

- Comprises of multiple independent networks.
- Functionality of edges and nodes in different layer is different

Outline:

- Introduction
- ***Related Work***
- Motivation
- Objective
- Community Detection Algorithm
- Evaluation
- Summary and future work



Related Work

Newman, Louvain , 2006	<ul style="list-style-type: none">• Used Modularity as the optimization function• Detects communities in a single-layer network
Yu-Ru Lin, MetaFac, 2009	<ul style="list-style-type: none">• Used matrix factorization to detect communities.
Kuncheva, CompMod, 2015	<ul style="list-style-type: none">• Used the concept of random walk.• Works on multiplex networks.
Pramanik, DSAA , 2017	<ul style="list-style-type: none">• Developed modularity index for multi-layer communities.• Used single layer community detection algorithm.

Outline:

- Introduction
- Related Work
- **Motivation**
- Objective
- Community Detection Algorithm
- Evaluation
- Summary and future work



Motivation

- Can single layer community detection algorithm be used in multi-layer network?



Motivation

- Can single layer community detection algorithm be used in multi-layer network?



Motivation

- Can single layer community detection algorithm be used in multi-layer network?
- Because,
 - Links in multi-layer networks have different meaning.
 - Nodes may represent different entities

NO




Figure3. Cross layer edges in multilayer networks have a different meaning

Motivation




Figure4. Single layer community detection fails in multi-layer network

Outline:

- Introduction
- Related Work
- Motivation
- **Objective**
- Community Detection Algorithm
- Evaluation
- Summary and future work



Objective

Detecting communities in a multi-layer network comprising:

- Single type of nodes
- Multiple type of nodes




Figure5. Multi-layer community structure

Outline:

- Introduction
- Related Work
- Motivation
- Objective
- **Community Detection Algorithm**
 - Louvain
 - Mixmod
- Evaluation
- Summary and future work



Methodology




Figure6. Abopted methodology



Louvain Algorithm

1. Assign a different community to each node.
2. For each node i
 - a. For each neighbour j of i , consider removing i from its community and placing in j 's community.
 - b. Greedily chose to place i into community of neighbor that leads to highest modularity gain
 - c. If there is no positive gain , than i stays in its own community.
3. Repeat until no improvement can be done

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Louvain Algorithm:




Figure7. Louvain algorithm's steps

Outline:

- Introduction
- Related Work
- Motivation
- Objective
- ***Community Detection Algorithm***
 - **Louvain**
 - **Mixmod**
- Evaluation
- Summary and future work



Algorithm: MixMod

While merging nodes and constructing new network.

- If the community has multiple types of node, we form multiple nodes for each type.
- Keep the information of them being in one community




Figure8. MixMod algorithm steps



Algorithm: MixMod



Nodes of layer 1



Nodes of layer 2

All nodes of same colour belong to same community




Figure8. MixMod algorithm steps



Algorithm: MixMod



Nodes of layer 1



Nodes of layer 2

All nodes of same colour belong to same community





Figure8. MixMod algorithm steps

Algorithm: MixMod




- Nodes of layer 1
- Nodes of layer 2

All nodes of same colour belong to same community

Figure8. MixMod algorithm steps

Algorithm: MixMod



- Nodes of layer 1
- Nodes of layer 2

All nodes of same colour belong to same community

Figure8. MixMod algorithm steps

Algorithm: MixMod

- Nodes of layer 1
 - Nodes of layer 2
- All nodes of same colour belong to same community




Figure8. MixMod algorithm steps


Outline:

- Introduction
- Related Work
- Motivation
- Objective
- Community Detection Algorithm
- ***Evaluation***
- Summary and future work

Dataset

Layer1

Dark edges are in-community edges, light edges are cross-community edges



Layer2

Parameters:

- Alpha - denotes the fraction of cross layer communities
- D - density of coupling edges
- P- fraction of coupling edges inside community



Evaluation:





Figure9. Modularity plot for two different values of alpha (0.5,0.9) and varying P



Evaluation:

Gap between the modularity of detected community and ground truth community





Figure10. Modularity plot for two different values of alpha (0.5,0.8) and varying P

Outline:

- Introduction
- Related Work
- Motivation
- Objective
- Community Detection Algorithm
- Evaluation
- ***Summary and future work***



Summary and Future work:

The MixMod algorithm preserves the multi-layer structure of the network throughout.

The algorithm when plugged with Q_M (MixMod Q_M) performs better than Louvain Q_M

Future Work:

- Analysing the modularity index Q_M .
- Reduce the gap further between the detected communities modularity and the ground truth modularity.



References

1. Jianglong Song, Shihuan Tang, Xi Liu, Yibo Gao, Hongjun Yang, and Peng Lu. A modularity-based method reveals mixed modules from chemical-gene hetero-geneous network. PLoS one, 10(4):e0125585, 2015
2. P. J. Mucha, T. Richardson, K. Macon, M. A. Porter, and J.-P. Onnela, “Community structure in time-dependent, multiscale, and multiplex networks,” science, vol. 328, no. 5980, pp. 876–878, 2010.
3. Z. Kuncheva and G. Montana, “Community detection in multiplex networks using locally adaptive random walks,” in Proceedings of ASONAM’15. ACM, 2015.
4. M. Berlingerio, F. Pinelli, and F. Calabrese, “Abacus: frequent pattern mining-based community discovery in multidimensional networks,” DMKD, vol. 27, no. 3, pp. 294–320, 2013.
5. Y.-R. Lin, J. Sun, P. Castro, R. Konuru, H. Sundaram, and A. Kelliher, “Metafac: community discovery via relational hypergraph factorization”, SIGKDD’09, pp. 527–536.



Questions?

Thank You





Algorithm: MixMod






Figure10. Input network

Algorithm: MixMod



Algorithm: MixMod





Limitations of DSAA

- The method uses Louvain algorithm for community detection.
- However, Louvain is a single layer community detection algorithm.

Louvain algorithm merges nodes and modifies the network structure, So, if we apply it on multi-layer network:

1. We would lose the layer information after first the merge.
2. The network no more remains multi-layered.