

Official shop test result for Main Engine				Hull No.	N208	Weather	Cloudy
				Engine No.	AA2728	Measuring Time	11:00
				Eng. Type	6S60MC-C7	Test Date	Sep. 4th, 2009
Data sheet of 75% Load test				Owner	EML	Engineer	C. Y. Jang
				Class	LR	Operator	S. S. KIM

* Room Temperature : 27.4 °C				* Atmospheric Pressure : 1015 mbar			
------------------------------	--	--	--	------------------------------------	--	--	--

Engine Speed		Water Brake		Brake Power		Indicated Power		Mech.Efficiency		NOTCH	
95.4 rpm		1018.0 kNm		10170 kNm		10860 kW		93.65 %		7.7	

System		Main L.O		P.C.O		Exh. V/V		Fuel Oil		Cooling F.W	
In	Press. (kg/m ²)	2.08						7.90		4.00	
	Temp. (°C)	45.0						37.0		72.0	

Cyl. NO.		Avg.	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Pmax.	bar	134.5	134.0	134.0	134.0	135.0	135.0	135.0								
Pcomp.	bar	108.7	108.0	109.0	108.0	109.0	109.0	109.0								
Pi	bar	16.77	16.63	16.73	16.78	16.86	16.87	16.78								
F.O Pump	PΘ	72.5	72.0	72.0	73.0	72.0	73.0	73.0	BLANK							
	VIT	2.6	2.5	2.6	2.6	2.5	2.6	2.6								
Exh.Gas Out.	°C	342	340	330	345	335	350	350								
C.F.W Out	°C	76.3	77.0	77.0	76.0	76.0	76.0	76.0								
Cam L.O Out.	°C	47.0	47.0													
P.C.O Out	°C	56.3	56.0	58.0	56.0	56.0	56.0	56.0								

Air Cooler						Scavenging Air						
NO.		1	2	3	4	Avg.	Pressure			Temperature		
Bef. Cooler Press	mmHg	1570	BLAN			1570	2.09 kg/cm ²			36.0 °C		
Press. Drop	mmAq	190				190	Air Receiver Pressure			1540 mmHg		
Air In.	°C	156				156	Exhaust Manifold Pressure			1.72 kg/cm ²		
Air Out.	°C	34				34	Specific Fuel Oil Consumption					
Fresh Water In.	°C	30				30	Meas.(kg/h)		Meas.(g/kWh)		Correct(g/kWh)	
Fresh Water Out.	°C	39				39	1809.02		177.88		173.62	

TurboCharger												
Turbo Charger	Speed	Blower Inlet			Before Turbine		After Turbine		L.O. (°C, kg/cm ²)			F.W Temp
	rpm	°C		mmAq	°C	mmHg	°C	mmAq	IN	OUT	Press.	°C
NO. 1	10295	35.0	26.0	17	406	1250	258	100	44	65	1.65	-
NO. 2					BLANK							
NO. 3												
NO. 4												
Avg.	10295	30.5		17	406	1250	258	100	44	65	1.65	-

* Pressure VIT : 2.10 kg/cm ²	* Governor Position : 65.0	* AVM : 0.64mm	* Thrust Pad : 48.0 °C
--	----------------------------	----------------	------------------------

* Note : The Fuel Oil Consumption is corrected to Lower Calorific Value 10200 kcal/kg, and ISO condition
--