

Rajalakshmi Engineering College

Name: Prithika S
Email: 240701400@rajalakshmi.edu.in
Roll no: 240701400
Phone: 9790212894
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and $table_size$ — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert.

The third line contains an integer q — the number of queries.

The fourth line contains q space-separated integers — the roll numbers to search for.

Output Format

The output print q lines — for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>

#define MAX 100

// You are using GCC
void initializeTable(int table[], int size) {
    for (int i = 0; i < size; i++) {
        table[i] = -1;
    }
}

int linearProbe(int table[], int size, int num) {
    int index = num % size;
    while (table[index] != -1) {
        index = (index + 1) % size;
```

```
    }  
    table[index] = num;  
    return index;  
}
```

```
void insertIntoHashTable(int table[], int size, int arr[], int n) {  
    for (int i = 0; i < n; i++) {  
        linearProbe(table, size, arr[i]);  
    }  
}
```

```
int searchInHashTable(int table[], int size, int num) {  
    int index = num % size;  
    int start = index;  
    while (table[index] != -1) {  
        if (table[index] == num) {  
            return 1; // Found  
        }  
        index = (index + 1) % size;  
        if (index == start) {  
            break; // Checked full table  
        }  
    }  
    return 0; // Not found  
}
```

```
int main() {  
    int n, table_size;  
    scanf("%d %d", &n, &table_size);  
  
    int arr[MAX], table[MAX];  
    for (int i = 0; i < n; i++)  
        scanf("%d", &arr[i]);  
  
    initializeTable(table, table_size);  
    insertIntoHashTable(table, table_size, arr, n);  
  
    int q, x;  
    scanf("%d", &q);  
    for (int i = 0; i < q; i++) {  
        scanf("%d", &x);  
        if (searchInHashTable(table, table_size, x))  
            printf("Value %d: Found\n", x);  
    }  
}
```

```
        else
            printf("Value %d: Not Found\n", x);
    }

    return 0;
}
```

Status : Correct

Marks : 10/10