5 . LAB EXPERIMENTS

TCL Commands - COMMIT, SAVEPOINT, ROLLBACK

```
mysql> start transaction ;
Query OK, 0 rows affected (0.00 sec)

mysql> update students set sname = "vinoth" where sid = 3 ;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> commit ;
Query OK, 0 rows affected (0.24 sec)

mysql> select * from students ;
+-----+--------+------+-----------------+--------+
| sid | sname  | age  | email           | deptid |
+-----+--------+------+-----------------+--------+
|   2 | shree  |   20 | shree@gmail.com |    102 |
|   3 | vinoth |   20 | raja@gmail.com  |    103 |
+-----+--------+------+-----------------+--------+
2 rows in set (0.00 sec)
```

```
mysql> start transaction ;
Query OK, 0 rows affected (0.00 sec)

mysql> update students set sname = "varshaa" where sid = 2 ;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> savepoint s1 ;
Query OK, 0 rows affected (0.00 sec)

mysql> update students set age = 21 where sid = 2 ;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> select * from students ;
+-----+---------+------+-----------------+--------+
| sid | sname   | age  | email           | deptid |
+-----+---------+------+-----------------+--------+
|   2 | varshaa |   21 | shree@gmail.com |    102 |
|   3 | vinoth  |   20 | raja@gmail.com  |    103 |
+-----+---------+------+-----------------+--------+
2 rows in set (0.00 sec)

mysql> rollback ;
Query OK, 0 rows affected (0.14 sec)

mysql> select * from students ;
+-----+--------+------+-----------------+--------+
| sid | sname  | age  | email           | deptid |
+-----+--------+------+-----------------+--------+
|   2 | shree  |   20 | shree@gmail.com |    102 |
|   3 | vinoth |   20 | raja@gmail.com  |    103 |
+-----+--------+------+-----------------+--------+
2 rows in set (0.00 sec)
```