

EXPERIMENT 13:

The screenshot displays the Keil uVision IDE interface for a project named "Exp13.c". The main window shows assembly code for the "STARTUP.A51" file. The code includes a loop labeled "IDATALOOP" and a startup routine. The registers window on the left shows the values of registers r0 through r7, all set to 0x00. The command window at the bottom shows the command "Running with Code Size Limit: 2K" and the load path "C:\Keil_v5\CS1\Examples\HELLO\Objects\Exp13".

Registers Window:

Register	Value
r0	0x00
r1	0x00
r2	0x00
r3	0x00
r4	0x00
r5	0x00
r6	0x00
r7	0x00

Assembly Code:

```
135: IDATALOOP: MOV     @R0,A
136: F6      MOV     @R0,A
137: DJNZ    R0, IDATALOOP
138: D8FD    DJNZ    R0, IDATALOOP (C:0803)
139:
140: STARTUP1:
141: IF IDATALEN < 0
142: MOV     R0, #IDATALEN - 1
143: CLR     A
144: IDATALOOP: MOV     @R0,A
145: DJNZ    R0, IDATALOOP
146:
147: IF XDATALEN < 0
148: MOV     DPTR, #XDATASTART
149: MOV     R7, #LOW (XDATALEN)
150: IF (LOW (XDATALEN)) < 0
151: MOV     R6, # (HIGH (XDATALEN)) + 1
152: ELSE
153: MOV     R6, #HIGH (XDATALEN)
154: ENDIF
155: XDATALOOP: MOVX    @DPTR,A
156: INC     DPTR
157: DJNZ    R7, XDATALOOP
158: DJNZ    R6, XDATALOOP
159:
```

Parallel Port Configuration Windows:

- Parallel Port 0:** Port 0: 7 Bits, 0. Pins: P0: 0xCC, P1: 0xCC, P2: 0xCC.
- Parallel Port 1:** Port 1: 7 Bits, 0. Pins: P1: 0xAB, P2: 0xAB, P3: 0xAB.
- Parallel Port 2:** Port 2: 7 Bits, 0. Pins: P2: 0x01, P3: 0x01, P4: 0x01.

Command Window:

```
Running with Code Size Limit: 2K
Load "C:\Keil_v5\CS1\Examples\HELLO\Objects\Exp13"
ASM ASSIGN BreakDisable BreakEnable BreakKill BreakList BreakSet BreakAccess COVERAGE COVTOFILE
```

Simulation Status:

Simulation t1: 1406.18947950 sec L:141 C:43 CAP NUM SCRL OVR: R/W