

Branch: master ▾

Find file

Copy path

[cs-35l](#) / [assignment7](#) / formatted-patch.txt

prithvikannan Finished assignment7

0b325a9 19 days ago

[1 contributor](#)

Raw Blame History



343 lines (326 sloc) 12.8 KB

```

1  From 46ea25e4e70e3d32f355aaca91efe7f678b17ea3 Mon Sep 17 00:00:00 2001
2  From: Prithvi Kannan <prithvik@lnxsr05.seas.ucla.edu>
3  Date: Fri, 15 Nov 2019 11:04:31 -0800
4  Subject: [PATCH] 2019-11-15 Prithvi Kannan <prithvik@lnxsr05.seas.ucla.edu>
5
6      * quote-3.0-patch.txt: This patches updates character string constanst in .c files to match an update where the quote style
7  ---
8      src/cmp.c | 12 +++++-----
9      src/diff.c | 28 ++++++++-----
10     src/diff3.c | 20 ++++++-----
11     src/dir.c | 2 +-
12     src/sdiff.c | 16 ++++++-----
13     src/util.c | 8 ++++----
14     6 files changed, 43 insertions(+), 43 deletions(-)
15
16     diff --git a/src/cmp.c b/src/cmp.c
17     index 2455dc4..e19f013 100644
18     --- a/src/cmp.c
19     +++ b/src/cmp.c
20     @@ -115,7 +115,7 @@ try_help (char const *reason_msgid, char const *operand)
21         if (reason_msgid)
22             error (0, 0, _(reason_msgid), operand);
23         error (EXIT_TROUBLE, 0,
24             _("Try '%s --help' for more information."), program_name);
25     +    _("Try '%s --help' for more information."), program_name);
26     abort ();
27     }
28
29     @@ -134,7 +134,7 @@ specify_ignore_initial (int f, char **argptr, char delimiter)
30         if (! (e == LONGINT_OK
31             || (e == LONGINT_INVALID_SUFFIX_CHAR && **argptr == delimiter))
32             || TYPE_MAXIMUM (off_t) < val)
33         -    try_help ("invalid --ignore-initial value '%s'", arg);
34     +    try_help ("invalid --ignore-initial value '%s'", arg);
35         if (ignore_initial[f] < val)
36             ignore_initial[f] = val;
37     }
38     @@ -185,7 +185,7 @@ usage (void)
39         _("SKIP values may be followed by the following multiplicative suffixes:\n\
40     kB 1000, K 1024, MB 1,000,000, M 1,048,576,\n\
41     GB 1,000,000,000, G 1,073,741,824, and so on for T, P, E, Z, Y."),
42     -    _("If a FILE is '-' or missing, read standard input."),
43     +    _("If a FILE is '-' or missing, read standard input."),
44     _("Exit status is 0 if inputs are the same, 1 if different, 2 if trouble."));
45     emit_bug_reporting_address ();
46     }
47     @@ -231,7 +231,7 @@ main (int argc, char **argv)
48     {
49         uintmax_t n;
50         if (xstrtoumax (optarg, 0, 0, &n, valid_suffixes) != LONGINT_OK)
51     -    try_help ("invalid --bytes value '%s'", optarg);

```

```

52 +         try_help ("invalid --bytes value '%s'", optarg);
53         if (n < bytes)
54             bytes = n;
55     }
56 @@ -257,7 +257,7 @@ main (int argc, char **argv)
57     }
58
59     if (optind == argc)
60 -     try_help ("missing operand after '%s'", argv[argc - 1]);
61 +     try_help ("missing operand after '%s'", argv[argc - 1]);
62
63     file[0] = argv[optind++];
64     file[1] = optind < argc ? argv[optind++] : "-";
65 @@ -269,7 +269,7 @@ main (int argc, char **argv)
66     }
67
68     if (optind < argc)
69 -     try_help ("extra operand '%s'", argv[optind]);
70 +     try_help ("extra operand '%s'", argv[optind]);
71
72     for (f = 0; f < 2; f++)
73     {
74 diff --git a/src/diff.c b/src/diff.c
75 index cc1b611..256a984 100644
76 --- a/src/diff.c
77 +++ b/src/diff.c
78 @@ -330,7 +330,7 @@ main (int argc, char **argv)
79     {
80         numval = strtoumax (optarg, &numend, 10);
81         if (*numend)
82 -         try_help ("invalid context length '%s'", optarg);
83 +         try_help ("invalid context length '%s'", optarg);
84         if (LIN_MAX < numval)
85             numval = LIN_MAX;
86     }
87 @@ -505,7 +505,7 @@ main (int argc, char **argv)
88     case 'W':
89         numval = strtoumax (optarg, &numend, 10);
90         if (! (0 < numval && numval <= SIZE_MAX) || *numend)
91 -         try_help ("invalid width '%s'", optarg);
92 +         try_help ("invalid width '%s'", optarg);
93         if (width != numval)
94         {
95             if (width)
96 @@ -534,7 +534,7 @@ main (int argc, char **argv)
97     case HORIZON_LINES_OPTION:
98         numval = strtoumax (optarg, &numend, 10);
99         if (*numend)
100 -         try_help ("invalid horizon length '%s'", optarg);
101 +         try_help ("invalid horizon length '%s'", optarg);
102         horizon_lines = MAX (horizon_lines, MIN (numval, LIN_MAX));
103         break;
104
105 @@ -585,7 +585,7 @@ main (int argc, char **argv)
106     case TABSIZE_OPTION:
107         numval = strtoumax (optarg, &numend, 10);
108         if (! (0 < numval && numval <= SIZE_MAX) || *numend)
109 -         try_help ("invalid tabsize '%s'", optarg);
110 +         try_help ("invalid tabsize '%s'", optarg);
111         if (tabsize != numval)
112         {
113             if (tabsize)
114 @@ -744,9 +744,9 @@ main (int argc, char **argv)
115         if (argc - optind != 2)
116         {
117             if (argc - optind < 2)

```

```

118 -         try_help ("missing operand after '%s'", argv[argc - 1]);
119 +         try_help ("missing operand after '%s'", argv[argc - 1]);
120     else
121 -         try_help ("extra operand '%s'", argv[optind + 2]);
122 +         try_help ("extra operand '%s'", argv[optind + 2]);
123     }
124
125     exit_status = compare_files (NULL, argv[optind], argv[optind + 1]);
126 @@ -826,7 +826,7 @@ try_help (char const *reason_msgid, char const *operand)
127 {
128     if (reason_msgid)
129         error (0, 0, _(reason_msgid), operand);
130 - error (EXIT_TROUBLE, 0, _("Try '%s --help' for more information."),
131 + error (EXIT_TROUBLE, 0, _("Try '%s --help' for more information."),
132         program_name);
133     abort ();
134 }
135 @@ -870,11 +870,11 @@ static char const * const option_help_msgid[] = {
136 -W NUM --width=NUM Output at most NUM (default 130) print columns.\n\
137 --left-column Output only the left column of common lines.\n\
138 --suppress-common-lines Do not output common lines."),
139 - N_("-D NAME --ifdef=NAME Output merged file to show `#ifdef NAME' diffs."),
140 + N_("-D NAME --ifdef=NAME Output merged file to show '#ifdef NAME' diffs."),
141     N_("--GTYPE-group-format=GFMT Similar, but format GTYPE input groups with GFMT."),
142     N_("--line-format=LFMT Similar, but format all input lines with LFMT."),
143     N_("--LTYPE-line-format=LFMT Similar, but format LTYPE input lines with LFMT."),
144 - N_(" LTYPE is `old', `new', or `unchanged'. GTYPE is LTYPE or `changed'."),
145 + N_(" LTYPE is `old', `new', or `unchanged'. GTYPE is LTYPE or `changed'."),
146     N_(" GFMT may contain:\n\
147         %< lines from FILE1\n\
148         %> lines from FILE2\n\
149 @@ -895,7 +895,7 @@ static char const * const option_help_msgid[] = {
150     %c'C' the single character C\n\
151     %c'\000' the character with octal code 000"),
152     "",
153 - N_("-l --paginate Pass the output through `pr' to paginate it."),
154 + N_("-l --paginate Pass the output through 'pr' to paginate it."),
155     N_("-t --expand-tabs Expand tabs to spaces in output."),
156     N_("-T --initial-tab Make tabs line up by prepending a tab."),
157     N_("--tabsize=NUM Tab stops are every NUM (default 8) print columns."),
158 @@ -918,9 +918,9 @@ static char const * const option_help_msgid[] = {
159     N_("-v --version Output version info."),
160     N_("--help Output this help."),
161     "",
162 - N_("FILES are `FILE1 FILE2' or `DIR1 DIR2' or `DIR FILE...' or `FILE... DIR'."),
163 + N_("FILES are 'FILE1 FILE2' or 'DIR1 DIR2' or 'DIR FILE...' or 'FILE... DIR'."),
164     N_("If --from-file or --to-file is given, there are no restrictions on FILES."),
165 - N_("If a FILE is '-', read standard input."),
166 + N_("If a FILE is '-', read standard input."),
167     N_("Exit status is 0 if inputs are the same, 1 if different, 2 if trouble."),
168     0
169 };
170 @@ -960,7 +960,7 @@ specify_value (char const **var, char const *value, char const *option)
171 {
172     if (*var && strcmp (*var, value) != 0)
173     {
174 - error (0, 0, _("conflicting %s option value '%s'"), option, value);
175 + error (0, 0, _("conflicting %s option value '%s'"), option, value);
176         try_help (NULL, NULL);
177     }
178     *var = value;
179 @@ -1159,7 +1159,7 @@ compare_files (struct comparison const *parent,
180     = dir_file_pathname (dir, last_component (fnm));
181
182     if (STREQ (fnm, "-"))
183 - fatal ("cannot compare '-' to a directory");

```

```

184 +     fatal ("cannot compare '-' to a directory");
185
186     if (stat (filename, &cmp.file[dir_arg].stat) != 0)
187     {
188 diff --git a/src/diff3.c b/src/diff3.c
189 index 0f11fdc..fbfb28b 100644
190 --- a/src/diff3.c
191 +++ b/src/diff3.c
192 @@ -316,9 +316,9 @@ main (int argc, char **argv)
193     if (argc - optind != 3)
194     {
195         if (argc - optind < 3)
196 -         try_help ("missing operand after '%s'", argv[argc - 1]);
197 +         try_help ("missing operand after '%s'", argv[argc - 1]);
198         else
199 -         try_help ("extra operand '%s'", argv[optind + 3]);
200 +         try_help ("extra operand '%s'", argv[optind + 3]);
201     }
202
203     file = &argv[optind];
204 @@ -351,7 +351,7 @@ main (int argc, char **argv)
205         file instead. */
206         common = 3 - common;
207         if (STREQ (file[0], "-") || STREQ (file[common], "-"))
208 -         fatal ("'- ' specified for more than one input file");
209 +         fatal ("'- ' specified for more than one input file");
210     }
211
212     mapping[0] = 0;
213 @@ -412,7 +412,7 @@ try_help (char const *reason_msgid, char const *operand)
214     if (reason_msgid)
215         error (0, 0, _(reason_msgid), operand);
216     error (EXIT_TROUBLE, 0,
217 -         _("Try '%s --help' for more information."), program_name);
218 +         _("Try '%s --help' for more information."), program_name);
219     abort ();
220 }
221
222 @@ -435,7 +435,7 @@ static char const * const option_help_msgid[] = {
223     "",
224     N_("-m --merge Output merged file instead of ed script (default -A)."),
225     N_("-L LABEL --label=LABEL Use LABEL instead of file name."),
226 -     N_("-i Append 'w' and 'q' commands to ed scripts."),
227 +     N_("-i Append 'w' and 'q' commands to ed scripts."),
228     N_("-a --text Treat all files as text."),
229     N_("--strip-trailing-cr Strip trailing carriage return on input."),
230     N_("-T --initial-tab Make tabs line up by prepending a tab."),
231 @@ -460,7 +460,7 @@ usage (void)
232     else
233         putchar ('\n');
234     printf ("\n%s\n%s\n",
235 -         _("If a FILE is '-', read standard input."),
236 +         _("If a FILE is '-', read standard input."),
237         _("Exit status is 0 if successful, 1 if conflicts, 2 if trouble.));
238     emit_bug_reporting_address ();
239 }
240 @@ -1275,12 +1275,12 @@ read_diff (char const *filea,
241     if (EXIT_TROUBLE <= status)
242         error (EXIT_TROUBLE, werrno,
243             _(status == 126
244 -             ? "subsidiary program '%s' could not be invoked"
245 +             ? "subsidiary program '%s' could not be invoked"
246             : status == 127
247 -             ? "subsidiary program '%s' not found"
248 +             ? "subsidiary program '%s' not found"
249             : status == INT_MAX

```

```

250 -         ? "subsidiary program '%s' failed"
251 -         : "subsidiary program '%s' failed (exit status %d)",
252 +         ? "subsidiary program '%s' failed"
253 +         : "subsidiary program '%s' failed (exit status %d)",
254     diff_program, status);
255
256     return diff_result + total;
257 diff --git a/src/dir.c b/src/dir.c
258 index 5b4eaec..5e08318 100644
259 --- a/src/dir.c
260 +++ b/src/dir.c
261 @@ -154,7 +154,7 @@ compare_names (char const *name1, char const *name2)
262     r = strcoll (name1, name2);
263     if (errno)
264     {
265 -         error (0, errno, _("cannot compare file names '%s' and '%s'"),
266 +         error (0, errno, _("cannot compare file names '%s' and '%s'"),
267             name1, name2);
268         longjmp (failed_locale_specific_sorting, 1);
269     }
270 diff --git a/src/sdiff.c b/src/sdiff.c
271 index 4344e8d..5bbeed8 100644
272 --- a/src/sdiff.c
273 +++ b/src/sdiff.c
274 @@ -175,7 +175,7 @@ try_help (char const *reason_msgid, char const *operand)
275     {
276         if (reason_msgid)
277             error (0, 0, _(reason_msgid), operand);
278 - error (EXIT_TROUBLE, 0, _("Try '%s --help' for more information."),
279 + error (EXIT_TROUBLE, 0, _("Try '%s --help' for more information."),
280         program_name);
281         abort ();
282     }
283 @@ -230,7 +230,7 @@ usage (void)
284     else
285         putchar ('\n');
286     printf ("\n%s\n%s\n",
287 -         _("If a FILE is '-', read standard input."),
288 +         _("If a FILE is '-', read standard input."),
289         _("Exit status is 0 if inputs are the same, 1 if different, 2 if trouble.));
290     emit_bug_reporting_address ();
291 }
292 @@ -286,12 +286,12 @@ check_child_status (int werrno, int wstatus, int max_ok_status,
293     {
294         error (0, werrno,
295             _("status == 126
296 -         ? "subsidiary program '%s' could not be invoked"
297 +         ? "subsidiary program '%s' could not be invoked"
298             : status == 127
299 -         ? "subsidiary program '%s' not found"
300 +         ? "subsidiary program '%s' not found"
301             : status == INT_MAX
302 -         ? "subsidiary program '%s' failed"
303 -         : "subsidiary program '%s' failed (exit status %d)",
304 +         ? "subsidiary program '%s' failed"
305 +         : "subsidiary program '%s' failed (exit status %d)",
306         subsidiary_program, status);
307         exiterr ();
308     }
309 @@ -572,9 +572,9 @@ main (int argc, char *argv[])
310     if (argc - optind != 2)
311     {
312         if (argc - optind < 2)
313 -         try_help ("missing operand after '%s'", argv[argc - 1]);
314 +         try_help ("missing operand after '%s'", argv[argc - 1]);
315     }
316     else

```

```
316 -     try_help ("extra operand '%s'", argv[optind + 2]);
317 +     try_help ("extra operand '%s'", argv[optind + 2]);
318     }
319
320     if (! output)
321     diff --git a/src/util.c b/src/util.c
322     index 3be03e9..d18bf38 100644
323     --- a/src/util.c
324     +++ b/src/util.c
325     @@ -298,12 +298,12 @@ finish_output (void)
326         if (status)
327             error (EXIT_TROUBLE, werrno,
328                 _(status == 126
329 -                 ? "subsidary program '%s' could not be invoked"
330 +                 ? "subsidary program '%s' could not be invoked"
331                   : status == 127
332 -                 ? "subsidary program '%s' not found"
333 +                 ? "subsidary program '%s' not found"
334                   : status == INT_MAX
335 -                 ? "subsidary program '%s' failed"
336 -                 : "subsidary program '%s' failed (exit status %d)"),
337 +                 ? "subsidary program '%s' failed"
338 +                 : "subsidary program '%s' failed (exit status %d)"),
339             pr_program, status);
340     }
341
342     --
343     1.8.5.3
```