

1 dailyLog

```
std::bitset<5> intA;
struct s1 {
    int a:6;
}
#include <iostream>
#include <stdexcept>
#include <functional>
#include <bitset>
#include <locale>
#include <stdio.h>
#include <codecvt>
#include <assert.h>
using namespace std::string_literals;
auto s1 = "abc";
auto s1 = L"abc";
auto s1 = u8"abc";
auto s1 = u"abc";
auto s1 = U"abc";
auto s1 = "abc";
auto s1 = "abc";
auto s1 = 42;
auto s1 = 42l;
auto s1 = 42ul;
auto s1 = 42ull;
auto s1 = 42.f;
auto s1 = 42.;
auto s1 = 42;
auto s1 = 0b11
auto s1 = 0123;
auto s1 = 0x123;
std::cout << std::hex << std::dec << std::oct << std::boolalpha
std::setlocale(LC_ALL, "en_US.UTF-8");
std::u32string p1 = U"abc"s;
std::string p2 = "abc"s;
std::u16string p3 = u"abc"s;
enum e1{R,RED,YELLOW};
enum class e1{R,RED,YELLOW};
#define RED1 1
enum class e1:uint8_t
{
    R=253,
    RED,
    YELLOW
};

template <typename T> void type_name(){
    std::cout << _PRETTY_FUNCTION_ << std::endl;
}
```