

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)

Enterprise Java

Module - I

Practical – V

Roll No.:T054	Name:Priti Yadav
Class:TYIT	Batch:2
Date of Assignment: 1/08/26	Date/Time of Submission: 1/08/26

5. Implement the following JSP JSTL and EL Applications.

a. Create an html page with fields, eno, name, age, designation, salary. Now on submit this data to a JSP page which will update the employee table of database with matching eno.

CODE:-

SQL:

```
CREATE DATABASE company;
```

```
USE company;
```

```
CREATE TABLE employee (
```

```
    eno INT PRIMARY KEY,
```

```
    name VARCHAR(50),
```

```
    age INT,
```

```
    designation VARCHAR(50),
```

```
    salary DOUBLE
```

```
);
```

```
INSERT INTO employee VALUES
```

```
(101,'Priti',18,'Developer',25000),
```

```
(102,'Amit',22,'Tester',22000),
```

```
(103,'Ravi',23,'Manager',35000);
```

updateEmployee.jsp:

```
<%@ page import="java.sql.*" %>
```

```
<%
```

```
String enoStr = request.getParameter("eno");
```

```
String name = request.getParameter("name");
```

```
String ageStr = request.getParameter("age");
```

```
String designation = request.getParameter("designation");
```

```
String salaryStr = request.getParameter("salary");
```

```
if (enoStr == null || enoStr.trim().equals("") ||
```

```
    name == null || name.trim().equals("") ||
```

```
    ageStr == null || ageStr.trim().equals("") ||
```

```
    designation == null || designation.trim().equals("") ||
```

```
    salaryStr == null || salaryStr.trim().equals("")) {
```

```
    out.println("<h2>Please fill all fields.</h2>");
```

```
    return;
```

```
}
```

```
int eno = Integer.parseInt(enoStr);
```

```
int age = Integer.parseInt(ageStr);
```

```
double salary = Double.parseDouble(salaryStr);
```

```
Connection con = null;
```

```
PreparedStatement ps = null;
```

```
try {
```

```
    Class.forName("com.mysql.cj.jdbc.Driver");
```

```
    con = DriverManager.getConnection(
```

```
        "jdbc:mysql://localhost:3306/company?useSSL=false&serverTimezone=UTC",
```

```
        "root",
```

```
        "Priti@0103"
```

```
    );
```

```

String sql = "UPDATE employee SET name=?, age=?, designation=?, salary=? WHERE eno=?";
ps = con.prepareStatement(sql);
ps.setString(1, name);
ps.setInt(2, age);
ps.setString(3, designation);
ps.setDouble(4, salary);
ps.setInt(5, eno);
int rows = ps.executeUpdate();
if(rows > 0){
%>
<h2 style="color:green;">Employee Updated Successfully!</h2>
<%
}
else{
%>
<h2 style="color:red;">Employee Number Not Found!</h2>
<%
}
} catch(Exception e){
    out.println("<h3>Error:</h3>");
    out.println(e.getMessage());
} finally{
    if(ps != null)
        ps.close();
    if(con != null)
        con.close();
}
%>
<br>
<a href="update.html">Go Back</a>

```

Update.html:

```

<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Update Employee</title>
</head>
<body>
<h2>Update Employee</h2>
<form action="updateEmployee.jsp" method="post">
Employee No:
<input type="number" name="eno" required>
<br><br>
Name:
<input type="text" name="name" required>
<br><br>
Age:
<input type="number" name="age" required>
<br><br>
Designation:
<input type="text" name="designation" required>
<br><br>
Salary:
<input type="number" name="salary" required>
<br><br>
<input type="submit" value="Update Employee">
</form>
</body>
</html>

```

OUTPUT:-

Update Employee

Employee No:

Name:

Age:

Designation:

Salary:

```
mysql> select * from employee;
+-----+-----+-----+-----+-----+
| eno | name | age | designation | salary |
+-----+-----+-----+-----+-----+
| 101 | Priti | 18 | it support | 100000 |
| 102 | Amit | 22 | Tester | 22000 |
+-----+-----+-----+-----+-----+
```

Employee Updated Successfully!

[Go Back](#)

b. Create a JSP page to demonstrate the use of Expression language.

CODE:-

Index.html:

```
<!DOCTYPE html>
<html>
  <head>
    <title>TODO supply a title</title>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
  </head>
  <body>
    <div>Home Page</div>
    <a href="newjsp.jsp">click this</a>
  </body>
</html>
```

Newjsp.jsp:

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
  <head>
    <title>Expression Language Demo</title>
  </head>
  <body>
    <h2>JSP Expression Language Example</h2>
    <p>Addition: ${12+2}</p>
    <p>Multiplication: ${5*4}</p>
    <p>Division: ${20/5}</p>
    <p>Comparison: ${10>5}</p>
    <p>Logical Operation: ${true && false}</p>
  </body>
</html>
```

OUTPUT:-

JSP Expression Language Example

Home Page
[click this](#)

Addition: 14

Multiplication: 20

Division: 4.0

Comparison: true

Logical Operation: false

C. Create a JSP application to demonstrate the use of JSTL.

CODE:-

Index.html:

```
<!DOCTYPE html>
<html>
  <head>
    <title>TODO supply a title</title>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
  </head>
  <body>
    <div>Home Page</div>
    <a href="newjsp.jsp">click this</a>
  </body>
</html>
```

Newjsp.jsp:

```
<%@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core" %>
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
  <head>
    <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
    <title>Core Tag Example</title>
  </head>
  <body>
    <c:forEach var="j" begin="5" end="15">
      Item <c:out value="${j}" /><p>
    </c:forEach>
  </body>
</html>
```

OUTPUT:-

Item 5

Home Page
[click this](#)

Item 6

Item 7

Item 8

Item 9

Item 10

Item 11

Item 12

Item 13

Item 14

Item 15