


Adaptive Experimental Design For Drug Combinations

Mijung Park, Marcel Nassar, Brian L. Evans, Haris Vikalo


Electrical and Computer Engineering, The University of Texas at Austin

1. Drug combinations problem



2. Response modeling using Gaussian processes

generative model



MAP inference: $P(\mathbf{f}^*|X^*, X, \mathbf{y}, \theta) \sim \mathcal{N}(\mu, \Sigma)$
at test points

$$\mu = K(X^*, X)(K + \sigma^2 I)^{-1} \mathbf{y}$$

$$\Sigma = K(X^*, X^*) - K(X^*, X)(K + \sigma^2 I)^{-1} K(X, X^*)$$

Hyperparameter estimation:

$$\theta_{ml} = \arg \max_{\theta} P(\mathbf{y}|\theta) = \int P(\mathbf{y}|X, \mathbf{f}) P(\mathbf{f}|X, \theta) d\mathbf{f}.$$


3. Info-theoretic Active Learning

- maximize expected info gain about f

$$\mathbf{x}^* = \arg \max_{\mathbf{x}} \mathbb{E}_{p(y|\mathbf{x}, D_t)} [H(\mathbf{f}|D_t) - H(\mathbf{f}|D_t, \mathbf{x}, y)]$$

$$= \arg \max_{\mathbf{x}} \Sigma(\mathbf{x}, \mathbf{x}) \quad \text{uncertainty sampling}$$


- sequential active learning




4. Application to EGFR network

- Epidermal Growth Factor Receptor
 - Inhibiting EGFR desired

select drugs
 minimizing target: $t = \exp\left(\sum_{i=1}^3 t_i\right)$



5. Results



t1, t2, t3 with best combinations

