Dir	nens	ions														
Size		٨	В	С	D		Key	Upper flange					ANSI 150		DIN PN10/16	
IN	DN	А	D		D	L	bxl	Κ	Е	z-d	g	h	Dl	n-dl	D1	n-dl
2	50	120	83	108	52.9	32	3x16	70	50	4-7	35	3	120.5	4-19	125	4-18
2-1/2	65	130	93	112	64.5	32	3x16	70	50	4-7	35	3	139.5	4-19	145	4-18
3	80	145	100	114	78.8	32	3x16	70	50	4-7	35	3	152.5	4-19	160	4/8-18
4	100	155	114	127	104	32	5x19	90	70	4-9	55	3	190.5	8-19	180	8-18
5	125	170	125	140	123.3	32	5x19	90	70	4-9	55	3	216	8-22	210	8-18
6	150	190	143	140	155.6	32	5x19	90	70	4-9	55	3	241.5	8-22	240	8-23
8	200	205	170	152	202.5	45	5x19	125	102	4-12	70	3.5	298.5	8-22	295	8/12-23
10	250	235	198	165	250.5	45	8x28	125	102	4-12	70	3.5	362	12-25	350/355	12-23/27
12	300	280	223	178	301.6	45	8x28	140	102	4-12	70	3.5	432	12-25	400/410	12-23/27
14	350	310	279	190	333.3	45	8x28	140	102	4-12	70	3.5	476	12-29	350/355	16-23/27
16	400	340	300	216	389.6	51.2/72	10x50	175	140	4-18	100	4	540	16-29	515/525	16-27/30
18	450	375	345	222	440.5	51.2/72	10x50	175	140	4-18	100	4	578	16-32	565/585	20-27/30
20	500	430	355	229	491.6	527177.5	10x50	175	140	4-18	100	4	635	20-32	620/650	20-27/33
24	600	500	410	267	592.5	70.2/80	2-16x60	210	165	4-23	130	5	749.5	20-35	725/770	20-27/36
28	700	560	478	292	695	66/82	2-18x63	300	254	8-18	200	5.5	863.5	28-35	840	24-30/36
32	800	620	529	318	794.7	66/82	2-18x63	300	254	8-18	200	5.5	978	28-41	950	24-33/39
36	900	665	584	330	864.7	118	2-20x100	300	254	8-18	200	5.5	1086	32-41	1050	28-33/39
40	1000	735	657	410	965	141	2-22x140	300	254	8-18	200	5.5	1200	36-41	1160/1170	28-36/42