

OIL INDIA LIMITED — DAILY DRILLING REPORT (DDR)

24-HOUR OPERATIONAL LOG · REPORT NO: 28 · DATE: 12-SEP-2026

Well Name:	MORAN-29 (MOR-29)	Rig:	OIL-RIG-04 (2000 HP AC-SCR)
Current Depth:	2,418.0m MD (TVD: 2,396.2m)	24-hr Progress:	+12.0m drilled
Formation:	Barail Group (Tikak Parbat member)	ROP Avg:	6.8 m/hr
Mud Weight:	10.8 ppg (KCl-Polymer)	Standpipe Press:	2,440 psi @ 650 GPM

24-HOUR DRILLING TIMELINE & PARAMETERS

Time	Operation & Subsurface Observation
06:00 - 10:00	Rotary drilling 8-1/2" hole from 2,406m to 2,412m. WOB: 18.5 klbs, RPM: 120. ROP 1.5 m/hr.
10:00 - 10:30	Connection gas check. Background gas increased from 18 to 28 units. Trip gas peaked at 42 units.
10:30 - 14:00	Drilled ahead to 2,416m. Torque stable at 14,000 ft-lbs. Clean returns.
14:00 - 18:00	Drilled to 2,418m MD. Circulated bottoms-up. Mud density verified at 10.8 ppg.
18:00 - 06:00	SRISHTI-AI Lookahead Advisory: Bit is 32m above Barail Gas Precursor Horizon (2,450m).

SRISHTI-AI PROACTIVE LOOKAHEAD ALERT (ALT-101)

CRITICAL HAZARD WARNING: Bit at 2,418m MD is approaching 2,450m Barail overpressured gas kick precursor horizon. Offset well BAGHJAN-5 (13.2 km NE) recorded a 22 bbl gas influx at 3,380m in identical stratigraphic sequence. MANDATORY ACTION: 1. Calibrate trip tank sensors. 2. Prepare 12.8 ppg kill mud in reserve pit. 3. Conduct remote BOP choke drill per OISD-STD-174.

SIGNATURES: K. Sarma (Company Man) · R. Hazarika (Day Toolpusher) · OIL Duliajan