Question 8: Record all Dockerfiles, Kubernetes manifests, commands, screenshots, and observations for each experiment.

Executed on Ubuntu 24.04 LTS. All commands, configurations and screenshots are committed in the GitHub repository https://github.com/theabhinav0231/devops-lab-2.

1. Commit history (github.com/theabhinav0231/devops-lab-2)

```
* 62dcded add build 3 auto-trigger evidence and polling log screenshot
* 6cb9aa0 add q7 CD pipeline evidence and screenshots
* 496cf4e add lab 2 observations
* 0ff59ad fix CD health check: use kubectl node IP instead of minikube ip
* aeb0b2a add Jenkinsfile for continuous deployment to minikube
* eff439a add q5 k8s deployment and q6 rolling update, rollback, scaling evidence
* b8c283b add q2 container management, docker hub push and compose evidence
* 65e8eb8 add q1 docker build/run evidence, q3 storage and q4 network demos
* b8c283b (tag) initial commit: flask app v2.0.0 with Dockerfile, compose and k8s manifests
```

2. Dockerfile (Q1)

```
# Lab 2 - container image for the flask app
FROM python:3.12-slim

ARG APP_VERSION=2.0.0
ENV APP_VERSION=${APP_VERSION}

WORKDIR /app

# install dependencies first so this layer is cached
COPY app/requirements.txt /app/requirements.txt
RUN pip install --no-cache-dir -r /app/requirements.txt

# copy application code
COPY app/ /app/

EXPOSE 5000

# run as non-root user
RUN useradd -m appuser
USER appuser

CMD ["python", "app.py"]
```

3. Kubernetes manifests (Q5)

k8s/deployment.yaml

```
# Lab 2 - Deployment for the flask app
apiVersion: apps/v1
kind: Deployment
metadata:
  name: lab2-app
  labels:
    app: lab2-app
spec:
  replicas: 2
  selector:
    matchLabels:
      app: lab2-app
  template:
    metadata:
      labels:
        app: lab2-app
    spec:
      containers:
        - name: lab2-app
          image: devops-lab2-app:2.0.0
          imagePullPolicy: IfNotPresent
          ports:
            - containerPort: 5000
          envFrom:
            - configMapRef:
                name: lab2-app-config
          readinessProbe:
            httpGet:
              path: /health
              port: 5000
            initialDelaySeconds: 5
            periodSeconds: 10
          livenessProbe:
            httpGet:
              path: /health
              port: 5000
            initialDelaySeconds: 15
            periodSeconds: 20
```

k8s/service.yaml

```
# Lab 2 - NodePort service exposing the flask app
apiVersion: v1
kind: Service
metadata:
  name: lab2-app-service
spec:
  type: NodePort
  selector:
    app: lab2-app
  ports:
    - port: 5000
      targetPort: 5000
      nodePort: 30080
```

k8s/configmap.yaml

```
# Lab 2 - ConfigMap for the flask app
apiVersion: v1
kind: ConfigMap
metadata:
  name: lab2-app-config
data:
  APP_MESSAGE: "DevOps Lab 2 app running on Kubernetes (Minikube)"
```

4. Docker Compose (Q2)

docker/docker-compose.yml

```
# Lab 2 - multi-container setup: flask app + redis
services:
  web:
    build:
      context: ..
      dockerfile: docker/Dockerfile
    image: devops-lab2-app:2.0.0
    ports:
      - "5000:5000"
    environment:
      - APP_VERSION=2.0.0
    depends_on:
      - redis
    networks:
      - lab2net

  redis:
    image: redis:7-alpine
    container_name: lab2-redis
    ports:
      - "6379:6379"
    networks:
      - lab2net

networks:
  lab2net:
    driver: bridge
```

5. Key evidence screenshots

```
abhinav@LAPTOP-BSV7PCJK: docs/commands - terminal
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 5.24MB / 12.12MB 3.6s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 12.58MB / 29.86MB 3.9s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 14.68MB / 29.86MB 4.7s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 6.29MB / 12.12MB 4.8s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 16.78MB / 29.86MB 5.7s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 7.34MB / 12.12MB 6.2s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 8.39MB / 12.12MB 7.8s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 18.87MB / 29.86MB 7.8s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 9.44MB / 12.12MB 8.1s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 10.49MB / 12.12MB 8.3s
#5 sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 12.12MB / 12.12MB 8.6s done
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 20.97MB / 29.86MB 9.5s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 23.07MB / 29.86MB 9.6s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 25.17MB / 29.86MB 10.1s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 27.26MB / 29.86MB 10.4s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 29.36MB / 29.86MB 10.8s
#5 sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 29.86MB / 29.86MB 11.0s done
#5 extracting sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5
#5 extracting sha256:6fc242d221a673263eabd14a9ad9584d3177c96e5cb504c891497338e2f912f5 1.3s done
#5 DONE 13.2s
#5 [1/6] FROM docker.io/library/python:3.12-slim@sha256:b18b261e1b4974b4f321451ad5251ded85abb22c2b8b262da5
#5 extracting sha256:3eb77115150676568f88e2957181b8f7e3014e797f1ce8cd640086dfbed45e35
#5 extracting sha256:3eb77115150676568f88e2957181b8f7e3014e797f1ce8cd640086dfbed45e35 0.2s done
#5 DONE 13.4s
#5 [1/6] FROM docker.io/library/python:3.12-slim@sha256:b18b261e1b4974b4f321451ad5251ded85abb22c2b8b262da5
#5 extracting sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3
#5 extracting sha256:f574edac59d9f092df596f54e5b52656c803fd3ae30825b8ee5a189ed05f63d3 0.7s done
#5 DONE 14.1s
#5 [1/6] FROM docker.io/library/python:3.12-slim@sha256:b18b261e1b4974b4f321451ad5251ded85abb22c2b8b262da5
#5 extracting sha256:acca7542dfc736e9ce20cbefc58b2d09822276d15d4a0c531531a6f1b057928e 0.0s done
#5 DONE 14.2s
#6 [2/6] WORKDIR /app
#6 DONE 0.4s
#7 [3/6] COPY app/requirements.txt /app/requirements.txt
#7 DONE 0.1s
#8 [4/6] RUN pip install --no-cache-dir -r /app/requirements.txt
#8 3.327 Collecting flask==3.1.0 (from -r /app/requirements.txt (line 1))
#8 3.388   Downloading flask-3.1.0-py3-none-any.whl.metadata (2.7 kB)
```

Fig: Q1: docker build and run




Fig: Q2: image pushed to Docker Hub

```
abhinav@LAPTOP-BSV7PCJK: docs/commands  —  terminal
### Demo 2: a named volume SURVIVES container deletion
abhinav@LAPTOP-BSV7PCJK:~$ docker volume create lab2data
lab2data
abhinav@LAPTOP-BSV7PCJK:~$ docker run -d --name demo-vol -v lab2data:/data ubuntu:24.04 sleep infinity
c5e2183b5e8a4933f73199f9ef56a68767b0a923e3447e85ad75b03d3a07a625
abhinav@LAPTOP-BSV7PCJK:~$ docker exec demo-vol sh -c "echo persistent-data > /data/note.txt && cat /data/
persistent-data
abhinav@LAPTOP-BSV7PCJK:~$ docker rm -f demo-vol && docker run -d --name demo-vol -v lab2data:/data ubuntu
demo-vol
df34cc335ea2592ec4cffaf44142fdd4672dbcf9df3a0e9758cfe14633f3be93
abhinav@LAPTOP-BSV7PCJK:~$ docker exec demo-vol cat /data/note.txt
persistent-data
--> file SURVIVED: named volume lives outside the container lifecycle
abhinav@LAPTOP-BSV7PCJK:~$ docker volume inspect lab2data | grep -A2 Mountpoint
        "Mountpoint": "/var/lib/docker/volumes/lab2data/_data",
        "Name": "lab2data",
        "Options": null,
```

Fig: Q3: named volume demo

```
abhinav@LAPTOP-BSV7PCJK: docs/commands  —  terminal
### Two containers talking over a user-defined bridge network
abhinav@LAPTOP-BSV7PCJK:~$ docker network create lab2net
abhinav@LAPTOP-BSV7PCJK:~$ docker network ls | grep lab2net
0f6f494d736a   lab2net    bridge    local
abhinav@LAPTOP-BSV7PCJK:~$ docker run -d --name net-a --network lab2net ubuntu:24.04 sleep infinity
78803bf67a504aeeb6d3423b4cebe4d317ae2c106fa97719ccbc546bbd3b5232
abhinav@LAPTOP-BSV7PCJK:~$ docker run -d --name net-b --network lab2net ubuntu:24.04 sleep infinity
245105f4700b21dff87ecd8fbbb3c42c150565d8c7e7c22257706ffcf0607049
abhinav@LAPTOP-BSV7PCJK:~$ docker exec net-a apt-get install -y -qq iputils-ping   (minimal image: add pi
ping installed in both containers
abhinav@LAPTOP-BSV7PCJK:~$ docker inspect net-a --format "net-a IP: {{.NetworkSettings.Networks.lab2net.IP
net-a IP: 172.18.0.2
abhinav@LAPTOP-BSV7PCJK:~$ docker inspect net-b --format "net-b IP: {{.NetworkSettings.Networks.lab2net.IP
net-b IP: 172.18.0.3
### Communication using the container NAME (embedded DNS)
abhinav@LAPTOP-BSV7PCJK:~$ docker exec net-a ping -c 2 net-b
PING net-b (172.18.0.3) 56(84) bytes of data.
64 bytes from net-b.lab2net (172.18.0.3): icmp_seq=1 ttl=64 time=9.50 ms
64 bytes from net-b.lab2net (172.18.0.3): icmp_seq=2 ttl=64 time=0.090 ms
--- net-b ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1007ms
rtt min/avg/max/mdev = 0.090/4.792/9.495/4.702 ms
### Communication using the container IP ADDRESS
abhinav@LAPTOP-BSV7PCJK:~$ docker exec net-a ping -c 2 172.18.0.3
PING 172.18.0.3 (172.18.0.3) 56(84) bytes of data.
64 bytes from 172.18.0.3: icmp_seq=1 ttl=64 time=0.087 ms
64 bytes from 172.18.0.3: icmp_seq=2 ttl=64 time=0.116 ms
--- 172.18.0.3 ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1014ms
rtt min/avg/max/mdev = 0.087/0.101/0.116/0.014 ms
### Containers on the DEFAULT bridge network cannot resolve each other by name
abhinav@LAPTOP-BSV7PCJK:~$ docker run -d --name net-c ubuntu:24.04 sleep infinity
55e7620ea0cf21711585a65fd999571bdc9175eebdac7962bb405c4dd78faba7
abhinav@LAPTOP-BSV7PCJK:~$ docker exec net-c ping -c 1 net-a
ping: net-a: Name or service not known
--> default bridge has no embedded DNS: user-defined networks are required for name resolution
```

Fig: Q4: network demo

```
abhinav@LAPTOP-BSV7PCJK: docs/commands  —  terminal
====
Events:  <none>
### Access the app through the NodePort
abhinav@LAPTOP-BSV7PCJK:~$ minikube service lab2-app-service --url
X Exiting due to SVC_UNREACHABLE: service not available: no running pod for service lab2-app-service found
*
┌──────────────────────────────────────────────────────────────────────────────────────────┐
│                                                                                          │
│    * If the above advice does not help, please let us know:                              │
│      https://github.com/kubernetes/minikube/issues/new/choose                           │
│                                                                                          │
│    * Please run `minikube logs --file=logs.txt` and attach logs.txt to the GitHub issue. │
│    * Please also attach the following file to the GitHub issue:                          │
│    * - /tmp/minikube_service_3489c6d5f74fb6ad14c162c9fae5f0d8d14ea32c_0.log              │
│                                                                                          │
└──────────────────────────────────────────────────────────────────────────────────────────┘
abhinav@LAPTOP-BSV7PCJK:~$ curl $(minikube service lab2-app-service --url)/health
X Exiting due to SVC_UNREACHABLE: service not available: no running pod for service lab2-app-service found
*
┌──────────────────────────────────────────────────────────────────────────────────────────┐
│                                                                                          │
│    * If the above advice does not help, please let us know:                              │
│      https://github.com/kubernetes/minikube/issues/new/choose                           │
│                                                                                          │
│    * Please run `minikube logs --file=logs.txt` and attach logs.txt to the GitHub issue. │
│    * Please also attach the following file to the GitHub issue:                          │
│    * - /tmp/minikube_service_3489c6d5f74fb6ad14c162c9fae5f0d8d14ea32c_0.log              │
│                                                                                          │
└──────────────────────────────────────────────────────────────────────────────────────────┘
abhinav@LAPTOP-BSV7PCJK:~$ curl $(minikube service lab2-app-service --url)/
X Exiting due to SVC_UNREACHABLE: service not available: no running pod for service lab2-app-service found
*
┌──────────────────────────────────────────────────────────────────────────────────────────┐
│                                                                                          │
│    * If the above advice does not help, please let us know:                              │
│      https://github.com/kubernetes/minikube/issues/new/choose                           │
│                                                                                          │
│    * Please run `minikube logs --file=logs.txt` and attach logs.txt to the GitHub issue. │
```

Fig: Q5: kubectl apply and pods

```
abhinav@LAPTOP-BSV7PCJK: docs/commands  —  terminal
### SCALING: increase replicas from 2 to 4
abhinav@LAPTOP-BSV7PCJK:~$ kubectl scale deployment/lab2-app --replicas=4
deployment.apps/lab2-app scaled
abhinav@LAPTOP-BSV7PCJK:~$ kubectl get pods -l app=lab2-app
NAME                        READY   STATUS        RESTARTS   AGE
lab2-app-56dd487c9b-2ctj2   1/1     Terminating   0          73s
lab2-app-56dd487c9b-682tp   1/1     Terminating   0          86s
lab2-app-88f4c9fc9-bv4qd    1/1     Running       0          26s
lab2-app-88f4c9fc9-snrr5    1/1     Running       0          38s
lab2-app-88f4c9fc9-tnb9c    1/1     Running       0          12s
lab2-app-88f4c9fc9-v8vv5    1/1     Running       0          12s
abhinav@LAPTOP-BSV7PCJK:~$ kubectl get deployment lab2-app
NAME       READY   UP-TO-DATE   AVAILABLE   AGE
lab2-app   4/4     4            4           19m
### scale back down to 2
abhinav@LAPTOP-BSV7PCJK:~$ kubectl scale deployment/lab2-app --replicas=2
deployment.apps/lab2-app scaled
abhinav@LAPTOP-BSV7PCJK:~$ kubectl get pods -l app=lab2-app
NAME                        READY   STATUS        RESTARTS   AGE
lab2-app-56dd487c9b-2ctj2   1/1     Terminating   0          85s
lab2-app-88f4c9fc9-bv4qd    1/1     Running       0          38s
lab2-app-88f4c9fc9-snrr5    1/1     Running       0          50s
lab2-app-88f4c9fc9-tnb9c    1/1     Terminating   0          24s
lab2-app-88f4c9fc9-v8vv5    1/1     Terminating   0          24s
```

Fig: Q6: scaling demo




Fig: Q7: poll detected the push

6. Observations

```
# Lab 2 Observations

## Q1 - Containerize with Docker
- The image builds in layers: dependency install (`pip install`) was placed before the code copy so rebuilds
- `docker history` shows each layer with its size; the base image (python:3.12-slim) is most of the 204 MB,
- The container runs as a non-root user (`appuser`), which maps to uid 1000 (visible with `docker top`).
- Note: WSL2 + Docker 29.x uses the systemd cgroup driver by default, which breaks the minikube docker drive

## Q2 - Manage containers and images
- `docker stop` keeps the container (shows as Exited in `ps -a`); `start` resumes it. `rm` removes it entire
- Tagging with `docker tag` just adds a new name to the same image ID - `abhinaaav/devops-lab2-app:2.0.0` an
- Docker Hub accepted the push with a personal access token via `--password-stdin`; the image appeared on th
- Docker Compose: `up -d` created its own network (`docker_lab2net`), both services resolved each other by n
- Gotcha: the compose `web` service failed to start while the standalone container from Q1 still held port 5

## Q3 - Docker storage
- Container-layer data (`/tmp/note.txt`) disappeared after `docker rm` + recreate: writable layers die with
- A named volume (`lab2data`) survived deletion and recreation because it lives in `/var/lib/docker/volumes/
- A bind mount (`~/lab2-bindmount-data:/data`) synced both ways: host edits visible in the container, contai

## Q4 - Docker network
- On a user-defined bridge network, containers resolve each other by **name** through Docker's embedded DNS
- On the default `bridge` network there is no embedded DNS - `ping net-a` failed with "Name or service not k
- The minimal `ubuntu:24.04` image ships without `ping`; `apt install iputils-ping` was needed inside the de

## Q5 - Deploy to Kubernetes (Minikube)
- Minikube v1.39 on WSL2 needed two fixes: `--force-systemd=true` (minikube issue #20469 - without it the no
- With the containerd runtime, `eval $(minikube docker-env)` builds are experimental and failed (buildkit 40
- Deployment (2 replicas with readiness/liveness probes on `/health`) + NodePort Service (30080) + ConfigMap
- NodePort access works from inside WSL via the node IP (192.168.49.2:30080); from Windows, `kubectl port-fo

## Q6 - Rolling update, rollback, scaling
- `kubectl set image` triggered a rolling update: new pods came up one-by-one while old ones terminated - th
- `kubectl rollout undo` returned to the previous image; the version reverted from 2.0.1 to 2.0.0 because th
- Observation: the health curl taken *immediately* after `rollout undo` still returned 2.0.1 for a few secon
- `kubectl scale --replicas=4` produced 2 extra Running pods within seconds; scaling back to 2 terminated th

## Q7 - Continuous deployment
- The Jenkins user needed docker group membership and a copy of the kubeconfig (with cert paths rewritten in
- First CD run failed only at the final health check (the minikube profile issue above); build/push/deploy h
- A push to `main` is picked up by Poll SCM (H/5) and automatically: builds image `abhinaaav/devops-lab2-app
```