SOFTWARE USED:

- > FRONT END
 - HTML
 - CSS
 - PHP
- BACK END
 - PHP (FOR CODING)
 - MYSQL SERVER(PHPMYADMIN)
 - XAMPP

SCREENSHOTS OF THE FRONT-END PART AND BACKEND PART:

❖ LOGIN



There are three types of user in the system

- Administrator
- Student
- Volunteer

They can login through this page for accessing their respective functions.

❖ SIGNUP



When not, a user they can signup by mentioning their respective roles I.e., whether the user is an Administrator, Student, or Volunteer. Their Roles and functions would depend on their category.

❖ <u>ADMINISTRATOR</u>

❖ HOME PAGE—FUNCTIONS OF AN ADMINISTRATOR IS FOUND HERE



CONTINUATION...



❖ **ADD EVENT-**ADMINISTRATOR CAN ADD AN EVENT WITH DETAILS HERE



CONTINUATION...



❖ **ADD VOLUNTEER FOR AN EVENT**-ADMINISTRATOR CAN ADD VOLUNTEER FOR A PARTICULAR EVENT HERE




❖ ADD A FACILITY—ADMINISTRATOR CAN ADD A FACILITY FOR THE STUDENTS TO USE




* ADD STALLS-ADMINISTRATOR CAN ADD STALLS AND THEIR LOCATION FOR CUSTOMERS USE HERE




❖ VIEW EVENTS



❖ VIEW VOLUNTEERS



❖ VIEW STALLS:



***** LOGOUT



❖ STUDENT


HOMEPAGE—FUNCTIONS OF THE STUDENT IS AVAILABLE HERE TO ACCESS




CONTINUATION...




❖ JOIN IN EVENT—STUDENT CAN JOIN IN AN EVENT BY SELECTING THE EVENTS AS GIVEN BELOW



❖ INCLUDE A FACILITY—STUDENT CAN INCLUDE A FACILITY BY SELECTING THE FACILITIES AS SHOWN BELOW



❖ VIEW REGISTERED EVENTS




❖ VIEW INCLUDED FACILITIES




Similar to the functions of the adminstrator in the above screen shots students can also view events, stalls and also can logout of the session.

❖ <u>VOLUNTEER</u>

❖ HOMEPAGE—FUNCTIONS OF THE VOLUNTEERS CAN BE ACCESSED HERE



❖ VIEW VOLUNTEERING EVENTS—VOLUNTEERS CAN VIEW THE EVENTS THEY WOULD BE VOLUNTEERING



Similar to adminstrator ,volunteers can also view events, stalls and also can log out.

SAMPLE CODINGS

> ADDING

```
$host='localhost';
$user='root';
$pass='';
$db='dbms_online_event_management';
$con=mysqli_connect($host,$user,$pass,$db)or die("failed to connect");
mysqli select db($con,"dbms online event management")or die("no database");
session_start();
$a=$_POST['eventid'];
$b=$_POST['ename'];
$c=$_POST['evenue'];
$d=$ POST['edate'];
$e=$_POST['etime'];
$f=$ POST['echief'];
$g=$_POST['espeaker'];
$h=$_POST['esponsor'];
$i=$ POST['eprize'];
$j=$_POST['ecert'];
$id=$ SESSION['id'];
$ap=mysqli_query($con,"select * from events where event_id=$a ");
if($ap)
    $p=mysqli_fetch_array($e);
    $pd=$p['event_id'];
    if($pd)
        header("Location:./addevent.php?error=Event id already exists");
$qry=mysqli_query($con,"Insert into events values ($a,'$b','$c','$d','$e','$i','$j')
");
$aq=mysqli_query($con,"select * from chiefguest where guest_name='$f'");
if($aq)
    $r1=mysqli_fetch_array($aq);
    $a1=$r1['guest_id'];
$q=mysqli_query($con,"Insert into chiefguest_events values($a,$a1)");
echo "error". mysqli error($con);
```

```
$bq=mysqli query($con,"select * from speak judges where name='$g'");
if($bq)
    $r2=mysqli_fetch_array($bq);
    $a2=$r2['speak_id'];
$q1=mysqli_query($con,"Insert into event_speakers values ($a2,$a)");
if(!$q1)
echo "error". mysqli error($con);
$cq=mysqli_query($con,"select * from sponsor where sponser_name='$h'");
if($cq)
    $r2=mysqli_fetch_array($cq);
    $a3=$r2['sponsor_id'];
$q2=mysqli query($con,"Insert into event sponsors values ($a3,$a)");
if(!$q2)
echo "error". mysqli_error($con);
$q3=mysqli_query($con,"insert into events_created_by_admin values($a,$id)");
if(!$q3)
echo mysqli_error($con);
if($qry)
    header("Location:./welcomeadministrator.php?id=Successfully added an event");
else
 echo "error". mysqli_error($con);
```

Similar to the above code whenever we have to insert into table after verifying certain conditions is used after making the changes required.

> VFRIFYING

```
<?php
$host='localhost';
$user='root';
$pass='';
$db='dbms_online_event_management';
$con=mysqli_connect($host,$user,$pass,$db)or die("failed to connect");
mysqli_select_db($con,"dbms_online_event_management")or die("no database");
$uid=$_POST['user_id'];</pre>
```

```
$pas=$_POST['password'];
$qry=mysqli_query($con,"SELECT * FROM log_details WHERE user_id='$uid'");
if($qry)
    {$row=mysqli_fetch_array($qry);
    if($uid==$row['user_id'])
        if($uid=='' || $pas=='')
            header("Location:./login.php?id=Some fields are empty");
        else if($uid==$row['user_id']&&$pas==$row['password'])
            session start();
            $_SESSION['id']=$uid;
           if($row['user_type']=="Student")
            header("Location:welcomestudent.php");}
            if($row['user type']=="Volunteer")
            {header("Location:welcomevolunteer.php");}
            if($row['user_type']=="Administrator")
            {header("Location:welcomeadministrator.php");}
        else
            header("Location:./login.php?id= user id or password is wrong");
    else
        echo "Error " . mysqli_error($con);
else
    header("Location:./login.php?id= user id not available");
```

Similar to the above code whenever verification of the credentials entered is required changes are made with respect to the necessity.

> VIEW

```
$host='localhost';

$user='root';

$pass='';

$db='dbms_online_event_management';

$con=mysqli_connect($host,$user,$pass,$db)or die("failed to connect");

mysqli_select_db($con,"dbms_online_event_management")or die("no database");

session_start();?>
```

```
<html>
      <link rel="stylesheet" type="text/css" href="Sam.css?version=51">
<body>
   <h1>Techno fest</h1>
   if(isset($_SESSION["name"])){
echo "<h3>You can view events now |".$_SESSION['name']."</h3> ";}?>
<a href="welcomeadministrator.php"><h3>Back</h3></a>
<fieldset>
{$qry=mysqli_query($con,"SELECT * FROM events") or die("Qyery not obtained");
<h2>Events</h2>
Event_id
Event name
Event_venue
Event date
Event time
Event prizes
Event speakers
Event_Certifications
Event sponsors
Event_chiefguest
<?php
while($row = mysqli_fetch_array($qry))
{ $a=$row['event_id'];
   $q=mysqli_query($con,"SELECT * FROM chiefguest_events where attending_event_id=$
a") or die("Qyery not obtained");
  if($q)
  $r= mysqli_fetch_array($q);
  $b=$r['guest id'];
  $q=mysqli_query($con,"SELECT * FROM chiefguest where guest_id=$b") or die("Qyery
not obtained");
```

```
if($q)
  $r= mysqli fetch array($q);
  $cid=$r['guest name'];
  $q=mysqli_query($con,"SELECT * FROM event_speakers where event_id=$a") or die("Qy
ery not obtained");
  if($q)
 $r= mysqli fetch array($q);
 $b=$r['event_speaker_id'];
 $q=mysqli_query($con,"SELECT * FROM speak_judges where speak_id=$b") or die("Qyery
 not obtained");
 if($q)
 $r= mysqli_fetch_array($q);
 $sn=$r['name'];
 $q=mysqli_query($con,"SELECT * FROM event_sponsors where event_id=$a") or die("Qye
ry not obtained");
  if($q)
 $r= mysqli fetch array($q);
 $b=$r['event sponsors id'];
 $q=mysqli_query($con,"SELECT * FROM sponsor where sponsor_id=$b") or die("Qyery no
t obtained");
 if($q)
 $r= mysqli_fetch_array($q);
 $sp=$r['sponser_name'];
echo "";
echo "" . $row['event id'] . "";
echo "" . $row['event_name'] . "";
echo "" . $row['event_venue'] . "";
echo "" . $row['event_date'] . "";
echo "" . $row['event_time'] . "";
echo "" . $row['event_prizes'] . "";
echo "" . $sn. "";
echo "" . $row['event_certifications'] . "";
echo "" . $sp. "";
echo "" . $cid. "";
echo "";
echo "";
mysqli_close($con);
}?>
</fieldset>
</div>
</body>
</html>
```

```
h1{
    text-align: center;
    color:royalblue;
    font-size: 40px;
h2{
    text-align: center;
    color:maroon;
    font-size: 30px;
h3{
    text-align:left;
    font-size: 20px;
    margin-bottom: 0px;
table
    width: 100%;
    margin-left: 0%;
    margin-right: 0%;
    margin-bottom: 0%;
    margin-top: 0%;
    align-content: center;
    align-self: center;
.vertical-menu {
    width: 150px;
  .vertical-menu a {
    background-color: #eee;
    color: black;
    display: block;
    padding: 12px;
    text-decoration: none;
  .vertical-menu a:hover {
    background-color: #ccc;
  .vertical-menu a.active {
    background-color: #4CAF50;
    color: white;
```

```
label
    font-size: 18px;
fieldset
{ border-style:double;
    border-width: 5px;
    border-color:indianred;
input[type="text"]
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 100%;
    color:black;
input[type="password"]
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 100%;
    color:black;
select
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 25%;
    color:black;
textarea
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 100%;
    color:black;
```

```
input[type="submit"]
    margin-top: 5px;
    padding: 10px;
    border-width: 2px;
    border-color: brown;
    width: 100%;
    color:blue;
    text-align:center;
    font-size: 15px;
    align-items: center;
    align-self: center;
    align-content: center;
input[type="file"]
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 25%;
    color:blue;
    text-align:center;
    font-size: 15px;
    align-items: center;
    align-self: center;
input[type="date"]
    padding: 10px;
    border-style:double;
    border-width: 2px;
    border-color: brown;
    width: 100%;
    color:black;
input[type="time"]
    padding: 10px;
    border-style:double;
    border-width: 2px;
```

```
border-color: brown;
    width: 100%;
    color:black;
body
    margin-top: 50px;
    margin-left: 400px;
    margin-bottom: 70px;
    margin-right: 400px;
    align-items: center;
    align-self: center;
    background-image: url(tech3.jpg);
ul {
    list-style-type: none;
    margin: 0;
    padding: 0;
    overflow: hidden;
```

> FRONTEND

```
<h3>EVENT</h3>
                 <h3>Event id:</h3><input type="text" name="eventid" placeholder="ent</pre>
er your eventid in numbers"/>
                 <?php
if(isset($_GET['error']))
echo $_GET['error'];
                 <h3>Event name:</h3><input type="text" name="ename" placeholder="ent</pre>
er here"/>
                 <h3>Event venue:</h3><input type="text" name="evenue" placeholder="e
nter here"/>
                 <h3>Date:</h3><input type="date" name="edate" placeholder="enter her</pre>
                 <h3>Time:</h3><input type="time" name="etime" placeholder="enter her</pre>
e "/>
                 <h3>Chief Guest:</h3><input type="text" name="echief" placeholder="e</pre>
nter here "/>
                 <h3>Speaker:</h3><input type="text" name="espeaker" placeholder="ent</pre>
er here"/>
                 <h3>Sponsor:</h3><input type="text" name="esponsor" placeholder="ent
er here"/>
                 <h3>Prizes:</h3><input type="text" name="eprize" placeholder="enter</pre>
here"/>
                 <h3>Certifications:</h3><input type="radio" name="ecert" value="Yes"</pre>
/>Yes<br/>
                 <input type="radio" name="ecert" value="No"/>No<br/>>
                 <input type="submit" value="submit"/>
            </form>
        </fieldset>
    </div>
```

The above are the sample codes of frequent functions in the system slight changes are made and used for the other functions.