Application-specific access policies using Zscaler Private Access (ZPA)

Application-specific access policies using Zscaler Private Access (ZPA)

List of Team Members:

S.No	Name	College Name	Contact
1	Priyadharshini.R	Sri Ramakrishna College of Arts and Science for Women	srcw2322k141@srcw.ac.in
2	Kirthika.R	Sri Ramakrishna College of Arts and Science for Women	srcw2322k123@srcw.ac.in
3	Mahaboobani.M	Sri Ramakrishna College of Arts and Science for Women	srcw2322k125@srcw.ac.in
4	Madhula.M	Sri Ramakrishna College of Arts and Science for Women	srcw2322k127@srcw.ac.in

Project Details

Title:

Application-specific access policies using Zscaler Private Access (ZPA).

Overview:

In today's digital environment, organizations are increasingly adopting cloud services, remote work models, and distributed networks. Traditional network security models such as Virtual Private Networks (VPNs) and perimeter-based security approaches are becoming less effective in protecting enterprise applications. These traditional systems provide broad network access once a user is authenticated, which can expose internal resources to potential cyber threats. To address these security challenges, modern organizations are shifting towards the Zero Trust security model, which ensures that no user or device is trusted by default and access is granted only after proper verification.

This project focuses on implementing application-specific access policies using Zscaler Private Access (ZPA), a cloud-based Zero Trust Network Access (ZTNA) solution developed by Zscaler. ZPA enables secure remote access to internal applications without exposing the corporate network to the internet. Instead of providing full network access, ZPA allows users to connect only to the specific applications they are authorized to access. This approach significantly reduces the attack surface and improves overall network security.

The main goal of this project is to demonstrate how organizations can configure and enforce granular access policies that allow users to securely access internal applications based on identity, role, and predefined security conditions. Through ZPA, administrators can define policies that determine which users or groups can access specific applications. These policies are enforced using various parameters such as user identity, device status, application segments, and authentication mechanisms.

In this project, the ZPA platform is used to create secure connections between users and private applications hosted in a data center or cloud environment. Unlike traditional VPN solutions, ZPA does not place users directly onto the corporate network. Instead, it establishes a brokered connection through the Zscaler cloud platform, which ensures that the user and the application remain invisible to each other until access is verified. This architecture eliminates the possibility of unauthorized lateral movement within the network.

Another important feature explored in this project is the concept of Application Segmentation. Applications are grouped into segments, and access policies are applied to those segments based on organizational requirements. This allows administrators to implement least-privilege access, ensuring users only receive the minimum level of access required to perform their tasks. For example, an employee from the Human Resources department may only access HR applications, while a developer may access development servers or internal tools.

The project also highlights how ZPA integrates with identity providers and authentication systems to verify user identity before granting access. By integrating with directory services such as Active Directory or other identity management systems, organizations can ensure that only authenticated and authorized users are able to access sensitive applications. Additionally, device posture checks can be used to verify that the device meets security requirements before allowing access.

The implementation process involves configuring several components within the ZPA environment. These components include application connectors, application segments, access policies, and user authentication settings. Application connectors are lightweight virtual machines deployed within the organization's network that establish outbound connections to the Zscaler cloud. These connectors allow secure communication between the user and the private application without opening inbound firewall ports.

One of the major advantages demonstrated in this project is the ability of ZPA to protect internal applications from direct internet exposure. Since applications are never directly published to the internet, attackers cannot detect or scan them. This significantly reduces the risk of cyberattacks such as unauthorized access, data breaches, and network infiltration. Furthermore, ZPA provides detailed visibility into user activity, allowing administrators to monitor and control access effectively.

The project also emphasizes the importance of policy-based access control in modern cybersecurity strategies. By implementing application-specific policies, organizations can enforce strict access control measures that align with security best practices. These policies can be dynamically adjusted based on changing organizational needs, making the system flexible and scalable.

Overall, this project demonstrates how Zscaler Private Access (ZPA) can be used to implement a secure, scalable, and efficient method for accessing internal applications. By adopting a Zero Trust approach and enforcing application-level access policies, organizations can significantly enhance their security posture while still providing seamless and secure access to authorized users.

The successful implementation of application-specific access policies using ZPA proves that modern cloud-based security solutions can effectively replace traditional VPN-based systems. This approach not only improves security but also simplifies network management and supports the growing demand for remote access in today's digital workplaces.

Abstract

Zscaler Private Access is a cloud-based security solution designed to provide secure and application-specific access to internal resources without exposing the network to the internet. This project focuses on implementing application-specific access policies using ZPA to ensure that users can only access the applications they are authorized to use.

The system follows a Zero Trust architecture, where every user and device must be verified before gaining access to an application. Instead of giving full network access like traditional VPNs, ZPA connects users directly to specific applications based on defined policies such as user identity, device posture, and location.

By enforcing granular access control, the solution improves security, reduces the risk of unauthorized access, and protects sensitive organizational data. It also enhances performance and scalability because applications remain hidden from the public internet. This approach helps organizations maintain a secure and flexible remote access environment while ensuring that only authenticated and authorized users can access critical resources.

Use Case Scenarios:

Use Case Scenario 1: Secure Remote Employee Access

An employee working from home needs to access an internal company application such as an HR portal. Instead of connecting through a traditional VPN, the employee uses ZPA to securely access only the required application.

Output:

- The user is authenticated using company identity credentials.
- Access is granted only to the specific HR application.
- The internal network remains hidden from the user.
- A secure connection is established through the ZPA cloud platform.

Use Case Scenario 2: Role-Based Access Control

Different departments within an organization require access to different applications. For example, finance employees need access to financial systems, while developers need access to development access.

Output:

- Access policies are defined based on user roles or groups.
- Each department can only access its authorized applications.
- Unauthorized access to other applications is automatically blocked.
- Security policies ensure least-privilege access control.

Use Case Scenario 3: Third-Party Vendor Access

A third-party vendor requires temporary access to a specific internal application for maintenance or support purposes.

Output:

- Vendor access is restricted to a single authorized application.
- The vendor cannot view or access the internal network.

- Access can be time-limited or revoked at any time.
- All access activities are monitored and logged.

Use Case Scenario 4:

Secure Access from Untrusted Networks

An employee connects to the company application using a public Wi-Fi network at an airport or café.

Output:

- The user must complete identity verification before access is granted.
- A secure encrypted connection is created between the user and the application.
- Sensitive applications remain protected from public network threats.
- The organization maintains full visibility of user activity.

Use Case Scenario 5: Device-Based Access Control

The organization allows application access only from company-approved devices that meet security requirements.

Output:

1. Device posture checks verify security compliance.
2. Access is granted only to trusted devices.
3. Non-compliant or unknown devices are blocked automatically.
4. Security policies protect applications from risky endpoints.

Stage-1

Title:

Application-specific access policies using Zscaler Private Access (ZPA).

Overview:

Zscaler Private Access is a cloud-based security service that provides secure access to internal applications without exposing the organization's network to the internet. It is designed to replace traditional VPN solutions by offering application-specific access instead of full network access. This helps organizations protect sensitive resources while allowing employees to work from anywhere.

Application-specific access policies allow administrators to define rules that control which users can access particular applications. These policies are created based on factors such as user identity, role, device security status, and location. Only authenticated and authorized users are allowed to connect to the required application, ensuring better security and controlled access.

ZPA works based on the Zero Trust Security Model, where every request for access must be verified before it is granted. Instead of connecting users to the entire network, ZPA creates a secure connection between the user and the specific application, which reduces the risk of unauthorized access and cyberattacks.

By using application-specific access policies with ZPA, organizations can improve security, protect internal applications, and provide safe remote access for employees. This approach is especially useful for modern organizations that rely on cloud applications, remote work environments, and secure digital infrastructure

Another important aspect of Zscaler Private Access is its ability to provide centralized policy management and monitoring. Administrators can easily create, update, and manage application access policies from a single cloud-based dashboard. This helps organizations maintain better control over user access, track activity, and quickly respond to potential security threats while ensuring that only authorized users can access internal applications.

Zscaler Private Access is that it reduces the attack surface of the organization's network. Since applications are not directly exposed to the internet, unauthorized users and attackers cannot easily discover or access them. This improves the overall security posture and helps protect critical business applications from cyber threats while maintaining secure connectivity for legitimate users.

List of Team Members:

S.No	Name	College Name	Contact
1	Priyadharshini.R	Sri Ramakrishna College of Arts and Science for Women	srcw2322k141@srcw.ac.in
2	Kirthika.R	Sri Ramakrishna College of Arts and Science for Women	srcw2322k123@srcw.ac.in
3	Mahaboobani.M	Sri Ramakrishna College of Arts and Science for Women	srcw2322k125@srcw.ac.in
4	Madhula.M	Sri Ramakrishna College of Arts and Science for Women	srcw2322k127@srcw.ac.in

List of Vulnerability Name:

S.No	Category Name	Vulnerability	CWE-No
1	Broken Access Control	Exposure of Sensitive Information to an Unauthorized Actor	CWE-200
2	Security Misconfiguration	Cleartext Storage of Sensitive Information in a Cookie	CWE-315
3	Software Supply Chain Failures	Unimplemented or Unsupported Feature in UI	CWE-447
4	Cryptographics Failure	Reusing a Nonce, Key Pair in Encryption	CWE-323
5	Injection	Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)	CWE-80
6	Insecure Design	Missing Encryption of Sensitive Data	CWE-311
7	Authentication Failures	Reliance on IP Address for Authentication	CWE-291
8	Software or Data Intergrity Failures	Embedded Malicious Code	CWE-506
9	Security Loggings and Alerting Failures	Information Loss or Omission	CWE-221
10	Mishandling of Exceptional Conditions	Improper Handling of Insufficient Privileges	CWE-274

REPORT

1.Vulnerability Name: Exposure of Sensitive Information to an Unauthorized Actor

CWE/CVE: CWE-200

OWASP Category: A01:2025 Broken Access Control

Description: Exposure of sensitive information occurs when confidential or private data is accessed by someone who does not have permission. This may happen due to weak security systems, human error, or cyberattacks. Sensitive information can include passwords, personal details, financial records, or company data. Such exposure can lead to privacy violations, identity theft, and financial loss. Therefore, proper security measures must be implemented to protect important information.

Business Impact: Exposure of sensitive information can cause serious damage to an organization. It may lead to financial losses, legal penalties, and loss of customer trust. The company's reputation can also be affected if confidential data is leaked. In severe cases, it can result in business disruption and reduced market value.

Steps to Reproduce:



Recommendations:

1. Implement strong access control to ensure only authorized users can access sensitive information.
2. Use encryption to protect confidential data during storage and transmission.
3. Regularly update and patch software systems to fix security vulnerabilities.
4. Provide cybersecurity awareness training to employees to prevent accidental data leaks.
5. Monitor and audit systems regularly to detect and respond to unauthorized access quickly.

2. Vulnerability Name: Cleartext Storage of Sensitive Information in a Cookie

CWE/CVE: CWE-315

OWASP Category: A02:2025 Security Misconfiguration

Description: Cleartext storage of sensitive information in a cookie occurs when important data is stored in a browser cookie without encryption. This means the information can be easily read by anyone who accesses the cookie. Sensitive data such as session IDs, passwords, or personal details may be exposed. This vulnerability can allow attackers to steal user information and misuse it.

Business Impact: Storing sensitive information in cookies in cleartext can lead to unauthorized access to user accounts. Attackers may steal personal or financial data, causing security breaches. This can damage the organization's reputation and reduce customer trust. It may also result in financial losses and legal consequences for the company.

Steps to Reproduce:



Recommendations:

1. Avoid storing sensitive information such as passwords or personal data in cookies.
2. Encrypt cookie data to protect it from unauthorized access.
3. Use secure cookie attributes like Secure and Http Only to improve protection.
4. Implement proper session management instead of storing sensitive data in cookies.
5. Regularly review and test web applications to identify and fix security vulnerabilities.

3. Vulnerability Name: Unimplemented or Unsupported Feature in UI

CWE/CVE: CWE-447
OWASP Category: A03:2025 Software Supply Chain Failures

Description: An unimplemented or unsupported feature in the user interface occurs when a function or option is displayed in the UI but does not work as intended. Users may see buttons, links, or menus that are not properly developed or supported by the system. This can cause confusion and reduce the usability of the application. It may also lead to errors or unexpected behaviour when users try to access these features.

Business Impact: Unimplemented or unsupported features in the user interface can reduce user satisfaction and trust in the application. Users may become frustrated when features do not work as expected. This can damage the organization's reputation and affect customer retention. It may also lead to increased support requests and maintenance costs.

Steps to Reproduce:



Recommendations:

1. Remove or hide features in the UI that are not yet implemented or supported.
2. Clearly label features that are still under development.
3. Perform proper testing before releasing the application to users.
4. Ensure communication between developers and UI designers to avoid displaying incomplete features.
5. Regularly review and update the UI to ensure all features work correctly and provide a good user experience.

4.Vulnerability Name: Reusing a Nonce, Key Pair in Encryption

CWE/CVE:CWE-323

OWASP Category: A04:2025 Cryptographic Failures

Description: Reusing a nonce or key pair in encryption happens when the same cryptographic key or random number (nonce) is used for multiple encryption operations. This weakens the security of the encrypted data, making it easier for attackers to uncover the original information. Nonces and keys are meant to be unique for each operation to ensure data confidentiality. Reusing them can lead to data leaks, replay attacks, or compromise of sensitive information.

Business Impact: Reusing a nonce or key pair in encryption can compromise the confidentiality and integrity of sensitive business data. It may allow attackers to decrypt confidential information, leading to financial loss and data breaches. Customer trust and the company's reputation can be severely damaged. Regulatory penalties may also apply if sensitive data protection laws are violated.

Steps to Reproduce:



Recommendations:

1. Always generate a unique nonce for each encryption operation.
2. Avoid reusing cryptographic keys; rotate keys regularly.
3. Implement strong key management practices to securely store and handle keys.
4. Use well-tested encryption libraries and follow recommended cryptographic standards.
5. Regularly audit encryption processes to detect and prevent reuse of keys or nonces.

5. Vulnerability Name: Improper Neutralization of Script-Related HTML Tags in a Web Page (Basic XSS)

CWE/CVE: CWE-80

OWASP Category: A05:2025 Injection

Description: This vulnerability occurs when a web page fails to properly sanitize or encode user input containing HTML or script tags. As a result, attackers can inject malicious scripts into the web page, which are then executed in other users' browsers. This is commonly known as Cross-Site Scripting (XSS). It can lead to theft of session cookies, sensitive information, or unauthorized actions performed on behalf of users.

Business Impact: Improper neutralization of script-related HTML tags can lead to data theft, account hijacking, and unauthorized actions on the web application. It damages customer trust and the organization's reputation. Businesses may also face financial losses, regulatory penalties, and increased support costs due to security breaches. Repeated incidents can result in long-term loss of users and market credibility.

Steps to Reproduce:



Recommendations:

1. Properly sanitize and encode all user inputs before displaying them on web pages.
2. Use security libraries or frameworks that automatically prevent XSS attacks.
3. Implement Content Security Policy (CSP) to restrict execution of untrusted scripts.
4. Validate input on both client-side and server-side to ensure only safe content is accepted.
5. Regularly test web applications using automated and manual security testing for XSS vulnerabilities.

6.Vulnerability Name: Missing Encryption of Sensitive Data

CWE/CVE: CWE-311

OWASP Category: A06:2025 Insecure Design

Description: Missing encryption of sensitive data occurs when important information, such as passwords, financial details, or personal records, is stored or transmitted in plain text without any cryptographic protection. This makes it easy for attackers to access, read, or steal the data if they gain access to the system or network. Without encryption, confidential information is exposed to unauthorized users, increasing the risk of data breaches and privacy violations

Business Impact: Missing encryption of sensitive data can lead to data breaches, identity theft, and financial loss. It undermines customer trust and damages the organization's reputation. Non-compliance with data protection regulations may result in legal penalties and fines. It can also increase operational costs due to incident response and remediation efforts.

Steps to Reproduce:



Recommendations:

1. Always encrypt sensitive data at rest using strong algorithms like AES-256.
2. Ensure data in transit is protected using secure protocols such as **HTTPS** or **TLS**.
3. Implement robust key management to securely generate, store, and rotate encryption keys.
4. Regularly audit and monitor systems to verify that all sensitive data is encrypted.
5. Train developers and staff on secure data handling and the importance of encryption

7. Vulnerability Name: Reliance on IP Address for Authentication

CWE/CVE: CWE-291

OWASP Category: A07:2025 Authentication Failures

Description: Relying on IP addresses for authentication occurs when a system grants access or verifies a user based solely on their IP address. This method is insecure because IP addresses can be **spoofed, shared, or changed** by attackers. It does not reliably confirm the identity of a user, leaving systems vulnerable to unauthorized access. Such reliance can compromise sensitive information and reduce overall security.

Business Impact: Relying on IP addresses for authentication can lead to **unauthorized access** to sensitive systems and data. Attackers may exploit this weakness to steal information, perform fraudulent activities, or disrupt business operations. This can damage the organization's **reputation, customer trust, and lead to financial losses**. It may also result in **regulatory penalties** if data protection standards are violated.

Steps to Reproduce:



Recommendations:

1. Avoid using IP addresses as the sole method of authentication.
2. Implement strong authentication mechanisms such as **multi-factor authentication (MFA)**.
3. Use session tokens or secure cookies to validate user identity instead of IP-based checks.
4. Monitor and log suspicious login attempts for unusual locations or patterns.
5. Regularly review and update access control policies to ensure secure authentication practices.

8. Vulnerability Name: Embedded Malicious Code

CWE/CVE: CWE-506

OWASP Category: A08:2025 Software or Data Integrity Failures

Description: Embedded malicious code refers to harmful software or scripts that are hidden within legitimate applications, files, or web pages. When executed, this code can compromise system security, steal sensitive information, or disrupt normal operations. It is often delivered through downloads, email attachments, or compromised websites. Such code can be difficult to detect and can lead to significant security breaches if not properly managed.

Business Impact: Embedded malicious code can lead to **data theft, system compromise, and operational disruption**. It can damage the organization's reputation and erode customer trust. Businesses may face **financial losses, legal penalties, and regulatory non-compliance**. Cleanup and recovery from such attacks can also be costly and time-consuming.

Steps to Reproduce:

Recommendations:

1. Use reputable antivirus and anti-malware solutions to detect and remove malicious code.
2. Regularly update software and systems to patch security vulnerabilities.
3. Scan all files, downloads, and email attachments before use.
4. Educate employees about safe browsing, downloading, and email practices.
5. Implement code reviews and security testing to detect hidden malicious code in applications.

9.Vulnerability Name: Information Loss of Omission

CWE/CVE: CWE-221

OWASP Category: A09:2025 Security Logging & Alerting Failures

Description: Information loss or omission occurs when important data is accidentally deleted, corrupted, or not recorded in a system. This can happen due to software errors, human mistakes, system crashes, or inadequate data handling processes. Missing or incomplete information can lead to inaccurate decision-making, operational issues, and reduced reliability of business records. Ensuring proper data management is essential to prevent such problems.

Business Impact: Information loss or omission can cause **operational disruptions, poor decision-making, and financial losses**. It may lead to **inaccurate reporting, regulatory non-compliance, and damaged customer trust**. Businesses could also face **increased costs for data recovery and remediation**, along with long-term reputational damage.

Steps to Reproduce:



Recommendations:

1. Implement regular **data backups** and ensure they are securely stored.
2. Use data validation and error-checking mechanisms to prevent accidental omissions.
3. Maintain proper **audit trails** to track data changes and deletions.
4. Train employees on accurate data entry and handling practices.
5. Use reliable and fault-tolerant systems to minimize the risk of data loss or corruption.

10. Vulnerability Name: Improper Handling of Insufficient Privileges

CWE/CVE: CWE-274

OWASP Category: A10:2025 Mishandling of Exceptional Conditions

Description: Improper handling of insufficient privileges occurs when a system fails to correctly enforce access controls. Users may gain access to functions, data, or operations they are not authorized to use. This can happen due to coding errors, misconfigured permissions, or inadequate security checks. Such flaws can lead to unauthorized data access, privilege escalation, and potential system compromise, putting sensitive information and critical operations at risk.

Business Impact: Improper handling of insufficient privileges can result in **unauthorized access to sensitive data or critical systems**. It may lead to **data breaches, financial loss, and operational disruption**. The organization's reputation and customer trust can be severely affected. Additionally, non-compliance with regulatory requirements may result in **legal penalties**.

Steps to Reproduce:



Recommendations:

1. Implement strict **role-based access control (RBAC)** to enforce proper privileges.
2. Validate user permissions on both client-side and server-side before granting access.
3. Regularly audit and review access rights to ensure users have only necessary privileges.
4. Use logging and monitoring to detect unauthorized access attempts.
5. Train developers and administrators on secure coding and proper access control practices.

Stage-2

Overview: -

An overview of a Nessus scan typically involves the following key steps and aspects:

1. Preparation: Define Objectives: Determine the scope and objectives of the scan. What systems or networks

do you want to assess, and what specific vulnerabilities are you looking for?

System Access: Ensure that you have the necessary permissions and access rights to scan the target systems

or networks.

2. Configuration: Set Up Scan Policy: Create a scan policy that defines the parameters of the scan, such as the

types of vulnerabilities to check for, scanning frequency, and specific configurations.

Define Target Assets: Specify the IP addresses, hostnames, or network ranges of the systems you want to scan.

3. Scanning: Initiate Scan: Start the Nessus scan using the configured policy and target assets. Nessus will

systematically scan the target systems for vulnerabilities based on its plugins and policies.

4. Vulnerability Identification: Nessus performs a comprehensive assessment, checking for vulnerabilities,

misconfigurations, open ports, and other security issues. As the scan progresses, it categorizes vulnerabilities

by severity, making it easier to prioritize remediation efforts.

5. Reporting: Nessus generates detailed reports that list the vulnerabilities discovered during the scan. Reports

typically include information about the severity of each vulnerability, recommended actions for remediation,

and supporting evidence. These reports can be customized and exported in various formats, such as PDF,

HTML, or CSV.

6. Remediation: Review Findings: IT and security teams review the Nessus scan reports to prioritize and

address the identified vulnerabilities.

Remediation Steps: Take corrective actions to fix or mitigate the vulnerabilities. This may involve applying

patches, changing configurations, or implementing security measures.

7. Follow-up: Regular Scanning: Conduct periodic Nessus scans to continuously monitor the security posture of

the systems and networks. This helps identify new vulnerabilities and track progress in mitigating existing

ones.

Integration: Integrate Nessus with other security tools or workflows to automate the vulnerability

management process and streamline the response to new findings.

8. Compliance Auditing (if applicable): If compliance checks are part of your scan policy, review compliance

results and take actions to ensure systems meet the required standards and regulations.

9. Documentation: Maintain records of scan results, remediation efforts, and compliance checks for audit and

reporting purposes.

10. User Training: Ensure that your IT and security teams are trained in using Nessus effectively and interpreting

scan results.

Nessus scans are a critical component of proactive security, helping organizations identify and address

vulnerabilities in their IT infrastructure to reduce the risk of security breaches and data compromises. The

frequency and depth of scans can vary depending on an organization's security strategy and requirements.

Nessus is a popular vulnerability scanning tool used for identifying security weaknesses in computer systems

and networks. It is widely utilized by security professionals and organizations to assess the security posture of

their systems and to proactively identify potential vulnerabilities that could be exploited by attackers. Here's what

I understand about Nessus scans:

1. Vulnerability Assessment: Nessus performs a vulnerability assessment by scanning target systems or

networks to identify security issues, such as missing patches, misconfigurations, weak passwords, and

other potential weaknesses that could be exploited by attackers.

2. Network Scanning: Nessus can scan a wide range of network devices, including servers, routers, switches,

firewalls, and more. It examines network services, open ports, and software running on target systems.

3. Plugin Architecture: Nessus uses a plugin-based architecture, allowing it to check for a wide variety of

vulnerabilities. These plugins are regularly updated to include the latest security checks and support for

new vulnerabilities.

4. Compliance Auditing: It can also be used to assess systems against various compliance standards and

regulatory requirements, helping organizations ensure that their systems meet specific security

standards, like PCI DSS or CIS benchmarks.

5. Customization: Nessus scans can be customized to suit the specific needs of an organization. Users can

define scan policies, select the target systems, and specify the types of vulnerabilities to scan for.

6. Reporting:Nessus provides detailed reports that highlight vulnerabilities, their severity, and remediation

recommendations. These reports are essential for IT and security teams to prioritize and address

vulnerabilities.

7. Scanning Frequency: Organizations often perform regular Nessus scans to continuously monitor and

improve their security posture. This is crucial for staying ahead of evolving threats and vulnerabilities.

8. Integration: Nessus can be integrated with other security tools and platforms, allowing organizations to

automate the scanning process and streamline their vulnerability management.

9. Licensing:Nessus offers both free and commercial versions. The free version is limited in its functionality,

while the commercial version provides more features and support.

10. User-Friendly Interface: Nessus offers an easy-to-use web-based interface, making it accessible to a wide range of users, from security experts to less experienced IT professionals. It's important to note that Nessus is a valuable tool for identifying vulnerabilities, but it doesn't fix these vulnerabilities itself. It's up to the organization's IT and security teams to take the necessary steps to remediate the identified issues to enhance their security.

S. No	Vulnerability Name	Severity	Plugins
1.	Cross-site scripting (stored)	Low	Web application Scanner
2.	Broken Access Control	Medium	SSH weakHMAC Algorithms Supported
3.	SQL Injection	Medium	N/A
4.	Broken Authentication	Low	HSTS Missing from Server
5.	Insecure Direct Object Reference	Info	Service Detection
6.	Security Misconfiguration	Low	SSL cipher Block Chaining cipher suites
7.	Cross-Site Request Forgery	Low	HTTP Form- Based Authentication Detected
8.	Cleartext Transmission of Sensitive Information	Medium	Cleartext Transmission ofSensitive Information over HTTP
9.	ClickJacking	Info	HTML Rendering Layer Vulnerability

10.	webserver allows password auto completion	Low	SSL/TLS Diffie-Hellman Modulus<=1024 bits(Logjam)

Low SSL/TLS Diffie-Hellman

Modulus<=1024 bits(Logjam)

Target Website: testfire.net

Target IP Address: 54.83.41.36

Report:

1. VULNERABILITY NAME: Cross site scripting (stored)

SEVERITY: Low

PLUGIN: web application scanner

PORT: N/A

DESCRIPTION: It occurs when a malicious script is injected directly into a vulnerable web

application. Reflected XSS involves the reflection of a malicious script of a web application, onto a

user's browser.

SOLUTION:

• When interacting with databases, use parameterized statements or prepared statements to

avoid SQL injection, which can be a vector for XSS.

• Sanitize and validate all user inputs and ensure that any data displayed on the web page

properly encoded. Use output encoding libraries or functions to prevent script injection.

BUSINESS IMPACT: The application stores dangerous data in a database, message forum, visitor

log, or other trusted data store. Later, the dangerous data is subsequently read back into the

application and included in dynamic content. From an attacker's perspective, the optimal place to

inject malicious content is in an area that is displayed to either many users or particularly

interesting users. Interesting users typically have elevated privileges in the application or interact

with sensitive data that is valuable to the attacker. If one of these users executes malicious content,

the attacker may be able to perform privileged operations on behalf of the user or gain access to

sensitive data belonging to the user.

2. VULNERABILITYNAME: Broken access control

SEVERITY: medium

PLUGIN:SSH weakHMAC Algorithms supported

PORT: N/A

DESCRIPTION: When access control checks are not applied consistently - or not at all - users are

able to access data or perform actions that they should not be allowed to perform. This can lead to

a wide range of problems, including information exposures, denial of service, and arbitrary code

execution.

SOLUTION:

Ensure that the application has a robust authentication and authorization mechanism in place. Users should be authenticated before any sensitive actions are performed, and authorization checks should be conducted to verify that users have the necessary permissions for the requested operation.

• Ensure that session management is secure. Use strong session IDs, enforce session timeouts, and regenerate session tokens after login. Implement session fixation protection to prevent session hijacking.

BUSINESS IMPACT: wide-ranging business impact, including financial losses, reputation damage,legal consequences, operational disruption, and loss of customer trust. Addressing this vulnerability is crucial to protect the organization and its stakeholders from these potential negative effects.

3. VULNERABILITY NAME: SQL injection

SEVERITY: medium

PLUGIN: N/A (typically would be a security testing tool)

PORT: port 80/443

DESCRIPTION: The product constructs all or part of an SQL command using externally influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended SQL command when it is sent to a downstream component.

SOLUTION:

• If parameterized statements are not feasible, use proper input validation and escaping mechanisms to sanitize user inputs before they are used in SQL queries. This helps prevent malicious code injection.

• Utilize stored procedures for database operations. This can help separate SQL code from application code and reduce the risk of SQL injection.

• Implement strict input validation for all user inputs, ensuring that data adheres to the expected format and structure.

BUSINESS IMPACT: In summary, it is crucial to underscore that CWE-89, known as SQL Injection,can exert a profound and diverse business impact. This encompasses critical facets such as databreaches, financial setbacks, harm to reputation, legal ramifications, and operational turmoil. Hence, the imperative of preventing and remedying SQL injection vulnerabilities cannot be overstated,

as it is indispensable for fortifying the security and continuity of an organization'sapplications and data.

4. VULNERABILITYNAME: Broken authentication

SEVERITY: Low

PLUGIN: HSTS Missing from HTTPS Server (plugin id:142960)

PORT: port 443

DESCRIPTION: The system's authorization functionality does not prevent one user from gaining access to another user's data or record by modifying the key value identifying the data.

SOLUTION:

• Implement strong authentication mechanisms, such as multi-factor authentication (MFA) or two-factor authentication (2FA), to ensure that only authorized users can access the system.

• Implement proper authorization controls to ensure that users have the necessarypermissions to access specific functions or data. Use role-based access control (RBAC) to manage user privileges effectively.

• Deploy intrusion detection and prevention systems (IDS/IPS) to monitor and block suspicious activities related to authentication and authorization.

BUSINESSIMPACT: To effectively mitigate the business impact of CWE-285, it is imperative that organizations place a strong emphasis on bolstering their authentication and session management practices. This should encompass the adoption of multi-factor authentication, the secure storage of credentials, meticulous session handling, and a commitment to conducting routine security assessments and testing. The rectification of these vulnerabilities stands as a critical imperative, safeguarding sensitive data, user identities, and the organization's overarching security stature and reputation.

5. VULNERABILITYNAME: Insecure Direct object Reference

SEVERITY: Info

PLUGIN:Service Detection (plugin id:22964)

PORT: port 80/443

DESCRIPTION: Insecure Direct Object Reference (IDOR) is a vulnerability that arises when attackers can access or modify objects by manipulating identifiers used in a web application's URLs or parameters. It occurs due to missing access control checks, which fail to verify whether a user should be allowed to access specific data.

SOLUTION:

• Utilize parameterized queries or prepared statements when interacting with databases. This prevents user-controlled input from being executed as SQL code.

• Implement a Content Security Policy to mitigate the risk of cross-site scripting (XSS) attacks,

which can be used to execute unauthorized queries.

• Implement account lockout mechanisms that temporarily suspend accounts after a specified

number of unauthorized access attempts to prevent brute force attacks.

BUSINESS IMPACT: To effectively mitigate the business impact of CWE-639, organizations must make it a top priority to fortify their access control and authorization mechanisms. This entails the implementation of robust security measures, the regular conduct of comprehensive security assessments, and the deployment of intrusion detection systems to promptly identify and counter unauthorized access attempts. These measures stand as critical in the defence of sensitive data, the overall security of systems, and the preservation of the organization's esteemed reputation.

6. VULNERABILITY NAME: Security Misconfiguration

SEVERITY: low

PLUGIN: SSL cipher Block chaining cipher suites

PORT: port 443

DESCRIPTION: The product specifies permissions for a security-critical resource in a way that allows that resource to be read or modified by unintended actors.

SOLUTION:

• Implement a change management process to document and review all changes to system configurations. This helps prevent unauthorized or unintended alterations.

• Follow security guidelines provided by software and hardware vendors to ensure secure configurations.

• Regularly perform compliance checks against industry standards and regulations to ensure that configurations remain in compliance with security requirements.

BUSINESS IMPACT: To effectively lessen the business consequences stemming from CWE-732, organizations must place a strong emphasis on bolstering their configuration management practices. This involves the establishment of secure default settings, the routine conduct of comprehensive security evaluations, and the deployment of intrusion detection systems to promptly detect and address misconfigurations and vulnerabilities. These actions are of paramount importance in safeguarding sensitive data, fortifying system security, and preserving the organization's esteemed reputation.

7. VULNERABILITYNAME: Cross-Site Request Forgery

SEVERITY: Low

PLUGIN:HTTP Form-Based Authentication Detected

PORT: port 8080/443

DESCRIPTION: Cross-Site Request Forgery (CSRF) is an attack that forces an end user to execute unwanted actions on a web application in which they’re currently authenticated. With a little help of social engineering (such as sending a link via email or chat), an attacker may trick the users of aweb application into executing actions of the attacker’s choosing. If the victim is a normal user, a successful CSRF attack can force the user to perform state changing requests like transferring funds, changing their email address, and so forth. If the victim is an administrative account, CSRF can compromise the entire web application.

SOLUTION:

• Implement Synchronizer Token Patterns to include unique, randomly generated tokens in each HTTP request and validate these tokens on the server side to verify the authenticity of the request.

• Utilize the Same Site attribute in cookies to restrict their usage to same-site requests only, preventing them from being sent along with cross-site requests and effectively mitigating CSRF attacks.

• Utilize framework-specific protections and security features to prevent CSRF attacks. Many modern web frameworks have built-in mechanisms and libraries for handling CSRF vulnerabilities effectively.

• Implement a Content Security Policy to restrict the sources from which various types of content can be loaded. By specifying the trusted sources of content, you can minimize the risk of malicious code execution and reduce the likelihood of successful CSRF attacks.

BUSINESS IMPACT: To effectively reduce the business repercussions of CWE-352, organizations must prioritize secure coding practices, including the incorporation of anti-CSRF tokens, while also conducting routine security assessments and testing to detect and rectify CSRF vulnerabilities. Furthermore, educating users on secure browsing practices is pivotal in preventing CSRF attacks.

These actions are of paramount importance in the protection of data and in upholding the trust of customers and partners.

8. VULNERABILITYNAME: Cleartext Transmission ofSensitive Information

SEVERITY: Medium

PLUGIN: Cleartext Transmission ofSensitive Information overHTTP

PORT: port 443

DESCRIPTION: The product transmits sensitive or security-critical data in cleartext in a communication channel that can be sniffed by unauthorized actors. Many communication channels can be "sniffed" (monitored) by adversaries during data transmission. For example, in networking, packets can traverse many intermediary nodes from the source to the destination, whether

across the internet, an internal network, the cloud, etc. Some actors might have privileged access to a network interface or any link along the channel, such as a router, but they might not be authorized to collect the underlying data. As a result, network traffic could be sniffed by adversaries, spilling security-critical data.

SOLUTION:

• Educate users and employees on secure data handling practices, such as recognizing secure websites (look for "https") and avoiding insecure Wi-Fi networks.

• Employ data masking or redaction techniques to replace sensitive data with placeholders or cryptographic representations during transmission.

• Implement encryption for data in transit. Use secure encryption protocols such as TLS/SSL to protect sensitive information during transmission.

• Use secure communication protocols for transmitting data, such as HTTPS for web applications, and ensure that the selected protocols are kept up to date.

BUSINESSIMPACT: To effectively reduce the business consequences associated with CWE-319, organizations must prioritize the adoption of secure data transmission practices. This includes the utilization of encryption and robust, secure protocols. The routine conduct of security assessments and testing is pivotal in pinpointing and remedying vulnerabilities linked to data transmission.

Furthermore, the education of users on secure data handling practices plays a vital role in proactively preventing data exposure incidents. These actions are of paramount importance in the protection of sensitive data and in preserving the trust of both customers and partners.

9. VULNERABILITY NAME: Clickjacking

SEVERITY: Info

PLUGIN:HTML Rendering Layer Vulnerability

PORT: port 80/443

DESCRIPTION: The web application does not restrict or incorrectly restricts frame objects or UI layers that belong to another application or domain,

which can lead to user confusion about which interface the user is interacting with.

SOLUTION:

• Set the X-Frame-Options HTTP response header to deny or same-origin to control how your site can be framed. This is supported by most modern browsers.

• Utilize frame-busting JavaScript code in web applications to prevent the embedding of your site within malicious frame's. This code can disrupt clickjacking attempts.

• Implement a Content Security Policy to restrict which domains can embed your site in iframes. This can help prevent unauthorized framing.

• Implement additional security controls to prevent UI redress attacks, such as clickjacking, within your web application.

BUSINESS IMPACT: To effectively reduce the business consequences resulting from CWE-1021, organizations must prioritize the implementation of protective measures, such as frame-bustin code. Simultaneously, educating users on safe browsing practices plays a crucial role in preventing clickjacking incidents. Additionally, routine security assessments and testing are pivotal for identifying and mitigating vulnerabilities associated with clickjacking. These actions are of paramount importance in upholding user trust, ensuring data protection, and safeguarding the organization's reputation.

10. VULNERABILITY NAME: web server allows password auto-completion

SEVERITY: Low

PLUGIN: SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

PORT: port 443

DESCRIPTION: Weaknesses in this category are related to the design and implementation of data confidentiality and integrity. Frequently these deal with the use of encoding techniques, encryption libraries, and hashing algorithms. The weaknesses in this category could lead to a degradation of the quality data if they are not addressed.

SOLUTION:

• Implement secure password storage mechanisms, such as using strong and salted cryptographic hashing algorithms like crypt or script.

• Implement robust encryption key management practices, including secure key storage, key rotation, and access controls.

• Utilize well-established and proven cryptographic libraries and algorithms for encryption and decryption.

• Use secure encryption protocols, like TLS/SSL, for data transmission over networks to protect data in transit

BUSINESS IMPACT: To effectively lessen the business consequences associated with CWE-310, organizations must prioritize the adoption of secure cryptographic practices. This entails ensuring proper password storage and robust encryption key management. Simultaneously, conducting routine security assessments and testing is pivotal in detecting and mitigating vulnerabilities related to cryptographic issues. Striving for compliance with pertinent data protection regulations and industry standards is equally essential. These actions are of paramount importance in the protection of sensitive data, the upholding of user trust, and the preservation of the organization's esteemed reputation.

Stage-3

Title: Application-specific access policies using Zscaler Private Access (ZPA)

Zero Trust Network Access (ZTNA):

It is a modern security framework designed to protect organizational networks by eliminating the traditional concept of trusted internal networks. Instead of automatically trusting users or devices inside a network, ZTNA follows the principle of "never trust, always verify." This means that every user, device, and application attempting to access a resource must be continuously authenticated and authorized, regardless of whether they are inside or outside the corporate network. ZTNA solutions typically use strong identity verification, device posture checks, and contextual policies (such as location or behavior) to grant limited, application-level access rather than full network access.

Zscaler Private Access (ZPA):

It is a cloud-based security solution that provides secure access to private applications without exposing them to the public internet. It is part of the **Zscaler** Zero Trust platform and is built on the principles of **Zero Trust Network Access (ZTNA)**. Instead of connecting users directly to a corporate network through traditional VPNs, ZPA creates a secure, brokered connection between authenticated users and specific internal applications. The system verifies the user's identity, device posture, and security policies before granting access, ensuring that users can only access the applications they are authorized to use.

Principle of Least Privilege:

The Principle of Least Privilege (PoLP) is a fundamental security concept that ensures users, applications, and systems are granted only the minimum level of access necessary to perform their required tasks. Instead of providing broad or unrestricted permissions, PoLP restricts access rights based on specific roles and responsibilities. This approach helps reduce the risk of accidental or intentional misuse of sensitive data, system errors, and security breaches. By limiting privileges, organizations can prevent attackers from gaining extensive control if

an account or system is compromised. The Principle of Least Privilege is widely used in modern cybersecurity frameworks, operating systems, and environment

Identity-Aware Access:

It is a security approach that controls access to applications, systems, and data based on the verified identity of a user or device. Instead of relying solely on network location or perimeter-based security, identity-aware access evaluates multiple identity-related factors such as user credentials, device status, location, and behavior before granting access to resources. This method ensures that only authenticated and authorized users can access specific applications or services according to defined security policies. Identity-aware access is commonly used in modern cloud and enterprise security architectures, especially within **Zero Trust Architecture**, where every access request is continuously verified.

Application-Specific Access Policies:

Application-Specific Access Policies are security rules that control how users and devices access individual applications within an organization's network. Instead of granting broad network-level access, these policies restrict users to only the specific applications they are authorized to use. Access decisions are typically based on factors such as user identity, role, device security posture, location, and organizational policies. This approach is commonly used in modern security frameworks like Zero Trust Architecture, where access is granted at the application level rather than to the entire network. By implementing application-specific access policies, organizations can minimize the risk of unauthorized access, reduce the potential attack surface, and ensure that sensitive applications and data remain protected while still allowing legitimate users to work efficiently

ZPA Architecture and Components:

1. Client Connector – The ZPA Client Connector is installed on user devices such as laptops or mobile phones. It authenticates the user and sends secure access requests to the Zscaler cloud when the user tries to access a private application.
2. Public Service Edge – This cloud component acts as a secure broker between the user and the application. It verifies user identity and enforces policies based on the Zero Trust Network Access model before allowing any connection

3. App Connector - The App Connector is deployed in the organization's data center or cloud environment. It establishes an outbound connection to the Zscaler cloud and securely connects authorized users to internal applications without exposing them to the internet
4. Admin Portal and Policy Engine – The Admin Portal allows administrators to configure access policies, manage users, and monitor activity. The Policy Engine evaluates each access request based on identity, device posture, and security rules before granting access.

Implementation Methodology:

Phase 1: Assessment and Planning – In this phase, the organization evaluates its existing network infrastructure, security requirements, and application environment. The goal is to identify which internal applications will be protected and determine how the **Zero Trust Network Access** model will be applied.

Phase 2: Design and Architecture – A detailed ZPA architecture is designed based on organizational needs. This includes defining user groups, application segments, access policies, and determining where components like App Connectors will be deployed.

Phase 3: Deployment of ZPA Components – The required components such as the ZPA Client Connector on user devices and App Connectors in the data center or cloud environment are installed and configured to establish secure connections with the Zscaler cloud.

Phase 4: Policy Configuration – Security policies are created to control access to applications. These policies are based on factors such as user identity, device posture, location, and the **Principle of Least Privilege** to ensure users access only authorized resources.

Phase 5: Testing and Validation – The configured environment is tested to verify that users can securely access authorized applications while unauthorized access is blocked. Performance, security policies, and connectivity are validated during this stage.

Phase 6: Monitoring and Optimization – After deployment, administrators continuously monitor the ZPA environment through the admin portal, analyze logs and user activity, and optimize policies to improve performance, security, and user experience.

Tools and Technologies:

- **Zscaler Private Access Platform** – The main cloud-based platform used to provide secure access to private applications using the **Zero Trust Network Access** model.
- **Zscaler Client Connector** – A lightweight agent installed on user devices that authenticates users and securely connects them to applications through the Zscaler cloud.
- **Zscaler Client Connector** – A lightweight agent installed on user devices that authenticates users and securely connects them to applications through the Zscaler cloud.
- **Active Directory / LDAP** – Used for user identity management and authentication by integrating organizational user directories with the ZPA platform.
- **SAML based Identity Providers (IdP)** – Technologies such as Okta, Microsoft Azure Active Directory, or Ping Identity are used for secure user authentication and single sign-on.
- **Cloud Platforms** – Private applications may be hosted on platforms such as Amazon Web Services, Microsoft Azure, or Google Cloud Platform, which integrate with ZPA for secure application access.
- **Security Protocols** – Technologies like TLS (Transport Layer Security) and HTTPS are used to encrypt communication between users, the Zscaler cloud, and internal applications.

Integration with Identity Providers:

The integration is typically done using secure authentication protocols such as Security Assertion Markup Language (SAML) or OpenID Connect (OIDC). When a user attempts to access a private application through ZPA, the request is redirected to the configured Identity Provider for authentication. Once the user's identity is verified, the IdP sends authentication details back to ZPA, which then

evaluates access policies and grants application-specific access if the user is authorized. This integration enables Single Sign-On (SSO), improves security, and ensures that access decisions follow the Principle of Least Privilege, allowing users to access only the applications they are permitted to use.

Device Posture Checking:

Beyond user identity, ZPA can enforce policies based on the security posture of the connecting device. Through integration with endpoint detection and response (EDR) and mobile device management (MDM) solutions, ZPA can assess factors such as:

• Antivirus software status and definition updates

• Disk encryption status (e.g., BitLocker, FileVault)

• Operating system patch level

• Presence of jailbreak or root compromise on mobile devices

• Real-time risk score from the EDR tool If a device fails to meet the defined posture requirements (e.g., antivirus is disabled), ZPA can block access, grant limited access, or trigger a remediation workflow.

Micro-tunneling and Application:

Visibility ZPA establishes a secure TLS/DTLS tunnel between the ZPA Client Connector and the ZPA service edge, and another tunnel between the service edge and the App Connector. Crucially, this creates a direct "app-to-user" micro-tunnel. The user's device is never placed on the corporate network; instead, traffic is proxied at Layer 7 (application layer). From the user's perspective, they can only resolve and connect to the specific DNS names or IP addresses of the applications they are authorized to access. All other internal resources remain completely invisible, preventing port scanning, vulnerability reconnaissance, and lateral movement

Threat Intelligence Integration:

To enhance security monitoring, ZPA can be integrated with threat intelligence platforms. Logs generated by ZPA—including connection attempts, policy violations, and user activity—can be forwarded to a SIEM (Security Information and Event Management) system. Within the SIEM, these logs can be correlated with threat intelligence feeds (such as those from MISP) to identify suspicious behavior. For example, if a user's credentials are used to

access an application from an IP address associated with known malicious activity, the SIEM can trigger an alert, and integration with ZPA can automatically revoke that user's session.

Incident Response in a ZPA Environment :

ZPA significantly streamlines the incident response process. When a potential threat is detected, security teams can leverage ZPA's capabilities to:

1. Isolation: Immediately revoke access for a compromised user account or device through the ZPA console, cutting off their connectivity to all internal applications.

2. Forensics: Access detailed logs within ZPA showing exactly which applications were accessed, by whom, from which location, and for how long.

3. Containment: Because users have no network-level access, a compromised endpoint cannot be used to scan or attack other internal systems, containing the blast radius.

4. Granular Blocking: Temporarily block access to specific high-risk applications while allowing access to others, ensuring business continuity during an investigation.

Understanding ZPA: Key Takeaways :

Zscaler Private Access represents a fundamental shift in how remote access is architected and secured. Here are the key aspects to understand about the solution:

1. It is cloud-native: ZPA is delivered entirely from the Zscaler cloud, eliminating the need for hardware appliances and complex VPN head-end management.

2. It is identity-centric: Policies are built around users and groups, not IP addresses, making access control more intuitive and aligned with organizational structure.

3. It ensures network invisibility: By never placing users on the network, ZPA renders internal infrastructure invisible to the internet, preventing reconnaissance and DDoS attacks

4. It is scalable: The cloud architecture allows ZPA to scale instantly to accommodate thousands of concurrent users without performance degradation.

5. It supports hybrid environments: ZPA works seamlessly for applications hosted in on-premises data centers, private clouds, and public cloud environments.

6. It improves user experience: Users get direct, optimized connections to applications without back hauling traffic through a centralized VPN concentrator, reducing latency

Conclusion:

Stage 1:

In conclusion, web application testing is a crucial process that ensures the security, functionality, and reliability of web-based software. It involves a comprehensive evaluation of various aspects, including user interface, functionality, performance, and security to identify and rectify issues before they impact end-users. This process not only enhances the quality of web applications but also bolsters their resilience against potential threats and vulnerabilities. In an age where online services and applications are integral to our daily lives, effective web application testing is essential to deliver a seamless and secure user experience.

Stage 2:

The Nessus report for the specific website has highlighted key security insights. It identified vulnerabilities, categorized by severity, with a focus on critical and high-risk issues that need immediate attention. Recommendations for addressing these vulnerabilities include patching, reconfiguration, and other security measures, with a priority on actions that can have the most significant impact. Compliance with industry standards and best practices is considered, ensuring alignment with recognized security benchmarks like OWASP guidelines. The report underscores the need for continuous monitoring, regular updates, and ongoing security efforts to maintain a strong security posture. In summary, the Nessus report offers a clear view of the website's security state, provides guidance on mitigating vulnerabilities, and stresses the importance of sustained vigilance against evolving threats.

Stage 3:

The implementation of Zscaler Private Access marks a pivotal shift from a vulnerable, networkcentric security model to a resilient, identity-centric Zero Trust architecture. By enforcing leastprivilege access and rendering private applications invisible to the internet, this project effectively neutralizes the

threats of lateral movement and network-based attacks. The solution not only fortifies the organization's security posture against modern cyber threats but also delivers a seamless and high-performance experience for a distributed workforce. Furthermore, the decoupling of access from the network simplifies IT operations, reduces dependency on legacy VPN infrastructure, and provides granular visibility into user-application interactions. Ultimately, this initiative establishes a future-ready foundation for secure digita