

DAILY DRILLING REPORT (SYNTHETIC)

OIL-CHR-010 - Charali-010

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Charali / Barail
Report Timestamp	2004-09-04 18:00:00
Current Depth	3056.0 m
Mud System	PHPA Water-Based Mud
Well Risk	High (58.5/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
08-31 04:36	2950	3416	270	116	11.86	777/785	8.4	Normal
08-31 16:45	2962	3354	288	101	11.66	729/722	8.3	Normal
09-01 04:54	2973	3426	272	113	11.78	812/770	11.3	Normal
09-01 17:04	2985	3420	333	95	11.80	758/744	12.4	Normal
09-02 05:13	2997	3530	267	106	11.68	821/798	9.3	Normal
09-02 17:22	3009	3489	254	118	11.72	788/785	10.0	Normal
09-03 05:32	3021	3425	303	109	11.67	802/820	12.4	Normal
09-03 17:41	3032	3552	296	111	11.76	760/746	12.0	Normal
09-04 05:50	3044	3436	294	110	11.89	762/782	11.0	Normal
09-04 18:00	3056	3466	271	124	11.81	833/805	9.6	Normal

Operational Events / Lessons

Torque Spike (Medium) at 2568 m: Torque Spike at 2568 m in Barail. High torque developed while WOB remained elevated. Adjusted rotary parameters and observed response. Outcome: Spike cleared with no equipment damage. Torque 392 kNm, drag 17.0 t, ROP 13.2 m/h. Recommended action: Reduce WOB/RPM proactively near correlated torque-spike depth

Stuck Pipe (Medium) at 2616 m: Stuck Pipe at 2616 m in Barail. Torque and drag increased while ROP declined. Back-reamed cautiously while monitoring torque. Outcome: Pipe movement restored after circulation and working. Torque 361 kNm, drag 33.6 t, ROP 7.1 m/h. Recommended action: Plan preventive wiper trip near analogous interval

Mud Loss (Medium) at 2772 m: Mud Loss at 2772 m in Barail. Active pit volume declined during stable pump rate. Stopped drilling and performed flow check. Outcome: Loss rate reduced to acceptable level. Flow balance: 815/676 LPM (in/out); pit change -4.2 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

Mud Loss (Medium) at 2926 m: Mud Loss at 2926 m in Barail. Flow-out dropped below flow-in with pit loss. Reduced pump rate and monitored active pits. Outcome: Loss rate reduced to acceptable level. Flow balance: 845/713 LPM (in/out); pit change -6.5 bbl. Recommended action: Monitor pit volume continuously within +/-50 m of this depth

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.