

DAILY DRILLING REPORT (SYNTHETIC)

OIL-CHR-012 - Charali-012

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Charali / Barail
Report Timestamp	2024-10-24 18:00:00
Current Depth	3108.0 m
Mud System	Low-Solids WBM
Well Risk	Moderate (53.2/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
10-19 15:23	2987	3125	283	98	11.60	753/777	11.2	Precursor
10-20 05:00	3000	3396	298	103	11.63	753/857	7.0	Event
10-20 18:38	3014	3508	318	106	11.80	746/779	11.4	Recovery
10-21 08:15	3027	3532	292	108	11.87	806/818	9.9	Normal
10-21 21:53	3041	3479	281	115	11.88	812/830	13.1	Normal
10-22 11:30	3054	3591	279	106	11.56	742/746	10.7	Normal
10-23 01:07	3068	3428	290	123	11.84	760/751	12.8	Normal
10-23 14:45	3081	3491	337	118	11.88	761/770	10.8	Normal
10-24 04:22	3094	3491	280	105	11.89	758/757	9.7	Normal
10-24 18:00	3108	3679	299	114	11.85	797/812	9.0	Normal

Operational Events / Lessons

Kick (Medium) at 2878 m: Kick at 2878 m in Barail. Flow-out exceeded flow-in and gas units increased. Increased monitoring frequency and prepared kill-weight mud. Outcome: Well stabilized after controlled circulation. Gas 123 units; pit change +12.9 bbl; mud weight 11.72 ppg. Recommended action: Raise kick advisory when flow-out exceeds flow-in with rising gas

NPT (Medium) at 2892 m: NPT at 2892 m in Barail. Drilling parameters were stable but operations were suspended. Performed checks before restarting operations. Outcome: Operational hold cleared after checks. Recommended action: Flag repeated downtime patterns before mobilization

Torque Spike (Medium) at 2973 m: Torque Spike at 2973 m in Barail. Rotary speed fluctuated during constant pump rate. Adjusted rotary parameters and observed response. Outcome: Spike cleared with no equipment damage. Torque 441 kNm, drag 16.1 t, ROP 13.1 m/h. Recommended action: Set warning on rapid torque rise with RPM instability

Kick (High) at 3000 m: Kick at 3000 m in Barail. Drilling break followed by positive flow check. Shut in well and recorded pressures. Outcome: Operations resumed after well-control verification. Gas 245 units; pit change +6.3 bbl; mud weight 11.63 ppg. Recommended action: Raise kick advisory when flow-out exceeds flow-in with rising gas

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.