

DAILY DRILLING REPORT (SYNTHETIC)

OIL-DGB-006 - Digboi-006

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Digboi / Tipam
Report Timestamp	2002-12-06 18:00:00
Current Depth	2248.0 m
Mud System	Low-Solids WBM
Well Risk	Moderate (47.1/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
12-01 11:56	2188	2882	221	106	11.12	760/769	14.2	Normal
12-02 01:56	2195	2832	234	116	10.73	740/757	10.7	Normal
12-02 15:57	2201	2851	278	110	10.94	718/719	8.2	Normal
12-03 05:57	2208	2909	253	109	11.02	783/778	12.6	Normal
12-03 19:57	2215	2839	264	111	11.17	796/775	11.8	Normal
12-04 09:58	2221	2871	246	96	11.12	793/788	11.7	Normal
12-04 23:58	2228	2755	243	112	11.20	644/653	9.6	Normal
12-05 13:59	2235	2858	280	104	11.00	823/802	12.6	Normal
12-06 03:59	2241	2980	234	109	11.15	724/713	9.3	Normal
12-06 18:00	2248	2958	241	113	11.06	750/773	13.5	Normal

Operational Events / Lessons

Stuck Pipe (High) at 1790 m: Stuck Pipe at 1790 m in Tipam. Hookload became erratic during pipe movement. Reduced WOB and increased hole-cleaning circulation. Outcome: Restriction cleared without fishing operation. Torque 327 kNm, drag 30.0 t, ROP 5.8 m/h. Recommended action: Increase hole-cleaning surveillance before this depth

Mud Loss (Low) at 1797 m: Mud Loss at 1797 m in Tipam. Intermittent circulation losses developed while drilling ahead. Reduced pump rate and monitored active pits. Outcome: Circulation stabilized after treatment. Flow balance: 714/627 LPM (in/out); pit change -2.3 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Mud Loss (High) at 1824 m: Mud Loss at 1824 m in Tipam. Intermittent circulation losses developed while drilling ahead. Reduced ROP and conditioned the hole. Outcome: Loss rate reduced to acceptable level. Flow balance: 844/645 LPM (in/out); pit change -12.9 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Mud Loss (Medium) at 1885 m: Mud Loss at 1885 m in Tipam. Intermittent circulation losses developed while drilling ahead. Reduced pump rate and monitored active pits. Outcome: Loss rate reduced to acceptable level. Flow balance: 765/679 LPM (in/out); pit change -10.6 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.