

DAILY DRILLING REPORT (SYNTHETIC)

OIL-DGB-013 - Digboi-013

NWIS prototype document - not an Oil India Limited operational record

Field / Formation	Digboi / Barail
Report Timestamp	2024-07-29 18:00:00
Current Depth	2722.0 m
Mud System	PHPA Water-Based Mud
Well Risk	Moderate (53.9/100)
Latest Alert	Normal

Recent Drilling Parameters

Timestamp	Depth	SPP	Torque	RPM	MW	Flow In/Out	ROP	State
07-24 15:30	2575	3130	286	120	11.35	726/674	9.1	Precursor
07-25 05:06	2591	3387	270	114	11.35	783/697	7.2	Event
07-25 18:43	2608	3422	285	112	11.53	796/778	7.3	Recovery
07-26 08:20	2624	3146	302	112	11.35	804/791	11.0	Normal
07-26 21:56	2640	3116	223	112	11.38	857/847	12.0	Normal
07-27 11:33	2657	3265	271	102	11.58	781/805	11.2	Normal
07-28 01:10	2673	3240	252	94	11.40	816/814	5.7	Normal
07-28 14:46	2689	3122	263	105	11.61	805/787	10.8	Normal
07-29 04:23	2706	3346	266	117	11.48	727/747	10.0	Normal
07-29 18:00	2722	3416	273	118	11.33	775/757	11.9	Normal

Operational Events / Lessons

Mud Loss (Medium) at 1776 m: Mud Loss at 1776 m in Barail. Partial returns observed at shale shaker. Reduced ROP and conditioned the hole. Outcome: Full returns restored and drilling resumed. Flow balance: 752/708 LPM (in/out); pit change -3.8 bbl. Recommended action: Reduce pump rate/ECD before entering analogous interval

Cementing Issue (Medium) at 1911 m: Cementing Issue at 1911 m in Barail. Displacement pressure became unstable. Recorded pressure-volume response for remedial decision. Outcome: Returns improved after rate reduction. Cement returns 56% with density 16.52 ppg. Recommended action: Alert when cement-return percentage drops below expected envelope

Cementing Issue (High) at 2328 m: Cementing Issue at 2328 m in Barail. Displacement pressure became unstable. Recorded pressure-volume response for remedial decision. Outcome: Returns improved after rate reduction. Cement returns 21% with density 13.88 ppg. Recommended action: Use pressure-volume reconciliation during displacement

Mud Loss (High) at 2591 m: Mud Loss at 2591 m in Barail. Partial returns observed at shale shaker. Reduced pump rate and monitored active pits. Outcome: Loss rate reduced to acceptable level. Flow balance: 783/697 LPM (in/out); pit change -12.4 bbl. Recommended action: Pre-stage LCM and set early-warning threshold on flow-out deficit

This DDR is generated from synthetic telemetry for OCR/NLP/RAG and risk-engine prototyping.